Index

A

active solar energy usage 107. see also photovoltaics, solar thermal advanced envelope 65 aesthetics – sustainable 142 air – heat recovery, mechanical 73 – natural flows 27 - temperature, indoor 171 air source heat pumps (ASHP) 75 Alberta, Canada – Riverdale 42, 183 125 amorphous silicon PV architects - priorities 3 - role in building design 114 architectural design 104 135 architectural structures (typologies) ASHRAE GreenGuide 27 asymmetrical weighting factors 11 automation 7, 209 autonomous architecture 1 A/V ratio 138

В

balance boundaries 10, 111 Barcelona, Spain Case Study building 42 basic satisfaction survey 173 Beijing, China – SIEEB 120 benchmark – user surveys 177 Bennau, Switzerland – Kraftwerk B 42 bioclimatic design 1 103 biomass fired boilers biomass powered CHP 103 black globe temperature 181 brief 113 building-applied PV (BAPV) 100 building-integrated PV (BIPV) 100 - PVT systems 126 - T 30, 33, 89, 101 building management system (BMS) 186 buildings - communication with occupants 213 - designed and measured performance 157 – design hierarchy 35 - dysfunctions 157, 166 – embodied energy 10 - energy balance 6, 104 - energy monitoring protocols 165 - footprint 109 - hypothetical boundary 132 – load curve 168 - multi-occupant 208 - non-residential (see non-residential buildings) – orientation 201, 207 – overall performance 156 - owner/tenant feedback interviews 198 - post-war period 133 - quality levels 114 18 requirements - energy efficiency measures 26 – passive measures 22 - renewable energy measures 32 residential (see residential buildings) - shape 104 – standards 105 - types 103 – classification 16 – use studies 173.177 - warranty 206

С

CAD tools 117 Canada – case study buildings 42, 126 – discomfort 211 – monitoring 183 CAPA 121 Cargese, France - IESC 42 monitoring 183 case studies - Net ZEBs 5, 15 - selection criteria 41 ceiling fans 81, 203 chilled beams 77, 203 cities – building design 129 - dense 120 – future concepts 143 - Smart City 147 CityNext programme 146 climate classification - Köppen-Geiger 15 - tool, Ecotect 16 climate types 103 clothing garment checklists 180 clusters Net ZEBs 136, 145 combined heat and power (CHP) 8, 33, 103 comfort - architectural design 105 - Givoni zones 179 - monitoring 7, 154, 174 - occupant considerations 208 - required/expected conditions 114 - station 176 – totem 180 commissioning – BMS 186 - monitoring systems 163 communication with building occupants 213 compact structure 121 Comprehensive Assessment System for Built Environment Efficiency (CASBEE) 132 cooling - energy efficiency 203 – evaporative 81 - feedback interviews 199 – ground 64 – Net ZEB measures 55, 65 - passive measures 21

radiant 77
cost constraints 114
cost optimization 154

D

daily load 170 data acquisition systems 162 database – Case Study buildings 41 - standardized format 2 data loss 186 daylighting - diffusing roof 207 200 – feedback interviews deciduous vegetation 201 demand-reduction technology 10 dense cities 120 – solar potential 142 design – architectural 104 - bioclimatic 1 - definition 103 - domain 112 hierarchy 197 – IDP 113 - low risk concepts 4 - occupant conscious 210 - occupant considerations 208 - organizational decision making 115 - renewable energy systems 108 designed and measured data 157 designers 3, 5 diffusing roof daylighting 207 Dijon, France - Elithis Tower monitoring 183, 188, 190 direct current (DC) electricity 121 Directive on Energy Performance of Buildings (EPBD) 2 discomfort 211 – thermal 178 domestic hot water (DHW) 25, 29 – efficiency 85 double skin façade 200 dysfunctions 157, 166

Ε

earth tube heat exchanger 64 Ecotect climate classification tool 16 ÉcoTerra, Eastman, Canada 42, 126 - discomfort 211 efficiency path 10, 13 electricity - annual load/generation balance 168 – DC 121 end-use 166 – Net ZEB measures 89 - renewable generation 205 Elithis Tower, Dijon, France - monitoring 183, 188, 190 energy - building embodied 10 – local grids 41 - monitoring 154 - protocols 165 - natural flows 27 - weighting system 11 energy balance - buildings 6, 104 - designed and measured 157 energy efficiency – feedback interviews 202 – Net ZEB measures 18, 71 - strategies 25 EnergyFlex, Taastrup, Denmark 42, 124 energy flows measured 161 - reusing 103 Energy Independence and Security Act of 2007 (EISA 2007) 2 energy independence ratio (EIR) 158 Energy Performance of Buildings Directive (EPBD) 10 energy supply options 108 ENERPOS. Reunion Island – monitoring 166, 183 - occupant behavior 212 envelope – advanced 65 - feedback interviews 201, 207 - integrated supply options 6, 119 environmental image, marketability 198

European Model Home 2020 140 evaluation – POE (*see* post occupancy evaluation) evaporative cooling 81 exergy 26

F

facades - double skin 200 – green 208 196 feedback interviews films – solar 200 fixed sensors 176 fixed solar shading 202 France - Case Study buildings – monitoring 183, 188, 190 Freiburg, Germany - Case Study buildings 42, 136 – Kleehaeuser 42 - Plus Energy Settlement 136 – Solar Factory 139

G

gable roofs 140 generalized solution set 53 geothermal heating 32, 103 Givoni comfort zones 179 glare control 62 glazing systems - advanced 23 Gleisdorf, Austria - Sundays 139 green façades 208greenhouses 130 green image, marketability 198 ground cooling, natural 64 ground source heat pumps (GSHP) 75, 103

Н

Hamburg, Germany – LichtAktivHaus 140 heat – exchanger, earth tube 64 – geothermal 32 - recovery 86 - reflection 20 - solar 19, 31 - 31 heating – Net ZEB measures 54, 65 - passive measures 21 - radiant 72 heat pumps 75 - architectural design 106 – esthetic consequences 118 - feedback interviews 207 Hol Church, Norway 124 horizontal wind turbine 103 hot water heat recovery 86 household appliances - efficiency 83 human behavior – energy monitoring 190 humidity - ENERPOS measurements 176 - relative 171 HVAC 25 – IDP 117 hypothetical boundary 132

I

IEA SHC Task 41 118 IEA SHC Task 51 130 IEA SHC Task 40/EBC Annex 52 2, 5, 6, 39, 121 IESC, Cargese, France 42 - monitoring 183 ighting - efficiency 204 import/export balance 9 indoor air temperature 171 indoor environmental quality (IEQ) 25, 105. 153. 154 - monitoring protocol 170 inertia of occupants 210 information panels 215 installations zoning 172 integrated design process (IDP) 113 - feedback interviews 197

integrated project delivery 116 internet of things 148 investors 5 Italy – case study buildings 42

Κ

Kleehaeuser 41, 42 Köppen-Geiger climate classification 15 Kraftwerk B 42 Kreuzlingen, Switzerland – Educational Therapy Centre 136 Kyoto High School, Poitiers, France – monitoring 183, 189

L

Leafhouse, Rosora, Italy 42 LichtAktivHaus, Hamburg, Germany 140 life cycle balance overall 12 light - natural 21 lighting - efficiency 81 feedback interviews 200 - Net ZEB measures 69, 81 – passive measures 21 Lima - Barcelona, Spain 42 Lisbon, Portugal – Solar XXI 126 load/generation balance 9 load management 82 local energy grids 41 low risk design concepts 4 LycÉe Saint-Benoit IV, Reunion Island 214

М

Mähdle, Austria – Community School refurbishment 135 maintenance 105, 157 – BMS 186 – regular 164 marketability – green/environmental image 198 Masdar (United Arab Emirates) 8 measure categories 18 measurement and verification (M160 measurements - objective 180 - subjective 179 measures 51. see also Net ZEB measures - summary matrix 34 mechanical air heat recovery 73 Melbourne, Australia - Pixel 128 Meridian, Wellingthon, New Zealand 127 Minergie Standard 136 monitoring - building energy and comfort 154 – ENERPOS 7. 174 software 187 - standard protocol 158 monthly net balance 9 multi-occupant buildings 208

Ν

natural ground cooling 64 natural light 21 59 natural ventilation Near Zero Architecturestandard 105 Neighbor Act (Norway) 130 net floor area 12 Net ZEB line 167 Net ZEBs - basic forms 134, 137 5.15 - case studies classification 7 - clusters 136, 145 2, 7, 14 definition – IDB 115 measures 51 104 - objective occupant considerations 208 - performance assessment 15 physical boundary 8 – solution sets 34 Net ZE communities 6, 112, 143 non-residential buildings 45 - feedback interviews 196 - primary energy balance 155

– solution sets 103NREL RSF 212

0

objective measurements 180 occupant conscious design 210 occupant considerations 208 office equipment - energy efficiency 84, 204 off-site renewable energy systems 110 on-site renewable energy systems 109 optimization - costs 154 organizational design decision making 115 orientation buildings 201, 207 outbuildings 141 overall building performance 156 overall life cycle balance 12 overheating 200 owner – feedback interviews 198

Ρ

parking lots – PV use 110 passive approach strategies 19 passive design measures - feedback interviews 199 passive energy design 3 Passive House standard 106 passive Net ZEB measures 18, 54 performance assessment - Net ZEBs 15 photovoltaics (PV) 89 - architectural design 106 - building design 118, 121 – solar thermal 107 systems 29 physical boundary – ZEB 8 Pixel, Melbourne, Australia – building design 128 planned sprawl 143 plug load – energy monitoring 190

- Net ZEB measures 82 Plus Energy Settlement, Freiburg, Germany 42, 136 Poitiers, France - Kyoto High School - monitoring 183, 189 polygonal building structures 141 post occupancy evaluation 105 post-occupancy evaluation (POE) 105, 153, 154, 158 – IEQ 173 post-occupancy visits 213 post-war period buildings 133 primary energy balance 155 programmed solution sets 115 psychometric chart 178 PV-only all-electric approach 120 PVT systems 125

R

radiant cooling 77 radiant heating 72 Rainbow Headquarters, Loreto, Italy 122 rebound effect 210 reflection - heat 20 reiteration feedback interviews 203 relative humidity 171 renewable energy systems 86 – building design 118 - categorization 111 - design 108 - feedback interviews 205 - Net ZEB measures 18 - off-site 110 – on-site 109 - strategies 29 renewable supply options 9 residential buildings 45 - primary energy balance 155 – solution sets 103 retrofitted Net ZEB buildings 131, 135 Reunion Island - case study buildings - monitoring 166, 183

occupant behavior 212
LycÉe Saint-Benoit IV 214
reusing energy flows 103
Riehen, Switzerland 42
right to sunlight 130
Riverdale, Alberta, Canada 42
monitoring 183
roof area maximazation 106
roof daylighting, diffusing 207
Rosora, Italy
Leafhouse 42

S

Saint-Pierre, Reunion Island - Case Study buildings - monitoring 166, 183, 188, 190 - occupant behavior 212 Schlierberg, Freiburg, Germany 42, 136 self-consumption 13 self-sufficiency 123 sensors 162 - fixed 176 SIEEB, Beijing, China 120 silicon-based PV modules 100 single family home – solar potential 142 site context 198 site vegetation 56 skylights 69, 200 small and medium sized enterprises (SME) 115 Smart City 147 smart grids 6, 145 Solar Factory, Freiburg, Germany 139 200 solar films solar heat 19, 31 - gain 54 solar hot water (SHW) 206 solar ovens 130 solar shield 200solar thermal – building design 118, 123 - collectors 103 - vertical absorber 124 solar tubes 70 Solar XXI, Lisbon, Portugal

- PVT systems 126 solution sets 40 – generalized 53 – Net ZEBs 34 - measures 103 - non-residential buildings 103 – programmed 115 - residential buildings 103 space applications 123 standardized database format 2 standard monitoring protocol 158 state-of-the-art technology 206 storage subsystem - 19 subjective measurements 179 Sundays, Gleisdorf, Austria 139 sunshading 25, 62 - feedback interviews 200, 201, 207 supply options - envelope integrated 6, 119 – renewable - 9 surface requirements 107 surface to volume ratio 121 survey population 181 surveys 181. see also user surveys sustainability aesthetics 142 system design monitoring 162

Т

Taastrup, Denmark EnergyFlex 42, 124 temperature - black globe 181 - ENERPOS measurements 176 – indoor air 171 temporal match 14 tenants, feedback interviews 198 thermal discomfort percentage 178 thermal mass 69 thermal zoning 68 Tricesimo, Italy 42 triple flow system 203 Trombe walls 23 typological repertoire 135

U

underfloor air distribution (UFAD) 74 urbanization 6, 143 user awareness 156, 210, 213 user controls 209 user education 191, 208 user surveys 165 – benchmark 177 – comfort 175 – IEQ 173 U-value, windows 66

۷

variable refrigerant volume (VRV) group 166 vegetation 56 - deciduous 201 - passive heating/cooling 25 ventilation 27 - energy efficiency 203 - feedback interviews 199 natural 59 74 – UFAD vertical axis wind turbines 103. 129 vertical ST absorber 124 volatile organic compounds (VOC) 174

W

walls, Trombe 23 warranty 206 weather station 175 weighting system – energy 11 Wellingthon, New Zealand - Meridian 127 wind generation systems - 30 windows - control 24 – distribution 138 – U-value 66 wind turbines 103 – building design 128 - vertical axis 103, 129

Ζ

Zero energy house, Tricesimo, Italy 42 zoning 28 – installations 172 – thermal 68