

Index

a

AA-/AB-type structure 238
 abrasion 147
 ABS/graphene oxide nanocomposites 53
 ABS/Mg(OH)₂ nanocomposites 59
 acoustic parameters 151
 acrylate-based polymer latex 314
 acrylic resin 128
Actinobacteria 334
 activation energy
 – glass transition 180
 – PEO 299
 – relaxation 169–170, 177
 adhesion 147
 adhesive contact 198–200
 adhesive energy map 203
 aerobic environments 325
 AFM (atomic force microscopy) 185–228
 – AM 218
 – elasticity measurements 193–201
 – nanopalpatation 197–198
 – tapping mode 188–191
 agents, nanostructured 126
 aggregated nanoclay platelets 34
 aliphatic polyesters 259–260
 alkyl chain 240, 244
 alloys, PAB 83
 alumina, nano- 39, 57–58
n-alumina 41
 alumina trihydrate (ATH) 62
 aluminosilicate layers 9
 amines 131–133
 aminopropylisooctil-POSS 130
 ammonium-modified fillers 6–7
 ammonium-modified montmorillonite 17
 amorphous polymers 105
 amplitude, cantilever oscillation 192, 220
 amplitude–modulation AFM (AM-AFM)
 218

anaerobic environments 325
 analytical ultracentrifugation (AUC)
 304–306
 “anchoring” effect 290
 angular frequency, resonant 189
 anisotropic interactions 284
 antitumoral drugs 133–135
 approximation, parabolic 197
 Arrhenius plots 177, 299
Ascomycota 335
 ashes, volcanic 75
 aspect ratio 253
 ATH (alumina trihydrate) 62
 atmosphere, effect on test samples 22
 atomic distance 186
 atomic force microscopy (AFM) 185–228
 – AM 218
 – elasticity measurements 193–201
 – nanopalpatation 197–198
 – tapping mode 188–191
 AUC (analytical ultracentrifugation)
 304–306
 Australian test standard AS ISO 14855
 326–327

b

ball bearing effect 161–164
 BAP (biodegradable aliphatic polyesters)
 259–260
 barrier, clay 67
 basal spacing 22
 BaTiO₃ 175–177
 bearings, dry-running 153
 bentonites 336
 benzoyl peroxide 118
 benzylamine 137
 Berthelot’s rule 102
 bimorph 187–189
 Bingham behavior 255

- bioconjugated systems 133–135
 - biodegradability
 - PNCs 323–346
 - standards 331
 - biodegradable aliphatic polyesters (BAP) 259
 - biodegradable nanocomposites 331–336
 - bioreactors 325
 - bisphenol A glycerolate dimethacrylate (BisGMA) 116, 121–124
 - blending, melt 272
 - blends
 - compatibilized 209
 - PAB 83
 - block copolymers (BCPs), nanomechanical properties 213–225
 - block-on-ring test 151, 157
 - bonding, hindered hydrogen 296–298
 - bonds
 - N–O 234
 - Si–C/Si–O 127
 - breakage, fibers 160
 - 1-bromodocosane 28
 - Brownian motion 275
 - Brownian rotational diffusion 234
- c**
- C18–4C18-modified filler 27
 - cables, coaxial 62
 - CaCO₃ pigment 314
 - cage structure, POSS 42
 - calorimeter
 - combustion 45
 - cone 44–45
 - calorimetric behavior, PP nanocomposites 30–31
 - calorimetry, differential scanning, *see* differential scanning calorimetry
 - cantilever 187–188
 - oscillation 190
 - carbon, diamond-like 194
 - carbon black 206
 - carbon dioxide (CO₂) demand 325
 - carbon fibers, short 156–161
 - carbon nanofibers (CNFs) 36
 - flammability 54
 - high-/low-density 271–274
 - carbon nanotubes (CNTs) 36
 - CNT-reinforced elastomer nanocomposites 201–207
 - flammability 54–55
 - functionalization 131–135
 - modification with ODA 132
 - PNC synthesis 129
 - polymer– 63–66
 - Raman spectroscopy 135–137
 - rheological characterization 266–267
 - XPS 130–135
 - carbonaceous char residue 67
 - carbonyl groups 243
 - carboxylated SWNCT 137
 - carboxylic groups 131
 - Carreau equation 255
 - casting, solvent 272
 - cation-exchange capacity (CEC) 76, 237
 - C30B 261–262
 - CED (cohesive energy density) 93
 - cell count, direct 328
 - cell-hole theory, Simha–Somcynsky 90–97
 - cellular structure 207–208
 - char residue 67
 - char yield 49
 - characterization techniques
 - AFM 185–228
 - biodegradability 323–346
 - DRS 167–184
 - DSC 25–26
 - enzymatic 329
 - examples 5–11
 - flame-retardancy 33–74
 - microbiological 328–329
 - molecular 329
 - multidirectional 307
 - organoclays 237–242
 - PVT 75–114
 - rheological properties 251–281
 - sedimentation analysis 303–321
 - surface reactions 19
 - TGA 5, 13–25, 43
 - thermal 13–32, 42–45
 - tribological 143–166
 - chemical composition, clays 78–79
 - chemical reactions
 - reactive polymer–polymer interface 207–213
 - reactivity 126
 - surface 19
 - tribochemical reactions 147
 - chemical structure, *see* structure
 - chromatography 325
 - clays 19–28
 - chemical composition 78–79
 - clay barrier 67
 - esterified 20
 - exfoliated PMA/clay nanocomposites 286–293
 - HCP model 102
 - intercalant/compatibilizer effects 82–83

- intercalated PEO/clay nanocomposites 293
 - kaolinite aluminosilicate 39
 - montmorillonite, *see* montmorillonite
 - organo- 62–63, 237–242
 - platelets 22, 77–78
 - polymer–clay nanocomposites 46–52, 229–249
 - polyol/clay mixtures 260–262
 - PVDF/clay-based nanocomposites 171–175
 - (semi)synthetic 76–77
 - sodium salt 77
 - Somasif ME-100 77, 236–247, 287–295
 - clear-zone 328–329
 - Cloisite 30B TPUNs 51–52
 - CNFs (carbon nanofibers) 36
 - flammability 54
 - high-/low-density 271–274
 - CNTs (carbon nanotubes) 36–39
 - CNT-reinforced elastomer nanocomposites 201–207
 - flammability 54–55
 - functionalization 131–135
 - modification with ODA 132
 - PNC synthesis 129
 - polymer- 63–66
 - Raman spectroscopy 135–137
 - rheological characterization 266–267
 - XPS 130–135
 - CO₂ (carbon dioxide) demand 325
 - coaxial cables 62
 - coefficient of friction 158, 163
 - cohesive energy density (CED) 93
 - Cole–Cole plot 174
 - collective stress 145, 149
 - colloids
 - hybrid dispersions 305
 - organic–inorganic hybrid 303
 - PNC 303–321
 - combination of fillers 156–161
 - combustion calorimeter 45
 - compatibilized blends 209
 - compatibilizer 25, 82–83
 - complex permittivity 168
 - composites
 - multiscale 153
 - nano-, *see* nanocomposites
 - composition dependence, dielectric permittivity 171
 - compost media 341
 - compressibility coefficient 83–89
 - concentric tube structure 38
 - conductivity, thermal 148
 - cone calorimeter 44–45
 - configurational Helmholtz free energy 92
 - contact, adhesive 198–200
 - contact mechanics 194
 - contact solution, Hertzian 197
 - contact temperature 163
 - continuous wave (CW) technique 231
 - cooling, isobaric/isothermal 81–82
 - cooperative relaxation 168
 - copolymerization 123
 - copolymers, block 213–225
 - corrected mass loss 14
 - corresponding states principle (CSP) 92
 - Coulomb equation of sliding friction 146
 - counterbody 145
 - coupling, dipole–dipole 230
 - crack-free network 68
 - cracking 147
 - cross-over transition 80
 - crystalline relaxation 168–169, 177
 - crystalline solids 99
 - crystallization, inhibited 295
 - crystallization temperature 29–30
 - cumulative sedimentation coefficient 308–310
 - curing conditions 29–32
- d**
- data interpolation 83–84
 - Debye equation 169
 - DEER (double electron–electron resonance) 232, 235
 - degradation
 - bio-, *see* biodegradation
 - hydrolytic 335
 - thermal 17
 - dendritic polymers 133–135
 - density gradients, static 306
 - depth wear rate 159
 - derivatives 83–89
 - partial 92
 - design, PNCs 153
 - Desmopan–clay TPUNs 51–52
 - deuterium solid-echo NMR 240
 - diamond-like carbon (DLC) 194
 - dielectric permittivity 171–172
 - composition dependence 171
 - Vo–Shi model 172–173
 - dielectric relaxation spectroscopy (DRS) 167–184
 - frequency dependence 173–176
 - low-temperature spectra 178–180
 - normalized spectra 180

- differential scanning calorimetry (DSC) 6
 - fillers 25–26
 - nanocomposites 26–32
 - PEO 297
 - differential sedimentation coefficient 308–310
 - diffusion, Brownian rotational 234
 - dimethylditallow-montmorillonite 258
 - dioctahedral smectites 1
 - dipole–dipole coupling 230
 - direct cell count 328
 - disappearance of glass transition 295
 - disorder band 136
 - dispersion
 - force 185
 - hybrid colloid 305
 - nanoalumina 41
 - nanofillers 251
 - SWNT 55
 - dissipation, phase and energy 191–193
 - distal distance 241–242
 - docosyltriethylammonium bromide 28
 - dotriacontanoic acid 20
 - double electron–electron resonance (DEER) 232, 235
 - double-wall carbon nanotubes (DWNTs) 36–39
 - drugs, antitumoral 133–135
 - dry-running slide bearings 153
 - dynamic TGA, fillers 18–19
- e**
- Einstein-theory of intrinsic viscosity 253
 - elastic coefficient 200
 - elastic contact, Sneddon's 194–197
 - elastic (storage) modulus 256
 - SWNT/PMMA nanocomposites 270
 - elasticity measurements 193–201
 - elastomer–clay nanocomposites 50–52
 - polyurethane 50–52
 - elastomer nanocomposites, CNT-reinforced 201–207
 - electric modulus 176–177
 - electron nuclear double resonance (ENDOR) 232, 235
 - electron paramagnetic resonance (EPR) 229–249
 - slow-motion 237
 - spin label 232–236, 283–303
 - electron spin echo envelope modulation (ESEEM) 232, 235
 - electron spin resonance (ESR) 284
 - elongational viscosity 277–278
 - empirical Tait equation 83
 - encapsulated pigment particles 317
 - energy
 - adhesive 203
 - CED 93
 - dissipation 191–193, 219
 - Helmholtz free 92
 - relaxation activation 169–170, 177, 180
 - entanglement, MWNTs 39
 - environment
 - (an)aerobic 325
 - measurement 19–22
 - enzymatic characterization techniques 329
 - EPDM-Mg(OH)₂ nanocomposites 59
 - epoxy-based nanocomposites 9, 158
 - epoxy–clay nanocomposites 47–50
 - epoxy–graphene nanocomposites 53
 - epoxy-Mg(OH)₂ nanocomposites 60
 - epoxy resins 48
 - EPR (electron paramagnetic resonance) 229–249
 - slow-motion 237
 - spin label 232–236, 283–303
 - equation of state (eos)
 - semicrystalline PNC 98–100
 - Simha–Somcynsky cell-hole theory 90
 - ESR (electron spin resonance) 284
 - esterified clay 20
 - EVA-Mg(OH)₂ nanocomposites 58–59
 - exfoliated PMA/clay nanocomposites 286–293
 - exfoliation state 264
 - expansion coefficient, thermal 83–89
 - extreme separation (ES) 286
 - extruder, TSE 86
- f**
- Fe₃O₄ 177–180
 - Fermi contact interaction 231
 - fibers
 - carbon 156–161
 - short 155–161
 - thinning/breakage/pulverization 160
 - fillers
 - combination of 156–161
 - concentration 23–24
 - DSC 25–26
 - dynamic TGA 18–19
 - inorganic 312
 - modified 5
 - Nanofil 804 3–4
 - particulate 153–155
 - stability 15–18
 - surface cleanliness 14–15

- TGA 13–22
- *see also* nanofillers
- film formation 148
- films, SEBS 215
- flame-retardants (FRs)
 - multicomponent systems 62–66
 - nanoadditives 33–42
 - PA11–HNT 56–57, 64–65
- flame-retardancy 33–74
- flammability
 - characterization techniques 42–45
 - elastomer–clay nanocomposites 50–52
 - epoxy–clay nanocomposites 47–50
 - polymer–clay nanocomposites 46–47
 - polymer–graphene nanocomposites 52–54
- Flory’s interaction parameter 212
- flow-induced structure change 275
- fluids, Newtonian 253
- force–deformation curve 210, 217
- force–distance curve 186, 198–200
- forced oscillation 189
- Fourier transformation, NMR 230
- fractal structure 85
- fragility index 80
- free energy, Helmholtz 92
- free induction decay 230
- free volume, relative 94
- free-volume-frozen fraction 98
- frequency, resonant 189
- friction
 - coefficient of 158, 163
 - sliding 146
- fully synthetic clays 77
- fumed silica 338
- functional groups, polymerizable 115
- functionalized POSS molecules 127–128
- g* value 232

g

- gallery thickness 300–302
- glass transition 81, 87
 - disappearance 295
 - relaxation 180
 - temperature 288
- graphene, nano-, *see* nanographene
- graphite 154
- graphitic band 136
- gravimetric analysis 324
- groups
 - carbonyl 243
 - carboxylic 131
 - methacrylic 125
 - polymerizable functional 115

- TMC 287
- trimethylammonium 290
- unmodified headgroups 236

h

- ²H solid-echo NMR 240
- hairy clay particle (HCP) model 102
- halloysite nanotubes (HNTs) 39
 - flammability 55–57
- Havriliak–Negami (HN) function 169, 179
- HD-CNFs 271
- headgroups, unmodified 236
- heat paths 148
- heat release rate 46–47
- heating, isobaric/isothermal 81–82
- height image 224
- Helmholtz free energy, configurational 92
- Hencky strain rate 257, 277–279
- Herschel–Bulkley model 254
- Hertzian contact solution 197
- heterogeneity of organoclays 237–238
- hexadecyl-TBP (HTBP) 237
- hexagonal lattice 35
- hexyl-TMA (HTMA) 238
- Hi-Res TGA 13
- high-performance tribomaterials 143
- hindered hydrogen bonding 296–298
- HIPS–graphene oxide nanocomposites 53
- HISO-POSS 119–121
- HN (Havriliak–Negami) function 169, 179
- HNTs (halloysite nanotubes) 39
 - flammability 55–57
- homopolymerization 122
- honeycomb structure 35
- Hooke’s law 197
- “house-of-cards”-like structure 278
- hybrid colloid dispersions 305
- hybrid rheological response 277
- hybridization process 304, 313
- hydrogen bonding, hindered 296–298
- hydrolytic degradation 335
- 4-hydroxy-2,2,6,6-tetramethyl-piperidin-1-oxyl (TEMPOL) 236
- hyperfine couplings 232

i

- imidazolium-treated montmorillonite 17
- immiscible polymers 207
- immobilization, surfactant 238–239
- impurities 79
- in-situ* polymerization 309
- inhibited crystallization 295
- inorganic filler 312

- interaction coefficients, thermodynamic 100–104
- interaction parameter, Flory's 212
- interactions
 - anisotropic 284
 - local 283
- intercalants 82–83
- intercalated nanocomposites (INCs) 242–243
- intercalated PEO/clay nanocomposites 293
 - segmental mobility 300–302
- interface
 - PMA/clay 288–291
 - reactive polymer–polymer 207–213
 - rigid 292
- interfacial medium 145
- interfacial region, thickness 291–293
- interfacial removal 160
- interfacial rubber phase 206
- interference AUC 305–306
- internal lubricants 156–157
- internal pressure 93
- interpolation 83–84
- intrinsic viscosity 253
- iron, PVDF/Fe₃O₄-based nanocomposites 177–180
- isobaric/isothermal cooling/heating 81–82
- IUPAC nomenclature 75
- j**
- Johnson–Kendall–Roberts (JKR) model 198–199
 - SEBS 217, 221–223
- jump-in 187
- k**
- kaolinite aluminosilicate clay 39
- KBKZ's model 256
- l**
- latex, acrylate-based polymer 314
- lattice
 - constants 99
 - hexagonal 35
- laws and equations
 - Berthelot's rule 102
 - Carreau equation 255
 - compressibility/thermal expansion 80
 - configurational Helmholtz free energy 92
 - corresponding states principle 92
 - Coulomb equation of sliding friction 146
 - Debye equation 169
 - electric modulus 170
 - empirical Tait equation 83
 - Herschel–Bulkley model 254
 - Hertzian contact solution 197
 - HN function 169
 - Hooke's law 197
 - 5 point formula 84
 - Poiseuille's law 252–253
 - Poisson's ratio 195
 - rheological Maxwell equations 255
 - viscosity coefficient 189
 - Vogel–Fulcher–Tammann (VFT) equation 170
- layered silicate nanocomposites 1
 - PLSNs 229–249
 - PS- 307–313
- layers
 - aluminosilicate 9
 - organically modified 237–242, 334–335
 - surfactant 240–242, 244–247
- LD-CNFs 271
- Lennard–Jones potential 93–95, 101–104
- Lichtenecker model 172–173, 181
- Limiting Oxygen Index (LOI) 44
- line shapes
 - nitroxide radicals 285–286
 - spectral 233
- linear wear rate 152
- liquids 90
 - viscosity 97
- local interactions 283
- loss factor 168
- loss modulus 256
 - SWNT/PMMA nanocomposites 270
- low-temperature dielectric relaxation spectra 178–180
- lubricants, internal 156–157
- m**
- MA-POSS (methacrylic POSS) 119–121
- macrotribology 144
- magnetic parameters 298
- magnetic polymeric matrix 177–180
- magnetic resonance
 - EPR, *see* electron paramagnetic resonance
 - nuclear 229–249
- maleic anhydride 265–266
- manometric respirometer 328
- mapping, nanomechanical 200–201
- mass loss, corrected 14
- matrix
 - magnetic polymeric 177–180
 - polymeric 67, 115–128, 156
- Maxwell equations (rheological) 255

- Maxwell–Wagner–Sillars (MWS) relaxation
168–169
- activation energy 177
- MC (Monte Carlo) computations 101
- MD (molecular dynamics) computations
101
- measurement
- biodegradability 323–329
 - elasticity 193–201
 - environment 19–22
 - PVT 79–83
 - wear experiments 149–151
- melt blending (MB) 272
- melt-compounded nanocomposites 178
- melting point 87
- melting temperature 29–30
- methacrylic group conversion 125
- methacrylic POSS (MA-POSS) 119–121
- methacrylic resins 117
- methods
- characterization, *see* characterization techniques
 - sol–gel 118
 - two-point 199
- microbiological characterization techniques
328–329
- microscale combustion calorimeter 45
- microscopy
- AFM, *see* atomic force microscopy
 - biodegradability 324
 - tunneling 185
- microtribology 144
- migration of nanoclays 66
- mobility
- polymers 290
 - segmental 300–302
- models, *see* theories and models
- modified fillers 5
- ammonium 6–7
 - C18–4C18 27
 - montmorillonite 2, 21, 339–342
 - thermal transitions 26
- Modified Sturm Test 327
- modulus
- elastic (storage) 256, 270
 - electric 176–177
 - formalism 170–171
 - tensile 11
 - viscous (loss) 256, 270
 - Young’s, *see* Young’s modulus
- molecular characterization techniques 329
- molecular dynamics (MD) computations
101
- molecular motion, restricted 289–292
- molecular weight 300
- mono-vinyl POSS 119
- Monte Carlo (MC) computations 101
- montmorillonite 1
- ammonium-modified 17
 - dimethylditalloy- 258
 - flame-retardancy 34–35
 - imidazolium-treated 17
 - OMMT 2, 21, 339–342
 - organophilic 259–260
 - surface-treated 15
- morphology
- characterization 1–5
 - morphological analysis 324
 - spherulite 341
- multicomponent systems 93–97
- FR 62–66
- multidirectional characterization 307
- multifunctional MA-POSS 119–121
- multiphase systems 252
- multiscale composites, design 153
- multiwall carbon nanotubes (MWNTs)
36–39, 129
- AFM studies 201–207
- MWS (Maxwell–Wagner–Sillars) relaxation
168–169
- activation energy 177
- n**
- N–O bond 234
- Na, *see* sodium
- nanoadditives, flame-retardant 33–42
- nanalumina 39, 57–58
- nanoclays 34, 66
- nanocomposites
- biodegradable 331–336
 - CNT-reinforced elastomer 201–207
 - elastomer–clay 50–52
 - epoxy-based 9, 47–50, 52–54, 60, 158
 - epoxy–clay 47–50
 - epoxy–graphene 53
 - exfoliated PMA/clay 286–293
 - flame-retardancy 33–74
 - intercalated PEO/clay 293
 - melt-compounded 178
 - (non)intercalated 242–243
 - NR60 202
 - PA66 163
 - polymer, *see* polymer nanocomposites
 - polymer–clay 46–52, 229–249
 - polymer–graphene 52–54
 - polypropylene, *see* polypropylene nanocomposites
 - polyurethane 3–4, 10

- POSS-based 60–61
 - PS-layered silicate 307–313
 - PVDF-based 167
 - PVDF/clay-based 171–175
 - silicate 1
 - starch 336
 - SWNT/PMMA 270
 - synthesis 115–142
 - thermoplastic-CNF 54
 - TPUNs 50–52
 - nanofillers
 - dispersion 251
 - Nanofil 804 filler 3–4
 - *see also* fillers
 - nanographene 35–36, 52–54
 - nanomagnesium hydroxide 40–41, 58
 - nanomaterials
 - one-dimensional 34–36
 - three-dimensional 39
 - two-dimensional 36–39
 - nanomechanical mapping 200–201
 - nanomechanical properties, BCPs 213–225
 - nanopalpation 197–198
 - nanoparticles, short carbon fibers 157–161
 - nanosilica 39, 57
 - nanostructured agents 126
 - nanotribology 144
 - nanotubes
 - carbon, *see* carbon nanotubes
 - halloysite 39, 55–57
 - natural rubber (NR) 201–207
 - Newtonian fluids 253
 - Newtonian region 268
 - nitroxide radicals 233
 - ESR 284–286
 - nomenclature, IUPAC 75
 - non-Newtonian behavior 254
 - nonintercalated composites (NICs) 242–243
 - nonrestricted segment 290, 292
 - normal stress 194
 - normalized spectra 180
 - NR60 nanocomposite 202
 - NR (natural rubber) 201–207
 - nuclear magnetic resonance (NMR)
 - ²H solid-echo 240
 - solid-state 229–249
 - numerical differentiation 84
 - nycodenz 314
- o**
- octa-vinyl POSS 119, 127
 - octadecylamine (ODA) 132
 - octadecyltrimethylammonium 15
 - oligomeric silsequioxanes, polyhedral 41–42, 115–128
 - one-dimensional nanomaterials 34–36
 - optics set-up, Schlieren 306, 314–317
 - optimization, curing conditions 29–32
 - order–disorder transition 244
 - organic–inorganic hybrid colloids 303
 - organic matter 22
 - organically modified layered silicates (OMLSs) 237–242
 - biodegradability 334
 - organically modified montmorillonite (OMMT) 2, 21
 - PHBV/OMMT 339–342
 - organoclays 62–63
 - characterization techniques 237–242
 - heterogeneity 237–238
 - organomagadiites 239–241
 - organophilic montmorillonite 259–260
 - oscillating-wear test 151
 - oscillation
 - amplitude and phase 192, 220
 - cantilever 190
 - forced 189
 - oxygen demand 325, 327–338
 - oxygen index 44
 - oxygen transmission rate 10
- p**
- PA-6, specific volume 100
 - PA-6-based PNC 87–89
 - PA11–HNT–FR 56–57, 64–65
 - PA66 nanocomposites 163
 - PABs (polymer alloys and blends) 83
 - palpation, nano- 197–198
 - PALS (positron annihilation lifetime spectroscopy) 97
 - PAMAM 134–137
 - parabolic approximation 197
 - paramagnetic resonance, electron 229–249
 - partial cellular structure 208
 - partial derivative 92
 - particulate fillers 153–155
 - PBAT (polybutylene adipate-co-terephthalate) 336
 - PC (polymer carbon)–graphene oxide nanocomposites 53–54
 - PCL (poly(caprolactone)) 242–247
 - biodegradable nanocomposites 333–336
 - PDMS (polydimethylsiloxane) 266–267
 - PDS (poly(dimethyl-diphenyl siloxane)) 258
 - peak heat release rate (PHRR) 46–47
 - PEB (poly(ethylene-butylene)) 215–221
 - PEG (polyethyleneglycol) 135

- PEI (polyetherimide) 155
 pellethane TPU 51–52
 PEMA (poly(ethyl methacrylate)) 242
 PEO (poly(ethylene oxide)) 264, 293
 – intercalated 300
 percolation 208
 perdeuterated PS 245
 permittivity
 – complex 168
 – dielectric 171–172
 petrochemical-based polymers 342–343
 phase, cantilever oscillation 192
 phase and energy dissipation 191–193
 phase separation 68, 124
 phase shift 218
 phase transitions 79–80
 PHBV-OMMT 339–342
 piezo displacement 198
 piezoelectric tube 187–188
 pigment
 – CaCO₃ 314
 – encapsulated particles 317
 – polyurethane 316
 pin-on-disk test 151
 PLA (polylactic acid) 333–336
 PLA (poly lactide) 278–279
 plastic behavior, Bingham 255
 plate/streak, plate 329
 platelets 22
 – aggregated nanoclay 34
 – nanographene 35–36
 – size distribution/shape 77–78
 – Somasif 290–293
 PLSNs (polymer-layered-silicate nanocomposites) 229–249
 – PS 307–313
 PMA (poly(methyl acrylate)) 286–293
 – segmental dynamics 288–293
 PMMA (poly(methyl methacrylate)) 55–56, 269
 PNCs, *see* polymer nanocomposites
 5 point formula 84
 Poiseuille's law 252–253
 Poisson's ratio 195
 poly(3-hydroxybutyrate-co-3-hydroxyvalerate) (PHBV)-based OMMT 339–342
 polybutylene adipate-co-terephthalate (PBAT) 336
 poly(ϵ -caprolactone) (PCL) 242–247
 – biodegradable nanocomposites 337–339
 poly(dimethyldiphenyl siloxane) (PDS) 258
 polydimethylsiloxane (PDMS) 266–267
 polydispersity 105
 polyesters, biodegradable aliphatic 259–260
 polyetherimide (PEI) 155
 poly(ethyl methacrylate) (PEMA) 242
 poly(ethylene-butylene) (PEB) 215–221
 poly(ethylene oxide) (PEO) 264, 293
 – intercalated 300
 polyethyleneglycol (PEG) 135
 polyhedral oligomeric silsesquioxanes (POSSs) 41–42
 – aminopropylisooctil 130
 – Raman spectroscopy 115–125
 – structure 116
 – XPS 126–128
 polylactic acid (PLA), biodegradable nanocomposites 333–336
 polylactide (PLA) 278–279
 polymer alloys and blends (PAB) 83
 polymer-carbon nanotubes 63–66
 polymer carbon (PC)-graphene oxide nanocomposites 53–54
 polymer-clay nanocomposites 46–52
 – PLSNs 229–249
 polymer-graphene nanocomposites 52–54
 polymer latex, acrylate-based 314
 polymer-layered-silicate nanocomposites (PLSNs) 229–249
 – PS 307–313
 polymer nanoalumina nanocomposites 57–58
 polymer nanocomposites (PNCs)
 – AFM 185–228
 – biodegradability 323–346
 – CNT-based 129
 – colloids 303–321
 – design 153
 – dielectric relaxation spectroscopy 167–184
 – effect of α/κ 86–87
 – flame retardant mechanisms 66–68
 – layered silicate 1
 – materials 128
 – nanomagnesium hydroxide 58
 – PA-6-based 87–89
 – petrochemical-based 342–343
 – PNC-2 87, 89
 – PNC-5 87, 89
 – POSS-based 60–61, 115–128
 – PS-based 104, 307–313
 – reducing parameters 96
 – rheological properties 251–281
 – semicrystalline 98–100
 – specific wear rate 155, 157
 – *see also* nanocomposites
 polymer nanosilica nanocomposites 57

- polymer–polymer interface, reactive 207–213
 - polymeric matrix 67
 - magnetic 177–180
 - Raman spectroscopy 115–125
 - specific wear rate 156
 - polymeric nanocomposites 76
 - polymerizable functional groups 115
 - polymerization
 - *in-situ* 309
 - preparative ultracentrifugation 319
 - polymers
 - α/κ 84–86
 - amorphous 105
 - dendritic 133–135
 - immiscible 207
 - mobility 290
 - petrochemical-based 342–343
 - segmental dynamics 251, 283–303
 - surfactant dynamics 243–247
 - poly(methyl acrylate) (PMA) 286–293
 - segmental dynamics 288–293
 - poly(methyl methacrylate) (PMMA) 55–56, 269
 - polyol/clay mixtures 260–262
 - polyolefin elastomer (POE) 209
 - polypropylene 6
 - polypropylene (PP) 271–272, 275–277
 - polypropylene (PP) nanocomposites 7–8, 11
 - calorimetric behavior 30–31
 - TGA 24–25
 - poly(styrene-*b*-ethylene-*co*-butylene-*b*-styrene) (poly-SEBS) 213–218
 - polystyrene (PS) 82
 - perdeuterated 245
 - PS-based PNCs 104
 - PS-layered silicate hybrid particles 307–313
 - PS-*co*-ma 265–266
 - polytetrafluorethylene (PTFE) 156–157
 - polytetramethylene ether-glyco-*b*-polyamide-12 polyimide-12 (PTME-PA) 60–61
 - polyurethane
 - elastomer–clay nanocomposites 50–52
 - nanocomposites 3–4, 10
 - pigment 316
 - poly(vinylidene fluoride) (PVDF)-based nanocomposites 167
 - PVDF/BaTiO₃-based 175–177
 - PVDF/clay-based 171–175
 - PVDF/Fe₃O₄-based 177–180
 - position dependence 238–239
 - positron annihilation lifetime spectroscopy (PALS) 97
 - potential, Lennard–Jones 93–95, 101–104
 - powder spectra 284–285
 - PP (polypropylene) 271–272, 275–277
 - PP-Mg(OH)₂ nanocomposites 59
 - preparation of nanocomposites 286–287, 293
 - preparative ultracentrifugation 306, 313
 - internal 93
 - polyurethane pigment 317–318
 - pressure
 - PVT characterization 75–114
 - proximal distance 241–242
 - PS-*co*-ma (polystyrene-*co*-maleic anhydride) 265–266
 - PS (polystyrene) 82
 - perdeuterated 245
 - PS-based PNCs 104
 - PS-*co*-ma 307–313
 - Pseudomonas aeruginosa* 345
 - PTFE (polytetrafluorethylene) 156–157
 - PTME-PA (polytetramethylene ether-glyco-*b*-polyamide-12 polyimide-12) 60–61
 - pulse technique 231
 - pulverization, fibers 160
 - PVDF (poly(vinylidene fluoride))-based nanocomposites 167
 - PVDF/BaTiO₃-based 175–177
 - PVDF/clay-based 171–175
 - PVDF/Fe₃O₄-based 177–180
 - PVT (pressure–volume–temperature) characterization 75–114
 - pyrolysis 68
- q**
- Q-value 192
 - quadrilayer model, surfactant 246
- r**
- radial breathing mode (RBM) 134
 - radicals, nitroxide 233, 284–286
 - radiofrequency pulses 230
 - Raman spectroscopy 115–125, 135–137
 - Rayleigh interferometer 306
 - RDP (resorcinol bis(diphenyl phosphate)) 48–49
 - reactions
 - surface 19
 - tribochemical 147
 - reactive polymer–polymer interface 207–213
 - reactivity 126
 - reducing parameters 96

- relative free volume 94
- relaxation
 - activation energy 169–170, 177, 180
 - cooperative 168
 - crystalline 168–169
 - crystalline/MWS 177
 - dielectric 167–184
- resins
 - acrylic 128
 - epoxy 48
 - methacrylic 117
- resonant angular frequency 189
- resorcinol bis(diphenylphosphate) (RDP) 48–49
- respirometry 325
 - manometric 328
- restricted molecular motion 289–291
- restricted segment 290–291
- rheology 251–281
 - biodegradability 323
 - hybrid response 277
- rheopexy behavior 277
- rigid interface 292
- roll wear test 151
- roller-on-plate test 151
- “rolling” effect 161–164
- rotational diffusion, Brownian 234
- rubber
 - interfacial rubber phase 206
 - natural 201–207
- S**
- salts, sodium 77
- sample deformation 193–194, 198
- sample degradation 328
- saturation, surfactant 245
- SC (solvent casting) 272
- scanning calorimetry, differential, *see* differential scanning calorimetry
- scanning tunneling microscopy (STM) 185
- Schlieren optics set-up 306, 314–317
- SDI (smoke developed index) 45
- SEBS (styrene-*b*-ethylene-*co*-butylene-*b*-styrene) 213–218
- sedimentation
 - analysis 303–321
 - coefficient 308–310
 - velocity 307
- segmental dynamics 251, 283–303
 - intercalated PEO mobility 300
 - PMA 288–293
- semicrystalline PNC 98–100
- semisynthetic clays 76
- sepiolite 338
- SH (strain hardening) 257
- shape, clay platelets 77–78
- shape function 196
- shear, steady 258–259
- shear rate 253
- shear thinning parameter 262
- shear thinning region 268
- short fibers 155–161
 - carbon 156–161
- Si–C bonds 127
- silica
 - fumed 338
 - nano- 39, 57
- silicate nanocomposites 1
 - PLSNs 229–249
 - PS-layered 307–313
- silicates, layered 237–242, 334–335
- silicone compounds 115
- siloxane 61
- silsequioxanes, oligomeric 41–42, 115–128
- Simha–Somcynsky cell-hole theory 90–97
- single-wall carbon nanotubes (SWNTs) 36–39, 129
 - carboxylated 137
 - dispersion 55
 - rheological characterization 266–269
- size distribution, clay platelets 77–78
- slide bearings, dry-running 153
- sliding friction 146
- sliding velocity 161–162
- slow-motion EPR 237
- smectites, dioctahedral 1
- smoke characterization techniques 42–45
- smoke developed index (SDI) 45
- Sneddon’s elastic contact 194–197
- sodium salt clays 77
- soil burial 342
- sol–gel methods 118
- solid base body 145
- solid-echo NMR, deuterium 240
- solid-state NMR 229–249
- solids, crystalline 99
- solubility 126
- solubility parameter 93
- solvent casting (SC) 272
- Somasif ME-100 77, 236–247, 287–294
- spacing, basal 22
- specific volume, PA-6 100
- specific wear rate
 - PNCs 155, 157
 - polymeric matrices 156
- spectral line shapes 233

- spectroscopy
 - biodegradability 324–325
 - dielectric relaxation 167–184
 - EPR, *see* electron paramagnetic resonance
 - PALS 97
 - Raman 115–125, 135–137
 - solid-state NMR 230–231
 - XPS, *see* X-ray photoelectron spectroscopy
 - spherical probes 196
 - spherulite morphology 342
 - spin label EPR 232–236, 283–303
 - spin-labeled PEO/TMA 300
 - spin tracers 236, 238–239
 - spring constant 219
 - stability, fillers 15–18
 - stacked-cup CNTs 37
 - standards, biodegradability 331
 - starch nanocomposites 336
 - static density gradients 306
 - statistical analysis 78
 - steady shear 258–259
 - Steiner tunnel test 45
 - STM (scanning tunneling microscopy) 185
 - storage modulus 256, 270
 - strain
 - Hencky strain rate 257, 277–279
 - time-dependent 256
 - strain hardening (SH) 257
 - streak plate 329
 - stress
 - collective 145, 149
 - normal 194
 - transient shear 276
 - yield 11
 - structure
 - cage 42
 - cellular 207–208
 - concentric tube 38
 - exfoliated nanocomposites 287–288
 - fractal 85
 - honeycomb 35
 - “house-of-cards”-like 278
 - intercalated PEO/clay nanocomposites 294–298
 - POSS 116
 - spin-labeled PEO 294
 - superstructure 238
 - surfactant layer 240–242, 244–247
 - Sturm Test, modified 327
 - styrene-*b*-ethylene-*co*-butylene-*b*-styrene (SEBS) 213–218
 - surface
 - modification 14
 - reactions 19
 - surface-treated montmorillonite 15
 - topography 201, 215
 - surfactants
 - dynamics 238–240, 243–247
 - immobilization 238–239
 - interphase 229–249
 - quadrilayer model 246
 - saturation 245
 - spin tracers 236, 238–239
 - surrounding medium 145
 - suspensions 252–254
 - SWNTs (single-wall carbon nanotubes)
 - 36–39, 129
 - carboxylated 137
 - dispersion 55
 - rheological characterization 266–269
 - synthesis of nanocomposites 115–142
 - synthetic clays 77
- t**
- tactoids 48
 - Tait equation, empirical 83
 - tapping mode AFM 188–191
 - TBP (tributylphosphoniumalkyl) 229
 - techniques, characterization, *see* characterization techniques
 - TEGDMA (triethylene glycol dimethacrylate) 116
 - temperature
 - contact 163
 - dependence of electric modulus 176
 - glass transition 87, 288
 - PVT characterization 75–114
 - wear mechanisms 148–149
 - templated synthetic clays 77
 - TEMPO (4-hydroxy-2,2,6,6-tetramethylpiperidin-1-oxyl) 236
 - tensile modulus 11
 - tests
 - Australian test standard AS ISO 14855 326–327
 - Modified Sturm Test 327
 - principles 151
 - Steiner tunnel test 45
 - turbidity 329
 - UL 94 Vertical Flame Test 43–44, 64–65
 - tetraglycidyl-4,4′-diaminodiphenylmethane (TGDDM) 48–49
 - TGA (thermogravimetric analysis) 5, 23–25
 - fillers 13–22
 - flame-retardancy 43
 - Hi-Res 13
 - theoretical oxygen demand (TOD) 327

- theories and models
- Brownian motion 275
 - “cellular structure” model 207–208
 - dielectric permittivity 172–173
 - dielectric relaxation spectroscopy 168–171
 - Einstein-theory of intrinsic viscosity 253
 - HCP model 102
 - Herschel–Bulkley model 254
 - JKR model 198–199, 217, 221–223
 - KBKZ’s model 256
 - Lichtenecker model 172–173, 181
 - modulus formalism 170–171
 - rheological 252–257
 - Simha–Somcynsky cell-hole theory 90–97
 - Sneddon’s elastic contact 194–197
 - surfactant quadrilayer model 246
 - thermodynamic 89–100
 - Vo–Shi model 172–173
 - wear models 150–151
- thermal characterization 13–32, 42–45
- thermal conductivity 148
- thermal degradation 17
- thermal expansion coefficient 83–89
- volumetric 85
- thermal protection 68
- thermal stability 18
- thermal transitions 26–29
- thermodynamic theories 91–100
- interaction coefficients 100–104
- thermogravimetric analysis (TGA) 5, 23–25
- dynamic 18–19
 - fillers 13–22
 - flame-retardancy 43
 - Hi-Res 13
 - weight loss thermogram 16
- thermoplastic nanocomposites 54
- TPUNs 50–52
- thermoplastic starch 336
- thickness
- gallery 300
 - interfacial region 291–293
- thinning
- fibers 160
 - shear 262, 268
- three-dimensional cellular structure 208
- three-dimensional nanomaterials 39
- tilt angle 246
- time-dependent strain 256
- tip-sample displacement 221
- titanium dioxide 154
- Tixogel VP 16
- TOD (theoretical oxygen demand) 327
- TPUNs (thermoplastic polyurethane elastomer–clay nanocomposites) 50–52
- trans-gauche* transitions 240, 244
- transfer film formation 148
- transient extensional viscosity 274
- transient response, cantilever oscillation 190
- transient shear stress 276
- transient shear viscosity 273
- triblock copolymers 213–218
- tribological systems 145–146
- characteristic values 151–152
 - characterization 143–166
 - reactions 147
- tribomaterials, high-performance 143
- tributylphosphoniumalkyl (TBP) 229
- triethylene glycol dimethacrylate (TEGDMA) 116
- trimethylammonium chloride (TMC) 287
- trimethylammonium groups 290
- trimethylammoniumalkyl (TMA) 229
- Trouton’s ratio 274–275
- tube structure, concentric 38
- tunnel test, Steiner 45
- tunneling microscopy 185
- turbidity 305–306, 311
- biodegradability testing 329
- twin screw extruder (TSE) 86
- two-dimensional nanomaterials 36–39
- two-point method 199
- u**
- UL 94 Vertical Flame Test 43–44, 64–65
- ultracentrifugation
- analytical 304–306
 - preparative 306, 313, 317–318
- unloading force curve 217
- unmodified headgroups 236
- v**
- van der Waals force 185, 197
- velocity
- sedimentation 307
 - sliding 161–162
- vertical flame test, UL 94 43–44, 64–65
- viscoelastic properties 223
- viscosity 97
- coefficient 189
 - elongational 277–278
 - intrinsic 253
 - transient extensional 274
 - transient shear 273
- viscous (loss) modulus 256
- SWNT/PMMA nanocomposites 270
- vitreous region 97–98

- Vo–Shi model 172–173
 - Vogel–Fulcher–Tammann (VFT) equation 170, 179
 - volcanic ashes 75
 - volume
 - PVT characterization 75–114
 - relative free 94
 - specific 100
 - volumetric thermal expansion coefficient 85
- W**
- washing protocols 15
 - WAXRD (wide-angle X-ray diffraction) 3
 - ammonium modified fillers 6–7
 - wear experiments 149–151
 - wear mechanisms 146–148, 161–164
 - wear rate 152
 - depth 159
 - weight, molecular 300
 - weight loss thermogram 16
 - wide-angle X-ray diffraction (WAXRD) 3
- X**
- X-band ESR 285
 - X-ray diffraction (XRD)
 - PMA 288
 - rheological characterization 263
 - Somasif ME-100 295
 - wide-angle 3, 6–7
 - X-ray photoelectron spectroscopy (XPS)
 - CNT-based PNCs 130–135
 - POSS-PNCs 126–128
 - xyz scanner 187–188
- Y**
- yield, char 49
 - yield stress 11
 - Young’s modulus 193–195, 200–206
 - polymer interfaces 209–212
 - SEBS 215–218
- Z**
- Zeeman interaction 230
 - zinc sulfide 154