

## Index

- a**
- aberration-corrected transmission electron microscopy (AC-TEM), 572
  - ab initio* calculations, 750
  - abrupt Si–Ge interface, TEM image, 863
  - absorption, 236
    - emission in nonselective coating, 209
    - hexagonal lattices, made with Ag/Au nanoparticles, 94
    - pressure composition isotherm, 446
    - electrochemical, 441, 445
    - spectrum, 173
  - abstract binary element, 681
  - AC. *see* activated carbon
  - acetate, formed during dark fermentation, 264
  - acetic acid, 254
    - fermentation, 251
  - acetomicrobium flavidum, 252
  - acetonitrile (ACN), 382, 399
  - acetothermus paucivorans, 252
  - acetyl coenzyme A (acetyl-CoA), 253
  - acid-base interactions, 305
  - acid-catalyzed processes, 3
  - acidification, 256
  - activated carbon, 379, 395, 397
    - electrodes, 385
    - supercapacitor, 404
  - activated sintering, 338
  - activation energy, 597, 746
  - active sites, 65
    - formylmethanofuran dehydrogenase, 259
    - resist coking tuning, 65
  - adsorbents, 1168
  - advanced composite material (ACM), 332
  - Advanced Energy Consortium (AEC), 41
  - aeroacoustic emissions, 327
  - aerodynamic force predictions, 326
  - aeroelasticity, 328
  - aerogels, 940, 944, 970, 1153, 1155
    - applications, 942, 943, 948
    - architectural, 970
    - based plaster, 956
    - building insulation, use in, 970
    - challenges/future perspectives, 961
    - inkjet printer-based, 972
    - insulation, 972
    - monoliths, granules, and sheets, 945
    - preparation, 944
      - drying of gel, 945
      - gel formation, 944
    - products/properties 948
    - safety/hazard measures, 29, 962
    - thermal insulation in, 944
  - aerospace components, lightweight materials, 809
  - aerospace diligence, 843
  - aerospace industry, PMNCs applications, 836
  - aerostructural applications, material properties, 332
  - Ag/AgCl electrode, 637
  - agglomeration, at high temperatures, 435, 913, 925
  - Ag nanoprisms, UV-vis spectra, 151
  - Ag<sub>2</sub>S/CZTS/TiO<sub>2</sub> photoanode, 640
  - airborne pollutants, 983, 1161
  - airborne wind energy system (AWES), 1102
  - air-cleaning gypsum board systems, 988
  - air conditioning, 977
  - airfoils, 329
  - air mass, 867
  - air purification, 978
  - alcohols, 599
  - alkali earth metal oxides, 68
  - alkali metal tetrahydroborates, 751
  - alkaline fuel cells (AFCs), 1058
  - alkene cycle, 19, 28
  - alkoxylation, 9

- alkyl amine solutions, 1168
  - alloys
    - alloying process, 437, 862
    - chemical composition
    - –  $M_s$  temperature and critical cooling rate (CCR), 711
    - low melting point, thermophysical properties, 905
    - steel, property of, 664
  - alumina ( $Al_2O_3$ ), 838, 844
    - $\gamma$ - $Al_2O_3$ 
      - – time dependent, 1001
      - – thermal conductivity, 1000
      - – nanoparticle, 50, 922
    - $\alpha$ - $Al_2O_3$  nanofluids, 1001
    - ceramic matrix, 846
  - aluminophosphates, 3
  - aluminum, 3
    - Al–Zn nanoparticles, 1013
    - film, 281
    - foams, 844
    - matrices, 838
  - aluminum oxide nanoparticles, 43, 44
  - AM. *see* air mass
  - American Solar Energy Society, 967
  - aminated carbon, 402
  - amines deteriorate, 1168
  - 2-aminobenzonitrile (ABN)
    - dicyandiamide/cyanamide, copolymerization, 621
  - 3-aminopropyl triethoxysilane, 212
  - ammonia-oxidizing *Nitrosomonas europaea* cell, 1135
  - ammonia production plant, 1164
  - amorphous silicon films, 359
  - anaerobic heterotrophic microorganisms, 252
  - anaerobic sequence batch reactor (AnSBR), 256
  - anatase  $TiO_2$  beads
    - SEM images, 107
  - Anglo-Saxon press, publications on nanotechnology, 317
  - aniline
    - copolymerization of dicyandiamide/cyanamide, 621
  - anisotropic nanostructures, 110, 113
  - anisotropic nanowhiskers  $W_{18}O_{49}$ , 754
  - anisotropic peak broadening analysis
    - for morphology investigations, 17
  - annealed TiNi sample
    - microstructure, 442
    - TEM micrograph and electron diffraction patterns, 443
  - annual energy consumption, 59
    - global consumption, 597
  - anode-active materials, 357
    - intermetallics, 358
    - silicon, 359
  - anomalous diffusion, 787
  - anticorrosion, 849
  - antifreeze agent, 404
  - antireflective coating (AR), 236, 241
    - top layer, 235
  - aqueous-based  $CO_2$  reduction reactions, 1126
  - aqueous electrolytes, 399, 404
    - disadvantages, 399
    - high ionic concentration, 399
    - low resistance, 399
  - AREVA NP (nuclear power), 304
  - argon gas, 970
  - arithmetic logic unit (ALU) operations, 682
  - Armchair nanotubes, 487
  - aromatic hydrocarbons, 27
  - aromatics cycle, 28
  - Artemia cyst shell (AS), 584
  - artificial atoms, 138
  - asbestos, 991
  - Aspen<sup>TM</sup>, 62
  - asphalt binders, 988
  - asphaltenes
    - nanocolloids
      - – crude oil properties, 52
      - – structural states, 51
    - nanophase boundaries, 53
    - temperature-concentration phase diagram, 51
  - asphalt roofs, 988
  - asphalt shingles, 988
  - asthma trigger, 986
  - Auger electron spectroscopy (AES), 437
  - austenite
    - behavior of, 721
    - stability, 716
  - austenitic steels, 303
  - austenitization temperature, 711
  - autoclave, 947
  - automobile industry
    - PMNCs, potential applications of, 837
  - AZ31 alloys, 818, 820
    - B/ $Al_2O_3$  nanocomposite, 821
    - nanocomposites, endurance strength of, 821
  - azimuthal splitting, 771
- b**
- back surface field (BSF) layer, 148, 166
  - bainitic ferrite plate thickness, 713

- bainitic transformation, and  
     microstructure, 712  
 ball mill system, 437, 919  
   – quartz ( $\text{SiO}_2$ ), cycling behavior, 366  
 bandgap, 746  
   – semiconductor materials, 300  
 band-to-band transfer, 635  
 basalt rock cliffs, 1164  
 base-treated zeolite (BTZ-13), 25  
 batteries  
   – chemistries, 386  
   – energy storage mechanisms, 393  
   – industry, 975  
   – waste, 976  
 batteryless sensors, 990  
 B-doped Si/Ge nanocomposites, 559  
 bending stiffness, of cantilever, 663  
 bentonite suspension, 44  
 benzene-silica electrolyte  
   – periodic mesoporous, 577  
 benzonitrile  
   – copolymerization of dicyandiamide/  
     cyanamide, 621  
 beryllium, 421  
 Bi–Ag alloy nanospheres, 623  
 binary operations, fundamental physics of, 690  
 binary switches  
   – 3D organization, in circuit with fan out, 699  
   – energy associated with fan out, 693  
   – energy diagram, 691  
 binary transitions, for computing, 685  
 binder-free carbon electrodes fabrication, 382  
 biocides, 985  
 bioelectrosynthesis, 1133  
 bioenergy, 377  
 $\text{bioH}_2$  production, 252  
   – via photofermentation/nanoparticles  
     role, 260  
 biological gaseous energy recovery, 263  
 biomass, 1173  
 biosphere, 929  
 biosystems, 367  
 bipolar effect, 528  
 birefringent liquid crystal behavior, 495  
 bishydroxydeoxybenzoin, 986  
 bismuth (Bi)-based carbon monoxide  
   (CO), 1131  
 bismuth telluride material ( $\text{Bi}_2\text{Te}_3$ ), 22, 313,  
   519, 521, 554  
   – antimony alloys, 879  
   – based nanocomposites, 556, 558  
   – peak ZT values, 549  
   – nanowires, 880  
  
 $\text{Bi}_2\text{Te}_{2.7}\text{Se}_{0.3}$  pellet, phonon scatterings, 553  
 $\text{BiVO}_4$  porous film, 641  
 blackbody radiation, 208, 232–234  
 black materials, 212  
 black silicon, 975  
 black titania nanotube arrays (B-TNT), 610  
   – absorption spectra and photographs of, 611  
 blanket insulating sheets, 970  
 block polymer lithography (BCPL), 580  
 body-centered cubic (BCC), 719  
 Bohr radius, 184  
 Boltzmann constant, 550  
 Boltzmann transport equation (BTE), 516  
 borohydride, 426  
 boron-doped graphenes (BG), 573  
 boron-oxygen centers, 167  
 boundaries, TEM image, 275  
 box counting method, 784, 785  
 Bragg reflectors, 198  
 brake fluids, 997  
 Brønsted acid, 23  
 bronchial irritants, 986  
 Brownian motion, 919, 931  
   – of nanoparticles, 925  
 Buchwald–Hartwig reactions, 929  
 bucky gels, 919  
 buckypaper, 383  
 building-integrated photovoltaics (BIPV), 973,  
   975  
 building materials, strength-to-weight  
   ratios, 969  
 bulk ceramic nanomaterials  
   – fracture strength/toughness, 341  
   – hardness/yield strength, 339  
 bulk conducting material, 149  
 bulk fluid properties, modification of, 42  
 bulk heterojunction (BHJ), 145  
 bulk insulators, 971  
 bulk nanocrystalline ceramic materials, 337  
 bulk Pd–H system, 423  
 bulk plasmons, 149  
 bulk silicon, 874  
 1-butyl-3-methylimidazolium  
   hexafluorophosphate (BMIM- $\text{PF}_6$ ) ionic  
   liquid, 1128  
 butyric acid, 254  
  
**c**  
 cadmium telluride (CdTe), 135  
 calcia-stabilized zirconia (CSZ), 284  
 calcination, 10  
 calcium carbonate nanoparticles, 45  
 calcium leaching, 983

- calcium sulfate, 988
- calthrate hydrides, 434
- Calvin–Benson–Bassham (CBB), 1134
- Ca-modified counterparts, 822
- cantilever piezoelectric energy harvester, 659
  - alternative design, 660
  - efficiency enhancement, 659
  - geometries, 660
- capacitance, 400, 408
  - performance, 404
  - pore size. effect of, 396
- capacitors
  - charging through a transistor in inverter circuit, 688
  - coin cell, 385
  - energy storage, 386
  - rolling system, 385
- capping agents, 120
- carbide-derived carbon (CDCs) 395
  - cyclic voltammograms, 403
- carbide, 236
  - bainitic steels, 717
  - microstructure, 717
  - precursors, 408
- carbon
  - accumulation, 63, 75, 79
  - aerogel scaffolds, 424
  - allotropes, 380, 1147
    - schematic representations, 379
  - based capacitor systems, 386
  - based conductors, 487
  - based nanomaterials, 461
  - based (organic) pigments, 210
- carbon black, 125, 396, 921
  - based coatings, 210
- carbon capture
  - nanoparticle ionic materials (NIMS), 1172
  - and storage/sequestration (CCS), 1109, 1111, 1164
    - and use (CCU), 1110, 1164
- carbon-coated silicon nanotubes, 360
- carbon deposition, 64, 68
  - methane decomposition, TPO-MS profiles of, 76
  - characterization, 71
- carbon diffusion, 68
- carbon dioxide, 59, 63, 1164
  - activation, 68
  - capture, 1165
    - cellulose-based porous nanomaterials, 1172, 1173
    - CuO nanoparticle-loaded porous carbons, 1173
      - efficiency, 1169
      - nanocomposites, 33, 1173
      - nanoparticle ionic materials (NIMS), 1172
      - nanoporous membranes, 1172
      - technologies overview, 1166
    - concentrations, 1109
    - conversion, 1111
    - costs, 1163
    - electrochemical reduction of, 1112
    - electrolysis
      - on transition metal catalysts, 1129
    - emissions, 271, 970, 975, 1109, 1161, 1162, 1163
      - warming *versus* cumulative, 1162
    - equilibrium constants, 1121, 1122
    - molecule possesses
      - water molecule nucleophilically attacks, 1121
    - global warming mitigation strategy, 1111
    - Ni/SiO<sub>2</sub> catalysts, conversion 66
    - producing plants, 1110
    - reactions, 1122
    - reduction, 967, 1113
      - cathodic half-cell reaction, 1113
      - to N-formylmethanofuran, 257
      - thermodynamic properties, 1117
      - value-added products, 1112
    - as resource, 1163
    - separation technologies, 1165, 1167, 1171, 1172
      - *versus* electrolyte pH, 1120, 1121
      - variation of H<sup>+</sup>, 1124
    - solubility of, 1121
    - using selectively permeable membranes, 1173
- carbon emissions, 871, 968, 982
  - global, 977
- carbon-enriched austenite, 712
- carbon fiber growth mechanisms/false color micrograph, 75, 331
- carbon formation, 64, 71
  - demarcation of, 64
- carbon-free electricity, 295
  - worldwide, 298
- carbon fullerenes, 746
- carbonic acid
  - acid dissociation constants, 1123
  - formation from water-solvated CO<sub>2</sub> molecule, 1120
- carbon monoxide (CO), 59
- carbon nanocoil (CNC), 571
- carbon nanofibers (CNF), 126, 571, 833, 982

- carbon nanomaterials, 391, 571, 1146
  - based catalysts, 574
  - composites, 386
  - enhanced PCMs, 461
  - fatty acids-based PCMs, 21, 466
  - inorganic nanoparticles-enhanced PCMs, 21, 474
  - metal nanoparticles-enhanced PCMs, 21, 473
  - paraffin-based PCMs, 21, 462
  - polymer-based PCMs, 21, 469
  - salt and salt hydrates PCMs, 461
  - printing of, 380
- carbon nanoions (CNOs), 572
- carbon nanostructures, 115, 400, 409
  - based counter electrodes, 125
- carbon nanotube (CNT)
  - aerogels, 493
  - bundles, 396
  - twisting of, 492
  - cables
    - electrical conductivity, 500
    - fabricated prototype coaxial, 500
  - coatings, 210
  - on Al substrate, reflectance spectra, 218
  - by CVD method, reflectance, 217
  - conductors, 487
  - Cu composite
    - Ashby plot comparing ampacity and, 499
  - fibers, 501
  - in forecast of
    - adoption of, 486
  - growth mechanisms, 488
  - hexadecane composites, 1016
  - interfaces, 497
  - matrix concentrations, effect on coating reflectance in UV-vis range, 218
  - metal composites, 22, 497, 498
  - wires and cables, 499
  - yarns, 498
  - nanofluids, 1009
  - organic composites, 977
  - polypropylene composite material, 211
  - properties of, 21, 486
  - purification and enrichment of, 22, 489
  - reinforced Mg nanocomposites, 821
  - Si anode, 501
  - side effects, 992
  - sponges
    - morphology, 1148
  - synthesis of, 21, 487
  - wet spinning, of yarns, 491, 493
  - chemical doping, 22, 495
    - from dispersions, 22, 490
    - from liquid crystalline solutions, 22, 494
    - winding prototype generator, 501
    - wires, 22, 490, 500
    - and cables, applications of, 22, 500
    - prototypes of devices using, 500
    - technical feasibility of, 500
- carbon nitride (C<sub>3</sub>N<sub>4</sub>) nanocomposite, 636
- carbon quantum dot (CQD), 636
  - quantum-confined electron energy levels, 142
- carbon templates, 6, 7
  - zeolite (CTZ-16), 25
- carcinogens, 991
  - chlorinated hydrocarbons, 980
- cardiac pacemaker, 656
- Carnot efficiency, 549
- carrier energy filtering, 554
- carrier mobility, 513, 726
- carrier pocket engineering, 555
- carrier solar cell, 156
- catalyst
  - characterization, 76
  - coated alumina wires, 380
  - coated whiskers, SEM views, 579
  - coking
    - evaluation, analysis tools, 78
    - thermodynamic view of, 60
  - deactivation, 21
  - performance, of zeolite, 4
  - ZSM-5 catalysts, 25
- cathode-active materials, 361
- CB. *see* conduction band
- CDC. *see* carbide-derived carbon
- CdSe nanoparticles, 615
  - energy diagram of, 140
- CdS/MoS<sub>2</sub> pn junction, 640
- CdS photoanodes, 640
- CdTe nanocrystal (NC)
  - colloidal suspensions, absorption spectra of, 140
- cell phone displays, 977
- cell resistance (ESR), 404
- cellulose fiber, 973
- cement composites, 983
- cementite nanowires, 182
- ceramic materials, 231
  - fibers, 844
  - dielectric matrix, 235
  - lightweight composites, 336
  - matrix nanocomposites, 845
  - manufacturing methods, 27, 845
  - mechanical properties, 27, 846

- transport industry, 846
- nanocomposites, 845, 851
- polymer membranes, 368
- cerium oxide ( $\text{CeO}_2$ ), 68, 69
  - lattice, 69
- cerium-zirconia oxide solid solutions ( $\text{CeO}_2\text{-ZrO}_2$ ), 69
- certification
  - methodology
    - illustration of, 344
    - type testing/type evaluation, 343
    - wind energy applications, 342
    - approval of designer, 344
    - manufactures/suppliers, 343
    - nanomaterial processing, 343, 344, 345
    - nanostructured components, 345
- $\text{CeS-CrS}_2$  nanotube, 771
  - high-resolution HAADF STEM image of, 772
- $\text{CF}_3$ -aerogels, 1153
- chalcogenides, 522
- $\text{CH}_4$  conversion
  - by Ni/Ce-ZrO<sub>2</sub> catalysts, 67
  - by Ni/SiO<sub>2</sub> catalysts, 66
- charge-based memory, 695
- charge carrier injection, in bR/TiO<sub>2</sub> photoanode cell, 610
- charge-discharge cycling, 380
  - curve, 365, 380
  - processes, 356
  - stability tests, 385
- charge storage mechanism, 392, 394
- charge-transfer resistance, 403
- Charpy test, 717
- chemical vapor deposition (CVD), 147, 214, 380, 487, 786, 860, 971
- chemical vapor transport (CVT), 765
  - of chalcogenides, 747
- chemisorption, 67
- chitin, 368
- chitosan, 491
- chloralkali process, 1132
- chlorine, 765
  - gas, 986
  - water purification, used in, 980
- chlorites, 746
- $\text{C}_{5+}$  hydrocarbons, 23
- CIGS. *see* copper, indium, gallium, and selenium
- circular CO<sub>2</sub> economy, 1165
- clathrates, 519, 528, 530
- Clausius–Mosotti relation, 86
- clean energy, 597
- cleaning contaminated water, in oil spill sites, 1139
  - aerogels, 1153
  - conventional routes, 1140
  - crude oil composition, 1139
  - inorganic nanomaterials and composites, 1141
  - nanomaterials-based membranes, 1153
  - nanoremediation, 1139
  - nanosized natural and synthetic polymers, 1151
  - oil–water interfacial tension, 1140
  - toxicity, cost, and selection of nanomaterials, 33, 1154
- cleaving zeolite (MTT), 15
- Clemson Nanomaterials Center (CNC), 377
  - contributions, 380
- climate change, energy revolution requirement, 297
- Clostridia butyricum*, 250, 251
- Clostridium aceticum*, 1133
- Clostridium beijerinckii*, 251
- Clostridium ljungdahlii*, 1133
- Clostridium pasteurianum*, 251
- Clostridium welchii*, 251
- clumped graphene sheets, 396
- CNC. *see* Clemson Nanomaterials Center
- CNT. *see* carbon nanotube
- coal-burning power plants, 975, 1167
- coal gasification, 597
- coating, 849
  - absorptance vs. wavelength bands spectrum, 221
  - corrosion, 226
  - nanoparticles, 1151
  - oxidation, 235
  - for solar collectors, reflectance curves, 215
- cobalt, 259
- CODE (COating DEsigner) software, 240
- CO disproportionation, 76
- coefficient of performance, 872
- coherent oxygen-enriched nanoclusters (NCs), 274
- coin cell-type supercapacitors, 384
- coke-free methane reforming catalysts, 79
- coke resistance, 68
- coking rate deposition, 67
- colloidal chemical synthesis, 120
- colloidal dispersion, 914
- colloidal materials, 43, 918
- colloidal stability, 919

- commercial fuel, 597
- communication devices, 650, 681, 679, 680
- complex metal hydrides
  - properties of, 421
- complex metal oxides, 634
- composite formation
  - with carbon nanostructures, 115
  - SEM image, 112
  - using hydrothermal method, 466
- compound annual growth rate (CAGR), 1079
- compressive strength, 940
- computational fluid dynamics (CFD), 328
- concentrated solar power (CSP), 207, 232
- concrete, 981
  - compressive strength
    - – nanobinders, effect of, 982
  - reinforcing with nanofibers, 983
  - titanium dioxide nanoparticles, role of, 982
- conducting polymers, 573
- conduction band edge (CBE), 105, 598, 636
- conductive glass plate, 104
- conductive nanofiber mats, 117
- conductivity, 498
  - of metallic CNTs, 487
  - performances of, 312
  - temperature plot, 500
- contact angle
  - adhesive and cohesive forces, 305
- contact metalization, 867
- contractive symmetry, 783
- controlled potential electrolysis (CPE), 1127
- conversion efficiency, 547
  - as function of temperature and thermocouple material, 873
- conversion electrodes, 365
- co-oligomerization
  - of unsaturated hydrocarbons, 1111
- Co-Operative Patent Classification (CPC), 1061
- CoOx/NCNC hybrid catalysts, 572
- COP. *see* coefficient of performance
- copper, indium, gallium, and selenium (CIGS), 973, 135
  - solar cells, 176
- copper–indium–gallium–diselenide, 135
- copper nanowires (CuNWs), 474
- copper oxide, 43
  - nanofluid, 999
  - nanoparticles, 44, 1173
  - – porous carbons, 1173
  - nanowires, 236
- copper sulfide, 235
- copper wires, 500
- core–shell
  - coaxial nanocable structure, 608
  - heterojunction, 862
  - nanostructures, 108
    - – configurations, 108
  - single NW silicon solar cell
    - – SEM image, 865
  - structure, 573
- corrosion, 185, 487
  - protective coatings, 287
- CoSb<sub>3</sub>-based skutterudites, 529
- Co<sub>4</sub>Sb<sub>11.2</sub>Te<sub>0.8</sub>Sn<sub>2</sub> material, 529
- cosmetics, drug delivery, 997
- cost-effective materials, 325, 550
- Coulombic force, 395
- counter electrodes, 124, 125
- coupled ferroelectrics thermoelectric materials, 525
- covalent hydrides, 421
- crack blunting effect, 716, 981
- crack bridging, 342
- crack growth resistance curve, 342
- crack initiation, 721
- crack propagation
  - carbon nanotubes, role in, 983
- critical cooling rate (CCR), 712
- critical micellar concentration (cmc), 1003
- critical resolved shear stress (CRSS), 817
- Cr–Ni ODS, high-resolution TEM image, 274
- Cr<sub>2</sub>O<sub>3</sub>–Cr composite coating, 211
- 9Cr–ODS (Fe–9Cr–0.11C–2W–0.2Ti–0.35Y<sub>2</sub>O<sub>3</sub> ferritic–martensitic) cladding tubes
  - TEM micrograph, 280
- 9Cr–ODS steel
  - cladding tubes, 278
  - creep rupture strength of, 280
- CrS<sub>2</sub>/VS<sub>2</sub>-based misfit compounds, 774
- crude oil production, 59
- 9Cr–2W–0.1C–0.2Ti–0.35Y<sub>2</sub>O<sub>3</sub> ODS cladding tube, 279
- cryogenic rocket fuel, 972
- cryogenic separation captures, 1167
- cryogenic temperature, 940
- cryotechnology, 958
- crystal growth, 12
  - modification, 13
- crystalline silicon panels, 974
- crystalline Si solar cells, 165
  - application, antireflection coatings, 165
  - chemical texturing, 165
  - conventional chemical texturing, 165
  - conventional light trapping for, 165

- designs, 166
  - integration of, Mie coatings, 14, 166
  - monocrystalline, 165
  - polycrystalline, 165
  - crystalline TiO<sub>2</sub>, 1149
  - crystallization processes, 4
  - crystallographic parameter, 721, 817
  - crystal size effects, 8, 20, 21, 69
  - CsCl-type cubic structure, 451
  - 1CSi steel, 716
  - CTAB, thermal conductivity, 1003
  - cultivating energy, 788
  - Cu nanofluid, 999
  - Cu<sub>2</sub>O nanoparticles, 929
  - current density (CD), 1127
  - Cu<sub>2</sub>Se nanocomposites, 559
  - Cu<sub>0.44</sub>Ti<sub>0.44</sub>Mn<sub>0.84</sub>Fe<sub>0.28</sub>O<sub>3</sub> with bixbyite structure, 211
  - Cu vacancies, 235
  - CV. *see* cyclic voltammogram
  - CVD. *see* chemical vapor deposition
  - cyanobacteria, 598
  - cyclic adsorption–desorption operations, 1169
  - cyclic voltammetry, 381, 393
  - β-cyclodextrin-grafted MWCNTs, 1147
- d**
- dark current, 870
  - dark fermentative H<sub>2</sub> production, 257
    - biochemistry of, 252
    - domains of, 251
    - improvement in, 254
    - metabolic pathway of, 253
    - using nanoparticles, 250
  - Darwin's theory, 95
  - D-band stemming, 76
  - 3D bulk/2D quantum well/1D quantum wire
    - DOS in terms of average energy, 513
  - 2D carbides (MXene), 397
  - DC SQUID sensor, photograph of, 282
  - dealkylation, 28
  - De Broglie wave, 890
  - decarbonized energy, 295
  - deep reactive ion etching, 858, 864, 865
    - method, 858, 864
  - degradation mechanisms, 224
    - in evacuated tube collector, 224
  - degree of fractalness, 784
  - delithiation, 356
  - dendrimers, 980
  - densification, 357
  - density functional theory (DFT), 931
    - calculations, 1127
  - Department of Energy (DOE), 1110
  - depolluting titanium dioxide, 979
  - deposition techniques, 142
  - desilication, 5
    - in alkaline media, 5
  - desorption, electrochemical pressure-composition isotherm, 445
  - 3D graphene networks, 729
  - diamond nanorods, 989
  - dibenzyl toluene-based MoS<sub>2</sub> nanofluids, 1004
  - diborane, 865
  - dibutyl magnesium, 424
  - dicyandiamide, 620
  - dielectrics, 238
    - constant, 942
    - nanoparticles, 164, 174
    - nanostructures, 163
      - – optical resonance, 163
  - Diels-Alder and Mukaiyama aldol reactions, 928
  - diethanolamine (DEA), 1167
  - differential scanning calorimetry (DSC), 405
  - diffuse doping profile, 866
  - diffusion barrier properties, 301
  - diffusion coefficient, 404
  - diffusion distances, 356, 395
  - digital information processing, 682
  - diiodooctane, 195
  - dilatation symmetry, 787
  - DIM. *see* dynamic insulation material
  - dimethyl ether, 59
  - dimethyl sulfoxide (DMSO), 534
  - dip coating, 237, 380, 864
  - dipolar approximation, 85, 86
  - dipolar moment, 85
  - diquaternary ammonium-type surfactant, 12
  - direct absorption collection (DAC), 900
  - direct current, generated by wind, 249
  - directional electron transport, 113
    - path, 110
  - directly growing VACNTs
    - roll-to-roll (R2R) process, 381
  - direct methanol fuel cell (DMFC), 577, 1057
  - direct sonication, 916
  - disintegrated melt deposition, 811
  - dispersants, 919
  - dispersion, 65
  - dissolution and precipitation (DP), 449
  - distributed Bragg reflector (DBR), 176, 197
  - 3D Kagome nanolattice, 981
  - DMD-synthesized composites, 815
  - DNA materials, 509
  - DNA memory, array-free organization 703
  - donor/acceptor nanomaterials, 145, 195



- donor material, 145
  - dopant
    - exposure time, 868
    - gas precursors, 865
    - silicon system, 866
  - doping, 530, 630
    - chemical, 757
    - gas precursors, 866
    - of IFs/INTs by Re atoms, 757
    - inorganic fullerenes/nanotubes, 757
    - of MoS<sub>2</sub> and WS<sub>2</sub> fullerenes and nanotubes, 745
    - of nanoparticles, 757
  - double layer capacitance, 309, 394
  - double metal hydroxides, 979
  - double oxide coating on Ti for reconditioning (DOCTOR), 285
    - blading, 380
  - down-shifting (DS), 152
  - 3D photonic crystals, 109, 198, 199
  - dressed polarizability, 87, 88
  - DRIE. *see* deep reactive ion etching
  - drilling fluids, 42
    - dependencies, 45
    - effects of nanoparticles, 43
  - droplets states
    - on microstructured surfaces, 306
  - dropwise condensation, 306
  - Drude–Lorentz classical dispersion formula, 238
  - dry powder glue, 982
  - dry reforming of methane (DRM), 66
  - drywall, 988
  - DSC. *see* differential scanning calorimetry
  - dual cycle, 19
    - hydrocarbon pool mechanism, 19
  - ductility, 714, 715, 716, 717
  - durability test, 224, 641
  - dye bilayer sensitizer, schematic, 122
  - dye-sensitized solar cell (DSSC), 13, 102, 103, 136, 733
    - construction and working, 13, 103
    - TiO<sub>2</sub> morphologies, photovoltaic performance, 118
    - history, 13, 102
    - nanotechnology, role of, 105
    - photovoltaic conversion efficiency, 108
    - technologies, 734
  - dynamic aeroelastic stability
    - interaction triangle, 328
  - dynamic insulation material, 972
  - dynamic light scattering (DLS), 920
  - dynamic tensile strength, 345
- e**
- e-beam evaporation, 237
  - ecosystems, 1139
  - EDF (Electricité de France), 295
    - facility, 307
    - generating technologies, 296
    - nuclear plants, 296
  - edge boundary scattering, 881
  - effective medium approximation (EMA), 242
  - EG. *see* ethylene glycol
  - eggshell membrane (ESMs), 581
  - E-glass fiber, 331
  - e-HEPA. *see* electric high-efficiency particulate arrest
  - elastic beam bending analysis, 662, 663
  - elastic modulus, 663
  - elastic strain energy, 749
  - elastomers, 325
  - electrical capacitors, 377
  - electrical charge, 918
  - electrical conductivity, 189, 487, 497, 499, 512, 514, 517, 921, 987
    - Seebeck coefficient, 877
  - electrical energy, 181, 649, 651
  - electrical generator, 871
  - electrical resistance, 872
  - electric dipoles, 91
    - moment, 84
    - resonance, 175
  - electric double layer, 379, 393, 395, 409
    - capacitance(EDLC), 379, 393, 406
    - stern model, 394
  - electric high-efficiency particulate arrest, 979
  - electricity production, 597, 649, 679
    - from fossil fuels, 297
  - electric polarizability, 87
  - electric power, 295
    - energy storage, 309
    - electrochemical, 115, 355, 377
    - energy transformation, 305
    - GEN-IV nuclear reactors, 302
    - group presentation, 295
    - heat transfer, 17, 300, 305
    - mechanical properties, 299
    - nano risk, perception, 316
    - National Nanotechnology Initiative (NNI), 317
    - quantum effects, 300
    - thermodynamical stability, 300
    - thermoelectric materials, 311
  - electroactive polymers, 386
  - electrochemical active surface areas (ECSAs), 570

- electrochemical anodization, 114
- electrochemical capacitors, 377, 393
  - electrolytes used, 398
- electrochemical CO<sub>2</sub> reduction reaction, 1115, 1116
  - half-cell reactions of cathode, 1117
  - particle size on electrode performance, 1125
- electrochemical impedance spectroscopy, 385
- electrochemical lithiation, 365
- electrochemical pressure-composition (EPC), 441
  - isotherms for absorption and desorption of hydrogen, 445
- electrochemical testing, 402
- electrochromic
  - film, 985
  - technology, 985
  - windows, 968, 985
- electrode
  - capacitive performance, optimization, 408
  - designing, 404
  - – effect of surface chemistry, 401
  - electrolyte interface, 409
  - materials, 185, 380, 401, 404
  - volumetric capacity, 359
- electrodeposition, 397
- electrokinetic potential analysis, 918
- electrolysis, 362, 629, 631
  - additives, 404
  - development, 399
- electromagnetic
  - energy, 652
  - environments, 314
  - power, 84
  - shields, 485
  - waves, 150
- electromechanical coupling factor, 659
- electromotive force, 652
- electron diffraction, 16
- electron energy loss spectroscopy, 606
- electron–hole pairs, 134, 144, 184
- electronics, 679
  - band structure, of oxides, 525
  - components, 681
  - conductivity, 356
  - devices, 649, 650, 680
  - thermal conduction, 512
- electron microscopy analysis, 16
  - of Ce- and Gd-substituted LaS-CrS<sub>2</sub> nanotubes, 774
- electron mobility, 727
- electron scattering effects, 517, 552
- electron transfer reactions, 729
- electron transport layer (ETL), 115, 174
- electrophoresis, 380
- electroplating, 499
- electrospinning/electrospraying (E/E) technique, 111, 117, 578
- electrospun graphene/TiO<sub>2</sub> composite
  - TEM image, 118
- electrostatic
  - charge storage, 377
  - devices, 652
  - energy, 650
  - interactions, 65
- elemental anode-active materials, 356
- ellipsometry, 240
  - measurements, 239
- elliptical profile
  - geometrical equation of, 666
- embedded nanoepoxy bubbles, 968
- EMIM-BF<sub>4</sub> electrolyte, 1131
- EMIM-TFSI electrolyte, 403
  - cyclic voltammograms, 406
- emission trading system, 1163
- enantioselectivity, 928
- endothermic reactions, 62, 598
  - CO<sub>2</sub> reduction reaction, 1111
- energetics of computing, 25, 697, 698
  - data-centric chip architectures, 699
  - optimization for energy reduction, 698
- energy applications, 298
- energy band alignment, 116
- energy band gap (E<sub>G</sub>), 139, 517
- energy barriers, 555
- energy conservation, 939, 969
  - building, 970
- energy consumption, 679, 1169
  - global, 459, 967
  - logic operation, 691
  - millions of instructions per second (MIPS), 25, 687, 688
  - – MOSFET, 25, 687
- energy conversion efficiency, 656
- energy density, 404
- energy diagram, photosynthesis in green plants, 609
- energy efficiency, 679, 939
  - building, 979
  - nanostructured thermoelectric materials
    - – cost-effective, development of, 555
    - thermoelectric materials, 547
    - – cost of, 556
- energy field/temperature, in ultrasonic bath and, 916
- energy for communication, 695

- energy generation, 939
  - energy geometry, 789
  - energy harvesting techniques, 651, 652, 782
  - energy needs, 857, 968
  - energy production
    - projected total energy of, 686
  - energy security, 1079
  - energy sources, alternative, 781
  - energy storage, 975
    - density, 395
    - devices
      - power and energy density metrics, 392
      - Ragone plot, 378
      - specific power vs. specific energy, 378
    - industry, 397
    - materials, classification of, 460
    - puzzle, 395
    - short- and long-term, 782
    - technologies, 386, 392
  - enhanced oil recovery (EOR), 49
  - enthalpy, 62
  - environmentally beneficial nanotechnologies, 969
  - epitaxial attachment, 859
  - epoxy resin
    - with steel, 336
  - equal channel angular extrusion (ECAE), 810
  - equilibrium methane and carbon dioxide conversion values, 63
  - equilibrium rate constant, 62, 419
  - $\text{Er}^{3+}$  concentration, 154
  - Escherichia coli*, 702, 980
  - ETA cell, 147
  - ethanol, 569
  - ethylenediaminetetraacetic acid, 599
  - ethylene glycol (EG), 404, 997, 1012, 1013, 1144
    - $\text{Al}_2\text{O}_3$  nanofluids, 999
    - Al–Zn hybrid nanofluid, 1014
    - Cu nanofluid, 999
    - graphene nanosheets, 1013
    - iron (Fe) nanofluid, 1000
  - ethylene/propylene carbonates, 1111
  - 1-ethyl-3-methylimidazolium tetrafluoroborate (EMIM- $\text{BF}_4$ ), 1129
  - ethyl-methylimidazolium tri(fluorosulfonyl) imide, 406
  - Euclidean dimensionality, 782, 783, 785
  - Eurofighters Typhoon, 824
  - European Union, 970
  - $\text{CO}_2$  emission reductions, 968
  - Europium-doped ceria, 583
  - evaporation, 142
  - exciton, binding energy of, 139
  - exfoliated graphite nanoplatelets (xGnPs), 1141
  - exfoliation adsorption, 834
  - exhaust flue gas
    - of thermal power plants, 1124
  - exothermic reactions, 928
  - expanded perlite/paraffin/graphene oxide, 465
  - external quantum efficiency measurements, 199
- f**
- fabrication methods, 212, 379
  - Fabry-Pérot interference, 173
  - face centered cubic (FCC), 522, 719
  - facultative anaerobic bacteria, 250, 254
  - Faradaic efficiency, 639, 644
    - energy storage, 383
  - fast breeder test reactor (FBTR), 272
    - steam generators, 272
  - fatigue, 719
    - crack growth, 346
    - damage, 721
    - effects, 329
    - metallic materials, 719
    - performance, 720
    - strength, 720, 721
    - tests, 720
  - faujasite, 9
  - Federal Aviation Administration (FAA), 824
  - Fe–Fe hydrogenase, 256
  - Fe impurities, 449
  - $\alpha$ -Fe metallic phase, 1142
  - FEM simulation
    - dimensions of metal shim, 666
    - flexure hinge profile, 669
    - stress, 669, 670
    - simulation of metal shim, 668
    - values, 666
  - Fenton system –  $\text{Fe}_2\text{O}_3$ – $\text{H}_2\text{O}_2$ , 1144
    - oxidation ranges, 1141
  - $\text{Fe}_2\text{O}_3$ @C nanoparticles, 1142
  - $\text{Fe}_3\text{O}_4$  crystal, 1002
  - $\text{Fe}_2\text{O}_3$  nanoparticles, 1015
  - Fermi–Dirac statistics, 516
  - Fermi energy, 395, 528, 554
    - of conduction band, 149
  - ferredoxin, 253
  - ferric oxide, 211
  - ferritic–martensitic steels, 273, 275, 276
  - ferrocene-xylene method, 382

- catalyst solution, 382
- precursor, 380
- ferrofluid, on glass, 898
  - on glass, 898
  - sensor, color pattern, 283
  - speakers, 899
- ferrous oxide, 982
- FF. *see* fill factor
- F16 Fighting Falcon fighter jet, 824
- fiberglass, 335, 971, 988
  - batts, 973
- fiber microbuckling, 329
- fiber-reinforced composites, dominate wind turbine blade, 1101
- fiber-reinforced plastic (FRP), 331, 332, 333
  - using CNTs, 333
- fiber-to-fiber bonding, 985
- fiber volume fraction (FVF), 331
- field-assisted sintering technique (FAST), 339
- filamentary rods, of nanoscaled thickness, 325
- fillers, 299
- fill factor, 125, 866
  - efficiency, 125
- filmwise condensation, 306
- filter paper, 383
- Fischer–Tropsch synthesis, 59, 597
- flame reduction process, 606
- flame-retardant additives, 369
- flat-plate collector designs, 224
- flexible element (metal shim)
  - with uniform profile, 662
  - with varying profile, 662
- flexible/on-demand 3D connection/routing, 703
- flexible piezoelectric energy harvesters, 657
- floating catalyst, 382
- flocculation, 918
- flue gas
  - capturing, 1168, 1169
  - desulfurization, 988
- fluid chemistry, 913
- fluidized bed reactor (FBR), 747
  - advanced cladding and wrapper materials, 277
  - typical nanocrystalline materials, 283
- fluid pressure, 44
- fluorescence emission wavelength, 120
- fluorescent ceiling lights, 977
- fluorine tin oxide (FTO), 104, 733
- fly ash, 983
- foaming agent, 986
- foam insulation materials, 971, 1170
- formate hydrogen lyase, 254
- formation enthalpy, 419
- formic acid oxidation reaction (FAOR), 265, 569
  - oxidation, commercial Pd/C, 570
- formylmethanofuran dehydrogenases, 257, 259
- Forouhi–Bloomer formulation, 238
- fossil fuels, 249, 629, 871, 1161
  - burning, 1109
- fourfold absorption enhancement, 173
- fractal dimensionality, 782, 785, 787
- fractal process zone (FPZ), 342
- fractals, 784, 788
  - overview, 782
- fracture
  - fluids, 46
  - tests, 984
  - toughness, 331
- free energy, 774
- freezing transition, 1017
- French Alternative Energies and Atomic Energy Commission (CEA), 304
- Fresnel coefficients, 238
- Fresnel reflection, 869
- friction mechanisms of multilayered IF NP, 762
- friction reduction, 44
- front contact, 183
- frozen smoke, 970
- FTO. *see* fluorine-doped tin oxide
- fuel cells, 309, 1057
  - assignee activity across
    - components, 31, 1071, 1073
    - catalyst support/active materials, 1071
    - classification of, 1064
    - type of electrolyte, 1064
    - types of fuel and oxidant, 1064
  - commercial products, 31, 1075
  - distribution of
    - applications, 1070
    - patents, 1061, 1063, 1065, 1067, 1069, 1071–1073
  - future perspectives, 1077
  - nanotechnology-based products, 1076
  - nonexhaustive schematic, 736
  - operating on organic molecules, 569
  - geographical distribution of, 31, 1067
  - organization-wise distribution of, applications, 1069
  - proton exchange membrane, 1067
  - publication trend, 31, 1058–1062, 1063, 1065, 1066, 1068, 1069
  - research activities
    - catalyst active materials, 1074

- MWCNT application in, 1058
  - research publications of top 10 countries, 1059
  - technology, 569
  - types vs catalysts-active materials, 1073
  - fuel cycle facilities
    - fast breeder reactors, 272
  - fullerenes, 125, 378, 603, 774
    - nanostructures, 745
    - nanotubular structures
      - from misfit layered compounds, 764
  - functional elements of a solar cell, 182
  - functionalized grapheme sheet (FGS), 1012
  - functionalized HEG (f-HEG), 1014
  - functional oxides, 30
  - fungicides, 985
  - futuristic buildings, 990
- g**
- GaAs/GaInP<sub>2</sub> photocathode, 643
  - GaAs
    - photocathode, 643
    - quantum wells, 555
    - solar cells, 171
  - gadolinia-doped ceria (GDC), 582
  - gallium-based liquid metal, 889
    - melting-point, 889
  - gallium-based magnetic nanofluid
    - properties of, 900
  - gallium-based thermal interface material
    - thermal conductivity of, 893
  - gallium fluids
    - boiling point, 899
  - gallium–indium droplets, 900
  - gallium oxide, 891
  - gallophosphates, 3
  - Garnet-type oxides, 427
  - GaSb nanoinclusion in (GaSb) Yb<sub>3</sub>Co<sub>4</sub>Sb<sub>12</sub> nanocomposite, 530
  - gas chromatograph, 75
  - gas-cooled fast reactor (GFR), 276
  - gaseous energy extraction
    - via biomethanation process, 256
  - gas-fired plants, 1168
  - gasification, 69
  - gasoline energy, 509
  - gas-phase method, 214
  - gas precursor disilane, 862
  - gas precursor dissociation rate, 859
  - gas ratio, 644
  - gas separations, 1171
    - gate-opening process, 1171
  - gas-to-liquid (GTL) 59, 79
    - catalysts, 65
    - process, 60, 79
    - technologies, 60
  - gas turbine, 231
  - gate length
    - vs. switching energy for MOSFET, 693
  - G-band, 76
  - GDC-KAlZn composite, 583
  - GdS-CrS<sub>2</sub>
    - orthorhombic crystals of, 771
  - Ge coating, 212
  - gel drying processes, for silica aerogel, 946
  - generic electron-charge-based memory element, 695
  - generic fuel cell design, 736
  - genetic algorithm, operating principle of
    - used to optimize a n-ary lattice, 95
  - GEN-III PWR reactors, 302
  - GEN-IV reactors, 271, 302
  - geometrically necessary dislocation (GND), 814
  - geometrical optics approaches, 869
  - geometrical resonances, 163
  - geothermal energy, 377
  - germanium, 22, 524, 859
    - quantum dots, 859
  - giant IF-MoS<sub>2</sub> “bubbles”, 753
  - Gibbs energy, 599, 631, 1115
    - free energy, 15, 61, 62, 419, 1114
  - glass, 985
    - like disordered grain boundaries, 436
    - microspheres, 986
  - glassy carbon electrode (GCE), 1131
  - global warming, 509, 629, 1161
  - glucose, 253
  - gold (Au) NPs
    - catalyzed VLS, 859
    - diffusion coefficient, 861
    - nanodroplets, 859
    - nanoparticles, 150, 498
    - coated with palladium, 980
    - reduce CO<sub>2</sub> to CO, 1127
  - gold
    - Au oxide film, 1128
    - mesh electrode, 149
    - silicon phase diagram, 859, 860
  - GO/S<sub>2</sub> composite counterelectrode, 734
  - grain boundaries, 340, 552
  - graphene, 115, 126, 378, 395, 572, 727, 776, 850, 921, 922, 942, 972, 1098, 1101
    - aerogel, insulating properties, 972
    - based DSSC, 734
    - based supercapacitors, 730

- fabrication, 729
  - batteries, applications, 732
  - derived materials, 727
  - electrodes in PVCs, 733
  - electronic properties, 397
  - in fuel cells, 738
  - for hydrogen splitting of electrolytes, 740
  - lithium titanate, 1049
  - metal oxide composite materials, 1043
  - for MOR
    - electrochemical performance, 575
  - MWCNT composites (FLG/MWCNT), 573
  - MWCNT hybrid nanofluids, 1014
  - nanoparticles, 924
  - nanoplatelets coatings on wind blades, 1100
  - for ORR
    - electrochemical performance, 576
    - properties, 726, 728
    - in solar technologies, 735
    - in supercapacitors, 730
    - symmetric capacitors, 729
  - graphene nanoribbon (GNR), 573, 1012
  - graphene nanosheet (GNS), 1012
  - graphene/Ni<sub>12</sub>P<sub>5</sub> composite
    - electron transport mechanism, 127
    - SEM image, 127
  - graphene oxide (GO), 603, 929, 1012
    - batteries, 730
    - electrolyzers, 738
    - electronic properties, 727
    - in energy generation devices, 734
    - in energy storage devices, 725, 727
    - fuel cells, 735
    - sheets, 466
    - solar energy, 733
    - supercapacitors, 728
  - graphene quantum dot (GQD), 573
    - GQD-GNR hybrid, HRTEM images, 574
  - graphene sheet (GS), 469
  - graphite, 833
    - bulk material, 378
    - microbeads, 367
    - nanofiber, 464
  - graphitic carbon, 71, 74
    - helical microtubules of 485
  - graphitic carbon nitride, 620
  - gravitational forces, 324
  - green algae, 598
  - green building, 967, 968
    - nanotechnology, role of, 967
  - greenhouse gases, 60, 249, 1081
  - green hydrogen, 738
  - green tensor, 94
  - grid-connected PV–electrolysis, 632
  - Griffith's criterion, 341
  - groundwater
    - contamination of, 1139
  - gypsum, 988
- h**
- half Heusler alloys, 519, 526, 536
    - negative Seebeck effect, 526
    - of NiSn, CoSb, and PdBi groups with substitutions, merits of, 527
  - halloysite (HNT), 475
  - Hall–Petch equation, 339, 340
  - Halobacterium salinarum*, 609
  - H<sub>2</sub>/O<sub>2</sub> evolutions, of Z-schematic water-splitting system, 636
  - H<sub>2</sub>/O<sub>2</sub> generation, 637
  - hard-chromizing processes, 984
  - hardened ferritic steel, 435
  - hardness values, 718
  - harvested energy, 650
  - Hausdorff dimension, 783, 786, 789
    - fractal dimension, 784, 785
  - hazardous cleansers, 979
  - health-monitoring devices, 651
  - hearing aids, 650, 656
  - heat absorbing films, 971, 972
  - heat capacity, 514, 921, 922, 930
  - heat conversion efficiency, 234
  - heat engines, 871
  - heat exchangers, 511
  - heat gain, 985
  - heat leakages, 519
  - heat management, 939
  - heat storage, 459, 912
    - capability, 461
  - heat-to-electricity conversion, 871
  - heat transfer coefficient (U-value), 307, 912, 929, 956
    - experimental measurements, 308
  - heat transport mechanism, 301, 911
    - in different forms of aerogel, schematic of, 952
  - heat-treatable titanium alloys, 332
  - heliothermal efficiency, 234
  - Helmholtz layer, 395
    - capacitance, 394
    - double-layer model, 394
  - hematite particles, 365
  - Henry's constant, 1121, 1123
    - for CO<sub>2</sub> in water, 1118
  - heteroatom-doped graphenes, 573
  - heterocoagulation, 44

- heterogeneous catalysis, 3, 928
- heterojunction, 635
  - with intrinsic layer (HIT), 165
- heteropoly acid, 608
- hexadecane (HD), 1004
  - thermal conductivity with temperature, 1005
- hexadecyltrimethoxysilane, 8
- hexafluorophosphate (PF<sub>6</sub>), 400
- hexagonal cell, 879
- hexagonal TiO<sub>2</sub>, TEM, 113
- 1,2,3-hexanetriol, 13, 14
- HF. *see* hydrofluoric acid
- high-Cr corrosion/oxidation-resistant nanodispersion-strengthened NFAs, 278
- high-energy ball milling (HEBM), 435, 438, 439
- high-energy photons
  - thermalization of, 152
- high-index semiconductors, 164
- high-melting-point refractory metals, 235
- high-performance building materials, 981
- high-performance thermoelectrics, 547
- high-pressure carbon monoxide (HiPco), 489
- high-resolution transmitting electron microscopy (HRTEM), 633
  - optimized phase contrast conditions, 772
- high specific capacitance, 396
- high-temperature and high-pressure (HTHP), 43
- high-temperature fuel cell (HTFC), 569
- high-temperature solar receivers, 236
- HIPing, 339, 846
- H<sub>2</sub>O, C ratio, 67
- hole transport layer (HTL), 174
- hollow carbon nitride sphere
  - photochemical reaction, 623
  - surface morphology of, 622
- hollow mesoporous zirconia nanospheres (hm-ZrO<sub>2</sub>), 287
- hollow multiwall WS<sub>2</sub> nanotube, 747
- HOMO. *see* highest-occupied molecular orbital
- homocoagulation, 44
- homoepitaxy, 859
- Honda–Fujishima effect, 598
- hot carrier cell
  - in conventional semiconductor
  - – relaxation process, 154
  - energy band diagram, 156
- hot electron–hole gas, 155
- HSS, strength–formability relationship, 335
- human resonant motion, 655
- human vibration energy harvester with PZT, 655
- hybrid dye solar cells, 146
- hybrid electric vehicle, 1033
- hybrid nanocomposite (HyNPCM), 474
- hybrid nanofluids, 1013
- hybrid organic/inorganic thermoelectric materials, 313
- hydrides
  - derivatives of, 20, 425
  - thermodynamic properties and hydrogen content for, 419
  - types of, 425
- hydrocarbons, 3, 20, 28, 922
  - fuels, 569
  - reservoirs, 47
- hydrocracking, 3
- hydro energy, 296
- hydrofluoric acid, 863
- hydrogen (H<sub>2</sub>), 59, 415, 751, 752
  - absorption, in palladium metal, 418
  - adsorption of, 417
  - boiling point, 415
  - bond dissociation enthalpies, 417
  - CO ratio, 59
  - desorption, PC isotherms, 452
  - energy, 597
  - – density in, liquid state, 416
  - evolution
  - – over Pt/In<sub>2</sub>S<sub>3</sub>/CdS/CZTS cathode, 641
  - – performance of semiconductor HJ photocatalysts, 638
  - feedstock to recycle carbon dioxide, 597
  - generation
  - – solar water splitting by PV–electrolysis (PEC), 645
  - gravimetric energy density for, 415
  - as ideal gas, 416
  - limit for solubility, 418
  - metallic hydrides, 418
  - nanoconfinement, 20, 423
  - physical properties, 415
  - physisorption of, 417
  - production
  - – biological process, 249
  - – rate, 637
  - – by renewable energy, 416
  - storage in, solid state, 416
  - stronger bonds, 20, 418
  - volumetric energy density, 415
  - weaker bonds, 20, 417
  - wind energy, storage of, 416
  - as a zero emission fuel, 597
- hydrogenase system, 261
- hydrogenation, 64, 610, 630, 635

- hydrogen evolution reaction (HER), 600, 1113
    - from aqueous solution, 619
  - hydrogen exfoliated graphene (HEG), 1014
  - hydrogen–hydrogen bonds, 416
  - hydrogenotrophic methanogens, biomethane production using CO<sub>2</sub> and H<sub>2</sub> by, 257
  - hydrogen oxidation reaction (HOR), 572
  - hydrogen-powered vehicles, 597
  - hydrogen production rate, 255, 262, 598
    - through biological routes, 265
  - hydrogen storage, 433
    - high-energy ball milling, 438
    - hydride properties, 439
    - materials, 439, 440
    - mechanical alloying, 434, 436
    - mechanochemical activation synthesis (MCAS), 439
    - milling processes, 435
    - nanomaterials, 434
    - nanotechnology, 433
    - top-down approach, 434
  - hydrogen sulfide (H<sub>2</sub>S), 48, 747
  - hydrogen-transfer reactions, 26
  - hydrolysis, 256
  - hydrophilic surfaces, 309
  - hydrophobic
    - character, 305
    - coatings, 308
    - compound, 48
    - foams, 1152
    - with quaternary amines, 1140
    - – *p*-hydroxybenzaldehyde, 929
    - surfaces, 305, 914
  - hydroxyl free radical, 265
  - hypersonic shock tunnel, 755
  - hypothetical capacitor plates, 379
  - hysteresis loop, 900
- i*
- ICT energy consumption, 681
  - IF-MoS<sub>2</sub> nanoparticles, 752
  - imidazolium, 923
  - immobilization, 928
  - impedance, 407
  - incandescent lights, 977
  - incident flux, 94
  - incident light radiation, 151
  - indium-doped tin oxide, 104
  - indium tin oxide (ITO), 149, 167, 733
  - indoor air quality, 978
    - nanotechnology, role of, 979
  - inductively coupled plasma mass spectrometry (ICP-MS), 758
  - industrial marine tidal turbine, 297
  - industrial solvents, 980
  - infiltration process, 311
  - informational display panels, 978
  - information/communication technology, 680, 681
  - information processing, elements of, 681
    - basic computing system, 25, 682
    - bits, realization of binary elements, 681
    - millions of instructions per second (MIPS), 682
    - performance metrics for computing systems, 682
  - infrared
    - absorbing coatings, 972
    - radiation, 208
  - infrared reflective (IRR) metallic layer, 234, 235
  - inhibitor-loaded nanocontainer-based coatings, 289
  - inorganic nanotube (INT), 745
    - and fullerene-like nanoparticles
    - – applications, 758
    - – nanocomposites, 762
    - – synthesis and structural characterization, 746
    - – tribological properties, 758
  - inorganic pigment-based coatings, 211
  - inorganic semiconductors, 193
  - Institute for Nanoscale Technology, 979
  - insulations, 940, 969, 970
    - applications, in energy conservation/storage, 940
    - coatings, 971
    - material, 940, 970
    - nanoparticles, 971
    - technologies, 972
  - intercalation, 393
  - interdigitated back contact (IBC), 165
  - interfacial corrosion reactions, 225, 226
  - Intergovernmental Panel on Climate Change (IPCC), 1109
  - intermatrix synthesis, 834
  - intermediate reflectors, 198
  - intermetallics-based hydrides
    - LaNi<sub>5</sub>-type materials, 447
    - Mg<sub>2</sub>Ni alloy, 450
    - with nanostructure, 440
    - TiFe-type system, 440
    - ZrV<sub>2</sub>-type system, 444
  - intermolecular-ionic interaction, 914
  - internal quantum efficiency IQE of
    - solar cells, 191



- International Energy Agency (IEA), 1109  
 International Patent Classification (IPC), 1061  
 interstitial metal hydrides, 418  
 inverse opal carbon, 126  
 inverse silica photonic crystals  
 – FESEM image, 109  
 $\text{In}_x\text{Ce}_y\text{Co}_4\text{Sb}_{12}$  composite, 530  
 IoBiofluids, 912  
 iodine, 747, 754, 765  
 – doped graphenes, 573  
 ion adsorption/desorption, 397  
 IoNanofluid (INF), 28, 911, 912, 914, 915, 916, 918, 919, 921, 922, 929  
 – applications of, 926  
 – challenges to industrial applications, 931  
 – dependence on temperature and, 922  
 – as nano-driven catalysts, 928  
 – Newtonian zone of, 926  
 – preparation, 921  
 – properties, 920  
 – research, challenges in, 930  
 – for solar energy applications, 929  
 – stability, 923, 928  
 – surfactant-free, 921  
 – thermal conductivity enhancement, 922  
 ion diffusion, rate of, 356  
 ion dynamics, 401, 402  
 ion electrosorption, 402  
 ion-exchange resin, 1169  
 ionic hydrides, 420  
 – coordination number, 420  
 – properties of, 420  
 ionic impedance, 403  
 ionic liquids (ILs), 911, 915, 918, 919, 922, 924, 928, 929, 930  
 – advantages, 405  
 – approach to molecular structure of, 924  
 – constant, 401  
 – electrolytes, 397  
 – mixtures, 405, 406  
 ionic percolation, 301  
 ionophilic pores, 402  
 ionophobic pores, 402  
 ion sieving, 402  
 ions size, role of, 395  
 ion storage film, 985  
 IPCE measurement, 112, 114  
 IQE curves, 191  
 iron hydroxide nanoparticles, 45  
 iron nanoparticles oxidize  
 – in water, 1141  
 iron oxide particles, 44  
 iron phthalocyanine/NG, 573  
 iron sulfate complex, nZVI particle, 1143  
 irradiation damage, 303  
 – resistance, 274, 303, 304  
 isomerization, 3  
 isothermal transformation, 713, 718  
 ITO. *see* indium-doped tin oxide
- j**  
 jelly-roll type supercapacitors, 384  
 Jobin Yvon ellipsometer, 239  
 J–V characteristics, 112
- k**  
 Kerker scattering, 174, 175  
 kerosene, 997  
 –  $\text{Fe}_3\text{O}_4$  nanofluids, 1004, 1005, 1009, 1010, 1011  
 – – magnetic field strength, 1010  
 – magnetite nanofluids, 1010  
 – thermal conductivity, 1005  
 kinetically stable dispersions, 917  
 kinetic energy, 650  
 Kirchhoff's law of radiation, 232  
 Knudsen cell, 859  
 Koch snowflake, 783  
 Kolbe–Schmitt reaction, 1111  
 K\_Pt95Ru5 particles, SEM images, 571  
 Kretschmann coupler, 149  
 krypton, 970
- l**  
 Lagrangian multiplier method, 61  
 Lambertian limit, 870  
 lamellar zeolites, 9  
 $\text{LaNiO}_3$  perovskite, 70  
 $\text{La}_2\text{NiO}_{4+6}$  polyhedra, 70  
 La/Ni powders  
 – XRD spectra of, 448  
 $\text{LaNi}_5$ -type negative electrodes, 448  
 lanthanides, 772  
 – -based misfit nanotubes, 767  
 lanthanum gallate (LSGM), 580  
 lanthanum oxide ( $\text{La}_2\text{O}_3$ ), 68  
 LaS– $\text{CrS}_2$  nanoscroll, 769, 771  
 – HRTEM image of, 770  
 –  $\text{CeS-CrS}_2/\text{GdS-CrS}_2/\text{TbS-CrS}_2$  nanoscrolls/nanotubes  
 – – SEM images of, 769  
 laser sintering, 871  
 $\text{La}_{0.75}\text{Sr}_{0.25}\text{Cr}_{0.5}\text{Mn}_{0.5}\text{O}_{3-d}$  (LSCM), 585  
 lattice strain energy, 860  
 layered thermoelectric structures

- p-type  $K_{0.5}CoO_2$  and  $Sr_2TiO_4$ , 525
- lead–acid batteries, 976
- lead-based materials, 22, 522
- Leadership in Energy and Environmental Design Council, 967
- lead selenide quantum dots, 974
- LED. *see* light-emitting diode
- Lenz's law, 652
- Lewis acid–base interactions, 363
- $LiBH_4$ , endothermic desorption, 422
- $LiFePO_4$  nanoparticles
  - carbon-coating of, 361
  - development of, 362
  - electrochemical signature, 362
  - electronic conductivity of, 361
- light absorption
  - beyond dipolar approximation, 91
  - binary Au–Ag lattice, 96
  - collection of particles, 86
  - layers, 134
  - by single particle, 84
- light-emitting
  - diode, potential energy savings, 977
  - technology, 978
- light gauge steel framing, 984
- light harvesting
  - efficiency, 109
  - vesicular pigments, 260
- lightning strikes, 325
- light resonances, 867
- light-to-heat conversion/storage
  - schematic of, 472
- light-trapping device, 869
- lightweight high-strength metal matrix nanocomposites, 838
  - aerospace applications, 843
  - dispersion of nanoparticles, 841
  - manufacturing, 838
  - metallic foam-based lightweight structure, 844
  - MMNCs
    - in automobile sector, 843
    - mechanical property of, 842
    - thermal stability of nanoparticles, 841
    - wettability, 841
- lignins, 386
- lignocellulosic biomass, 264
- lignocellulosic fibrils, 985
- $Li^+$  ions
  - batteries costs, 386
  - schematic representation of, 364
- $Li/MgH_2$  cell
  - voltage profile of, 366
- limit cycle oscillations, 328
- $LiMn_2O_4$ , 364
- Li-molybdate battery, 1038
- linear oscillator, 659
- linear proportionality, 925
- liquid-based electrostatic energy harvester, 653
- liquid catalyst, reservoir effect, 862
- liquid crystal display technology, 989
- liquid-gallium suspensions
  - thermal conductivity enhancement ratio, 895
- liquid gold/silicon alloy, 859
- liquid hydrocarbons, 59
- liquid metal-based MF
  - electrical resistivity of, 897
  - modification procedure for preparation of, 892
  - thermal and electrical conductivity of, 889
- liquid metal droplets, 901
- liquid metal gallium
  - substitute of mercury, 899
  - thermal conductivity, 899
  - wettability and compatibility of, 899
- liquid metal poly (LMP) grease, 895
  - electrical resistivity of, 897
  - fabrication process, schematic diagram 896
  - thermal greases thermal conductivities of, 897
- liquid metals
  - as thermal interface materials, 894
- liquid-phase processing, 811
- liquid sodium metal, 282
- liquid solar collecting coating, 974
- liquid/solid surface energy, 860
- liquid-vapor interface meets, 305
- Li recycling, 386
- Li-sulfur battery, 1038
- lithiation, 356
- lithium-alloying elements, 357
- lithium borohydride–magnesium hydride, 422
- lithium cobalt oxide (LCO) battery, 1038
  - uses in, 1038
- lithium dendrites, 368
- lithium hydrides, 420
- lithium ion batteries, 30, 309, 355, 501, 975, 1031
  - advantages of, nanostructured materials, 1034
  - annual growth of, patents, 1036
  - application of, nanomaterials in, 31, 1040, 1041
  - assignees *vs.* publication year, 1046

- carbon nanotubes, 1042
  - charging process, 1031
  - classification of, 31, 1033, 1038
  - country-wise distribution of, 1037
  - discharging process, 1032
  - 3D representation of patents, 1048
  - electrodes of, 1032
  - energy density of, 1032
  - future perspectives, 1051
  - graphene, 1043
  - iron oxides, 1044
  - lithium iron phosphate (LiFePO<sub>4</sub>), 1044
  - market for, 1051
  - nano-enabled Li-ion batteries, 1050
  - nanosilicon, 1044
  - patents distribution, 1042
    - application sector, 1045, 1046
    - pie chart, 1037
    - publication trends, 1046, 1047
    - segregation, 1039, 1041, 1049
    - top assignees, 1040
  - performance parameters, 1033
  - power density, 1034
  - pulverization of electrodes, 1034
  - rate capability, 356, 1034
  - reactions during, charging-discharging process, 1032
  - safety, 367, 368
  - sulfur-based cathodes, 732
  - technological aspects of nanostructured materials for, 355, 975
  - types and application areas of, 1033
  - lithium-ion conducting ceramic, nanofibrer mat, 310
  - lithium-ion diffusion, 362
    - coefficient of, 356
  - lithium iron phosphate (LiFePO<sub>4</sub>) battery, 309, 1038
    - applications in, electric vehicles, 1038
    - power storage capability, 1038
  - lithium manganese oxide (LMO) battery, 1038, 1050
    - applications in, 1038
  - lithium metal–electrolyte, 364
  - lithium nickel manganese cobalt oxide (NMC) battery, 1038
    - applications in, 1038
    - energy densities, 1038
  - lithium titanate (LTO) battery, 1038, 1050
    - advantages of, 1038
  - lithium titanate oxide materials, 975
  - lithography, 120, 914
  - LnS-CrS<sub>2</sub> nanotube, 771
    - growth model of, 773
  - load-bearing structural material, 980
  - local type certification committee (LTCC), 345
  - Lorentz number, 514, 547, 881
  - Lotus effect, 289
  - low and high metal volume fraction (LMVF/HMVF), 235
  - low-density polyethylene (LDPE), 1132
  - low-melting point metals, 902
    - thermophysical properties of, 904
  - low-refractive-index materials, 164
  - low-temperature fuel cell (LTFC), 569
  - low-temperature solid oxide fuel cell (LTSOFC), 580
  - LSCM/LSGMg/LSCM configuration, 585
  - lubrication mechanism, of nanoparticles, 44
  - LUMO. *see* lowest-unoccupied molecular orbital
  - lung inflammation, 991
- m**
- MACE. *see* metal-assisted chemical etching
  - macro- to nanoscale, 911
  - magnesium alloys, 450, 809, 824
    - automobile components, 810
    - metal matrix, 811
    - nanocomposites for cleaner transport, 809
  - magnesium-based nanocomposites
    - challenges, 825
    - corrosion properties, 820
    - creep properties, 818
    - dynamic mechanical properties, 818
    - engineering properties, 822
    - fabrication of, 811
    - fatigue properties, 820
    - machinability, 823
    - potential applications in transport industries, 824
    - tensile/compressive properties, 814
    - wear, 822
  - magnesium boride, 422
  - magnesium borohydride, 426
  - magnesium hydrides, 420
  - magnesium nanocomposites, 820, 825
  - magnetic carbon nanotubes
    - physical properties of, 1146
  - magnetic dipole resonance, 175
  - magnetic flux leakage (MFL), 282
  - magnetic force, 915
  - magnetic impurities, 1146
  - magnetic nanofluids, 1009

- magnetic nanoliquid metal fluid
  - fabrication of, 899
- magnetite-coated rosin amidoxime, 1145
- magnetization–temperature curve, 900
- magnetodielectric resonator networks, 83
- magnetorheological fluid
  - magnetization of, 899
- Mahan–Sofa theory, 554
- manganese oxide, 929
- marine renewable energy, 295
- mass activity (MA), 570
  - nanocrystalline Mg<sub>2</sub>Ni alloy, 452
  - for synthesizing nanometer-sized powders
    - – schematic cross-sectional representation, 437
- mass spectrometer, 75
- match-like ZnO/Au heterostructure, synthesis of, 616
- material design, nanotechnology, role of, 967
- materials, 980
  - toxicity, 968
- matrix modification, using micro-or nanostructured fillers, 1100
- maximum power factor
  - vs. cross-sectional area, 877
- maximum ZT over time, 873
- MAX phase precursors, 398
- Maxwell limit, 1000
- Maxwell's equation, 92
  - using finite element method, 96
- Maxwell supercapacitors, 386
- 2-MBT-loaded TiO<sub>2</sub> nanocontainer-impregnated epoxy coatings, 289
- MCM-22 cage, 11
- MCNTs
  - transmission electron micrograph, 1146
  - wrapped oil droplets, 1147
- mean free path, 881
- mechanical alloying (MA), 435
- mechanical stability, 715, 717
- mechanochemical activation synthesis (MCAS), 435
- mechanochemical processing (MCP), 435
- mechanochemical synthesis (MCS), 435, 439
- medical devices, 510
- MEG. *see* multiple exciton generation
- melamine, 620
- melanin, 930
- melting temperature, 42, 466
- melt intercalation, 834
- melt spinning (MS), 314
- membrane-bound photosynthetic components, 261
- membrane diffusion, 1167
- Menger sponge, 783
- MeOH conversion, 24
- mercury, 978
- mesophilic temperatures, 250
- mesoporosity
  - in single zeolite crystal, 7
  - as variable parameter, 24
- mesoporous
  - carbon, 125
  - nanocomposite, 361
  - Pt nanorods, 571
  - silica, 1173
  - system, 11
  - TiO<sub>2</sub> beads
    - – SEM images, 107
- meso-tetra(4-carboxyphenyl) porphine (TCPP), 534
- metal–anion bond, 231, 365
- metal-assisted chemical etching method, 858, 863, 864, 871
- metal borides, 15, 212
- metal borohydrides, 423
  - perovskites, 20, 426
  - stability of, 425
- metal cathodic systems in acetonitrile (MeCN) electrolyte, 1129
- metal/ceramic composites or cermets, 235
- metal chalcogenides, 747, 765
- metal charge transfer, 774
- metal crystallites, 75
- metal 3d dopants, 602
- metal diffusion, 238
- metal halides, 423, 747
- metal hydrides
  - as ion conductors in batteries, 20, 426
- metal hydroxides, 747
- metal ions, 65, 259
- metallic bonding
  - thermodynamic properties/hydrogen content for, 419
- metallic conductors, 487
- metallic hydride, 418
  - crystallization and growth of, 418
- metallic nanoparticle welding of CNTs, 498
- metallic nanostructures, 163
- metallic solar receivers, 232
- metal loadings, 67
- metal matrix composite (MMC), 831, 1098
- metal matrix nanocomposite (MMNC), 832, 842
- metal nanocatalysts, 928
- metal nanoparticles, 30, 928

- metal organic chemical vapor deposition, 117
  - TiO<sub>2</sub> on PECVD grown carbon nanofiber, 119
- metal-organic frameworks (MOF), 33, 434, 1170
  - using zinc nitrate, 1170
- metal-oxide semiconductor field effect transistor (MOSFET), 688
- metal oxides/semiconductor nanocrystals, 105, 185, 211, 423, 747, 913
  - conduction band position, 104
  - fibers, 111
- metals, 234
- with low melting point, 905
  - PCM category, 905
  - phosphates, 747
  - properties of, 420
  - shim surface, 662, 669
- metal shim
  - elliptical cut profile, simulated stress distribution, 667
  - parabolic cut profile, simulated stress distribution, 668
  - rectangular shape, simulated stress distribution of, 665
  - tapered cut profile, simulated stress distribution, 670
  - trapezoidal shape, simulated stress distribution of, 665
  - triangular shape, simulated stress distribution of, 665
- metal silicides, 212
- metal sulfides, 635
- metal-sulfur chemical bond, 746
- methanation, 256
- methane, 59
  - conversion, 63
  - decomposition, 64, 76
  - dry reforming, 61, 63
  - – feasible reactions during, 62
  - generation, during activated sludge anaerobic digestion, 256
  - production by hydrogenotrophic methanogens, mechanism of, 258
  - reforming systems, 61
- Methanobacterium thermoautotrophicum*, 259
- Methanobacterium wolfei*, 260
- methanofuran, 257
- methanogenic bacteria, 257
- methanol (MOR), 265, 569, 600, 1110
  - Al<sub>2</sub>O<sub>3</sub>, 999
  - conversion variation, with time-on-stream, 23
- Methanobolus tindarius*, 257
- methanol oxidation
  - polycrystalline electrode, 286
- methanol synthesis, 597
- methanol-to-aromatic reactions, 18
- methanol-to-gasoline process, 18, 23
- methanol to hydrocarbons reaction (MTH), 4, 27, 29
  - using a series of ZSM-5 catalyst samples, 28
- methanol-to-olefins/propene (MTO)
  - conversion, 23, 26
  - product selectivity, 26
- Methanosphaera stadtmaniae*, 257
- methylbenzenes, 20
- methyl free radical, 265
- methylotrophs, 250
- methyl silicone oil, 895
- MFI nanosheets, 27
- MFI unilamellar structure, 12
- MFP. *see* mean free path
- Mg alloys, 810, 818, 825, 831
  - development of, 811
  - mechanical properties enhancement, 810
- Mg<sub>2</sub>Cu intermetallic phase, 816
- Mg<sub>1.5</sub>Mn<sub>0.5</sub>Ni/LaNi<sub>3.75</sub>Mn<sub>0.75</sub>Al<sub>0.25</sub>Co<sub>0.25</sub>
  - discharge capacities, 455
  - XRD spectra, 453, 454
- Mg<sub>1.5</sub>Mn<sub>0.5</sub>Ni/TiFe<sub>0.25</sub>Ni<sub>0.75</sub> hydride nanocomposites, 454
- Mg<sub>1.5</sub>Mn<sub>0.5</sub>Ni/25% Zr<sub>0.35</sub>Ti<sub>0.65</sub>V<sub>0.85</sub>Cr<sub>0.26</sub>Ni<sub>1.30</sub>, 453
- Mg nanocomposites, 822
  - compressive properties, 816
  - creep rates of, 820
  - dynamic mechanical properties, 819
  - fabrication methods, overview of, 812
  - by micromilling method, 823
  - synthesis technologies, 813
  - tensile properties, 815
  - tension-compression yield asymmetry, 817
  - wear characteristics of, 823
- Mg<sub>2</sub>Ni alloy, 451
- Mg<sub>2</sub>Ni electrode, 451, 454
- Mg<sub>2</sub>Ni transforms, 451
- MgO nanoparticles, 46
- Mg/ZnO nanocomposites, 818
- Mg-Zn-Y alloy, 810
- microbial electrolytic cell (MEC), 739
- microbial electrosynthesis (MES), 1133
- microbial fuel cell, 1133
- microbial H<sub>2</sub> production, 250

- microcomputed tomography (micro-CT) scan
  - reconstructed three-dimensional, 471
- microcrystalline  $\text{Mg}_2\text{Cu}$ ,  $(\text{Mg}_{1-x}\text{M}_x)_2\text{Ni}$  alloys, 450
- microcrystalline  $\text{Mg}_2\text{Ni}$  alloy, 451
- microcrystalline powders, 337
- microcrystalline Si ( $\mu\text{-Si}$ ), 181
- microcrystalline
  - $\text{Zr}_{0.35}\text{Ti}_{0.65}\text{V}_{0.85}\text{Cr}_{0.26}\text{Ni}_{1.30}$ , 453
  - for hydrogen absorption and desorption, 445
  - pressure composition isotherm, 446
- micro-CT scan slice of UGF-wax composite, 471
- micro-electromechanical-systems (MEMS), 991
  - cantilever piezoelectric power generator, 659
  - EM harvester, 652
  - technologies, 656
- microencapsulated healing agent, 983
- microencapsulated phase change material particles (MEPCM) suspension, 1014
- micro energy harvesting technologies, 649
  - hierarchy of, 650
- microfluids, 997
- micro/MEMS technologies, 652
  - miniaturization, 657
- micromorph silicon tandem solar cell, 198
- microporous aluminosilicate materials, 1170
- microporous carbons, 400
- microporous metal–organic frameworks, 1170
- microprocessor unit
  - 1994–2014 MPU summary, 684
- microscale, 785
  - energy harvesting systems, 649
- microsizes, 785
- Microsoft Excel<sup>TM</sup>, 62
- microstructure
  - characterization of phase change composites, 463
  - in hydrogenated microcrystalline silicon, 192
  - and properties, 712
- microwave, 747
  - absorbing wind power blade coating, patent application, 1094
  - assisted rapid sintering-based powder metallurgy, 811
  - assisted rapid synthesis, 752
  - irradiation method, 753
- Mie coatings, 172
- Mie scattering theory, 85, 941, 942
- Miller indices, 771
- misfit compounds, 774
- misfit fullerene-like particles, 774
- misfit layered compound (MLC), 764
  - nanotubes, 768, 771
- misfit nanotubes with O-T-O-T-T, 767
- mixed-oxide-coated titanium anode (MOCTA), 286
  - electrodes, 286
- MMFX steel, 984
- mobile devices, 510, 656
- MOCVD. *see* metal organic chemical vapor deposition
- model-driven synthesis, 409
- modified montmorillonite (MMT) zeolite, 577
- modifier/template effect on morphology, 15
- module glass, 177
- molecular drafting
  - process, 117
  - schematic, 118
- molecular dynamic simulations, 14, 402, 409, 1017
- molten carbonate fuel cell, 1058
- molten salt method, 107
- molten salt reactor (MSR), 271
- molybdenum-containing formylmethanofuran dehydrogenases, 259
- molybdenum disulfide ( $\text{MoS}_2$ ), 1132
- molybdenum suboxide, 755
- molybdopterin guanine dinucleotide, oxidized form, 259
- monocrystalline ZnO porous matrices, 146
- monoethanolamine (MEA), 1167
- monolithic devices, 630
- monolithic nanowires, 862
- monolithic PV–PEC configuration, 643
- monolithic solar-driven water-splitting system, 643
- Moorella thermoacetica, 1133
- Moore's law, 679
- $\text{MoO}_{3-x}$  nanowhiskers, 755
- MOR (magnetite–oil ratio), 1144
  - magnetite nanoparticles, efficiency of, 1145
- morse-type potential, 879
- mortars, 983
- $\text{MoS}_2$  closed nanoparticles
  - in nanooctahedral core undergoes morphology change, 752
- $\text{MoS}_2$  cocatalyst, 634
- $\text{MoS}_2$ /graphene composite, 731, 740
- $\text{MoS}_2$  INTs growth in solar ablation, 755
- $\text{MoS}_2$  lattice, 755

- MoS<sub>2</sub> nanooctahedron
- atomic resolution image of, 751
  - phase-contrast TEM, atomic resolution image of, 750
- MoS<sub>2</sub> nanotubes, 748, 754, 755, 757
- calculated energy per atom for, 749
  - formation mechanism, schematic of, 757
- MoS<sub>2</sub> particles, produced by microwave irradiation method
- HRTEM images of, 753
- Mo-Ti alloy, 758
- motion harvesters, 650
- Mott–Jones relations, 550
- MQW heterostructures, 156
- MTBE (methyl tertiary butyl ether), 1144
- multielement-doped graphenes, 573
- multifunctional nanocomposites, 334
- multijunction solar cells, 183
- multilayer coating, 212, 241
- multilayer insulation (MLI), 958
- multiple exciton generation (MEG), 120, 154
- multiple internal reflections, 869
- multiplicity factor, 771
- multipolar interactions, 96
- multiwall carbon nanotube (MWCNT), 43, 44, 45, 74, 380, 749, 921, 983, 1018
- buckypaper, scalable production, 384
  - coated aluminum electrodes, fabrication of, 380
  - electrodes supercapacitors, performance, 385
  - functionalization, 116, 1018
  - thermal conductivity, 1018
  - phase contrast optical microscopic images, 1017
  - thermal conductivity, 1018
- multiwall (mother) nanotubes, plasma treatment of
- formation of daughter nanotubes, 750
- mutations, 95
- M13 viruses, 116
- MWCNT. *see* multiwalled carbon nanotube
- MXenes, 398
- MX subsystem, 774
- MX-TX<sub>2</sub> MLC with O-T stacking order
- c-axis periodicity values of tubular structures, 775
- n**
- NaAlH<sub>4</sub>
- nanoconfinement of, 425
- NaBr electrolyte, 404
- aqueous electrolyte, 404
- naked metal, 890
- nanoadditives, 44
- nano-Al<sub>2</sub>O<sub>3</sub> particle-reinforced AZ31 alloy, 820
- nano-based sensors, 284
- nanobinders, 983
- nanobowls, 476
- nanobranched nanorod arrays, 115
- nanocapsules, 476
- nanocermet, 235
- nanochitin, 362
- nanoclay-reinforced PMNCs
- with PMCs, 834
- nanocoatings, potential energy-saving characteristics, 973
- nanocolloids, 52
- nanocomposites, 184, 231, 511, 549, 657, 745, 969, 981
- bulk materials, 519
  - challenges and opportunities for, 27, 849
  - coating, 849
  - demand in wind energy, growth drivers for, 1087
  - fuel efficiency, 831
  - generator, using aligned PZT nanowires, 658
  - based hydrides, 452
  - Mg<sub>1.5</sub>Mn<sub>0.5</sub>Ni/LaNi<sub>3.75</sub>Mn<sub>0.75</sub>Al<sub>0.25</sub>Co<sub>0.25</sub>, 452
  - Mg<sub>1.5</sub>Mn<sub>0.5</sub>Ni/Zr<sub>0.35</sub>Ti<sub>0.65</sub>V<sub>0.85</sub>Cr<sub>0.26</sub>Ni<sub>1.30</sub> hydride materials, 452
  - nanoscale Mg<sub>2</sub>ni/Tini composites, 454
  - materials, 187, 455
  - magnet, 1102
  - plastics, 986
  - selective coatings, 235
- nanoconfinement, 423, 870
- chemical hydride, 424
  - complex hydrides, 424
- NANOCRYL<sup>®</sup>A product series, 1093
- nanocrystalline, 633
- alumina–copper hybrid (Al<sub>2</sub>O<sub>3</sub>–Cu) powder, 1014
  - bainite, 709, 713
  - hydrogen storage alloys, 450
  - LaNi<sub>4.2</sub>Al<sub>0.8</sub> alloy
  - AES spectrum of, 449
  - LaNi<sub>5</sub> alloy powder, 447
  - LaNi<sub>5</sub>-type alloys, 449
  - materials, 436, 437
  - Mg<sub>2</sub>Ni-type materials, 451
  - Mg<sub>2-x</sub>Mn<sub>x</sub>Ni-H alloys, 452

- powders
    - – electrochemical properties of, 444
    - – to form agglomerates, 338
  - selected properties of, 455
  - silicon absorber, 192
  - silicon oxide, 181
  - steel grades, design of, 25, 709
  - – additional refinement of microstructure, 710
  - – carbide-free microstructure, 710
  - – faster rate of reaction, 710
  - – increased hardenability, 710
  - – low austenite to bainite transformation temperature, 710
  - – simple alloy system, 710
  - synthesized CdO thin films, 284
  - TiFe, discharge capacity, 443
  - TiFe materials, 442
  - $\text{TiFe}_{1-x}\text{Ni}_x$  materials, 442
  - YDT sintered pellet, SEM image of, 285
  - ZrN film, AFM image of, 288
  - $\text{Zr}_{0.35}\text{Ti}_{0.65}\text{V}_{0.85}\text{Cr}_{0.26}\text{Ni}_{1.30}$  material, 446, 447
  - ZrV<sub>2</sub>-type materials
    - – discharge capacities, 447
  - nanocrystalline bainite
    - wear performance, 718
  - nanocrystalline chemical deposition (NCD), 786
  - nanocups, 124
  - $\text{NaNO}_3$  electrolyte, 404
  - nanoelectronics, 398
  - nanoemulsions, 476
  - nano-enabled commercialized products, 1099
  - nano-enabled Li-ion batteries
    - commercial status of, 1050
  - nano-enabled membranes, 1074
    - filing trend for, 1075
  - nano-enabled permanent magnets, 1102
  - nano-enabled polymer electrolyte membrane fuel cell, 1057
  - nano-enabled sensors, 1101
  - nanoencapsulated PCMs, 478
  - nanoengineered materials, 182, 183, 184, 967, 968
  - nano-enhanced e-HEPA, 979
  - nano-enhanced lighting technologies, 968
  - nano-enhanced paints, 992
  - nanoenhanced PCMs, 460, 461
  - nano ferrofluid, 282
  - nanofibers, 113, 476, 657
    - of lithium-ion conducting ceramic, 309
    - mats, 117
    - reinforcement, 982
  - nanofibrillar bonding, 985
  - nanofibrillated cellulose (NFC), 1169
  - nanofiltration techniques, 1140
  - nanoflakes, 746
  - nanofluids, 476, 478, 913, 919, 929, 1005
    - effective thermal conductivity of, 888
    - for heat transfer applications, 997
      - – CNT-based nanofluids, 1008
      - – graphene nanofluids, 1012
      - – hybrid nanofluids, 1013
      - – magnetic nanofluids, 1009
    - phase change material, thermal conductivity of, 1015
    - – traditional nanofluids, 999
  - IoNanofluids systems, 918
  - – solar energy applications, 928
  - preparation methods, comparison of, 914, 915
  - schematic representation of, 998
  - stability, 917
    - – methods to improve, 919
  - structural characterization of, 920
  - thermal conductivity of, 887, 998
- nanofractal, 786
- nanogel translucent aerogel, 989
- nanoimprint lithography, 185
- nanoinsulations, 971
  - future market, 972
- nano-iron oxide composite, 1146
- nanolayers, 231
- nanoliquid metal, 888
  - additional energy conversion mechanisms, 906
  - applications of, 890, 906
  - challenging scientific and technological issues, 904
  - energy conversion, 898
  - energy management, 892
  - energy storage, 901
  - piezoelectricity generation, 906
  - properties of, 889
  - synthesis of, 891
- nanolithium–titanate battery cells, 975
- nanolithography, 914
- nanomanipulation, 914
- NanoManufacturing Institute, 990
- nanomaterials, 181, 184, 210, 478, 921
  - application areas, 102
  - as catalysts, 928
  - component performance in wind turbines, 1085
  - components, 343



- origin of increased surface area, 102
- problem, 913
- processing, 345
- surface functionalization, 101
- toxicity, 1154
- in wind energy, commercialization challenges of, 1082
- nanometers, 185
  - sized precipitates trap helium bubbles, 278
- nanometric scales, 138
- nanometric-size oxides, 1144
- nano/micro-electromechanical (N/M-EM), 289
- nano/nanotype CMNCs, 845
- nanoparticles (NPs), 45, 155, 235, 630, 967
  - Ag based, 864
  - aggregation, 918
  - agglomeration, 924
  - bulk synthesis, 982
  - catalysis, 30
  - dye-sensitized solar cells, role in, 107
  - geometry, 176
  - H<sub>2</sub> production via dark fermentation, 254
  - networks, in light absorption, 89
  - size distribution, 926
- nanoparticles-enhanced ionic liquid (NEIL), 912
- nanoparticulate titanium dioxide, 983
- nanophase ceramics, 339
- nanophotonic back reflector designs, 197
- nanophotonic intermediate reflector designs, 199
- nanopillars (NP), 133
- nano-platinum coating, 286
  - titanium electrodes, 286
- nanoporous materials, 30;944
  - aerogel, SEM of, 942
  - BiVO<sub>4</sub> anode, 637
  - BiVO<sub>4</sub> electrode, 639
  - traps, 970
- nanopowders, 336, 915
- nanoribbons, 748
- nanorods, 657
- nanoscale, 60, 785
  - adhesives, 968
  - antenna arrays, 975
  - filters, 980
  - materials, 101, 200, 970
  - mixtures, 184
  - Ni-YSZ anode, 580
  - plastic beads, 985
- nanoscrolls, 769, 771
- nano semiconductor materials, for photocatalytic water splitting, 600
  - carbon nitrides, 620
  - iron oxide, 611
  - other materials, 623
  - titanium dioxide, 602
  - zinc oxide, 613
- nanosensors, 41, 46, 47, 48, 968, 982, 984, 990, 1101
  - Ag-based, optical properties, 48
  - building maintenance and safety, role in, 990
- nanosheets, 11
  - SAPO-34 catalyst, 26
- nanosilica, 983, 1094
- nanosilver, 914
- nanosized fillers, 299
- nanosized gypsum, 988
- nanosized reinforcements, 849
- nanosized SAPO-34 crystals, 26
- nanosized titanium/titanium diboride particles, 823
- nanosolar employed semiconductor, 973
- nanosponges, 46
  - selectively absorbs oil, 1148
- nanostuctured materials, 25, 184, 356, 514
  - advantages and disadvantages, 19, 356
  - applications in wind energy sector, 1083
    - nanocoatings, 1088
    - nanofluids, 1091
    - nanolubricants, 1089
    - nanosensors, 1092
    - structural adhesives, 1093
    - structural applications, 1083
    - ultracapacitors, 1092
  - Bi<sub>2</sub>Te<sub>2.7</sub>Se<sub>0.3</sub> nanoplates, 554
  - carbons, 391
  - ceramics
    - schematic illustration, 348
  - coatings, 164, 176
  - contact material, 187
    - properties, 188
  - cost-effective materials, 547
    - band engineering to power factor enhancement, 554
    - material requirements, 550
  - ionic conductors, 582
  - magnesium hydroxide (nano-MH), 474
  - in wind energy components, potential applications of, 1084
  - in wind energy industry, challenges, 1081
    - dispersion, 1081
    - high aspect ratio, 1081
    - stricter environmental regulations and toxicity issues, 1082
- nanostuctured thin-film (NSTF), 578

- nanostructured transformable steel (NTS), 278
- nanostructure ferritic alloy (NFA), 275
- nanostructures, 184. *see also* nanostructured materials
  - engineering to lower thermal conductivity, 551
  - material, 300
  - – absorber, 191
  - metal oxides for gas detection, 439
  - nonporous carbon materials, 396
  - PCMs, 476
  - porous carbon materials, 396
  - PZT material, 658
  - schematic representation, 434
  - thermoelectric materials, 511
    - – challenges to increase efficiency, 511
    - – electronic properties, 22, 516
    - – future challenges, 22, 23, 530, 533
      - – device level performance, 22, 532
      - – fabrication level performance, 22, 531
      - – material level challenges, 22, 531
    - – high-temperature applications, 511
    - – large-scale applications, 511
    - – low-temperature applications, 511
    - – phonon properties, 22, 516, 518
    - – small-scale applications, 511
    - thermoelectric materials synthesis, 548, 556, 557
- nanotech-based spray, 972
- nanotech-based window films, 971
- nanotechnologies, 41, 60, 858, 1080
  - applications, 319
  - for energy, societal implications, 316
  - methodologies, 208
  - relevance, 101
  - role of, 967
  - water treatment technologies, 1140
  - wind energy
    - – components, growth drivers for, 1081
    - – intellectual property scenario, 1095
- nanotextured interfaces, in silicon thin-film solar cells, 186
- nano-TiO<sub>2</sub>
  - as photocatalysts or adsorbents, 1140
- nanotubes, 630, 657, 745, 746, 771, 1171
  - from inorganic compounds, 745
  - of misfit-layered compounds, 774
- nanowire quantum dot (NWQD), 517
- nanowires (NW), 133, 511, 519, 549, 605, 630, 657, 858
  - Ag based, 475
  - – glass, SEM image, 187
    - assemblies
      - – 3D Pt-Co, 570
    - axial heterojunction, 862
    - cell, 869
    - in-situ NW, TEM image, 860
  - membranes, 1153
    - thermoelectric property, 879
  - nanozeolites, 8
  - nano-ZnO, 257
  - Na<sub>2</sub>SO<sub>4</sub>·10YH<sub>2</sub>O@SiO<sub>2</sub> solid nanobowls
    - TEM observation of, 477
  - National Nanotechnology Initiative (NNI), 317
  - National Renewable Energy Laboratory, 974
  - National Wind Technology Center (NWTTC), 327
  - natural container, 1140
  - natural gas, 59, 60, 629
  - natural photosynthesis, 1110
  - natural polymers, 1152
  - Nb–AlO<sub>x</sub>–Nb Josephson junctions, 281
  - Nb doping, 757
  - Nb<sub>2</sub>O<sub>5</sub>, 105
  - NbS<sub>2</sub>- and TaS<sub>2</sub>-based compounds, 774
  - N-butyl-N-methylpyrrolidinium bis (fluorosulfonyl)imide, 405
  - NCA battery, 1038
  - N doping, 607
  - NdYAG laser pulses, 765
  - near-theoretical densification, 338
  - neodymium-nickel crystalline precursor, 585
  - Nernst equation, 441
  - neutrons flow
    - irradiation caused, 303
  - neutrons flux, 303
  - Newtonian fluid, 922, 925
  - NFC/PEI material, 1170
  - N-formylmethanofuran, 257
  - N<sub>2</sub> gas adsorption isotherm
    - for as-prepared silica aerogel, 953
    - for plane aerogel sheet/sandwich aerogel sheet, 953
  - NH<sub>3</sub>H<sub>2</sub>O-catalyzed reaction, 1153
  - Ni/Al<sub>2</sub>O<sub>3</sub> catalyst, 69
  - Ni/pure gallium
    - DSC curves of, 900
  - Ni–B alloy, 68
  - Ni–B matrix, 68
  - Ni catalysts, 66, 68
  - Ni cermet, 580
  - nickelate backbones, 311
  - nickel-based superalloys, 276
  - nickel black, 226
    - coatings, 226

- nickel carbide, 71, 76
  - nickel coating, 226
  - nickel crystallites, 74
  - nickel lattice, 68
  - nickel–metal hydride (Ni–MH<sub>x</sub>) batteries, 444
  - Ni crystals, 67, 70, 71
    - size, 67
  - Ni dispersion, 74
  - Ni–Fe hydrogenase, 250, 256
  - Ni/GDC anode, 580
  - Ni lattice, 68
  - Ni loading, 67
  - Ni/MgAl<sub>2</sub>O<sub>4</sub>
    - catalysts, 76
    - TEM images of, 74
  - Ni/Mo electrodes, 643
  - Ni nanoparticles, 66, 67, 255
  - NiO-YSZ anode, 583
  - Ni powders
    - XRD spectra of, 450
  - Ni surface, 68
  - nitric acid, 497
  - nitrides, 634
  - 2-nitrobenzoic acids, 929
  - nitrogen-based complex ions, 421
  - nitrogen doping, 757
    - carbon nanocage (N-CNC), 572
    - CNTs, 382
    - graphene (NG), 468, 573
    - graphene oxide, 603
    - ordered mesoporous carbon, 574
  - nitrogen fixation, 250
  - nitrogen oxides, 3
  - nitrosomonas europaea, 1134
  - Ni/Y<sub>2</sub>O<sub>3</sub> catalysts, 70
  - N-methyl-N-propylpiperidinium bis (fluorosulfonyl)imide, 405
  - NMI. *see* NanoManufacturing Institute
  - N,N'-dihydroxyethyl aniline, 469
  - nobel metals, 262
    - component, 65
  - Noether theorem, 787
  - nonbasal cross-slip activation, 818
  - nondestructive evaluation (NDE)
    - as SQUID-based technique, 281
  - nonequilibrium Green's function model, 517
  - nongeminate recombination, 195
  - nonlinear hybrid energy harvester, 657
  - nonlinear oscillator, 659
  - nonporous carbon material, 395, 396
  - nonrenewable energy resources, 649
  - nonselective coatings, 208, 209, 210
    - advantages and disadvantages of, 227
    - performance, prepared by gas-phase method, 221
    - performance, prepared by wet-chemical method, 219
  - nonsilicon semiconductor materials, 973
  - nonuniform refractive index, 868
  - normal hydrogen electrode (NHE), 1125
  - normalized capacitance
    - vs. CDC samples pore size, 402
  - notched tension-tension fatigue specimens, 719
  - novel fracture toughness, 981
  - novel TiO<sub>2</sub>@BiVO<sub>4</sub> photoanode, 644
  - NP10
    - thermal conductivity, 1003
  - N–P homojunction, 135
  - N<sub>2</sub> separation, 1171
  - n-type band structure, 865
  - n-type Bi<sub>2</sub>Te<sub>3</sub>-based nanocomposite, ZT value, 521
  - n-type conductors, 185
  - nuclear reactor vessel, 303
  - nuclear systems, nano materials, 271, 273
    - hydrogen sensor, 284
    - nano ferrofluid-based sensors, 282
    - nanoscale sensors, 280
    - oxygen sensor, 284
    - sodium-cooled fast reactors, 17, 276
    - sodium monitoring in fast reactors, 282
    - SQUID-sensors, 281
  - nucleation rate, 8
  - NW. *see* nanowire
  - N-W relationship, 720
  - nylon fibers, 1140
  - Nyquist plots, 403
  - nZVI particle
    - iron sulfate complex, 1143
    - surfaces, 1143
  - nZVI reactivity, 1155
- o**
- obligate anaerobes, 250, 252
  - ocean deterioration, 1161
  - ohmic damping, 171, 174
  - oil degradation
    - Fenton-type catalyst, 1141
  - oilfield nanotechnologies, 41, 42
  - oil recovery, 50
    - purposes, 1147
  - oil remediation, 1155
  - oil spills, 1140, 1154
  - oil–water separation

- confocal laser-scanning fluorescence microscopy, 1147
  - OLC. *see* onion-like carbon
  - OLED. *see* organic light-emitting diode
  - olivines, 361
  - one-dimensional nanostructures, 13, 110
  - one-pot hydrothermal synthesis process, 112
  - onion-like carbon, 395
    - electrodes, 409
  - on-site energy storage, 976
  - on-site renewable energy, 973
    - solar, 973
  - open-circuit electromotive force, 871
  - operating potential window, 406
  - operating temperature window, 405
  - operating voltage window, 392, 406
  - optical absorption spectrum, 138, 865
  - optical cavity, 867
  - optical gap, 139
  - optical indices, 239
  - optical modeling, 242
    - theory for multilayer systems, 236
    - W-SiCH multilayer stacks, 242
  - optical rectenna solar cell (ORSC), 136
  - optical scattering, 164
    - beneficial for, 164
  - optical transparency, 972
  - optimal carrier concentration yielding peak, 879
  - optimum phase mixture (OPM), 192
  - optimum pore size, 400
  - optoelectronics, 398
    - devices, 115
    - properties, 181
  - ordered mesoporous carbon (OMC), 572
  - organic bulk heterojunctions, 181
    - solar cells, 193
  - organic electrolytes, 399
    - advantage, 399
  - organic enamels, 211
  - organic insecticides, 985
  - organic light-emitting diodes, 977, 989
  - organic photovoltaics, 195
    - nanotechnology, 976
  - organic solar cell, 145, 174
    - with bulk heterojunction absorber, 194
  - organic thin films
    - advantage, 973
    - solar cells, 975
  - organosilanes, 833
  - orientation relationship (OR), 719
  - Orowan strengthening, 814
  - oscillation frequency, 150
  - Ostwald ripening/aggregation, 570, 861
  - oxidation evolution reaction, 600
  - oxide dispersion-strengthened (ODS), 274, 303
    - alloy, 276
    - ferritic martensitic steel, 278
    - irradiation data, 278
    - typical chemical composition of, 279
  - oxidizing reagents, 599
  - oxidoreductase complex, 259
  - oxidoreduction reactions, 301
  - oxyfuel combustion, 1166, 1167
  - oxygen mobility, 69
  - oxygen reduction reaction (ORR), 569
  - oxygen storage, 68
    - capacity, 69
  - oxynitrides, 236, 634
- p**
- pacemaker, 650, 654
  - paints, 213
    - coating, 213, 929
  - palmitic acid (PA), 468, 473
  - PAO-based alumina nanofluids, 999
  - PAO-based hybrid sphere/CNT nanofluids, 1014
  - PAO-based MWCNT nanofluid, 1008
  - paraffin, in CNT, 465
  - paraffin wax, infiltrated into a porous deformable carbon nanotube sponge, 464
  - parasitic absorption, 173
  - Paros and Weisbord (PW) equations, 661
  - particle agglomeration, 337, 435
  - particle size, 29, 42, 67
    - distribution, 931
    - of SAPO-34, 21
  - particles polarizability, 87
  - patent analysis, 1035
    - geographical region-wise distribution of, 1036
    - in Li-ion batteries, 1035
    - methodology, 1035
    - patenting activity, 1036
    - year-wise patent publication trend, 1035
  - patents segmentation, 1049
  - PbS film, 141
  - PbS-NP-based cells
    - with bandgap, photovoltaic properties of, 141
  - Pb-stabilized oxide whiskers, 755
  - PbTe-based alloy  $\text{Ag}_{1-x}\text{Pb}_{18}\text{SbTe}_{20}$  (LAST), 523, 559
  - PbTe-based nanostructured materials, 559

- PC. *see* propylene carbonate
- p*-cresol, 929
- PdAg nanorings on graphene (PdAg/G), 572
- Pd crystallites, low-magnification TEM  
micrograph of 66
- Pd infiltration  
– on porous YSZ scaffold, 584
- Pd nanoparticles, 570, 572
- Pd octahedrons, in MOR, 570
- PdPt nanocube, 570
- PEG-Ag/EVM ss-CPCM0  
– SEM images of, 476
- PEG-GO-GNP composite PCM, 472
- Peltier coefficient, 871
- Peltier effect, 871, 872  
– thermoelectric cooling, 871
- PEO-based electrolytes, 363
- perovskite solar cell (PSC), 103, 632  
– electrolysis system, 644
- perovskite tandem cell  
– J–V curves of, 644  
– for water splitting, 644
- petroleum nanotechnologies, 42
- petroleum oil, 249
- PHAPTMS surface silanization, 9
- phase change material (PCM), 21, 459, 468, 901, 997, 1015  
– categories of, 903, 904  
– cool storage, degree of supercooling, 902  
– thermal conductivity particles, 1015
- phase change materials for cool storage (PCMCT), 901
- phase stability boundaries, 300
- phase transformation, 304
- phase transition, 460, 902  
– of PCM, 460  
– temperature, 460
- phenylaminopropyltrimethoxysilane, 9
- phenyl-C<sub>61</sub>-butyric acid methyl ester (PCBM), 174
- phonon, 874  
– boundary scattering, 874  
– conductivity of, 517, 529  
– –  $\beta$ -Zn<sub>4</sub>Sb<sub>3</sub>, 524  
– diffusion, 313  
– dispersion relation, 875  
– mean free path, 514, 881  
– scattering, 519, 874
- phonon glass–electron crystal (PGEC), 519
- phonon–phonon Umklapp scattering, 874, 881
- phonon thermal conductivity, 514, 518, 529  
– in superlattice, 524
- phonon transport, 881  
– kinetic theory of, 880  
– properties, 516
- phosphine, 865
- phosphonium, 923
- phosphoric acid fuel cells (PAFCs), 1058
- photoactive centers, 105
- photoanodes, 108, 117
- photobiological water splitting, 598
- photocatalysis, 598, 602, 635, 636
- photocatalytic coatings, 968  
– conversion of acetate, 262  
– drawback, 979
- photocatalytic H<sub>2</sub> production  
– reaction mechanism, 264
- photocatalytic nanomaterials, 980
- photocatalytic water splitting reaction, 598, 599, 602
- photocathode, 639, 640
- photochromic technologies, 986
- photocurrent, 109  
– density, 639, 641, 866, 868  
– enhancement, 173
- photoelectrochemical (PEC), 630  
– electrodes, 641  
– H<sub>2</sub> evolution  
– – photocathodes for, 642  
– silver nanowire, 475  
– water splitting, 598  
– – single-crystal TiO<sub>2</sub>, 631
- photoelectrolysis cell configurations, 601
- photoexcitation, 105, 195
- photo-Fenton-like method, 1142
- photofermentation, mechanism of, 261
- photogenerated carriers, 861
- photoinduced polymerization, 834
- photo-Kolbe reaction, 265
- photoluminescence quantum yield, 155
- photolytic H<sub>2</sub>, 635  
– based on nanoenhanced materials, 632  
– photocatalyst powders, 633  
– production, basic principle and evaluation methods for, 630  
– tandem PV-electrolysis or PV-PEC systems, 642  
– using PEC systems, 636
- photonic band gap, 109
- photonic crystals, 109
- photons, 182, 183  
– absorption process, 193, 238  
– down-conversion, 134, 137
- photoprotectors, 930
- photosensitizer, 121

- photosynthetic bacteria, 250
- photothermal conditions, 752
- photovoltaic absorber materials, 183, 191, 196
- photovoltaic cells (PVCs), 133, 148, 194, 237, 727, 969
  - based on bandgap, 135
  - geometric-confinement effects, 14, 144
  - hot carrier solar cells, 155
  - multiple exciton generation solar cells, 154
  - nanomaterials, 13, 137
  - nanostructured cells based on silicon, 14, 146
  - nanowire-based, 865–870
  - optical management, based on nanostructures, 149
  - organic and hybrid nanostructured cells, 145
  - plasmonics for, 14, 149
  - principle, 138
  - quantum-confinement effects, 13, 138
  - solar cells based on silicon nanoparticles, 142
  - solar cells on PbS/PbSe nanoparticles, 141
  - technologies, 137
    - schematic representation, 136
  - up/down photon conversion, 14, 152
  - windows, 968
- photovoltaic conversion, 133
- photovoltaic devices, 207, 974
  - applications in, 190
  - present photovoltaic technologies, 134
  - principle and limiting factors, 134
- photovoltaic electricity, 231
- photovoltaic energy, 182
- photovoltaic performances, 117
  - different counter electrode materials based, 126
- phthalates, 986
- physical adsorption, 392
- physical vapor deposition (PVD), 237
- physisorption, 417
- p-, i-, and n- core–shell Si nanowire solar cells
  - J–V curves, 865
- piezoelectric cantilevers, 661
- piezoelectric coefficients, 663, 657
- piezoelectric conversion, 652
- piezoelectric energy, 650
  - harvesting, 653
- piezoelectric materials, 655, 657, 659, 660, 661
  - deformation of, 671
  - selection, 659
- piezoelectric MEMS energy harvesters, 656
- piezoelectric power generator, 655, 656
- piezoelectric transducer (PZT), 653
  - embedded in shoes, 654
  - human vibration energy harvester with, 655
  - nanofiber generator, 658
  - nanogenerator attached to a Teflon cantilever, 658
  - nanowires, nanocomposite generator, 658
- pigments
  - organic and inorganic, 210
- p-i-n junctions, 865, 867
- pinwheel fractal, 784
- planar metal–dielectric interfaces, 149
- planar polycrystalline Si solar cells, 866
- Planck’s law, 232, 550
- planetary milling processes, 438
- plasma ablation, 747
- plasma coating, 971
- plasma deposition techniques, 237
- plasma-enhanced chemical vapor deposition (PECVD), 142, 187, 191, 232, 237
- plasmon, 149
  - resonance, 88
- plasmonics, 122, 181
  - Ag NP coating, 173
  - coating, 171
  - nanoparticles, 174, 176
  - particles, design of absorption spectrum with, 93
- plastics, 986
  - solar cells, 973
- plugging indicators, 284
- plug-in hybrid electric vehicles (PHEV), 1033
- plywood effect, 984
- PM-processed Mg/Al<sub>2</sub>O<sub>3</sub> nanocomposites, 815
- p–n junction, 865, 866
- point defect (PD), 552
- point of zero charge (PZC), 65
- polar solvent, 630, 919
- polyacetylene, 534
- polyalkyl thiophenes, 534
- polyaniline (PANI), 473, 534, 729
- polyanionic cathodes, 362
- poly(2,7-carbazolyenevinylene), 534
- polycrystalline Cu electrode, 1128
- polycrystalline silicon solar cells, 857
- polycyclic aromatic hydrocarbon (PAH), 1139
- polycyclic aromatics (coke), 26
- polydiallyldimethylammonium chloride, 13
- poly(3,4-ethylenedioxythiophene) (PEDOT), 534, 734
  - poly(styrenesulfonate) (PEDOTPSS), 149
- poly(ethylene glycol) (PEG), 603, 731
- polyethylene oxide, 362

- membrane network, 737
- polyethylenimine (PEI), 1169
- polyhedral oligomeric silsesquioxane (POSS), 833
- poly(3-hexylthiophene)-coated GaAs nanopillars grown, 149
- poly(3-hexylthiophene) solution, 623
- polymerase chain reaction systems, 509
- polymer-coated nanoparticle (PCNP), 914, 1151
- polymer electrolyte membrane fuel cell, 23, 569
  - carbon nanomaterials as catalyst support, 23, 571
  - nanocomposite membranes, 574
  - nanostructured catalyst layers, 578
  - noncarbon-supported electrocatalysts, 573
  - nonprecious metals/metal-free catalysts, 573
  - porous PGM-based nanocatalysts, 23, 570
  - supported electrocatalysts, 571
- polymer electrolyte membrane fuel cell (PEMFC), 572
  - gas diffusion layer, 1074
- polymer electrolytes, 574
  - ionic conductivity, 363
- polymeric carbon nitride, 620
- polymeric nanoparticles, 1173
- polymer immobilized ionic liquid phase catalysts, 928
- polymer–inorganic nanocomposites, 137
- polymerized octadecylsiloxane (PODS), 1152
  - modified sponge, toluene/water collection process, 1152
- polymer matrix composite (PMC), 331, 986, 1100
- polymer matrix nanocomposites (PMNC), 831, 832
  - potential automobile applications, 833
  - synthesis routes for fabrication, 835
  - in transport sector, 832
    - manufacturing methods, 27, 834
    - matrices and reinforcement materials uses, 27, 833
    - potential applications in transport industry, 834
- polymer solar cell (PSC)
  - thick-film, 145
- polymethylbenzenes, 28
- polymethylmethacrylate panels, 970
- polymorphic transition, 460
- polypropylene fiber fabric, 1146
- polypyrrole (PPy), 534
  - CNTs nanocomposite, 1140
  - nanofiber, 752
- polystyrene (PS)
  - boards, 971
  - microsphere, 1142
- polystyrene nanosphere (PSNS), 147
- polystyrenesulfonate (PSS), 734
- polyurethane-based phase change materials (PUPEG), 472
- polyurethanes, 473
- polyvinyl acetate (PVA), 48
- polyvinyl alcohol, 490
- poly(vinylbutyral), 491
- pore size/ion size
  - in aerogels, 944
  - relationship between, 400
- porous carbons, 395, 396, 408
- porous metal borohydrides, 426
- porous Pt nanotubes, 570
- porous silica, 369
- portland cement, 982
- postannealing methods, used to dope Re into MoS<sub>2</sub> IFs/INTs, 758
- postcombustion technology, 1166
- postnucleation, 120
- postsynthesis Redoped INT-WS<sub>2</sub>
  - HRTEM image, 759
- potassium carbonate, 1167
- potassium tetrabromoaaurate, 495
- power conversion efficiency (PCE), 142
- power densities, 234
  - electronic devices, energy sources/average power consumption of, 651
- power distribution activities, in Europe, 295
- power-plant class installation, 857
- power plastic, 973
- power transmission, in Europe, 295
- precession electron diffraction, 16
- precombustion, 1166
- precursor solution, 120
- predicting zeolite equilibrium morphology, 15
- prefractals, 783
- prefractal transfers, 785
- pressureless sintering, 338
- pressure-treating wood, 985
- pressurized water reactor (PWR), 273
- pristine nanotubes, 757
- pristine ZSM-5 (ZST-12), 25
- product, after annealing
  - TEM images of, 754
- PROMES, 232
- property-composition correlations, 52

- propylene carbonate, 399
    - mechanism of suspension-based system, 630
  - proton-conductive bifunctional materials, 577
  - proton exchange membrane (PEM), 737
  - proton exchange membrane fuel cell (PEMFC), 737, 1058
  - protonic ceramic fuel cell (PCFC), 311
  - prototype fast breeder reactor (PFBR), 272
  - pseudocapacitive behavior, 402
  - pseudocapacitive charge storage mechanisms, 393
  - pseudocapacitive material, 398
  - pseudocapacitors, 393
  - Pt
    - deposits, 639
    - hollow nanospheres, 571
    - loaded carbon nitride, 623
    - loaded  $\text{CuGaS}_2/\text{RGO-TiO}_2$  composite, 636
    - loading, 569
  - Pt/ $\text{In}_2\text{S}_3/\text{CdS}/\text{CZTS}$  cathodes
    - cross-sectional SEM images of, 641
  - Pt/ $\text{In}_2\text{S}_3/\text{CdS}/\text{CZTS}$  photocathode, 641
  - Pt nanocups, SEM images, 124
  - Pt nanoflower, SEM images, 124
  - Pt nanoparticles, 124
    - coated Ti mesh electrode, 286
  - PtPb nanoparticles, 573
  - Pt/ $\text{TiO}_2/\text{Al}_2\text{O}_3/\text{ZnO}/\text{Al}/\text{Cu}_2\text{O}$  photocathodes, 641
  - p- type band structure, 865
  - p-type conduction, 185
  - p-type Pt-doped  $\text{Sb}_2\text{Te}_3$  nanocomposites, 554
  - public lighting management, 297
  - public water purification systems, 980
  - pulsed laser deposition (PLD), 584
  - pumping carbon dioxide, 1164
  - pure electric vehicle, 1034
  - pure ionic liquids
    - DSC profiles, 405
  - purple non-sulfur bacteria, 260
  - PV–electrolysis configuration, 632
  - PV–PEC tandem device, 642
  - pyridine-catalyzed reaction, 1120
  - pyrococcus furiosus, 252
  - pyrogel®, 961
  - pyrolysis, 922
    - of biomass, 597
  - pyrrolidinium, 923
  - pyruvate ferredoxin oxidoreductase, 252, 253
  - pyruvate formate lyase, 254
- q**
- QD. *see* quantum dot
  - QDSSC. *see* quantum dot sensitized solar cell
  - quadrupolar interactions, 97
  - quantum capacitance, 382, 395
  - quantum-confined nanomaterials, 137
  - quantum confinement effect, 120, 141, 313, 550, 875
  - quantum dots, 120, 138, 153, 511, 519, 549, 859, 968, 973, 975, 978
    - based silicontandem cell, 143
    - lighting, 978
    - schematic, 122
    - as sensitizers, 120
    - – solar cell (QDSC), 121, 136
    - technology, 974
  - quantum effects, 517
  - quantum efficiency of cells
    - FESEM image, 109
  - quantum information treatment, 83
  - quantum size effects, 101
  - quantum wells, 138
    - energy region, Quasi-Fermi level splitting, 157
  - quantum wires, 517
  - quartz reactor, 768
  - quasi-Fermi level, 156
  - quaternary nanotubular structures, 771
- r**
- radiation-induced point defects, 273
  - radiative emission, 232
  - radiative thermal losses, 234
  - radioactive thermoelectric generator (RTG), 509
  - radiofrequency (RF) energy harvesting, 649
  - Ragone plot, 377, 392
  - rainbow solar cells, 121
    - schematic of, 122
  - Ralstonia eutropha cells, 1134
  - Raman spectroscopy, 76, 776
    - single  $\text{LaS-TaS}_2/\text{NdS-TaS}_2$  tubular crystals, 775
  - R-AN amidoximes, 1145
  - rate-determining step (RDS)
    - $\text{CO}_2$  reduction process, 1119
  - raw DWCNT bundles, extracted from CNT aerogel
    - SEM micrograph of, 496
  - Rayleigh scattering, 941, 942
  - reactive hydride composites (RHC), 20, 422
    - tailoring thermodynamic properties, 422
    - schematic illustration of, 422



- reactive ion etching (RIE), 166, 870
  - real-time VLS self-assembly, 860
  - rear-side nanostructured reflectors, 164
  - Re-doped  $\text{MoO}_{3-x}$  nanoparticles, 758
  - Re-doped  $\text{MoS}_2$  fullerenes, 758
  - Re-doped  $\text{MoS}_2$  IFs
    - SEM images of, 758
  - Re-doped  $\text{MoS}_2$  nanotube
    - postannealing method, TEM image of, 758
  - redox polymers, 386
  - REDOX reactions, 569, 599
  - redox shuttles, 369
  - red phosphorus (RP), 474
  - reduced graphene oxides (rGO), 729
  - refined silicon, 857
  - reflectance measurements, 239
  - refractory metals, 276
  - refrigerators, 997
  - Re:IF- $\text{MoS}_2$  nanoparticle
    - high-magnification HAADF-HRSTEM of, 760
  - reinforced concrete construction, 984
  - reinforcement, 304
    - phases, 814
    - products, 336
  - relaxation time approximation (RTA), 516
  - remote radar sensing
    - feasibility demonstration, 315
  - renewable energy, 249, 781, 857
    - nanotechnology
      - applications of, 106
      - role of, 105
    - sources, 386, 630, 887
  - renewable fuels
    - equilibrium constants, 1122
  - renewable resources, 459
  - residential framing, 984
  - residual steam pressure, 307
  - resin-transfer molding (RTM), 334
  - resonant nanostructures, 176
    - application of, 164
    - beneficial for, solar applications, 176
  - response surface methodology (RSM), 578
  - reverse current treatment (RCT), 580
  - reverse disproportionation, 68
  - reverse-microbial fuel cell (R-MFC), 1133
    - practical artificial leaves, 1133
  - reversible energy storage, 309
  - reversible hydrogen electrode (RHE), 637
  - reversible nitrogen-based complex hydrides, 421
  - Rhodospseudomonas palustris*, 262
  - rice grain-shaped  $\text{TiO}_2$ 
    - SEM image, 111
  - Richardson–Mandelbrot diagram, 784, 785
  - rigid polystyrene boards, 973
  - RK-AN amidoximes, 1145
  - robust SAM (R-SAM), 142
  - roll on installation method, 974
  - roll-to-roll method, 380
    - production, 973
  - rooftop solar systems, 975
  - room-temperature ionic liquid (RTIL), 399, 1129
  - rotating bending
    - fatigue behavior, 719, 720
    - fatigue strength, 720
  - rotor blades, 335
  - R2R processes, 385
    - polymer filter, 383
  - RTA model, 517
  - RTIL. *see* room temperature ionic liquid
  - $\text{RuO}_2$ , 397
    - thin-film electrodes, 398
  - ruthenium oxide, 385, 386
  - rutile  $\text{TiO}_2$  nanorods on FTO
    - SEM images, 115
- s**
- Sahara Desert, 207
  - samarium-doped ceria (SDC), 580
    - nanocomposite electrolyte, 583
  - sandvik nanoflex, 984
  - SAPO materials, 16
    - SAPO-34 crystallite, 20, 24–27
    - SAPO-34 morphologies, 26
    - SAPO-34 nanocrystals, 26
    - SAPO-34 zeotype catalysts, 24
  - saturated calomel electrode (SCE), 637
  - $\text{Sb}_{1.5}\text{Bi}_{0.5}\text{Te}_3$ 
    - thermoelectric properties, 314
  - SBS. *see* sick building syndrome
  - scanning electron micrograph (SEM), 471
    - rhombohedral SAPO-34 particles, 22
  - scanning electron microscope, 765, 859
  - scattering cross section (SCS), 175
  - Scherrer equation, 17
  - Schockley–Queisser limit, 137, 156
  - Schottky junction, 866, 868
  - Scotch tape method
    - for thin film isolation, 725
  - scratch-resistant, 849
  - screen-printed metallic (Ag) finger contacts, 166
  - SDS. *see* sodium dodecyl sulfate
  - sedimentation kinetics, 917, 918

- Seebeck coefficient, 301, 313, 512, 547, 548, 871, 872, 874
  - undoped  $\text{Bi}_2\text{Te}_3$  (p-type), 519
- Seebeck effect, 551, 871
  - thermoelectric generator, 871
- Seebeck voltage, 872
- selected area electron diffraction (SAED), 769
- selected microstructural parameters, 716
- selective coatings, 234
  - with double cermet and tandem absorber multilayer structures, 235
- selective etching, 397
- selective methane oxidation, 79
- selective niobium etching process (SNEP), 281
- selective surfaces, 233
  - optical properties of, 232
- selenide, 235
- selenium-doped CNT/graphene composites (Se-CNT-graphene), 573
- self-assembled monolayer (SAM), 142
- self-assembly synthesis, 834, 859
- self-cleaning, 849
  - buildings, 968
  - clay roof tiles, 988
  - surfaces, 979
  - wood surfaces, 985
- self-fueled electrodeposition (SFED)
  - method, 498
- self-healing concrete, 287, 968, 983, 991
- self-jumping, 308
- SEM. *see* scanning electron microscope
- semiconductors, 212, 236, 513, 518, 598, 599, 620, 630, 635, 679, 928
  - bandgap energy, 191
  - devices, 679
  - Landauer limits of energy efficiency, 701
  - materials, 105
  - nanocrystals, 235
  - nanostructures, 942
  - particle size distribution, 236
  - pigmented paints, 221
  - solar cell, 857
  - substrate, 102
- sensor technologies, 115, 398, 1103
- shell-in-shell  $\text{TiO}_2$  hollow spheres, 112
- shim thickness, 664
- Shockley-Queisser theory, 182
- Shockley-Read-Hall recombination, 187
- shock wave, 747
- Si/Al ratio, 5, 17
- Si-based solar cells, 102
- SiC ceramics, 339
- SiC electrode
  - CDC electrodes, 408
  - SEM images of, 367
- SiCH film, 242
  - optical indices, 243
  - thin films, 237
- sick building syndrome, 979
- SiC nanoparticle-strengthened magnesium, 818
- SiC(N)H thin films, 238
  - optical behavior of, 238
- Si crystallinity, 189, 868
- Sierpinski triangle, 783
- SiGe alloys, 555
- Si/Ge interface, 862
- SiGe nanocomposites, 559
- SiGe/SiGe superlattices, 524
- silanated YSZ porous electrode, 581
- silane ( $\text{SiH}_3$ ), 859
- silica aerogels, 940, 962, 970
  - flexible sheet roll, 954
  - granules seen under optical microscope, 954
  - infiltrated, in fiber mat
    - magnified image of, 953
  - infiltrated refractory mat, 953
  - properties of, 943
- silica colloidal crystal, FESEM image, 109
- silicalite-1 nanozeolites, 8, 9
- silica-supported poly(ethyleneimine) (PEI) materials, 1169
  - nanomaterials, 1169
- silicides, 236
- silicoaluminophosphate, 3
  - SAPO-34 zeotype, 18
- silicon, 3, 22, 359, 524
  - based heat transfer liquids, 930
  - based microelectronic industry technology, 858
  - based photovoltaic manufacturing industry, 974
  - based solar market, 974
  - conductivity of, 359
  - quantum effects, 144
  - silicon-germanium nanowires
    - fabrication of, 858–864
  - specific capacity, 359
- silicon carbide (SiC), 237, 238, 844, 1000
- silicon-carbon nanocomposite, 359
- silicon cast bainitic steels, 717
- silicon dioxide ( $\text{SiO}_2$ ), 970, 999
- silicon film
  - cycled, SEM micrographs of, 358
  - high magnification, 360
- silicon gas precursor, 859

- silicon–germanium nanowires
  - superlattice nanowires, synthesis of, 862
  - thermoelectric property of, 877
- silicon heterojunction (SHJ), 188, 191
  - solar cells, internal quantum efficiency IQE of, 190
- silicon nanocrystal 974
  - ink, 974
  - TEM image, 155
- silicon nanoparticles, 974
- silicon nanostructures, 360, 871
- silicon nanotubes, 360
  - arrays, 360
- silicon nanowires (SiNWs), 149, 858, 874
  - arrays;868
  - bundle solar cell, 868
  - J-V curve, 869
  - fabrication by PSNS lithography, 148
  - light-trapping effect, 870
  - measured thermal conductivity, 875
  - Ostwald ripening, 861
  - sandwiching, 731
  - schematic illustration, 148
  - solar cells, 147, 866, 869, 870
  - thermal conductivity, 874
  - thermoelectric property, 876
  - vapor–liquid–solid synthesis, 858–861
- silicon oxide, 189
- silicon/silicon–germanium axial superlattice, 863
- silicon solar cells, 152
- silicon solar enhancement, 973
- silicon wafers, 238
- silver antimony telluride ( $\text{AgSbTe}_2$ ), 523
- silver dioxide, 982
- silver nano-based organic ester (SNOE), 473
- silver nanoparticles, 89, 255, 863, 992
- silver nanowires (AgNW), 47, 186
- Si Mie coating, 167, 171
  - application of, 167
  - light trapping properties of, 167
  - scattering properties, 168
- simple vacuum filtration, 383
- simulated (PCID)  $V_{oc}$ , 170
- Si nanowires
  - grown by gold catalyst VLS, 860
- single-crystalline solar cells, 867
- single-crystal misfit compounds, 765
- single-crystal silicon wafer production, 974
- single-junction solar cell
  - photovoltaic efficiency, 152
- single micro-CT scan slice of nickel foam template, 471
- single molecular transistors, 115
- single  $\text{MoS}_2$  nanotube
  - high-resolution aberration-corrected HAADF image of, 756
- single-nanowire solar cells, 867
- single-phase electrolytes (SDC), 582
- single-wall carbon nanotube (SWCNT), 47, 487, 991
- single-walled carbon nanohorns, 466
- SiNW. *see* silicon nanowire
- $\text{SiN}_x$  (Au)/GaAs/Au structure, 150
- $\text{SiO}_2$  nanoparticles, 50
- $\text{SiO}_2$  nanosensors
  - optical properties of, 48
- Si/SiGe prealloyed heterojunctions, 862
- Si solar cells
  - light trapping properties, 171
  - properties of, nanostructured coatings, 169
- Si thin film, 869
- Si wafer, 870
- skutterudites, 519, 528, 532, 536
- sliding/rolling wear resistance, 717
- sludge solubilization, 256
- smart aggregates, 991
- smart environments, 990
- smart nanobattery, 975
- smart textile curtains, 976
- SMAT material, 968
  - strength–formability relationship, 335
- smog-eating concrete, 968, 979
- $\text{SnS}_2/\text{SnS}$  misfit layers, exfoliation/scrolling of
  - tubular (scroll) structures, SEM image, 766
- $\text{SnS-SnS}_2$  misfit nanotubular structures, 765, 768
- $\text{SnS-SnS}_2$  nanotubes, 765
- $\text{SnS-SnS}_2$  tubule, with O-T . . . periodicity
  - TEM images of, 767
- Soave–Redlich–Kwong (SRK) model, 61
- sodium carbonate, 1111
- sodium-cooled fast reactor (SFR), 272
  - GEN-IV SFR concept, 276
  - nanomaterials components, 277
  - spectrum reactor, 271
  - surface modification
    - nanocomposite coatings, 289
    - nanocontainer-based coatings, 287
    - stainless steels, 287
    - superhydrophobic coatings, 289
    - titanium, 285
- sodium dodecylbenzenesulfonate (SDBS), 1002
- sodium dodecyl sulfate, 383, 389, 490

- NP 9, silica nanoparticle volume fraction, 1004
- thermal conductivity, 1003
- sodium lauryl sulfate (SLS), 1013, 1014
- sodium yttrium fluoride (NaYF<sub>4</sub>) matrices, 153
- solar ablation, 747, 752, 774
- solar absorption, 208, 233, 234, 241, 972
- solar arrays, 649, 974
- solar cells, 183, 190, 192, 969
  - applications, 858
  - classical, 182
  - devices, 134
  - fabrication of, 144
  - PbS, 13, 141
  - Si, TiO<sub>2</sub>, and Ag nanoparticle coatings, 170
  - spectrum modification, 152
- solar collectors, 928, 975
  - paint, 975
  - plates, factors, leading degradation of, 224
  - windows, 974
- solar devices, 997
- solar energy, 208, 296, 377, 597, 629, 630, 921
  - conversion, 137
  - dependency, 1110
  - flux, 631
- solar energy generating system (SEGS), 207
- solar furnace, 774
- solar hydrogen production, from water, 598
- solar irradiation, 234
- solar minimodule, 176
- solar panels, 968, 975
- solar/photothermal ablation, 751
- SolarPly, 973
- solar power density, 233
- solar radiation, 207, 208, 231, 234, 641
  - absorber(s), 235
- solar roof tiles, 975
- solar spectrum, 208, 866
- solar thermal systems, 231
  - absorbers, 212
  - applications, 232
    - nonselective coatings for, 209
    - coating, performance of, 215
      - absorptance and emittance, 215
      - factors affecting emittance, 221
    - conversion, 208
    - electricity, 232
    - energy system, 207, 231
    - power plants, 231
    - spectra
      - ideal selective, selective, and nonselective coatings, spectral characteristic, 209
- solar water splitting, 632, 974
  - schematic model for, 637
- solar window, 974
- sol-gel method, 309, 846
  - schematic representation of, 945
- synthesis of membranes with anionic conduction, 311
- solid electrolyte interphase, 357
- solid oxide fuel cell (SOFC), 310, 311, 579, 1057
  - SEM images, 582
  - nanomaterials, role of, 579
  - nanostructured anode materials, 580
  - nanostructured cathode materials, 584
  - nanostructured electrolytes, 23, 581
- solid-phase conduction, 971
- solid-phase crystallization, 74
- solid-phase materials, properties of, 782
- solid-phase processing, 811
- solid plasticizer, 363
- solid state heterojunction solar cells, 121
- solid-state hydrogen storage, thermodynamic consideration, 419
- solid-state ion-conducting composite, 369
- Solnova Solar Power Station, 207
- solvated ions, 396
  - size, 400
- solvation shell, 400, 401
- solvent annealing, 195
- solvent-free electrolytes, 399
  - polymer, 362
- sonication time, 915, 999
- Span 80, in hexadecane
  - thermal conductivity, 1016
- spark plasma sintering (SPS), 314, 339, 583
- specific capacitance plot, 401
- specific wear rate (SWR), 718
  - for commercial steel, 718
- spectral absorbency analysis, 918
- spectral lattice thermal conductivity, 552
- spectral reflectance, of ideal solar selective material, 233
- SPEX ball mill, 435
- SPEX model 8000, 435
- spherical nanocrystals
  - theoretical evolution of optical bandgap, 139
- sp<sup>2</sup>-hybridized carbon atom, 115
- spin coating, 237, 397
- spongy graphene (SG)
  - oil absorption and characterization, 1149
  - recycling process
    - four-step schematic diagram, 1150
- sporomusa ovata, 1133
- spray coating, 237

- electrodes, 386
- spray pyrolysis process, 986
- S<sub>1</sub>Pt<sub>95</sub>Ru<sub>5</sub>
  - high-magnification (a-2, b-2) SEM images of, 571
  - mass-normalized current density, 571
- sputtering, 142, 397
  - deposition, 214
- SQUID-based NDE system, 281, 282
- SQUID-based NDT system, 281
- Sr<sub>x</sub>Ti<sub>y</sub>–Er samples
  - photocatalytic reaction on, 624
- SSA. *see* specific surface area
- stainless steel
  - carburization/decarburization of, 283
  - foils, 380
- standard lithographic top-down approaches, 857
- steam condenser
  - in 1300 MW French nuclear power plant, 307
- stearic acid (SA), 466, 475
  - TiO<sub>2</sub> nanofluids, 474
- steel, 984
  - quenched and tempered, 719
- steered molecular dynamic (SMD) simulations, 919
- steric filtration, 980
- steric repulsions, 401
- STH efficiency, 641
- stiffen blades, 336
- Stockholm Environment Institute (SEI), 1163
- strain energy, 859
- stress, 663
  - factor, 720
  - ratio, 719
  - relief, 716
- stress distribution, 664, 667
  - comparison of, various surface shapes and profiles, 671
  - for conventional shapes and modified profiles, 672
  - on shim, 671
  - simulation for different surface shapes, 664
- structural sensitivity analysis, 79
- submicrometer-scale topology, 305
- substrate conformal imprint lithography (SCIL), 176
- substrate-level phosphorylation, 250
- subterranean coal deposits, 975
- sulfonated poly(ether ether ketone) (SPEEK), 577
- sulfonated polyimide containing triazole groups (SPI-8), 577
- sulfur-based materials, 731
- sulfur-doped graphenes, 573
- sulfuric acid
  - voltammetric cycling, 383
- supercapacitors, 377, 380, 382, 391, 404, 485, 501, 651, 728
  - benefits, 391
  - characteristic, 391
  - devices, 400, 405
  - double-layer charge storage, 393
  - electrode, 397
  - electrolytes, 399, 405
  - energy storage mechanisms, 393
  - interfaces, modeling efforts, 409
  - nanostructured electrode materials, 395
  - performance, 379
  - properties, 391
  - with symmetric electrodes, 398
  - theory, 409
- supercritical water-cooled reactor (SCWR), 271
- superheaters, 308
- superhydrophobic
  - condensation, 305
  - nanostructured surface, 975
  - titanium coatings, 289
- superimposed J–V curves of the individual TiO<sub>2</sub>@BiVO<sub>4</sub> photoanode and PSC device, 632
- superlattices, 511
- supersaturation, 120, 859, 862
- superspace symmetry, 764
- superthin nanotube sheet, 989
- supplementary cementing materials, 983
- supported ionic liquid phase, 928
- surface carbon gasification, 71
- surface energy density, 42
- surface localized plasmons, 301
- surface mechanical attrition treatment (SMAT), 334
  - strength–formability relationship, 335
- surface modification
  - of materials, 285
- surface passivation, 169
  - advantages, 168, 169
  - nanostructures for, 168
- surface plasmons, 149, 150
  - polaritons, 196, 197
  - resonance, 122
- surface-protected Cu<sub>2</sub>O electrode, 640
- surface recombination effects, 869

- surface reflectance, 208
  - surface roughness effect, 876
  - surface-to-volume ratio, 861
  - SWCNH nanoinclusions, SEM visualization of, 467
  - switching energies, of microprocessors, 690
  - SWNT-COOH functionality, 572
  - SWNT-PCM composites, 469
    - chemical structures and synthetic scheme, 472
  - symmetric conic-section flexure hinge, parameters defining, 667
  - synthetic amorphous silica, 913
  - synthetic gypsum, 988
  - synthetic polyalphaolefin oil-based MWCNTs nanofluid, 1008
- t**
- TALK operation, 682
  - taming lithium, 364
  - tandem GaAs/GaInP<sub>2</sub> solar cell, 642
  - tandem PV–electrolysis (or PEC–electrolysis) system, 642
  - Tanner, Fung, Virkar (TFV) model, 580
  - TbS–CrS<sub>2</sub> nanotubes, 769
  - T–C diagram for asphaltene nanophases, 51
  - telluride, 235
  - temperature-programmed oxidation (TPO), 75
  - templated carbon, 395
  - tensile ductility values, 716
  - tension-compression yield symmetry, 817
  - ternary oxide compounds, 771
  - tetrabutylammonium, 5
  - tetraethoxysilane, 212
  - tetraethylammonium tetrafluoroborate ([TEA]–[BF<sub>4</sub>]), 399
  - tetraethylphosphonium tetrafluoroborate ([P(C<sub>2</sub>)<sub>4</sub>]–[BF<sub>4</sub>]), 399
  - tetrafluoroborate (BF<sub>4</sub>), 400, 407
  - tetrahydridoaluminate ion, 421
  - tetrahydridoborate ion, 421
  - tetrahydroborate complex anion BH<sub>4</sub><sup>–</sup>, 426
  - tetramethylbenzenes, 19
  - tetra-n-butylphosphonium acetate, 929
  - tetrapropylammonium, 5
  - TFSI<sup>–</sup> anion, 402
  - theoretical stress, 668
    - values, 667
    - vs. FEM stress, comparison of, 668, 669, 671
  - thermal annealing method, 195, 768, 771
  - thermal conductivity (TC), 45, 300, 313, 461, 475, 512, 516, 517, 518, 519, 523, 529, 872, 913, 918, 919, 921, 922, 928, 940, 944, 1002
    - in aerogels, 944
    - enhancement ratio, 893
    - as function of roughness factor, 876
    - heat capacity per unit volume, comparison of, 890
    - of MWCNT-modified water-based drilling muds, 45
    - of pressurized sintered SiGe alloy, 524
    - of p-type Hf<sub>0.5</sub>Zr<sub>0.5</sub>CoSb and n-type Hf<sub>0.5</sub>Zr<sub>0.5</sub>NiSn, 528
  - thermal conductivity enhancement
    - for [C<sub>2</sub>mim][C(CN)<sub>3</sub>], 923
    - for ionic liquids, 923
  - thermal conductivity materials, 940
    - of PCMs, 461
    - Si/Ge/GaAs NWs
      - effect of roughness root mean square, 875
  - thermal containment unit, 464
  - thermal emissivity, 929
  - thermal emittance, 233, 241
  - thermal energy storage (TES), 459, 511
    - density, 472
  - thermal expansion
    - anisotropic crystal structure/coefficient, 341
    - coefficient, 532
    - of PdS and SnS<sub>2</sub> subsystems, 774
  - thermal insulation, 939
    - aerogel property, 944
    - applications, 954
      - aerospace, 29, 958
      - architectural, 29, 955
      - automotive, 29, 957
      - cold storages and cryogenic insulation, 29, 957
      - defense, 29, 958
      - industrial, 954
      - textiles, 29, 959
    - materials, 939, 940
      - commercially used, 941
  - thermal insulator, 972
  - thermal interface material (TIM), 895, 898
  - thermally stable electrolytes, 368
  - thermal management, 510, 904
    - applications, 510
  - thermal performances, 306
  - thermal radiative losses, 237
  - thermal resistance values, 971
  - thermal stability, 209, 222, 232, 304, 465, 831, 928, 940
    - of W–SiCH multilayer coatings, 242
  - thermochromic technologies, 986
  - thermoelectric components
    - of H<sub>2</sub> production, 250

- p- and n-type, 548
- thermoelectric cooler, 871, 873
- thermoelectric devices, 764, 862, 871
  - real application, 879
- thermoelectric effects
  - introduction of, 871
- thermoelectric energy, 649
- thermoelectric generators, 650
  - energy generator, 872
- thermoelectricity (TE), 509
  - development, 511
  - materials, 311, 514, 524, 550, 764
  - nano materials materials, 22, 518
- thermoelectric modules, 509, 512, 871
- thermoelectric optimization, 514
- thermoelectric parameters, 516
- thermoelectric power, 516
  - factor, 876
  - generation, 873
- thermoelectric systems, 510, 511
- thermogravimetric analysis (TGA), 75
- thermophilic temperatures, 250
- thermophotovoltaic energy, 83
- thermoplastics, 325, 834
- thermosets, 325
- thermosyphon effect, 895
- Thiele modulus, 21
- thin [C<sub>2</sub>mim] [(CF<sub>3</sub>SO<sub>2</sub>)<sub>2</sub>N] film coated onto CNTs, 928
- thin-film coatings, 985
- thin-film insulation, 971
- thin-film silicon anodes, 359
  - specific capacity, 359
- thin-film solar cell
  - five functionalities, prototypical layer sequence for, 182
  - nanostructured coatings for, 171
  - organic solar cells, 969
  - technologies, 135, 176, 973
- thiourea, 620
- third-generation solar cells, 102
- Ti/AlTiN/AlTiON/AlTiO coatings, 237
- Ti(C, O, N)/a-C:H nanocomposite depicting
  - schematic multicomponent, 290
- Ti(C, O, N)/a-C:H thin film, 289
- Ti doping in MoS<sub>2</sub> nanotubes, 758
- TiFe alloys
  - discharge capacities, 441
  - electrochemical isotherms pressure-composition, 441
  - powder, 442
- TiFe<sub>0.25</sub>Ni<sub>0.75</sub> nanopowders
  - on hydrogen storage behavior, 455
  - pressure-composition isotherms, 456
- TiFe<sub>0.25</sub>Ni<sub>0.75</sub> phase, 442, 455
- Ti/Fe powders
  - XRD spectra, 440
- TiFe<sub>1-x</sub>Ni<sub>x</sub> alloys, 442
- tight-binding method, 876
- tin dioxide nanofacets (SnO<sub>2</sub>NFs), 573
- TiNi<sub>0.6</sub>Fe<sub>0.1</sub>Mo<sub>0.1</sub>Cr<sub>0.1</sub>Co<sub>0.1</sub> powder, 443
- TiNi(Fe) phase, 455
- tin oxide (SnO<sub>2</sub>) nanocrystals, 1127
- Ti–O–Fe nanotubes, 606
- Ti, on glass plate
  - schematic, 114
- titanate route, 112
- titania inverse photonic, FESEM image, 109
- titania nanotubes, 114
  - absorption spectra and photographs, 611
- titanium dioxide (TiO<sub>2</sub>), 43, 69, 980
  - BiVO<sub>4</sub> photoanode, 644
  - electrodes, for photocatalytic H<sub>2</sub> production, 262
  - fibers, SEM image, 111
  - flower-shaped, SEM image, 113
  - hollow sphere, SEM images, 107
  - HRTEM/FESEM images, 288
  - leaf-shaped, SEM image, 111
  - membranes, 1148
  - Mie coating, 171
  - on MWCNT
    - FESEM image, 116
  - nanofibers, 113
  - nanofluids, 999
  - nanoparticles, 44, 50
  - nanorods, 114, 115
  - nanospider film grown, on FTO glass
    - SEM images of, 604
  - nanospider morphology
    - optical micrograph of, 604
  - nanotube array by anidization of Ti foil
    - FESEM image, 114
  - nanotubes grown, on conducting glass
    - SEM, 114
  - nest shaped, SEM image, 113
  - particles by molten salt method
    - SEM images, 107
  - surface morphologies and cross sections of, 605
  - thermal conductivity, 1000
  - TiSi<sub>2</sub> heterostructures, structure of, 612
  - transition metal doping of, 606
- TMD. *see* transition metal dichalcogenide
- TNTs, absorption spectra/photographs of, 611
- topological dimension, 782

- insulators, 534, 535
  - surface state, 535
  - total cell potential, 406
  - total power consumption
    - by information and communication technologies, 680
  - total reflectance, 870
  - total thermal conductivity, 944
  - tower configurations, 324
  - toxic battery chemicals, 977
  - toxin-sniffing nanosensors, 968
  - trailing-edge flaps, 329
  - transformation-induced plasticity (TRIP), 715
    - effect of, 715, 716, 719
  - transformation temperature, 714
  - transformer oil (TO), 999
  - transforming nonselective to selective coating, 222
  - transistors, 485
  - transition metals, 65
    - based materials, 236
    - carbides, 398
    - component, 65
    - dichalcogenides, 398, 746
    - oxides, 236
  - translucent systems, 989
  - translucent wall panels, 970
  - transmission electron microscope (TEM), 71, 189, 195, 745
  - transparent carbon nanotube sheets, 989
  - transparent conducting substrate, 104
  - transparent/conductive front electrodes, 185
  - transparent conductive oxide (TCO), 164, 167, 197
  - transport agent, 747
  - transport industry, 831
  - triangular  $\text{MoS}_{2-x}$  nanostructures, 750
  - trichalcogenides, decomposition of, 747
  - trichloroethylene (TCE) mineralization, 1142
  - triethylmethylammonium tetrafluoroborate ( $[\text{TEMA}][\text{BF}_4]$ ), 399
  - tri-n-octylphosphineoxide (TOPO), 120
  - trivalent erbium, 153
  - trivalent rare-earth materials, 528
  - tube collector designs, evacuation of, 224
  - tubular structures/common by-products, SEM images of, 768
  - tubule's agglomerate
    - secondary electron image of, 766
  - tunable fluorescence, 120
  - tungsten carbide (WC), 435
    - coated balls, 437
  - tungsten–halogen lamp, 642
  - tungsten oxide, 968
  - tungsten–SiCH composite, 243
  - tungsten–silicon carbide (W–SiC)-based coatings, 232
  - tunneling emission microscopy (TEM), 919
  - turbine
    - generated electricity, 323
    - lifetime, 326
    - in wind farms, 327
  - turbo engines, thermal protection, 846
  - turnover frequency (TOF), 1120
  - turnover number (TON), 1120
  - two-layer daughter nanoscroll, HRTEM of, 750
  - type II heterojunction, band diagram of, 193
  - typical HRTEM image, XRD pattern, 634
- u**
- UASB reactor, used for  $\text{H}_2$  production, 264
  - UC layers absorb photons, upconversion process, 153
  - UGF-CNT-erythritol composite, 469
  - UGF-wax composite, 471
  - ultimate tensile strength (UTS), 715
  - ultracapacitors, 393, 1100
  - ultrafine-grained AZ61 alloy, 810
  - ultralight panels, 988
  - ultranano-crystalline chemical deposition (UNCD), 786
  - ultraporous cellulose (UPC), 1152
  - ultrasonic
    - agitation, 915
    - assisted stirring, 841
    - bath, 916
    - cavitation, 811
    - energy methods, 915
  - ultrasound techniques, 929
  - ultrathin bilayer electrolytes, 582
  - ultrathin-graphite foam (UGF), 469
  - ultraviolet, 631
    - illumination, 1148
    - NIR spectroscopies, 918
    - visible spectrum, 122
  - Umklapp processes, 553
  - unilamellar MFI zeolite, 27
  - US-published Patent Application 2013/0216390
    - for production of carbon nanotube-reinforced wind turbine blade, 1094



## v

VACNT. *see* vertically aligned carbon nanotube  
 vacuum-assisted resin transfer molding (VARTM), 334, 1098  
 vacuum evaporation, 215  
 vacuum insulation panel (VIP), 475, 971  
 vacuum permeability, 84  
 value-added chemicals  
 – converting CO<sub>2</sub>, challenges of, 1110  
 Van Der Walls (VDW), 918  
 – forces, 305, 496, 746, 764, 774  
 – interactions, 753, 1017  
 – – dispersion, 416  
 – solids, 397  
 Van't Hoff equation, 419  
 vapor barrier property, 940  
 vapor-deposited thin films, 786  
 vapor–liquid–solid (VLS) method, 147, 858, 862  
 vapor–solid–solid (VSS), 147  
 – growth technique, 862  
 variable-pitch drive systems, 336  
 variable profile thickness, of metal shim, 666  
 – elliptical profile, 666  
 – parabolic profile, 668  
 – tapered profile, 669  
 vermiculite, 1141  
 vertically aligned carbon nanotubes (VACNT), 377, 578, 1146  
 – coated electrodes, 381  
 vertically aligned TiO<sub>2</sub> nanostructures, 113  
 very high-temperature reactor (VHTR), 271  
 vinyl (polyvinyl chloride (PVC)), 986  
 virus template approach, schematic, 117  
 visible light photocatalysis, 979  
 VLS. *see* vapor–liquid–solid  
 VOC. *see* volatile organic compound  
 vortex fluidic device (VFD), 572

## w

Walden inversion, 749  
 W/AlSiN/AlSiON/SiO<sub>2</sub> tandem absorber selective coatings, 237  
 waste heat, in automotive, 510  
 waste stream greenhouse CO<sub>2</sub> gas, 1109  
 water and liquid metal, comparison, 893  
 water-based  
 – Ag<sub>2</sub>Al nanofluid, 1002  
 – aggregating (TiO<sub>2</sub>), 1000  
 – Ag–HEG hybrid nanofluid, 1014  
 – Ag–MWNT hybrid nanofluid, 1013  
 – alkaline electrolysis, 597  
 – Al<sub>2</sub>O<sub>3</sub> nanofluids, 1004

– CNT–AuNP hybrid nanofluids, 1013  
 – CuO–HEG, 1014  
 – exfoliated graphene nanofluid, 1012  
 – Fe<sub>3</sub>O<sub>4</sub> nanofluids, 1002  
 – gold nanofluids, 1001  
 – nanofluids, thermal conductivity with temperature, 1005  
 – silica–MWCNT hybrid nanofluid, 1014  
 – TiO<sub>2</sub> nanofluids, 1000  
 – untreated diamond nanofluids, 1005  
 water conservation, 30, 979  
 water contaminants, 980  
 water-free deposition environment, 142  
 water-in-oil emulsions, 1140  
 water–oil filtration process, 1150  
 water–oil separation, 1141  
 water oxidation reaction, 1114  
 water purification, 979  
 water-soluble surfactants, 919  
 water splitting, 629, 630  
 – on TiO<sub>2</sub> surface in response to light energy, 264  
 water sweeping, 308  
 watertight lithium-ion conducting membranes, 310  
 WC-Co cemented carbides, 340  
 Weibull modulus, 339, 340  
 weight-induced fatigue loads, 330  
 well-dispersed MWCNTs, 1017  
 wet-chemical method, 212  
 wettability, 49  
 – alteration by nanoparticles, 49  
 wetting angle, 860  
 whole rate spectrum, 408  
 Wiedemann–Franz law, 514, 881  
 wind blades, 324  
 – lightning receptors, 334  
 wind energy applications, 296, 323, 326, 1079, 1080, 1100  
 – aeroacoustic properties, 327  
 – aerodynamics properties, 326  
 – aeroelastic properties, 328  
 – bulk nanocrystalline ceramics, 338  
 – challenges, due to agglomerated powders, 338  
 – fatigue properties, 18, 329  
 – future development and directions, 1100  
 – high strength requirement, 331  
 – material selection criteria, 329  
 – polymer-based lightweight materials, 332  
 – processing-related challenges, 336  
 – steels/conventional materials, 335

- ultrafine grained/nanostructured materials, 336
  - wing-shaped blades, 323
  - wind energy industry, 323
    - cost reductions, 1080
    - high-performance nanostructured materials, 1080
    - optimization of wind farm, 1080
    - requirements, 1080
  - wind energy-related research, 323
  - wind mills, 325
  - wind park effects, 326
  - wind power, 323
    - capacity, 1079
  - wind shear, 329
    - effect, 331
  - wind turbine, 335, 1080
    - blade, 1100
    - – aerodynamics, 326
    - components, commercialization, and potential of nanotechnology, 1083
    - related aerodynamic research, 326
    - schematic diagram, 324
  - winter heating season, 977
  - wireless sensor network (WSN), 510, 650
  - WO<sub>3</sub>/MoO<sub>3</sub> nanopowders, 751
  - wood performance, 984
  - WO-published Patent Application 2009/038971, 1098
  - World Energy Outlook (WEO), 1109
  - World Health Organization, 979
  - world's technological information-processing capacity, trend in, 683
  - WRITE operation, 682
  - W–SiCH multilayer stacks
    - optical modeling and synthesis of, 239
  - W/SiCH/W/SiCH four-layer stack reflectance, comparison of, 241
  - W–SiC multilayers, 232
  - W–SiCNH nanocomposite, 242
  - WS<sub>2</sub> nanotubes, 748, 757
    - SEM and TEM images of, 748
    - synthesis, 754
  - Wulff construction, 15
- x**
- xerogels, 1155
  - XPS spectra of Ni/MgAl<sub>2</sub>O<sub>4</sub> sample, 77
  - x-ray absorption fine structure (XAFS), 758
  - x-ray diffraction (XRD) method, 76, 818
    - profiles of spent catalyst, 77
  - x-ray photoemission spectroscopy (XPS), 76, 437
  - p*-xylene, 23
- y**
- Yb<sub>3</sub>Co<sub>4</sub>Sb<sub>12</sub> nanocomposite, 530
  - YDT-based oxygen sensor assembly, 285
  - Young's modulus, 727, 810
  - yttria (Y<sub>2</sub>O<sub>3</sub>), 838
    - nano-oxides of, 303
  - yttria-doped thoria (YDT)
    - nanocrystalline electrolytic-grade, 284
  - yttria-doped zirconia (YSZ), 69, 580, 581
    - matrix, SEM images, 581
- z**
- zeolite frameworks
    - synthesis of, 13
  - zeolites, 3, 20, 1170
    - vs. carrier concentration, 877
    - catalysts, 30
    - crystallization, 7, 13
    - crystals, 6, 7, 13, 19
    - 1D, 15
    - 2D, 9
    - dependence on Ge content, 878
    - enhancement, 556
    - growth modifiers, 12
    - materials, 27
    - morphologies, 14, 15
    - nanocrystals, 20
    - nanostructure, 4
    - pores, 19
    - synthesis, 3
    - – gel chemistry, 14
    - zeotype material, 20
  - zero-strain, 360
  - zero-valent iron, 1141
  - zeta potential, 918
    - determination, 918
    - measurements, 919
  - zinc oxide, 613
    - composites, synthetic step, 620
    - nanocolumns, 146
    - nanoparticles, 46
    - nanorods, 613
    - – arrays, 1150
    - – SEM images of, 1151
    - nanostructure array
    - – cross-sectional SEM images of, 617
    - nanotube
    - – TEM images of, 614
    - nanowires, 616
    - – Fe<sub>2</sub>O<sub>3</sub> core-shell, 613
    - titania nanotube, 613
  - zintl phases, 519
  - zirconium alloys, 273

- $\beta$ -Zn<sub>4</sub>Sb<sub>3</sub>, 22, 524
  - Seebeck coefficient, 524
- ZrN films, 287
- ZrO<sub>2</sub>(3Y) nanopowders, TEM image, 337
- Zr<sub>0.35</sub>Ti<sub>0.65</sub>V<sub>0.85</sub>Cr<sub>0.26</sub>Ni<sub>1.30</sub> alloy, 445
  - discharge capacity, 446
  - electrochemical pressure-composition isotherm, 445
- ZrV<sub>2</sub> alloy, 444
  - nanopowder, 453
- Zr, XRD spectra of, 444
- Z-scheme mechanism, 630, 635
  - ZnO/CdS nanocomposites, 635
- ZSM-5 zeolites, 23
  - crystals, 9, 23
  - deactivation, 24
  - nanocrystal, 9
  - samples, synthesis, 24
- ZT<sub>Max</sub>
  - p-type and n-type superlattice NWs, 878
- ZT values, 530
  - maximum achievable for respective length scales, 522

