

## Index

### a

- Adiabatic Longitudinal Transport
  - After Dissociation Engenders Nuclear Alignment (ALTADENA) 306
- aluminum–nickel–cobalt (AlNiCo) magnets 11
- asymptotic waveform evaluation (AWE) 30

### b

- back-end-of-line (BEOL) 147
- bipolar complementary metal oxide semiconductor (BiCMOS) technologies
  - low-noise amplifier (LNA) design process 149
  - narrowband applications 163–167
  - wideband and applications 156–163
  - low-noise behavior 150
  - optimum transconductance 150
  - transit frequency 150
- Bode–Fano criterion 280
- broadband microcoil system
  - broadband detection 276
  - chip and probe setup 269
  - coil geometries 266
  - deuterium spectra 267
  - electroplating 268
  - heteronuclear 1D NMR experiments 273
  - homonuclear 1D NMR experiments 269–272

- impedance matching and front-end electronics
  - coil impedance transformation network 278
  - coil *Q*-factor 280
  - conventional matched excitation scheme 280–281
  - detection schemes 281
  - Hall effect 278
  - H-bridge amplifier 283–284
  - LNA bandwidth 285–286
  - LNA input voltage 283
  - magnetoresistive effects 278
- impedance transformation 277
- inductance vs. frequency 275
- self-resonance frequency 275, 276
- solenoid and planar spiral 267
- 2D homo- and heteronuclear experiments 273

### c

- capacitive coupling 60
- catheter receivers
  - $B_1$ -field decoupling 241–242
  - designs 238–239
  - E*-field decoupling 242–244
  - elongated loop receivers 239–240
  - internal imaging 238
  - magnetic resonance imaging
    - EBG detectors 256–257
    - MI detectors 257–258
    - resonant detectors 255–256
  - thin-film catheter receivers
    - MR-safe thin film interconnects 246–248

- catheter receivers (*contd.*)
    - thin-film coils 244–245
    - thin-film interconnects 245–246
    - tuning and matching 240–241
  - center-field magnets
    - compact NMR 11–13
    - Halbach magnet 9
    - passive shimming 10
  - CMOS *see* complementary metal oxide semiconductor technologies (CMOS)
  - coil fabrication techniques, miniaturized
    - MR detectors
    - high filling factor microcoils 128–130
    - ink-jet printing
      - electroplating 133
      - functional ink-jet printing 132
      - graphical ink-jet printing 132
      - three-dimensional structures 132
      - UV-based lithography technique 133
    - MACS technique 115–123
    - micro-Helmholtz coil pairs 123–128
      - magnetic field profile 124–125
      - in magnetic resonance 123–124
      - micromachining of 125–128
    - wire-bonding
      - bicone microcoils 112
      - coil-winding machines 110
      - dry-photoresist lamination 114
      - flexibility and cost-effectiveness 109
      - microcoil manufacturing 109
      - microcontact printing 110
      - micro-Helmholtz detector 114
      - quasi-planar combinations 114
      - reactive ion etching (RIE) 110
      - solenoidal microcoils 112, 113
      - spiral planar microcoils 110
      - 3D printer 112
      - 3D trajectory 109
      - 2D techniques 113
  - complementary metal oxide semiconductor technologies (CMOS)
    - back-end-of-line (BEOL) 147
    - extrinsic effects 146
    - frequency division multiplexer (FDM)
      - bandpass filter 66–67
      - frequency mixer 65–66
      - low-noise amplifier (LNA) 64–65
      - MRI experiment 68–70
    - integrated circuits 63
    - inter-metal dielectric (IMD) 148
    - linear mode of operation 145
    - low-noise amplifier (LNA) 145
      - narrowband applications 163–167
      - for wideband applications 158–161
    - metal–insulator–metal (MIM) capacitor 148
    - MOSFET behavior 145
    - NMOS and PMOS transistors 145
    - photolithographic process 144
    - power amplifier (PA) 145
    - saturation mode 145
- d**
- direct coupling 60
  - discretized Maxwell's equations
    - Arnoldi mathematical algorithm 26
    - Berenger's PML 28
    - conductivity parameters 26
    - electromagnetic interactions 26
    - first-order differential state–space system 26
    - integral equation techniques 23
    - Laplace domain 23
    - magnetic and electric conductivities 24
    - magnetic field components 25
    - partial differential equation (PDE) 24
    - perfect electric conductors (PECs) 26
    - uniaxial perfectly matched absorbing layers (UPML) 27
    - Yee algorithm 23
  - DNP *see* dynamic nuclear polarization (DNP)
  - double-quantum magnetometry 414
  - 3D solenoidal microcoils 109

- dual-coil chip 269
- dynamic nuclear polarization (DNP)
  - 297
  - electron donor 298
  - instrumentation 302–304
  - microtechnological approaches
    - alkali metals and noble gases 313
    - high-field DNP resonators 314–318
    - low-and intermediate-field DNP 318–322
    - low-power and compact solid-state MW sources 312
    - MEMS technologies 313–314
    - microfluidics and 322–323
  - microwave (MW) irradiation 297
  - polarization transfer 301
  - theoretical enhancement factor 298
- e**
- E*-field decoupling 242–244
- electromagnetic bandgap (EBG)
  - detectors 256–257
- electron paramagnetic resonance (EPR)
  - sensors
  - MOR model 21
    - asymptotic waveform evaluation (AWE) 30
    - degrees of freedom (DOF) 30
    - discretized Maxwell's equations 23–29
    - Gram–Schmidt process 32
    - Krylov subspace algorithms 31
    - Lanczos method 32, 33
    - Laplace domain impulse response 29
    - nonsymmetrical Arnoldi algorithm 31
    - Padé approximation 31
- elongated loop receivers 239–240
- f**
- ferromagnetic resonance (FMR) 387
- finite difference frequency domain (FDFD) method 22
- force-detected nuclear magnetic resonance (NMR)
  - AFM 381
  - “Boomerang” experiment 389
  - diphenylpicrylhydrazyl (DPPH) 387
  - displacement oscillations 387
  - ferromagnetic resonance (FMR) 387
  - magnetic resonance force microscopy (MRFM) 382
  - microfabricated cantilevers and nanoscale ferromagnets 387
  - nanometer-scale polystyrene sample 389
  - nanowire (NW) transducer 389
  - pulsed magnetic resonance schemes 389
  - radio-frequency (RF) magnetic field 382
  - scanning probe microscopy (SPM) 382
  - sensitive transducers 386
  - signal-to-noise ratio (SNR) 385
  - single electron spin detection 388
  - statistical fluctuations 387
  - 3D image reconstruction technique 388
- frequency division multiplexer (FDM)
  - bandpass filter 66–67
  - frequency mixer 65–66
  - low-noise amplifier (LNA) 64–65
  - MRI experiment 68–70
- g**
- gradient echo-based imaging
  - EPI 219–220
  - FLASH-type gradient echoes 214–219
- Gram–Schmidt process 32
- h**
- Hall effect 278
- high-field magnets 1
- hyperpolarization methods 2
- hyperpolarization techniques
  - dynamic nuclear polarization (DNP)
    - electron donor 298
    - instrumentation 302–304
    - microtechnological approaches 312–323

- hyperpolarization techniques (*contd.*)
    - microwave (MW) irradiation 297
    - polarization transfer 301
    - theoretical enhancement factor 298
  - hydrogenative PHIP 298
  - metabolomics 299
  - microtechnology 299
  - para*-hydrogen-induced polarization (PHIP) 298
    - ALTADENA 306
    - antiisymmetric wave functions 304
    - Born–Oppenheimer approximation 304
    - exothermic conversion process 306
    - level anticrossing (LAC) condition 308
    - microtechnological approaches 324–333
    - ortho-to-*para* conversion rate 305–306
    - PASADENA 306
    - Pauli’s principle 304
    - SABRE method 308
    - thermal H<sub>2</sub> molecule 306
  - SABRE 298
  - spin-exchange by optical pumping (SECOP)
    - alkali metal atomic energy levels 310
    - collisional interactions 309
    - hardware requirement 312
    - parameter descriptions 310
    - photon reemission 310
    - rubidium and cesium 312
    - spin–orbit coupling 310
    - <sup>129</sup>Xe and <sup>3</sup>He polarization 312
    - xenon application 300
  - hyphenation
    - capillary isotachopheresis (CITP) 354
    - chip-based microseparations 355
    - continuous monitoring of *in situ* biological systems 368
    - electrically driven microseparations
      - capillary electrophoresis NMR 360–362
      - capillary isotachopheresis NMR 362–363
    - flowcells and micro channels 370–371
    - in-line ultraviolet/visible light detector 354
    - microfluidic mixing and reaction kinetics 368, 370
    - off-line hyphenation
      - EC–SPE–stripline-NMR setup 367
      - flow-loading micro samples 365
      - fused silica capillaries 368
      - high chromatographic resolution 364
      - LC-MS-NMR platform 366
      - LC-UV-MS-NMR platform 367
      - microdroplet techniques 363
      - nano-Splitter LC-MS method 364
      - segmented flow 354
      - stripline detector 364
      - zero-dispersion segmented flow 363
    - optimum approach 353
    - pressure-driven microseparation
      - capillary gas chromatography 358
      - capillary high-pressure liquid chromatography 357–359
    - radio-frequency coils geometries
      - planar coils 356
      - solenoids 355–356
      - stripline and microslot resonators 357
- i**
- inductive coupling 60
  - ink-jet printing
    - electroplating 133
    - functional ink-jet printing 132
    - graphical ink-jet printing 132
    - three-dimensional structures 132
    - UV-based lithography technique 133
  - integrated circuits (ICs)

- CMOS 63
  - intravascular NMR systems 173
  - monolithic transceiver electronics,  $\mu$ NMP applications 151–155
  - MR imaging and microscopy systems 171–173
  - NMR spectroscopy 170–171
  - portable NMR systems 167–169
  - technological considerations and device models
    - BiCMOS technology 148–150
    - complementary metal oxide semiconductor technologies (CMOS) 143–148
- k**
- Krylov subspace method 31
  - k*-space imaging
    - FOV 203
    - frequency spectrum 201
    - Larmor frequency 200
    - nonuniform fast Fourier transform (NUFFT) 204
    - Nyquist theorem 201
- l**
- Lanczos method 32, 33
  - level anticrossing (LAC) condition 308
  - low-noise amplifier (LNA)
    - BiCMOS technologies
      - design process 149
      - narrowband applications 163–167
      - for wideband applications 156–163
    - CMOS technologies 145
      - narrowband applications 163–167
      - for wideband applications 158–161
- m**
- magic angle coil spinning (MACS) technique
    - anisotropic spin interactions 115
    - automatic wire-bonding process 119
    - coil-winding process 120
    - conventional CPMAS 119
    - cost of inductive coupling 116–117
    - double-resonant MACS insert 120–123
    - efficiency approaches 116
    - Larmor frequency 116
    - NMR experiments 118
    - solid-state NMR spectroscopy 115
    - wafer-level process 119
    - wire-bonded MACS resonators 120
  - magnet development
    - magnet construction and passive shimming 11
    - permanent magnet materials 10–11
  - magnetic resonance force microscopy (MRFM)
    - AFM cantilever 382
    - cantilever's mechanical oscillations 382
    - cryo-electron microscopy 415
    - 2D nano-MRI 414
    - double-quantum magnetometry 414
    - fluorescent labeling 412
    - magnetic field gradients 398–400
    - magnetic fields and Fourier transform techniques 382
    - measurement protocols 405–408
    - mechanical transducers 400–405
    - nuclear magnetization 413
    - nuclear MRI, with nuclear spin imaging organic nanolayers 396–398
    - micro-fabricated components 391
    - MRI resolution 391–392
    - virus particles 392–396
  - NV center 412–413
  - polymer films and self-assembled monolayer 416
  - radio-frequency (RF) magnetic field 382
  - single-electron MRFM
    - mass-loaded cantilevers 389
    - OSCAR 389

- magnetic resonance force microscopy (MRFM) (*contd.*)
  - TMV experiment 398
  - Zeeman splitting 382
- magnetic resonance imaging
  - EBG detectors 256–257
  - MI detectors 257–258
  - resonant detectors 255–256
- magnetic resonance microsensor
  - compact model simulation results 46
  - device–circuit co-simulation 46–54
  - model description 40–42
  - parametric model order reduction 43–45
- microarrays
  - brain-imaging array 60
  - capacitive coupling 60
  - direct coupling 60
  - geometrical configuration 59
  - inductive coupling 60
  - microfabrication techniques
    - conventional printed circuit board (PCB) technology 61
    - decoupling 62
    - solenoidal microcoils 63
    - thin film technology 62
  - mutual coupling 60
  - RF array coils 60
  - single-array coils 59
- microcoils
  - broadband microcoil system
    - broadband detection 276
    - chip and probe setup 269
    - coil geometries 266
    - deuterium spectra 267
    - 2D homo- and heteronuclear experiments 273
    - electroplating 268
    - heteronuclear 1D NMR experiments 273
    - homonuclear 1D NMR experiments 269–272
    - impedance matching and front-end electronics 276–287
    - impedance transformation 277
    - inductance vs. frequency 275
    - self-resonance frequency 275, 276
    - solenoid and planar spiral 267
- microfabrication techniques
  - conventional printed circuit board (PCB) technology 61
  - decoupling 62
  - solenoidal microcoils 63
  - thin film technology 62
- micrometer-scale yttrium iron garnet (YIG) film 387
- microscopic flow imaging techniques
  - experimental setup 186
  - limitations
    - spatial resolution 185–186
    - temporal stability 184
    - velocity range 183–184
- liquid exchange in aneurysm models
  - methods 186–187
  - optimization, of sequence parameter 189
  - results 187–189
- mean flow 182
- PC measurements, with constant flow
  - flow and wall shear stress, aneurysm model 190–193
  - laminar flow in pipe 189–190
- phase contrast 181–182
- pulsatile flow
  - dark curve marking 193
  - data acquisition 192
  - repetitive flow patterns 192
  - ToF technique 193
  - volume flow 194
  - time of flight 180–181
- miniaturization 11, 13, 16
- model order reduction (MOR)
  - EPR resonators, fast simulation of 21
  - asymptotic waveform evaluation (AWE) 30
  - degrees of freedom (DOF) 30
  - discretized Maxwell's equations 23–29
  - Gram–Schmidt process 32
  - Krylov subspace algorithms 31
  - Lanczos method 32, 33

- Laplace domain impulse response 29
- nonsymmetrical Arnoldi algorithm 31
- Padé approximation 31
- magnetic resonance microsensor,
  - system level simulation
  - compact model simulation results 46
  - device–circuit co-simulation 46–54
  - model description 40–42
  - parametric model order reduction 43–45
- planar coil EPR resonator 34–39
- structure-preserving model order reduction 33–34
- mutual coupling 60
  
- n**
- neodymium–iron–boron (NeFeB) magnets 11
- nuclear magnetic resonance imaging
  - nanowire force sensor 408–411
  - with nuclear spin
    - imaging organic nanolayers 396–398
    - micro-fabricated components 391
    - MRI resolution 391–392
    - virus particles 392–396
- nuclear magnetic resonance (NMR)
  - microscopy
  - contrast mechanisms
    - $T_2^*$ -decay 207–211
    - $T_1$ -relaxation 206–207
    - $T_2$ -relaxation 207
  - diffusion 221–229
  - gradient echo-based imaging
    - EPI 219–220
    - FLASH-type gradient echoes 214–219
  - $k$ -space imaging
    - FOV 203
    - frequency spectrum 201
    - Larmor frequency 200
  - nonuniform fast Fourier transform (NUFFT) 204
  - Nyquist theorem 201
  - motion artifacts and compliance 199
  - pulse sequences
    - 3D acquisition 211
    - sampling efficiency 212
    - spin echo sequences 212–214
  - slice selection 204–206
  - susceptibility mapping and QSM 231–232
  - time-of-flight imaging 230
  - ultrashort TE 220–222
  - velocity phase imaging 229–230  
- o**
- off-line hyphenation
  - EC–SPE–stripline-NMR setup 367
  - flow-loading micro samples 365
  - fused silica capillaries 368
  - high chromatographic resolution 364
  - LC-MS-NMR platform 366
  - LC-UV-MS-NMR platform 367
  - microdroplet techniques 363
  - nano-Splitter LC-MS method 364
  - segmented flow 354
  - stripline detector 364
  - zero-dispersion segmented flow 363
- Overhauser’s theory 297
  
- p**
- Padé approximations 31
- Parahydrogen and Synthesis Allow Dramatically Enhanced Nuclear Alignment (PASADENA) 306
- para*-hydrogen-induced polarization (PHIP) 298
  - ALTADENA 306
  - antisymmetric wave functions 304
  - Born–Oppenheimer approximation 304
  - exothermic conversion process 306
  - level anticrossing (LAC) condition 308
  - microtechnological approaches

- para*-hydrogen-induced polarization (PHIP) (*contd.*)
    - catalyst solubility in water 331
    - gas-phase characterization 324–327
    - liquid phase 327–330
    - quantification 331–332
    - SABRE method 330–331, 332–333
  - ortho-to-*para* conversion rate 305–306
  - PASADENA 306
  - Pauli's principle 304
  - SABRE method 308
  - thermal H<sub>2</sub> molecule 306
  - parametric model order reduction (pMOR) method
    - Arnoldi method 45
    - frequency moments 43
    - Krylov techniques 44–45
    - Laplace variable 43
    - system transfer function 43
  - passive shimming
    - center-field magnets 10
    - strategies for 13–14
  - permanent magnets
    - center-field magnets
      - Halbach magnet 9
      - passive shimming 10
    - homogeneity and lower field 3
    - stray-field magnets
      - bulk-volume analysis 7–8
      - classification 5–6
      - 1D and 2D Imaging 6–7
  - pulse sequences
    - sampling efficiency 212
    - spin echo sequences 212–214
    - 3D acquisition 211
- r**
- reactive ion etching (RIE) 110
  - resonant detectors 255–256
- s**
- Samarium–cobalt (SmCo) magnets 11
  - shim coils 14–16
  - spatial resolution
    - field, stability of 184–185
    - self-diffusion 184
    - signal-to-noise ratio 185
    - transverse spin relaxation 184–185
  - spin alignment by reversible exchange (SABRE) 298
  - spin-exchange by optical pumping (SECOP)
    - alkali metal atomic energy levels 310
    - collisional interactions 309
    - hardware requirement 312
    - hyperpolarization techniques
      - laser diode systems 333
      - online determination 336
      - Ti:sapphire and dye lasers 333
      - volumetric holographic grating 333
    - X-factor*, 335
    - Zeeman splitting 335
  - microtechnological approaches
    - laser diode systems 333
    - online determination 336
    - Ti:sapphire and dye lasers 333
    - volumetric holographic grating 333
  - X-factor*, 335
  - Zeeman splitting 335
  - parameter descriptions 310
  - photon reemission 310
  - rubidium and cesium 312
  - spin-orbit coupling 310
  - <sup>129</sup>Xe and <sup>3</sup>He polarization 312
  - stray-field magnets
    - bulk-volume analysis 7–8
    - classification 5–6
    - 1D and 2D Imaging 6–7
  - system-level simulation 39, 50
- t**
- thin-film catheter receivers
    - MR-safe thin film interconnects 246–248
    - thin-film coils 244–245
    - thin-film interconnects 245–246
  - thin-film device fabrication
    - design and modeling 249



- electrical performance 252–255
  - materials and fabrication 249–251
  - mechanical performance 251–252
  - time-of-flight imaging 230
- U**
- ultrashort TE 220–222
- V**
- velocity phase imaging 229–230
- W**
- wave guides, micromagnetic resonance
    - characteristic impedance and transport characteristics 79
    - direct induction method 75
    - dynamic nuclear polarization 98–100
    - flattened solenoid probes 76
    - Fourier spectroscopy method 75
    - lab-on-a-chip (LoC) approach 77
    - Larmor frequencies 76
    - lithographic techniques 77
    - mass sensitivity 77
    - microfluidic culture assays 77
    - microfluidic NMR 87
    - microstrip detectors 88–90
    - microstrip NMR probes 84–87
    - nonresonant detectors 90–92
    - parallel plate transmission lines 96–97
    - planar detectors 87–88
    - planar TEM transmission lines 82–83
  - propagating electromagnetic modes 77–78
  - radio-frequency and microwave circuits 78
  - solid-state physics 97–98
  - stripline detectors 92–96
  - superconducting solenoids 75
  - TEM wave modes
    - Ampere’s law 81
    - axis of transmission line 79
    - electric and magnetic field distributions 80
    - independent of frequency 80
    - power losses in transmission line 82
  - transmission line detectors and resonators 83–84
  - ultraviolet–visible (UV/vis) techniques 76
  - wire-bonding
    - bicone microcoils 112
    - coil-winding machines 110
    - dry-photoresist lamination 114
    - flexibility and cost-effectiveness 109
    - microcoil manufacturing 109
    - microcontact printing 110
    - micro-Helmholtz detector 114
    - quasi-planar combinations 114
    - reactive ion etching (RIE) 110
    - solenoidal microcoils 112, 113
    - spiral planar microcoils 110
    - 3D printer 112
    - 2D techniques 113
    - 3D trajectory 109

