

Index

a

accelerator driven system (ADS) 314
 ageing, RPC 82
 aging events
 BaBar experience 230–234
 L3 and Belle 229–230
 LHC experiment 237–244
 oilless melamine 235–237
 aging studies
 changes in bakelite electrodes 244
 closed loop gas systems, LHC RPC
 244–245
 multigap RPC 246–248
 a large ion collider experiment (ALICE)
 2, 20, 181, 255
 anode streamer 15, 367
 application specific integrated circuit
 (ASIC) 315, 323
 Astrophysical experimet Ground-based
 Observatory at YangBaJing
 (ARGO-YBJ) 2, 101, 176–180
 a toroidal LHC apparatus (ATLAS)
 experiment 1, 41, 66, 181, 255,
 267, 295
 muon trigger 267
 RPC prototype efficiency vs. applied
 voltage 239
 attachment 367
 coefficient 367
 process 50
 avalanche 367
 conceptual view 128
 mode 60–64, 367

b

BaBar experience 230–234
 instrumented flux return of the BaBar
 172–176
 BaBar RPC
 chambers 233
 efficiency map 233
 electrodes 231
 bakelite 46, 221–223, 241–243
 electrodes 222
 sheets, resistance of 224
 resin 46
 resistivity vs. applied pressure 225
 surface resistivity 226, 227
 bi-dimensionally sensitive MWPC 19
 brass electrodes 227
 breast tomosynthesis 326
 bubble chamber 17, 20, 367
 bulk resistivity 219–220, 223, 225, 226
 burning-in treatment 87

c

“canal”, from which a spark forms 128
 capacitance 234
 cathode streamer 15, 367
 centroid of charges 367
 ceramics 213, 228, 229, 274, 276, 323,
 358
 charge distribution, RPC 74–76
 China Spallation Neutron Source
 (CSNS) Project 314
 closed loop gas systems, LHC RPC
 244–245

- cloud chamber 368
- cluster size 68, 185, 297, 368
- compact muon solenoid (CMS)
 - experiment 1, 113, 180–182, 255, 260, 266
- CMS RPC prototypes 239, 240
- computer numerical control (CNC)
 - machine 289, 301
- conditioning operation 48
- continuous operation spark counters
 - 20, 24
- cryogenic detectors 338–340
- current, in RPC 92–96
- cylindrical detector
 - electric field strength 28
 - primary electrons 28
- d**
- dark current 2, 83, 94, 101–102, 229, 234, 241, 246
- delta electrons 368
- delta rays 68
- diamond like carbon (DLC) 292
- discharge 8–14, 20–24, 34, 42, 50, 86, 92, 246, 273, 289, 290, 368
- double-gap resistive plate chambers
 - definition 111
 - layout of gaps 113
 - schematic layout 112
 - time resolution 111
- dynamic model, RPC 261–266
- e**
- EDS method, for normal bakelite 243
- E771 experiment 163, 165, 166
- efficiency 368
 - vs. incident flux 255
 - vs. local particle flux 257
 - vs. operating voltage 264
 - RPC 76
- effective first Townsend coefficient 50
- electrolytic process, equivalent model 223
- electron avalanche 27
 - affected by space-charge 131–133
- electron drift velocity, in
 - argon-isobutane mixtures 29
 - electron jets emission 270
 - electron-photon feedback process 10
 - electron tunnelling 11, 368
 - European Spallation Source (ESS) 314
 - explosive field emission 91, 97
 - Extreme Energy Events experiment
 - (EEE) 2, 201–206, 361, 363–365
- f**
- fast breakdown process 14–16
- Fe doped glass 213
- FENICE detector 163
- Fermi level 218, 368
- first Townsend coefficient 9, 50, 70, 78, 115, 141, 368
- flash chamber
 - working principle 34
 - cosmic ray events 36
 - schematic illustration 35
- fluoridric acid 83
- freon 47, 61, 62, 83, 88, 232, 244
- front-end electronics 261
- full width at half maximum (FWHM)
 - 151, 277, 299, 308, 368
- fused silica glass 214
- g**
- gain-rate characteristics 272
- Gamma Irradiation Facility (GIF) 181, 218, 246, 257
- gap-to-gap bridge 231
- gas chromatogram, of gas mixture 245
- gas electron multiplier (GEM) 286, 289–294, 330, 333, 337
- gaseous detectors, aging 229
- gaseous photomultipliers 331, 332
- gaseous planar detectors 29
- gas gain 10, 14, 140, 299–230, 368
- gas gap 23, 46, 48, 67, 69, 72, 74, 95, 114, 125, 134, 140, 188, 258
- gas mixture selection, RPC 81–84
- gas number density 8, 369
- Geiger modes 7, 13
- glass cathode 247
- glass resistive plate chambers 52–55, 256

glow discharge 56, 273, 369
graphite film 234

h

hadron calorimetry 341
high acceptance di-electron
spectrometer (HADES)
experiment 2, 195–201
high counting rate hybrid prototype
271
high energy physics and astrophysics
experiments
ALICE experiment 181
ARGO-YBJ experiment 176–180
ATLAS experiment 181
BaBar experiment 172–176
CMS experiment 180–182
E771 experiment 163
Extreme Energy Events experiment
(EEE) 201–206
FENICE detector 163
HADES experiment 195–201
L3 experiment 169–172
MINI experiment 165
NADIR experiment 161
other experiments 206–207
WA92 experiment 163
High Luminosity of LHC (HL-LHC)
266, 269
high position resolution RPCs
276–279
high rate RPCs 269–276
hopping conductivity 218, 369
hopping mechanism 218
hydrofluoric acid (HF) 83, 106, 230,
235
corrosive action 237

i

Iarocci tube 2, 41
inefficiency mechanism 232
injection molded spacers 52, 54
internal quenching mechanism 37
ion and photon feedback 301, 369
ionic conduction 228, 229
ionic conductive D-263 glass 230
ionization chambers 5–7

planar and cylindrical 6
typical current vs. applied voltage
curve 5, 6

j

jet emission 288, 369

k

Kanal mechanism 15, 51
Kanal process 369
Keuffel parallel plate counters
coincidence rate and time resolution
vs. operating voltage 31
layout of 30, 31
spark mode 30
total working time 30

l

L3 experiment, large electron positron
(LEP) collider 169–172, 229
L3 muon spectrometer 170
laser etching technique 290, 292
limited proportionality mode 369
limited streamer mode 15, 41
linseed oil 2, 48, 52, 175, 221–223, 231,
235–237
linseed oil-coating facility 48
low-resistivity narrow gap 272

m

Madansky parallel plate detectors 32,
33
Malter effect 91, 97, 369
mammographic scanner 3, 278, 323,
324
materials
glass RPC 213
crystal lattice, of sodium disilicate
215
Fe doped glass 213
quartz crystal 214
Roman glass structure 217
sodium disilicate crystal 215
measure of bakelite resistivity
223–228
semiconductive materials, RPC
228–229

- microelectronic technology 3, 285–287, 330
 - MICRO-MESh GAS chamber (MICROMEGAS) 3, 285, 294–300, 303
 - micropattern gaseous detectors 271, 285–288, 299, 303, 330
 - breakdowns 288
 - features 285
 - Gas Electron Multiplier (GEM) 286
 - microdot/micropin/micro-pixel detectors 287
 - microstrip gas chambers (MSGC) 230, 285, 286, 298
 - “micro Time Projection Chamber” (μ TPC) mode 297
 - microelectronic technology 287
 - MINI experiment 165
 - MIP detection efficiency 254
 - multiconductor transmission line (MTL) 131, 135–138
 - multi-gap resistive plate chambers (MRPC)
 - conceptual layout 120, 121, 123, 124
 - vs. conventional RPC 123, 125
 - efficiency and current vs. operating voltage 126
 - efficiency and time resolution 127
 - fishing lines 121, 122
 - history 117
 - for Time Of Flight system 121, 122
 - time spectra 124, 126
 - multi wire proportional chamber (MWPC) 18, 319
 - advantage 20
 - drawback 20
 - schematic illustration 18, 19
 - muonographies/muon radiographies 169
 - Muon systems, of ATLAS and CMS 266–269
 - Muon tomography
 - advantages 318
 - detector performance 315
 - nuclear treaty verifications and reactors imaging 322
 - shallow geological surveys 316
 - Time Of Flight techniques 318
- n**
- Neutron Antineutron Doublet Investigation by Reactor (NADIR) experiment 161, 162
 - neutron backscattering technique (NBT) 310, 311
 - noise counting rate, in RPC 96
 - noise pulses 2, 96–98, 188, 229, 241
 - number density 8, 84, 88
- o**
- oil coated bakelite electrodes 235, 242
 - oiled bakelite RPC 221
 - oilless melamine 235–237
 - OMEGA group 269
 - oscillograms 55, 62, 90, 91, 279
 - overvoltage 57, 87
- p**
- pads 36, 49, 51, 72, 81, 178, 315, 361
 - parallel plate avalanche chambers (PPACs) 35, 56, 98, 269, 270, 294
 - parallel plate detectors 16, 27, 29, 35, 37, 294
 - parallel-plate geometry, importance of 27–30
 - particle flow algorithms (PFAs) 341
 - Pestov’s planar spark chambers (PSCs) 37–41
 - phenolic sheet 46, 221, 235
 - photo multipliers tubes (PMTs) 338, 339
 - photon counting technique 322
 - planar spark chambers (PSCs) 37–41
 - position resolution 80
 - positive column 51, 369
 - positron emission tomography (PET) with RPC 3
 - converter plate approach 308
 - detection efficiency 309
 - 511 keV γ -rays 307
 - lower detection efficiency 308
 - precursor 35, 55, 59, 369

- proportional avalanche 369
 - pulsed spark and streamer detectors 16–18
- q**
- quartz crystal 213
 - quasi particles 228
 - quenching gas 84–86, 369
- r**
- radiographic technique 314
 - radon detectors
 - α emitter 327
 - advantages 329
 - Radon monitoring stations 329
 - “wall-less GEM” detector 330
 - Raether limit 14, 35, 55, 127, 271, 288, 294
 - rate capability 60, 99, 181, 238, 253–257, 369
 - rate capability issue 253–257
 - resistive electrode approach 289, 293, 298, 301, 303
 - resistive gaseous detectors 5, 27–42, 253
 - resistive GEMs
 - cost efficient Radon detectors 326–331
 - UV photons detection
 - cryogenic detectors 338–340
 - CsI-based resistive GEMs, RICH applications 332–336
 - flame and spark detection and visualization 337–338
 - Raether limit 332
 - resistive MICRO-MEsh GAS chamber (MICROME GAS) 294
 - resistive electrode technology 290
 - resistive GEMs-like detectors
 - direct mechanical contact 292
 - laser etching technique 292
 - photolithographic technology 289
 - resistive kapton 289
 - resistive paste 289
 - resistive microhole-microstrip and microstrip-microdot detectors with resistive lectrodes 301–303
 - resistive micromesh detectors 294–298
 - resistive microstrip detectors
 - energy resolution 299
 - gas gains 299
 - resistive microwell detector 292–294
 - resistive plate chambers (RPC) 1, 211
 - aging 350
 - avalanche development 22
 - avalanche mode 60–64
 - bakelite RPC
 - araldite epoxy adhesive 354
 - edge spacers and gas nozzles 354
 - edges and graphite layer 354
 - gas tightness 353
 - gas tubes and high voltage connections 355
 - glued spacers 357
 - polycarbonate button spacers 354
 - shielding foil 357
 - spacers and gas nozzles 354
 - spacers assembling process 356
 - cathode and anode plate 22
 - ceramic anodic plates and silicon cathodes 323
 - charge distribution 74–76
 - comprehensive simulation model 349
 - conditioning 370
 - current in 92–96
 - design of 35, 37
 - double-gap 2, 111
 - efficiency 76–78
 - electrical induction, materials with varied electrical properties 135
 - electrode surfaces 211, 230
 - electron avalanches, affected by space-charge 131–133
 - features 24
 - gas mixture selection 81–84
 - glass RPC
 - ceramic ball spacers 358
 - construction procedure 356
 - copper readout strips 359
 - efficiency vs. particle rate 220
 - glass cleaning 357

- resistive plate chambers (RPC) (*contd.*)
- high voltage connections 359
 - hopping mechanism 218
 - ion movement 218
 - low-resistivity doped glass 219
 - MRPCs 361–365
 - pad readout board 360
 - polyethylene terephthalate 358
 - resistivity vs. transferred charge 219
- multiconductor transmission lines, fast signal propagation in 135–138
- multi-gap RPC 117–127
- noise counting rate in RPC 96–99
- operating conditions of various RPCs 212
- physical simulation 349
- prototypes of 313
- RPC detection efficiency 313
- RPC, developed by Santonico & Cardarelli 45–52
- RPC PET 307–310
- RPCs with secondary electron emitters 143–153
- Ring Imaging Cherenkov (RICH) 20, 294, 332
- Roman glass structure 217
- S**
- saturated avalanche 367, 370
- screen printing technology 289
- SDHCAL prototype 342
- secondary avalanches (successors) 13
- secondary electron emission 143–153
- second Townsend coefficient 12
- self-quenched streamer (SQS) 15, 20, 370
- semiconductive materials 228–229
- sensitivity 7, 16, 24, 91, 97, 143–153, 266, 308, 327, 331, 337, 339, 370
- signal formation 64–74
- silicon coating 223
- simplified circuit model 22, 23
- single-wire cylindrical counter
- schematic illustration 7
 - voltage-current characteristic curve 8
- slow breakdown process 14, 16
- soda-silica glass 216
- sodium disilicate crystal 215
- space charge effects 2, 12, 13, 59, 76, 79, 125, 127–129, 131, 139–141, 247, 277, 369–371
- space charge field 12, 127, 128, 131, 370
- spark counters
- advantage of 17
 - modification 17
 - schematic illustration 16, 17
- spark development stages 14
- spatial resolution resistive plate chambers 51, 114, 147, 151–153, 251, 274, 277, 279
- static model, RPC 257–261
- standard gap RPC
- CMS RPC prototypes 239
 - effects of HF and chemical species 241–244
 - temperature effects 240
- standard gravimetric techniques 315
- static model, RPC 257–261
- streamer/Kanal 2, 14–18, 20–22, 24, 41, 42, 50–52, 55–65, 87–90, 93, 94, 96, 113–116, 229–237, 241, 246, 263–265, 367–371
- streamer mode 51, 55–64, 83, 93, 170, 181, 370
- streamer probability 89, 114, 115, 370, 371
- streamer quenching 368, 370
- streamer to avalanche mode transition 143
- strip multiplicity 368, 371
- surface polarization charge 253
- surface resistivity 48, 53, 226, 230, 235, 237, 312, 341, 354
- t**
- temperature and pressure effects, on RPC 99–106
- tetrafluoroethane $C_2H_2F_4$ 82, 170, 230

- thermal neutron detection
 - accelerator GELINA 312
 - “forward” and “backward” configurations 312
 - NBT technique 310, 311
 - thin gap cathode strip multi wire proportional chamber 41
 - time of flight (TOF)
 - multi-gap RPC 280
 - systems 2
 - techniques 318
 - time of flight positron emission tomography (TOF-PET) 1, 308
 - time projection chambers (TPCs) 3, 20, 194, 287, 297, 398
 - time resolution 24, 27, 29, 48, 78–80, 101, 111, 371
 - timing 138–143
 - timing RPCs 138–143
 - tomosynthesis 325, 326, 371
 - Townsend avalanche 371
 - avalanche structure, schematic illustration 10
 - elastic collisions 8
 - energy levels and tunnelling effect, of ion 12
 - inelastic collisions 9
 - photoelectrons 10, 11
 - schematic illustration 9
 - size dependence 12
 - space charge effects 12, 13
 - Townsend avalanche 7, 17, 18, 22, 131, 139
 - Townsend coefficients 70, 71, 92, 141
 - first Townsend coefficient 9, 50, 69, 78, 124, 141
 - effective first Townsend coefficient 50, 78, 79, 114, 115, 129, 141
 - second Townsend coefficient 12
 - Tsinghua glass RPC 269
- U**
- useful plateau 88, 89, 115, 371
- V**
- Vacuum ultraviolet (VUV) photons 15, 84, 371
 - veto counter system 161, 162
- W**
- WA92 experiment 163, 167, 168
 - weakly interacting massive particles (WIMPs) 338
 - wide-gap 113–117
 - wide-gap resistive plate chambers
 - efficiency plateau 115, 116, 118
 - history 113–117
 - induced charge distributions 115, 117
 - streamer probability 114
 - time distributions 119
 - useful plateau 115
 - wire-type detectors, with resistive cathodes 41–42
- X**
- X-ray EDS spectrum 242
 - X-ray imaging 322–326
 - novel tomosynthesis system 325
 - photon counting technique 322
 - XCounter imaging system 325

