

Index

a

abrasive materials, 12, 134, 155
 adsorption layer, 42, 69, 74, 125, 143, 146
 adhesion forces, 15, 25, 26, 45, 115, 124
 aggregative dynamic stability, 42, 48, 71
 aggregative stability, 11, 34, 42, 72, 74, 142, 143
 aging of bitumen, 77, 83, 156
 ampholytic surfactants, 74
 amphoteric surfactants, 74
 anionic surfactants, 73
 anisometric particles, 37, 40
 anisometry of particle shape, 145
 apolar medium, 72, 85
 apparent pseudoplasticity, 93
 asphalt concrete, 13, 14, 23, 27, 155
 atomic contacts, 12, 13, 15, 31, 43, 125, 148

b

bentonite clay suspension, 62, 146
 – effective viscosity, 147
 – shear stress, 146
 bitumen, 13, 23, 34, 77–81, 156
 bitumen–mineral composition, 78, 82, 83
 bitumen–shungite composites, 83, 157
 – cone immersion, 84, 85
 – flow curves, 82, 83
 – rheograms, 78
 – rheological properties, 83, 84
 – shear stress *vs.* shungite content, 84, 86
 – structural–rheological properties, 77
 – vibration exposures, 81
 bitumen–concrete mixtures, 5
 breaking of contacts, 37, 43, 47
 Brownian motion, 17, 18, 33, 110
 bulky two-phase (S–G) systems, *see* highly dispersed powders (HDP)

c

calcium carbonate, 97
 calcium hydroxide, 83, 156, 157
 capillary radius, 56
 capillary viscometer, 98, 99
 cation–active surfactants, 73, 83
 cement concretes
 – cement/water ratio, 2–4
 – excessive water content, 4
 – segregation, 3
 – water segregation, 3
 cement–water suspension
 – discontinuity aperture, 65, 66
 – dispersion degrees, 63, 64
 – full rheological flow curves, 64, 70
 – mineralogical composition, 63
 – vibration and surfactant effects, 69–71
 – water–cement ratio, 64, 65
 characteristic relaxation time, 67
 coagulation contacts, 12–16, 24, 25, 69, 110, 125, 135, 157
 coagulation structure, 16, 96
 coalescence, 11, 45–47, 65, 72, 86, 123, 148, 149
 coalescence of aggregates, 125, 126
 coaxial cylinders, 53–55, 98, 101
 colloid cement glue (CCG), 149
 colloid dispersed systems, 11, 34
 colloid dispersed systems, 11
 colloid polymer–cement mixtures (CPCM), 152
 colloid precipitation, 145
 compacted layer, 134
 complete disaggregation, 111
 computer simulation, 68, 94, 134
 concentration factor, 18
 cone immersion, 84, 85

- contact interactions, 6, 7, 37
 - HDP, 43, 102
 - nonequilibrium dynamic state, 36
 - three-phase dispersed systems, 45
 - two-phase dispersed systems
 - elasticity modulus, 42
 - particle shape factor, 40
 - slipping effect, 37
 - structural–mechanic barrier, 2
 - contact types between particles, 11, 12
 - continuous shear rate, 81
 - continuous vibromixer, 113
 - critical particle size, 14, 17
 - critical velocity, 39
- d**
- decomposition of emulsion, 86
 - defects of the structure, 27, 65
 - deformation rate, 5, 26, 38, 53, 60, 78
 - degraded structure, 52, 61, 62, 65, 67, 68, 90, 133
 - degree of structure destruction, 164
 - density distribution, 95, 154
 - dielectric permeability, 143
 - direct atomic contacts, 12–15, 24, 31, 125, 148
 - dispersion viscosity, 53, 90
 - dynamic conditions, 6, 7, 18, 22, 25, 26, 32, 36, 38, 39, 41–45, 51, 52, 74, 88, 122, 129
- e**
- effect of vibration and surfactants, 68
 - elasticity modulus, 12, 23, 41, 42, 46, 75, 129, 133
 - elasto–plasto–viscous state, 115, 118, 122, 126, 127
 - electrohydrodynamic processing, 146, 147
 - electrostatic stabilization factor, 143
 - emulsions, 72, 84, 85
 - application, 84
 - decomposition, 86
 - direct, 85
 - drop model, 87
 - kinds, 86
 - stability, 88
 - surfactants, 87, 89
 - energy consumption, 112, 127, 139, 147
- f**
- far particle coagulation, 16, 17
 - fluidization, 100, 118
 - fractal dimension, 21, 90
 - frequency response technique, 59
 - full limiting disaggregation, 32, 103
 - full rheological flow curves, 60
 - cement–water suspension, 64, 70
 - plastic–elastic systems, 67, 68
 - SDS, 61
- g**
- globular porous structure model, 18
- h**
- Hamaker’s constant, 91
 - HCWS, *see* high–concentration coal–water suspensions (HCWS)
 - HDP, *see* highly dispersed powders (HDP)
 - high–concentration coal–water suspensions (HCWS), 141
 - high-concentration emulsions, 86
 - high-concentration pastes, 109
 - high–filled highly dispersed composites, 153, 157
 - maximum fluidity, 6, 7
 - high-frequency vibration, 68
 - highly dispersed powders (HDP)
 - capillary viscometer, 99
 - contact interactions, 43, 101
 - dynamic state, 97, 98
 - effective viscosity, 97, 99, 100, 102
 - rotary viscometer, 98, 101
 - shear stress variation under mixing, 111, 115, 116
 - vibrorheology, 97
 - volume flow, 98, 100
 - highly filled three–phase dispersion systems, 134, 135
 - hydration hardening materials, 149
 - hydrocarbon radical, 42, 44, 73
 - hydrodynamic lubrication, 97
 - hydrophilic surfaces, 16, 39, 72
 - hydrophobic surfaces, 16, 40
 - hygroscopic powders, preventing consolidation of, 148
- i**
- interaction energy, 15, 41, 48, 170
 - interparticle contacts, *see* contact types
 - between particles/inverse emulsions
 - interparticle interaction, 16, 33, 35, 71, 90
 - inverse emulsions, 85
 - iron particles, 114
 - irreversibly destroyed contacts, 13, 23, 24, 163
 - isotropic dynamic state, 32, 34
- k**
- kinetic energy, 35, 45

l

layered flow, 66, 67
 liquefaction, 118
 liquid flowing layers, 92, 93
 liquid intermediate layer, 65
 low-concentration emulsions, 85
 lyophilic surface, 16, 38

m

macrodrop, 86–88
 maximum compaction degree, 132, 134
 mechanical exposure, 13, 35, 36, 47, 86, 102, 111, 125, 146–148
 mechanical–chemical destruction, 42
 microinhomogeneities, 65
 mineral particles, 65, 79
 mineral suspensions, 63
 mixing chamber, 113, 114, 122
 mixing efficiency, 114, 118
 mixing uniformity, 115
 model emulsions, 86
 multicomponent highly dispersed aggregation, 145
 multicomponent powdered systems, 97
 multifrequency nonlinear oscillation, 135

n

nanodispersed systems, 34
 near particle coagulation, 15, 17
 nonequilibrium dynamics, 22, 36
 nonionogenic surfactants, 73
 number of contacts, 18, 20, 31, 167

o

optimum dynamics state, 69
 ore mining, wasteless technology of, 141
 orthogonally (to flow direction) directed oscillation, 69, 83, 112

p

particle interaction, 15, 17, 39
 particle shape factor, 39
 particle size (average emulsion), 14, 17, 33, 34, 71, 86, 143
 pastelike dispersions, 12, 13, 15, 17
 phase contacts, 12, 13, 24, 148, 154
 physico–chemical mechanics, 5, 6
 pipeline hydrotransport, 141
 plasticity, 3, 5, 6, 31, 63, 69, 77, 90, 92, 93, 95, 96, 103
 plastifying effect, 42, 74
 polar continuous dispersion medium, 85
 powder efflux, 97
 powders, 12, 13, 25

principle of synergism, 139
 pseudoliquefied HDP, 97, 100
 pseudoplasticity, 103
 pseudoviscosity, 103

q

regulated isotropic state, 36
 Rehbinder effect, 12, 42, 72, 75, 76, 147
 relaxation rate, 22, 126
 reversible–strength contacts, 13, 14, 24, 110
 rheological flow curves, 53, 60–64, 67, 91, 99
 rheological properties, 53, 83, 97
 rotation vibro-viscometer, 98, 101, 130
 rupture energy, 46
 rupture zone, 65, 67
 ruptures of continuity, 67, 68, 102, 103, 128, 133

s

sedimentation processes, 34, 95, 145
 sedimentation resistant dispersions, 145
 segregation, 2, 3, 114, 127
 separation, 69, 71, 120, 121, 123
 shear stress coefficient, 54
 shungite composite, 83, 84
 solid phase effect, 80
 solid phase–liquid phase systems (S–L systems), 17
 – elasticity modulus, 42
 – particle shape factor, 40
 – slipping effect, 37
 – structural–mechanic barrier, 42
 solid phase–liquid–gas medium systems, *see* three–phase S–L–G dispersed systems 109
 solidified dispersed composites, 22, 23
 specific molding pressure, 135
 static conditions, 3, 6, 31, 36, 66, 87, 88, 97, 101, 102
 strength of contacts, time factor of, 22
 stress relaxation, 23, 46, 126
 strong dispersed structures, 32
 structural bonds, 79, 124, 126, 127
 structural–mechanic barrier (SMB), 42, 143
 structural–mechanical properties, 11, 43, 46, 48, 79, 102, 115, 130, 131, 133, 139, 144, 152, 156
 structured dispersed systems (SDS)
 – flow mechanism of, 90
 – full rheological flow curves, 61, 91
 – optimum dynamic state, 32
 – spreading over solid surface, 93, 94, 96
 structured mineral suspensions, *see* cement–water suspension

- structure formation in consecutive stages, 129
 - structure hardening, 147
 - superfluidity, 69, 103, 139, 149, 163
 - surface wetting, 16
 - surfactant Layer, 41, 42, 44, 48, 142, 143
 - surfactants, 71, 102
 - suspensions, 12, 15, 17, 25, 26
 - pipeline hydrotransport, 141
 - structural–rheological properties, regulation of, 144
 - structured mineral, *see* cement–water suspension
- t**
- thermoplastic organic binders, 65
 - thermorheological effect, 5
 - thixotropic S–L dispersions, 63
 - three–phase S–L–G dispersed systems
 - compaction
 - – rheological curves, 131, 132
 - – static *vs.* vibration compaction, 133
 - – transition mechanism, 130
 - – vibroviscometer, 130, 131
 - – volume variation, 132, 133
 - contact interactions, 45
 - mixing
 - – component distribution, uniformity of, 110
 - – continuous vibromixer, 112
 - – effective viscosity, 111
 - – nonuniformity variation kinetics, 114
 - turbulent mode, 145
 - two–phase dispersed L–L systems, *see* emulsions
 - two–phase S–L dispersed systems
 - bitumen–mineral systems, *see* bitumen–shungite composites
 - capillary viscometers, 56, 57
 - cone–plane type measuring systems, 55
 - contact interactions
 - – elasticity modulus, 42
 - – particle shape factor, 40
 - – slipping effect, 37
 - – structural–mechanic barrier, 42
 - dynamic loading modes, 59
 - dynamic states, 51, 52
 - flow and spreading, 89
 - full rheological flow curve, 60
 - plane–plane type measuring systems, 56
 - rheological characteristics, 53
 - rotation viscometers, 53–55
 - suspensions, *see* cement–water suspension
- u**
- ultrasonic Doppler method, 144
- v**
- vibration amplitude, 44, 67, 80, 81, 98, 102, 118
 - vibration compaction modes, 134
 - vibration fluidization, 43, 44, 102, 118, 121, 124
 - vibration intensity, 67–69, 81, 96, 122, 128, 150
 - vibration mixing, 45, 118, 119, 127, 129, 149, 150, 153
 - vibration rate, 46, 129
 - vibration viscosity, 67, 79, 80
 - vibrofluidization, 97, 98
 - vibroliquefaction, 97–99
 - vibromixer, 112–114
 - vibrorheology, 51, 63–71, 77–84
 - vibroviscometer, 54, 55, 57, 59, 69, 98, 130
- w**
- water/cement ratio, 2, 4, 64
 - water-soluble surfactants, 85
 - weakly aggregated dispersions, 63, 90
- y**
- Young's elasticity modulus, 92, 134
 - Young's law, 16