

Index

a

aberrations 185, 277
 absolute sum of normalized dot products 669
 absorbance 97, 98, 111
 absorbing filter 124
 absorption 97
 acceptance test 49
 accommodation 3, 5, 25
 accumulator array 658, 660, 661
 accuracy 596, 702, 718, 724, 725, 778, 782, 787
 camera parameters 629–631
 contour moments 560
 edges 512, 597–602
 gray value features 512
 gray value moments 557–558, 560
 hardware requirements 601–602
 region moments 557–558
 subpixel-precise threshold 512
 achromatic axis 10
 acquisition 371
 action commands 361, 371, 372, 375–377
 action potentials 16
 active optical cables (AOC) 381
 active pixel sensor 331
 adaptation 12, 14, 17, 26
 contrast 26
 light/dark 26
 motion 26
 to optical aberrations 26
 to scaling 26
 tilt 26
 adaptive lighting 118, 171

A/D conversion 357
 additive mixed illumination colors 103
 additive noise 272
 additivity 253
 adjustment 719, 720, 722, 723, 732
 vs. calibration 732
 affine transformation 532–533, 555, 644, 662, 668
 afocal system 229
 aging 88
 Airy disk 244, 246
 algebraic distance 608
 algebraic error 608
 aliasing 529–530, 537–538, 649
 effect 267, 269
 function 276
 potential 276
 ratio 276
 alignment 532, 544, 545
 Altera Cyclone V series 405
 amacrine cells 17, 20
 amplitude distribution in the image plane 242
 analog cameras 435
 analog connectors 439
 analog front end (AFE) 357, 358
 analog image acquisition 437
 analog processing 356
 analog-to-digital converter (ADC) 329, 330, 336, 366, 388
 analog video signal 436
 analyzer 108
 Ando filter 589
 angel kappa 3
 anisometry 554, 557, 559, 674

- anterior chamber 2
 anti-reflective coating (AR) 126, 283
 aperture 206
 correction 354
 stop 206, 514
 a posteriori probability 677
 application-package, *see* systems,
 application-package 699
 Application Programming Interface
 (API) 475
 applications
 code recognition 701
 completeness check 701, 702, 772,
 774, 776
 object recognition 701, 779
 position recognition 701, 781
 shape and dimensioncheck 702
 surface inspection 702, 788
 types 702
 application-specific integrated circuits
 (ASICs) 345, 402
 a priori probability 677, 679
 Aptina 337
 area 552, 557–560
 of interest 329, 348
 MT 22
 sensor 319, 614
 artificial astigmatism 124
 aspect ratio 744
 astigmatism 5, 11, 600
 attention 22, 23
 Automated Imaging Association (AIA)
 454
 axial magnification ratio 200, 233
 axons 3, 11, 16, 17, 19
- b**
- backlight (ing) 44, 138, 174
 back side illumination (BSI) 337, 338
 band-limited system 269
 bandpass filter (BP) 125
 bandwidth 122, 395 *see also* signal,
 bandwidth, 699
 bar codes, *see* codes, bar codes 699
 batch production, *see* production, batch
 699
 Bayer color encoding 485
- Bayer Color Filter Array (CFA) 485
 BAYER pattern 351, 359
 Bayes decision rule 677
 Bayes theorem 677
 beam converging lens 193
 beam diverging lens 193
 Bessel function 244
 bilateral telecentric systems 229
 bilinear 359, 367
 binary image 507, 549, 552, 561, 563,
 567, 573
 binning 338, 345, 347
 binocular stereo reconstruction
 631–643
 bin-picking 767, 771
 bipolar cells 16
 OFF 13
 ON 13
 black light 107
 blob analysis 60
 blobs 22, 23
 block diagram 350, 354
 blooming 326
 boundary 550, 556, 567–568
 condition 239
 bounding box 555, 560, 675
 bright field 45
 illumination 138
 brightness 206
 behavior 90
 control 166
 perception 74
 b/w 338
- c**
- C-Mount 318, 350
 C-Mount lens 43
 calcium 13
 calibration 731, 748, 750, 782–784
 vs. adjustment 732
 geometric 600, 601, 613–632
 accuracy of interior orientation
 629–631
 binocular stereo calibration 633
 calibration target 622–623

- camera constant, *see* calibration,
 geometric, principal distance
 690
 camera coordinate system
 615–616, 618–620, 633
 camera motion vector 618
 distortion coefficient (division
 model) 616–632, 636
 distortion coefficients (polynomial
 model) 616, 618, 632
 exterior orientation 601, 623–626
 focal length 614–615, 632
 image coordinate system 618, 620
 image plane coordinate system
 616, 620
 interior orientation 601, 623–626,
 632
 pixel size 618, 620, 632
 principal distance 614–616, 620,
 629–632
 principal point 618, 620, 629–632
 projection center 614, 632, 633,
 635, 637
 relative orientation 632, 633
 world coordinate system
 615–616, 620
 radiometric 512–517, 600
 calibration target 513
 chart-based 513
 chart-less 514–517
 defining equation for chart-less
 calibration 514
 discretization of inverse response
 function 514, 515
 gamma response function 513,
 516
 inverse response function 514
 normalization of inverse response
 function 515, 516
 polynomial inverse response
 function 516
 response function 513, 514, 516
 smoothness constraint 516
 camera (s) 505–506
 bus
 analog cameras 435
 analog connectors 439
 analog image acquisition 437
 analog video signal 436
 bandwidth 459
 cables 460
 Camera Link 449
 Camera Link HS 432, 451
 Camera Link signals 450
 CoaXPress 432, 452
 differential signaling 441
 digital video transmission 439
 FireWire/IEEE 1394, 432
 frame grabber 432
 frame rate 460
 G3 433
 GenICam 433
 Gigabit Ethernet for machine vision
 455, 456
 GigE Vision 432
 IEEE 1394 (FireWire) (Legacy)
 442
 IEEE 1394 for machine vision 445
 IIDC2 standard 434
 interlaced video transfer 436
 LCD inspection 462
 line scan 441, 460
 manufacturing inspection 461
 parallel digital camera buses 439
 parallel digital connectors 441
 progressive scan video 437
 reliability 460
 resolution 459
 RGB 438
 security 463
 S-Video 438
 taps 440
 timing signals 437
 USB 452
 USB for machine vision 454
 USB3 Vision standards 432, 433
 calibration
 accident photography 313
 additional object information 304
 affinity and non-orthogonality
 299
 applications with simultaneous
 calibration 309
 architecture 313

- camera (s) (*contd.*)
 - camera model 295
 - camera system 292
 - car safety applications 312
 - central projection 295
 - coordinate systems 292
 - direct linear transformation 308
 - distortion and affinity 297
 - extended system calibration 307
 - exterior orientation 293
 - focal length and principal point 297
 - image information 302
 - image rectification 628–629
 - interior orientation 293
 - in the laboratory 302
 - optical system 293
 - plumb-line method 307
 - radial asymmetrical and tangential distortion 299
 - radial symmetrical distortion 297
 - sensor flatness 301
 - sensor stability 294
 - signal processing and transfer 294
 - system calibration 293
 - tube measurement 311
 - variant camera parameters 299
 - verification 308
 - whitelight scanners 312
 - world coordinates from single image 601, 626–628
 - world coordinates from stereo reconstruction 631, 643
 - constant 182
 - exposuretime 514
 - electrical design 46, 58
 - fill factor 558, 598, 601
 - gamma response function 513, 516
 - gray value response 512–513
 - linear 512, 600, 601
 - nonlinear 512, 600
 - inverse response function 514
 - line scan 614, 618–622, 628
 - mechanical design 46, 58
 - model 32, 37, 39, 40
 - pinhole 614–618, 627–628
 - resolution 39
- response function 513, 514, 516
- sensor
 - aspect ratio 37, 39, 51
 - resolution 37, 38
 - telecentric 614–618, 626–627
- Camera Link 345, 395, 432, 449, 716
 - connector 451
 - HS 432, 451
 - signals 450
- candela 110
- Canny filter 586, 591, 597
 - edge accuracy 597, 598
 - edge precision 597
- cardinal elements 191
- center of gravity 552–554, 557, 558, 560, 603, 605
- center of perspective 182
- center wavelength 83, 122
- central disk 244, 248
- central moments 553–554, 557, 560, 603
- central projection 182, 219
- chamfer-3–4 distance 574
- changeover 720, 748, 750
- channel capacity 11, 16
- characteristic function 507, 557, 575
- charge 328, 345
 - transfer 321
- charge-coupled device (CCD) 317, 320–322, 324–328, 334, 336, 337, 339–342, 345, 348–351, 353–357, 359, 360, 369, 375, 391, 392, 394, 397
- chessboard distance 574
- chief ray 207
- chroma 351
- chromatic aberration 6, 10, 600
 - longitudinal 10
 - transverse 10
- chrominance 351
- circle fitting 607–608
 - outlier suppression 607
 - robust 607
- circle of confusion 211, 214
 - permissible size 218
- circular aperture 243
- city-block distance 573, 574

- classification 674, 676–690
 - Bayes classifier 679–681
 - classification accuracy 688
 - classifier types 678
 - curse of dimensionality 679, 685
 - decision theory 676–678
 - Bayes decision rule 677
 - Bayes theorem 677
 - error rate 679
 - expectation maximization algorithm 681
 - features 674
 - Gaussian mixture model classifier 680–681, 689
 - generalized linear classifier 685
 - k nearest-neighbor classifier 679–680
 - linear classifier 681–682
 - neural network 681–685, 688–689
 - hyperbolic tangent activation function 683
 - logistic activation function 683
 - multilayer perceptron training 682–685, 688–689
 - sigmoid activation function 683–684
 - single-layer perceptron 681–682
 - softmax activation function 684
 - threshold activation function 682, 683
 - universal approximator 683, 684
 - nonlinear classifier 682–689
 - polynomial classifier 685
 - a posteriori probability 677
 - a priori probability 677, 679
 - rejection 688–689
 - support vector machine 685–689
 - Gaussian radial basis function kernel 687
 - homogeneous polynomial kernel 687
 - inhomogeneous polynomial kernel 687
 - kernel 687
 - margin 686
 - separating hyperplane 685–686
 - sigmoid kernel 687
- universal approximator 687
- test set 679
- training set 678, 684
- training speed 688
- Closed Circuit TeleVision (CCTV) 317–319
- closing 571, 577
- cloudy day illumination 150
- cluster 710
- clutter 654, 657, 661, 668
- CMOSIS 328, 335, 336
- coaxial diffuse light 140
- coaxial directed light 142
- coaxial telecentric light 143
- CoaXPress 432, 452
- coded light 145
- code recognition, *see* codes, recognition 699
- codes
 - bar codes 701
 - DataMatrix 701, 708, 730, 731, 734
 - recognition 701
- coherent light 85
- cold light source 78
- collision avoidance 771
- color 338
 - alias 367
 - Burst 437
 - constancy 23, 25
 - contrast 23, 25
 - correction 368
 - difference 354
 - filter 130
 - information 367
 - interpolation 367
 - color perception 73
 - color space 371
- ColorChecker 369
- column parallel readout 330
- coma 11, 600
 - horizontal 5
- combined lighting technique 162
- compact systems, *see* systems, compact 699
- Compact Vision System (CVS) 41, 423
- compactness 556, 674

- complement 561–562
- complementary color 101, 322, 351, 353
- complementary
 - metal-oxide-semiconductor (CMOS) 317, 320, 328, 329, 331, 332, 335–337, 339–342, 348, 351, 354, 355, 357, 359, 375, 382, 391, 392, 394
- completeness check, *see* applications, completeness check 699
- complex cells 22
- component labeling 549
- computer bus
 - cost 471
 - ISA/EISA 463
 - machine vision applications 463
 - PCI/CompactPCI/PXI 464
 - PCI Express/CompactPCI Express/PXI Express 467
 - PCI-X 466
 - prevalence and lifetime 471
 - throughput 469
 - throughput requirements application 473
 - throughput requirements determination 471
 - timeline 464
- condition monitoring 793
- cone pedicle 16
- cones 6, 12, 16, 24, 26, 27
- configuration management 709, 710, 785
- confocal frontlight 45
- connected components 548–549, 672
- connectivity 548–549, 562, 568, 573
- constancy of luminance 113
- Consultative Committee for International Radio (CCIR) 338, 435
- Consulting Team Machine Vision (CTMV) 55
- continuous production, *see* production, continuous 699
- contour 508–509
 - feature, *see* features, contour 690
 - length 556
- segmentation 609–612, 655
 - lines 609–611
 - lines and circles 611–612
 - lines and ellipses 611–612
- contour-based algorithms 34
- contrast 44, 118
 - adaptation 11
 - enhancement 510–512
 - normalization 511–512
 - robust 511–512, 676
 - sensitivity function 17, 18
 - threshold 17
- control, *see* evaluation, control 699
- controlled lighting 167
- control signals, *see* data, control signals 699
- convex hull 555–556, 560
- convexity 555–556
- convolution 522–523, 528–529
 - integral 256
 - kernel 522
 - theorem 259, 267
- coordinates
 - homogeneous 533, 534
 - inhomogeneous 533, 534
 - polar 538
- cornea 1–3, 5
- correct perspective viewing distance 213
- correction data 365
- Correlated Double Sampling (CDS) 334, 348, 349, 357, 359, 392
- correlation 529, *see also* normalized cross-correlation, 690
- \cos^4 -law 283
- counters 372, 376
- CPU load 367, 368, 379, 380, 396
- crosstalk 269
- CRT 322, 363
- crystalline lens 1
- CS-Mount 318
- CS-Mount camera 43
- cumulative histogram 511, 557
- cutoff spatial frequency 6
- cutoff wavelength 122
- cuton wavelength 122

- cycle time, 34, *see* production, cycle time 699, 737
- Cyclic Redundancy Check (CRC) error checking 454
- d**
- dark current noise 391
 - darkfield illumination 139
 - dark field lighting 45, 152
 - dark noise 16, 364, 366
 - data
 - control signals 731, 736
 - images 733, 734
 - packets 378
 - rate, *see* signal, data rate 699
 - structures
 - images 505–506
 - regions 506–508
 - subpixel-precise contours 508–509
 - type data 733, 785, 786
 - valid signal 450
 - DataMatrix code, *see* codes, DataMatrix 699
 - daylight suppression filter 128
 - decision theory 676–678
 - Bayes decisionrule 677
 - Bayes theorem 677
 - a posteriori probability 677
 - a priori probability 677, 679
 - defocused image plane 248
 - delay time 167
 - deltaE 370
 - demosaicing 367, 368
 - depth-first search 549
 - depth of field 214, 215, 234
 - depth of field T 216
 - depth of focus, *see* focus, depth of 699
 - depth of focus T 216
 - Deriche filter 586–587, 591, 597
 - edge accuracy 597, 599
 - edge precision 597
 - derivative
 - directional 581
 - first 580, 583
 - gradient 581
 - Laplacian 582
 - partial 581, 582, 589, 591
 - second 580, 583
- deterministic system 253
- deviation from telecentricity 284
- dichromatic 24
- difference 561
- differential signaling 441
- diffraction 99, 235
- diffraction integral 236, 237
- diffraction-limited 3, 241
 - depth of focus 247
 - MTF 3
- diffuse area lighting 141
- diffuse bright field incident light 140
- diffuse bright field transmitted lighting 155
- diffuse dark field incident light 152
- diffuse directed partial bright field
 - incident light 148
- diffuse lights (ing) 45, 136
- diffuse on axis light 140
- diffuse transmitted dark field lighting 161
- digital I/O, *see* interface, digital I/O 699
- digital signal processor (DSP) 351, 404
- Digital Video Interface (DVI) connector 413, 443
- digital video transmission 439
- dilation 562–565, 567–568, 576, 594
- dimension check, *see* applications, dimension check 699
- DIN 1335, 204
- DIN 19040, 202
- diplopia 25
- Dirac comb 266, 269
- directed bright field incident light 142
- directed bright field transmitted lighting 157
- directed dark field incident light 152
- directed light (ing) 45, 136
- directed on axis light 142
- directed reflection 93
- directed transmission 97
- directed transmitted dark field lighting 161
- directional properties of the light 135

- direction of light 192
 - direct linear transformation
 - (DLT) 308
 - Direct Memory Access (DMA) 380, 396, 474, 478
 - discharging lamp 76, 78
 - discrete Fourier transform (DFT) 270, 529–532, *see also* discrete Fourier transform, 690
 - disparity 25, 27, 638–639
 - dispersion 102
 - dispersion of light 184
 - distance
 - chamfer-3–4 574
 - chessboard 574
 - city-block 573, 574
 - Euclidean 574
 - transform 573–575, 655, 657
 - distortion 280, 600, 616–618, 620
 - barrel 616–618, 620
 - division model 616
 - pincushion 616–618, 620
 - polynomial model 616–618
 - distribution of illuminance 115
 - DL-Cutfilter 355
 - DNL 357
 - dorsal stream 22, 25
 - drift 78, 84, 88
 - driver software
 - acquisition mode 479
 - API 475
 - Bayer color encoding 485
 - display modes 488
 - image display 488
 - image representation on disk 482, 487
 - layers of 474
 - nondestructive overlays 490
 - palettes 489
 - performance 477
 - supported platforms 477
 - utility functions 478
 - duality
 - dilation–erosion 567, 576
 - hit-or-miss transform 569
 - opening–closing 571, 577
 - dynamic 336, 375, 387, 393
 - range 328, 393
 - thresholding 542–544, 577, 672
- e**
- edge
 - amplitude 548, 581, 590
 - definition
 - 1D 580–581
 - 2D 581–582
 - gradient magnitude 548, 581, 590
 - gradient vector 581
 - Laplacian 582, 594–596
 - non-maximum suppression 580, 587, 591–592
 - polarity 581
 - spread function 278
 - edge extraction 579–602, 655
 - 1D 583–589
 - Canny filter 586
 - Deriche filter 586–587
 - derivative 580, 583
 - gray value profile 584
 - non-maximum suppression 587
 - subpixel-accurate 588
 - 2D 548, 589–596
 - Ando filter 589
 - Canny filter 591, 597
 - Deriche filter 591, 597
 - Frei filter 589
 - gradient 581
 - hysteresis thresholding 592–593
 - Lanser filter 591, 597
 - Laplacian 582, 594–596
 - non-maximum suppression 591–592
 - Prewitt filter 589
 - Sobel filter 589
 - subpixel-accurate 593–596
 - edge filter 586–587
 - Ando 589
 - Canny 586, 591, 597
 - edge accuracy 597, 598
 - edge precision 597
 - Deriche 586–587, 591, 597
 - edge accuracy 597, 599
 - edge precision 597
 - Frei 589

- Lanser 591, 597
 edge accuracy 597
 edge precision 597
 optimal 586–587, 590–591
 Prewitt 589
 Sobel 589
 edge spread function (ESF) 278
 effective f-number 216
 Eikonal equation 180
 electromagnetic compatibility (EMC)
 80
 electromagnetic wave 179
 Electronic Industries Association (EIA)
 RS-170 338, 435
 electronic shutter 323
 ellipse fitting 608–609
 algebraic error 608
 geometric error 609
 outlier suppression 609
 robust 609
 ellipse parameters 553–555, 557, 559,
 560, 603, 605, 608, 609
 embedded image processing 713
 embedded MultiMediaCard (eMMC)
 407
 embedded vision systems
 better shock and vibration ratings and
 testing 423
 built-in hardware 423
 closed loop control applications 424
 definition 401
 environment 425
 fanless design and greater
 temperature range specifications
 423
 flexibility in component selection
 422
 flexibility in system integration 422
 full bus bandwidth 423
 higher performance processing 421
 I/O set 422
 multi-camera applications 424
 multi-camera connectivity 421
 programming and configuration 425
 SLC vs. MLC memory solid state
 memory 423
 emmetropia 3
 EMVA1288 386–388, 394
 enclosing circle 555, 560
 enclosing rectangle 555, 560, 675
 engineering framework 747
 entocentric perspective 222
 entrance pupil 198, 208
 entrance window 209
 epipolar image rectification 637–638
 epipolar line 634
 epipolar plane 634
 epipolar standard geometry 636–637
 epipole 634
 erosion 565–568, 576
 error of second order 159
 error signal 61
 errors of the first order 160
 Ethernet, *see* interface, Ethernet 699
 Euclidean distance 574
 evaluation
 control 705, 706, 781, 786, 787
 inspection 704, 772, 774, 776, 787
 monitoring 705
 recognition 705
 verification 704, 705, 772, 774, 776,
 779
 exit pupil 198, 208
 exit window 209
 exposure 115, 120, 318, 327, 329, 332,
 335, 345, 359, 361, 371, 372, 374,
 375, 383, 384, 387
 time 120, 514
 Extended Industry Standard
 Architecture (EISA) bus 464
 extensibility 710, 714, 791
 exterior orientation 601, 615–616,
 620, 623–626
 world coordinate system 615–616,
 620
 extraneous light 175
 ExViewHAD 325
 eye lens 1
 eye movement 10, 12, 27
 eye protection 106
f
 face-distortion aftereffect 26
 face recognition 707, 794

- facet model 593
- far cells 25
- far point 214, 223
- fast Fourier transform 530, *see also* Fourier transform, 690
- feature extraction 552–560
- features
 - contour 552, 559–560
 - area 560
 - center of gravity 560
 - central moments 560
 - contour length 559
 - ellipse parameters 560
 - major axis 560
 - minor axis 560
 - moments 560
 - normalized moments 560
 - orientation 560
 - smallest enclosing circle 560
 - smallest enclosing rectangle 560
- gray value 552, 556–559
 - α -quantile 557
 - anisometry 557, 559
 - area, 557–559
 - center of gravity 557, 558
 - central moments 557
 - ellipse parameters 557, 559
 - major axis 557, 559
 - maximum 511, 556
 - mean 556
 - median 557
 - minimum 511, 556
 - minor axis 557, 559
 - moments 557–559
 - normalized moments 557
 - orientation 557
 - standard deviation 556
 - variance 556
- region 552–556
 - anisometry 554, 674
 - area 552, 558
 - center of gravity 552–554, 558
 - central moments 553–554
 - compactness 556, 674
 - contour length 556
 - convexity 555–556
 - ellipse parameters 553–555
- major axis 553–554
- minor axis 553–554
- moments 552–555
- normalized moments 552–553
- orientation 553–555
- smallest enclosing circle 555
- smallest enclosing rectangle 555, 675
- Fermat's principle 180
- FFT, *see* fast Fourier transform 690
- fields 322, 323, 345
 - angle, object side 202
 - buses, 411*see* interface, field bus 699
 - integration, 321–323
 - readout 351
 - stop 206
- field-programmable gate array (FPGA) 354, 361, 365–367, 402, 405, 709, 714, 794
- files, *see* interface, files 699
- fill factor 321, 322, 334, 558, 598, 601
- filter
 - anisotropic 524, 591
 - border treatment 520–521
 - combination 131
 - convolution 522–523, 528–529
 - kernel 522
 - definition 522
 - edge 586–587
 - Ando 589
 - Canny 586, 591, 597
 - Deriche 586–587, 591, 597
 - Frei 589
 - Lanser 591, 597
 - optimal 586–587, 590–591
 - Prewitt 589
 - Sobel 589
 - factor 123
 - Gaussian 524–526, 538, 542, 543, 586, 591, 649
 - frequency response 525, 529
 - isotropic 524, 525, 591
 - linear 522–523, 583
 - mask 522
 - maximum, *see* morphology, gray value, dilation 690

- mean 519–522, 526, 538, 543, 584, 649
- frequency response 523–524, 528, 650
- median 526–527, 543
- minimum, *see* morphology, gray
 - value, erosion 690
- nonlinear 526–527, 576
- rank 527, 576
- recursive 522, 523, 525, 577
- runtime complexity 521–522
- separable 521, 523, 525
- smoothing 517–527
 - optimal 524–525, 586, 591
- spatial averaging 519–522
- temporal averaging 518–519, 545
- finite extension of ray pencils 205
- FireWire, 361, 449, *see* interface, FireWire 699
- FireWire/IEEE 1394, 432
- first Bessel function 18
- first in–first out (FIFO) 362
- fitting
 - circles 607–608
 - outlier suppression 607
 - robust 607
 - ellipses 608–609
 - algebraic error 608
 - geometric error 609
 - outlier suppression 609
 - robust 609
 - lines 603–606
 - outlier suppression 604–606
 - robust 604–606
- fixation 717, 718, 722, 723
- fixed pattern noise 334, 392
- flash 322, 323, 327, 332, 335, 350
 - duration 80
 - lighting 84, 167
 - mode 167
 - repeating frequency 167
 - time 170
- fluorescent lamp 81
- fluorescent tubes 45
- f*-number 210, 514
- focal length 42, 614–615, 632
 - image side 192
 - object side 192
- focal point
 - image side 189
 - object side 189
- focus depth of 718, 742
- focusing plane 211, 214
- Fourier transform 240, 523, 528–532
 - continuous 528–529
 - convolution 528–529
 - discrete 529–532
 - inverse 530
 - fast 530
 - frequency domain 528
 - Nyquist frequency 529
 - 1D 528
 - inverse 528
 - real-valued 530
 - spatial domain 528
 - texture removal 530–532
- 2D 528
 - inverse 528
- fovea 3, 10
- FPGA counter 59
- FPN 392
- frame 4, 37
 - averaging 366
 - frame grabber 350
 - analog, line jitter 597
 - integration 321, 323, 324
 - memory 361
 - rates 336, 382
 - transfer 321
- work, *see* engineering framework 699
- FrameBurstStart* 373
- Fraunhofer approximation 240
- Frei filter 589
- frequency, 183, *see* signal, frequency 699
 - domain 528
- Fresnel's approximation 239
- FTP, *see* interface, network 699
- Full frame 321
- Full well 336
- fuzzy membership 557–559
- fuzzy set 557–559
- FX3 384

g

- G3 433
 gage capability 718, 724
 Gamma function 362
 gamma response function 513, 516
 gamut 351, 369, 370
 ganglion cells 11, 17, 18, 20–22, 24, 27
 gauge capability 724, 779
 Gaussian filter 524–526, 538, 542, 543,
 586, 591, 649
 frequency response 525, 529
 Gaussian optics 185, 235
 GenAPI 378
 generalized Hough transform 658–661
 accumulatorarray 658, 660, 661
 R-table 660
 Generic Application Programming
 Interface (GenApi) 434
 Generic Control Protocol (GenCP)
 434
 Generic Transport Layer (GenTL) 434
 GenICam, 354, 371, 378, 380, 384,
 394–396 433, 457, 716
 GenTL 378
 geometrical optics 179, 180
 geometrical path 180
 geometric camera calibration 600,
 601, 613–631, 632
 binocular stereo calibration 633
 calibration target 622–623
 exterior orientation 601, 615–616,
 620, 623–626
 world coordinate system
 615–616, 620
 interior orientation 601, 614–618,
 623–626, 632
 accuracy 629–631
 camera coordinate system
 615–618, 633
 camera motion vector 618
 camera constant, *see* geometric
 camera calibration, interior
 distortion coefficient (division
 model) 632, 636
 distortion coefficients (polynomial
 model) 632
 focal length 632
 pixel size 632
 principal distance 632
 projection center 614, 632, 633,
 635, 637
 orientation, principal distance 690
 camera coordinate system 616,
 620
 distortion coefficient (division
 model) 616–629, 631
 distortion coefficients (polynomial
 model) 616, 618
 focal length 614, 615
 image coordinate system 618–620
 image plane coordinate system
 616–620
 pixel size 618–620
 principal distance 614–629, 631
 principal point 618–632
 relative orientation 632, 633
 base 633
 base line 635
 geometric error 609
 geometric hashing 662–663
 geometric matching 661–671
 gesture recognition 766
 Gigabit Ethernet for machine vision
 456
 Gigabit Ethernet (GigE Vision) 340,
 341, 345, 354, 361, 363, 375,
 377–380, 384, 385, 394–396, 432,
 455, 716
 GigE Vision Control Protocol (GVCP)
 378, 456
 GigE Vision device discovery 456
 GigE Vision Stream Protocol (GVSP)
 378, 379, 457
 Global Machine Vision Interface
 Standards 433
 Global Reset Release Shutter 332
 global shutter 332, 334
 glutamate 13
 grab acquisition 480
 gradient 581, 754, 762
 algorithm 119
 amplitude 548, 581, 590
 angle 581, 660
 direction 581, 658, 660

- index lens 5
 length 581
 magnitude 548, 581, 590
 morphological 577–578
 graphics processing unit (GPU) 404
see also GPU, 699, 710, 794
 grating acuity 8, 18
 gray value 506
 α -quantile 557
 camera response 512–513
 linear 512, 600, 601
 nonlinear 512, 600
 difference 118
 feature, *see* features, gray value 690
 maximum 511, 556
 mean 556
 median 557
 minimum 511, 556
 normalization 511–512
 robust 511–512, 676
 1D histogram 511–512, 541–542
 cumulative 511, 557
 maximum 541–542
 minimum 541–542
 peak 541–542
 profile 584
 robust normalization 675
 scaling 510
 standard deviation 556
 transformation 510–512, 556, 559
 2D histogram 515
 variance 556
 GretagMacbeth 369
 grey filter 129
- h***
- H264 318
 half-power points 122
 half-width 82
 halogen and xenon lamps 45
 halogen lamp 77
 handling, *see* production, part handling 699
 handshaking, *see* interface, handshaking 699
 hardware trigger 371
 harmonic wave 258
- Hausdorff distance 656–658
 HD 343, 350
 height map 754, 755, 757, 758, 760, 762, 765, 770, 771
 Helmholtz equation 237
 Hessian normal form 603
 HF-ballast 81
 High-Definition Multimedia Interface (HDMI) connector 413
 higher order aberrations 5
 high dynamic range (HDR) 328, 331
 high speed imaging 331
 high-speed inspection 168
 HiRose 350, 382
 histogram 361
 1D 511–512, 541–542, 557
 cumulative 511, 557
 maximum 541–542
 minimum 541–542
 peak 541–542
 2D 515
 hit-or-miss opening 570
 hit-or-miss transform 568–569, 572
 HMI, *see* human machine interface 699
 hole accumulation diode 325
 homocentric pencil 180, 185
 homogeneity 253
 homogeneous coordinates 533, 534
 homogeneous lighting 151
 horizon line 223
 Horizontal Synchronization (Hsync)
 pulse 437
 HSL color space 500
 Hsync signal 439
 HTTP, *see* interface, network 699
 Huber weight function 605
 human machine interfaces 34, 735, 745–747, 749, 750
 human perception 119
 100-pin SCSI connector 443
 hyper acuity 25
 hyper centric perspective 226
 hyper column 23
 hyper focal depth, near limit 217

- hyper focal distance 217
- hyper polarization 13, 14
- hypothesize-and-test paradigm 661
- hysteresis thresholding 592–593

- i*
- ICP 756, 757, 768
- ideal lens transformation 242
- idealized impulse 253
- IEEE 1394, *see* interface, IEEE 1394, 699
- IEEE 1394 (FireWire) (Legacy) 442
- IEEE 1394 for machine vision 445
- IIDC 371, 378
- IIDC Isochronous video packet 448
- IIDC2 standard 434
- IIoT 716, 730, 735, 793–795
- illuminances 110, 111, 113, 169
 - at image sensor 114
 - choice of 44, 52, 58
 - component 67
- imaging equations 195
 - general 198
 - Newtonian 197
- imaging optics 134
- images 505–506 *see also* data, images, 699
 - acquisition time 34
 - binary 507, 549, 552, 561, 563, 567, 573
 - bit depth 506
 - circle diameter 211, 256
 - complement 576
 - construction, graphical 195
 - domain, *see* region of interest 690
 - edges 37
 - enhancement 509–527
 - function 506–507
 - gray value 506
 - scaling 510
 - transformation 510–512
 - gray value normalization 511–512
 - robust 511–512, 676
 - label 507, 549
 - multichannel 506
 - noise, *see* noise 690
 - orientation 186
- plane 632, 636, 637, 639
- processing library 53, 385
- pyramid 649–652, 670
- quality 49, 277
- real 187
- rectification 535, 538, 628–629, 637–638, 673
- representation on disk 482, 487
- RGB 506
- segmentation, *see* segmentation 690
- sensors 409
- side focal length 192
- single-channel 506
- space 191, 200
- smoothing 517–527
- spatial averaging 519–522
- temporal averaging 518–519, 545
- transformation 534–539, 544
- virtual 187
- impact acquire 370
- impulse response 238, 241, 242
- incandescent emission 76
- incandescent lamp 77
- incident light (ing) 138, 150, 174
- incoherent imaging 243
- incoherent light 137
- incoherent transmission chain 267
- incoming light 93
- Industrial Internet of Things, *see* IIoT 699
- industrial lighting 67
- Industry 4.0, 716, 730, 735, 793–795
- Industry Standard Architecture (ISA)
 - bus 463
- information interfaces 56
- information theoretical aspect 252
- Infrared Light (IR) 70, 322, 325, 340, 341, 348, 355
 - cut filter 348, 355
 - suppression filter 128
- inhomogeneous coordinates 533, 534
- INL 357
- inline tubing inspection 55
- input 382
- inspection, *see* evaluation, inspection 699
- inspection protocol 56

- installation space 56
 integration time 14, 17
 intelligent camera, *see* systems, compact systems 699
 intensity distribution near focus 246
 interface
 comparison 396
 digital I/O 728, 729, 732–734
 Ethernet 727–729, 733–735, 737, 751, 783
 field bus 728, 729, 733–735
 files 736
 hand shaking 737, 739, 783
 multi threading 737, 738
 network 734
 real-time Ethernet 735
 serial 733
 USB 727–729, 734
 interference filter 125
 interfering lighting 46
 interior orientation 614–626
 accuracy 629–631
 camera constant, *see* interior orientation, camera constant 690
 camera coordinate system 615–616, 618–620, 633
 camera motion vector 618
 distortion coefficient (division model) 616–631, 632, 636
 distortion coefficients (polynomial model) 616, 618, 632
 focal length 614–615, 632
 image plane coordinate system 616, 620
 image plane system 618, 620
 pixel size 618, 620, 632
 principal distance 614–616, 620, 629–631, 632
 principal point 618, 620, 629–632
 projection center 614, 632, 633, 635, 637
 interlaced 321–324, 345, 350, 351
 scan 321, 322
 transfer 321
 video transfer 436
 intermediate pupil 208
 International System of Units 110
 interpolation 359, 367, 380
 bilinear 536–537, 550, 584
 nearest-neighbor 535, 584
 interrupt moderation 379
 interrupt service routine (ISR) 478
 intersection 561
 invariant moments 555
 IoT 709
 irregular diffuse reflection 93
 irregular diffuse transmission 97
 ISO 361
 ISO9001:2000 70
 Isochronous 378
 isoplanasie condition 256
 isoplanatic region 256
 Iterative Closest Point, *see* ICP 699
 iteratively reweighted least-squares 605
- j**
 jitter 318, 371, 375, 377
 job-shop production, *see* production, job-shop 699
 Journaling Flash File System (JFFS / JFFS2) 407
 JPEG 318
 jumbo packets 361, 379
 junction 509
- k**
 Keplerian telescope 230
 kernel, *see* convolution, kernel *and* support vectormachine, kernel 690
 knee 328–331
 koniocellular pathway 21, 24
 kT/C noise 349
- l**
 label image 507, 549
 labeling 549
 LabVIEW 475
 LAG 379
 Lambert radiator 116, 136
 Lanser filter 591, 597
 edge accuracy 597

- Lanser filter (*contd.*)
 edge precision 597
- Laplacian 582, 594–596
- laser 76, 85
- laser protection classes 85
- latency 362, 367, 368, 371, 375, 377, 395
- law of reflection 181
- law of refraction 181, 183
- LCD inspection 462
- L cone 10, 24, 26
- LED lights 45, 76, 82
- lens
 aperture stop 514
 design 41, 52, 58
 diameter 43
 extension 43
 f-number 514
 magnification factor 618
 quality 43
 vignetting 513
- lens aberrations
 astigmatism 600
 chromatic aberration 600
 coma 600
 distortion 600, 616–618, 620
 barrel 616–618, 620
 pincushion 616–618, 620
- LGN, *see* lateral geniculate nucleus 17, 18, 21
- LIDAR 760, 770
- lifetime 77–80, 82, 84, 86, 357
- light 70, 179
 color 101
 deflection 175
 distribution 115
 emitting diode 82
 filter 121
 guides 337
 infrared 70
 perception 73
 propagation 71
 ray 71, 179
 shielding 721, 722
 source 76
 life-span 723
 wavelength 723
- ultraviolet 70
 visible 70
- light-slit method 147
- lighting control 163
- lighting systematic 135
- lighting technique 131, 135
- lighting with through-camera view 149
- line
 frequency 744, 745
 fitting 603–606
 outlier suppression 604–606
 robust 604–606
 Hessian normalform 603
 line jitter 597
 scan 320, 441
 scan camera 39, 614, 618–622, 628
 sensor 319, 614
 spread function 264
- linea camera model 212
- linearity 357, 387, 388
- linear system 253
- line-scan processing 743
- line spread function (LSF) 278
- link aggregation grouping 379
- Linux® kernel 407
- local deformation 672
- Lommel functions 244, 245
- long-wavelength pass filter (LWP) 125
- look-up table (LUT) 362–364, 497, 510, 514
- low-pass filter 260
- low-voltage differential signaling (LVDS) 330, 384
- luminance 110, 351
 channel 21, 24
 distribution 116
 indicatrix 116
 of the object 113
- luminescence radiator 76
- luminous efficiency 76
- luminous intensity 110
- LUT, *see* look-up table 690
- m**
- M12 355, 382
- machine learning 793

- machine vision 317, 324
 acquisition architectures 431
 hardware 134
 software 134
 system 31, 32
 accuracy 34
 color space conversion 499
 designing desi 36
 different part types types 33
 image reconstruction 491
 look-up table 497
 memory handling 494
 part presentation perf 33
 parts 33
 region of interest 499
 shading correction 501
 task and benefit 32
 time performance 34
 timing and triggering 492
 magnification factor 618
 magnification ratio 186
 magnocellular pathway 21, 24
 maintenance modus 48
 major axis 553–554, 557, 559, 560, 603, 605
 manufacturing tolerances 284
 marginal ray 207
 mass production, *see* production, mass 699
 material flow 701
 mathematical operator 253
 maximum filter, *see* morphology, gray
 value, dilation 690
 maximum likelihood estimator 680
 maximum transmission unit (MTU) 361, 375, 378
 M cone 10, 24, 26
 MDR connector 443
 mean filter 519–522, 526, 538, 543, 584, 649
 frequency response 523–524, 528, 650
 mean squared edge distance 655–656
 measurement accuracy 38
 measuring error 159
 median filter 526–527, 543
 mesh 757
 metal vapor lamp 78
 Microlens 325
 minimum filter, *see* morphology, gray
 value, erosion 690
 Minkowski addition 562–564, 567, 575–576
 Minkowski subtraction 565, 567, 576
 minor axis 553–554, 557, 559, 560, 603
 mirror 175
 miscellaneous points 41
 missing codes 357
 modulation transfer function (MTF) 6, 17, 281
 semiconductor imaging device 265
 Moiré pattern 7
 moments 552–555, 557–559
 invariant 555
 monitoring, *see* evaluation, monitoring 699
 monochromatic aberration 10
 monochromatic light 82, 85, 101
 monocular images 758, 762
 morphological adaptation 10
 morphology 560–578, 672
 duality
 dilation–erosion 567, 576
 hit-or-miss transform 569
 opening–closing 571, 577
 gray value
 closing 577
 complement 576
 dilation 576
 erosion 576
 gradient 577–578
 Minkowski addition 575–576
 Minkowski subtraction 576
 opening 577
 range 577–578
 region 561–575
 boundary 567–568
 closing 571
 complement 561–562
 difference 561
 dilation 562–565, 567–568, 594
 distance transform 573–575, 655, 657
 erosion 565–568

- morphology (*contd.*)
- hit-or-miss opening 570
 - hit-or-miss transform 568–569, 572
 - intersection 561
 - Minkowski addition 562–564, 567
 - Minkowski subtraction 565, 567
 - opening 569–571
 - skeleton 571–573
 - translation 562
 - transposition 562
 - union 561
- structuring element 562, 568, 575, 576
- motional blurring 121, 169
- motion blur 704, 739–742
 - computation 741, 742
- motion sensitivity 3, 21
- movements 720, 726, 739, 740, 751, 783
 - adjustment 720
 - changeover 720, 722
 - process 720
- MPEG 318
- multi-coated lens 126
- multi-core 710, 713
- multi-drop bus configuration 465
- multi-tap 324
- MultiMediaCard (MMC) 407
- multithreading, *see* interface, multithreading 699
- mvPropView 329
- MVTec's Embedded HALCON 414
- myopia 3
- n**
- National Instruments Compact Vision System (NI CVS) 52
- National Television Systems Committee (NTSC) 435
- natural light 107
- natural vignetting 114, 283
- near cells 25
- near limit 217
- near point 214
- negative principal points 198
- neighborhood 548–549, 568, 573
- neural network 681–685, 688–689
 - activation function
 - hyperbolictangent 683
 - logistic 683
 - sigmoid 683–684
 - softmax 684
 - threshold 682, 683
 - multilayer perceptron 682–685, 688–689
 - training 684–685
 - single-layer perceptron 681–682
 - universal approximator 683, 684
- neutral density filter 125, 129
- neutral filter 129
- noise 330, 334–336, 338, 347–349, 357, 366, 386, 387, 391–393, 517–518
 - floor 393
 - suppression 518–527
 - variance 517, 519, 520, 525, 584, 597
- nondestructive overlays 490
- nonhomogeneous illumination scenes 47
- non-maximum suppression 580, 587, 591–592
- normal distribution 680
- normalized cross-correlation 640, 646–648
- normalized moments 552–553, 557, 560, 603, 605
- null direction 20
- numerical aperture 210
 - image side 229
- Nyquist bandpass 272
- Nyquist frequency 277, 281, 529
- Nyquist limit 7
- Nyquist sampling theorem 269
- o**
- object
 - virtual 187
 - field angle 202
 - field stop 209
 - plane 138
 - recognition, *see* applications 699
 - side field angle 210

- side focal length 192
 side telecentric perspective 226
 side telecentric system 228
 space 191, 200
 object-side field angle 202
 obliquity factor 238
 occlusion 654, 657, 661, 668
 OCR, *see* optical character recognition
 690
 ocular dominance column 23
 OmniVision 337
 ON and OFF channels 18
 one-chip 359
 1-D 319
 one-dimensional representation 262
 1/f noise 392
 OneShot 375
 on-the-go (OTG) interface 412
 OPC Unified Architecture 735, 738 *see also* OPC UA, 699
 opening 569–571, 577
 Open Source Automation Development Lab (OSADL) 408
 “Open Source Computer Vision” (OpenCV) 416
 operating system 41
 optical axis 3, 185
 eye 3
 optical character recognition 512, 532,
 533, 552, 672–690
 character segmentation 672–673
 touching characters 673
 classification, *see* classification 690
 features 674–676
 image rectification 535, 538, 673
 optical density 123
 optical path difference 240
 optical path length 123
 optical transfer function (OTF) 260
 multiplication rule 276
 optic nerve 10–12, 27
 head 3
 optimum setup 45
 orientation 553–555, 557, 560
 exterior 601, 615–616, 620, 623–626
 world coordinate system
 615–616, 620
- column 23
 interior 601, 614–626, 632
 accuracy 629–631
 camera constant, *see* orientation,
 interior, principal distance 690
 camera coordinate system
 615–616, 618–620, 633
 camera motion vector 618
 distortion coefficient (division
 model) 616–631, 632, 636
 distortion coefficients (polynomial
 model) 616, 618, 632
 focal length 614–615, 632
 image plane coordinate system
 616, 620
 image plane system 618, 620
 pixel size 618, 620, 632
 principal distance 614–616, 620,
 629–631, 632
 principal point 618, 620, 629–632
 projection center 614, 632, 633,
 635, 637
 relative 632, 633
 base 633
 base line 635
 outlier 602, 604
 outlier suppression 604–607, 609
 Huberweight function 605
 iteratively reweighted least-squares
 605
 random sample consensus 606
 RANSAC 606
 Tukey weight function 605
 output 382
 overtemperature 88
- p**
- parallax 25
 parallel capturing 742
 parallel digital camera buses 439
 parallel digital connectors 441
 parallel lighting 137
 parallel offset 124
 parameter data, *see* data, parameters
 699
 paraxial region 185

- part handling, *see* production, part handling 699
- partial bright field illumination 139
- parvocellular pathway 21, 24
- pattern recognition 790
- PC-based systems, *see* systems, PC-based 699
- PCI/CompactPCI/PXI 464
- PCI Express/CompactPCI Express/PXI Express 467
- PCI-X 466
- Peripheral Component Interconnect (PCI) bus 464
- permissible defocusing tolerance 247
- permissible size for the circle of confusion 218
- perspective 219
 - transformation 533–534, 538, 672, 673
- PFNC 378, 380
- pharoid ray 207
- phase-lock loop (PLL) 350
- photogrammetry 291
- photometric inverse square law 111
- photometric quantity 110
- photon 12, 14, 71
 - counter 23
 - noise 16, 19, 391
 - shot noise 366, 386
 - transfer 387, 388
 - receptor 1, 3, 6, 7, 11, 12, 23, 25, 26
 - response non uniformity 392
- Photo Response Non Uniformity (PRNU) 392
- phototransduction 12, 26
- photovoltaic effect 328
- pick-and-place 766–767, 771
- pinhole camera 181, 221, 614–618, 627–628
- projectioncenter 614, 632, 633, 635, 637
- pinning, cameras 718
- pipelined global shutter 334
- pixels 265, 267, 318–326, 328–332, 334–338, 345, 347, 349, 351, 357, 359, 363, 365–368, 371, 375, 378, 380, 384, 386, 391, 392, 505–506
 - clock signal 439
 - internal sensor 38
 - rate 40
 - resolution, calculation of 39
 - sensitivity function 265
- plane wave 237
- PLC cycle 737
- PLS 335, 336
- point cloud 754–757, 768
- point spread extension 250
- point spread function (PSF) 256
- Poisson distribution 391
- Poisson statistics 14
- polar coordinates 538
- polarization 107
 - effect of 44
 - filter 125, 130
 - phenomena 236
- polarized light 107
 - circular 107
 - elliptical 107
 - linear 107
 - unpolarized 107
- polarizer 107
- polar transformation 538–539, 673
- polygonal approximation 609–611
 - Ramer algorithm 610–611
- pose 532, 615–616, 620, 644, 672, 702
 - recognition 766
- position recognition, *see* applications, position recognition 699
- position variation 718
- Power-over-Ethernet (PoE) 355, 375, 381, 382, 396
- power supply 726, 727, 773
 - uninterruptible 727
- precision 596, 724
 - edge angle 661
 - edges 596–597
 - hardwarer equirements 597
- preferred direction 19, 20, 22, 27
- Pregius 336, 382
- presynaptic 13
- Prewitt filter 589
- primary colors 351, 359, 360, 367
- principle of triangulation 146
- principal plane 190

- image side 190
- object side 190
- principal point 618, 620, 629–632
- principal ray 207
- print inspection 544–548
- prism 175
- processing load 41
- processing parameters 48
- processing speed 56
- processing time 119
- production
 - batch 703
 - continuous 703, 704, 738, 740
 - continuous motion 737, 740
 - cycle time 739, 778
 - discrete motion 738, 745
 - discrete unit 703, 740
 - job-shop 704
 - mass 703, 704
 - part handling 739
- programmable logic controller (PLC) 715, 730, 732–735, 737, 748–750, 786
- progressive scan 321, 324, 344, 345
 - video 437
- projection 159
 - center 182, 212, 213, 222, 614, 632, 633, 635, 637
- projective transformation 182, 533–534, 538, 644, 672, 673
- PropView 363, 370
- pulse-duty-factor 84, 90
- pulse mode 167
- pupil 3, 10, 12, 27
 - function 243
 - magnification ratio 200, 211, 234
- q**
- quantization noise 392
- r**
- radial spatial frequency 264
- radiant intensity 110
- radii of curvature 192
- radiometric camera calibration 512–517, 600
 - calibration target 513
- chart-based 513
- chart-less 514–517
 - defining equation 514
- gamma response function 513, 516
- inverse response function 514
 - discretization 514, 515
 - normalization 515, 516
 - polynomial 516
 - smoothness constraint 516
 - response function 513, 514, 516
- radiometric quantity 110
- Ramer algorithm 610–611
- rank filter 527, 576
- rapid-prototyping 711
- RAW 367, 368, 380
- RGB to YUV 370
- real object 187
- real-time 714
 - operating systems 408
- receptive field 17–22, 27
- recipes, *see* data, type data 699
- reciprocity equation 196
- recognition, *see* evaluation, recognition 699
- reduced coordinates 244
- reflectance 92, 98, 111
- reflection 92, 179
 - directed 93
 - irregular diffuse 93
 - regular diffuse 93
 - law 92
- refraction 100, 179
 - law 72
- refractive index 183
- region 506–508
 - as binary image 507, 549, 552, 561, 563, 567, 573
 - boundary 556, 567–568
 - characteristic function 507, 557, 575
 - complement 561–562
 - connected components 548–549, 672
 - convex hull 555–556
 - definition 506
 - difference 561
 - feature, *see* features, region 690
 - intersection 561

- region (*contd.*)
- run-length representation 507–508, 549, 552, 561, 563, 573
 - translation 562
 - transposition 562
 - union 561
 - regions of interest (ROIs) 47, 506, 532, 534, 565, 575, 594, 645
 - registration 756, 772
 - regression testing 793
 - regular diffuse reflection 93
 - relative illumination 283
 - relative irradiance 283
 - relative orientation 632, 633
 - base 633
 - base line 635
 - remote maintenance 751, 793
 - removal of surface reflexes 108
 - repeatability, *see* precision 690
 - representation space 258
 - reproducibility 718, 722, 723
 - reserved signal 450
 - reset noise 392
 - resolution 319, 323, 324, 338, 343, 351, 354, 359
 - limit 281
 - resolution 336, 338–340, 342
 - result data, *see* data, results 699
 - retina 2, 3, 6, 11, 12, 19, 26, 27
 - reverse engineering 768
 - RGB cameras 438
 - RGB color space 500
 - rhodopsin 14
 - rigid transformation 615, 644, 653, 662, 672
 - ring acquisition 481
 - ring light 149
 - rivet image 54
 - RJ-45 Ethernet connector 455
 - robot 700
 - assistant 700
 - collaborative 795
 - navigation 770
 - rod photoreceptor 12
 - rods 6, 12, 14, 16, 18, 26
 - ROI, *see* region of interest 690
 - rolling (curtain) shutter 332
 - rotary encoders 372
 - rotation 533, 535, 555, 644, 653, 673
 - RS-170 video standard 437
 - RS-232 382, *see also* interface, serial, 699
 - RS-422 345, 441
 - RS-644 Low Voltage Differential Signaling (LVDS) 441
 - R-table 660
 - run-length encoding 507–508, 549, 552, 561, 563, 573
- s**
- sampling interval 6
 - sampling theorem 7
 - saturation 12, 26, 119, 335, 388, 391
 - scaling 533, 537–538, 555, 644, 654
 - scan camera 36
 - scan cycle 737
 - scattering 92
 - Scheduled Action Command 377
 - S cone 10, 24
 - secondary wavelet 235
 - Secure Digital (SD) 407
 - security, *see* systems, security 699
 - segmentation 540–552
 - connected components 548–549, 672
 - dynamic thresholding 542–544, 577, 672
 - hysteresis thresholding 592–593
 - subpixel-precise thresholding 550–552, 595
 - thresholding 540–542, 672
 - automatic threshold selection 541–542, 672
 - variation model 544–548
 - self-adjustment 793
 - self-retooling 793
 - sensitivity 338, 393
 - sensor 319, 339, 340, 342, 344, 369, 375, 382, 505–506
 - resolution 43, 52
 - size 43
 - sequencer 374
 - sequences 372

- acquisition 480
- SG-pulse 345
- shading correction 365
- shading images 365
- Shannon 7
- shape-based matching 667–671
- shape check, *see* applications, shape check 699
- shifting property 254
- shift register 322, 324, 326, 345
- shift theorem 275
- short-wavelength pass filter 125
- shutter 318, 321–323, 326, 331–337, 345, 349, 350, 371
 - efficiency 335
 - speed 742
 - time 120, 170
- signal
 - bandwidth 727, 728, 750, 751
 - frequency 727, 728, 744, 745, 786
- signal-to-noise ratio 357, 393, 586, 597, 661
- similarity measure 644–649, 668–670
 - absolute sum of normalized dot products 669
 - normalized cross-correlation 640, 646–648
 - sum of absolute gray value differences 640, 645–648
 - sum of absolute normalized dot products 669
 - sum of normalized dot products 669
 - sum of squared gray value differences 640, 645–646
 - sum of unnormalized dot products 668–669
- similarity transformation 644, 653, 662
- simple cells 22
- simultaneous location and mapping, *see* SLAM 699
- 62-pin high-density DSUB connector 443
- skeleton 571–573
- skew 533
- SLAM 770
- slant 533
- slope, *see* gradient 699
- smallest enclosing circle 555, 560
- smallest enclosing rectangle 555, 560, 675
- smart cameras, 41, *see* systems, compact systems 699
 - applications 403
 - block diagram 404
 - cross-compiling 414
 - definition 401
 - design parameters 403
 - field buses 411
 - FPGA processing 406
 - image sensors 409
 - ingress protection 417
 - Java and .NET 414
 - memory and storage 407
 - on-the-go interface 412
 - power dissipation 416
 - processors 404
 - real-time operating systems 408
 - scripting 413
 - third-party tools 416
 - timers and counters 413
 - updates 409
 - USB host interface 412
 - visual programming 415
- Smear 326
- smoothing filter 517–527
 - Gaussian 524–526, 538, 542, 543, 586, 591, 649
 - frequency response 525, 529
- mean 519–522, 526, 538, 543, 584, 649
 - frequency response 523–524, 528, 650
- median 526–527, 543
- optimal 524–525, 586, 591
- spatial averaging 519–522
- temporal averaging 518–519, 545
- SNR 336, 357, 366, 387, 393, 394
- Sobel filter 589
- SoC 709, 714, 794
- software library software 47
- software structure str 47
- solid angle 111
- solid state disk (SSD) 407
- solid state material 83

- SONY HAD 325
 SONY SuperHAD 325
 space invariance 255
 space variant nature of aliasing 274
 spatial averaging 519–522
 spatial depth 219
 spatial domain 528
 spatial frequencies 3, 6, 7, 11, 27, 240,
 260
 components 261
 spatial resolution 38, 57
 SPC, *see* statistical process control 699
 speckle 137
 pattern 85
 spectral band 79
 spectral opponency 21
 spectral response 73, 123
 Gaussian filter 525, 529
 mean filter 523–524, 528, 650
 sensor 505
 spectral sensitivity 348, 351, 356, 360
 spectral transmittance 283
 spectrum 78
 spectrum of light 71
 spherical aberration 5
 spherical wave 237
 spikes 16, 17
 spontaneous spike activity 17
 spurious resolution 6
 square pixels 38, 321
 stabilization 78
 Standard Feature Naming Convention
 (SFNC) 371, 378, 434
 standardization 708, 715, 716, 723,
 730, 791
 standardized viewing distance 219
 standoff distance 42
 static lighting 167
 statistical process control 705
 statistics engine 361
 stereo geometry 632–639
 corresponding points 633
 disparity 638–639
 epipolar line 634
 epipolar standard geometry
 636–637
 epipolar plane 634
 epipole 634
 image rectification 637–638
 stereo matching 639–643
 robust 642–643
 disparity consistency check 643
 excluding weakly textured areas
 642–643
 similarity measure
 normalized cross-correlation 640
 sum of squared gray value
 differences 640
 subpixel-accurate 641–642
 window size 642
 stereopsis 25, 27
 stereo reconstruction 631–643
 stochastic process 517, 519
 ergodic 520
 stationary 517
 streaking light 154
 Strehl ratio 247
 strongly translucent part 161
 structured bright field incident light
 145
 structured lighting 137, 145, 728
 structuring element 562, 568, 575, 576
 subpixeling 38
 subpixel-precise contour 508–509
 convex hull 560
 features, *see* features, contour 690
 subpixel-precise thresholding
 550–552, 595
 sub-pixel region 265
 SUB pulse 345
 sub sampling 338
 sum of absolute gray value differences
 640, 645–648
 sum of absolute normalized dot
 products 669
 sum of normalized dot products 669
 sum of squared gray value differences
 640, 645–646
 sum of unnormalized dot products
 668–669
 superdiffuse ring lights and shadow-free
 lighting 150
 Super HAD 325
 superposition integral 238

- support vector machine 685–689
 kernel 687
 Gaussian radial basis function 687
 homogeneous polynomial 687
 inhomogeneous polynomial 687
 sigmoid 687
 margin 686
 separating hyperplane 685–686
 universal approximator 687
- surface inspection, *see* applications,
 surface inspection 699
- surface orientation 758
- SVGA 338
- S-Video 438
- SVM, *see* support vector machine 690
- SWP 125
- synaptic plasticity 26
- synchronization of flash lighting 170
- sync pulse 349
- system of lenses 202
- System of Units (SI) 110
- systems
- application-package 711, 712
 - compact systems 709, 710, 714, 727–729, 733
 - library-based 711
 - PC-based 709–711, 751, 752
 - security 709, 711, 751
 - types of 706–715
 - vision controllers 710
 - vision sensors 708, 714, 729, 744
- systems-on-chip, *see* SoC 699
- t**
- tangential spatial frequency 264
- taps 440
- TCP/IP 35, 728, 729, 733–735, 751, 783, 784
- telecentric bright field incident light 143
- telecentric bright field transmitted lighting 158
- telecentric camera 614–618, 626–627
- telecentric lighting 136, 159
- telecentric objective 137
- telecentric on axis light 143
- telecentric path 44
- telecentric perspective 228
- telecentric system 219
- object side 228
- telescope magnification 231
- television 317
- temperature compensation 166
- temperature radiator 76
- template matching 544, 643–673
- clutter 654, 657, 661, 668
 - erosion 567
 - generalized Hough transform 658–661
 - accumulator array 658, 660, 661
 - R-table 660
- generalized Hough transform
- accumulator array 658, 660
 - geometric hashing 662–663
 - geometric matching 661–671
 - Hausdorff distance 656–658
 - hierarchical search 651–652, 670
 - hit-or-miss transform 568
 - hypothesize-and-test paradigm 661
 - image pyramid 649–652, 670
 - linear illumination changes 646
 - matching geometric primitives 663–666
 - mean squared edge distance 655–656
 - nonlinear illumination changes 654, 661, 668–669
 - occlusion 654, 657, 661, 668
 - opening 569
 - robust 654–672
 - rotation 653–654
 - scaling 653–654
 - shape-based matching 667–671
 - similarity measure 644–649, 668–670
 - absolute sum of normalized dot products 669
 - normalized cross-correlation 640, 646–648
 - sum of absolute gray value differences 640, 645–648
 - sum of absolute normalized dot products 669

- template matching (*contd.*)
 - sum of normalized dot products
 - 669
 - sum of squared gray value
 - differences 640, 645–646
 - sum of unnormalized dot products
 - 668, 669
- stopping criterion 647–649
 - normalized cross-correlation 648
 - sum of absolute gray value
 - differences 647–648
 - sum of normalized dot products
 - 670
- subpixel-accurate 652–653,
 - 670–671
 - translation 644–652
- temporal averaging 518–519, 545
- temporal control 167
- test object 91, 134
- texture, removal 530–532
- TFT 363, 375
- thermal noise 14
- thicklens
 - of the lens 192
 - magnification factor 618
- thin films 126
- thin lens 193
 - model 42
- 1394a 395
- 1394b 395
- 3D data acquisition
 - active 757, 759–764
 - computer tomography 769
 - deflectometry 757, 761, 768–770
 - interferometry 757, 763, 764, 769, 770
 - laser triangulation 760, 765, 766, 768–771
 - passive 757–759
 - photometric stereo 753, 754, 757, 758, 762, 763, 765, 769, 770
 - shape from disparity 757, 759, 769
 - shape from focus 757, 758, 769
 - shape from shading 757, 758, 762, 769
 - shape from texture 757, 759
 - sheet of light 760
- stereo 753, 757–759, 761, 766, 768–772
- structured light 757–761, 768, 769, 771
- structure from motion 759
- time-of-flight 709, 757, 759, 760, 768, 770, 771
- 3D reconstruction 631–643
- 3D-Systems 753, 772
- thresholded image 54
- thresholding 540–542, 672
 - automatic threshold selection 541–542, 672
 - subpixel-precise 550–552, 595
- tilt rule 188
- timed 371
- time-invariant system 255
- time response 375
- timers 372, 376
- time stamp 361, 377
- timing signals 437
- tolerances 34, 47, 54
- topography 147
- total reflection 95
- traceability 730–732, 736
- transfer function 259
 - of the pixel 267
- transformation
 - affine 532–533, 555, 644, 662, 668
 - geometric 532–539, 673
 - gray value 510–512
 - image 534–539, 544
 - local deformation 672
 - perspective 533–534, 538, 672, 673
 - polar 538–539, 673
 - projective 533–534, 538, 644, 672, 673
 - rigid 615, 644, 653, 662, 672
 - rotation 533, 535, 555, 644, 653, 673
 - scaling 533, 537–538, 555, 644, 654
 - similarity 644, 653, 662
 - skew 533
 - slant 533
 - translation 533, 555, 562, 644, 653
- Transistor-Transistor Logic (TTL)
 - signaling 441
- translation 533, 555, 562, 644, 653

- transmission 96, 98, 122, 123
 chain 267
 diffuse 97
 directed 97
 irregular diffuse 97
 through the lens 114
- transmittance 96, 111
- transmitted lighting 138
- transposition 562
- triangulation 757–761, 769, 770
- trichromatic 24
- trigger 371, 703, 704, 707, 719, 720, 737, 741–743, 745
- triggering pulse 167
- trigger width 371
- Tristimulus theory 359
- Tukey weight function 605
- 12-pin Hirose connector 443
- 2-D 319
- 2.5D 754, 770
- type data, *see* data, type data 699
- u**
- UBS3 Vision 377
- UDP 378
- ultra-short light pulse 722
- ultraviolet (UV) 70, 106, 348
 blocking filter 127
 light 106
- uninterruptible power supply, *see* power supply, uninterruptible 699
- union 561
- unit production, *see* production, discrete unit 699
- Universal Asynchronous Receiver–Transmitter (UART) 450
- Universal Serial Bus (USB) 345, 452, *see also* interface, USB, 699
 host interface 412
 for machine vision 454
- unpolarized light 107
- UPS, *see* power supply, uninterruptible 699
- USB 2.0, 395
- USB 3 Vision standards 342, 345, 378, 380, 385, 394–396, 432, 433
- USB 3.0, 345, 395, 396
- User Datagram Protocol 378
- user interface, *see* human machine interface 699
- v**
- variable height acquisition (VHA) 494
- variance 387, 392
- variation model 544–548
- VD 350
- veiling glare 283
- velocity of light 180
- ventral stream 22
- verification, *see* evaluation, verification 699
- Vertical Synchronization (Vsync) pulse 437
- vertices 192
- VHDCI connector 443
- vibrations 739
- Video Graphic Array (VGA) 338, 413
 camera 52
- video signal 267
- vignetting 116, 513
- visible light (VIS) 70, 101, 103
- vision controllers, *see* systems, vision controllers 699
- vision sensors, *see* systems, vision sensors 699
 applications 419
 component parts 420
 definition 401
 description 418
 environmental considerations 421
 programming and configuring 420
- vision system design 399
- visual cortex 12, 22, 23, 25
- vitreous chamber 2
- $V(\lambda)$ -curve 73
- Vsync signal 439
- w**
- wave–particle dualism 71
- wave equation 179
- wavefront
 aberration 247
 plane 180

- wavefront (*contd.*)
 spherical 180
waveguides 8
wavelength, 183, *see* light source,
 wavelength 699
wave nature of light 235
wave number 237
web server, *see* interface, network 699
weight function
 Huber 605
 Tukey 605
WEN 350
white light 103
 scanners 312
windows 209
wiring 729, 742
wood effect 106
working distance 123, 717, 718
world coordinates
 from single image 601, 626–628
- line scan camera 628
pinhole camera 627–628
telecentric camera 626–627
from stereo reconstruction 631–643
the world is grey 361
- x**
Xenon flash lamp 79, 80
Xilinx Zynq® 405
XML 378
- y**
Y'CbCr 371
Yet Another Flash File System (YAFFS)
 407
YUV 370, 371
- z**
zero copy mechanism 380
zero-crossing 581, 582, 595

