

Table of content

| | |
|--|-----|
| Acknowledgement | VII |
| Foreword | IX |
| List of symbols used | XV |
| I. Greek symbols | XV |
| II. Latin symbols | XV |
| 1 Basics | 1 |
| 1.1 Basics and technical implementation of bentonite lubrication systems ... | 1 |
| 1.1.1 Control unit | 2 |
| 1.1.2 Mixing tank | 2 |
| 1.1.3 Storage tank | 3 |
| 1.1.4 Main jacking station | 3 |
| 1.1.5 Tunnelling machine | 3 |
| 1.1.6 Lubrication ring | 3 |
| 1.1.7 Intermediate jacking station | 3 |
| 1.1.8 Jacked pipe | 3 |
| 1.1.9 Lubrication station | 3 |
| 1.1.10 Injection fittings | 4 |
| 1.1.11 Bentonite pump | 4 |
| 1.1.12 Compressed air feed | 5 |
| 1.1.13 Control cable | 5 |
| 1.1.14 Bentonite or feed line | 5 |
| 1.2 Annular gap lubrication in pipe jacking | 5 |
| 1.3 Preliminary remarks about the ground | 6 |
| 2 Bentonite and bentonite suspensions | 9 |
| 2.1 Composition and structure | 9 |
| 2.2 Hydration behaviour | 10 |
| 2.3 Card house structure and thixotropy | 11 |
| 2.4 Yield point, viscosity and gel strength | 12 |
| 2.5 Stability | 17 |
| 2.6 Usual types of bentonite | 19 |
| 2.6.1 Natural bentonite (Ca or Na) | 19 |
| 2.6.2 Activated or active bentonite | 19 |
| 2.6.3 Bentonite with polymer additives | 20 |
| 3 Additives | 21 |
| 3.1 Polymers | 21 |
| 3.1.1 Functions of polymer additives | 21 |
| 3.2 Types of polymer additives | 24 |
| 3.2.1 Starch | 24 |
| 3.2.2 Xanthan | 25 |
| 3.2.3 Guarana | 26 |
| 3.2.4 Modified celluloses (PAC, MEC, HEC, CMC) | 26 |

| | | |
|----------|---|-----------|
| 3.2.5 | Polyacrylamide/-acrylate | 27 |
| 3.3 | Overview of polymer additives and their functions | 27 |
| 4 | Correct preparation of bentonite suspensions | 29 |
| 4.1 | Mixing | 29 |
| 4.1.1 | Procedure for the preparation of suspension | 30 |
| 4.2 | Mixing equipment | 33 |
| 4.3 | Mixing instructions | 34 |
| 4.3.1 | Mixing instructions for mixers with mixing pump | 34 |
| 4.3.2 | Mixing instructions for mixers with water jet pump | 34 |
| 4.4 | Hydration tank | 35 |
| 5 | Properties of the suspension and measurement processes | 37 |
| 5.1 | Viscosity: Marsh funnel | 37 |
| 5.2 | Yield point: ball-harp rheometer | 40 |
| 5.3 | Viscosity and gel strength: Rotational viscometer | 42 |
| 5.4 | Filtrate water and thickness of filter cake: filter press | 43 |
| 5.5 | Density | 45 |
| 5.5.1 | Measurement using a mud balance | 45 |
| 5.5.2 | Measurement using a pycnometer | 45 |
| 5.6 | Water hardness: test strips | 46 |
| 5.7 | pH value | 46 |
| 5.7.1 | Determination with pH test strips | 46 |
| 5.7.2 | Measurement with a pH meter | 46 |
| 5.8 | Conductivity | 46 |
| 5.9 | Temperature | 47 |
| 6 | Ground and groundwater | 49 |
| 6.1 | Geology of solid rock | 49 |
| 6.1.1 | Classification of rocks | 50 |
| 6.1.2 | Mineral content and mineral structure | 50 |
| 6.1.3 | Uniaxial rock compression strength | 50 |
| 6.1.4 | Tension strength | 53 |
| 6.1.5 | Rock mass strength | 54 |
| 6.1.6 | Rock abrasiveness | 54 |
| 6.1.7 | Interface structure | 55 |
| 6.1.8 | Degree of weathering | 58 |
| 6.1.9 | Rock mass classification | 59 |
| 6.2 | Geology of soils | 65 |
| 6.2.1 | Types of minerals | 65 |
| 6.2.2 | Grain size and grain size distribution | 65 |
| 6.2.3 | Grain rounding | 77 |
| 6.2.4 | Pores | 78 |
| 6.2.5 | Compactness | 80 |
| 6.2.6 | Shear strength | 82 |
| 6.2.7 | Atterberg limits | 83 |
| 6.2.8 | Swelling capability | 85 |

| | | |
|----------|---|------------|
| 6.3 | Stability and stand-up time..... | 85 |
| 6.3.1 | Assessment of stability according to the working face behaviour..... | 85 |
| 6.3.2 | Evaluation of stand-up time using the RMR and Q systems..... | 87 |
| 6.4 | Hydrogeology..... | 88 |
| 6.4.1 | Basic hydrological terms..... | 88 |
| 6.4.2 | Permeability..... | 89 |
| 6.4.3 | Determination of permeability of soil..... | 93 |
| 6.4.4 | Determination of permeability in rock..... | 96 |
| 6.5 | Influence of various rock properties on the use of bentonite..... | 99 |
| 6.6 | Contamination in the ground, groundwater or mixing water..... | 100 |
| 6.6.1 | pH value..... | 100 |
| 6.6.2 | Salt water..... | 101 |
| 6.6.3 | Water hardness due to calcium or magnesium ions..... | 101 |
| 6.6.4 | Chlorine..... | 102 |
| 6.6.5 | Iron..... | 102 |
| 6.6.6 | Humic acids..... | 102 |
| 6.6.7 | Cement / concrete..... | 102 |
| 6.6.8 | Overview of the thresholds for contamination of the mixing water..... | 103 |
| 6.6.9 | Effects of contaminations on the properties of the suspension..... | 103 |
| 7 | Bentonite suspensions for annular gap lubrication..... | 105 |
| 7.1 | Size of the annular gap..... | 105 |
| 7.1.1 | Skin friction..... | 106 |
| 7.2 | Vertical position of the pipe string in the driven cavity..... | 107 |
| 7.2.1 | Floating..... | 108 |
| 7.2.2 | Ballasting..... | 109 |
| 7.2.3 | Vertical position of the pipe string in stable ground..... | 109 |
| 7.2.4 | Vertical position of the pipe string in unstable ground..... | 110 |
| 7.3 | Functions of the lubricant in the annular gap..... | 111 |
| 7.3.1 | Support function..... | 112 |
| 7.3.2 | Lubricating function..... | 115 |
| 7.3.3 | Carrying capacity..... | 116 |
| 7.3.4 | Consequences of poor adaptation of the lubricant..... | 117 |
| 7.4 | Adaptation of the bentonite suspension to the ground..... | 119 |
| 7.4.1 | Basic geological parameters..... | 119 |
| 7.4.2 | Flow diagrams for rock..... | 119 |
| 7.4.3 | Flow diagrams for soils..... | 121 |
| 7.4.4 | Relationships between ground and lubricant parameters..... | 123 |
| 7.4.5 | Hydrogeological parameters..... | 124 |
| 7.5 | Rheological parameters of the bentonite suspension..... | 124 |
| 7.5.1 | Particle size..... | 125 |
| 7.5.2 | Yield point..... | 127 |
| 7.5.3 | Viscosity..... | 129 |
| 7.5.4 | Gel strength..... | 130 |
| 7.6 | Suspension quantities..... | 132 |
| 7.6.1 | Definition of terms..... | 132 |

| | | |
|-----------|---|-----|
| 7.6.2 | Basic principles for the determination of the required suspension quantity..... | 141 |
| 7.6.3 | Calculation of the suspension quantities V_{machine} and $V_{\text{pipe string}}$ | 145 |
| 7.7 | Time-dependant loss volumes..... | 147 |
| 7.8 | Lubrication strategies..... | 148 |
| 7.8.1 | Interval-controlled systems..... | 148 |
| 7.8.2 | Volume-controlled systems..... | 150 |
| 7.8.3 | Lubrication strategies for initial and subsequent injection..... | 152 |
| 7.8.4 | Special lubrication strategies with Direct Pipe© and related processes... | 153 |
| 8 | Lubrication technology | 155 |
| 8.1 | Arrangement and spacing of the lubrication points in the pipe string..... | 155 |
| 8.2 | Number and arrangement of the injection fittings per lubricating point in the pipe cross-section..... | 156 |
| 8.3 | Non-return valves..... | 157 |
| 8.4 | Lubrication circuit..... | 158 |
| 8.5 | Interaction between the support pressure at the face and the annular gap pressure..... | 159 |
| 8.6 | Bentonite supply in the starting area..... | 160 |
| 8.7 | Lubricant pressure, lubricant quantity and pressure losses..... | 161 |
| 9 | Reporting | 163 |
| 9.1 | Which parameters should be documented for bentonite lubrication?..... | 163 |
| 9.2 | Forms..... | 163 |
| 10 | Lists of the required injection quantities | 167 |
| 10.1 | Explanation of the lists..... | 167 |
| | Literature | 197 |