

Index

a

abutments, of bridge 90, 108, 112, 113
 access on 241–242
 continuous deck
 with dampers located on 223
 with single fixed point at one
 203–211
 with expansion joint
 only in structure 90
 in structure and track 90–92
 fixed loads
 forces acting on 138–140
 loads transmitted by deck 137–138
 transversal cross section of 137
 fixed point 91–95
 accidental situations 118
 aerodynamic actions, from passing trains
 123
 Alcántara Bridge 20, 306, 307
 alert limit (AL) 47
 alignment, track geometric quality 47
 Almonte Bridge 20, 304, 305
 antimetric vibration modes 169–171
 anti-noise panel, on bridge 14
 AP-7 Viaduct Almeria, Spain 82
 arch bridges
 tied 85, 86
 upper deck bridges 83–85
 Arroyo de las Piedras Viaduct 223
 asymmetric switch rail profile 197, 198
 Avignon viaducts 8, 284, 285

b

ballasted track 186, 187
 definitions, functions, and qualities
 32
 evolution of 36–37
 longitudinal design 65–66
 optimised 41–43
 partial ballast removal 119, 120
 ballastless track 43–45, 66
 bearings, for bridges
 arrangement continuous decks 97, 99
 friction 124
 layout 112
 POT bearings 95, 98, 112
 replacement 242, 243
 simply supported bridges 96–98, 224,
 226
 spherical bearing 96, 98
 track-structure interaction 189–190
 Beipanjiang Bridge 18–20, 324, 325
 bi-block sleepers 37, 38
 braking force 121–122
 bridge substructure elements, impact on
 126
 British high-speed bridges 12
 Built Bridges 66

c

cable-stayed bridges 13, 86–88
 cable-supported bridges
 cable-stayed bridges 86–88

- cable-supported bridges (*contd.*)
 - extradosed bridges 85–86
 - hybrid bridges 89
 - suspension bridges 88
- central fixation 71–72
- central piers
 - continuous deck
 - with fixed point at one 211
 - with several fixed points at 221, 222
 - for fixed point, in Spanish HS railway 220
- centrifugal forces 122, 132, 134–135
- characteristic equation, dynamic analysis 174–177
- China bridges
 - Beipanjiang Bridge 18–20, 324, 325
 - description of 317
 - high-speed railway bridges 10, 11
 - Hutong Yangtze River Bridge 21–22
 - isostatic deck 17
 - isostatic multi span bridge 10, 11
 - isostatic solutions 13
 - Nanjing Dashengguan Yangtze River Bridge 320, 321
 - Tianxingzhou Yangtze River Bridge 318, 319
 - Tongling Yangtze River Bridge 322, 323
 - Wufengshan Yangtze River Bridge 88, 328, 329
 - Yachihe Bridge 326, 327
- Colne Valley Viaduct, England 12, 15
- columns, track-structure interaction 190
- Complete Quadratic Combination (CQC) 155
- composite bridges, with double ‘I’ steel beam 80, 81
- concentrated mass matrix 171–172
- conceptual design
 - arch bridges
 - tied 85, 86
 - upper deck bridges 83–85
 - cable-supported bridges
 - cable-stayed bridges 86–88
 - extradosed bridges 85–86
 - hybrid bridges 89
 - suspension bridges 88
 - deck pre-dimensioning 109–111
 - design situation 66–67
 - high-level viaducts 71–72
 - long span structures 72
 - long viaducts 67–71
 - low profile 68–71
 - short crossing at low level 67
 - fixed point, of bridge 108
 - information analysis 107–108
 - infrastructure pre-design
 - abutments 112, 113
 - fixed point and bearings 112
 - piers 113–114
 - longitudinal design strategies
 - ballasted track 65–66
 - ballastless track 66
 - fixed points, design of 66
 - short and long viaduct 64
 - simply supported decks 64
 - ultra-long and continuous viaducts 64, 65
 - methodology 107
 - overview of 61
 - plan and elevation 106
 - preliminary geotechnical data 107
 - railway platform 106
 - seismic design (*see* seismic design)
 - span distribution 109
 - straight deck solutions 72
 - concrete box hollow sections 78–80
 - continuous slab concrete decks 73–75
 - precast beam decks 74–77
 - simply supported solutions 72–73
 - steel beam decks 80–81
 - steel semi-through decks 81–82
 - structural and functional requirements
 - braking and traction forces 62–63
 - expansion joints 62, 63
 - longitudinal fixation 62
 - track to bridge deck interaction 63
 - vertical accelerations control 62
 - vertical stiffness 62

- structural elements
 - abutments 90–95
 - bearings 95–99
 - piers 95–97
 - topography 106
 - truss bridges 82, 83
 - water flood level 107
 - concrete box hollow sections 78–80
 - Concrete-Filled Steel Tube (CFST)
 - scaffolding method 324
 - concrete slab deck type, solid pier for 95, 96
 - continuous bridges 17–19
 - continuous decks
 - with dampers located on 223
 - longitudinal behaviour, seismic design 100–101
 - seismic design 220–223
 - with single fixed point at one 203–211
 - Spanish bridge with 8, 9
 - track-structure interaction 220–223
 - continuous frame 69
 - continuous slab concrete decks 73–75
 - continuous viaduct 71
 - continuous welded rail (CWR) 35–36, 185, 186
 - Contreras Bridge 300, 301
 - conventional vs. high-speed railway bridges 4
 - creep and shrinkage 192–193
 - crossbar control lever mechanism 199
 - cross-level, track geometric quality 47
 - CWR *see* continuous welded rail (CWR)
- d**
- damping devices plus bearings 104–105
 - damping index 180, 181
 - dead loads 110, 111, 118–119
 - deck (bridge) 72
 - access on 240
 - concrete box hollow sections 78–80
 - continuous (*see* continuous decks)
 - continuous slab concrete decks 73–75
 - cross section of 110, 111
 - double-level truss 87
 - drainage of 247
 - expansion joints 243–246
 - impact against structural elements of 125–126
 - isostatic 7, 17
 - loaded state 134
 - longitudinal displacement of 54–55
 - longitudinal schemes (*see* longitudinal track-bridge interaction)
 - precast beam 74–77
 - pre-dimensioning 109–111
 - simply supported (*see* simply supported deck)
 - steel beam 80–81
 - steel semi-through 81–82
 - track-structure interaction 189
 - track to deck interaction 63
 - transverse deformation and vibration of 53–54
 - twist 51
 - unloaded state 133
 - vertical acceleration of 48–50
 - vertical deformation of 51–53
 - wind force in 133, 134
 - deck twist 51
 - derailment 125
 - design regulations, for bridges
 - accidental load situations 117
 - cross section 129
 - deformation and vibrations, verifications 128–129
 - dynamics effects
 - consideration of 125
 - principal factors 124–125
 - railway vehicle derailment 125–126
 - static forces 124
 - elevation 129
 - fixed abutment, forces and preliminary design of 130
 - fixed abutment loads
 - forces acting on 138–140
 - loads transmitted by deck 137–138
 - transversal cross section of 137
 - horizontal forces
 - centrifugal force 132

- design regulations, for bridges (*contd.*)
 - traction and braking 131–132
- permanent loads
 - dead loads 118–119
 - partial ballast removal 119, 120
 - self-weight 118
- pre-dimensioning 130
 - centrifugal forces 134–135
 - loads per bearings 136
 - pier heads, reaction in 135
 - transversal wind bearings reactions 136
 - vertical forces 133–134
 - wind at unloaded state 135
 - wind with live load 135
- project situations 117–118
- traffic loads
 - application of 126–128
 - for fatigue 128
- variable loads
 - aerodynamic actions, from passing trains 123
 - bearings' friction 124
 - centrifugal forces 122
 - nosing forces 123
 - thermal actions 123
 - traction and braking forces 121–122
 - vertical live loads 119–121
- vertical loads
 - dynamic factor 131
 - eccentricity of 131
 - live loads 130–131
 - permanent loads 130
 - wind speed 132–134
- diagonal matrix 172–173
- discontinuous deck, seismic design 223–226
- displacements, verification of
 - horizontal displacement 195–196, 231–234
 - vertical displacement 196, 234–235
- DLF *see* Dynamic Load Factor (DLF)
- double-level truss deck 87
- drainage maintenance 246–247
- dynamic amplification
 - of deck deformation and acceleration 49
 - and resonance 2–3
- dynamic analysis *see also* Dynamic Load Factor (DLF)
 - antimetric vibration modes 169–171
 - characteristic equation 174–177
 - concentrated mass matrix 171–172
 - damping effects 164–165
 - damping index 180, 181
 - degrees of freedom 169
 - diagonal matrix 172–173
 - eigenfrequency and eigenmode 180
 - eigenvectors matrix 178–179
 - interoperability 167–168
 - isolated load 158–161
 - maximum deflection 182–183
 - modal superposition method 153
 - eigenforms, formulation based on 155–158
 - matrix formulation, for finite element analysis 153–155
 - resonance 143–144
 - stiffness matrix 170
 - symmetric vibration modes 169–171
- train load 162–164
- vehicle-structure interaction model 165–167
- dynamic load factor (DLF)
 - damping effects 165
 - defined 143
 - dynamic analysis 147–152
 - envelope dynamic factor 144–145, 168–169
 - for real trains 145–147
 - single degree-of-freedom system 249–257
 - train velocity, function of 164
- dynamics effects, of bridge
 - consideration of 125
 - derailment 125
 - principal factors 124–125

- railway vehicle impacts
 - on bridge substructure elements 126
 - structural elements, of deck 125–126
 - static forces 124
- e**
- earthquake intensity levels 225
- Eigenforms, formulation based on 155–158
- elastic direct fastener 39
- elastic indirect fastener 39, 40
- EN 1337-1 124
- EN-1990 127, 128
- EN 1991-2 50–52, 54, 121–123, 125, 127, 130, 145, 148, 167, 189, 191, 194
- EN 1990 Annex A2 52, 53, 56
- England, Colne Valley Viaduct in 15
- envelope dynamic factor 144–145, 168–169
- ERRI committees 55
- ERRI D190 committee 57
- Europe
 - aesthetics in 22
 - continuous bridges 13
- European railways systems, interoperability of 167
- exceptional geometries, track-structure interaction 226–228
- expansion joints
 - drain trough 247
 - example of 244, 246
 - neoprene expansion joint 244, 246
 - rotation at 62
 - steel plates joint
 - in fixed abutment 243, 244
 - in movable abutment 244, 245
 - track 63
- extradosed bridges 85–86
- f**
- fasteners 33, 39–40
- Filstal Bridge 278, 279
- finite element analysis, matrix formulation for 153–155
- first high-speed bridges 6
 - French bridges 8
 - German bridges 6–7
 - Spanish bridges 8–9
- ‘Fish belly’ rail 40
- fixed abutments
 - with brackets 92, 93
 - with friction slab 94, 95
 - longitudinal configuration of 91, 92
 - with POT bearings 91–94
 - with prestress 92, 94
- fixed transversal support 101–102
- force per length vs. longitudinal displacement law 189, 190, 208, 226
- foundations, track-structure interaction 190–191
- frame sleepers 38, 39
- French bridges
 - Avignon viaducts 284, 285
 - description of 281
 - first-generation 8
 - Garde-Adhémar Viaduct 282, 283
 - Mornas Viaduct 286, 287
 - Savoireuse Viaduct 9, 17, 288, 289
- Fresno Viaduct, in California 12
- g**
- Gänsebachtal Viaduct 5, 6, 9, 10, 72, 274, 275
- Garde-Adhémar Viaduct 282, 283
- Gemünden Bridge 7, 18, 264, 265
- German bridges
 - description of 263
 - Filstal Bridge 278, 279
 - first-generation 6–7
 - Gänsebachtal Viaduct 5, 6, 9, 10, 18, 19, 72, 274, 275
 - Gemünden Bridge 18, 264, 265
 - Hämerten Bridge 276, 277
 - Nantenbach Bridge 21, 270, 271
 - Pfeiffetal Bridge 18, 268, 269
 - semi-integral bridges 13

German bridges (*contd.*)
 Unstruttal Bridge 9, 10, 18, 19, 272, 273
 Veitshöchheim Bridge 7, 266, 267
 German Requirements Catalogue 200
 grooved rail 41

h

Hämerten Bridge 276, 277
 heavy load models 120
 high-level viaducts 71–72
 High Speed Load Model (HSLM-A) 50, 148, 167
 geometry of 148, 149
 maximum acceleration 150, 151
 maximum displacement 150, 151
 parameters of 148, 149
 hollow pier, with variable dimensions 95, 97
 HSLM-A *see* High Speed Load Model (HSLM-A)
 HSLM-B trains 167–168
 Hutong Yangtze River Bridge, China 21–22
 hybrid bridges 89
 hydraulic dampers, deck and abutment 100
 hydraulic viscodamper 104, 105

i

immediate action limit (IAL) 47
 International Union of Railways
 publication UIC 776-1 145
 interoperability 167–168
 intervention limit (IL) 47
 inverted frame system 69–70
 isolated load 158–162
 isostatic bridges 17
 isostatic multi span bridge, China 10, 11

j

Japan bridges
 description of 309
 Kumagawa Bridge 312, 313

Sannai-Maruyama Bridge 314, 315
 Yashiro Bridge 310, 311

k

Kumagawa Bridge 312, 313

l

La Grenette Viaduct 8
 landscape
 bridges in 15–22
 traveller's 13–15
 Lisbon, Tagus River Crossing in 22, 87, 88
 Llinars Del Vallès Viaduct 294, 295
 longitudinal displacement, of deck 54–55
 longitudinal level
 defined 47
 limit values for 47, 48
 longitudinal track-bridge interaction 203
 continuous deck
 with fixed point, one central piers 211
 with single fixed point, one abutments 203–211
 deck divided into continuous stretches 216–218
 fixed points at two abutments and structural joint in middle 212–216
 simply supported spans 211–213
 long-span bridges 11, 13, 23

m

maintenance, conceptual design for
 accesses 240
 abutments 241–242
 decks 240
 piers 240–241
 bearings 242–243
 designers work 239
 drainage 246–247
 expansion joints 243–246
 optimal structures 239

Maria Pia Bridge, Portuguese 23–24
 mean wind speed 132
 Millipede bridges 69
 modal superposition method 153
 eigenforms, formulation based on 155–158
 matrix formulation, for finite element analysis 153–155
 monobloc sleepers 37, 38
 monotonous bridge 69
 Mornas Viaduct 286, 287
 movable scaffolding systems (MSS) 79, 80
 multicomponent action, characteristic values of 127–128
 multiple degrees of freedom (MDOF) 153

n

Nanjing Dashengguan Yangtze River Bridge 320, 321
 Nantenbach Bridge 21, 270, 271
 Nationally Determined Parameters (NDP) 189
 neoprene expansion joint 244, 246
 nosing forces 123

o

Osera Bridge 292, 293

p

passenger comfort 3, 55–57
 peak wind speed 132
 pendulum devices 103, 104
 permanent loads 130
 dead loads 118–119
 partial ballast removal 119, 120
 self-weight 118
 persistent situations 117
 Pfeiffetal Bridge 7, 18, 268, 269
 pier heads
 maximum axial reaction in 136
 reactions in 135
 piers 95–97
 access on 240–241

elastic re-centring element 105
 foundations of 113–114
 transversal damping system in 102
 transversal stoppers at 102
 Portuguese, Maria Pia Bridge 23–24
 pot-bearing behaviour model 223, 224
 precast beam decks 74–77
 pre-fabricated solution 76
 Prud'homme formula 45

r

rail expansion joints (REJs)
 bridge needed 204–206
 bridge not needed 206–211
 deck divided into continuous stretches 216–218
 design of
 asymmetric switch rail profile 197, 198
 crossbar control lever mechanism 199
 functional principle of 197
 gaps 199, 200
 maximum displacement 197
 picture of 198
 uplift forces 200
 installation 201–204
 rail stresses with 215, 216
 regulation 201, 202

rails

track component 33–34
 ‘fish belly’ 40
 grooved 40, 42
 Vignoles type 40, 41
 track-structure interaction 189

rail stresses

braking load 210
 computed for bridge 207, 213
 envelope of 211, 228
 for left viaduct 218
 with REJ 215, 216
 for right viaduct 218
 seasonal variation of temperature 214
 vertical traffic load 210
 rail traffic security 3

- Real Trains 50
- REJs *see* rail expansion joints (REJs)
- Riudellots Viaduct, Spain 67

- S**
- Salto Del Carnero Railway Bridge 296, 297
- Sannai-Maruyama Bridge 314, 315
- Sar Viaduct, Spain 4, 5
- Savoireuse Viaduct 9, 17, 288, 289
- SDOF system 150, 152, 154 *see also*
 - single degree-of-freedom (SDOF) system
- seismic design
 - longitudinal behaviour
 - continuous decks 100–101
 - simply supported spans 100
 - seismic behaviour and deck articulation 99–100
 - strategies 99
 - track-structure interaction 218–220
 - continuous deck 220–223
 - discontinuous deck 223–226
 - transversal behaviour
 - damping devices plus bearings 104–105
 - fixed transversal support 101–102
 - relative vertical rotation axis 101
 - transversal damping systems 102–104
- seismic situations 118
- Serviceability Limit State (SLS) 117
 - for bridge 31
 - deck
 - longitudinal displacement of 54–55
 - transverse deformation and vibration of 53–54
 - twist 51
 - vertical acceleration of 48–50
 - vertical deformation of 51–53
 - levels of comfort 55–57
 - track geometry quality 46–48
 - track-vehicle dynamic interaction 44–46
- Shock Transmitter Units (STUs) 222, 225
- short-span bridges 22
- simply supported deck 72–73, 96–98
 - bearings for 224, 226
 - longitudinal behaviour, seismic design 100
 - without longitudinal continuity 211–213
- single degree-of-freedom (SDOF) system
 - damped system, subjected to triangular load 258
 - auxiliary expressions 259–261
 - time interval 261–262
 - Dynamic Load Factor 249–257
 - resonance 257–258
- singular bridges 18–22
- sleepers 32–33, 37–39
- SLS *see* Serviceability Limit State (SLS)
- span by span isostatic solution (China) 5
- Spanish bridges
 - Alcántara Bridge 20, 306, 307
 - Almonte Bridge 20, 304, 305
 - AP-7 Viaduct Almeria 82
 - Contreras Bridge 300, 301
 - description of 291
 - first-generation 8–9
 - Llinars Del Vallès Viaduct 294, 295
 - Osera Bridge 292, 293
 - recent bridges 10
 - Riudellots Viaduct 67
 - Salto Del Carnero Railway Bridge 296, 297
 - Ulla Bridge 21, 24
 - Viaduct Over AP7 Riudellots de la Selva 298, 299
 - Viaduct Over River Ulla 302, 303
- Spanish HS railway, central pier for fixed point in 220
- Square Root of the Sum of the Squares (SRSS) 154, 161
- steel beam decks 80–81
- steel damping bearings 103, 104

- steel plates joint
 - in fixed abutment 243, 244
 - in movable abutment 244, 245
 - steel semi-through decks 81–82
 - steel sleepers 37, 38
 - steel truss bridges 82, 83
 - stiffness matrix 170
 - STUs *see* Shock Transmitter Units (STUs)
 - suspension bridges 88
 - switches/crossings 34–35
 - symmetric vibration modes 169–171
- t**
- Tagus River Crossing, in Lisbon 22, 87, 88
 - temperature variations 191
 - thermal actions 123
 - Tianxingzhou Yangtze River Bridge 318, 319
 - tied arch bridges 85, 86
 - timber sleeper 37
 - Tongling Yangtze River Bridge 322, 323
 - track, for high-speed bridges
 - ballasted 65–66
 - ballastless 43–45, 66
 - components
 - ballast 32, 36–37
 - fasteners 33, 39–40
 - rails 33–34, 40–41
 - sleepers 32–33, 37–39
 - switches and crossings 34–35
 - continuous welded rail 35–36
 - conventional track superstructure 31
 - dead loads, road vs. railway bridges 29, 30
 - description of 29
 - expansion joints 63
 - operational conditions 31
 - optimised ballasted track 41–43
 - SLS (*see* Serviceability Limit State (SLS))
 - track-infrastructure interaction 36
 - traffic loads, road vs. railway bridges 29–31
 - ULS, track and vehicle 31
 - track gauge, defined 47
 - track geometry quality 46–48
 - track-infrastructure interaction 36
 - track joints 187, 188, 191, 196
 - track-structure interaction 4, 123
 - analysis, model for 188
 - bearings 189–190
 - columns 190
 - force per length vs. longitudinal displacement 189, 190, 208, 226
 - foundations 190–191
 - horizontal levels 188
 - rails and deck 189
 - creep and shrinkage 192–193
 - description of 185
 - exceptional geometries 226–228
 - load combinations for 194
 - longitudinal schemes 203
 - continuous deck with fixed point, one central piers 211
 - continuous deck with single fixed point, one abutments 203–211
 - deck divided into continuous stretches 216–218
 - fixed points at two abutments 212–216
 - simply supported spans 211–212
 - problem statement
 - ballasted track 186, 187
 - continuous welded rail 185, 186
 - relative displacements 187
 - relative movements 186
 - structural configuration 187–188
 - vertical traffic loads 187–188
 - rail expansion joints 197–203
 - seismic design 218–220
 - continuous deck 220–223
 - discontinuous deck 223–226
 - step-by-step computations 193–194, 209, 210
 - temperature variations 191
 - traction and braking forces 191–192
 - verifications
 - horizontal displacement 195–196, 231–234

- track-structure interaction (*contd.*)
 - stresses 194–195, 229–234
 - track joints 196
 - vertical displacement 196, 234–235
 - vertical loads 192
 - track-vehicle dynamic interaction 44–46
 - traction and braking forces 121–122
 - horizontal forces 131–132
 - track-structure interaction 191–192, 195
 - traffic loads
 - application of 126–128
 - for fatigue 128
 - train load 162–164
 - transitional situations 118
 - transversal behaviour, seismic design
 - damping devices plus bearings 104–105
 - fixed transversal support 101–102
 - relative vertical rotation axis 101
 - transversal damping systems 102–104
 - transversal wind bearings reactions 136
 - transverse deformation and vibration, of deck 53–54
 - transverse load imbalances, between rails 121
 - traveller's landscape 13–15
 - truss bridges 82, 83
 - 21st century, structural engineering of 24
- U**
- U cross sections 67–69
 - UIC leaflet 774-3 54
 - UIC leaflet 776-3 52, 53, 200
 - Ulla Bridge, Spain 21, 24
 - tubular-framed 89
 - Ultimate Limit State (ULS) 31, 117
 - Universal dynamic train A 167
 - Universal dynamic train B 167–168
 - Unstruttal Bridge 9, 10, 18, 19, 272, 273
 - upper deck arch bridges 83–85
 - USA high-speed rail bridges 12
 - U-shaped beams 75
- V**
- Veitshöchheim Bridge 7, 266, 267
 - verifications, of track-structure interaction
 - horizontal displacement 195–196, 231–234
 - stresses 194–195, 229–234
 - track joints 196
 - vertical displacement 196, 234–235
 - vertical acceleration
 - control of 62
 - of deck 48–50
 - vertical deformation, of deck 51–53
 - vertical loads 133–134
 - dynamic factor 131
 - eccentricity 131
 - live loads 119–121, 130–131
 - permanent loads 130
 - POT bearings 136
 - track-structure interaction 192
 - vertical track stiffness 46
 - vertical traffic loads 186–187
 - Viaduct Over AP7 Riudellots de la Selva 298, 299
 - Viaduct Over River Ulla 302, 303
 - vibration modes 161, 162
 - Vignoles rail 40, 41
- W**
- wind speed 132–134
 - Wufengshan Yangtze River Bridge 88, 328, 329
- Y**
- Yachihe Bridge 326, 327
 - Yashiro Bridge 310, 311

