

Index

a

acoustical comfort 2
 adsorption constant 170
 air displacement 134
 airflow in, open-porous materials
 at building level
 applications 145–148
 conservation law 143–145
 defined 141–142
 large openings 142–143
 thermal stack 142
 combined heat and airflow
 air-permeable layers, joints
 and leaks 153
 heat balance 148
 non-steady-state, flat assemblies
 152–153
 non-steady-state, two and three
 dimensions 153
 steady-state, flat assemblies
 148–152
 steady-state, two and three
 dimensions 152
 vented cavities 153–155
 conservation law 135–138
 one dimension, flat assemblies
 138–139
 through assemblies 140–141
 two and three dimensions 139–140
 air flux 242
 air permeance 134, 137

air pressure differentials
 fans 133
 stack effect 130–133
 wind 130
 air properties, measured values
 air permeance, test method 325–326
 test results
 air barriers 335–336
 building materials and building parts
 327–330
 insulation materials and insulating
 layers 330–335
 internal linings 336
 air resistance 138
 American Society for Testing and
 Materials (ASTM) 340
 American Society of Heating and
 Ventilation Engineers (ASHVE) 9
 anisotropic materials 140
 applied physics
 acoustics 8–9
 heat, air, moisture 5–8
 lighting 9
 average sol-air temperature 80

b

balance equations
 air 276
 closing the loop 278–279
 heat 276–278
 vapour 275–276

- barometric relation 132
 - black surface constant 68
 - Brunauer–Emmett–Teller/BET-equation 170
 - building materials
 - autoclaved cellular concrete masonry 321
 - concrete 344
 - aerated concrete 345
 - autoclaved aerated 318
 - block masonry 320–321
 - with expanded polystyrene pearls 319
 - lightweight 318, 344
 - polystyrene 345–346
 - fibre cement 322, 351
 - gypsum board 322
 - gypsum plaster 321, 348
 - lightweight and normal cement mortars 319
 - lime-sandstone 319, 347–348
 - masonry walls 351–352
 - mortar and brick 346–347
 - outside rendering 321
 - particle board 322, 350
 - perforated brick masonry 320
 - plywood 322
 - stone 342–343
 - stucco 348–349
 - timber 349
 - wood 322
 - woodwool-cement boards 349
 - building physics
 - constraints
 - architecture and materials 3
 - comfort 2–3
 - economy 3
 - health and well-being 3
 - sustainability 3–4
 - defined 1–2
 - history 5, 12–13
 - applied physics 5–9
 - building design and construction 11–12
 - building services 11
 - indoor air quality and thermal comfort 9–10
 - KULeuven and universities, in low countries 13–14
 - importance 4–5
 - building-related applications, heat transfer
 - heat balances 100–101
 - local inside surface film coefficients 91–92
 - non-steady-state
 - any boundary conditions, thermal bridges 105
 - periodic boundary conditions, flat assemblies 101
 - periodic boundary conditions, spaces 101–105
 - steady-state, flat assemblies
 - average thermal transmittance, parallel envelope parts 83–84
 - electrical analogy 84
 - interface temperatures 86–87
 - solar transmittance 88–90
 - thermal resistance of, non-ventilated cavities 84–86
 - thermal transmittance 80–83
 - thicker insulation layers, on thermal transmittance 87–88
 - surface film coefficients and reference temperatures
 - indoors 76–78
 - methodology 76
 - outdoors 78–80
 - two and three dimensions steady-state
 - building envelopes 99–100
 - floors, on grade 93–94
 - pipes 92–93
 - thermal bridges 94–98
 - windows 98–99
 - buoyancy 130
- C**
- capillary hygroscopic materials 125
 - capillary non-hygroscopic materials 125

- capillary water absorption coefficient 215
 - capillary water flux 233
 - Carrier, W. 11
 - central control volumes 95
 - CFD *see* computerized fluid dynamics (CFD)
 - chlorine corrosion 173
 - coloured surfaces 74
 - combined heat and airflow
 - heat balance 148
 - non-steady-state, flat assemblies 152–153
 - non-steady-state, two and three dimensions 153
 - steady-state, flat assemblies
 - equation 148–149
 - multi-layered 151–152
 - single-layered 149–151
 - steady-state, two and three dimensions 152
 - vented cavities 153–155
 - computerized fluid dynamics (CFD) 54, 266
 - conduction 17
 - laws
 - first law 20–21
 - second law 22
 - non-steady-state 38–39
 - boundary conditions, flat assemblies 48–51
 - periodic boundary conditions, flat assemblies 39–48
 - two and three dimensions, thermal bridges 52
 - steady-state 26
 - one dimension, flat assemblies 27–33
 - two and three dimensions, thermal bridges 35–38
 - two dimensions, cylinder symmetric 33–34
 - conservation of mass 266–267
 - control volume method (CVM) 35, 153, 274
 - convection
 - convective surface film coefficient, quantifying 55–58
 - forced 59
 - typology
 - driving forces 55
 - flow types 55
 - convective heat flux 76
 - convective surface film coefficient
 - quantifying
 - analytical 55
 - dimensional 56–58
 - numerical 55–56
 - values for
 - cavities 60–62
 - flat surfaces 58–60
 - pipes 62–63
 - Cranck–Nicholson scheme 278
 - Cremer, L. 9
 - CVM *see* control volume method (CVM)
- d**
- De Grave, A. 13
 - diffusion constant 180
 - diffusion resistance, of unvented cavities 198
 - dirac impulses 48
 - drying flux 235
 - dynamic thermal resistance 43
- e**
- electrical analogy 31
 - electrical resistors 31
 - electromagnetic waves 63
 - emissivity 72
 - enclosures 99
 - energy conservation 268
 - EN-ISO standards 340
 - enthalpy and vapour saturation pressure 271
 - envelope
 - assemblies 44, 78, 86, 87
 - building 99–100
 - leaky 151, 152
 - transparent 278

equivalent conduction 269
 equivalent diffusion 248
 equivalent hydraulic circuit 141
 expanded polystyrene (EPS) 324, 353
 extruded polystyrene (XPS) 324, 353

f

fibrous insulation materials 26
 Fick, A. 8
 Fick's empirical diffusion law 173
 fine porous, hygroscopic material
 assemblies 274
 floor heating system 118
 fluid's kinematic viscosity 57
 fluid's velocity 57
 flux equations
 heat 270
 mass, air 270
 mass, moisture 270–271
 forced convection 59
 force equilibrium 216
 Fourier, J. 5
 Fourier's law 148, 270
 friction factor 135, 136

g

gas constant 135
 Grasshof number 57, 58
 grey surfaces 72–74
 groove and tongue timber lathing
 353–354
 gypsum transformation 173

h

heat absorption coefficient 51
 heat, air and moisture combined
 material and assembly level
 assumptions 265
 conservation of energy 267–269
 conservation of mass 266–267
 equations of state 271
 flux equations 270–271
 simplified models 272–274
 solution 266

 start, boundary and contact
 conditions 271–272
 whole building level 274–275
 balance equations 275–279
 consequences 284–287
 sorption active surfaces and hygric
 inertia 279–280
 heat, air and moisture material property
 values 303
 air properties
 measured values 325–336
 standard values 325
 dry air and water 304
 moisture properties
 measured values 340–356
 standard values 336–340
 thermal properties
 defined 305
 measured values 317–325
 standard values 305–316
 surfaces, radiant properties 316
 heat balances 112
 heat conduction 267
 heat exchange, at surfaces 52–53
 convection 53–54
 convective surface film coefficient,
 quantifying 55–58
 typology 55
 radiation
 defined 63–64
 radiant surfaces 66–74
 reflection, absorption and
 transmission 64–66
 thermal radiation 63
 heat flux equation 29
 heating, ventilating, air conditioning
 (HVAC) 11, 17
 heat of evaporation 170
 heat transfer
 building-related applications
 heat balances 100–101
 local inside surface film coefficients
 91–92
 non-steady-state 101–105
 steady-state, flat assemblies 80–90

- surface film coefficients and
 - reference temperatures 76–80
 - two and three dimensions
 - steady-state 92–100
 - conduction
 - conduction laws 20–22
 - conservation of energy 19–20
 - non-steady-state 38–52
 - steady-state 26–38
 - thermal conductivity 22–26
 - defined 19
 - heat 17
 - heat exchange, at surfaces 52–53
 - convection 53–63
 - radiation 63–76
 - latent heat 18
 - sensible heat 17–18
 - temperature 18
 - heat transmission 5
 - HVAC *see* heating, ventilating, air conditioning (HVAC)
 - hygroscopic behaviour 126
 - hygroscopic equilibrium 235
 - hygroscopic materials 175, 187–189
- i**
- IAQ *see* indoor air quality (IAQ)
 - IEQ *see* indoor environmental quality (IEQ)
 - indoor air quality (IAQ) 10
 - indoor environmental quality (IEQ) 3
 - indoor/outdoor vapour pressure
 - difference 241
 - in- or outside, of thermal insulation
 - 305–309
 - glued masonry, joint width 310–312
 - gypsum, with and without lightweight aggregates 313
 - insulation materials 314–315
 - lightweight concrete, for slabs/screeds 313
 - masonry with, mortar joints 312
 - normal concrete 312
 - plaster 313
 - values 310
 - wood and wood-based materials 314
 - insulation materials 24
 - cellular glass 323, 352
 - cork 323, 352
 - EPS 324, 353
 - expanded perlite 353
 - glass fibre 323, 352
 - mineral fibre 323, 353
 - XPS 324, 353
 - integration constants 283
 - interstitial condensation 8, 183–185
 - boundary conditions
 - diffusion and air movement 202–203
 - diffusion only 201–202
 - calculation
 - diffusion and moist air movement 204
 - diffusion only 203
 - example 204–209
 - inter-zone airflows 276
 - isobaric 162
 - isothermal 162
 - air diffusivity 137
 - drying 233
 - water flow in pore
 - after water contact 218
 - balancing forces 212–214
 - horizontal pore, substitute for rain absorption 214–217
 - non-isothermal water transfer, after water contact 218–219
 - vertical pore, substitute for rising damp 217–218
 - isotropic open porous materials 139
- k**
- Kirchhoff's law 74
- l**
- Lambert's law 66, 74
 - laminar forced convection 54
 - latent heat of transformation 128
 - life cycle inventory and analysis tools (LCIA) 3

linear thermal transmittance 98
 local loss factors 135, 136
 long wave emissivity 316
 luminosity constant 66

m

mass conservation 176
 mass displacement 127
 mass flows 55
 mass transfer
 air
 airflow in, open-porous materials
 135–140
 air permeability and air permeances
 133–135
 air pressure differentials
 130–133
 dry air 129
 moist air 129
 and moisture, related to durability
 127
 and moisture transfer 123–125
 conservation of mass 128
 defined 122–123
 links with, energy transfer 127–128
 moisture 209
 flow, through materials and
 assemblies 221–225
 simple moisture flow model
 225–239
 sources 125–127
 vapour flow in, pore containing
 water isles 219–221
 water flow, in pore 209–219
 saturation degree scale 123
 water vapour
 in air 156–163
 interstitial condensation 201–209
 in open-porous materials 168–172
 relative humidity on, inside surfaces
 165–168
 in spaces 163–165
 surface film coefficients, for diffusion
 195–201
 vapour flow by diffusion, and moist
 air 189–195
 vapour flow by diffusion, in
 open-porous materials 174–189
 vapour transfer, in air 172–174
 measured values, moisture properties
 test results 355–356
 building and finishing materials
 342–352
 finishes 353–355
 insulation materials 352–353
 vapour retarders 356
 mercury thermometer 18
 moist air-related convective vapour flux
 174
 moisture 121, 209
 content 266
 flow, through materials and assemblies
 mass conservation 223–224
 moisture permeability 223
 starting, boundary and contact
 conditions 224
 transport equations 221–222
 ratio, at indoor and outdoor conditions
 309
 simple moisture flow model 225–226
 capillary suction 227–231
 drying 232–237
 interstitial condensation, limit state
 237–239
 wind driven rain 231–232
 transfer equation 221
 vapour flow, in pore containing water
 isles 219–221
 water flow, in pore
 capillarity 209–211
 isothermal 212–218
 moisture flow, through materials and
 assemblies 221–225
 non-isothermal water transfer, after
 water contact 218–219
 Poiseuille's law 211–212
 simple moisture flow model
 225–239

- moisture properties
 measured values
 diffusion resistance factor, test method 340–342
 insulation materials 352–353
 test results 342–352
 standard values
 building and finishing materials 336–340
 insulation materials 340
 multi-layer adsorption 170
 multi-layered assemblies 28–31
- n**
 natural convection 58
 Navier–Stokes’s equations 266
 net energy demand for heating 297, 300
 Newton’s law 53, 212
 non-capillary materials
 hygroscopic 125
 non-hygroscopic 125
 non-dimensional temperature factor 97
 non-hygroscopic materials 189
 non-capillary materials assemblies 272–273
 non-isothermal conditions 138
 non-steady-state, conduction 38–39
 boundary conditions, flat assemblies
 convolution 48–50
 temperature change, semi-infinitely thick layer 50–51
 periodic boundary conditions, flat assemblies
 methodology 39–41
 multi-layered 47–48
 single-layered 41–46
 Nusselt number 24, 57
- o**
 one dimension, flat assemblies 27
 electrical analogy 31
 multi-layered assemblies 28–31
 single-layered walls 27–28
 special cases 31–33
 open-porous materials 121
- Organization Petroleum Exporting Countries (OPEC) 6
 oriented strand board (OSB) 127
- p**
 Pécle, J.-C. 5
 Pécllet number 149
 Planck’s law 67, 68
 Poensgen method 317
 Poiseuille’s law 134, 270
 polyurethane foam, polyisocyanurate foam (PUR/PIR) 324, 353
 Prandtl number 57, 196
 predicted mean vote (PMV) 10
 predicted percentage of dissatisfied (PPD) 10
 pressure equilibrium 259
 pressure factor 130
 data 131–132
- r**
 radiant flux 64
 radiant heat flux 77
 radiant heat transfer, variables 64
 radiant surfaces
 black surfaces 66–72
 coloured surfaces 74
 grey surfaces 72–74
 simple formulae 74–76
 types 66
 radiant temperature 75
 related heat flux 33
 related hygric capacitances 280
 relative humidity (RH) 2
 in moisture content 271
 reshuffled conservation equation 269
 Reynolds number 57, 58, 136, 211
 RH *see* relative humidity (RH)
 Rietschel, H. 5, 11
 rising damp 217
- s**
 second law of thermodynamics 66
 second-order differential equation 213
 semi-infinite vertical surface 54

- sensible heat 17–18
 - Sherwood number 195, 196
 - shortwave absorptivity 316
 - sick building syndrome (SBS) 10
 - single-layered walls 27–28
 - six grey surfaces combination 115
 - sol-air temperature 107
 - solar heat flux 88
 - solar short-wave absorptivity 74
 - sorption active surfaces and hygric inertia 279–280
 - harmonic analysis 284
 - sorption-active thickness 280–282
 - zone with one sorption-active surface 282–283
 - zone with several sorption-active surfaces 283
 - sorption/desorption isotherm 168–169
 - consequences 172
 - physics 170–172
 - salts, impact of 172
 - specific gas constant 20
 - specific heat capacity 20
 - stack effect 130–133
 - stack pressures 293
 - steady-state equivalent diffusion 250
 - steady state heat flux ambient 80
 - structural mechanics 4
 - suction, in moisture content 271
 - surface condensation 165, 166, 201, 224, 240
 - and vapour balance, in spaces 200–201
 - surface film coefficients and reference temperatures
 - indoors 76–78
 - methodology 76
 - outdoors 78–80
 - surface temperature 50
- t**
- tangent method 183–184
 - Technical University Eindhoven (TU/e) 14
 - temperature damping 45
 - temperature equilibrium 66
 - thermal bridges 94–98
 - thermal comfort 2, 9
 - thermal conductivity 6, 22, 305
 - of fluid 57
 - heat transfer modes, property fixing 22–26
 - thermal diffusivity 53
 - thermal inertia 101
 - thermal properties, measured values
 - test results
 - building materials 318–322
 - insulation materials 323–325
 - thermal conductivity, test methods 317
 - thermal resistance 28
 - thermal stack 133, 291, 296
 - thermal transmittance 93
 - thermal water permeability, of pore 219
 - thermodynamic equilibrium 266
 - Thompson's law 170, 171
 - total diffusion resistance 181
 - total thermal resistance 29
 - transparent envelope 278
 - transport equations 221–222
 - turbulent dissipation 55
 - turbulent kinetic energy 55
- u**
- U-value 111
- v**
- vapour diffusion, in cold storage walls 8
 - vapour flow by diffusion, in open-porous materials
 - <equivalent> diffusion concept, applicability of 177
 - flow equation 174–175
 - mass conservation 176
 - non-steady state
 - equation 187
 - hygroscopic materials 187–189
 - non-hygroscopic materials 189
 - steady state, flat assemblies
 - equations 177

- isothermal, multi-layered 178–179
 - isothermal, single-layered 177–178
 - non-isothermal, multi-layer
 - 181–186
 - non-isothermal, single-layered
 - 180–181
 - vapour resistance factor 175–176
 - vapour permeability 270
 - vapour pressure
 - damping 189
 - outdoors 240
 - vapour resistance factor (μ) 175–176, 235
 - vapour saturation pressure 158–160, 191, 276, 295
 - ventilating cavities, veneer drying
 - 198–200
 - Verein Deutsche Ingenieure (VDI) 11
 - Vermeir, G. 13
 - visual comfort 3
 - volumetric expansion coefficient 58
 - Vrije Universiteit Brussel (Free University Brussels) (VUB) 14
- W**
- wall's harmonic properties 113
 - wall surface-related heat balances 116
 - water flow, in pore
 - capillarity 209–211
 - isothermal 212–218
 - non-isothermal water transfer, after water contact 218–219
 - Poiseuille's law 211–212
 - vapour flow, in pore containing water
 - isles
 - isothermal 219–220
 - non-isothermal 220–221
 - waterproofing 222
 - water vapour
 - in air 156
 - changes of state, in humid air
 - 161–162
 - enthalpy of, humid air 162
 - measuring air humidity 162–163
 - quantities 156–157
 - relative humidity 157–161
 - vapour saturation pressure 157–160
 - in, open-porous materials
 - vs. air 168
 - sorption/desorption isotherm
 - 168–172
 - interstitial condensation, evaluation
 - boundary conditions 201–203
 - calculation 203–204
 - examples 204–209
 - relative humidity, on inside surfaces
 - 165–168
 - surface film coefficients, for diffusion
 - applications 198–201
 - derivation 195–197
 - vapour balance, in spaces 163–165
 - vapour flow by diffusion, and moist air
 - 189–190
 - isothermal, single- and multi-layered assemblies 190–191
 - non-isothermal, single- and multi-layered assemblies
 - 191–195
 - vapour flow by diffusion, in open-porous materials
 - applicability of, equivalent diffusion concept 177
 - flow equation 174–175
 - mass conservation 176
 - steady state, flat assemblies
 - 177–186
 - vapour resistance factor 175–176
 - vapour transfer, in air 172–174
 - wet interface/wet zone 236
 - wind 130

