

Index

a

accelerated drying 20
 acidification 215
 acoustical comfort
 ears, anatomy of 93–94
 physiological facts 94
 unacceptable noise, effects of 94
 pathological view 96–97
 physiological view 95–96
 psychological view 94–95
 active house alliance 70
 air density 22
 air temperature 6–9
 airtightness
 airflow patterns 229–231
 performance requirements
 air in- and exfiltration 231
 air looping 232–233
 indoor air washing and wind
 washing 232–233
 alkali-granulate reaction 199
 ambient conditions 3, 5
 indoors 35
 air temperature 35–37
 indoor to outdoor air pressure
 differentials 47–48
 RH and vapour pressure 37–47
 microclimate around buildings 28
 outdoors
 air temperature 6–9
 clear sky long wave radiation
 15–18
 solar radiation 9–15

rain

impact 23
 precipitation 23–25
 wind-driven rain 25–27
 standardized outside climate data
 condensation and drying, equivalent
 temperature 32–34
 design temperature 28–30
 hot summer and cold winter day 30
 moisture reference year 30–32
 monthly mean vapour pressure
 outdoors 35

wind

impact 20–21
 wind pressure 22–23
 wind speed 21–22

ambient or environmental loads 3
 annual end energy use, for heating 176
 methods
 predesigned single-family houses
 145
 using degree-days 145–147
 annual net cooling demand 28, 176
 annual net heating demand 28
Aspergillus spp. 113
 A. fumigatus 114
 atmospheric turbidity 12, 14
 average long-wave emissivity 80
 average solar constant 9

b

basilar membrane 94
 beam and diffuse solar radiation 58

- Bernoulli's law 22
- bio-germs
 - bacteria 111–112
 - dust mites 114–115
 - insects 115
 - moulds 112–114
 - pets 115
 - rodents 115
 - viruses 111
- black surface emittance equations
 - 17, 18
- building energy simulation (BES) tools
 - 28
- building envelope, consequences
 - one-step control 252–255
 - performance-based control 255–256
 - two-step control 255
- Building Research Establishment
 - Environmental Assessment
 - Methodology (BREEAM) 216
- c**
- capillary insulation layer 248
- capillary water absorption coefficient
 - 192
- carbon dioxide (CO₂) 116
- carbon monoxide (CO) 111
- central thermal transmittance 236
- CFD *see* computational fluid dynamics (CFD)
- Cladosporium* 113
- clear sky long wave radiation 15–18
- clo-value 79
- cochlear septum 93
- combustion linked contaminants
 - 110–111
- computational fluid dynamics (CFD)
 - 277
- Construction Products Directive (CPD)
 - 66
- contaminant control 121
 - minimizing emissions 121
 - ventilation flow
 - to avoid dust mite overpopulation 127
 - to avoid mould 125–127
 - for healthy indoor air 121–125
 - for smoking indoors 128
 - standards 128–129
 - to upgrade IAQ 127–128
- contaminants, emitted by materials
 - HCHO 108
 - pentachlorophenol 109
 - phthalates 108–109
 - (S)VOC 107–108
- control volumes (CVM) 147
 - assumptions 156
 - calculations 156–157
- cosmic radiation 103
- cracking 188
- crystallization pressures 196
- CVM *see* control volumes (CVM)
- d**
- damage patterns
 - biological attack 188–190
 - chemical attack 198–199
 - corrosion 199–200
 - frost 190–194
 - salt attack 194–198
 - strength and stiffness, decrease in 185
 - stress, strain, deformation and cracking
 - induced 185–188
 - moisture coupled 186–187
 - temperature and moisture combined 187–188
 - thermally induced 185–186
 - thermal insulation performance, decrease in 184
- daylight factor 101
- dewpoint outdoors 15
- domestic hot water (DHW) 132
- drying function 31
- durability
 - damage patterns
 - biological attack 188–190
 - chemical attack 198–199
 - corrosion 199–200
 - frost 190–194
 - salt attack 194–198

- strength and stiffness, decrease in 185
- stress, strain, deformation and cracking induced 185–188
- thermal insulation performance, decrease in 184
- durable construction 183
- loads 183–184
- dynamic thermal resistance 149

e

- earth's inclination 5
- economics
 - building optimum
 - application 204–210
 - methodology 203–204
 - investment in, thermal insulation 201
 - optimal insulation thickness 202–203
 - total and net present value 201–202
- electric analogy 172
- electro-kinesis 261
- electromagnetic loads 184
- electromagnetic radiation 103
- end energy use, in buildings
 - DHW
 - non-residential buildings 136
 - residential buildings 135–136
 - HVAC 132
 - LA
 - non-residential buildings 134–135
 - residential buildings 133–134
 - space heating, cooling and air conditioning 136
- energy autarkic 178
- energy efficiency 131
 - end energy use, in buildings 132–136
 - DHW 132, 135–136
 - HVAC 132
 - LA 132, 133–135
 - space heating, cooling and air conditioning 136
 - space heating, steady-state
 - annual end energy use, for heating 145–146

- net heating demand 157–175
- non-steady-state evaluation 146–157
- steady state heat balance, at zone level 138–143
- terminology 136–137
- statistics 132
- equivalent temperature 149
- European Construction Products Regulation (CPR) 66
- European Organisation for Technical Approvals (EOTA) 64
- excess factors (EF) 290
- expectancy factor 85

f

- favoured insulation materials 103
- feet comfort 89
- fire safety 71–73
- Flemish region 163
- formaldehyde (HCHO) 108
- frost-resisting 191

g

- genetic algorithms 204
- germination 188
- glass perimeter 236
- glass surface 236
- global warming 4, 212–215
- green hydrogen 73

h

- harmonic analysis
 - assumptions 148
 - solar and internal gains, zone nodes 148–153
 - heating and cooling 151
 - internal gains 151
 - opaque parts, conduction through 149–150
 - solar gains and longwave losses 151
 - transparent parts, conduction through 150
 - ventilation and infiltration 150–151
 - zone balance 151–154

- heat, air, moisture (HAM) metrics,
 - building assembly level
 - air-related, measured values 323–330
 - airtightness
 - airflow patterns 229–231
 - performance requirements 231–233
 - combined HAM
 - limitation 279–283
 - modelling 277–278
 - performance requirements 278–279
 - contact coefficients 288
 - full HAM tools, usability of
 - detached house 286–287
 - office building 284–286
 - university building 283–284
 - hygrothermal stress and strain 288–289
 - moisture tolerance 245
 - accidental leakages 263
 - construction moisture 245–248
 - hygroscopicity 263–265
 - interstitial condensation 267–277
 - pressure heads 261–263
 - rain 248–256
 - rising damp 256–261
 - surface condensation 265–267
 - solar transmittance, transparent parts
 - consequences for, envelope 290
 - defined 289
 - performance requirements 290
 - thermal bridging
 - consequences, for envelope 288
 - defined 287
 - performance requirements 288
 - thermal transmittance
 - examples, requirements 238–242
 - grade floors, as three-dimensional case 233–235
 - opaque envelope assembly, above grade 233
 - requirements, basis for 238
 - transparent parts 235–237
 - whole envelopes 237
 - transient thermal response
 - building fabric, consequences 244–245
 - performance requirements 243–244
 - properties of, importance 242–243
 - heat, air, moisture (HAM), timber-frame
 - performances
 - assembly 295–296
 - moisture tolerance
 - advanced modelling 308–309
 - construction moisture 300
 - hygroscopic moisture and surface condensation 302
 - interstitial condensation 302–308
 - rain 300–301
 - rising damp 301
 - performance evaluation 296
 - airtightness 296–297
 - thermal transmittance 297–298
 - transient response 299–300
 - thermal bridging 310
 - heat balance 244
 - heating, ventilating, air conditioning and cooling (HVAC) 132
 - human ear 93
 - human eyes 99
 - human related contaminants 115
 - bio-odours 116
 - CO₂ 116
 - tobacco smoke 116–118
 - water vapour 116
 - hygric loads 184
 - hygroscopicity
 - building fabric, consequences 265
 - defined 263–264
 - modelling 264
 - performance requirements 264
- i*
- impeded communication 94
 - indoor air quality (IAQ) 104
 - indoor air enthalpy 119–120
 - odour 118–119
 - SBS 120–121
 - indoor climate classes (ICC) 45

- indoor environmental quality (IEQ)
 - 103–104
 - air cleaning and personal protective measures 130
 - bio-germs 111–115
 - combustion linked contaminants 110–111
 - contaminant control 121–130
 - contaminants emitted, by materials 107–109
 - definitions 104–105
 - health 104
 - human related contaminants 115–118
 - perceived indoor air quality 118–120
 - pollution outdoors vs. indoors 105
 - process-related contaminants 105–107
 - soil linked radon 109–110
- indoors 35
 - air temperature 35–36
 - measured data 36–37
 - to outdoor air pressure differentials 47–48
 - RH and vapour pressure 37–38
 - climate classes 45–47
 - measured data 38–45
 - vapour release indoors 38
- intermittent heating 174
- International Council for Research and Innovation in Buildings (CIB) 66
- International Energy Agency (IEA) 66
- interstitial condensation 32, 277
 - avoiding 276
 - defined 267
 - modelling 267–275
 - diffusion 268–270
 - example 271–275
 - flowing through combined 270–271
 - history 267–268
 - performance requirements 275–276
- L**
- Leadership in Energy and Environmental Design (LEED) 217
- Leed certification 218
- Legionella pneumophila 111
- Legionnaire's disease 111
- life cycle inventory and analysis (LCIA)
 - acidification 215
 - defined 211–212
 - global warming 212–215
 - ozone depletion 215
 - recycling 216
 - total energy use 215–216
- lighting and appliances (LA) 132
 - non-residential buildings 134–135
 - residential buildings 133–134
- linear interpolation 34
- luminosity, at solar disk 14
- m**
- mean aerosol emission rate 125
- mechanical material processing 105
- melamine (Mel) 185
- metabolic equilibrium 76
- metabolic heat flux 76
- microclimatic factors 5
- micro-porous materials 192
- minimum/maximum mercury thermometer 5
- modulus of elasticity 186
- moisture diffusivity 258
- moisture tolerance 245
 - accidental leakages 263
 - construction moisture 245–248
 - building fabric, consequences 246–248
 - defined 245–246
 - performance requirements 246
- hygroscopicity
 - building fabric, consequences 265
 - defined 263–264
 - modelling 264
 - performance requirements 264
- interstitial condensation 277
 - avoiding 276
 - defined 267
 - modelling 267–275
 - performance requirements 275–276

- moisture tolerance (*contd.*)
 - pressure heads
 - building fabric protection 262–263
 - defined 261
 - modelling 262
 - performance requirements 261–262
 - rain 248–250
 - building envelope, consequences 252–256
 - modelling 250–252
 - performance requirements 250
 - problematic wetting 248
 - rising damp
 - avoiding 259–261
 - defined 256
 - modelling 257–259
 - performance requirements 256–257
 - surface condensation
 - defined 265
 - modelling 265–267
 - performance requirements 265
 - mould-specific isopleths 112
- n**
 - nasal conchae 102
 - nearly net zero (nZEB) 177
 - net heating demand 157
 - building design and construction
 - airtightness 174–175
 - compactness 167–168
 - floor organisation 168
 - glazing 168–169
 - protected volume 166–167
 - residential buildings 175, 176
 - thermal inertia 171–174
 - thermal insulation 169–171
 - building use 158–159
 - internal gains 166
 - non-residential buildings 179
 - school renovation 179–182
 - outdoor climate 157–158
 - residential buildings, energy efficiency 177–179
 - statistical facts and consequences 159–165
 - ventilation 165–166
 - nitrous dioxide (NO₂) 111
 - non-steady-state evaluation, space conditioning and overheating 146
 - CVM
 - assumptions 156
 - calculations 156–157
 - harmonic analysis
 - assumptions 148
 - solar and internal gains, zone nodes 148–153
 - lines of influence
 - assumptions 154
 - surface balances 155–156
 - zone node balances 154
 - methodologies
 - CVM 147
 - evaluation 147
 - harmonic analysis 146–147
 - lines of influence 147
 - normalized wetting 31
 - Nusselt number 232
 - o**
 - olfactory comfort
 - anatomy of, nose 102
 - comfort values 102–103
 - physiological facts 102
 - olfactory system 102
 - opaque parts 155–156
 - optic factor 12
 - outdoors 5
 - air temperature 6–9
 - clear sky long wave radiation 15–18
 - RH and (partial water) vapour pressure 18–20
 - solar radiation 9–11
 - beam radiation 11–13
 - diffuse radiation 13–14
 - reflected radiation 15
 - total radiation 15
 - ozone (O₃) concentration 107
 - ozone depletion 215

p

- (partial water) vapour pressure 18–20
- Penicillium* colonize substrates 113
- performance arrays
 - buildings and building assemblies 66–70
 - built environment 66, 67
 - demands
 - building physics-related requirements 71
 - durability 73
 - fire safety 71–73
 - functionality 70
 - maintenance 73
 - structural adequacy 70–71
 - sustainability 73
- performance demands
 - acoustical comfort
 - comfort values 97–99
 - ears, anatomy of 93–94
 - physiological facts 94
 - unacceptable noise, effects of 94–97
 - durability
 - damage patterns 184–200
 - durable construction 183
 - loads 183–184
 - economics
 - building optimum 203–210
 - investment in, thermal insulation 201
 - optimal insulation thickness 202–203
 - total and net present value 201–202
 - energy efficiency 131
 - end energy use, in buildings 132–136
 - statistics 132
 - high-performance buildings 216–217
 - rationale, for governmental office building 217–220
 - IEQ 103–104
 - air cleaning and personal protective measures 130
 - bio-germs 111–115
 - combustion linked contaminants 110–111
 - contaminant control 121–130
 - contaminants emitted, by materials 107–109
 - definitions 104–105
 - health 104
 - human related contaminants 115–118
 - perceived indoor air quality 118–120
 - pollution outdoors vs. indoors 105
 - process-related contaminants 105–107
 - soil linked radon 109–110
 - olfactory comfort
 - anatomy of, nose 102
 - comfort values 102–103
 - physiological facts 102
 - sustainability 210
 - thermal comfort
 - autonomous control system 77–78
 - physiological basis 76–77
 - steady state thermal comfort 78–81
 - visual comfort
 - anatomy of, eyes 99
 - comfort values 100–101
 - physiological facts 99–100
- performance metrics
 - functional demands 63
 - history 64–66
 - performance arrays
 - buildings and building assemblies 66–70
 - built environment 66, 67
 - demands 70–73
 - performance requirements 64
- permanent clear sky conditions
 - beam and diffuse solar radiation 58
 - beam, diffuse and reflected solar radiation 58–59
- phantom theories 103
- phenol-formaldehyde (PF) particle 185
- phosphoric gypsum 110
- pollution indoors 105

- polycyclic aromatic hydrocarbons (PAH)
 - 106
 - potassium carbonate (KCO₃) 197
 - precipitation intensity 26
 - predicted mean vote (PMV) 83
 - predicted percentage of dissatisfied (PPD)
 - 83
 - preferred speech interference level (PSIL)
 - 94, 95
 - pressure coefficient 22
 - process-related contaminants
 - fibres 106
 - ozone 107
 - vapours, smoke, mist and gaseous
 - clouds 105–106
 - psychic disturbances 95
- r**
- radiant asymmetry 88–89
 - radiant heat 103
 - radon 109
 - rain-buffering 9
 - random variables 201
 - receptor neurons 102
 - recycling 216
 - reference years 28
 - relative humidity (RH) 5, 18–20
 - representative volumes (REV) 279
 - RH *see* relative humidity (RH)
 - rime formation 16
- s**
- sea-based wind turbines 21
 - (semi) volatile organic compounds
 - ((S)VOC) 107–108
 - sick building syndrome (SBS) 120–121
 - sodium sulphate (Na₂SO₄) 197
 - soil linked radon 109–110
 - solar angles 9
 - solar-driven vapour flow 31
 - solar height 14
 - solar radiation 5
 - beam radiation 11–13
 - diffuse radiation 13–14
 - reflected radiation 15
 - total radiation 15
 - Uccle, Belgium 48–59
 - solar spectrum 9
 - solar transmittance 140
 - sound waves 94
 - specific heat capacity of air 80, 140
 - specific transmission losses 171
 - speech audibility 94, 95
 - Stachybotrys* 113
 - static electrical fields 103
 - steady state heat balance, at zone level
 - 138–139
 - annual end energy use, for heating
 - 144–145
 - building net heating balance 143–144
 - internal gains 142
 - overheating, correcting for 142–143
 - protected volume, as one zone 145
 - solar gains 140–141
 - transmission 139
 - ventilation and infiltration 139–140
 - steady ventilation flow 122
 - structural thermal bridges 288
 - sulphates diffusing 199
 - sun-radiated surfaces 34
 - surface condensation 190
 - defined 265
 - modelling 265–267
 - performance requirements 265
 - surface film coefficients 258
 - surface resistance 245
 - synthetic insulation foams 186
- t**
- temperature damping 149, 244
 - temperature indoors 33
 - temperature transients indoors 87
 - terrestrial radiation 103
 - thermal comfort
 - autonomous control system 77–78
 - comfort parameters and variables
 - comfort appreciation 82–85
 - comfort temperature 81–82
 - problem 81

- thermally equivalent environments
 - 81–82
 - consequences for, enclosure
 - performance 92–93
 - local discomfort
 - draught 87–88
 - feet comfort 89
 - radiant asymmetry 88–89
 - vertical differences, in air
 - temperature 88
 - non-uniform, non-steady-state
 - conditions 86
 - drifts and ramps 87
 - refined body model 86–87
 - physiological basis 76–77
 - exotherm 76
 - homoiotherm 76–77
 - standard-based comfort requirements
 - 89–91
 - steady state thermal comfort 78–81
 - adaptive model 85–86
 - clothing 78–79
 - comfort equations 81
 - comfort model 78
 - heat exchange b/w body and ambient
 - 79–80
 - thermal expansion coefficient 185
 - thermal insulation 103
 - heat related standard values, inside vs.
 - outside of 311–322
 - thermal reference years (TRY) 28–30
 - thermal sensation scale 85
 - thermal stack 47
 - thermal transmittances 20, 92, 139,
 - 232
 - requirements 239
 - thermometer hut 6
 - TIM *see* transparent insulation (TIM)
 - time angle 11
 - transparent insulation (TIM) 140
 - transparent parts 156
 - trias energetica 131
 - TRY *see* thermal reference years (TRY)
- U**
- United States, the Green Building Council
 - (USGBC) 217
 - urea-formaldehyde (UF) 185
- V**
- vapour resistance factor, standard values
 - 331–335
 - ventilation
 - effectiveness 122
 - flow
 - to avoid dust mite overpopulation
 - 127
 - to avoid mould 125–127
 - for healthy indoor air 121–125
 - for smoking indoors 128
 - to upgrade IAQ 127–128
 - standards 128–129
 - visual comfort
 - anatomy of, eyes 99
 - comfort values 100–101
 - physiological facts 99–100
 - volatile organic compounds (VOC) 118
- W**
- warmer outdoors 43
 - water-like fluid 99
 - water-tightening 287
 - wind-driven 23
 - rain intensity 26
 - wind pressure coefficients 24
 - wind velocity 22, 26
 - World Federation of Technical
 - Assessment Organisations
 - (WFTAO) 64
 - World Health Organization (WHO) 104
 - World Meteorological Organization
 - (WMO) 6
- Z**
- zero carbon 178–179
 - zone's heat storage capacity 142
 - zone's time constant 142

