

## Index

Note: *Italicized* and **bold** page numbers refer to figures and tables, respectively.

### a

- accidental leakage 500
- aerated concrete
  - blocks *12*, 153, *153*, *154*, 156, *156*, 211, 216, 404
  - concrete masonry 155, *155*
  - concrete wall 13, 157, **157**, 158, 158, 159, *159*, 160, 161, **161**, 162, 162
- air
  - attic floors insulated 335
  - roof pitches insulated 335–337
- air barriers 265, 284, 393–394, 490
  - and air retarders 39–40
- air leakage 67, 68, 149, 234, 240, 342, 349, 382, 384, 460, *461*, 478, 489, 490, 533
- air permeance 39, 68, 168, **190**
  - of cellular sheet-metal outer wall systems 258, **258**
  - of covers, underlays, insulations and inside linings 335, **336**
  - of insulated attic pitches as measured on site 337, **340**
  - of insulated roof pitches, no underlay, laboratory measurements 337, **338–339**
  - of veneer walls and inside leaf's 214, **215–216**
- airtightness
  - carpentry 523
  - cavity walls 214
  - concrete panels 252
  - double-skin façades 472
  - floors 115–116
  - glazing 428
  - grade parts and spaces 67–69
  - heavyweight masonry 149
  - inside insulation 168
  - interior finishes
    - of ceilings 520
    - on floors 516
    - on walls 513
  - lightweight masonry 154
  - low-slope roofs 283–285
  - outer walls 140–141
    - with transparent insulation 265–267
  - outside insulation 190
  - partition walls 401
  - party walls 398
  - roofs 146
  - shafts
    - for elevators 412
    - for pipes and ducts 414
  - sheet-metal-covered roofs 383–385
  - sheet-metal options 258

- airtightness (*contd.*)
    - timber frame construction 488–491
    - windows and outer doors 452
  - aluminium 263, 307, 380, 380, 386–387, 447, 449, 450, 455, 456, 463, 464, 466, 502
  - aluminium frames
    - anodized 461
    - with thermal breaks 459, **463**
  - apartment building 58, 86, 245
    - cavity walls of 244, 244
    - two thermal bridges 246
  - APP polymer *see* atactic polypropylene (APP) polymer
  - architectural heritage buildings 186, 186
  - atactic polypropylene (APP) polymer 36, **36**
  - attic floors insulated 335, 340–342
- b**
- balconies 403, 407
    - as cantilevered slab 405
    - design and construction
      - fences and handrails 410
      - flooring 410
      - rain proofing and drainage 409–410
      - thermal breaks minimizing thermal bridging 409
    - durability 408
    - fences 410
    - fire safety 408
    - function 404
    - methodology 404–405
    - moisture tolerance 408
    - protruding 407
    - structural integrity 405–406
    - thermal bridging 406–408, 406
    - user safety 408–409
  - ballast
    - heavy 276, 278, 286
    - vented tiles as 318
  - basement walls 73, 76, 77, **90**
    - loads on 66, 67
    - thermal admittance and time shift of **83**
  - Berliner wall 52
    - buttressing using 52
  - bitumen 32–33, 278–280, 369, 388
    - build-up bitumen membranes 279
    - and polymer bitumen membranes 36
      - combinations with the substrate 276–278
      - execution 275–276
      - number of layers 275
    - SBS bitumen membrane 99
  - bituminous membranes 33–36, **34–35**, 402
  - brass 377–378
  - brick
    - concrete and brick outer wall 174
    - lightweight brick masonry 11
    - one-brick masonry wall 150, 168, 171, 172, 177, 177, 179
      - and stainless-steel chimney 418
    - brick masonry, lightweight 11, 11
      - application 12
      - properties 11
    - brick slips 206
    - brick veneers
      - calculated temperatures **238**
      - neither painted nor glazed 233–234
      - painted or glazed 234–236
  - building physics-related 57, 135, 527
  - building-ups 274, 307, 308, 309, 318, 409
  - build-up bitumen membranes 279, 279
  - build-up polymer membranes 278, 280
  - Burj Khalifa building 107, 107
- c**
- capillary water absorption coefficient
    - 158, 159, 193, 194, 195, 255
  - capillary water in the ground 85
  - carpentry 2, 367, 522
    - air-tightness 523
    - building physics: acoustics 524
    - design and execution 524
    - fire safety 524, 525
    - structural integrity 523
    - thermal transmittance 524
  - cavity run-off 228, 229

- cavity trays 121, 126, 240, 242, 242
- cavity walls 211
  - airtightness 214
  - of apartment building 244, 244
  - building physics: acoustics 237
  - deficiencies causing discontentment 530–531
  - design and execution 240
    - airtightness 240–242
    - correctly mounted cavity trays 242, 242
    - excluding air looping and wind washing 242
  - discontentment with the consequences 531–534
  - durability 238–239
  - filled versus non-filled 529
  - fire safety 239
  - history 211–212
  - insulating 212
  - maintenance 239
  - moisture tolerance
    - construction moisture 227–228
    - interstitial condensation 233–236
    - mould and surface condensation 233
    - wind-driven rain 228–233
  - post-filling existing cavity walls 243–246
  - probabilities 531, 532, 534
    - mould 534–536
    - rain penetration 536
  - risk evaluation 539
  - structural integrity 212–213
  - tested 224
  - thermal bridging 236–237
  - thermal transmittance 214–227
  - transient response 227
  - upgrades 539–540
- ceilings, interior finishes of
  - air-tightness 520
  - alternatives 519
  - building physics: acoustics 521
  - design and execution 522
  - fire safety 521
  - moisture tolerance 521
  - structural integrity 520
  - thermal transmittance 520
  - transient response 520
- cellular glass 19, 19, 57, 191
  - application 20
  - properties 20
- cellular sheet-metal outer wall systems,
  - air permeance of 258, **258**
- cellulose 15, 15
  - application 17
  - properties 16
- ceramic tiles 321–322, **322**, 347, 355
  - clipping **322**
  - insulated pitch, measured moisture content in 348
  - unglazed 367
- chimneys 414
  - brick and a stainless-steel chimney 419
  - for central heating boiler **419**
  - design and construction 417
  - dimensioning 414–417
  - heat balance 415
  - for stoves **417**
- circles method 74
  - crawlspaces 78–79, 78
  - floor on grade 74–76
  - heated basements 76–77, 77
  - unheated basements 79–80, 81
- clearing the building site 51
- clear wall thermal transmittance 117, **117**, 149, 154, 157, 158, 159, 168, 191, **191**, 214, **218**, 227, 230, 473
- CLT *see* cross-laminated elements (CLT)
- compact low-slope roofs 280, 281
  - acoustics 302
  - air-tightness 283–285
  - fire safety 302–304
  - hygrothermal loading 291–294
  - maintenance 304
  - moisture tolerance 295–301
  - roof deck as classification variable 280–283
  - structural integrity 283

- compact low-slope roofs (*contd.*)
    - thermal bridging 302
    - thermal transmittance 285–289
    - transient response 289–291
  - compartmentalization of the cavity 213, 213
  - concrete
    - and brick outer wall 174
    - and glazed lift shaft 412
    - lightweight 12, 12
      - application 13
      - properties 12–13
    - and steel skeleton 105, 105
    - waterproof concrete 99
  - concrete blocks, aerated 12, 153, 153, 154, 156, 156, 211, 216, 404
  - concrete decks and prefabricated structural floor units 133–135 spans 132–134
  - concrete masonry, aerated 155, 155
  - concrete panels
    - airtightness 252
    - building physics: acoustics 256
    - common assemblies 251
    - design and execution 257
    - durability 256
    - fire safety 257
    - maintenance 257
    - moisture tolerance
      - interstitial condensation 255
      - mould and surface condensation 255
      - wind-driven rain 255
    - structural integrity 251–252
    - thermal bridging 256
    - thermal transmittance 252–254
    - transient response 255
  - concrete tiles 324
  - concrete wall 159, 160
    - aerated 13, 157, 157, 158, 158, 159, 159, 160, 161, 161, 162, 162
    - air permeance of 168
    - with one glass TIM panels 270, 271
  - cone-sounding test 52
  - construction moisture
    - cavity walls 227–228
    - floors 119–121
    - heavyweight masonry 151
    - lightweight masonry 157–158
    - low-slope roofs 295–298, 296
    - outer walls with transparent insulation 142, 269–270
    - pitched roofs 349
    - timber frame construction 495–496
  - control volume method (CVM) 455
  - copper 377–378, 379
  - cork 14, 14
    - application 15
    - insulation 14
    - properties 14–15
  - corner room 156, 156
  - corrugated roof sheets 326, 327
  - crack formation 144, 163, 532, 538
  - crawlspace 67, 68, 69, 78–79, 78, 84, 90–91, 94
    - floors above 72–73, 78
    - warm crawlspace 80, 82
  - cross-laminated elements (CLT) 505
  - curtain walls 469–471, 470, 480
  - CVM *see* control volume method (CVM)
- d**
- damaged timber stud due to rain seepage 497
  - deep foundations 55, 56
    - piles 60–62, 61
    - wells 59–60
  - deep walls 52, 54, 62
    - nailed with grout anchors 53
  - deformable reinforced concrete footings 58, 58
  - design errors and workmanship
    - inaccuracies
      - examples 530, 531
      - probability of 532
  - dew-point ratio 479
  - differential settling 40, 53, 57, 57, 59–60, 62
  - door and window fittings 451

dormer window 347, 368, 371, 371, 460, 460

double glazing 267, 426, 427, 431–432, **432**, 441, 442, **443**, **443**, 445, **445**, 458, 478

heat transfer 431

low-e double glazing 433, **433**, **433**, 434, **434**, 435, 474, 475, **475**

reflective 439

double-skin façades 477

airtightness 472

building physics: acoustics 478–479

energy efficiency at building level 480

fire safety 479–480

moisture tolerance 476–478

with solar shading closed 475

sound transmission loss 480

thermal transmittance 473–474

transient response 474–476

typology 472, 473

downpipes 304, 306, 306

drainage 85, 95–97, 96

paved terrace with a drainage layer

below 411

well point 53, 53

draught 533

dual frame and twofold windows 463, **463**

dust mites 123

dynamic horizontal loads 104, 112

## e

earthquakes 104

eccentric loaded footings 62, 62

edge spacers 433, 444, 447, 447, 463, **463**, 478

impact of 436–437

linear thermal transmittance **457**

EIFS systems *see* exterior insulation and finish system (EIFS) systems

elastomeric sealants 45, 46, 46

electro-chromic glazing 439, 447

elevators, shafts for 411

building physics

acoustics 412

air tightness 412

design and construction 412–413

fire safety 412

structural integrity 411

engineered timber studs 492

EN ISO 13370 method 70, 78, 82

crawlspace, floors above 72–73

grade, floors on 70–72, 71, 72

heated basements and spaces partly

below grade 74

unheated basements, floors above 73–74

EPS *see* expanded polystyrene (EPS)

equilibrium load-bearing capacity 54–56, 55, **55**, 57

excavations 52–54, 56

expanded polystyrene (EPS) 21, 21

application 22

properties 21–22

expansion joint 239, 291, 307, 309, 398, 410

exterior insulation and finish system (EIFS) systems 188, 189, 189, 190, 190, 192, 193–195, **193**, 197, 197, 199–200, 201, 202, 205–208, 206, 207

extruded polystyrene (XPS) 22, 23, 57, 87, 88

properties 23–24

usage 24

## f

façades

double-skin 477

airtightness 472

building physics: acoustics 478–479

energy efficiency at building level 480

fire safety 479–480

moisture tolerance 476–478

with solar shading closed 475

sound transmission loss 480

thermal transmittance 473–474

transient response 474–476

typology 472, 473

- façades (*contd.*)
  - hung glass 471–472, 471
  - photovoltaic (PV) 480–481, 481
  - single-skin
    - curtain walls 469–471, 470
    - structural glazing and hung glass
      - façades 471–472, 471, 472
      - window fronts 469
- FCC *see* fibre cement underlay (FCC)
- fibre cement underlay (FCC) 355–356, 366
- filled cavity walls 227, 230, 233
  - temperature damping, dynamic
    - thermal resistance, admittance **228**
  - veneer 239, 239
- fire safety
  - balconies 408
  - carpentry 524
  - cavity walls 239
  - concrete panels 257
  - double-skin façades 479–480
  - floors 128–129
  - glazing 445–446
  - grade parts and spaces 93–94
  - heavyweight masonry 153
  - inside insulation 185
  - interior finishes of ceilings 521
  - interior finishes on walls 514
  - lightweight masonry 163
  - load-bearing structures 105–106
  - low-slope roofs 302–304
  - outer walls 145
  - outside insulation 202
  - partition walls 403
  - party walls 400
  - pitched roofs 367
  - roofs 148
  - shafts for elevators 412
  - shafts for pipes and ducts 414
  - sheet-metal options 263
  - stairs 421–422
  - timber frame construction 502
  - windows and outer doors 465
- floor insulation 24, 76, 91, 133, 368
- floor leakage 67, 68
- floor on grade 60, 71, 71, 74–76
  - and ground floor assemblies 82, **82**
  - typical 82, 82
- floors 113
  - acoustics
    - airborne noise 126
    - impact noise 126–127
  - airtightness 115–116
  - assemblies 113, 114
  - classification 130
  - concrete decks and prefabricated
    - structural floor units
      - spans 132
  - durability 127–128
  - fire safety 128–129
  - interior finishes on
    - air-tightness 516
    - building physics: acoustics 518
    - choices 515–516
    - design and execution 518
    - moisture tolerance 517–518
    - structural integrity 516
    - thermal transmittance 517
    - transient response 517
  - moisture tolerance
    - construction moisture 119–121
    - dust mites 123
    - interstitial condensation 123–125
    - mould 122, 123
    - rising damp 121
    - sources 119
    - surface condensation 123
    - wind-driven rain 121–122
  - steel floors
    - spans 135–136
  - structural integrity 113–115
  - thermal bridging 125–126
  - thermal transmittance 116–119
  - timber floors 116
    - spans 130–131
  - transient response 119
- floor slab with drawn-in pipes 515, 515
- folding shutter 466–467, 467, **467**
- footings 58–59

- eccentric loaded 62
  - under wide openings 62, 63
  - foundations 54
    - below existing party walls
      - with footings 62–63, 63
      - with pressed piles 63–64
      - with wells 63
    - deep foundations
      - piles 60–62, 61
      - wells 59–60
    - durability 58
    - eccentric loaded footings 62, 62
    - footings under wide openings 62, 63
    - physics-related, building 57
    - spread foundations
      - footings 58–59
      - foundation slabs 59, 59
      - soil consolidation 59
    - structural integrity
      - equilibrium load-bearing capacity 54–56
      - settling load-bearing capacity 56–57
  - free-spanning stair 421
- g**
- gas-filled, low-e double glazing 434–435, **434, 435**
  - glass and mineral fibre 17, 17, 18
    - application 19
    - properties 17–18
  - glass façades 469
    - double-skin
      - airtightness 472
      - building physics: acoustics 478–479
      - energy efficiency at building level 480
      - fire safety 479–480
      - moisture tolerance 476–478
      - thermal transmittance 473–474
      - transient response 474–476
      - typology 472
    - photovoltaic (PV) façades 480–481
    - single-skin
      - curtain walls 469–471, 470
      - structural glazing and hung glass
        - façades 471–472
        - window fronts 469
  - glazed partitions 401, 402
  - glazing
    - airtightness 428
    - building physics
      - acoustics 441–443
      - daylight 443–444
    - and building sealants **43**
    - burglar safety 447
    - developments 426
    - durability 444–445
    - electro-chromic 439
    - fire safety 445–446
    - functions 425
    - hung 472
    - moisture tolerance 439
      - interstitial condensation 441
      - surface condensation 439–440
    - reflective 438, 438
    - solar transmittance 437–439, **438**
    - structural 471–472, 471
    - structural safety 426–428
    - technology 447–448
    - thermal bridging 441
    - thermal transmittance
      - double glazing 431–432, 431, **432, 442, 443, 443, 445, 445**
      - edge spacers 436–437
      - gas-filled, low-e double glazing 434–435, **434, 435**
      - low-e double glazing 433–434, 433, **433**
      - multi-pane glazing 432–433, **433**
      - single glazing 428–431, 429, 430
      - still better insulating 435–436
  - grade, floors on 70–72, 71, 72, 74–76, 82, **82**
  - grade parts and spaces 65
    - air tightness 67–69
    - building physics: acoustics 92
    - design and construction 94–99
    - durability 92
    - fire safety 93–94

- grade parts and spaces (*contd.*)
- moisture tolerance
    - capillary water in the ground 85
    - groundwater 84
    - interstitial condensation 86–89
    - leakages due to the façades above 85–86
    - mould and surface condensation 86
    - seeping rain 85, 85
    - sources 84
    - vapour infiltrating from crawlspace into the spaces above 90–91
  - protective measures
    - different classes 95
    - drainage 95–97, 96
    - waterproof concrete 99
    - watertight encasement inside 97–98, 98
    - watertight encasement outside 98–99, 99
  - radon 94
  - structural integrity 65
    - stability 65
    - strength and stiffness 66
  - thermal bridging 91–92
  - thermal transmittance
    - circles method 74–80
    - EN ISO 13370 method 70–74
    - problem 69
    - typical floor on grade and ground floor assemblies 82, **82**
    - $U_{\text{red}}$ -values recommended 82
    - transient response 82–84
  - green roofs 275, 308–310, 310, 318, 318
  - Grenfell tower 202, 203
  - groundwater 53, 56, 57, 84
- h**
- heated basements 69, 70, 76–77
    - isoflux lines 77
    - and spaces partly below grade 74
  - heat storage materials 1, 31–32
  - heavyweight assembly variants **289**
  - heavyweight deck 281, 281, **286**, **292**, 317
    - insulation thicknesses **286**
    - temperatures in all layers in a temperate climate **292**
  - heavyweight low-slope roof 285, 288, 295, 298
  - heavyweight masonry
    - air-tightness 149
    - building physics: acoustics 152
    - construction moisture 151
    - durability 153
    - fire safety 153
    - history 149
    - moisture tolerance 151
    - rising damp 151, 151
      - interstitial condensation 152
      - mould 151–152
      - surface condensation 152
      - wind-driven rain 151
    - structural integrity 149
    - thermal bridging 152
    - thermal transmittance 149
    - transient response 150
  - hot box/cold box test 176, 197, 211, 234, 234, 299, **299**, 342, 343, **345**, 356, 386
  - hung glass façades 471–472, 471
  - hung glazing 472, 472
- i**
- ICC *see* indoor climate class (ICC)
  - indoor climate class (ICC) 89, 160, 180, 351, 369, 369, 394
  - inhabited basement 88, 89, 92
  - installation shaft 413, 413, 414
  - insulated pitches 337, 346, **347**, 348, 364, **366**
    - airflow patterns 341
    - air permeance **363**
    - cover temperatures **367**
    - measured moisture content in the ceramic tiles 348
    - self-bearing insulation boards on the ribs 372
    - transient properties **347**
  - insulated roof-decking composites 369
  - insulating building materials 9, 10



- characterization 10
  - lightweight brick masonry 11–12, 11
  - lightweight concrete, aerated concrete 12–13, 12
  - insulation, inside
    - airtightness 168
    - building physics: acoustics 183
    - common assemblies 167
    - design and execution 186–187
    - durability 183–185
    - fire safety 185
    - moisture tolerance
      - interstitial condensation 178–182
      - sources 173
      - wind-driven rain 173–178
    - overall evaluation 186
    - structural integrity 167
    - thermal bridging 182–183
    - thermal transmittance 168–171
    - transient response 172
  - insulation, outside
    - acoustics 199
    - airtightness 190
    - common assemblies 187–188
    - design and execution
      - EIFS systems 189, 189, 190, **193**, 197, 201, 202, 205–208, 206, 207
      - stud systems 204
    - durability 200–201
    - fire safety 202
    - maintenance 203
    - moisture tolerance
      - interstitial condensation 195–197
      - sources 192
      - wind-driven rain 193–195
    - overall evaluation 203–204
    - structural integrity 189
    - thermal bridging 197–199
    - thermal transmittance 191
    - transient response 192
  - insulation materials
    - cellular glass 19–20, 19
    - cellulose 15–17, 15
    - characterization 13–14
    - cork 14–15, 14
    - expanded polystyrene (EPS) 21–22, 21
    - extruded polystyrene (XPS) 22–24, 23
    - glass and mineral fibre 17–19, 17, 18
    - polyurethane and polyisocyanurate
      - foam (PUR and PIR) 24–26, 25, 26
    - pressed perlite (PPB) 26–28, 27
    - radiant barriers 28, 28
    - transparent insulation (TIM) 28–29, 29
    - vacuum insulation (VIP) 29–30, 30
  - interior finishes 511
    - building services 511–512
    - carpentry 522–524
    - of ceilings 519–522
    - on floors 515–518
    - on walls 512–514
  - interstitial condensation
    - cavity walls 233–236
    - concrete panels 255
    - floors 123–125
    - glazing 441
    - grade parts and spaces 86–89
    - heavyweight masonry 152
    - insulation, inside 178–182
    - insulation, outside 195–197
    - lightweight masonry 159–160
    - low-slope roofs 299–301
    - outer walls 142
    - outer walls with transparent insulation 270
    - pitched roofs 349–352
    - sheet-metal-covered roofs 382–385
    - sheet-metal options 260–261
    - timber frame construction 498–500
    - windows and outer doors 463
- j**
- John Hancock building 107, 107
  - joints 40–41
  - joint sealants
    - execution 45–46
    - performance checks
      - building physics related 41–42
      - mechanical 41

- joint sealants (*contd.*)
    - sealant choice 42
    - sealant classification 42
    - structural aspects 42–45, 45
  - joint solutions and finishing options 41, 41
  
  - k**
  - Knudsen diffusion 37
  
  - l**
  - lead 377, 378
  - leakages
    - accidental 500
    - air 67, 68, 149, 234, 240, 342, 349, 382, 384, 460, 461, 478, 489, 490, 533
    - due to the façades above 85–86
    - floor 67
    - rain 139, 147, 211, 269, 295, 460
  - leaking joint 99, 100
  - level 1 performance requirements 4, 6
  - level 2 performance requirements 5, 6
  - lightweight brick masonry 11, 11
    - application 12
    - properties 11
  - lightweight concrete, aerated concrete
    - 12, 12
    - application 13
    - properties 12–13
  - lightweight deck 282, 312
    - insulation thicknesses 288
    - transient response 290
  - lightweight handrails 410, 411
  - lightweight high speed brick walls 161, 161
  - lightweight inside leaf 216, 218
  - lightweight low-slope compact roofs 288
  - lightweight masonry
    - air-tightness 154
    - building physics: acoustics 161
    - design and construction 163–164
    - durability 162–163
    - fire safety 163
    - maintenance 163
  - moisture tolerance
    - construction moisture 157–158
    - interstitial condensation 159–160
    - mould and surface condensation 159
    - rising damp 158
    - thermal bridging 160–161
    - wind driven rain 158–159
  - structural integrity 154
  - thermal transmittance 154–155
  - transient response 155–156
  - types 153
- lintels 150, 213
    - insulated at the inside 538
    - insulating 241, 241
    - manufactured 539, 540
  - load-bearing capacity 51, 57, 57, 58, 58
    - equilibrium 54–56, 55, 55
    - settling 56–57
  - load-bearing partitions 121, 130, 173, 329, 398, 401, 401
  - load-bearing party walls 397
  - load-bearing structures 103
    - dynamic horizontal loads 112
    - horizontal loads
      - in massive construction 107–110
      - in skeleton construction 110–111
    - options 103
    - performance checks
      - fire safety 105–106
      - structural integrity 103–105
    - vertical loads 106–107
  - load-bearing system 6
  - loads and sealant choice per load 44
  - local leaks 140, 140
  - low-e double glazing 426, 433–434, 433, 433, 475
    - gas-filled 434–435, 434, 434, 435
    - properties 475
  - low-rise buildings 94, 110, 304, 405
  - low-slope roof coverings
    - bitumen and polymer bitumen membranes
      - combinations with the substrate 276–278

- execution 275–276
  - number of layers 275
- polymer membranes 278, 278
- problems with membranes
  - bitumen 278–280
  - polymers 280
- low-slope roofs 19, 148, 273
  - acoustics 302
  - air-tightness 283–285
  - assemblies 304–305
  - bitumen and polymer bitumen
    - membranes 275–278
  - combinations with the substrate
    - 276–278
  - execution 275–276
  - number of layers 275
- building-ups 307, 309
- fire safety 302–304
- heavy and lightweight low-slope
  - compact roofs 288
- heavyweight assembly variants **289**
- heavyweight deck **286, 292**
- heavyweight low-slope roof 298
- history 273–274
- hygrothermal loading 291–294
- lightweight deck **288, 290**
- maintenance 304
- mediumweight deck **290**
- moisture tolerance
  - construction moisture 295–298, **296**
  - interstitial condensation 299–301
  - precipitation 295
  - sources 295
- pitched versus 140
- polymer membranes 278
- problems with membranes
  - bitumen 278–280
  - polymers 280
- protected membrane roofs
  - design and construction 317–318
  - performance checks 311–317
- roof deck as classification variable
  - 280–283
- roof edges 307, 307
- settling and expansion joints 307, 309

- sewers and downpipes 306, 306
- sloping screed 305
- special uses
  - green roofs 308–310, 310
  - parking decks 310
  - terraces 310–311, 310
- structural integrity 283
- temperate climates **303–304**
- thermal bridging 302
- thermal transmittance 285–289
- transient response 289–291
- wind suction on 283, **284, 285**

## ***m***

- masonry
  - cavity wall 514
- heavyweight
  - air-tightness 149
  - building physics: acoustics 152
  - construction moisture 151
  - durability 153
  - fire safety 153
  - history 149
  - moisture tolerance 151
  - rising damp 151–152, 151
  - structural integrity 149
  - thermal bridging 152
  - thermal transmittance 149
  - transient response 150
- lightweight
  - air-tightness 154
  - building physics: acoustics 161
  - design and construction 163–164
  - durability 162–163
  - fire safety 163
  - maintenance 163
  - moisture tolerance 157–161
  - structural integrity 154
  - thermal transmittance 154–155
  - transient response 155–156
  - types 153
- massive construction 103
  - horizontal loads in 107–110
- massive outer walls 167
  - inside insulation 167–187

- massive outer walls (*contd.*)
  - outside insulation 187–208
  - see also* masonry
- massive walls 171, 181, 200, 204, 205, 205
- materials for hygrothermal performance 9
  - air barriers and air retarders 39–40
  - heat storage materials 31–32
  - joints 40–41
  - joint sealants
    - execution 45–46
    - performance checks 41–42
    - sealant choice 42
    - sealant classification 42
    - structural aspects 42–45, 45
  - joint solutions and finishing options 41, 41
  - thermal insulation, materials for
    - cellular glass 19–20, 19
    - cellulose 15–17, 15
    - cork 14–15, 14
    - expanded polystyrene (EPS) 21–22, 21
    - extruded polystyrene (XPS) 22–24, 23
    - glass and mineral fibre 17–19, 17, 18
    - lightweight brick masonry 11–12, 11
    - lightweight concrete, aerated concrete 12–13, 12
    - low apparent thermal conductivity 9
    - polyurethane and polyisocyanurate foam (PUR and PIR) 24–26, 25, 26
    - pressed perlite (PPB) 26–28, 27
    - properties 10
    - radiant barriers 28, 28
    - transparent insulation (TIM) 28–29, 29
    - vacuum insulation (VIP) 29–30, 30
  - vapour barriers and vapour retarders 37–38
- waterproof layers 32
  - basic property 32
  - bituminous membranes 33–36, 34–35
  - polymer-bitumen membranes 36
  - polymer membranes 36–37
  - short history 32–33
- mediumweight deck 280, 281, 282, 290
- metals 377
  - cellular sheet-metal outer wall systems, air permeance of 258, 258
  - outer sheet-metal finish, gutter under 262
  - sheet-metal elements 257, 258
  - sheet-metal roof typology 380–381
  - see also* sheet-metal-covered roofs; sheet-metal options
- metal tiles 327, 328
- moisture tolerance
  - balconies 408
  - cavity walls 227–236
  - concrete panels 255
  - double-skin façades 476–478
  - floors 119–125
  - glass façades 476–478
  - glazing 439–441
  - grade parts and spaces 84–91
  - heavyweight masonry 151
  - inside insulation 173–182
  - interior finishes of ceilings 521
  - interior finishes on floors 517–518
  - interior finishes on walls 513
  - lightweight masonry 157–161
  - low-slope roofs 295–301
  - outer walls 142–143
  - outer walls with transparent insulation 269–270
  - outside insulation 192–197
  - partition walls 402
  - party walls 399
  - pitched roofs 347–364
  - roofs 147
  - sheet-metal-covered roofs 381–390
  - sheet-metal options 260–261

timber frame construction 495–500  
 windows and outer doors 460–463  
 mould 147  
   cavity walls 233, 534–536  
   concrete panels 255  
   floors 122  
   grade parts and spaces 86  
   heavyweight masonry 151–152  
   lightweight masonry 159  
   on a lintel caused by a ventilation pipe  
     317  
   outer walls 143  
   and rain penetration 532  
   risk analysis 534–536  
   timber frame construction 498  
 mouldy doors 86, 88  
 multi-pane glazing 426, 432–433, **433**

## **n**

natatoriums 157, 234, 235, 393, 521, 521,  
   528  
 negative consequences 527–528, 534  
   weighting **533**  
 non-cohesive soils 52  
 non-load-bearing panels 252, 253

## **o**

obliqueness 104, 105  
 ODP *see* ozone depleting potential  
   (ODP)  
 office at floor 32 476, 477  
 office building 251, 255, 260, 401, 403,  
   475, 477, 511  
 one brick and half masonry wall 149,  
   150  
 one-brick masonry wall 150, 168, 171,  
   172, 177, 177, 179  
 outer sheet-metal finish, gutter under  
   262  
 outer walls  
   air-tightness 140–141  
   building physics: acoustics 143–144  
   durability 144  
   fire safety 145, **145**  
   maintenance and economics 145

massive 149  
   heavyweight masonry 149–153  
   lightweight masonry 153–164  
 moisture tolerance  
   interstitial condensation 142, 143  
   mould 143  
   rising damp 142  
   surface condensation 143  
   wind-driven rain 143  
 structural integrity 139–140  
 thermal bridging 143  
 thermal transmittance 141  
 thermal transmittances 141, **141**  
 transient response 142  
 outer walls with transparent insulation  
   265  
   airtightness 265–267  
   application 271  
   assemblies 265  
   durability 271  
   moisture tolerance  
     construction moisture 269–270  
     interstitial condensation 270  
     which sources 269  
   structural integrity 265  
   thermal transmittance 267–268  
   transient response 268–269  
 overhangs 230, 307, 308, 497  
 ozone depleting potential (ODP) 24

## **p**

parking decks 310  
 partial bond 275, 276, 276  
 partition walls  
   acoustics 403  
   air tightness 401  
   design and construction 404  
   durability 403  
   fire safety 403  
   moisture tolerance 402  
   structural integrity 401  
   thermal bridging 402–403  
   thermal transmittance 401  
   transient response 402  
   types 400–401

- party walls 183, 199, 397
  - acoustics 400
  - air tightness 398
  - design and construction 400
  - fire safety 400
  - moisture tolerance 399
  - structural integrity 397–398
  - thermal bridging 399–400
  - thermal transmittance 399
  - with tieless cavity 398
  - transient response 399
  - with wood wool cement board 502
- paved terrace with drainage layer below 411
- PCMs *see* Phase Change Materials (PCMs)
- performance, defined 3
- performance-based requirements
  - advantages 3–4
  - definitions 3
  - impact 6–7
  - integrating the approach 6
  - process 4
- perimeter beam above thermal break 91–92, 93
- Phase Change Materials (PCMs) 31–32, 493
- photovoltaic (PV) façades 480–481, 481
- pile foundations 60–62, 61
- piles as soil anchor 65, 66
- pipes and ducts, shafts for 413
  - building physics
    - acoustics 414
    - air tightness 414
  - design and construction 414
  - fire safety 414
  - structural integrity 413
- PIR *see* polyisocyanurate foam (PIR)
- pitched roof coverings
  - ceramic tiles 321–322, 322
  - concrete tiles 324
  - corrugated roof sheets 326
  - metal tiles 327
  - quarry and fibre-cement slates 324
  - shingles 326
  - timber slates and plain tiles 326
- pitched roofs 321
  - air
    - attic floors insulated 335
    - roof pitches insulated 335–337
  - assemblies 331–332, 331, 332
  - building physics: acoustics 365–366
  - durability 367
  - fire safety 367
  - history 334–335
  - insulation between concrete rafters 346
  - maintenance 368
  - moisture tolerance
    - construction moisture 349
    - interstitial condensation 349–352
    - rain 347–348
    - sources 347
  - roof assemblies
    - attic unused or used as storage space 368
    - attic used as living space 368–370
  - roof details 371–373
  - structural integrity 333–334
  - thermal bridging 364–365
  - thermal transmittance
    - attics floor insulated 340–342
    - clarification 339
    - roof pitches insulated 342–346
  - transient response 346–347
- pitched roofs typology
  - according to the coverings 331
  - according to the form
    - composite forms 328, 329
    - simple forms 328, 329
  - according to the supporting structure 328
    - purlins on trusses 329–330
    - rafters 330, 331
- pitched versus low-slope roof 139, 140
- plastic hinge formation 105, 106
- PMV *see* predicted mean vote (PMV)
- polyamide foil, diffusion thickness of 39
- polyisocyanurate foam (PIR) 24, 25, 26
  - application 26
  - properties 25

- polymer-bitumen membranes 36  
 polymer membranes 36–37, 278, 278  
 polymers 280  
 polyurethane (PUR) 24, 25, 26, 450  
   application 26  
   properties 25  
 PPB *see* pressed perlite (PPB)  
 precipitation 147, 275, 295, 347, 460  
 predicted mean vote (PMV) 476, 478  
 prefabricated piles 61  
 pressed perlite (PPB) 26, 27  
   application 28  
   properties 26–27  
 probability of design errors and  
   workmanship inaccuracies **532**  
 protected membrane roof 274, 274, 312,  
   313, 316, 317  
   design and construction  
     details 317–318  
     MW as insulation material 318  
     roofing membrane 317  
   performance checks  
     moisture tolerance 316–317  
     questions advanced 311  
     thermal transmittance 311–316  
 PUR *see* polyurethane (PUR)  
 purlins on trusses 329–330  
 PV façades *see* photovoltaic (PV) façades
- q**  
 quadruple glazing 434, 435  
 quarry and fibre-cement slates 324, 326
- r**  
 radiant barriers 28, 28  
 radon 68, 94  
 rafters 330, 331  
 rain  
   leakage 139, 147, 211, 269, 295, 460  
   in the basement 94, 94  
   penetration 532, 533, 536, 539, 540  
     across an initially dry veneer 229,  
     **229**  
     giving a wet inside leaf along a  
     window bay 537  
   seeping 84, 85, 85, 97, 311, 408  
   wind-driven  
     cavity walls 228–233  
     concrete panels 255  
     floors 121–122  
     heavyweight masonry 151  
     insulation, inside 173–178  
     insulation, outside 193–195  
     outer walls 143  
     sheet-metal options 260  
     timber frame construction 496–498  
 Redtenbacher's equation 417, **418**  
 reflective glazing 438, 438  
 reinforced glass 446, 446  
 relative humidity (RH) 57, 86, **87**  
 retrofitted roof 351, 352  
 RH *see* relative humidity (RH)  
 rising damp  
   floors 121  
   heavyweight masonry 151–152, 151  
   lightweight masonry 158  
   outer walls 142  
   timber frame construction 496  
 risk, defined 527  
 risk analysis 186, 527  
   cavity walls  
     deficiencies causing discontentment  
     530–531  
     discontentment with the  
     consequences 531–534  
     filled versus non-filled 529  
     mould 534–536  
     probability 531  
     rain penetration 536  
     risk evaluation 539  
     upgrades 539–540  
   definitions 527–528  
   identification and probability of likely  
     and possible deficiencies 528  
   proposals limiting the risks 529  
   seriousness of discontentment 528  
   steps to take 528  
 roller shutter 466–467, 467, **467**  
 Roman tiles 322  
 roof cover 147, 147, 332, 349, **349**, 365

- roof cover (*contd.*)
    - with critical rain tightness 147
    - low-slope *see* low-slope roof coverings
    - measured equivalent diffusion
      - thickness **349**
    - pitched *see* pitched roof coverings
  - roof edges 278, 283, 288, 307, 307, 521
    - finishing 278
  - roof pitches insulated 335–337, 342–346, 352
  - roofs
    - air tightness 146
    - building physics: acoustics 148
    - durability 148
    - fire safety 148
    - maintenance and economy 148
    - moisture tolerance 147
    - structural integrity 146
    - thermal bridging 147
    - thermal transmittance 146, **146**
    - transient response 146
    - see also* compact low-slope roofs; green roofs; low-slope roofs; pitched roof coverings; pitched roofs; protected membrane roof; sheet-metal-covered roofs
- S**
- sandwich panels 10, 24, 172, 251, 252, 253, **254**, **256**, 386
  - SBS polymer *see* Styrene/Butadiene/styrene (SBS) polymer
  - screeds and cover 519
  - sealant
    - choice 42
    - classification 42
    - cracking 464, 465
    - elastomeric 45, 46, 46
    - glazing and building sealants **43**
    - loads and sealant choice per load **44**
    - see also* elastomeric sealants; joint sealants
  - seeping rain 84, 85, 85, 97, 311, 408
  - self-cleaning glass 426, 447
  - settling and expansion joints 307, 309
  - settling load-bearing capacity 54, 56–57
  - sewers 306, 306
  - shafts for elevators 411
    - building physics
      - acoustics 412
      - air tightness 412
      - design and construction 412–413
    - fire safety 412
    - structural integrity 411
  - shafts for pipes and ducts 413
    - building physics
      - acoustics 414
      - air tightness 414
      - design and construction 414
      - fire safety 414
      - structural integrity 413
  - sheet-metal-covered roofs 377
    - aluminium 380, 380
    - copper and brass 377–378, 379
    - design and construction 393–394
    - durability 392–393
    - lead 377, 378
    - moisture tolerance
      - first case from practice 386–387
      - history 381–382
      - interstitial condensation 382–385
      - second case from practice 387–388
      - test building results 388–390
  - sheet-metal roof typology 380–381, 380
  - thermal bridging 391
  - zinc 379, 379
  - sheet-metal elements 258, 258, 386
  - sheet-metal options
    - air tightness 258
    - building physics: acoustics 262
    - common assemblies 257
    - design and construction 263
    - durability 262–263
    - fire safety 263
    - maintenance 263
    - moisture tolerance
      - interstitial condensation 260–261



- surface condensation 260
  - wind-driven rain 260
- structural integrity 257–258
- thermal bridging 261–262
- thermal transmittance 259
- transient response 259–260
- sheet-metal roof typology 380–381
- shingles 326, 327
- shrinkage joints 127, 519
- single glazing 426, 426, 428–431, 429, 430, 431–432, 441, 466, 474, 475, 476, 477, 479
- single-skin glass façades
  - curtain walls 469–471, 470
  - structural glazing and hung glass façades 471–472, 471, 472
  - window fronts 469
- skeleton construction, horizontal loads in 110–111
- sketch designs 4, 8
- softwood 498
  - mechanical properties of **489**
  - mould risk under long-lasting relative humidity **495**
- soil consolidation 59
- soil freezing 57
- soiling
  - excessive 185, 185
  - minimizing 257
- solar radiation 437, 439, 458, 474, 476
- solar shading 29, 458–459, 458, **459**, 468, 472, 475, 476, 480, 492
- sound insulation 115, 130, 161, 237, 256, 302, 337, 398, 403, 414, 464, 472, 478, 501, 502, 520, 523
- southwest looking one-brick outer wall 183, **184**
- sprayed gypsum 332, 335, 512, 512
- spread foundations
  - footings 58–59
  - foundation slabs 59, 59
  - soil consolidation 59
- stairs
  - building physics: acoustics 420–421
  - design and construction 422
  - fire safety 421–422
  - free-spanning 421
  - structural integrity 420
  - types 419–420, 419
  - user safety 422
- steel 103, 450
- steel and concrete skeletons 105, 105
- steel floors 135, 136
  - spans 135–136
- steel framed walls **493**
- steel frames 466
- stiffly coupled walls 109, 110
- structural glazing 471–472, 471
- structural integrity
  - balconies 405–406
  - carpentry 523
  - cavity walls 212–213
  - concrete panels 251–252
  - floors 113–115
  - foundations 54–57
  - grade parts and spaces 65–66
  - heavyweight masonry 149
  - inside insulation 167
  - interior finishes of ceilings 520
  - interior finishes on floors 516
  - interior finishes on walls 513
  - lightweight masonry 154
  - load-bearing structures 103–105
  - low-slope roofs 283
  - outer walls 139–140
  - outer walls with transparent insulation 265
  - outside insulation 189
  - partition walls 401
  - party walls 397–398
  - pitched roofs 333–334
  - roofs 146
  - shafts for elevators 411
  - shafts for pipes and ducts 413
  - sheet-metal options 257–258
  - stairs 420
  - timber frame construction 487–488
- stuccoed ceiling in a historic building 519

- Styrene/Butadiene/styrene (SBS) polymer  
36, **36**, 97–98
- surface condensation  
cavity walls 233  
concrete panels 255  
floors 123  
glazing 439–440  
grade parts and spaces 86  
heavyweight masonry 152  
lightweight masonry 159  
outer walls 143  
sheet-metal options 260  
timber frame construction 498  
windows and outer doors 461–462
- t**
- temperature damping 150, 155, 172, 192,  
**494**
- terraced house 78, 79, 80, **80**, **81**, 321,  
536
- terraces 283, 310–311, 310
- thermal bridging 57, 91, 92, **93**, 191, 192  
balconies 406–408  
cavity walls 236–237  
concrete panels 256  
floors 125–126  
glazing 441  
grade parts and spaces 91–92  
heavyweight masonry 152  
inside insulation 182–183  
lightweight masonry 160–161  
low-slope roofs 302  
outer walls 143  
outside insulation 197–199  
partition walls 402–403  
party walls 399–400  
pitched roofs 364–365  
roofs 147  
sheet-metal-covered roofs 391  
sheet-metal options 261–262  
timber frame construction 501  
windows and outer doors 463
- thermal cut at grade 503, 503
- thermal insulation materials  
cellular glass 19–20, 19  
cellulose 15–17, 15  
characterization 13–14  
cork 14–15, 14  
expanded polystyrene (EPS) 21–22, 21  
extruded polystyrene (XPS) 22–24, 23  
glass and mineral fibre 17–19, 17, 18  
insulating building materials 10  
characterization 10  
lightweight brick masonry 11–12,  
11  
lightweight concrete, aerated  
concrete 12–13, 12  
low apparent thermal conductivity 9  
objective 9  
polyurethane and polyisocyanurate  
foam (PUR and PIR) 24–26, 25,  
26  
pressed perlite (PPB) 26–28, 27  
properties  
air 10  
fire 10  
mechanical 10  
moisture 10  
temperature, IR and UV 10  
radiant barriers 28, 28  
transparent insulation (TIM) 28–29,  
29  
vacuum insulation (VIP) 29–30, 30
- thermal transmittance 453  
carpentry 524  
cavity walls 214–227  
concrete panels 252–254  
double-skin façades 473–474  
floors 116–119  
glazing 428–437  
grade parts and spaces 69–82  
heavyweight masonry 149  
inside insulation 168–171  
interior finishes of ceilings 520  
interior finishes on floors 517  
lightweight masonry 154–155  
low-slope roofs 285–289  
outer walls 141  
outer walls with transparent insulation  
267–268

- outside insulation 191
  - partition walls 401
  - party walls 399
  - pitched roofs 339–346
  - protected membrane roofs 311–316
  - roofs 146
  - sheet-metal options 259
  - timber frame construction 491–492
  - windows and outer doors 452–457
  - tight stainless-steel cladding 195, 196
  - TIM *see* transparent insulation materials (TIM)
  - timber 106
    - ceiling 341, **342**
    - clapboarding 502
    - floors 116, 132
      - spans 130–132
    - and metal windows 453, **454**
  - timber frame construction 485, 486
    - airtightness 488–491
    - building physics: acoustics 501
    - construction, assemblies 485–486
    - design and construction
      - air and vapour retarder 504
      - buildingwrap covering the sheathing 504–505
      - frame 503–504
      - thermal insulation 504
      - variants 505
    - durability 501–502
    - fire safety 502
    - foundation walls, anchoring in 487
    - history 485
    - hot box test 491
    - maintenance 502
    - moisture tolerance 495
      - accidental leakage 500
      - construction moisture 495–496
      - interstitial condensation 498–500
      - mould and surface condensation 498
      - rising damp 496
      - wind-driven rain 496–498
    - outside wall, insulation thickness **492**
    - prefabrication 486
    - structural integrity 487–488
    - sustainability 503
    - thermal bridging 501
    - thermal transmittance 491–492
    - traditional detailing 504
    - transient response 492–493
  - timber framed wall as a series/parallel circuit 491
  - timber frame low-energy homes 494
  - timber frame outer wall 498, 499, **499**
    - with brick veneer 497
  - timber frame outside wall 531
  - timber frame party wall 501
  - timber frame walls, drying of **496**
  - timber slates and plain tiles 326
  - timber window 448, 451, 453
  - top floor 113, 515–518, 515, 517, 520
  - transparent insulation materials (TIM)
    - 28, 29, 265, 266, 267
      - application 29
      - properties 29
  - trickle vents 68, 91, 468–469, 468, 478–479
  - two-ply coverage 275, 275
- U**
- UF *see* ureumformaldehyde foam (UF)
  - unheated basements 79–80, 81, 84
    - floors above 73–74
  - ureumformaldehyde foam (UF) 243, 243, 244
- V**
- vacuum glass 435, 436
  - vacuum insulation (VIP) 29, 30
    - application 30
    - properties 30
  - valley gutter 328, 329, 368, 371, 393, 394
  - vapour barriers 37–38
  - vapour infiltrating from crawlspace into the spaces above 90–91
  - vapour retarder 37–40, 89, **90**, 176, 177, 179, 181–182, **181**, 270, 273, 282, 361, 370
  - veneer wet 231, 532

vented tiles as ballast 318  
 ventilated low-sloped roofs 274  
 Vierendeel girder 111, 111, 134, 134  
 vinyl 449–450, 450, 461, 464, 466, 502  
 VIP *see* vacuum insulation (VIP)

## W

### walls

aerated concrete wall 13, 157, **157**,  
 158, 158, 159, 159, 160, 161, **161**,  
 162, 162  
 basement walls 73, 76, 77, **90**  
 loads on 66, 67  
 thermal admittance and time shift of  
**83**  
 clear wall thermal transmittance 117,  
**117**, 149, 154, 157, 158, 159, 168,  
 191, **191**, 214, **218**, 227, 230, 473  
 concrete and brick outer wall 174  
 concrete wall 159, 160  
 aerated 161, **161**, 162  
 air permeance of 168  
 with one glass TIM panels 270, 271  
 curtain walls 469–471, 470, 480  
 deep walls 52, 54, 62  
 nailed with grout anchors 53  
 filled cavity walls 227, 230, 233  
 temperature damping, dynamic  
 thermal resistance, admittance  
**228**  
 veneer 239, 239  
 interior finishes on  
 air-tightness 513  
 building physics: acoustics 513–514  
 choices 512  
 fire safety 514  
 gypsum board 514  
 moisture tolerance 513  
 structural integrity 513  
 wet plasters 514  
 lightweight high speed brick walls  
 161, 161  
 load-bearing party walls 397  
 massive outer walls 167  
 inside insulation 167–187

outside insulation 187–208  
 massive walls 171, 181, 200, 204, 205,  
 205  
 one-brick masonry wall 150, 168, 171,  
 172, 177, 177, 179  
 steel framed walls **493**  
 stiffly coupled walls 109, 110  
 timber frame outer wall 498, 499, **499**  
 with brick veneer 497  
 timber frame outside wall 531  
 timber frame party wall 501  
 timber frame walls, drying of **496**  
 wet one-brick masonry wall 178  
 whole-wall thermal transmittance  
**170, 494**  
*see also* cavity walls; outer walls;  
 partition walls; party walls  
 warm crawlspace 79, 80, 82, 91  
 waterproof concrete 99  
 waterproof layers 32  
 basic property 32  
 bituminous membranes 33–36,  
**34–35**  
 polymer-bitumen membranes 36  
 polymer membranes 36–37  
 short history 32–33  
 waterproof mortars 98  
 water puddles 312, 314, 314, 316, 460  
 watertight encasement inside 97–98, 98  
 watertight encasement outside 98–99, 99  
 well foundation 59–60, 60  
 well point drainage 53, 53  
 wet one-brick masonry wall 178  
 whole-wall thermal transmittance 169,  
**170, 494**  
 wind-driven rain  
 cavity walls 228–233  
 concrete panels 255  
 floors 121–122  
 heavyweight masonry 151  
 insulation, inside 173–178  
 insulation, outside 193–195  
 outer walls 143  
 sheet-metal options 260  
 timber frame construction 496–498

- window frames 169, 206, 448, 452
      - made of different materials 450
      - thermal transmittance **456**
    - windows
      - airtightening window reveal 241, 241
      - bay 505
      - dormer 347, 368, 371, 371, 460, 460
      - dual frame and twofold windows 463, **463**
      - equivalent thermal transmittance as mandated **455**
      - fitting 451
      - fronts 469
      - with small subdivisions 457
      - surface 454
      - timber window 448, 451, 453
    - windows and outer doors
      - airtightness 452
      - building physics: acoustics 463–464
      - durability 464–465
      - fire safety 465
      - frame materials 448–450
      - frame sections and glass mounting 450–451
      - maintenance and safety at use 466
      - moisture tolerance 460
        - interstitial condensation 463
        - rain 460–461
        - surface condensation 461–462
    - solar shading 458, 458, **459**
      - outer glass pane 459
    - structural safety 451–452
    - technology
      - roller and folding shutters 466–467, 467, **467**
      - solar shading 468
      - trickle vents 468–469
      - vinyl, aluminium and steel frames 466
      - wooden frames 466
    - thermal bridging 463
    - thermal transmittance 452–457
    - types 448, 449
    - wind pressure classes 460, **461**
    - wind speed 104, 346, 346, 361, 364
    - wind suction on low-slope roofs 283, **284**, 285
    - wood 448–449, 450
    - wood-based panel clad 204, 204
    - wooden frames 466
    - workmanship inaccuracies 528, 530, 530, **532**, 533
- X**
- XPS *see* extruded polystyrene (XPS)
- Z**
- zinc 379, 379





