

Index

a

- α -Si solar cell 375
- acoustic energy harvesters 271
 - brief history 272–274
 - challenges 277
 - electroacoustic transduction 277–278
 - impedance matching and energy focusing 281
 - modeling 278–281
 - transduction methods 281–283
 - transduction structures 284–288
 - fabrication methods 288
 - materials 288
 - processes 289
 - fundamentals 276, 277
 - principles and concepts 276
 - reported performance survey 274–276
 - testing and characterization 289–290
- active system 224,
- actuator disc 298, 300
- aluminum nitride (AlN) 205, 207, 210, 217
 - electromechanical properties 207
- ambient vibrations stochastic character 14
- amorphous silicon solar cell 366–367
- anode and cathode potential and total cell potential 350–351
- antenna–rectifier matching 326–327
 - antenna matched to rectifier 328–329
 - antenna not matched to rectifier/multiplier 329–330
 - design consequences 330
 - voltage boosting technique 327–328
- areal and volumetric current density and areal and volumetric power density 351
- areal resistivity reduction 355
 - application of materials with high surface-area-to-volume ratio 355, 358
 - oxygen intrusion mitigation 358–359

autonomous wireless sensor systems 417–419

- axial-flux permanent magnet (AFPM) generator 301, 302
- axial force 227–229
- axial induction factor 298

b

- beams 288
 - Betz limit 298, 300
 - bimorph cantilever 134
 - bistable harvesters 446–450
 - bistable oscillators
 - buckled beam 21–23
 - cantilevers 19–21
 - blackbody 66, 71, 74, 75
 - blade element momentum (BEM) 303, 304
 - bluff body 307
 - body heat 251, 257, 259
 - Boltzmann transport equation (BTE) 61, 62, 63
 - breakdown voltage 53
 - buckled beam 21–23
 - bulk heterojunction (BHJ) 371, 372
 - bulk single crystals
 - energy harvesting with perovskites 135
 - perovskites 135
 - bypass heat flow domination 113
- ### c
- canonical resonant-type electrodynamic energy harvester 176
 - cantilevers 19–21
 - cantilever-shaped out-of-plane generator 168
 - capacitive voltage boost converter 340
 - cation exchange membrane (CEM) 350
 - ceramics
 - energy harvesting examples 134

- ceramics (*contd.*)
 - fabrication process 132, 133–134
 - chalcogenides properties (group 16) 106
- chamber 350
- chemical bath deposition (CBD) 369
- CMOS-MEMS technology 254–255
- cold start 97
- commercialized micro technologies
 - Micropelt technology 257–258
 - Nextreme/Laird technology 258–259
 - Thermogen technology 259–260
- composite and piezoelectricity 134
- conjugate power variables 185, 279, 280
- converters for ultra-low-output transducers and examples 396–397
- copper indium gallium selenide (CIGS) 363, 375, 376
 - and CdTe solar cell development 367–370
- corona charging 162–163
- Coulombic efficiency 353
- coupling strength 191
- cross-plane configuration (CPC) 247, 249, 250
- crystallogens properties (group 14) 106, 107
- current status and trends 3–4

- d**
- deep reactive-ion etching (DRIE) 208, 209–210, 214, 289
- diaphragms 286–287
- dielectric polymers 54
- die-level hermetic packaging 210, 213
- direct transduction 280–281
- dry etching 208, 209
- dyadic Green's functions (DGFs) 68, 69, 73
- dye-sensitized solar cells (DSSCs) 373–374
- dynamic models 12–13
 - ambient vibrations stochastic character 14
 - electromagnetic generator 15
 - piezoelectric cantilever generator 14, 15
 - transfer function 15–16
- dynamic thermoelectric harvesting prototype 428

- e**
- eddy current damping 192
- effective damping coefficient 312
- effective isotropic radiated power (EIRP) 325
- effective radiated power (ERP) 325
- electrets *see under* electrostatic/electret-based harvesters
- electrical contact resistances domination 112–113
- electrical damping 203, 204
- electrical interface 34
- electroacoustic transduction 277–278
 - impedance matching and energy focusing 281
 - modeling 278–281
 - transduction methods 281–283
 - transduction structures 284–288
- electrochemical deposition *See* electrodeposition
- electrodeposition 253
- electrodes 350
- electrodynamics physics 179
 - Faraday's law 179–180
 - Lorentz force 180
 - simplified equations 180–181
- electrodynamics transduction coefficient 181
- electrodynamics vibrational energy harvesting 175–178
 - fabrication of harvesters 194–196
 - harvester architectures 181–183, 184
 - harvesters design 192–194
 - modeling and optimization 183
 - modeling 184–190
 - optimization 190–191
 - theoretical background 178
 - electrodynamic physics 179–181
 - energy storage, dissipation, and conversion 178
- electrolyte 401
- electromagnetic generator 15
- electromagnetic harvester 10–11
- electromagnetic induction 177
- electromagnetic transducers 27–28
 - basic principle 27–28
 - induced voltage 28
 - mechanical aspect 29–30
 - self-induction 28–29
 - energy extraction cycle 33
 - figures of merit and limitations 36–37
 - rectification cycle 35
 - resistive cycle 34
 - self-inductance cancelation 34–35
 - Synchronized Magnetic Flux Extraction (SMFE) 36
 - typical architectures 30, 31
 - case study 30, 32–33
 - general case 33
- electromagnetic transduction 282
- electromechanical coupling factor and piezoelectric materials 126–128
 - special considerations for energy harvesting 128–129
- electromechanical transducers 27
 - electromagnetic transducers 27–28

- – basic principle 27–30
 - – energy extraction cycle 33–37
 - – typical architectures 30–33
 - electrostatic transducers 45
 - – capacitance 45, 46
 - – design parameters for capacitor 47–48
 - – electric potential 46
 - – energy extraction cycles 48–51
 - – energy 46–47
 - – force 47
 - – Gauss's law 45
 - – limits 51, 52–53
 - electrostrictive materials 53
 - – energy harvesting strategies 54, 55
 - – physical origin and constitutive equations 53–54
 - magnetostrictive materials 55
 - – constitutive equations 56
 - – physical origin 55
 - piezoelectric transducers 37
 - – constitutive equations 38
 - – energy extraction cycles 41–44
 - – maximal power density and figure of merit 44–45
 - – physical origin in ceramics and crystals 37–38
 - – typical architectures for energy harvesting 39–41
 - vibration energy harvester mechanical structure effect 56–58
 - electromotive force 28
 - electronic loads 86
 - electroplating, electrophoresis, and dielectrophoresis 117–118
 - electroquasistatic (EQS) regime 279
 - electrostatic/electret-based harvesters 149
 - conversion cycle 149–151
 - electrets 160–161
 - – charging technologies 162–163
 - – generator model 163–168
 - – generators 168–171
 - – materials 161–162
 - electrostatic generators
 - – design and fabrication methods 156–158
 - – examples 158–159
 - generator models
 - – configuration 151–153
 - – electrode design 153–156
 - electrostatic harvester 11
 - electrostatic pull-in 282–283
 - electrostatic transducers
 - basic principles 45
 - – capacitance 45, 46
 - – electric potential 46
 - – energy 46–47
 - – force 47
 - – Gauss's law 45
 - design parameters for capacitor 47
 - – architecture 47–48
 - – dielectric 48
 - energy extraction cycles 48–49
 - – charge-constrained cycle 49–50
 - – electret cycle 51
 - – voltage-constrained cycle 50–51
 - limits 51
 - – breakdown voltage 53
 - – parasitic capacitors 51, 52
 - – pull-in force 53
 - electrostatic transduction 282–283
 - electrostrictive materials 53
 - energy harvesting strategies 54, 55
 - physical origin and constitutive equations 53–54
 - energy-autonomous sensors for air flow temperature 261
 - energy conversion efficiency 354
 - energy harvesting, meaning and definition of 1–2
 - EnOcean 261
 - equivalent circuits 279–280
 - evanescent modes 67, 71, 72, 73, 74, 76, 79
 - exoelectrogen 350
 - external tuning 16
 - extracellular electron transfer (EET) mechanism, elucidating 359
- f**
- Faraday's law 175, 176, 179–180, 186
 - far-field radio frequency (RF) energy transfer and harvesting 321
 - examples and future perspectives 341–344
 - harvesting versus transfer 324–325, 326
 - nonradiative transfer 322, 323
 - radiative transfer 323, 324
 - rectifier 330–331
 - – 50- Ω antenna 335
 - – antenna 334–335
 - – complex conjugately matched antenna 335, 336
 - – DC output voltage 332–334
 - – rectenna results 336, 337–338, 339
 - – RF input impedance 331–332
 - – voltage up-conversion 339, 340
 - rectifying antenna 326
 - – antenna–rectifier matching 326–330
 - – transmission 340–341

- Fermi–Dirac and Bose–Einstein distributions 62
 - ferroelectricity, in perovskites 129, 130–131
 - figure of merit 66, 104, 207, 425
 - material 126–129
 - and maximal power density 44–45
 - fill factor 365
 - finite element method 185, 188–189
 - combination with lumped element method 189–190
 - finite element modeling (FEM) 278, 287
 - flame spraying *See* thermal spray
 - fluctuation-dissipation theorem 69
 - fluid flows and energy harvesting 297–298
 - energy harvesters based on flow instability 306
 - – devices based on galloping and flutter 310, 311–316
 - – vortex shedding devices 307–310
 - fundamental and practical limits 298–300
 - miniature wind turbines 301–302
 - – scaling effects 302–306
 - performance comparison 316–317
 - flutter *See* galloping and flutter
 - foil 248, 249, 259, 260
 - Fourier heat equation 422
 - fractional open-circuit voltage technique 377, 378
 - frequency response function (FRF) 443, 444
 - frequency tuning 16
 - of electromagnetic harvester 393–395
 - friction damping 193
 - Friss equation 340
- g**
- galloping and flutter 310, 311–316
 - gap-closing electrostatic/electrets generators 152, 153, 154, 155, 156, 157
 - Gauss's law 45, 160
 - Gibbs energy 125–126
 - gyrators 89
- h**
- Halbach array 183, 184
 - Harman method 114
 - head actuator, in hard drives 183, 184
 - heartbeat oscillations estimation 437–438
 - heart motion characterization 450–456
 - heat flow 245, 247, 249, 251, 257
 - heat sink 249, 250, 261, 263
 - heat storage thermoelectric harvester for aircraft strain sensors 428, 429–430
 - Helmholtz resonators 272, 284–285, 286
 - high-temperature flux technique 135
 - horns 285
- i**
- impedance matching
 - energy focusing 281
 - structures 284–285
 - incremental conductance (INC) technique 377
 - indirect transduction 281
 - indoor-light-powered wireless sensor networks 380–382
 - inductively coupled plasma (ICP) dry etching 209
 - inertial vibration energy harvester 57–58
 - Infinite Power Solutions Thinergy® cells 398
 - in-plane configuration (IPC) 247, 249, 250
 - in-plane electrets generator 168
 - and equivalent circuit 163–164
 - fabricated with precision machining 169
 - one-dimensional model 165
 - with parylene high-aspect-ratio spring 169
 - with shared electrodes 170
 - soft-X-ray charged 170–171
 - two-plate 167
 - in-plane gap closing 48
 - in-plane generator with comb drive 153–154
 - in-plane strain 124
 - intelligent thermostatic radiator valve (iTRV) 262–263
 - internal resistance and areal resistivity 352–353
 - ion exchange membrane 350
 - ionic electrostrictive polymers 53–54
- j**
- jacket-integrated wireless temperature sensor 263, 264
 - Joule effect 420, 422
- k**
- Kanai's waveform 451, 452, 453, 455–456
 - Kirchhoff's law 13, 160, 165
- l**
- Langevin equation set 14
 - laser Doppler vibrometer (LDV) 450, 452, 453, 455, 457
 - laser vibrometry 290
 - lead-free perovskites 138–139
 - energy harvesting 139
 - lead zirconate titanate (PZT) 204–205, 207, 216, 217

- electromechanical properties 207
- Lenz's law 29
- linear energy harvesters 438–444
- Linear Technologies 398
- Lorentz force 175, 177, 180
- low-power micro photovoltaic systems 376
 - indoor-light-powered wireless sensor networks 380–382
 - maximum power point (MPP) tracking 376, 377–379
 - output voltage regulation 379–380
- lumped element method 184–188
 - combination with finite element method 189–190
- lumped element modeling (LEM) 278–279
- m**
- magnetostrictive materials 55
 - constitutive equations 56
 - physical origin 55
- material hysteresis damping 193
- Maxim Instruments 398
- maximum power point (MPP) tracking 376, 377–379
 - *see also* power conditioning
- maximum power transfer tracking (MPTT) 96
- Maxwell's equations 67, 72
- mean flow acoustic engine (MFAE) 274
- mechanics and dynamics 7–8
 - dynamic models 12–13
 - – ambient vibrations stochastic character 14
 - – electromagnetic generator 15
 - – piezoelectric cantilever generator 14, 15
 - – transfer function 15–16
 - beyond linear micro-vibration harvesting 16
 - – frequency tuning 16
 - – multimodal harvesting 17
 - – up-conversion techniques 17, 18
 - micro vibration energy harvesting strategies 8–9
 - – electromagnetic 10–11
 - – electrostatic 11
 - – from macro to micro to nano 11–12
 - – piezoelectric 9–10
 - nonlinear micro-vibration energy harvesting 18–19
 - – bistable oscillators 19–23
 - – monostable oscillators 23
- metal oxide semiconductor field effect Transistor (MOSFET) 388, 389, 390, 392
- microbatteries 404–405
 - microbial fuel cell (MFC) 347–348
 - future work 355
 - – areal resistivity reduction 355–359
 - – autonomous running 359
 - – extracellular electron transfer (EET) mechanism elucidation 359
 - MEMS, fundamentals of
 - – critical parameters for testing 350–354
 - – materials 350
 - – prior art MEMS MFCS 354–355
 - – structure 348–349
- micro device technologies 252–253
 - research and development 255, 257
 - – CMOS-MEMS technology 254–255
 - – electrodeposition 253
 - – silicon-MEMS technology 253–254
- micro-electro-mechanical-system (MEMS) 153, 156, 157, 158, 161, 168
 - CMOS-MEMS technology 254–255
 - silicon-MEMS technology 253–254
 - *see also* microbial fuel cell (MFC); piezoelectric MEMS energy harvesters
- micro energy storage 401
 - boundary conditions 401–404
 - – microbatteries 404–405
 - – supercapacitors 405, 406
 - primary energy storage approaches 405, 406–407
 - – caveat emptor 409
 - – future work and first-order problems 409–410
 - – volume-constrained versus conformally demanding approaches 408–409
- micromachined acoustic energy harvesters *See* acoustic energy harvesters
- micromachining 208, 213
- Micropelt technology 257–258
- micro photovoltaic module energy harvesting 363
 - amorphous silicon solar cell 366–367
 - CIGS and CdTe solar cell development 367–370
 - dye-sensitized solar cells (DSSCs) 373–374
 - low-power micro photovoltaic systems 376
 - – indoor-light-powered wireless sensor networks 380–382
 - – maximum power point (MPP) tracking 376, 377–379
 - – output voltage regulation 379–380
 - monolithically integration of solar cells with IC 375–376
 - p–n junction and crystalline Si solar cells 363–366

- micro photovoltaic module energy harvesting (*contd.*)
 - polymer solar cell 370–372
 - micro thermoelectric generators 245–247
 - classification 247–250
 - complete systems applications 260
 - energy-autonomous sensors for air flow temperature 261
 - intelligent thermostatic radiator valve (iTRV) 262–263
 - jacket-integrated wireless temperature sensor 263, 264
 - wireless power generator evaluation kit 263
 - wireless pulse oximeter SpO₂ sensor 261–262
 - general considerations 250–252
 - micro device technologies 252–253
 - commercialized micro technologies 257–260
 - research and development 253–257
 - miniature wind turbines 301–302
 - scaling effects 302
 - generator and bearing losses 305–306
 - turbine performance 302–305
 - monolithically integration of solar cells with IC 375–376
 - monostable nonlinear harvesters 441–446
 - monostable oscillators 23
 - motion-based energy harvesting 3
 - multilayer ceramic capacitors (MLCCs) 134
 - multimodal harvesting 17
- n**
 - nanomaterials 143–144
 - nanoscale-gap thermophotovoltaic power generation 76–80
 - nanoscale heat conduction and Seebeck effect 62–64
 - nano-TPV power generators 71
 - nanowires 113, 114
 - near-field thermal radiation and thermophotovoltaic power generation 66–67
 - fluctuational electrodynamics 67–70
 - heat transfer between two bulk materials separated by subwavelength vacuum gap 70–76
 - nanoscale-gap thermophotovoltaic power generation 76–80
 - negative springs 229
 - Nernst equation 350–351
 - Newton's law 13
 - Nextreme/Laird technology 258–259
 - nonlinear input impedance circuits 90
 - nonradiative transfer 322, 323
 - numerical approaches, for acoustic energy harvesters 281
- o**
 - Ohm's law 351
 - on-board tuning 16
 - open-circuit voltage 365
 - out-of-plane finger type *See* in-plane gap closing
 - out-of-plane gap closing 48
 - out-of-plane strain 124
 - overlapping-area-change electrostatic/electrets generators 152, 153, 154–155, 156, 157
- p**
 - pacemakers powering with heartbeat vibrations 435–436
 - bistable harvesters 446–450
 - design specifications 436–437
 - experimental investigations 450
 - heart motion characterization 450–456
 - heartbeat oscillations estimation 437–438
 - linear energy harvesters 438–444
 - monostable nonlinear harvesters 441–446
 - parallel SSHI (Synchronized Switch Harvesting on Inductor) 43
 - parasitic capacitance 86, 163, 164, 165, 166, 167, 168
 - parasitic capacitors 51, 52
 - passive system 224,
 - peak power 365
 - peak rectifiers 90–92
 - Peltier effect 422, 423
 - permittivity change electrostatic/electrets generators 152, 153
 - perovskite materials 129
 - bulk single crystals 135
 - ceramics 132–134
 - lead-free 138–139
 - phase diagram 131–132
 - polycrystalline perovskites thin films 136–137
 - single-crystal thin films 137–138
 - structure 129–131
 - Perpetua Power Source Technologies 259, 260, 263, 264, 265
 - perturb and observe (P&O) technique 377
 - phase change material (PCM) 420, 426, 431
 - photoionization 163
 - photovoltaic (PV) cells 3
 - piezoelectric cantilever generator 14, 15
 - piezoelectric effect 9–10

- piezoelectric energy harvester (PEH) 453, 455, 456
- piezoelectric materials 123–125
 - electromechanical coupling factor 126–128
 - special considerations for energy harvesting 128–129
 - nanomaterials 143–144
 - perovskite materials 129
 - bulk single crystals 135
 - ceramics 132–134
 - lead-free 138–139
 - phase diagram 131–132
 - polycrystalline perovskites thin films 136–137
 - single-crystal thin films 137–138
 - structure 129–131
 - PVDFs 141
 - energy harvesters 143
 - structure 141–142
 - synthesis 143
 - thermodynamics 125–126
 - typical values 144–145
 - wurtzites
 - doping 141
 - structure 139–140
 - thin films and energy harvesting 140–141
- piezoelectric MEMS energy harvesters 201–202
 - challenging issues 213
 - frequency response 215–216
 - output power 213–215
 - piezoelectric material 217–218
 - development 204–205
 - characterization 211–213
 - fabrication technologies 205, 207–210
 - general governing equation 202–203
 - design consideration 203–204
- piezoelectric pre-biasing 92–94
- piezoelectric transducers 37
 - constitutive equations 38
 - energy extraction cycles 41
 - active cycles 43
 - comparison 43–44
 - rectification cycles 43
 - resistive cycles 41–42
 - maximal power density and figure of merit 44–45
 - physical origin in ceramics and crystals 37–38
 - typical architectures for energy harvesting 39
 - application to typical configurations 40–41
 - modeling 39, 40
- piezoelectric transduction 281–282
- piston/spring arrangements 288
- Planck's blackbody distribution *See* blackbody
- pnictides properties (group 15) 107, 108
- p-n junction and crystalline Si solar cells 363–366
- Poincaré maps 447, 448
- Pointing vector 68
- polycrystalline perovskites thin films
 - energy harvesting with poly-PZT films 136, 137
 - fabrication process 136
- polydimethylsiloxane (PDMS) 350, 358
- polymer solar cell 370–372
- Polytec[®] laser Doppler vibrometer 450
- polyvinylidene fluoride (PVDFs) 141, 234
 - energy harvesters 143
 - structure 141–142
 - synthesis 143
- potassium hydroxide (KOH) etching 289
- power conditioning 85, 385–386
 - commercial products 397, 398
 - converters for ultra-low-output transducers and examples 396–397
 - frequency tuning of electromagnetic harvester 393–395
 - function of 85–86
 - circuits with nonlinear input impedance 90
 - circuits with reactive input impedance 89–90
 - circuits with resistive input impedance 87–89
 - highly dynamic load power 98–99
 - interface to harvester 86–87
 - peak power controllers 96–97
 - peak rectifiers 90–92
 - piezoelectric pre-biasing 92–94
 - system architectures 97–98
 - voltage regulation 94–96
 - power processing for electrostatic devices 397
 - single-supply pre-biasing for piezoelectric harvesters 388–392
 - submilliwatt electromagnetic harvester circuit example 386–388
 - ultra-low-power rectifier and MPPT for thermoelectric harvesters 392–393
- power conversion efficiency 365
- power processing for electrostatic devices 397

propagating modes 71, 72, 73, 76, 79
pull-in force 53

q

quasi-static state 419

r

radiative transfer 323, 324
radial flux 183, 184
Radio Technical Commission of Aeronautics (RCTA) 416
reactive input impedance circuits 89–90
reactive-ion etching (RIE) 208, 210
rectifier 330–331
– 50- Ω antenna 335
– antenna 334–335
– complex conjugately matched antenna 335, 336
– DC output voltage 332–334
– rectenna results 336, 337–338, 339
– RF input impedance 331–332
– voltage up-conversion 339, 340
rectifying antenna, receiving 326,
– antenna–rectifier matching 326–330
reduced damping *See* Scruton number
resonance frequency 211
resonant coupling RF energy transfer system 322
resonant-type harvesters 89
resonator tubes 285
Reynolds number 302–303, 307
Ritz–Galerkin averaging method 332

s

Scruton number 309
Seebeck coefficient 418
Seebeck effect 250, 422
– and nanoscale heat conduction 62–64
self-tuning system 224, 233–234, 241
shake-powered flashlight 176
short-circuit current density 364
silicon-MEMS technology 253–254
single-crystal thin films 137
– energy harvesting with SC perovskite films 137–138
– fabrication process 137
single degree of freedom (SDOF) 215, 216
single-supply pre-biasing 92, 94
single-supply pre-biasing for piezoelectric harvesters 388–392
skutterudites properties 108, 109–110
Snell's law 71
soft-X-ray charged in-plane electrets generator 170–171

sol–gel method 208, 209
sputtering 140
stall flutter 315
static thermoelectric harvester for aircraft seat sensors 427–428
stiffness modification, for frequency tuning 226–227
– using axial force 227–229
– using electrical external spring 231–232
– using external spring 229–231
Strouhal number 307
submilliwatt electromagnetic harvester circuit example 386–388
supercapacitors 405, 406
surface polaritons 72, 73
synchronized switch harvesting on inductor (SSHI) 273
synchronous switched harvesting on inductor (SSHI) 92, 93
system architecture 2
system damping 192–193

t

tachometer 394
tape casting 134
TEGwearTM 263, 264, 265
temperature difference 247, 249, 250, 251, 255, 261, 262, 263, 265
temperature gradient 247, 258, 259, 260, 261
Texas Instruments 398
thermal conductance mismatch 111, 112
thermal conductivity 247, 251
thermalization 79
thermal resistance 251, 252, 257
thermal spray 118
ThermobilityTM 263, 264
thermoelastic damping 193
thermoelectric devices 3
thermoelectric energy harvesting in aircraft 415–416, 419–420
– aircraft standardization 416–417
– applications 427
– – dynamic thermoelectric harvesting prototype 428
– – heat storage thermoelectric harvester for aircraft strain sensors 428, 429–430
– – outlook 430–431
– – static thermoelectric harvester for aircraft seat sensors 427–428
– autonomous wireless sensor systems 417–419
– design considerations 425–427
– dynamic thermoelectric energy harvester 423–425

- static thermoelectric energy harvester 421–423
 - thermoelectric energy harvesting device efficiency 420–421
 - thermoelectric generators (TEGs) 392, 393
 - *see also* micro thermoelectric generators; thermoelectric energy harvesting in aircraft
 - thermoelectric materials 103
 - internal micro/nanostructure and related approaches 114–115
 - thermal expansion and role in materials selection 115–116
 - material synthesis with relevance to micro energy harvesting 116, 117
 - electroplating, electrophoresis, and dielectrophoresis 117–118
 - thin and thick film deposition 118
 - performance considerations in materials selection 103–105
 - chalcogenides properties (group 16) 106
 - crystallogens properties (group 14) 106, 107
 - pnictides properties (group 15) 107, 108
 - skutterudites properties 108, 109–110
 - raw material cost considerations 116
 - scale influence on material selection and synthesis 110, 111
 - bypass heat flow domination 113
 - electrical contact resistances domination 112–113
 - thermal conductance mismatch 111, 112
 - thermoelectric property measurement challenges 113–114
 - thermoelectric power generation
 - heat transfer analysis 64–66
 - nanoscale heat conduction and Seebeck effect 62–64
 - Thermogen technology 259–260
 - thermopile 250, 251
 - thin film 245, 246, 247, 249, 252, 255, 257, 258, 259, 264
 - and thick film deposition 118
 - Thomson effect 420
 - transduction and acoustic energy harvesters 280–281
 - methods 281
 - comparative analysis 283
 - electromagnetic transduction 282
 - electrostatic transduction 282–283
 - piezoelectric transduction 281–282
 - structures 284
 - for acoustical to mechanical transduction 286–288
 - impedance matching 284–285
 - transfer function 15–16
 - tunable resonant systems 224, 225, 240
 - active schemes 225–226
 - mass modification for frequency tuning 232
 - stiffness modification for frequency tuning 226–232
 - passive schemes 232–233
 - modification by coupling axial force with centrifugal force from rotation 234
 - modification by coupling mass position with beam excitation 233–234
 - modification using centrifugal force to toggle beam clamp position 234–235
- u**
- ultra-low-power rectifier and MPPT for thermoelectric harvesters 392–393
 - up-conversion techniques 17, 18
- v**
- variable capacitance 11
 - velocity-damped resonance generator (VDRG) 156, 167
 - vibration-driven electrets generators 166
 - vibration energy harvesting, from wideband and time-varying frequencies 223, 225, 240–241
 - active schemes for tunable resonant devices 225–226
 - mass modification for frequency tuning 232
 - stiffness modification for frequency tuning 226–232
 - device classification 223–225
 - future research directions
 - system size considerations 242
 - tuning range and resolution 241–242
 - tuning sensitivity to driving vibrations 242
 - passive schemes for tunable resonant devices 232–233
 - modification by coupling axial force with centrifugal force from rotation 234
 - modification by coupling mass position with beam excitation 233–234
 - modification using centrifugal force to toggle beam clamp position 234–235
 - wideband devices 235–236
 - multimodal designs 236–237
 - nonlinear designs 237–239
 - Villard cascaded multiplier 333
 - Villari effect 55

- viscid damping 192
 - voice-coil architecture 183, 184
 - vortex shedding devices 307–310
- W**
- wake galloping 313
 - wearable electronics 245, 247, 251, 260, 264, 408
 - wet etching 208, 209
 - wideband systems 224, 225, 235–236, 241
 - multimodal designs 236–237
 - nonlinear designs 237–239
 - windbelt energy harvester 315–316
 - wireless power generator evaluation kit 263
 - wireless pulse oximeter SpO₂ sensor 261–262
 - wireless sensor network, made by
 - vibration-driven wireless nodes 8
 - wireless sensor node (WSN) 86, 99
 - wurtzites
 - doping 141
 - structure 139–140
 - thin films and energy harvesting 140–141
- Z**
- zinc oxide (ZnO) 207
 - electromechanical properties 207
 - ZT meter *See* Harman method