

Index

a

Ab initio (first principles) simulations
461–462

Acceleration methods of computing
Gramians 82–83

Acceleration sensitivity 304

Accelerometer 148–149, 360, 474

- seismic perturbations detection of using
363–370
- battery modeling 368–369
- digital controller in SystemC 365–366
- embedded software, cross-compiled GNU
GCC application for MIPS 369
- timed dataflow model of 359–361
- electrical linear network model of
361–363

Across quantities 26

Additive white Gaussian noise
(AWGN) 366

Algebraic equations 95, 97–102

Analog and mixed signal (AMS) 357–374

Analog hardware description languages
(AHDLS) 4, 11–12, 506

- simulation capabilities 13–14

ANSYS[®], MOR for 343, 425–437

- Arnoldi algorithm model 427
- open problems 432–436
- tonpilz transducer 435
- practice-oriented research 426–429
- programming issues 429–432
- obtaining system matrices from ANSYS
430–431
- partial solve (PSOLVE) 430
- solvers 431–432
- Second Order ARnoldi (SOAR) 428

Antiresonance 327

Application Programming Interface (APIs)
492

Arnoldi algorithm 64, 216, 279, 427–435

Arrayed bent-beam thermal actuator 128

Asymptotic waveform evaluation (AWE) 60

Automated model order reduction
methods 9

b

Balanced realization 70

Balanced system 80

Balanced truncation, motivation of 78

Balancing transformation 78–80

- computation 81–82

Band Arnoldi process 65

Basic electrothermal actuator 127

Basis 57–59

- definition 58
- equivalent definition of 59

BCA (Bit-Cycle Accurate) compliant 365

Beam

- coupled electrothermal model of 138
- electrothermal model of 131–134
- thermomechanical model of 134–136

Behavioral compact models 30

Behavioral model composability 513–515

Behavioral model performance 8

- encoding MEMS behavioral models
508–515
- behavioral model composability
513–515
- behavioral model extensions 512–513
- nonlinear beam 511–512

Bent-beam actuators 128

Biot number 132

Block–Arnoldi algorithm 213, 216–220

Black Box, nonlinear beam 509–511

Block Krylov Subspace 59–60

Block moments 74

Body load contribution vector 297–298

- Boolean equations 96, 102–104
- Boundary model 173–174
- Branch 12
- c**
- Cadence simulation 191
- Cadence Virtuoso's plotting capabilities 420
- Cantilever model 277
- Carbon nanotube (CNT) models 448–450
- Chip/adhesive/package model 153–155
- Circuit model or network model 8
- Circuit-level design for RF MEMS devices 335–355
 - extraction of reduced order model 340–345
 - – extraction procedure 343–345
 - – input function, handling nonlinearities in 341–343
 - – second order ODE systems 341
 - microswitch 351–354
 - reduced order models application in 335–355, *See also* Vibrating devices
 - – model equations for 337–340
 - – Rayleigh mode preserving damping 338
 - – stress stiffening 338
- Circuit-level simulation 348
- Closed loop force-feedback loop 378
- Coefficient of thermal expansion (CTE) 130–131, 152
- Comdrive 265
- Commercial MEMS design environment 461–481
 - accelerometer 474
 - benchmarks 474–476
 - coupled package-device modeling 478–480
 - fluid damping 477
 - inertial gyroscope 474–476
 - IntelliSense's design methodology 467–470
 - IntelliSuite 470–474, *See also individual entry*
 - model order reduction implementations in 461–481
 - – *Ab initio* (first principles) simulations 461–462
 - – layout-based design (bottom-up design) 463–464
 - – schematic or component-based design (top-down design) 462–463
 - – system model extraction (SME) 464–465
 - – system simulation 467
 - – technology CAD (TCAD) 462
 - – verification 465–467
- Communicating synchronous finite state machines (CSFSMs) 366
- Compact model builder 483
- Compact model derivation 29–32
 - behavioral compact models 30
 - compact modeling of MEMS 30–31
 - equivalent network models 30
 - finite network (FN) models 29–30
 - mathematical model order reduction (MOR) 32
 - mixed-level modeling (MLM) 31
 - Physics-based compact models 31
- Compact modeling of MEMS 8, 30–31, 192–194, *See also* RF-MEMS devices, compact modeling of
 - behavioral compact models 30
 - equivalent network models 30
 - Physics-based compact models 31
- Complementary variables 117
- Complex matching 328–330
 - consequence of matching 331–332
 - real matching 330–331
- Complex matrix-valued function 62
- Complex Navier-Stokes equations 170
- Component mode synthesis (CMS) 427
- Component, terminology 8
- Composable model libraries 14–15
- COMSOL 454–457
- Constraint mechanical systems (CMS) 99
- Controllability 68–69
 - controllability (of a state) 68
 - controllability Gramian 68
- Coriolis forces 293, 299–300, 397
- Correction factors 175
- Cosimulation 110–112
 - cosimulation interface 112
 - coupling algorithms 111–112
- Cosimulation aspects 357–374
- Coupled electrothermal model, equivalent circuit of 137–138
 - of a beam 138
- Coupled multiphysics microsystems 4–6
 - multiscale modeling and simulation hierarchy 6
 - sampling of 5
- Coupled package-device modeling 478–480
- Coupling algorithms 111–112
- CoventorWare™ 149–150
- Current 101

d

- 3D parametric-library-based MEMS/IC design 407–423
 - 3D parametric library for MEMS design–MEMS+[®] 409–415
 - 3D design entry 409–410
 - integration with EDA tools 414–415
 - integration with MATLAB and Simulink 413–414
 - integration with Simulink 413–414
 - integration with system simulators 412–413
 - MEMS model library 410–412
 - micromirror array design example 419–422
 - obstacles to widespread adoption 408
 - toward manufacturable MEMS designs 415–419
 - free parameter in MEMS design 415
 - parameterization of process and material properties 415–418
 - process design kits 418–419
- De facto* standard 14
- Deep reactive-ion etching (DRIE) 488
- Deflation 64
- Degrees of freedom (DOFs) 7, 164
- Delays 358
- Delta cycles 110
- ‘Device level’ continuous-field models 19
- Differential algebraic equations (DAEs) 53, 96, 450–453
- Differential equations of MEMS models 97–102
- Digital controller in SystemC 365–366
- Digital light processing (DLP) projection system 419
- Digital micromirror device (DMD) 419
- Dirichlet boundary condition 215
- Discontinuous forcing functions 114–116
- Discrete empirical interpolation method (DEIM) 237, 250–255
- Display 360
- Distributed effects in microsystems, modeling of 163–187, *See also* Squeeze film damping (SQFD) in MEMS modeling
 - mixed-level approach for 163–187, *See also* Mixed-level modeling (MLM)
- Distributed nodal method (DNM) 151
- Dominant modes 302
- Doubly fixed beams 148
- Dynamic pull-in voltage 268

e

- Electrical linear networks (ELNs) 357, 361–363
- Electrical stiffness 342
- Electrofluidic Kirchhoffian network 28
- Electromechanical sigma–delta modulators for inertial MEMS sensors 377–401, *See also under* Inertial MEMS sensors
- Electrostatic driving principles for MEMS 263–287
 - dynamic pull-in voltage 268
 - examples
 - electrostatic micropump diaphragm 281–285
 - IBM scanning-probe data storage device 275–281
 - plate model formulation 282–284
 - linear MOR for 263–287
 - model order reduction methods 269–274
 - for nonlinear systems 272–274
 - parametric systems 272
 - polynomial projection 273–274
 - representation of nonlinearities 270
 - second-order linear systems 270–272
 - systems with few nonlinearities 272
 - systems with many nonlinearities 273
 - systems with nonlinear inputs 272
 - training input 274
 - trajectory piecewise-linear (TPWL) method 274
 - nonlinear MOR for 263–287
 - phase space 268
 - pull-in 266–268
 - pull-in voltage 267
 - regimes of the trajectory 268–269
- Electrostatically actuated micropump
 - physics-based electrofluidic compact model of 32–41
 - membrane drive 34–36
 - micropump 39–40
 - model calibration 40–41
 - parameter extraction 40–41
 - tubes 38–39
 - valves 36–38
- Electrostatically actuated RF MEMS switch 41–48
- Element integration 156–157
- Element Menu Window (EMW) 451
- Embedded Linux file (ELF) 366
- Embedded Software, Cross-Compiled GNU GCC Application for MIPS 369
- Energy harvesting modules, system-level simulation of 313–333
 - experimental results 318

- Energy harvesting modules, system-level simulation of (*contd.*)
 - micropower module 315–316
 - modeling and simulation 318–327
 - – finite element method (FEM) model 320–321
 - – harmonic MEMS circuit cosimulation 325–327
 - – lumped element modeling 319–320
 - – model order reduction 322–323
 - – piezoelectric energy harvester 319
 - – transient MEMS circuit cosimulation 323–325
 - piezoelectric harvester, maximum power point for 327–332
 - – complex matching 328–330
 - – consequence of matching 331–332
 - – real matching 330–331
 - vibrational harvesters 316–317
 - wireless autonomous sensor nodes 314–315
 - Energy storage system (ESS) 313–315
 - Equation of motion 440–444
 - Equivalent circuit method 136
 - Equivalent network models 30
 - Etch holes 447
 - Euler–Bernoulli beam theory 154
 - Events 113
 - Expansion points, different choices of 75–76
- f**
- Feedback control system 378
 - Feedback linearization 395–396
 - Fill_table(...) function 369
 - Fingers 513
 - Finite element analysis/method (FEA/FEM) 126, 147, 320–321, 337
 - FEM-based spatial discretization 215
 - Finite networks (FNs) 29–30, 163–164, 170–173
 - Finite state machines (FSMs) 96, 102–104
 - Fluid damping 477
 - Fluidic systems 99–100
 - Fraunhofer EMFT 32
 - Function block 389
 - Functional mock-up interface (FMI) 112
- g**
- Galerkin method 73, 84, 134, 243
 - ‘Gappy-least-squares’ approximation 250
 - Gas rarefaction effects 175–177
 - Gaussian pulse module 360–361
 - Gauss-Seidel iteration 111
 - Generalized Kirchoff’s current law (GKCL) 25–26
 - Generalized Kirchoffian network 43–44
 - Generic modeling approach for microdevices and systems 21–23
 - Gramian-based MOR methods 77–83, 239
 - acceleration methods of computing the Gramians 82–83
 - balanced system 80
 - balanced truncation, motivation of 78
 - balancing transformation 78–80
 - – computation 81–82
 - error bound of 84–85
 - extension to more general systems 83
 - passivity of 84–85
 - square-root algorithm (SR-method) 82
 - stability of 84–85
 - truncation 80–81
 - Gram-Schmidt process 63–64
 - Graphical user interface (GUI) to SUGAR 444, 450–451
 - Graphical Window (GW) 451
 - Guyan reduction 427
 - Gyros 149
 - Gyroscopic matrix 300
- h**
- Hall sensors 150
 - Hankel singular values (HSVs) 70
 - Hardware description language (HDL) 20, 213, 344, 489
 - Harel state charts 103
 - Harmonic distortion 258–259
 - Harmonic MEMS circuit cosimulation 325–327
 - Heterogeneous modeling with SystemC AMS 358–363, *See also under* SystemC AMS
 - Hexpresso 469
 - Hierarchically nested states 104
 - High-dimensional equation systems 108
 - Higher order electromechanical $\Sigma\Delta M$ 391–400
 - band-pass $EM\Sigma\Delta M$ approach 399
 - for MEMS accelerometer 391–397
 - – advanced model 396–397
 - – design methodology 391–392
 - – example design 392–395
 - – feedback linearization 395–396
 - for MEMS gyroscopes 397–400
 - Hole model 174–175
 - Homotopy 108
 - Hybrid systems 113

i

- Index reduction 109
- Induced norm 62
- Inertial gyroscope 474–476
- Inertial MEMS sensors 377–401, *See also*
 - Higher order electromechanical $\Sigma\Delta M$;
 - Second order electromechanical $\Sigma\Delta M$
- electromechanical sigma–delta modulators
 - for, system level modeling of 377–401
- – feedback control system 378
- Initial state (z_0) 103
- Initial state of the system 67
- Initialize() function 361
- In-plane actuators 127–129
- Input alphabet (X) 103
- Integrated circuit (IC) systems 483–498
- IntelliSense’s design methodology
 - 467–470
 - closing the loop 469–470
 - one step at a time 468–469
 - from the top down 467–468
- IntelliSuite, system model extraction in
 - 470–474
 - high-LEVEL overview 470–471
 - implementation 473–474
 - lookup table (LUT) 471
 - residual stress and film damping effects, capturing 471–472
- Intellisuite™ 150
- Internal variables 106

k

- Kirchhoff’s current law (KCL) 25, 101, 171
- Kirchhoff’s flow law (KFL) 12
- Kirchhoff’s mesh rule 12
- Kirchhoff’s node rule 12
- Kirchhoff’s potential law (KPL) 12
- Kirchhoff’s voltage law (KVL) 101
- Kirchhoffian networks, system-level modeling using 19–48
 - basic principles 19–48
 - compact model derivation 29–32
 - from continuous-field level to compact models 23–29
 - generalized Kirchhoff’s current law (GKCL) 25
 - generalized networks for tailored system-level modeling of microsystems 20–32, *See also individual entry*
- Knudsen numbers 176
- Kronecker product 240
- Krylov-subspace methods 59, 215, 219, 239, 271, 314, 431

l

- Lagrange equations 98
- Lanczos algorithm 216
- Laplace transform 60
- Laplace variable 229
- Laser Doppler vibrometer (LDV) system 159
- Limiter block 389
- Linear independence 57–60
- Linear mechanical systems 295–297
- Linear model order reduction, for MEMS electrostatic actuators 263–287, *See also* Electrostatic driving principles for MEMS
- Linear system theory 66–71
 - balanced realization 70
 - controllability 68–69
 - observability 68–69
 - passivity of a system 70–71
 - realization theory 69–70
 - stability of a system 70–71
 - transfer function 66–67
 - two different LTI systems, measure of the difference between 67–68
- Linear time-invariant (LTI) systems 56
- Lithographie, Galvansformung, Abformung (LIGA) technology 125
- Long-short beam actuator 128–129
- Long-short-beam thermal microactuator 128
- Lumped element models 8, 30–31, 101, 198–201, 319–320
- Lyapunov equations 81

m

- Macromodeling 8, 30, 104–105
- Markov parameters 75
- Mass flow rate 100
- Master algorithms 112
- Mathematical model order reduction (MOR) 32
- Mathematical structure of MEMS models 96–104, *See also* Numerical methods for system-level simulation
 - algebraic equations 97–102
 - Boolean equations 102–104
 - differential equations 97–102
 - finite state machines 102–104
 - fluidic systems 99–100
 - hierarchically nested states 104
 - Lagrange equations 98
 - mass flow rate 100
 - model behavior 97
 - multibody system (MBS) 98–99
 - networks 101–102
 - solution of the DAE system 97

- Mathematical structure of MEMS models
 - (*contd.*)
 - terminal behavior 97
 - terminal variables 97
- MATLAB 413–414
- Matlab/Simulink 304–306
- Matrix function norms 62–63
- Matrix norms 61–62
- Matrix 57
- Maximum power point (MPP) principle 313
- McMillan degree of the system 69
- Mealy machines 103
- Membrane drive 34–36
- MEMS-Synth 469
- Microbeam model 152–153
- Microhotplates 214, 220–223
- Micromirror array design 419–422
- Cadence Virtuoso’s plotting capabilities 420
- Micropower module 315–316
- Micropump, physics-based system-level model of 39–40
- Microswitch 351–354
- Microsystems modeling, issues in 3–17
 - analog hardware description languages 11–12
 - automated model order reduction methods 9
 - composable model libraries 14–15
 - – *de facto* standard 14
 - coupled multiphysics microsystems 4–6
 - handling complexity, following the VLSI paradigm 10–11
 - – view 10
 - model validation 15–16
 - model verification 15–16
 - multiscale modeling and simulation 6–7
 - parameter extraction 15–16
 - system-level model
 - – general attributes of 12–13
 - – terminology 7–9
 - system-level models for microsystems 3–4
- Minimal realization of the system 69
- Mixed-level modeling (MLM) 15, 31, 163–164
 - alternative damping models, comparison with 185–186
 - evaluation 179–180
 - – numerical evaluation 179–180
 - experimental evaluation 180–185
 - of squeeze film damping in MEMS 169–179
 - – automated model generation 178–179
 - – coupling with mechanical models 177–178
 - – finite network-based evaluation of the Reynolds equation 170–173
 - – gas rarefaction effects 175–177
 - – motivation for using 168–169
 - – physics-based lumped element models 173–175
 - – total damping force calculation 177
- Mixed-mode simulation 7
- Mixed-signal systems 109–110, 113
- Modal-superposition (MSUP)-based nonlinear MOR for MEMS gyroscopes 291–308, *See also* Reduced order model generation pass algorithms
 - extraction of capacitances 301–302
 - – analytical approach 301
 - – for comb cell conductors and platelike capacitors 301–302
 - – hybrid approach 301
 - – numerical approach 301
 - flow chart of 294–295
 - – expansion pass 294
 - – generation pass 294
 - – master nodes 294
 - – use pass 294
 - multivariable capacitances, data sampling and function fit procedures for 302–304
 - system simulations of MEMS based on modal superposition 304–307
 - – based on Kirchhoffian networks 306
 - – full order FEM models 306–307
 - – Matlab/Simulink 304–306
 - theoretical background of 295–299
 - – body loads of capacitive sensors 297–298
 - – linear mechanical systems 295–297
 - – nonlinear electromechanical interactions 297–298
 - – parametric reduced order models for packaging interactions 298–299
- vibratory gyroscope 293–294
- Model behavior 97
- Model description languages 105–107
- Model order reduction (MOR) 4, 108, 238, 269–274, 322–323, *See also* ANSYS®, MOR for; Electrostatic driving principles for MEMS; Gramian-based model order reduction
 - basic idea of 71–73
 - expansion points, different choices of 75–76
 - moment-matching 73–77
 - – moments and moment vectors 73–74

- – projection matrices Wand V , computation of 74–75
 - Model order reduction (MOR), system-level modeling of MEMS by means of 53–87
 - applied to electrothermal simulation 54
 - Gramian-based MOR methods 55
 - linear system theory 66–71
 - mathematical background 53–87
 - mathematical preliminaries 56–66
 - – basis 57–60
 - – Block Krylov subspace 59–60
 - – Krylov subspace 59
 - – Laplace transform 60
 - – linear independence 57–58
 - – matrix 57
 - – norms 61–63
 - – orthogonality of the vectors 58
 - – rational function 60–61
 - – scalar 57
 - – subspace 57–58
 - – vector 57
 - – vector space 57–58
 - model order reduction, basic idea of 71–73
 - moment-matching MOR 73–77
 - nonlinear systems 86
 - nonzero initial condition 85–86
 - numerical algorithms 63–66
 - parametric systems 86
 - reduced model, stability, passivity, and error estimation of 84–85
 - for second-order systems 86
 - Model validation in microsystems modeling 15–16
 - Model verification in microsystems modeling 15–16
 - Modeling formalisms (MFs) 357
 - Models of computation (MoCs) 357
 - Modified Gram-Schmidt process 63–64
 - Moment-matching-based linear MOR 213–234
 - Moment-matching model order reduction 73–77, *See also* Model order reduction (MOR)
 - development of 76–77
 - error bound of 84
 - Padé approximation 76
 - passivity of 84
 - stability of 84
 - Moments of transfer function 73
 - Moore machines 103
 - Multibody system (MBS) 98–99
 - Multidimensional moment matching 229
 - Multifeedback and local resonators (MFLRs) architecture 398
 - Multilayer pads 447
 - Multiparameter moment-matching 229
 - Multiscale modeling 6–7, 108
- n**
- Nanohub 502
 - Navier-Stokes equations 166–167, 170, 175
 - NEMS 448–450
 - Netlist Window (NW) 451
 - Nètwork method 98
 - Network on Chip (NoC) 366
 - Networks 101–102
 - current 101
 - Kirchhoff's current law (KCL) 101
 - Kirchhoff's voltage law (KVL) 101
 - lumped elements 101
 - voltage 101
 - Newton iteration 111
 - Newton-Raphson iterations 108
 - NODal Design of Actuators and Sensors (NODAS) 506
 - Nodal model of microbeam element 152
 - Node voltages 101
 - Nonlinear DAEs, solution of 107–109
 - Nonlinear model order reduction, for MEMS electrostatic actuators 263–287, *See also* Electrostatic driving principles for MEMS
 - Nonlinear Navier-Stokes equations 170
 - Nonlinear transmission-line model 246–247
 - Nonzero initial condition 85–86
 - Norms 61–63
 - induced norm 62
 - matrix norms 61–62
 - operator norm 62
 - subordinate matrix norm 62
 - vector norms 61–62
 - Numerical algorithms 63–66
 - Arnoldi algorithm 64–65
 - Band Arnoldi process 65
 - deflation 64
 - Gram-Schmidt process 63–64
 - modified Gram-Schmidt process 63–64
 - Numerical methods for system-level simulation 107–112
 - mixed-signal simulation cycle 109–110
 - nonlinear DAEs, solution of 107–109
 - – choice of tolerances 108
 - – high-dimensional equation systems 108
 - – homotopy 108
 - – index reduction 109
 - – model order reduction 108
 - – stiffness and multiscale systems 108

o

Observability 68–69
 – observability Gramian 68
 – observability (of a state) 68
 One-end fixed beams 148
 Open circuit condition 327
 Open Core Protocol (OCP) 365
 Operator norm 62
 Optical-based microsystems 6
 Order of the Krylov subspace 59
 Order of the reduced model 250
 Ordinary differential equations (ODEs) 53,
 95, 131, 164, 215, 337
 Orthogonality of the vectors 58
 Out-of-plane actuators 129
 Output alphabet (Y) 103
 Output function (g) 103
 Oversampling ADC 379

p

Packaging effects of MEMS devices,
 system-level modeling of 147–160
 – element integration 156–157
 – FEM and experimental validation
 157–160
 – impact on typical MEMS devices
 148–150
 – – accelerometers 148–149
 – – doubly fixed beams 148
 – – fine meshing 150
 – – gyros 149
 – – hall sensors 150
 – – one-end fixed beams 148
 – – pressure sensors 149
 – – solid modeling 150
 – – thermal actuators 149
 – single substructures, behavioral modeling
 of 152–156
 – support model 155–156
 – – nodal model 156
 – system partitioning 151–152
 Packaging interactions, parametric reduced
 order models for 298–299
 Padé approximation 76, 271
 Padé via Lanczos (PVL) 77
 Parameter extraction in microsystems
 modeling 15–16
 Parametric electrothermal MEMS models
 213–234
 Parameterization 13, 492–494
 Parameterized Arrays 447–448
 Parametric model order reduction (pMOR)
 213, 228–230, 295
 – moment-matching-based linear MOR for
 213–234
 – – application of 223–227
 – – application to extraction of thin-film
 thermal parameters 227–232
 – – DOT[®] (Design Optimization Tools) 231
 – – parameter extraction methodology
 230–232
 – for packaging interactions 298–299
 Partial differential equation (PDE) 53, 95,
 131, 164, 337
 Partial solve (PSOLVE) 430
 Passivity of a system 70–71
 Periodic AC analysis 14
 Periodic steady-state analysis 14
 Periph_io_get() 369
 Periph_io_set() 369
 Petrov-Galerkin projection 72, 84
 Phase space 268
 Physical design kits 13
 Physics-based compact models 8, 19, 31–41,
See also under Electrostatically actuated
 micropump
 Physics-based lumped element models
 173–175
 – boundary model 173–174
 – hole model 174–175
 Piezoelectric energy harvesters 316–317
 Piezoelectric generator 317–318
 – design of 317–318
 – fabrication of 317–318
 Piezoelectric harvester, maximum power point
 for 327–332
 Poiseuille flow 172
 Polynomial projection 273–274
 Power spectral density (PSD) of output
 bitstream 385
 Pressure sensors 149
 Primitive behavioral model 8
 Probe-based microsystems 6
 Process design kits (PDKs) 418–419
 Processing() function 358, 361, 365
 Projection-based nonlinear model order
 reduction 237–260
 – discrete empirical interpolation method
 (DEIM) 250–255
 – – thermal analysis 251–253
 – evaluation cost for 239–240
 – harmonic distortion 258–259
 – problem specification 238
 – projection principle 239–240
 – pull-in effect 256–258
 – – generalizing from training inputs 258
 – Taylor series expansions 240–245

- – microfluidic channel example 241–242
- – model reduction via quadratic Taylor expansion 242–244
- – stability issues 244
- trajectory piecewise-linear method 245–250
- – nonlinear transmission-line model 246–247
- Proper orthogonal decomposition (POD) methods 55, 239
- Pseudo bimorph electrothermal actuator 127
- Pseudo-linear relation 22
- PSugar 450
- Pull-in effect 256–258
- q**
- Quadratic Taylor expansion, model reduction via 242–244
- Quadrature phase shift keying (QPSK)-modulated 364–367
- Quantization noise loop transfer function (QNTF) 385–386
- Quantizer block output 381
- r**
- Radio-frequency (RF) switches 3–5
- Rates 358
- Rational function 60–61
- Rational interpolation 75
- Rayleigh mode preserving damping 338
- Real matching 330–331
- Realization theory 69–70
- Reduced order modeling (ROM) of MEMS 8, 19, 483–498, *See also* SoftMEMS simulation environment
 - applications 494–498
 - error estimation of 84–85
 - generation pass algorithms 299–304
 - – extraction of body load contribution vectors for 299–301
 - MEMS development environment 484–485
 - passivity 84–85
 - stability 84–85
- Reference node 101
- Relevant modes 302
- Resistance Inductance Capacitance (RLC) 361
- Resistivity 130
- Reynolds equation-based modeling strategies 166–167
 - based on decomposition into cells 167
 - based on FEM 167
 - based on GKN theory 167
 - based on modified Reynolds equation 167
 - finite network-based evaluation of 170–173
- RF-MEMS devices, compact modeling of 191–208
 - RF-MEMS multistate attenuator parallel section 194–205
 - – lumped element network 198
 - whole RF-MEMS multistate attenuator network 205–207
- s**
- Scalar variable 57
- Scaling factor 472
- Second Order ARnoldi (SOAR) 428
- Second order electromechanical $\Sigma\Delta$
 - for a MEMS accelerometer 380–391
 - – advanced model 386–391
 - – basic model 380–386
 - – function block 389
 - – limiter block 389
 - – power spectral density (PSD) of output bitstream 385
 - – switch block 382
- Second-order linear systems, MOR methods for 270–272
- Second order ODE systems 341
- Seismic perturbations detection using accelerometer 363–370
- Serendi-CDI 501–504
- Sigma-delta modulators ($\Sigma\Delta$) 378–379, *See also* Second order electromechanical $\Sigma\Delta$
- Signal-flow model (or block-diagram model) 8
- Silicon-based microhotplate 220–223
- SIMPLORER[®] 223–225
- SIMULINK 413–414, 454–457
- Single substructures, behavioral modeling of 152–156
 - chip/adhesive/package model 153–155
 - microbeam model 152–153
- Single-input multiple-output (SIMO) system 56, 75
- Single-input single-output (SISO) system 56, 217
- Singular value decomposition (SVD) 239
- SoftMEMS simulation environment 485–494
 - implementation within 485–494
 - issues with 486–487
 - – range of validity of the model 487

- SoftMEMS simulation environment (*contd.*)
 - spatial resolution 486
 - temporal resolution 487
 - model output 492
 - modeling abstraction levels 486
 - modeling process 490–491
 - modeling requirements within 485–494
 - models and inputs 487–490
 - parameterization 492–494
 - Solution of the DAE system 97
 - Solvers 431–432
 - Source stepping 116
 - Sparse Lyapunov equations 83
 - Specific heat 130
 - Spectre-Verilog A model 279
 - SPICE (Simulation Program with Integrated Circuit Emphasis) 104–105, 137, 454–457
 - essential features of 105
 - subcircuits in 105
 - Spring force 472
 - Square-root algorithm (SR-method) 82
 - Squeeze film damping (SQFD) in MEMS modeling 165–169
 - mixed-level modeling of 169–179, *See also individual entry*
 - Reynolds equation-based modeling strategies 166–167
 - based on decomposition into cells 167
 - based on FEM 167
 - based on GKN theory 167
 - based on modified Reynolds equation 167
 - Stability of a system 70–71
 - State charts 96
 - State diagrams 102
 - State of the system 67
 - State set (Z) 102
 - State-space representation 56, 215
 - State-space transformation 69
 - Static random access memory (SRAM) 419
 - Stiffness 108
 - Stress stiffening 338
 - Structured model 8
 - Subcircuits in SPICE 105
 - Subordinate matrix norm 62
 - Subspace 57–58
 - SUGAR, for MEMS 439–458
 - compact modeling building blocks for designing 443
 - differential algebraic equations (DAEs) 450–453
 - equation of motion 440–444
 - model 440
 - nodes 440
 - parameters 440
 - simulation 453–454
 - SUGAR, COMSOL, SPICE, SIMULINK, integration of 454–457
 - SUGAR-based applications 444–454
 - accelerometers 444
 - common ground tracers 445–447
 - design/simulation 445
 - etch holes 447
 - GUI configuration 450–451
 - gyroscopes 444
 - layout generation 445
 - library 444
 - microgrippers 444
 - multilayer pads 447
 - NEMS 448–450
 - optimization 448
 - parameterized arrays 447–448
 - PSugar 450
 - RF-MEMS 444
 - thermal actuators 444
 - verification 457
 - Superposition 427
 - Support model effect on MEMS devices 155–156
 - Surface micromachined beamlike electrothermal microactuators 125–143
 - classification and problem description 127–131
 - arrayed bent-beam thermal actuator 128
 - bent-beam actuators 128
 - in-plane actuators 127–129
 - long-short beam actuator 128–129
 - out-of-plane actuators 129
 - coupled electrothermal model, equivalent circuit of 137–138
 - material properties 129–131
 - coefficient of thermal expansion 130–131
 - resistivity 130
 - specific heat 130
 - thermal conductivity 129–130
 - modeling 131–136
 - electrothermal model of a beam 131–134
 - thermomechanical model of beam 134–136
 - solving 136–139
 - system-level modeling of 125–143
 - Switch block 382
 - System in package (SiP) 147

- System model extraction (SME) 464–465
- System partitioning 151–152
- SystemC AMS 357–374
 - heterogeneous modeling with 358–363
 - – 2.4 GHz RF transceiver 366–368
 - – SystemC AMS timed dataflow (TDF) 358–359
 - – timed dataflow model of accelerometer 359–361
- System-level modeling of MEMS 53–87, 506–507, *See also under* Model order reduction (MOR); Packaging effects of MEMS devices; Surface micromachined beamlike electrothermal microactuators
 - algorithmic approaches for 95–118, *See also* Mathematical structure of MEMS models
 - – advanced simulation techniques 113–118
 - – complementary variables 117
 - – discontinuous forcing functions 114–116
 - – emerging problems 113–118
 - – hybrid or mixed-signal systems 113
 - – model equations, structural changes in 116–118
 - description 104–107
 - – general approaches for 104–107
 - – macromodeling 104–105
 - – model description languages 105–107
 - – SPICE (Simulation Program with Integrated Circuit Emphasis) 104–105
 - – general attributes of 12–13
 - – for microsystems 3–4
 - – terminology 7–9
 - – – behavioral model 8
 - – – circuit model or network model 8
 - – – compact model 8
 - – – component 8
 - – – lumped-element model 8
 - – – macromodel 8
 - – – physics-based model 8
 - – – primitive behavioral model 8
 - – – reduced-order model 8
 - – – signal-flow model (or block-diagram model) 8
 - – – structured model 8
 - using generalized Kirchhoffian networks 19–48, *See also* Kirchhoffian networks
- t**
 - Tailored system-level modeling, generalized Kirchhoffian networks for 20–32
 - generic modeling approach for microdevices and systems 21–23
 - pseudo-linear relation 22
 - Tanner’s C-code modeling 489
 - Taylor series expansions 240–245
 - quadratic Taylor expansion, model reduction via 242–244
 - TDF cluster 358
 - Technology CAD (TCAD) 462
 - Terminal behavior 97
 - Terminal variables 97
 - Thermal actuators 149
 - Thermal conductivity 129–130
 - Timed dataflow model of accelerometer 359–361
 - Timestep 358
 - Tire pressure monitoring systems (TPMS) 483
 - Total damping force calculation 177
 - Training input 274
 - Trajectory piecewise-linear (TPWL) 237, 245–250, 264, 274, 285
 - nonlinear transmission-line model 246–247
 - stability issues 247–249
 - Transfer function 66–67
 - Transient MEMS circuit cosimulation 323–325
 - Transition function (f) 103
 - Truncated-balanced realizations (TBRs) 244
 - Truncation 80–81
 - Tubes, system-level model of 38–39
- u**
 - UML behavioral state machines 103
 - Unsymmetric Lanczos process 74
 - U-shaped actuator 127
 - U-shaped principle 125
- v**
 - Valves, compact model of 36–38
 - Variable gap parallel plate capacitor 264–269
 - Vector function norms 62–63
 - real valued vector function 62
 - Vector norms 61–62
 - Vector space 57–58
 - Vector 57
 - VerilogA compact models 196–201
 - VerilogA model 352
 - Very high speed integrated circuit hardware description language–analog and mixed-signal extensions (VHDL-AMS) 106
 - Very-large-scale integration (VLSI) 4, 10–11
 - in handling complexity 10–11

- Vibrating devices 345–351
- Vibrational harvesters 316–317
- Vibratory gyroscope 293–294
- Viscous force 472
- Voltage 101
- Volterra method 240

- W**
- Wafer level package (WLP) 147
- Web-based community for MEMS modeling and design 501–515
 - concepts of web-based design 503–504
 - design community constitution 504–505
 - discussion forums 505
 - online simulation tools 505
 - open source philosophy 504
 - wiki-style collaborative authoring 505
 - encoding MEMS behavioral models 508–515
 - nonlinear beam 509–511
 - leveraging web-based communities 502–505
 - Designer’s Guide Community 502
 - Nanohub 502
 - Serendi-CDI 502
 - MEMS modeling and design online 505–508
 - system-level modeling of MEMS 506–507
 - web-based community conventions 507–508
- White Noise block 381
- Wireless autonomous sensor nodes 314–315
- Wireless sensor network (WSN) 357