

Index

a

- acrylate elastomer with polyester
 - thermoplastic, 284
- acrylate rubbers, 264, 283, 284
 - with iPP thermoplastic, 283
 - PMMA, 268
- acrylic acid-modified isotactic polypropylene, 171
- acrylic rubber, 316
- acrylonitrile, 258, 305
 - butadiene copolymer elastomers (NBR), 257
 - butadiene copolymer rubber (NBR), 280
 - butadiene rubber, 44, 356
- acrylonitrile butadiene styrene (ABS), 168, 235, 391, 444
 - resins stiff, 264
- acrylonitrile–(ethylene–propylene–diene terpolymer)–styrene, 264
- acrylonitrile–styrene–acrylic ester, 264
- activation stress, 237
- actual temperature, 55
- Adam–Gibbs model, 14, 31, 36
- additives, 232
 - value, 392
- additivity properties, 393
- adhesion, polymer blends, 136
- adhesive force, 349
- ad hoc assumptions, 14
- adsorption/disruption equilibrium, 462
- Aerosil-OX50, 408
- Aerosil-R812, 408
- Aerosil-R972, 408
- Aerosil-300, TEM micrograph, 409
- Aerosol-300, 408
- Aerosol-380, 408
- AFM phase images, 220
 - SBR/NR 50/50 vulcanizate, 321
- agglomeration, 230, 280
- aggregation, of matter, 29
 - Ajji–Choplin’s modified, 423
 - alcohol-treated TiO₂ (T)
 - on PP/PET blend morphology, 467
 - alkali counter ions, 403
 - alkyl ammonium ions, 403
 - ammonium ion chain arrangement, 404
 - amorphous–amorphous interaction, 141
 - amorphous component, 139, 146
 - determination, 143
 - glass transition, 163
 - interlamellar regions, 147
 - amorphous component, diffusion rate
 - segregation, 143
 - amorphous–crystalline interfaces, 42, 108
 - amorphous diluent, 139, 202
 - influences, 201
 - amorphous elastomers, 286
 - amorphous ethylene–propylene copolymers, 286
 - amorphous halo, 7
 - amorphous materials, reversible transformation, 1
 - amorphous matrix
 - crystallizable dispersed phase, 164
 - amorphous medium-cis-BR, 262
 - amorphous phase, 158
 - in semicrystalline, microstructure of, 108
 - amorphous rubbers, 273
 - amorphous systems, 7
 - angular frequency, 61
 - annealing, 354, 375
 - anomalous supermolecular behavior, 33
 - antiplasticization effects, 43
 - antiplasticizers, 43
 - Arrhenius diagram, 66
 - Arrhenius equation, 148
 - Arrhenius prefactor, 13
 - aryl polyesters, 113
 - Askadskii monograph, 342

- asymmetric PS/PVME blends
 - schematic phase diagram, 430
- atomic force microscopy (AFM), 138, 215, 240, 301, 370, 428
- atom transfer radical polymerization (ATRP), 424
- average equivalent diameter of PMMA phase, influence of the PP phase concentration on, 381
- average viscosity ratio, 364
- Avogadro number, 15
- Avrami analysis, 213
- Avrami equations, 149, 150, 207
- Avrami exponent, 150, 207
- Avrami index, 149
- Avrami model, 148
- Avrami plot, 148

- b**
- ballistic conduction, 407
- banded PVDF spherulites crystallized, 157
- BCKV model equation, 83, 93
- BDT temperature, 242
- bell-shape curve, 145
- Benabdelghani, 103
- binary blends, 347, 380
 - morphological types in, 347
- binary Flory–Huggins interaction parameters, 345
- binary interactions, asymmetry of, 339
- binary miscible crystalline polymer blends, 201
- binary mixtures, 137, 335
- binary polymer mixtures, 335
 - glass-transition signals of, 73
- binary PP/PS system, 354
 - mixtures, 383
- binary to ternary PMMA/PS/PC morphologies, transition from, 369
- binodal temperature (BT), 416
- bio-based PTT/PEEA blends, 171
- biopolymers, 169
- bis-(diisopropyl) thiophosphoryl disulfide, 322
- bisphenol A polycarbonate, 156
- bis-(triethoxysilylpropyl)-tetrasulfane, 317
- blending, 229, 230, 299
 - BR/CIIR, 318
 - BR/EPDM, 302, 307, 311
 - BR/IR, 318, 319
 - BR/NBR, 319
 - BR/NBR 50/50, 319
 - BR/NR, 318
 - BR/SBR, 310
 - composition, 196, 358, 379
 - made during polymerization, 285
 - miscibility, 139
 - morphology, 66, 364, 365
 - PE/SBR, 362
 - polymer pairs, viscosity difference, 441
 - ratios, 306
 - spherulites, formation of, 197
- blend PMMA/PP/PS/HDPE displaying partial wetting, topographical images of, 376
- blends containing
 - BR, 318
 - butyl rubber, 323
 - CR, 325
 - EPDM, 322
 - hydrogenated nitrile butadiene rubber (HNBR), 327
 - natural rubber, 311
 - NBR, 324
 - SBR, 319
 - silicone rubber, 326
- blend structure, three dimensional view, 373
- block copolymers, 171, 263, 316
- block polymers, 288
- Boltzmann constant, 13
- Boltzmann relation, 31
- bona fide phase transitions, 3
- Boson peak frequency, 15
- Brabender mixer, 307
- Bragg's law, 409
- Braun–Kovacs equation, 111
- brittle fracture, 238
- brittle mechanism, 234
- brittle plastics, 230
- brittle-to-ductile transition (BDT), 236
- BR molecular chains, 302
- Brownian diffusion
 - coefficient, 434
 - time, 437
- Brownian induced motion, 462
- Bässler-type expression, 26
- butadiene, 320
 - acrylonitrile copolymers, 286
 - based core elastomers, 287
 - styrene block copolymers, 288
- butadiene copolymer elastomers (NBR), 324, 390
 - AN level, 258
 - elastomer with iPP thermoplastic, 283
 - EPDM blends, 325
 - NR/CB compounds, 325
 - PVC blends, 259
 - PVC design, 260
- butene-1 (EBR) copolymers, 273

- butene-1 dissolve, 273
- butyl, and ethylene/octene-1 copolymers, 235
- butyl lithium processes, 285
- butyl rubber (IIR), 283, 323
 - elastomer with polypropylene thermoplastic, 283
- c**
- C15A, concentration, 455
- calorimetric analysis, 80
- calorimetric methods, 245
- calorimetric techniques, 52
- calorimetry, 52
- capacitance, 64
- carbon black (CB), 302
- carbon chloride bond, 38
- carbon nanofibers, 44
- carbon nanotubes (CNTs)
 - single- and multiwalled, 402
- carboxylic MWCNT-filled polylactide melts
 - Han plots, 414
- carboxyl-terminated NBR, 283
- case studies, 99
- cation-exchange capacity (CEC), 404
- cationic–organic surfactant, 403
- cavitation, 239
- cavitation process, 237
- cavitation stresses, 238
- CB-filled blend, 465
 - BR/EPDM, 319
- CB localization, 443
- cellulose nitrate, 257
- chain mobility state, 58
- Charpy impact strength, 260
- chemical modification, 101
 - of CNTs, 317
- chemical potential, 341
- chemical structure
 - effects of, 37
- chlorinated polyethylene (CPE), 323, 356, 417
- chlorinated PVC (CPVC), 255
- chloroform, 337, 338
- chloroprene, 260
- Closite 6A, 464
- Closite 15A, 455
- Closite 20A, 472
- Closite 30B, 450, 455
- cloud point, curve of, 417
- ¹³C NMR spectroscopy, 277
- CNTs
 - chemical reactivity, 407
 - coated PE domains, 460
 - filled PA/EA 10/90 blends, 461
 - filled PA/PP 60/70, 461
 - filled polymer blends, 459
 - localization, 461
 - temperature stability, 407
- coalescence, 158, 388
 - suppression role, 465
- co-continuous phase, 383
- coefficient theory, 355
- cohesive force, 349
- Cole–Cole plots, 413, 415, 418, 422, 423, 424
- combinatorial entropy, 70, 336, 340, 342
- comonomer, 45
- comparability, 239
- compatibility, 136
- compatibilized polymer blends, 167, 316
 - bio-based polymer blends
 - – reactive compatibilization, 169
 - blocks addition/graft copolymers, 167
 - reactive compatibilization, 168
- compatibilizers, 138, 231, 241, 335
- completely miscible, 137
- complex microstructures, 377
- composite domains, 372, 375
 - viscosity, 372
- compositional variations, 74
- composition in blends, dependence of domain diameter on, 359
- composition ratio, 361
- compressive modulus, 234
- compressive pressure, 240
- configurational entropy, 8, 20
 - temperature dependence of, 7
- configuron percolation model, 20
- configurons, 34
- constitutive thermodynamic parameters, 232
- contact angle, 349
- controlled temperature program, 57
- cooling crystallization function, 150
- cooling rate, schematic illustration, 7
- cooperatively rearranging region (CRR), 30
- cooperative motion, 48
- copolymerization, 299
- core–shell dispersed morphology, 372
- core–shell graft polymers, 287
- Core–shell impact modifiers, 288
- Core–shell modifiers, 287
- core–shell morphology, 354
- core–shell particles, 236, 389, 392
- core/shell PC/PMMA ratio, 368
- Couchman–Karasz function, 87
- coupling agents, 335
- coupling model, 20
- CR/BR blends, 325

- creep, 60
 - CR-elastomer, 390
 - CR/EPDM blends, 326
 - critical ligament size, 239
 - critical solution temperature, 336
 - critical surface tension, of rubbers, 306
 - CR/NR blend, 326
 - crosslink density, 394
 - cross-polarization magic angle spinning (CPMAS), 253
 - cryogenic fracture, 249
 - crystal growth geometry, 148
 - crystal growth rate, 211
 - crystallization, 2
 - crystalline/amorphous polymer blends, 139
 - crystalline component, 145
 - crystalline/crystalline miscible blends
 - types of crystallization, 153
 - crystalline/crystalline polyester blends, 172
 - crystalline/crystalline polymer blends, 152, 192, 201
 - crystalline lamellae, 142, 201
 - crystalline morphologies, 199
 - of miscible crystalline/crystalline polymer blends, 200
 - crystalline morphology, 194, 196, 198
 - crystalline phase
 - nucleation of, 158
 - spherulite growth rate, 159
 - crystalline polymers, 143, 192
 - blends, 143, 202
 - crystalline rubbers, 285
 - crystallinity, 109, 158, 192
 - miscible blends, 138
 - crystallizable components, 139, 143, 146, 156
 - polymer blends
 - – spherulite growth rate, 140
 - spherulite growth rate, 144
 - crystallizable dispersed phase, 158
 - fractionated crystallization, 164
 - number density of heterogeneities, 165
 - crystallizable matrix
 - blends with amorphous dispersed phase, 158
 - crystallizable molecule, 145
 - crystallizable phase, 158
 - crystallizable polymer, 139, 159
 - crystallization, 135, 139, 142, 143, 150, 245, 320
 - behaviors, 152, 192, 311, 313
 - – of NR, 313
 - – polymer blends *vs.* copolymers, 171
 - of compatibilized blends, 170
 - of dispersed phase, 164
 - growth rate, 145
 - – polymer blend, 145, 146
 - of immiscible blends, 158
 - – polymer effect of fillers, 166
 - peak temperature, 202
 - physical processes, 282
 - of polymers, 138, 239
 - processes, 149, 156, 214
 - rate, 311, 313, 318
 - crystallization kinetics, 136, 147, 201, 203, 245
 - isothermal kinetics, 147
 - nonisothermal kinetics, 150
 - crystallization temperature, 142, 145, 148, 156, 159, 160, 161, 167, 192, 193, 195, 200, 205, 208, 278, 302
 - crystallization time, in miscible blend, 204
 - crystallize, 192
 - crystals (pseudoeutectic type I), 156
 - crystal surface, 145
 - cure balance in rubber blends, 308
 - Cure systems, 282
 - cyclization, 53
 - cyclohexane, 370, 372, 380, 382
- d**
- damping factor, 61
 - data evaluations, 97
 - deformation, 234, 237, 239, 299
 - process, 237
 - degree of cure, 46
 - degree of dispersion, 394
 - degree of freedom, 37
 - degree of polymerization, 336
 - degree of utility, 229
 - Delaunay networks, 34
 - demixing, 143
 - density, 43
 - deuterated polystyrene (DPS), 429
 - diamond, 405
 - diblock copolymer, 470
 - compatibilization mechanisms, 470
 - dielectric analysis, 63
 - dielectric characterization, 246
 - dielectric glass-transition temperature, 65
 - dielectric relaxation spectroscopy, 64
 - diene rubbers, 285, 286
 - differential scanning calorimetry (DSC), 11, 138, 139, 245, 302, 411
 - cooling thermograms, 164
 - curves, 53
 - endotherms, 155
 - fusion endotherms, 155
 - plots, 52
 - spectra, 77

- thermograms, 80, 165, 166
- differential stress concentration, 234
- diffusion, 232, 339
 - coefficient, 146
- dilatational pressure, 240
- dilatational stresses, 240
- diluent + polymer systems, 82
- DiMarzio equation, 82
- N,N*-Dimethylformamide, 106
- dipole polarization, 246
- dispersed phases, 379
 - effects of interaction, 379
- dispersed rubber, 241
- dispersion, 299
- dissipation mechanisms, 238
- DMA damping factor
 - vs. temperature curves, 76
- DMTA analysis, 277
- Doi–Edwards model, 423
- domain size, 306, 307
- donor–acceptor interactions, 137
- Doolittle equation, 11, 28
- 1D PEL, schematic illustration, 22
- droplets, 465
 - deformation-induced elasticity, 422
 - fiber morphology, 348
 - like particles, 158
- drug delivery devices, 358
- DTA curve, 52
- dynamical freezing, 25
- dynamical transition, 24
- dynamic heterogeneity, 13
- dynamic interfacial energy, 354
- dynamic interfacial tension, 348, 355
- dynamic mechanical analysis (DMA), 60, 243, 301
- dynamic mechanical spectroscopy, 60
- dynamic quantity, 17
- dynamic testing, 302
- dynamic transition, 3
- dynamic vulcanization, 279, 280

- e**
- EBM droplet, 357
- EB-rich amorphous region, 274
- Ehrenfest ratio, 6
- EHR51 molecules, 274
- elasticity, 299, 357, 359, 383
- elastic phase, 348
- elastomeric properties, 279
- elastomers, 230, 233, 316
 - blends, 326
 - containing carbon–carbon double bonds, 281
 - phase, 283
- electrical conductivity, 358
- electrical percolation threshold, 438
- electromagnetic radiation, 254
- electron energy loss spectroscopy (EELS), 249
- π –electron interactions, 138
- electron microscopy (SEM), 138, 312
- electron spectroscopy for chemical analysis (ESPA), 255
- electron spin resonance, 50
- ellipsometry, 51, 256
- empirical concentration power, 89
- empirical mixing, 78
- emulsification role, 465
- emulsions, 259
 - low-viscosity, 433
 - polymerized ABS, 264
 - rubbers, 287
- encapsulated morphologies, influence of different factors, 358
- encapsulation effect, 373
- 1,2-enchainment, 279
- endothermic mixtures, 137
- energy absorption, 234, 235
 - of rubbers, 230
- energy dissipation, 235, 237, 239
- energy landscapes, 21
- EngageTM, 233
- engineering thermoplastics, 229
- ENR phase, 309
- enthalpic interactions, 233
- enthalpy change, 136
- enthalpy relaxation effects, 54
- entropy, 136, 336, 340
- EP copolymers, 286
- epoxide, 284
- epoxy resin, 75, 238
- EPR-G-MA/PP 70/30, 456
- equilibrium constants, 71, 114
- equilibrium melting point, 139
- equilibrium melting temperatures, 142
- equilibrium morphology, 364
- equivalent conductance, 64
- equivalent frequency, 66
- ethylene, 287
 - ethylene-acrylate (EA) copolymers, 445
 - ethylene-based elastomers, 286
 - ethylene–butene, 288
- ethylene buten rubber (EBM), 357
- ethylene copolymers, 287

- ethylene–hexene-1 copolymers (EHR), 273, 274
 - ethylene–higher α -olefin elastomers, 286
 - ethylene methacrylate (EMA), 445
 - ethylene–methyl methacrylic acid ionomer (EMAA), 357
 - ethylene–octene-1 copolymers (EOR), 233, 275, 365
 - ethylene– α -olefin elastomers, 233
 - ethylene–propylene, 286, 288
 - copolymers, 168
 - ethylene propylene diene monomer (EPDM), 354
 - blends, 271
 - BR blends, 302
 - CR blends, 323
 - elastomer with iPP thermoplastic, 282
 - ionomer, 272
 - 80/20/iPP composition, 281
 - matrix, 281
 - phases, 268
 - rubber
 - with iPP + PA6 thermoplastic, 284
 - with PA6 thermoplastic, 284
 - with PBT thermoplastic, 284
 - rubber, TPVs of, 284
 - ethylene–propylene–diene monomer (EPDM), 249
 - rubbers, 280
 - terpolymer, 271
 - ethylene–propylene–diene terpolymers (EPDM), 269
 - ethylene–propylene random copolymers (EPR), 269
 - ethylene–propylene rubber (EPR), 235, 356
 - ethylene–vinyl acetate, 258
 - ethylene–vinyl alcohol copolymer (EVON), 384
 - ethylene vinylacetate (EVA), 417
 - Etxeberria, 103
 - eutectic crystallization, 155
 - evolution of phase morphology in PMMA/PS/PBT 20/60/20 blend, 367
 - excitation spectra, 12
 - exfoliated organoclays, 459
 - experimental data, 33
 - experimental rubber–plastic blends, 257
 - blends of isotactic polypropylene, 269
 - with ethylene–butene-1 copolymer, 273
 - with ethylene–hexene-1 copolymer, 274
 - with ethylene–isotactic propylene copolymers, 272
 - with ethylene–octene-1 copolymer, 275
 - with ethylene–propylene copolymer rubber, 270
 - with higher α -olefin rubber, 272
 - blends of polyamides, 265
 - blends of polystyrene and styrene copolymers, 260
 - blends of polyvinyl chloride, 257
 - early work, 257
 - impact performance, 277
 - poly(butene-1) as semicrystalline rubber, 278
 - structure in injection-molded specimens, 276
 - styrene block polymer rubber, 278
 - tensile properties, 275
 - extended version of theory (eMCT), 25
 - externally controllable processes, 36, 40
 - confinement effects, 47
 - cross-linker effects, 45
 - crystallization effects, 42
 - filler effects, 44
 - plasticizer effects, 43
 - pressure effects, 40
 - ExxonMobil Chemical Co., 282
- f**
- fabrication, 230, 231, 233
 - fibrillation, 238
 - fillers, 167, 230, 231, 282
 - distribution in rubber, 308
 - filler network, 323
 - polymer combinations, 44
 - retention, 231
 - rubber interaction, 314
 - finite-element analysis (FEA), 239
 - computer models, 239
 - first-order phase transition, 6
 - flexible bonds additivity models, 81
 - flexural stiffness, 231
 - floating polymer, location and shapes of, 357
 - Flory diluent theory, 141
 - Flory equation, 146
 - Flory–Huggins binary interaction, 89
 - Flory–Huggins interaction, 99
 - parameter, 141, 146, 339, 342, 345
 - Flory–Huggins model, 70
 - lattice model, 112
 - Flory–Huggins parameters, 429
 - for binary blends, 340
 - interaction parameters, 420
 - Flory–Huggins theory, 89, 140, 305
 - Flory theory, 342
 - fluorocarbon elastomer/HNBR blend, 327

- Fourier's transformation analysis, 56, 473
 Fourier transform infrared spectroscopy (FTIR), 254
 – spectroscopy, 272
 Fourier transform Raman spectroscopy (FTRS), 254
 Fox equation, 88
 fracture surface of vulcanized NR/BR 80/20 blend, 313
 fracture toughness, 240
 fragility, 11, 17
 – concept, 17
 – index, 66
 free energy, 231, 342, 343
 – change, 136
 – of crystallization, 139
 – of mixing, 136, 137
 – states, 32
 free interfacial energy, 354
 – model, 354
 free radical polymerization, 286
 free space of matrix (FSM), 386
 free surface energy, 347
 free volumes
 – additivity of, 82
 – theory, 82
 full width at half-maximum (FWHM), 410
 functionalization of the rubber, 266
- g**
- gel-like behavior, 422
 gel-like criterion, 422
 GHz–THz region, 12
 Gibbs–DiMarzio theory, 31, 37
 – entropy, 82
 Gibbs free energy, 67, 353
 – change, 136
 – function, 5, 339
 Girifalco–Good theory, 436
 glass beads (GB), 384
 glass densification, 10
 glass formation
 – disaccharides, 2
 – liquids, 20
 – – fragility plots, 18
 – materials, relaxations in, 12
 – percolative phenomena in, 34
 glassification, 2
 glass microsphere (GMS), 379
 glass transformation range, 56
 glass transformation region, 2
 glass transitions, 1, 63, 66, 71, 139, 244, 245
 – behavior, 4
 – breadth, 78
 – manipulation, 36
 – mechanism, 20
 – phenomenon, 34
 – region, 139
 – shape characteristics, 78
 – signals, 58, 74
 – strength, 78
 – temperatures, 3, 55, 139, 160, 232, 245, 285, 299, 300, 301, 302
 – – composition-dependent, 28
 – – determination of, 55
 – – effect of pendant group length, 39
 – – effect of tacticity, 38
 – theoretical approaches, 20
 – theories of, 4
 glassy behavior, kinetics of, 8
 glassy polymers, dielectric relaxation modes in, 65
 gold nanoparticles, 44
 graft copolymers, 167, 263
 grafting, 408
 grafting from approach, 408
 grafting to approach, 408
 graphene oxide (GO), 472
 graphene oxide sheets (GOSs), 168, 473
 graphene sheet, 405
 – rolling up, 406
 graphite, 405
 GT equation, 90
 gum elastomers, 285, 286
 gyration, of amorphous component, 143
- h**
- half-unfreezing temperature, 55
 Han plot, 413
 Harkins equation, 351
 Hausdorff–Besikovitich dimensionality, 35
 Havriliak and Negami (HN) functions, 65
 heart flow curves, 57
 heat capacity, 52, 79
 heat of reaction, 245
 heat resistance, 322
 heterogeneity, 72
 heterogeneous miscible blends, 94
 heterogeneous mixtures of polymers, 346
 heterogeneous morphology, 299
 Heterogeneous nucleation, 142
 heterogeneous rubber blends, 300
 heterogeneous system, 346
 heterophase mixture, 393
 hexene-1, ethylene copolymers of, 273

- high density polyethylene (HDPE), 166, 240, 354
 - cores, 361
 - EPDM core/shell minor phases, 360
 - PP interface, 377
 - PS/PMMA blends, 372
 - PS/PMMA 70/15/15 ternary blends, 365
 - rubber interface, 240
 - high impact polystyrene (HIPS), 168, 235, 391
 - polymers, 263
 - PPE blends, 265
 - high temperature crystallizing component (HTC), 153
 - high-throughput (HTP), 424
 - high- T_m component
 - crystallization of, 209
 - Hildebrand solubility, 71
 - histogenesis, 377
 - Hoffman–Weeks plots, 142
 - for PAS/PEO blends, 142
 - homogeneity, 305
 - homogeneous polymers, 393
 - homogeneous system, 339
 - homopolymers, 40, 81, 144
 - miscible blends, 140
 - HPDE/PMMA interface, 372
 - HTC dendrites, 156
 - hydrocarbon solvents, 284
 - hydrodynamic interaction, 379
 - hydrogenated nitrile butadiene rubber (HNBR), 327
 - hydrogenated styrene
 - block polymers, 278
 - Hydrogen bonding
 - interactions, 38, 254
 - networks, 2
 - proton, 88
 - hydrogen bonding, 100, 137, 138
 - hydrophilic (A200), 431
 - hydrophilic nanoparticles, 467
 - hydrophilic silica, 440
 - filled blends, 436
 - particles, 439
 - hydrophilic silica nanoparticle-filled
 - near-critical PS/PVME (10/90) blends, 432
 - hydrophobic (R972) concentration, 431
 - hydrophobic polymers, 404
 - hydrophobic silica nanoparticles, 433
 - hydrophobic SiO₂-filled PS/PVME blends, 431
 - hydrostatic stress, 239
 - hydroxypropyl methylcellulose (HPMC), 83
 - hydroxypropyl methylcellulose acetate succinate (HPMCAS), 83
 - hysteresis peak, 53
- i*
- ideal glass transition, 8
 - IIR/EPDM blends, 322
 - immiscibility, 68, 389
 - immiscible amorphous component, 160
 - immiscible blends, 158
 - complex modulus, 446
 - immiscible polymer blends, 159
 - containing nanoparticle, 433
 - carbon nanotubes, 459
 - compatibilizing effect of nanoparticles, 464
 - feeding sequence effect, 437
 - kinetic parameters, 437
 - nanoclay, 450
 - nanofilled polymer blends, morphology evolution of, 462
 - nanoparticle migration, 462
 - nanosilica, 447
 - parameters determining localization, 433
 - rheology of, 446
 - thermodynamic parameters, 434
 - viscosity effect, 441
 - crystallization characteristics, 136
 - crystallization rate, 161
 - melting behavior of crystalline matrix, 163
 - superstructures, 158
 - immiscible polymers, 347
 - chains, 470
 - inelastic deformation, 239
 - inelastic neutron scattering (INS), 252
 - influence of content of PMMA enveloping phase on average equivalent volumetric diameters of PBT + PMMA composite domains, 361
 - Infrared spectroscopy, 254
 - initialization, 240
 - in'situ emulsion polymerization of NBR, 257
 - in'situ ester-interchange reactions, 171
 - interaction energy density, 141
 - interassociation equilibrium constant, 114
 - interassociation interactions, 90
 - interfacial energy, 230, 350
 - interfacial free energies, 353
 - interfacial property, 256
 - interfacial surface, 231
 - interfacial tensions, 256, 307, 325, 347, 349, 350, 353, 355, 356, 357, 358, 365, 372, 379, 394, 434
 - values, 356
 - interfibrillar, 139, 143
 - segregation, 143
 - interlamellar segregation, 143, 201

- intermolecular interactions, 38, 344, 389, 390, 391
- internal cavitation, 240
- interpenetrated spherulites, formation process, 224
- interphase boundary, 335
- interspherulite, 139
- interspherulitic segregation, 192
- intramolecular hydrogen bonding, 114
- intraspherulitic phase separation, 214
- Inverse gas chromatography (IGC), 70, 255
- ion–dipole intercomponent interactions, 2
- ion-exchange reaction, schematic picture, 404
- ionomers, 287
- isobaric capacity, 86
- isochronal DMA scan, 62
- isochronal $\epsilon(T)$ spectra, 95
- isochronous dynamic temperature, 421, 430
- isomers, 233
- isoprene, 317
 - based unsaturated rubbers, 235
- isotactic polypropylene (iPP), 155, 160, 233, 269, 270
 - emanating, 279
 - EP blends, 275
 - failure, 276
 - lamellar crystals, 275
 - matrix, 276
 - PB-1 blends, 278
 - PE blends, 272
 - plastomer blends, 273
 - spherulites in a 50/50 iPP/LDPE blend, 162
 - ternary blends, 272
 - thermoplastic
 - – TPVs of, 284
- isothermal crystallization, 150, 221
 - data, 150
 - kinetics, 207
- isothermal plots, 64
- iTEM software, 472
- Izod impact strength, 268

- k**
- Kauzmann paradox, 22
- Kauzmann temperatures, 9, 22
- ΔK effect, 113
- Kerner model, 450
- Köhlrausch–Williams–Watts function, 23
- kinetic curves of mixing for ternary PMMA/PS/PBT 20/60/20 blends, 366
- kinetic factors, 363
- kinetic mixing curves for PMMA/PS/PC 20/60/20, 368

- kinetics, of dispersive actions, 231
- Köhlrausch's exponent, 12
- Kuhn length, 96

- l**
- lamellae structure, 143
- large melting point difference, 201
 - crystallization behavior of
 - – high- T_m component, 201
 - – low- T_m component, 209
 - morphology and structure of blend systems, 213
- Larson's based mean-field theory, 416
- laser scanning confocal microscopy, 248
- latent heat of transition, 5
- LDPE, 362
 - amorphous polymer, 161
 - droplets, 161
 - samples composition, 451
- LEST behavior, 428
- ligament, 238
- linear-chain polymers, 38
- linear heating cycles, 52
- linear mixing rule, 109
 - deviation from, 100
- linear thermal expansion, 59
- linear viscoelastic measurements, 412, 456
- liquid crystalline polymer (LCP), 365, 436
- liquid fragility, 17
- liquid–liquid demixing, 278
- liquid–liquid mixture, 139
- liquid–solid boundary, 145
- liquid–solid interface, 145
- liquid–solid-like transition (LST), 446
- liquid–solid phase separation, 192
- liquid–solid transition (LST), 412
- liquid to glass, transition from, 25
- lithium-neutralized poly(ethylene-co-methacrylic acid) copolymer, 171
- LM model, 96
- loading, 43
- loss angle tangent, 422
- loss modulus, 61, 63
- loss tangent, 61
- low critical solution temperature (LCST), 339, 345, 416
 - system, 417
- low-induced molecular orientation, 276
- low temperature crystallizing component (LTC), 153
 - spherulitic morphologies, 153
- low- T_m component
 - spherulitic growth, 209

m

- macromolecules, 299, 342, 392
- macroscopic uniform liquid layer, 350
- maleic anhydride (MA), 249, 323, 375
 - functionalized polypropylene, 170
 - grafted PP, 284
 - modified rubber (SEBS-MA), 267
- maleic anhydride grafted polypropylene (mPP), 155
- matrix-disperse morphology, 447
- matrix ligament size, 238
- matrix molecular weight, 263
- matrix thermoplastic material, 240
- MCM-41 nanoporous glass, 48
- mean-field theory, 355
- means of determination, 50
- mean square fluctuations, 14
- mechanical properties, 326
- melt annealing, 159
- melting behavior, 138, 139
- melting point, 147
 - depression, 140
- melt linear viscoelastic measurements, 460
- melt polymer blending, 231
- melt rheology, 450
- methacrylate–butadiene–styrene, 258
- methacrylated butadiene-styrene copolymer (MSBR), 391
 - particles, 391
- methyl acrylate, 283
- 4,4-methylenedianiline (MDA), 284
- α -Methylstyrene, 265
- Michaelis–Menten-type function, 48
- microcanonical partition function, 30
- microheterogeneity in blends, 326
- microhomogeneity in blends, 326
- micrometer scale, 192
- microscale, 300
- microscopic density fluctuations, 24
- microvolumes, 392
- minimal concentrations (percolation threshold), dependence of, 383
- miscibility achievement
 - via chemical modification, 99
- miscibility/compatibility, 67, 72, 109, 136, 137, 305, 389, 392
 - indicators, 72
 - partial, 72
 - of polymer blends, 136
- miscible binary crystalline blend systems, 214
- miscible binary polymer systems, 98
- miscible blends, 232, 233
- miscible crystalline, 202
- miscible crystallizable blends, crystallization behaviors of, 139
- miscible iPP/EPR84, 270
- miscible polymer
 - blends, 138, 415
 - – amorphous component, 144
 - composition curve of, 84
- mode-coupling theory, 20
- model blend systems, 471
- moderate-to-strong signal, 79
- modulated-temperature
 - DSC, 56
 - TMA, 59
- molar entropy, 86
- molecular dynamics computer simulations, 7
- molecular mobility, 314
- molecular weight, 233, 286, 307
 - diluent, 146
 - ratio, 307
- montmorillonite clay, 402
- Mooney viscosity, 308
- morphological observations, 211
- morphological types, 348
 - in ternary blends, 369
 - in ternary polymer blends, with phase encapsulation, 372
- morphology characterization, 247
- morphology–composition relationships, 372
- mosaic cells, 32
- multicomponent material, 394
- multicomponent polymer blends, 394
- multicomponent polymeric emulsions, 379
- multicomponent systems, 394
- multicomponent systems, thermodynamic equilibrium of, 339
- multifunctional block copolymers, 401
- multiparticulate computer models, 239
- multiphase blends, 346, 373
- multiphase mixtures, 393
- multiphase polymer blends, 355, 393
- multiphase systems, 353, 394
- multiple percolated structures, 372
- multiwall carbon nanotubes (MWNT), 170
- multiwalled nanotubes (MWNTs), 405
- mutual solubility, 336, 337
- MWCNT-filled PC/PE blends, 444
- MWCNT-filled PE/ABS blends, 444
- MWCNT-filled poly(butyl terephthalate) (PBT), 413
- MWCNT-filled polylactide, 413
- MWNTs
 - TEM micrographs, 445

- n**
- nanoclay, 323, 455
 - nanoclay-filled PET/PE 10/90 blends, 456
 - nanoclay-filled polymer blends, 450
 - nanocomposites
 - inear and nonlinear viscoelastic behavior, 412
 - WAXD patterns and TEM images, 410
 - nanofilled polymer blends, 433
 - nanofillers, 472
 - nanoheterogeneities, 67
 - nanometer scale, 201
 - nanoparticle-filled blends, 431
 - nanoparticle-filled composites, 403
 - nanoparticle-induced compatibilization, 472
 - nanoparticle-induced shift, 420
 - nanoparticle localization, 464
 - nanoparticle–polymer interaction, 433
 - nanoparticles containing polymer blends, 402
 - nanoparticles in polymer blends
 - compatibilizing effect, 465
 - nanopores, 48
 - nano-reinforcing, 452
 - nanoscopic structure, 433
 - nanosilica-filled, 418
 - nanostructural characterization, 409
 - differential scanning calorimetry (DSC), 411
 - linear rheological measurements, 412
 - transition electron microscopy (TEM), 410
 - x-ray diffraction, 409
 - nanotubes, thermal conductors, 407
 - natural rubber (NR), 235, 282, 392
 - blends containing, 311
 - BR blends, 307, 310, 312, 314, 316, 317
 - BR compounds, 302, 310, 314
 - CB compound, 302, 310, 314, 326
 - CB interaction, 309
 - CR blends, 315, 316, 317, 326
 - CSBR blends, 326
 - elastomer
 - with PE thermoplastic, 282
 - with polypropylene thermoplastic, 283
 - ENR blends, 314
 - ENR interface, 318
 - EPDM blends, 316, 323
 - IIR 50/50 blends, 324
 - iPP TPVs, 283
 - NBR blends, 316
 - polyurethane/layered silicate compound, 315
 - PP compositions, 283
 - PU blends, 315
 - SBR blends, 302, 313
 - SBR/CB compounds, 310
 - silica interaction, 316
 - silica nanocomposites, TSC spectra of, 45
 - star SBR blends, 322
 - TPI blends, 314
 - network–droplet morphological transition, 432
 - Neumann triangle method, 376
 - Neutron reflectivity, 256
 - neutron scattering, 12, 252
 - neutron spin echo (NSE), 252
 - spectroscopy, 253
 - Newtonian fluid, 61
 - Newtonian viscosity, 450
 - Nishi–Wang equation, 141
 - nitroxide radical, Arrhenius plots, 50
 - 4,4'-(N,N-dibutylamino)-(E)-nitrostilbene, 64
 - non-Arrhenius temperature behaviors, 15
 - noncombinatorial entropy, 340
 - noncrystallizable, diffusion behavior, 214
 - nonequilibrium glass, 9
 - nonequilibrium morphology, 80
 - nonergodic glass, 9
 - nonergodicity parameter, 25
 - noninteracting entities, 26
 - nonisothermal conditions, 150
 - nonisothermal crystallization
 - behaviors, 166
 - process, 150, 152
 - thermograms, 150
 - nonisotropic morphology, 231
 - nonlinear function, 231
 - nonlinear melt rheology, 448
 - non-Newtonian flow behavior, 277
 - nonpolar rubber
 - with nonpolar thermoplastic, 282
 - with polar thermoplastic, 284
 - nonradiative energy transfer (NRET), 255
 - nonreversible dimensional deformation, 59
 - non-wetting behavior, 349
 - normal phase separation (NPS), 429
 - N₂-plasma surface-treated PP (PP*), 471
 - nuclear magnetic resonance (NMR), 50, 253
 - nucleation, 148, 159, 240, 251, 313
 - ability of PES, 199
 - density, 161
 - efficiency, 212
 - nucleation and growth (NG), 416, 422
 - Nylon 6, 171
 - LDPE blends, 171
 - Nylon 66, 375

o

- oil resistivity, 323
- olefinic elastomers, 281
- α -olefin impact modifiers, 286
- oligomeric molecular weights, 256
- onset temperature, 62
- optical microscopy (OM), 112, 138, 247, 248, 300
- optical-shear technique, 467
- orevac/clay volume fraction
 - critical strain, 458
- Orevac-compatible blends, 459
- organic bentonite, 50
- organic small molecules, 232
- organoclay (Cloisite 20A), 318, 471
- organoclay-filled blends, 459
- organo-modified montmorillonite (OMT), 315
- organophilic montmorillonite, 50
- orientational motion, 24
- oscillating frequency, 51
- oscillating strain frequency, 112
- oscillatory heating rate, 245
- Osmium tetroxide, 248
- Owens–Wendt theory, 436
- oxidation, 232
- Ozawa equations, 150
 - plot of $\log[-\ln(1-X(t))]$, 151
- Ozawa's method, 151
- ozone resistance, 311, 322

p

- Painter–Coleman association model, 87, 88, 107, 113
- Palierne model, 446, 447, 456
 - palierne model, 456
 - viscoelastic model, 355
- partially miscible polymer blends
 - nanoparticles, 414
 - on phase separation, 415
 - PS/PVME behavior, 428
 - nanosilica on phase-separation behavior of PMMA/SAN blends, 418
 - silica nanoparticles on phase separation of PMMA/polyvinyl acetate, 417
- partial wetting, 351, 353, 378
 - morphology, 375
- particles
 - with highly elongated aspect ratio, 236
 - polymer interaction, 414, 434
 - shape, 394
 - sizes, 161, 236, 313, 365, 384, 386, 392
- Payne effect, 325
- PBT/PS blends, SEM photographs of, 385
- PCOM images, 320
 - at blending ratio of 75/25, 325
 - of CR/BR blends, 326
- PEG/PLA blends, 169
- pendant drop, 256
- percolation cluster, 35
- percolation theory, 35, 387
- percolation thresholds, 373, 382, 387, 394
 - experimental and theoretical dependences of, 388
 - volume fraction, 373
- peroxide, 281, 282
- perturbations, confinement-induced, 47
- phase angle, Van Gurp plot, 412
- phase contrast optical microscopy, 300
 - image of SBR/EPDM 50/50 blend, 304
 - images of SBR/BR 60/40 blends, 321
- phase diagram
 - LCST, 68
 - PPG–PHMA–p(MMA-n-BMA) ternary blends, 342
 - PS–PMMA–SAN chloroform solutions, 337
 - UCST, 68
- phase homogeneity, 94
- phase inversion, 359, 375, 389
- phase microscope images
 - 75/25, 303
 - of 75/25, 303
 - butyl/EPDM 50/50 blend, 304
 - SBR/NBR blends, 303
- phase morphology, 158, 346, 364
 - formation of, 345
 - in PMMA/PS/PBT 20/40/40 blends, 371
 - in PMMA/PS/PBT 40/40/20 blends, 371
 - polymer blends, 137
 - prediction of, 346
- phase selectively, 394
- phase-separated systems, 4
- phase separation, 337, 416
 - behavior, 414
 - of polymer blends, 415
 - morphology evolution, 432
 - temperature, 418
 - thermodynamics, 135
- phase viscosity ratio, 364
- PHBV/ENR blends, 162
- phenomenology, 4
- phenyl ketone hydrogenated, 59
- PHE/PCL 20/80 blend, 151
- 2:1 phyllosilicates, chemical structure, 404
- physical properties, 324
- PIB droplets, 447

- Pickering emulsion, 377
- Pickering-type structures, 377
- PI + P4tBS blends, MTDSC thermograms, 94
- plain kinetic effects, 11
- plastic, 229
- plasticizers, 230, 231, 281, 282
 - molecules, 90
 - plasticizing effect, 390
- plastic matrix, 238
- Plastic–rubber blends, 241
- plastics, 229, 230
- plastomers, 277
- P85LI5n4
 - storage modulus *versus* frequency, 451
- p-methylstyrene–isobutylene copolymers, 283
- Poisson distribution, 166
- Poisson ratio, 43
- polar esters, 44
- polarity, 43, 266, 318
- polarized optical micrograph (POM), 270
- polarizing light microscopy, 247
- polar rubber
 - with nonpolar plastic, 283
 - with polar thermoplastic, 284
- poly(acetoxy styrene) (PAS), 142
- polyacetylene, 325
- polyacrylates, 344
- polyamide (PA), 265, 444
 - ABS blends, 246
 - dispersed phase, 443
 - EA copolymer EA(10/90) immiscible blends, 461
 - EPR blends, 452
 - isothermal crystallization rate, 170
 - PA6 matrix, 246, 355, 444
 - PA6/PP/CNTs (60/40/3) nanocomposites, TEM images of, 462
 - PA6/PP nanocomposites, storage modulus variation, 452
 - PA6/PP/PS ternary blends, 355
 - PE 75/25 and 25/75 blends, 460
 - PE 80/20 blend, 470
 - PE 75/25 blend nanocomposite, 460
 - (–) PE/PA, complex viscosity, 459
 - rubber blends, 266
 - SAN/whisker system, 441
- polyamide 6 (PA6), 375
 - DSC cooling curves, 165
- polyamides, 284, 286
 - blends, 170
- polyarylates (PAr), 202
- poly(benzilmethacrylate), 345
- polyblends, 389
- polybutadiene (PBD), 69, 163, 235, 261, 264, 338
 - SAN blends, 268
- poly(butene-1), 273
- polybutene (PB), 248
- poly(butylene adipate) (PBA), 103, 202
 - crystals, 220
 - melt, different diffusion behavior, 206
 - rich blend, 222
- poly(butylenes adipate-co-terephthalate) (PBAT), 377
- poly(butylene succinate) (PBS), 103, 193, 377
 - crystallization
 - half-time, 212
 - temperature, 210
 - dependence of growth rate, 210
 - growth rate, variation, 211
 - PBA blends, 203, 205, 215, 217, 218, 222
 - AFM images, 191
 - AFM phase images, 216, 218, 221, 222
 - crystallization, 219, 220
 - DSC heating curves, 204
 - optical micrographs, 215, 217, 218, 219, 222
 - optical micrographs of, 191
 - PBA system, 225
 - PBAT/PCL blend, 379
 - spherulites, 206, 216, 219, 220
 - vs. crystallization time, 203
 - temperature dependence of spherulitic growth rates, 205
- poly(butylene succinate) (PBSU), 156
- poly(butylene succinate-co-butylene adipate) (PBSA), 152, 193
 - crystallization of, 223
 - kinetic parameters, 213
 - temperature dependence, 212
 - rich blends, 213
 - heterogeneous nucleation, 213
 - PVDF/PBSA, 213
 - spherulitic structures, 154, 224
- poly(butylene succinate-co-butylene carbonate). *See* poly(epichlorohydrin)
- poly(butylene terephthalate), 103, 202, 361
- poly(butyl terephthalate) (PBT)
 - cores, 366, 367
 - domains, 362
 - GMS solid particles on concentration, influence of content of, 385
 - matrix, 392
 - melt viscoelastic, 454
 - MWCNT, 413
 - particles, 389

- PC rubber blend, 392
- PE blends, 384
 - – nanoclay-filled, 471
- PMMA (PMMA/PS/PBT 20/40/40), 371
 - – core/shell domains, 366
 - – PS/PMMA 30/50/20, 361
 - – ratio, 362
 - – in ternary blends to co-continuous structures, 374
- PS interface, 362
- poly(ϵ -caprolactone), 345
- poly- ϵ -caprolactone (PCL), 151, 201, 377
 - PEO blends, 470
- polycarbonate (PC), 75, 201, 265, 343
 - blends, 391
 - SAN blends, 464
 - – graphene 59/40/1 blend, 473
 - shell, 392
- polycarbonate–ABS, 285
- polychloroprene (CR), 390
- poly(dicyclohexylitaconate) (PDCHI), 160
- poly(2,6-dimethylphenylene ether), 265
- poly(2,6-dimethyl-1,4-phenylene oxide, 49
- poly(2,6-dimethyl-1,4-phenylene oxide), 139
- polydimethylsiloxane (PDMS), 256
 - PIB blends, 466
 - – Cryo SEM freez fracture, 466
- polydispersity, 365
- poly(epichlorohydrin) (PEC), 156
- polyepichlorohydrin, 344
- polyester blends
 - transesterification on miscibility/morphology, 172
- poly(ester carbonate) (PEC), 193
- poly(ether imide) (PEI), 140
- polyethylene (PE), 235, 272, 340, 353, 359, 375
 - core dimensions, 362
 - g-MA, 458
 - matrix blends
 - – relaxation spectra, 457
 - PA6 blend systems, 472
 - PA interface, 384
 - PA/O, complex viscosity, 459
 - PE1/PP/PC system, 376
 - phase, 362
 - PP interface, 364, 376
 - PP/PS blends, 364
 - PP/PS systems, 375
 - PS 45/55 blend, optical micrographs, 438
 - PS co-continuous (45/55) blend
 - – electrical resistivity vs. mixing time, 439
 - PS ratios, 360
 - SBR composite domains, 359
 - SBR matrix, 362
 - SBR ratio, 359
- poly(ethylene adipate), 103
- polyethylene blends, 229
- poly(ethylene naphthalate) (PEN), 138
 - 40/60 PEN/PET blend
 - – crystallization behavior, 148
 - PET blends, 148, 173
- poly(ethylene oxide) (PEO), 27, 142, 193, 344
 - fibrils, 196
 - PECH, 338
 - PEO + phenolic + PCL blends, 114
 - PMMA, 338
 - spherulites, 194, 195, 196, 197, 199
 - – disappeared, 194
- polyethylene phase, 281
- polyethylene/polyamide (PE/PA) blends, 384
- poly(ethylene succinate) (PES), 103, 193
 - crystallization of, 198
 - fibrils, 196
 - PEO blends, 193, 198, 201
 - – composition dependence of morphological patterns, 200
 - – crystalline morphologies, 195
 - – polarized optical micrographs of spherulitic morphology, 194
 - – process of interpenetration, 194
 - spherulites, 193, 195, 197, 198, 199, 200
 - – type, 195
- poly(ethylene terephthalate) (PET), 138, 357
 - dispersed phases, 468
 - HDPE blends, 170
 - PEN blends, 173
 - – Thermal Properties, 172
 - PP/3MA/2T
 - – schematic, 469
 - – TEM images, 468
 - PP/TiO₂
 - – number and volume average diameter, 469
 - PP/2T nanocomposite
 - – TEM image, 467
- poly(2-ethyl-2-oxazoline), 59
- poly(hexamethylenedipate) (PHMA), 341
- poly(β -hydroxybutyrate), 103
- poly(3-hydroxybutyrate) (PHB), 201, 344
- poly(hydroxy ether of bisphenol-A) (PHE), 151
- poly(4-hydroxystyrene), 103
- poly(hydroxyvalerate), 103
- polyisobuthylene, 340
- polyisobutylene, 235, 436
- polyisoprene, 69, 168, 436
- poly(isoprene-butyl acrylate) block copolymer, 316

- poly(lactic acid) (PLA), 377
- polylactide plastic–acrylate rubber blends, 230
- poly(L-lactic acid), 444
- poly(L-lactide) (PLLA), 193
- polymer (PS), 337, 360, 389
 - blend, 3, 54, 135, 146, 192, 281, 335, 345, 346, 355, 358, 389, 401
 - crystallization kinetics, 147
 - melting behavior and crystallization, 136
 - phase boundaries in, 67
 - characteristics, 135
 - components, 335, 337, 340, 346
 - composite technology, 401
 - filler interaction, 435
 - energy, 435
 - film, 256
 - matrix, 446
 - miscibility, 336
 - nanocomposites, 407, 412, 446, 460
 - carbon nanotube
 - structure/characteristic of, 405
 - surface modification of, 407
 - layered silicate, 402
 - surface modification, 403
 - polymer–silicate nanocomposites
 - structure, 405
 - silica nanoparticles, structure/characteristics of, 408
 - slope, 414
 - type of nanofiller, 402
 - phases, 347
- polymer blends, samples of phase morphologies
 - prepared by melt extrusion, 347
- polymeric materials, 1
- polymerization, 229, 325
 - degree of, 3
 - of styrene, 263
- polymerizing solution, viscosity changes, 262
- polymerizing styrene/styrene–acrylonitrile, 261
- polymer-layered silicate nanocomposites, 405
- polymer/nanoparticle composites
 - time–temperature superposition, 425
- polymer–nanoparticle interfacial interaction, 412
- polymer–nanoparticle interfacial tension, 434
- polymer–polymer blend, 137
- polymer–polymer grafts, 283
- polymer–polymer interaction, 340
- polymer–polymer interdiffusion, 253
- polymer–polymer mixture, 137
- polymer–polymer pair, 141
- polymer–polymer systems, 392
- polymer ratio, 281
- polymethylacrylates, 344
- poly(methylmethacrylate)–poly(epichlorohydrin) (PECH), 338
 - PECH + PVME, 92
 - PMMA pair, 338
- poly(methyl methacrylate) (PMMA), 37, 99, 163, 265, 337, 339, 340, 354, 362, 375
 - co-continuous phase, 380
 - contents, 362, 382
 - dispersions, 382
 - domains, 365
 - sizes, 381
 - dosages, 382
 - droplets, 372, 383
 - encapsulated by PS (PS/PMMA), 354
 - fibrils, 354
 - phase, 368
 - morphologies, 380
 - separation of, 417, 418
 - viscosity, 365
 - PMMA + PMAA blends, composition dependences, 107
 - PP/PS ternary blends, 354
 - primary dispersed phase, 382
 - PS blends, 382
 - dynamic asymmetric blends, 416
 - HDPE ternary, 372
 - PBT blends, 366, 370
 - PBT ternary blends, 365
 - PC 20/60/20 ternary blends, 366
 - PS interfaces, 362
 - PVCN mixture, 344
 - PVPh mixture, 344
 - SAN blends, 421, 422, 426
 - binodal phase diagram, 423
 - OM images, 427
 - SAN 40/60 blends, 423
 - SAN 60/40, dynamic temperature ramp, 421
 - SAN, phase diagram, 425, 426
 - SAN(70/30)/SiO_{2.5} mixture
 - Cole–Cole plot, 419
 - SAN/SiO₂–OH 70/30/3 annealed
 - TEM images, 424
 - shell-forming phase, 354, 361, 362
 - viscosity, 442
- poly(methyl methacrylate-*b*-isoprene), 168
- poly[(*m*-methyl styren)-*co*(acrylonitrile)]/PMMA (PαMSAN/PMMA) blends, 427
- poly(*α*-methyl styrene), 69
- poly(*o*-chlorostyrene), 97
- polyolefins, 229, 278

- blends, 244, 250, 252
- elastomers, 284
- plastics, 282
- rubbers, 229, 235
- thermoplastics, 235
- poly(oxymethylene) (POM), 156
 - images, 193
- poly(ethyleneoxide) (PEO), 338
- poly(phenylene ether) (PPE), 135
- polyphenylene oxide (PPO), 473
- polyphosphazenes, 39
- polypropylene (PP), 170, 235, 280, 281, 353, 436
 - EOR (ethylene-co-octan copolymer 70/30) blends, 453
 - EPDM blend, 272
 - EPR blends, 248
 - EVA03 blend, 449
 - EVA80/20 blends
 - morphology of, 440
 - EVA/silica blends
 - TEM images, 442
 - gr-MA(MA), 467
 - LCP/PS ternary system, 364
 - melt viscoelastic, 454
 - PMMA blend
 - CB system, 441
 - TEM micrographs, 441
 - polyamide 6 (PA6)/PS blends, 360
 - PP-GMA/MMT/EOR nanocomposites
 - storage modulus, 453
 - PP + PS blends, 75
 - PP + PS samples, 74
 - PS 70/30
 - micrograph of, 439
 - PS binary blends, 385
 - PS core/shell droplets, 355
 - PS/PA6 40/30/30, 360
 - SEBS blends, 471
- polypropylene-glycidil methacrylate (PP-GMA), 453
- poly(propylene glycol) (PPG), 340
- polypropylene phase
 - crystallization, 282
- polystyrene (PS), 163, 260, 337, 344, 353, 359, 373, 375
 - blocks, 278
 - domain, 470
 - droplet size, 376
 - HDPE/PMMA blends, 365, 372
 - matrix, 362
 - OMLS, DSC traces, 411
 - PC-TMPC mixture, 344
 - PE blends, 359
 - PMMA (50/50) blends
 - tungsten disulfide multilayer onion-shaped (W2S) particle, 464
 - poly(phenyleneoxide) blend, 392
 - poly(vinyl methyl ether) (PS/PVME), 428
 - PP blends, 163
 - PS + PPO blends, glass-transition temperatures, 102
 - PS + TMPC blend, 80
 - PVME (10/90) blend
 - morphology evolution, 431
 - PVME blends, 429
 - rich phase network, 433
 - SBR matrix, 362
 - shell, 360
- poly(styrene-acrylonitrile) (SAN), 343
- poly(styrene-co-acrylonitrile), 101
- poly-(styrene-co-4-chlorostyrene), 139
- poly(styrene-co-vinylphenol), 108
- polystyrene/organoclay (PS/organoclay) mixture, 411
- poly(4-tert-butylstyrene), 99
- poly(trimethylene terephthalate) (PTT), 75
 - nonisothermal crystallization behaviors, 151
- polyurethane latex, 315
- polyurethanes, 258
- polyvinylidene fluoride (PVDF), 391
 - crystallization of, 208
 - dendrites, 157
 - kinetic parameters, 208
 - matrix crystallization temperature, 210
 - temperature, 212
 - vs. crystallization time, 204
 - spherulitic radius, 205
 - crystals, 213
 - dendrites, 156
 - dispersed particle, 472
 - matrix, 210
 - PBSA blend, 215
 - PBSA 50/50 blend, 222
 - PBSA blends, 209, 216
 - DSC cooling traces, 202
 - DSC cooling traces of, 202
 - PBSA system, 207
 - PBS blend, 209, 211
 - PBS blend crystallization
 - polarized optical micrographs, 209
 - PHB blends
 - crystallization of, 156
 - poly(hydroxy butyrate)(PHB), 156
 - rich blends, 208, 214
 - rich PVDF/PBSA blend
 - Avrami analysis, 207

- spherulites, 214, 223, 224, 225
 - – growth rates, 153, 154
 - – radius, 204
 - – structure crystallized, 157
 - temperature dependence of, 207
 - polyvinyl acetate (PVAc), 344, 417
 - enriched phase, 417
 - isobaric volume, 10
 - PVAc + epoxy resin blends, 46
 - PVAc + epoxy thermosets, 74
 - polyvinyl alcohol (PVOH), 256
 - poly(vinyl chloride) (PVC), 160, 249, 326, 390
 - butadiene–acrylonitrile copolymer, 392
 - NBR blends, NBR of, 259
 - PCL interactions, 255
 - poly(vinylcinnamate) (PVCN), 344
 - poly(vinylidene chloride-co-vinyl chloride) (PVDCVC), 156, 193
 - poly(vinylidene fluoride) (PVDF), 152, 201
 - poly(vinyl methyl ether) (PEMV), 345, 416
 - poly(vinyl methyl ether) (PVME)
 - phase, 432
 - PVME + PVPh, 99
 - rich phase, 433
 - polyvinyl(phenol) (PVPh), 344
 - KH + PPO blends, 60
 - miscible binary blends of, 104
 - Tg(w) patterns, 105
 - poly(4-vinyl pyridine), 88
 - positron annihilation lifetime spectroscopy, 29
 - postpolymerization production, 285
 - power-law fashion, 25
 - PPO–HIPS blends, 285
 - pre-existing system, 376
 - Prigogine, 338, 340
 - Prigogin rules, 344
 - property–composition curve, 389, 390
 - proton donating groups, 108
 - pseudosolid-like behavior, 451
 - PS/HDPE/PMMA
 - ultralow percolation threshold, in ternary co-continuous polymer blends of, 374
 - PS/SBR-2/PE blends, transmission electron micrographs of
 - PE contents in mixed SBR–2/PE dispersed phase, 363
 - 40/60 PTT/PEN blends, 152
 - pulse-induced critical scattering (PICS), 251
 - PVT method, 240
- q**
- quasielastic neutron scattering (QENS), 252
 - quiescent annealing, 377
- r**
- Radical-initiated reactions, 169
 - radical reaction routes, 169
 - radius of gyration, 387
 - Raman spectra finding, 473
 - Raman spectroscopy, 254
 - reactive compatibilization, 138, 169
 - recrystallization, 141, 142
 - reflected light microscopy, 247
 - refractive index, 55, 257, 300
 - values, 256
 - relative permittivity, 64
 - relative ratio, 229
 - relaxation, 245
 - dynamics, 11
 - relaxation function, time variation of
 - schematic illustration, 23
 - α -relaxation mechanism, 66
 - relaxation times, 14, 33
 - relaxation transitions, 392
 - resilience, 229, 230
 - rheological method
 - phase -separation temperature, 428
 - rheological percolation, 414
 - threshold, 412
 - rheological phase-separation temperature, 416
 - rotational freedom, degree of, 37
 - rubber blends, 299, 300, 301, 305, 307, 324
 - characterization techniques for, 300
 - distribution of fillers, 308
 - morphology and properties of different, 311
 - structure and morphology, effect of material parameters and processing on, 303
 - rubber dispersion, 229, 238
 - rubber domains, 230, 239
 - rubber/HDPE torque (viscosity) ratio, 364
 - rubber inclusions, 238
 - rubber-modified PA blends, 269
 - rubber–PA interface, 269
 - rubber particles, 235, 236, 238
 - average size of, 235
 - eliminates, 282
 - size, 235
 - rubber phase, 237
 - cross-linking, 39, 280
 - rubber–plastic blends, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 240, 243, 244, 245, 247, 261, 279
 - atomic force microscopy, 250
 - calorimetric methods, 245
 - characterization of interfacial properties, 256
 - dielectric characterization, 246

- dynamic mechanical characterization, 244
 - fluorescence spectroscopy
 - nonradiative energy transfer and excimer fluorescence, 255
 - glass transition, 243
 - infrared spectroscopy, 254
 - morphology/microscopy, 246
 - neutron reflectivity, 253
 - neutron scattering, 252
 - neutron spin echo spectroscopy, 253
 - nuclear magnetic resonance, 253
 - optical microscopy, 247
 - Raman spectroscopy, 254
 - of SAN, 263
 - scanning electron microscopy, 249
 - scanning tunneling microscopy, 250
 - scattering methods
 - light, X-ray, and neutron, 251
 - spectroscopic methods, 254
 - transmission electron microscopy, 248
 - UV–visible spectroscopy, 254
 - vapor sorption and solvent probe techniques, 255
 - X-ray microscopy, 251
 - X-ray photoelectron spectroscopy and secondary ion mass spectroscopy, 255
 - X-ray scattering, 251
 - rubbers, 229, 230, 235, 236
 - molecular weight distribution, 281
 - morphology, 299
 - plastic blends, discontinuous properties of, 239
 - plastic interface, 237
 - plastic phases, 232
 - plastic ratio, 264
 - plastic volume ratio, 264
 - products, 314
 - toughening epoxy resins, 286
 - vulcanization, 281
 - rubber toughening of plastics, models for, 240
 - Crazing model, 241
 - interparticle distance model, 242
 - percolation models, 243
 - rubber toughening, of thermoplastics, 233
 - failure process, 236
 - mechanism, 233
 - morphology, 235
 - rubbery inclusions, 237
- 5**
- saturated polyolefin plastics, 233
 - SBR–2/PS/PE blends, transmission electron micrographs of
 - different PE contents in, 360
 - scanning electron microscopy (SEM), 249, 301, 423
 - scanning force microscopy (SFM), 250
 - scanning probe microscopy (SPM), 250
 - scanning transmission electron microscopy, 281
 - Scanning tunneling microscopy (STM), 250
 - schema describe a proposed mechanism of action of solid domains of PBT phase, 387
 - schema illustrating double action of solid particles of phase 3 transformation, 386
 - SEB diblock copolymer, 377
 - secondary relaxation transitions, 245
 - second-order power equation, 90
 - second-order transition, 6
 - phase transitions, 5
 - second-run DSC thermograms, 114
 - segmental relaxation modes, 76
 - selective phase extraction, 373
 - semicrystalline morphology, 136
 - semicrystalline polymers, 54, 58, 142, 240
 - blend, 139
 - semicrystalline rubbers, 235
 - SEM images, 312
 - of cryo-fractured surface of SBR/BR 50/50 vulcanizate. Particles, 320
 - of etched silicone/EPDM 50/50 blend before vulcanization, 327
 - of fractured surface of vulcanized NR/IIR 50/50 blends, 324
 - of NR/acrylic rubber 50/50 blends, 317
 - semiquantitative theory, 347
 - SEM micrographs, 355
 - of morphology of HDPE/PP/PS blends, 377
 - of PA6/PP/PS 70/15/15 blends, 356
 - of PMMA phase morphologies in binary 45/55 PMMA/PS, 380
 - SEM microphotographs, 367
 - sessile drop, 256
 - shear stresses, 307
 - shear viscosity logarithm, 55
 - silane-modified silica rubbers, 325
 - silica dioxide (SiO₂), 408
 - silica-filled blend samples, 447
 - silica-filled PDMS/PIB blends
 - drop cluster of, 448
 - silica-filled PMDS/PIB system
 - linear viscoelastic behavior, 447
 - silica-filled PP/EVA blends, 449
 - silica-filled PP/PS blends, 449
 - silica nanoparticles, 402
 - silicon rubber, 326, 327, 408

- siloxane, 408
- Simha–Somcynsky hole theory, 29
- single covalent bonds, 37
- single/multiwalled carbon nanotube
 - artistic representation, 406
- single-phase polymer blends, 346
- single-phase systems, 4
 - glass transitions in, 78
- single-walled nanotubes (SWNTs), 405
 - bundles, 407
- sinusoidal stress, 61
- sliding-motions mechanism, 48
- slim-fast mechanism, 463
- slow secondary relaxation process, 13
- small angle light scattering (SALS), 415
- small-angle neutron scattering (SANS), 71, 252, 426
- small angle X-ray scattering (SAXS), 71, 138
- small melting point, 201
 - PES/PEO blends
 - – crystallization temperature on the crystalline morphologies, 198
 - – interpenetrating spherulites, formation of, 195
 - – morphology and structure of, 193
- smectic clay, 402
- sodium-neutralized poly(ethylene-co-methacrylic acid) copolymer, 171
- solar systems, 377
- solid dispersions, 83
- solidification, 240
- solid-like behavior, 455
- solid–liquid interface, 145
- solid particles, 384
- solid-state formulations, 2
- solid state polymerization (SSP), 173
- solid-state spectroscopy, 277
- solubility, 232, 306, 310, 345
- solubility parameters, 43, 231, 233, 305, 306, 355
 - difference between various rubbers, 305
 - for polymers, 356
- solvents, 233, 284
 - resistance, 312
- spatial fluctuations, 33
- specific volumes, 81
- spherical domains, 231
- spherulites, 111
 - crystallization and formation process of, 195
 - formation processes, 193
 - growth, 148
 - growth rate, 160, 161, 163
 - – amorphous component, 140
 - spherulitic growth, 159
 - – rate for immiscible blends, 159
- spherulitic, model of, 143
- spherulitic morphology, 197
 - in PES/PEO blends, 200
- spin-lattice relaxation time, 77
- spinning drop methods, 256
- spinodal curve, 343
 - for ternary blend, 343
- spinodal decomposition (SD), 416, 421
- spinodal decomposition temperature (ST), 416
- spinodal diagram, 343
- spreading coefficients, 350, 351, 352, 354, 356, 376
 - theory, 351, 363
- S-shape curve, 323
- stabilizing interaction, 233
- stable droplet–fiber dispersion, 348
- star SIB rubber, 322
- state of dispersion, 71
- STEM, 281
- stiffness, 43, 230
- Stokes–Einstein relation, 19
- storage modulus, 61
- strain, dissipation of, 237
- strain induced crystallization, 173, 314
- stress, 234, 299
- stress concentration, 237
- stress-induced cavitation, 238
- stress-induced nanoparticle, 414
- stress relaxation, 60
- stress–strain curves, 276
- structural relaxation, 10
 - time, 30
- structural voids, 27
- styrene, 305, 309, 320
- styrene-acrylonitrile (SAN), 168, 260, 337
 - dispersion, 263
 - SAN + PMMA blends, 101
- styrene(acrylonitrile) copolymers, 339
- styrene-based block copolymers, 288
- styrene-b-butadiene-b-styrene triblock copolymer (SEBS), 168, 364
 - droplets, 471
 - particles, 240
- styrene butadiene rubber (SBR), 287, 362
 - BR blends, 319, 320, 322
 - BR 60/40 blends, 320
 - BR/CB 80/20/20 compounds, 309
 - domains, 359
 - EPDM 50/50 blend, 304
 - NBR blends, 303, 322
 - NR blends, 320, 322

- NR 50/50 vulcanizate, 320
 - – AFM phase image of, 321
 - styrene-butadiene-styrene (SBS), 448
 - styrene-co-acrylonitrile (SAN), 418
 - styrene (maleic anhydride) copolymers, 339
 - styrene-ethylene-butylene-styrene (SEBS), 240, 267, 269, 375, 448
 - styrene-hydrogenated butadiene, 168
 - styrene-isoprene-butadiene (SIB), 322
 - styrene maleic anhydride copolymer (SMA), 170, 444
 - sulfonate groups, 443
 - sulfur donors, 282
 - supercooled liquids, 3, 9, 25
 - supercooling, 278
 - surface effects, 48
 - surface free energy, 350, 375
 - surface modified nanosilicates, 402
 - surface tensions, 306, 349
 - sweep and grab effect, 377
 - synergistic effects, 346
 - synthetic butadiene- based unsaturated rubbers, 235
 - synthetic butadiene-styrene rubber (SBR), 359
 - synthetic rubbers, 312
 - synthetic strategy, 233
- t**
- tailoring high-value polymers, 192
 - Taylor equation, 472
 - TEM analysis, 357
 - TEM characterization, 300
 - TEM examination, 301
 - TEM images, 461
 - of casted NR/PU/layered silica 50/50/10, 315
 - of fluorocarbon elastomer/HNBR blends, 328
 - of NR/BR blends, 308
 - of NR/BR blends with different blending ratios, 312
 - of NR/SBR blends, 306
 - of 45/55 PMMA/PS binary, 381
 - TEM micrographs, 370
 - of BR/CIIR/CB 50/50/50 compounded using different approaches, 319
 - microsectioned vulcanizates of blends, 312
 - of ultrathin sections, 380
 - temperature modulation
 - amplitude of, 56
 - DSC, 245
 - temperatures, 235, 245
 - tensile properties, 232, 325
 - tensile strength, 234, 235, 237, 316, 390, 392
 - tensile testing, 275, 326
 - tensile toughness, 238
 - in blend, 238
 - ternary blends, 340, 345, 348
 - components, 375
 - of polypropylene, 391
 - PS/SBR-2/PE, 362
 - with separated dispersed phases, 379
 - ternary blends, toughening mechanism in, 392
 - ternary compositions, 373
 - ternary liquid heterogeneous system, 350
 - ternary mixture, 336, 341
 - PS-SAN-MSBR, 391
 - PVC-polychloroprene-co (polybutadiene-acrylonitrile), 393
 - ternary PE1/PP/PC system, 376
 - ternary PMMA/PS/PBT 40/40/20 blend, 370
 - ternary PMMA/PS/PC 10/85/5 blends, 368
 - ternary PMMA/PS/PC 20/60/20 blends, 368
 - ternary PMMA/PS/PP blends, 381
 - ternary polymer blends, 335, 338, 339, 348, 351, 352, 353, 355
 - miscibility of polymers, 336
 - phase behavior, 111
 - properties of, 389
 - ternary polymer systems, 364
 - ternary polyolefin system, 364
 - ternary PP/PS/PBT blends, 386, 388
 - ternary systems, 343, 358, 379
 - morphologies in, 352
 - with one solid phase, 384
 - terpolymers, 258
 - testing fracture energy, 238
 - tetramethyl polycarbonate (TMPC), 49, 343
 - T_g
 - vs. amorphous phase composition, 110
 - vs. composition behaviors, 81
 - theoretical fundamentals of polymer blends, 335
 - thermal analysis, 302
 - thermal equilibrium, 54
 - thermal expansion coefficients, 74
 - thermal gradient, 54
 - thermally reduced graphene (TRG), 427
 - thermal motion, 340
 - thermal stability, 323
 - thermal stimulated currents (TSC), 246
 - thermal stirring, 340
 - thermoanalytical techniques, characteristics of, 51
 - thermodynamic affinity, 404
 - thermodynamically achievable polymer/layered silicate nanocomposites

- schematic illustration, 405
 - thermodynamically immiscible, 135
 - thermodynamic conditions, 364
 - thermodynamic considerations, predictions based, 85
 - thermodynamic critical point, 26
 - thermodynamic effects, 231
 - thermodynamic entropy, 85
 - thermodynamic equilibrium temperatures, 141
 - thermodynamic-induced phase-separation mechanisms, 421
 - thermodynamic parameters, 147
 - wetting parameters, 473
 - thermodynamic phase transitions, 4
 - thermodynamic potential, 339, 340
 - thermodynamic preferences, 434
 - thermodynamic solubility parameters, 232
 - thermodynamic stability, 339, 340
 - thermodynamic transition
 - low-temperature, 32
 - thermogravimetry analysis, 445
 - thermomechanical analysis, 57
 - thermoplastic, 234, 235
 - thermoplastic butyl rubber thermoset compounds, 283
 - thermoplastic elastomer (TPE), 45, 260, 323
 - thermoplastic matrix, 229, 235, 237, 239
 - thermoplastic polymers, 56
 - matrix, 279
 - thermoplastics, 229, 235
 - thermoplastic vulcanizate (TPV), 231, 279
 - principal classifications, 282
 - thiophosphoryl disulfide, 324
 - three-dimensional (3D) chemical network, 299
 - TiO₂ nanoparticles, 468
 - tissue engineering scaffolds, 358
 - TMA curves, schematic representation of, 59
 - Tool–Narayanaswamy–Moynihan formula, 17
 - toughening effect, 238
 - toughening, factors affecting extent and magnitude, 240
 - toughness, 230, 390
 - TPEg, 170
 - TPVs, 279
 - TPVs, improved properties over simple blends, 280
 - trans- and cis-1,4-polyisoprene, 135
 - transesterification reaction, 138, 172
 - in PET/PC blends, 172
 - transferring crystals, 145
 - transformation, 359
 - transitions, 245
 - transition temperatures, 42, 74
 - translational motion, 24
 - transmission electron microscopy (TEM), 248, 300
 - transmission light microscopy, 247
 - trans-1,4-polyisoprene (TPI), 314
 - triangular concentration diagram, showing regions of morphological states, 370
 - triangular region, 341
 - TTS method, 415
 - tunable morphologies in ternary blends, 377
 - turbidity points in chloroform solution, 338
 - twin-screw extruders, 231
 - two-dimensional (2D) images, 312
- u**
- ultrasonic velocity, 323
 - measurement, 323
 - ultrathin films, 47
 - universal values, 29
 - UV–visible spectroscopy, 254
- v**
- van der Waals gap, 402
 - van Gurp–Palmen plot, 413
 - Van Gurp plot of phase angles, 446
 - VanOene theory, 348, 355
 - vapor grown carbon fibers (VGCF), 166
 - VFTH equation, 16, 24
 - vinyl acetate, 287
 - 4-vinylpyridine, 103
 - viscoelastic measurements, 346, 415, 454
 - viscoelastic phase separation (VPS), 416
 - mechanism, 430
 - viscoelastic properties, 347
 - of blended polymers, 347
 - viscosities, 230, 231, 236, 256, 307, 310, 315, 318, 323, 348, 357, 359, 364, 383, 389
 - melts, 364
 - ratio, 305, 307, 364, 365
 - of rubber, 230
 - viscous and surface properties, blends measured, 379
 - viscous liquid, solidification of, 1
 - visualization, for these immiscible blends, 231
 - vitrification, 2
 - Vogel–Fulcher–Tammann–Hesse equations, 15
 - Vogel temperature, 16
 - volume fraction, 307
 - volumetric deformation, 239
 - vulcanization, 230, 232, 310, 311, 323, 327

- of blends, 322
- of elastomer phases, 232
- system, 280

w

- water–polymer interactions, 63
- WAXD measurements, 274
- wettability of a liquid, 349
- wetting behaviors, 349, 352
- wetting blend phase, 464
- wetting morphologies for the ternary blends, 378
- whitening in the fracture process, 237
- wide-angle X-ray scattering (WAXS), 240
- Williams–Landel–Ferry, 15
- Wunderlich's rule, 54

x

- X-ray diffraction (XRD), 409
- X-ray microscopy, 251

y

- Young's equation, 349, 434
- Young's modulus, 58, 271, 406

z

- zero thermodynamic temperature, 58
- Ziabicki method, 151
- Ziegler–Natta processes, 286
 - iPP, 270
- zinc oxide, 322, 323
- Zn²⁺-neutralized EPDM ionomer, 272