

Index

a

- additives 71, 82
- amorphous
 - polymer 9, 97ff.
 - structures 4, 6, 9
- atomic force microscopy (AFM)
 - droplet 145
 - nanofiber 74f., 102
- axisymmetric undulations, *see* fiber deposition

b

- bioerodible polymers 166, 169f.
- biopolymers 172ff.
- biostable polymers 166, 172, 228
- branching, *see* jet
- buckling, *see* fiber deposition
- burst release 174

c

- capillary flow porometry 107f., 117f.
- catalysis, *see* electrospinning applications
- chain
 - conformation 7ff.
 - extension 38
 - macromolecular 7, 166
 - molecules 9, 43
- chemical composition 73, 78, 80
- chemical vapor deposition (CVD) 116, 161, 230
- coalescence
 - fiber 43f., 116
 - fluid droplets 43f.
- cotton, *see* textile
- Coulomb forces 57f.
- counterelectrode
 - distance 31, 130, 153f.
 - nozzle 137
 - /substrate 31, 131
 - temperature 71

counterelectrode type

- bottom-up 37
- frame-shaped 111, 138
- planar 32, 110, 127, 129, 140, 148
- quadrupolar 139
- rotating cylinder-type 110f., 140
- star-type 139
- unstructured 109
- wheel-shaped 110, 140f.

crystalline

- partially 9, 11, 96, 99f.
- polymer 8, 11
- structures 4f.

crystallization 59, 96

crystals

- lamellar 9, 11, 77

current 70, 79

d

Darcy law 109, 119

die

- substrate distance 151
- tip 34
- tip–counterelectrode distance 39, 93, 153f.

dielectric

- constant 80
- permittivity 70

diffusion

- filter 188f., 194
- gas 114
- water vapor 199

dispersions 166

displacement velocity 39, 59, 152, 155

droplet

- cone-shaped 35, 52
- curve 49ff.
- deformation 35, 46f., 127
- fluid 47

- fluid protrusion 46
- formation 33ff.
- bending 35
- dumbbell models 52

e

- electric
 - conductivity 70f., 82f.
 - fields 47f., 83
 - parameters 83ff.
- electron scattering diagram 9
- electrospinning applications
 - catalysis 201f.
 - filter 12, 96, 136, 187ff.
 - inhalation therapy 232ff.
 - medical 217ff.
 - nanofiber reinforcement 203ff.
 - nonwoven 105, 187
 - plant protection 210ff.
 - surface modifications 206ff.
 - template 210
 - textile 197ff.
 - tissue engineering 3f., 21, 33, 90, 110, 218ff.
 - transport and release of drugs 228ff.
 - tumor therapy 230f.
 - wound healing 226ff.
- electrospinning 16ff.
 - chamber 131f.
 - deposition pattern, *see* fiber deposition
 - electrical parameters 31
 - experimental setups 29ff.
 - high-precision deposition (HPDE) 37f., 93, 143ff.
 - high-throughput 136
 - history 22f.
 - materials 165ff.
 - melt 180ff.
 - near-field 144ff.
 - process 29ff.
- electrospinning setups 18, 23, 25, 30, 32
 - coaxial 144, 155ff.
 - die-free multiple-jet injection 133ff.
 - microfluidic feeding 145
 - multiple-die 132f.
 - single-die 127ff.
 - syringe-type 127, 130, 134, 154
 - top-down arrangement 32
- electrospinning tubes by fiber technique (TUFT) 144, 160f., 210
- electrospraying 33
- extracellular matrix (ECM) 3, 13f., 219
- extrusion 10f., 69

f

- fiber
 - core-shell 155ff.
 - diameter 12ff.
 - elongation 42, 59f.
 - extrusion 10ff.
 - flexibility 116
 - formation 33
 - functionalized 13, 77
 - hollow 11, 86, 144, 155ff.
 - natural 2, 4, 11, 14
 - silk 2, 4
 - soft 43
 - solid 11, 17, 43
 - thickness 72f.
 - thinning 42
 - wool 4, 14
- fiber applications, *see* electrospinning applications
- fiber architectures 20, 22, 71
- fiber deposition 30f., 42ff.
 - axisymmetric undulations 39f.
 - buckling deformation 44f., 94f., 146, 150, 152f
 - crossgrating-type 39
 - individual 148ff.
 - pattern 93, 145ff.
 - spindle-like 42
 - test pattern 151f.
 - velocity 39
- fibrils 1, 3
- filter 12f.
 - capture ratio 194f.
 - coalescence 12, 196
 - diffusion 188f., 194
 - efficiency 188ff.
 - Knudsen regime 192f.
 - nanostructuring 190ff.
- fragmentation 95
- freezing-in process 97

g

- Gaussian coil 7f.
- glass formation 59, 96
- glass transition temperature 43, 97
- Gorham process 160

h

- hierarchical
 - structure 14, 16
 - trajectory 20
- high speed video analysis 34, 37, 42
- high voltage generator 31, 129ff.

humidity 84, 91, 198f
 hydroxypropyl cellulose (HPC)
 171f.

i

impurities 12
 instability
 – axisymmetric 42, 63ff.
 – bending 40f., 44, 52, 55f., 145f.
 – Rayleigh-type 33, 40f., 61f., 95f.
 – secondary 87
 – whipping 41, 62, 64
 insulation properties 4
 interference colors analysis 34, 36

j

jet
 – bending trajectory 55f., 94, 150
 – branching 41, 46, 66, 87
 – charged 57
 – deformation 37f., 70
 – diameters 34, 36, 38
 – flowing 32
 – linear trajectory 52f., 148
 – looping part 40, 59f., 150
 – mimicking 63
 – rectilinear 33
 – spiraling 40, 59f.
 – spraying 41
 – straight path 36ff.
 – stretching 52, 54, 79
 – trajectories 92ff.
 – undulating trajectory 39f., 149
 – velocity 37, 39
 jetting 46ff.

k

Kevlar fibers 12
 Knudsen number 191, 193,
 199f.

l

laser Doppler velocimetry 43
 lotus effect, *see* self-cleaning
 lyotropic polymer 12, 172

m

magnetic liquids 134f.
 Master lines 80
 Maxwell model 52ff.
 melt
 – electrospinning 30, 180ff.
 – extrusion 11

membranes 15, 20, 197
 – air flow resistivity 197f.
 – microporous 199
 – Gore-Tex 199
 Monte Carlo simulations, *see*
 porosity

n

nanofiber 12f., 15, 38, 69ff.
 – antibacterial 200f.
 – coating 136
 – diameter 78ff.
 – formation 69ff.
 – functionalized 77
 – geometry 72ff.
 – internal morphology 76f., 96ff.
 – nonwovens 105ff.
 – porosity 75, 78, 85f., 88, 91f.
 – scaffolds 78
 – single 101f.
 nanofiber structures 69, 72
 – band-type 85
 – barbed 87
 – breath figures 90
 – hollow 86
 – layer-like 110
 – linear 146, 208
 – parallel 110f., 148f., 204
 – pearl-necklace 95
 – planar 153
 – rectangular 150
 – ribbon-type 120
 – spherical 86, 91, 97
 – spike 134
 – topology 72f., 88f.
 nanofiber
 – ultrathin 197
 nanofilm 9, 97
 nanorods 15
 nanotubes 160f., 179, 181, 217
 Navier–Stokes equation 63, 191f.
 needle-punching technique 111
 neurons 13f.
 nonwoven 19, 42
 – architectures, *see* nanofiber
 structures
 – fiber diameter distribution 117ff.
 – heterogeneous 112f.
 – high-precision deposition electrospinning
 (HPDE) 151ff.
 – membrane 20, 107f.
 – nanofibers 105ff.
 – properties 106f., 124

o

- optical microscopy
 - charge-coupled device (CCD) camera 73
 - nanofiber 72ff.
 - nonwovens 106
 - polyamide 2
- optical properties 9, 14
- orientation
 - 3-D 111, 220
 - highly 43
 - molecular 124
 - order 98, 101
 - planar 32, 110
 - random 110
 - statistical planar 110
- orientational distribution 19
- oriented 32, 43, 110, 224

p

- permeation coefficient 109, 116, 119, 123f.
- phase
 - matrix 89
 - separation 89, 91f., 229
 - transition 97
- pheromones 210ff.
- photocrosslinking 171
- phototreatment, *see* thermal treatment
- polymer
 - block-copolymer 166, 172, 176ff.
 - complex systems 175ff.
 - graft-copolymer 166, 176f.
 - hybrids 178
 - poly(acrylic acid) (PAA) 70, 170
 - polyacrylonitrile (PAN) 81f., 90, 107, 112, 117ff.
 - polyamide (PA) 19, 32, 82, 85f., 88, 113, 166, 169
 - polybenzimidazole (PBI) 166, 169, 206
 - polycaprolactone (PCL) 70, 166, 170, 221f.
 - polycarbonate (PC) 157, 159
 - poly(ethylene-co-vinyl acetate) (PEV) 166
 - poly(ethylene imine) (PEI) 170
 - polyethylene oxide (PEO) 17f., 45, 65, 70, 81, 149, 158, 170, 221
 - poly(ethylene terephthalate) (PET) 166
 - polyimides (PI) 166, 169
 - poly(L-lactid acid) (PLLA) 44, 75, 78, 113, 162, 166f., 169f.
 - polymer processing, *see* fiber processing
 - poly(methyl methacrylat) (PMMA) 166, 169
 - poly(p-xylylene) (PPX) 160f., 230

- polystyrene (PS) 44, 72, 75, 90, 95, 166ff.
- poly(tetrafluoroethylene) (PTFE) 198f.
- polyurethanes (PU) 166, 228
- poly(vinyl acetate) 81, 88
- polyvinyl alcohol (PVA) 43, 87, 170
- poly(vinyl chloride) (PVC) 166
- poly(vinylidene fluoride) (PVDF) 9, 90, 157f., 166
- poly(vinyl pyrrolidone) (PVP) 102, 159, 170f.
- pore diameter 114
 - bubble point 108, 119, 123
- pore size 19, 78, 86, 91
 - distribution 108
 - geometric 107, 117f., 121
 - nonwovens 105, 107, 116
- porosity
 - 3-D 114
 - Monte Carlo simulations 114ff.
 - nonwovens 106, 113ff.
 - surface 208
 - total 85, 115, 120f.

q

- quantum effects 77, 209

r

- refractive index 38, 73
- reinforcement 2, 12f.
 - applications 21
 - nanofiber 90, 95, 103, 110, 138, 203ff.

s

- scaffolds
 - nanofiber-based 78, 220ff.
 - porous 221
- scanning electron microscopy (SEM) 2
 - cotton textile 2
 - nanofibers 15, 75
 - nonwovens 106
- self-
 - assembly 179
 - cleaning 114
 - organization 15f., 96, 229
- sol-gel process 162
- solution
 - concentration of polymer 80ff.
 - feeding rate 78f., 82
 - flow rate 70, 79
 - PEO/water 18
 - water-based systems 137
 - ultrasonic agitation 83

solvent

- DMF 166ff.
- mixtures 84, 91, 134
- organic 166ff.
- vapor pressure 71

stiffness 11, 43, 101, 124f.

strain 43, 125

strength 11, 101f.

- nonwovens 124

stress, 2, 73, 52, 125

superhydrophobicity 177, 180f.

supermolecular 15, 89

superparamagnetic particles 33, 134

surface

- charge density 70, 79, 87
- -energy contribution 62f., 95
- filtration 13
- modifications 206ff.
- roughness 33, 134
- solid 206f., 210
- tension 79f.
- topology 71, 84

surface area

- internal 12, 105, 108, 114
- specific 12, 20, 78, 105, 108, 118f., 122ff.

t

textile

- applications 11, 197ff.
- cotton 2, 11, 14

thermal

- conductivity 199f.
- properties 9
- treatment 137

TiO₂

- nanotubes 161f.
- shell material 159

tissue engineering, *see* electrospinning applications

top-down

- approach 10, 32
- die/counterelectrode 37

tracer-particle tracking technique 34, 37

trajectory, *see* jet

transmission electron microscopy (TEM) 2, 76ff.

tubes by fiber technique (TUFT), *see* electrospinning

v

viscoelastic

- dumbbell 54
- fluids 47
- Maxwellian fluid 52f.
- properties 9
- relaxation 52, 54, 70, 83
- stresses 52f.

viscous fluids 47, 83

x

X-ray diffraction (XRD) 76f., 100

