

Index

a

- accelerated aging techniques 723
 - principles 726
 - acidic aqueous media
 - polymerization reaction stages 659
 - acrylonitrile butadiene rubber (NBR)-based composites 300
 - NBR/butadiene rubber blends 558
 - acrylonitrile–butadiene–styrene copolymers 689
 - advanced functional fibers 444
 - adverse chemical reactions 85
 - aerobics group fitness class 780
 - aerospace industry 118, 125, 127, 130, 176, 179
 - development of GFRP 203
 - aggregate model 412
 - A-glass 187
 - alkaline treatment 478
 - alkali treatment 12
 - aluminum
 - flyer plates 19
 - poles 774
 - aluminum trihydrate 697
 - aluminum trihydroxide, Al(OH)₃ (ATH) 780
 - application of 780
 - 3-aminopropyltriethoxysilane
 - interactions with silica fiber surface, schematic presentation 345
 - ammonium peroxydisulfate
 - stoichiometry, aniline oxidation with 659
 - amorphous silica
 - equivalent loadings, vulcanizate based on 556
 - filler, comparison 547
 - amorphous thermoplastics 315
 - orientation of 315
 - aniline, oxidative polymerization
 - rate 660
 - temperature profile in 660
 - anterior cruciate ligament (ACL) 282
 - aramid fibers resemble inorganic fibers 776
 - area-to-volume (A/V) ratio 677
 - aspect ratio (AR) 577, 578, 686
 - ASTM cantilever bending device 372
 - asymptotic homogenization theory 87
 - atomic force microscopy (AFM) 661
 - study of 229
 - atomization 576
 - autoclave consolidation cycle 125
 - automated extruder compression molding
 - schematic presentation 116
 - automatic thermoplastic tape lay-up
 - schematic presentation 116
 - Automotive Composites Consortium 177
 - automotive industry 9, 11, 112, 116, 121, 133, 176, 177, 361, 479, 480, 692, 753
 - average-field homogenization theory 87
 - aviation, transportation 755–757
 - business aviation 756
 - commercial aircrafts 756
 - helicopter 757
 - military aircraft 755
 - space 757
 - axial modulus 410
 - axial ratio threshold 588
- ### b
- bag molding process 7, 8
 - banana fiber 12, 13
 - Beecher model 704
 - bending-induced damage 416
 - bending stiffness 384
 - standard test method 373
 - beta-modification 323
 - beta-nucleated PP films 323

- beta-polymorphs 323
 - BET technique 341
 - bias extension test
 - three zones 371
 - biaxial tensile device 369
 - bidirectional weaving (BW) 399
 - interlacing loops 401
 - schematic drawing 401
 - bifunctional coupling agents 342, 549, 550
 - biocompatible polymers 759
 - biodegradable matrix 4
 - biofiber composite 4
 - biotite 674
 - bis- β -hydroxyterephthalate 276
 - bisphenol-A epoxy resin 730
 - bistatic reflection measurements
 - setup for 626
 - bistatic reflection method 626
 - Boeing 787 dreamliner 756
 - Bombardier's, C-series aircrafts 756
 - π -bonding 154
 - bonds mill bridge 764
 - braided reinforcements 199
 - brake materials 771
 - Broutman test 86
 - Bruggeman effective medium theory 650
 - approximation 594
 - Bruggeman expression 651
 - Bruggeman model 593
 - bulk carbonyl iron
 - hysteresis loops 642
 - bulk ferrites 635–639
 - bulk ferromagnets
 - bulk ferrites 635–639
 - experimental magnetic spectra 635–641
 - ferromagnetic metals and alloys 639–641
 - bulk magnetic materials, magnetization processes in 628–641
 - bulk ferromagnets, experimental magnetic spectra 635–641
 - dynamic magnetization processes 632–635
 - magnetostatic magnetization processes 628–632
 - bulk MnZn ferrite
 - frequency dependence 643
 - hysteresis loops 642
 - bulk molding compound (BMC) 127, 191
 - butyl rubber 7
 - equivalent loadings, vulcanizate based on 556
 - filled natural rubber composites 515
 - filled sulfur-cured natural rubber (NR) 516
 - loading
 - coefficient of thermal expansion (CTE) 520
 - dielectric relaxation, time-temperature superposition of 525–529
 - function of 535
 - tensile behavior 519, 520
 - viscoelastic properties 520–522
 - volume resistivity and conductivity 522–525
 - nanofiller particles 515
 - primary physical properties, comparison 556
 - carbon black (CB) aggregate network
 - parameters, schematic diagram 534
 - structure 535–538
 - dielectric properties, relationship 536
 - carbon black-filled polymer surface 506
 - carbon black (CB)-filled sulfur-cured NR vulcanizates 518, 519
 - aggregate network structures 532
 - 3D network structures of 532
 - visualization of 533
 - average minimum distance, dependence of 531
 - d_p/d_g , definitions of 530
 - 3D-TEM images of 529–538, 530
 - loading 531
 - coefficient of thermal expansion (CTE) 520
 - dielectric relaxation, time-temperature superposition 525–529
 - tensile behavior 519, 520
 - viscoelastic properties 520–522
 - volume resistivity and conductivity 522–525
 - nuclear magnetic resonance (NMR) 532
 - standard deviations (STD) 529
 - carbon composite laminates 143
 - carbon/epoxy composites, uses 756
 - carbon-epoxy prepregs 755
 - carbon fiber (CF) 11, 137, 139, 140, 142, 143, 779
 - characterization of 146, 147
 - composite cored transmission conductors 178
 - cost 750
 - monocoque, Mercedes SLR McLaren Roadster F1 style 751
 - properties of grades of 142
- c**
- caprolactone 294
 - carbon black (CB) 516, 750
 - aggregates, function of 535

- reinforced epoxy fishing poles 779
- surface treatment 143
- electrochemical oxidation 143
- electroplating 143, 144
- oxyfluorination 144, 145
- plasma modification 145, 146
- carbon fiber-reinforced polymer composites (CFRCs) 137, 138, 142, 161, 168–171, 176, 177, 180
- applications 176–179
- characterization 148
- critical stress intensity factor 150
- fracture behaviors 151–153
- interlaminar shear strength 148–150
- mode I interlaminar fracture toughness factor 151
- preparation 146
- carbon fiber-reinforced polymers (CFRP) 751
- fiber glass tanks and silos 766
- carbon-filled polymer composites
- surface features, 506
- surface topography, 506
- PA12 and PA6.6, 506
- by TPM, mechanical property mapping, 501, 502
- averaged function parameters over scanned area, 507
- carbonization 139, 142
- carbon nanofibers (CNFs) 286, 322
- carbon racing sail boat 779
- Carbon Ultimate F10 772
- carbonyl iron (CI) powders 615, 645
- advantage 619
- chemical/mechanical treatment 619
- SEM photographs 648
- structural and electromagnetic characteristics 620
- Carl Walther GmbH 775
- LG300 XT carbontec air rifle of 775
- Cauchy–Green strain tensor 379, 380
- Cauchy stress tensor 375, 381
- C/C composite 405
- 3D, fracture in axial yarn 422
- CC test sample energy values 727
- cellulose fibers 4
- central frequency 627
- centrifugal casting 124, 125
- ceramic matrix composites (CMCs) 4
- CF/epoxy composites 758
- C-glass 187
- Charpy impact energy 476
- Charpy impact testing 718, 726, 727, 729
- chemical *in situ* methods 659
- chemical methods 576
- chemical resistance 189
- chloroprene rubber 7
- chopped strand composites 198
- chopped strand mats (CSM) 190
- closed magnetic system 644
- coefficient of thermal expansion (CTE) 188, 479
- cold plasma chemistry 12
- Cole–Cole plots 536, 537
- collagen 3, 13, 758
- collar jackets 480
- commercial glass fibers, properties 194
- compatibilizers 209
- compatibilizing effect of MA-g-PP 230
- DMTA analysis 233–235
- flow behavior 236, 237
- preparation of composites 230
- SEM study 237
- thermal properties 230–232
- X-ray study 233, 234
- complementary test 386
- complete particle debonding
- schematic diagram 95
- complex dielectric permittivity 657
- complex magnetic permeability 613
- complex permeability 640
- frequency dependence 645
- complex permeability spectra
- of carbonyl iron 641
- composite
- modulus 685
- with multicomponent filler, schematic picture 655
- composite fabrication process 347
- composite laminates 315
- composite materials 3, 15, 579
- characteristics 4
- classification 4, 5
- in current aeronautic structures 203
- dielectric spectra, CI particles microstructure effect 647
- electrical properties 592
- magnetic spectra 647, 653, 663
- particles shape effect on magnetic spectra 649
- poles, benefits 774
- predicted stress–strain responses 99
- properties, factors influencing 214
- chemical stability 214
- coupling agents, influence of 218
- fiber length 217
- fiber orientation 214
- modulus 214
- strength 214

- voids, influence of 217
 - volume fraction 214–217
 - properties, metallic particles effect 586
 - SEM and BSEM photographs 649
 - tensile strength 684
 - textile reinforcements 373
 - uses
 - helicopter blades 757
 - in naval applications 754
 - varieties of polymers for 7
 - composite technology 176
 - composite transport properties theory 593–605
 - effective medium theory 593, 594
 - electrical conductivity models 598–605
 - theory of percolation 594
 - thermal conductivity models 595–597
 - compressed three-axis composite
 - micrograph 421
 - compression-induced shear 421
 - compression molding 8, 112, 115–117, 121, 122, 302, 347, 476, 615
 - compressive stress 451, 457, 458
 - computer tomography 202
 - conducting filler, type 658
 - conducting polymer composites (CPC) 591, 767
 - conducting polymers, nanolayers 659
 - conductive compounds
 - influence of injection rate on surface resistances, 491
 - molding and electrical characterization, 489, 490
 - percolation threshold, 490
 - rheological characterization, 488, 489
 - shear viscosity, filled with carbon black, 489
 - surface resistances, 491
 - conductivity, filled polymers, 505
 - contact angle
 - on carbon fibers as a function of current 154
 - measurements 15
 - method 147
 - dynamic, theoretical considerations 147, 148
 - and surface free energy 153
 - continuous approach, advantage 382
 - continuous strand mats 190, 191
 - continuum mechanics approach 374
 - conventional circular fibers 192
 - conventional pull-out test 86
 - core–shelllike structure 655
 - correlation coefficient 458
 - corroded transmission pipeline, repair of 765
 - corrosion 194, 195
 - properties 195
 - resistance 3, 5, 10, 176, 187, 195, 203, 575
 - cotton fabric 473
 - coupling agent 343
 - covariant vectors 377
 - crack growth
 - schematic drawing 426
 - creep-recovery test cycle 724
 - creep-recovery test cycle
 - schematic presentation 724
 - creep resistance 197
 - critical amplitude 18, 46
 - critical fiber length 301
 - critical stress intensity factor (K_{IC}) 155
 - cross-ply (CP) 319, 323
 - crystalline fibril model 316
 - crystalline lamellae 315
 - crystallites 315
 - crystallization 307
 - Cu/LDPE composites
 - mechanical properties 585
 - Curie temperature 632
 - curing cycle 8, 34, 728
 - current density vector 623
 - curved neck specimen test 86
 - cycling loading 199
 - Cycom 4102 polyester resin matrix 20
- d**
- damage/failure mechanisms 84
 - damage mechanisms 413
 - damping coefficient 635
 - damping mechanisms 681
 - data reduction methods 87
 - Debye dispersion law 634
 - deformation gradient tensor 376
 - deformation process 374
 - degree of adhesion 352
 - delamination 37, 61, 78, 174, 192, 305, 394, 687, 740, 741, 743, 762, 783
 - demagnetization factors 631, 643, 646
 - magnetic particles 644
 - desized silica fiber
 - DRIFT spectra 344
 - 3D fabrics
 - with complex shapes 404
 - formation 405
 - 2D fabrics continuous modeling 373–382
 - geometrical approaches 373, 374
 - hyperelastic model 378–382
 - hypoelastic model 375–378
 - mechanical approaches 374–382
 - 2D fabrics discrete modeling 382–387

- global preform modeling 382–384
 - longitudinal behavior 385
 - mesoscale modeling use for permeability evaluation 386, 387
 - transverse behavior 385, 386
 - woven cell modeling 384–386
 - D-glass 187
 - diaminodiphenylmethane (DDM) 143
 - diaphragm–composite stack 119
 - diaphragm forming process 120
 - schematic presentation 120
 - dicyclopentadiene (DCPD) monomer 782
 - dielectric constant 699
 - dielectric relaxation characteristics 535–538
 - dielectric strength 699
 - diffuse reflectance infrared Fourier transform (DRIFT) spectroscopy technique 344
 - diglycidylether of bisphenol-A (DGEBA) 143
 - di(hydrogenated tallow) ammonium-modified mica 695
 - dimethyl terephthalate (DMT) 276
 - direct processing long-fiber-reinforced thermoplastics (D-LFT) 113
 - processing 117
 - dislocation-like model 93
 - dispersed (reinforcing) phase 3
 - distinction of image (DOI) 9
 - domain-wall
 - resonance 634, 635
 - schematic diagram 629
 - 3D orthogonal weaving
 - schematic drawing 397
 - double cantilever beam (DCB) test 151, 173–175
 - double strain amplitude (DSA) 564
 - dough molding 8
 - drainage process 437, 443
 - drainage system 456
 - dry reinforcement forming processes 382
 - 2D textile composite reinforcement
 - mechanical behavior 365
 - continuous modeling, macroscopic scale 373–382
 - discrete modeling, mesoscopic scale 382–388
 - future trend 388
 - and specific experimental tests 366–373
 - 3D textile composites 14
 - 3D woven composites design 429–431
 - energy-absorption and damage resistance 430–431
 - modulus 429
 - strain-to-failure 430
 - yield point 430
 - 3D woven composites modeling 407–412
 - bending fracture 413
 - compressive damage 417–424
 - failure behavior 412–428
 - fiber volume fractions 407, 408
 - fracture due to compression-induced bending 423, 424
 - fracture due to transverse shear 424–426
 - impact damage 427, 428
 - microband 417–420
 - miniband 420–423
 - rule-of-mixtures 409
 - surface loops influence 415–417
 - tensile fracture 413
 - weaker plane 414, 415
 - yarn rotation 410–412
 - yarns, elastic properties of 408
 - dynamic magnetization processes 632–635
 - domain-wall resonance 634, 635
 - natural resonance 633, 634
 - dynamic mechanical analyzer (DMA) 734
 - dynamic mechanical thermal analysis (DMTA) 226–228
 - dynamic wicking method 552
- e**
- easy magnetic axis (EMA) 630
 - E-class vehicles 753
 - Eddy current 632
 - effective elastic modulus 89–92
 - Mori–Tanaka method 90–92
 - self-consistent method 89, 90
 - effective elastic stiffness tensor 92
 - effective medium approximation (EMA) 593
 - type magnetic crystalline anisotropy 631
 - effective medium theory (EMT) 593, 614
 - effective opening size (EOS) 445
 - E-glass fibers 19, 33–35, 187, 193, 195, 199, 200, 204, 764, 775, 783
 - E-glass laminate 34
 - eigenstrain 88
 - eigenstress 88
 - elastically prestressed polymeric matrix composite (EPPMC) 715
 - long-term characteristics 716
 - elastic compliances of GRP 34
 - elastic constants 19, 34, 62, 409, 410, 604
 - elastic–elastic bilaminates 23–25, 28, 29, 46
 - elastic modulus 412, 684
 - elastic precursor decay 23–25, 28, 31, 32
 - elastic prestressing technique 715
 - elastic stiffness tensor 91
 - elastic tensor 90
 - elastic–viscoelastic bilaminates 20, 23, 28

- late-time asymptotic solution 24–33
 - solution at wave front 23, 24
 - wave propagation in 21–23
 - elastomer composites 282, 283
 - elastomeric polymers 769
 - elastomers 7, 115, 282, 283, 299, 550, 553, 554, 557, 569, 769
 - electrical characterization, of conductive compounds, 489, 490
 - electrical conductivity models 586, 589, 598–605, 768
 - of PP/Cu composites vs. filler content 578
 - electrical resistance, 496
 - electrical transmission 749
 - electric current density 155, 156
 - electric field strength vector 623
 - electrochemical *in situ* methods 659
 - electrochemical oxidations 141, 153
 - of carbon fibers 155
 - electromagnetic (EM) crystal materials 767
 - electromagnetic field 637
 - electromagnetic interference (EMI) 699
 - effects 768
 - shielding 768
 - electromagnetic–radiofrequency interference (EMI/RFI) shielding 767
 - electron-beam-treated silica-filled compound 560
 - electron microscopy 15, 202, 257, 516
 - electroplating 143, 144, 156, 160
 - electroplating, of injection-molded components, 494
 - microgear wheel made of nickel, 501
 - sample, made of, 494, 495
 - test results, transfer to standard material systems, 494–500
 - homogeneous deposition rates during, 499
 - injection rate, and optimization of parameter values, 499, 500
 - optical micrograph analysis, 498, 499
 - simulation of shear profile, and injection rate, 498
 - Vestamid LR1-MHI specimen, 494–497
 - effect of 156–163
 - electrospinning 302, 303
 - electrospun nanofibers 302
 - for reinforcement 302
 - electrostatic discharge (ESD) protection 767
 - ensemble-volume average method 84
 - micromechanical equation 94
 - EPDM-g-MA matrices 350
 - epichlorohydrin rubber 7
 - epoxy-based bonding agent 301
 - epoxy composite 4, 5, 200, 219, 221, 222, 286, 360, 522, 757, 783
 - epoxy resins (EP) 127, 137, 140, 143, 154, 319, 358, 689, 716, 735, 736, 755
 - CTE of 319
 - equation of state (EOS) of KAST-V 19
 - erosion control process 439
 - Eshelby-based homogenization techniques 197
 - Eshelby's equivalent inclusion method 88, 89
 - role in 90
 - Eshelby's tensor 88, 90, 91, 97
 - esterification 277
 - ethylene glycol (EG) 276
 - ethylene–octene copolymer 559
 - master curves 565
 - ethylene propylene (EP) copolymer 222
 - FTIR study 222, 223
 - preparation of composites 222
 - X-ray study 223–225
 - ethylene-propylene-diene terpolymer (EPDM) 349
 - carbon black 330
 - matrix 329
 - ethylene propylene rubber (EPR) compounds 7, 325, 551
 - peroxide-cured 551
 - ethylene-vinyl acetate (EVA)
 - copolymers 781
 - resin 448
 - thermal and electrical conductivities 590
 - Eulerian constitutive tensor 375
 - exponential function 22, 23, 721
 - extension ratio 563
 - extruders, role in 115
 - extrusion–compression molding 115
- f**
- fabric induces reinforcing effects 472
 - fabrics
 - thermal properties of 473
 - Falcon7X aircraft 756
 - fatigue
 - crack propagation resistance 678
 - properties 199, 200
 - testing 281
 - FE model 383
 - ferrites 655, 659
 - magnetic spectra 636
 - ferromagnetic resonance (FMR) 633, 667
 - frequency 668
 - ferromagnet, initial magnetization curve and hysteresis loop 630
 - ferromagnetis, characteristic feature 628

- fiber–fiber interaction 269
 - fiber-induced prestress 718
 - fiber–matrix adhesion 693
 - fiber–matrix debonding 726
 - fiber–matrix deformation 740, 741
 - fiber–matrix interface 739
 - fiber–matrix load transfer mechanisms 737
 - fiber orientation 113, 198, 214, 216, 257–259, 266–270, 377, 682, 700, 715, 760
 - prediction, theoretical basis for 257–259
 - simulation of 265
 - tensor vs. normalized thickness 260
 - fiber-processing techniques 729
 - fiber-reinforced composites 14, 358, 475, 736
 - fiber-reinforced concrete (FRC) 742
 - fiber-reinforced plastics 220
 - fiber-reinforced polymers (FRP) 761, 762, 770
 - based tribo components 770
 - composite materials 749, 759
 - composites 210
 - 3-D composites 10, 11
 - pipes growth 765
 - vessels 766
 - fiber reinforcements 141–143, 682, 750
 - fiber–resin bonding 139, 141
 - fiber–resin interface 141, 474
 - fiber rotation tensor 375
 - fibers
 - bundle 409
 - bundle deformation 386
 - fragmentation test 14
 - mesh 9
 - production 188, 189
 - tension effects 715
 - topography 734
 - viscoelastic properties 281
 - volume fraction 407
 - fibrous composites 4, 210, 214, 274, 296
 - fibrous fillers glass fiber 339
 - fibrous protein 3
 - fibrous reinforcements 700
 - filament winding process 7, 8, 129, 138, 176, 180, 189, 190, 198, 204, 326, 766, 778
 - schematic presentation 129
 - filler–filler interactions 553, 554, 565, 568
 - fillers 339
 - magnetic components 656
 - particles 693
 - shapes 683
 - filler surface modification, with bifunctional coupling agents 550–552
 - pretreatment methods 552
 - *in situ* method 551
 - film stacking 325
 - filtration process 437, 441
 - fisherman’s net method 374
 - fishnet algorithm 374
 - fishnet method. *See* fisherman’s net method
 - five-axis orthogonal fabric
 - schematic drawing 398
 - five-axis weaving technology 13
 - floating platforms 178
 - Floquet’s theory 20, 22
 - fluorinated Kevlar-reinforced composites 256
 - fluorination 209, 239, 319, 320
 - as polymer surface modification tool 219, 220
 - fluoroelastomers 7
 - fluororubber release layer 516
 - Folgar–Tucker model 269
 - Formula 1 car
 - primary structure of 776
 - fourth-order rank tensor. *see* Eshelby’s tensor
 - Fractions of branched chains (F_{branch}) 535
 - Fractions of cross-linked chains (F_{cross}) 535
 - F_{crit} relationship 538
 - relaxation strength on 537, 538
 - fracture behavior 75, 140, 151, 152, 221
 - fractured bone 758
 - plate and screw fixation 758
 - fracture toughness 150, 151, 155, 168, 169, 174, 296, 478, 678, 772
 - free energy. *See* surface free energy
 - free sliding model 94
 - free-space measurements
 - setup for 626
 - free surface
 - particle velocity 19, 39, 40, 43–46, 45, 53, 59–63, 61, 77
 - velocity profiles 45–48
 - FTIR spectroscopy 343
 - fully green composites 13
 - functional fillers
 - reinforcing action 682
- g**
- gel drawing 318
 - generalized effective medium (GEM) 593
 - geocomposites
 - schematic presentation 436
 - geogrids
 - specifications 447
 - tensile strains 448
 - geomembranes 446, 461
 - conducted soils interface, friction angles 462
 - geonet composites

- intrusion phenomena 454
- geosynthetic clay liner (GCL) 435, 445
 - schematic presentation 437
- geosynthetics
 - definition 435
 - functions 437
 - with polymeric materials 436
- geotextile/geomembrane composites
 - conducted soils interface
 - interface friction angles 465
 - direct shear test results 463, 464
 - photographs 462
- geotextiles/geogrids composites 446
- geotextile silt fences 439
- geotextiles, polymer composites
 - advanced functional fibers 444
 - advanced trend 444–446
 - application fields 440–443
 - applications, examples 442
 - definition 435–437
 - developments 443–446
 - for drainage and filtration 445, 446
 - drainage function 439
 - erosion control function 440
 - filtration function 439
 - function 437–440
 - geosynthetic clay liners 445
 - geotextiles/geonet, specification 450
 - hybrid composite 447–462
 - hydraulic properties 449
 - in-plane permeability 461
 - natural fibers 443
 - nonwoven types 444, 445
 - performance evaluation 462–467
 - required evaluation test items 465–467
 - test items 465
 - raw materials 443, 444
 - recycled fibers 444
 - reinforced concrete by 446
 - reinforced geomembrane by 446
 - reinforcement function 440
 - by role of function 441
 - schematic presentation 436
 - separation function 438
 - specifications 447
 - strength reinforcement 449
 - synthetic fibers 444
 - technology transition route 437
 - transmissivity 461
 - wide-width tensile strength-elongation curve 449
 - woven types 445
- Gilbert damping parameter 633, 634
- glass, chemical structure 186
- glass fiber composite armor systems 783
- glass fiber-reinforced composites 19, 187, 196, 199, 200, 205, 751
 - physical properties of 200, 202
 - strain rate effect in 200
- glass fiber-reinforced plastics 185, 199, 202–205, 762, 766, 773
- glass fiber-reinforced polymer (GFRP)
 - 33–35, 198, 202, 762
 - composite 773
 - composite tubes 763
 - fabric wrapping 762
 - fatigue resistance 199
 - pipe systems 204
 - properties of 201
- glass fibers 11, 192, 198, 738
 - composites, strength of 199
 - fabrication of 188
 - forms of 190
 - in polymer composites 196
 - production process 188, 189
 - properties 192
 - reinforcement 751
 - technology 783
 - types 187, 188
- glass mat-reinforced thermoplastics (GMT) 116, 191, 692
- glass/polypropylene plain weave 378
- glass-reinforced polyester pipes 766
- glass-reinforced polymer (GRP) composites 783
 - plates 20, 40, 42, 59, 76
- glass transition (T_g) 317
 - temperature 7, 226, 239, 240, 244, 245, 250, 251, 255, 256, 279, 282, 305, 308, 582, 616, 681
- glassy modulus 22
- glassy silica, chemical network of 186
- GNC-1, transmissivities 460
- GP resin 726, 727
- graft copolymerization 689
- grafted silica 550
- grand prix circuit 777
- Grand Prix motor racing 775
- graphite composite 4
- graphitization 139, 142
- green composites 4, 5, 13, 15
- Green–Naghdi axes
 - orientation 376
- Green–Naghdi frame 377
- Green's function 91
- “Green-Tire” technology 550
- GRIDFORM FRP reinforcement 763
- Griffith energy balance approach 708

h

- Halpin and Tsai model 705
 - hand lamination 123, 124
 - hand lay-up technique 7
 - hard magnetic axis (HMA) 630
 - healing glass fiber (HGF) 782
 - healing, polymerization 782
 - HEL. *See* Hugoniot elastic limit (HEL)
 - helix winding 118
 - Hertzian cone 427
 - hexadecyltrimethoxy silane (HDTMS) 550
 - hexagonal ferrite
 - crystalline cell 621
 - structural and magnetic characteristics 622
 - hexamethylenediamine 294
 - high density polyethylene (HDPE) 119
 - films 325
 - geomembranes 461
 - photo-oxidation 695
 - sericite–tridymite–cristobalite composites 695
 - high-modulus reinforcement 700
 - high-temperature epoxy resins 127
 - Hirsch and Counto models
 - schematic representation 704
 - homogenization process 87
 - homogenized elastic operator 90
 - Hugoniot curve 68
 - Hugoniot elastic limit (HEL) 20, 55, 58, 69
 - Hugoniot strain 51–54, 71, 72, 77
 - Hugoniot stress 43, 52–54, 56, 57, 68, 71, 72, 77, 78
 - vs. Hugoniot strain 51–54, 56
 - data of S2-glass GR 55, 56
 - vs. particle velocity 54, 55, 57, 58
 - data of S2-glass GR 57
 - hybrid composite geotextiles 447–462
 - for drainage 449–454
 - compressive stress and transmissivity 450–454
 - geotextiles/geonet composites manufacturing 449
 - nonwoven geotextiles/geonet composites 450
 - nonwoven/woven composite geotextiles 449
 - for frictional stability 461, 462
 - frictional properties 461, 462
 - geotextiles/geomembranes composites manufacturing 461
 - for protection and slope stability 454–461
 - thickness and compressive stress 457, 458
 - thickness and in-plane permeability 458–461
 - three-layered composite geotextiles manufacturing 454, 455
 - transmissivity 455–457
 - for separation and reinforcement 447–449
 - geotextiles/geogrids composites manufacturing 447, 448
 - hydraulic properties 448, 449
 - wide-width tensile strength 448
 - hybrid composites 4, 133, 216, 217, 222, 327, 469, 744
 - behavior of 469
 - strength of 469
 - hybrid fabrics
 - thermal properties of 473
 - hybrid filler system 693
 - hybridization 285
 - hybrid joints, tensile capacity 480
 - hybrid polymeric materials 444
 - hybrid reinforcement 327, 329
 - hybrid textile composites 478, 479
 - hybrid textile joints 479, 480
 - hybrid textile polymer composites 469–480
 - hydrodynamic effect 558
 - hydrogen bonding 154
 - in Kevlar 212
 - hydrolyzed tetraethyl orthosilicate (TEOS) gels 360
 - hydrophobic–hydrophilic properties 154
 - hydroxyapatite-reinforced high-density polyethylene (HA/HDPE) 759
 - hyperelastic behavior law 379
 - hyperelastic constitutive model 379
 - hyperelastic models 375, 379
 - hypoelastic laws 375
- i**
- impact stress 19, 44, 45, 49, 50, 62, 63, 68, 77, 78
 - impedance method 17, 24, 26, 29, 32, 40, 41, 60, 72, 76, 623, 624, 627, 628, 629
 - measuring instruments 624
 - measuring technique 624
 - imperfect interfaces 92
 - characteristics 83
 - induced kink-bands 420
 - inductance method 624
 - infinite conductive cluster (IC) 586
 - inhomogeneity 89
 - initial in-plane permeability 459
 - injected PBT thermoplastic 581
 - injection-molded carbon-filled polymers, 486–488
 - injection-molded composite 592

injection-molded thermoplastic matrix
 composites
 – modulus of elasticity 114
 injection molding 8, 485
 – advantages 8, 9
 – cooling phase 684
 in-plane shear 381
 – moment 368, 371
 – strain 372
 – test 378
in situ method 343
 INSTRON universal testing
 machine 272
 intercrystalline bridge models 316
 interface model 92–94, 212, 213
 – characterization 14, 84
 – dislocation-like model 93
 – free sliding model 94
 – interface stress model 93
 – linear spring model 92, 93
 – stress tensor 93
 interfacial adhesion 6, 137, 138,
 687–693
 – coupling agents 689, 690
 – hybrid effect in systems 692, 693
 – interfacial modification mechanisms
 690–692
 interfacial damage modeling 94–100
 – conventional Weibull’s probabilistic
 approach 94–96
 – cumulative damage model 98–100
 – multilevel damage model 97, 98
 interfacial debonding phenomenon 84
 interfacial shear
 – schemes 320
 – strength 140
 interlacing-induced deflection
 – in axial yarns 406
 interlacing loops
 – covering weaker planes 428, 429
 – holding axial yarns 429
 – role 428, 429
 interlaminar shear 192
 – strength measurements 352
 interleaving concept 322
 interpenetrating network (IPN) structure
 – phenolics of 328
 intrusion phenomena
 – of geonet composites 454
 – schematic diagram 457
 ionizing energy 305
 Iosipescu method 424
 iso-strain model 412
 isotropic hardening law 94

j

Jacquet model 704
 Jeffery model 269
 J_2 -type von Mises yield criterion 94

k

Kapok–cotton fiberreinforced polyester
 composites 473
 KES-FB system 372
 Kevlar composite 4, 221, 230, 238, 250, 271
 Kevlar fibers 11, 209, 211, 218, 271, 757
 – properties of 212, 213
 – reinforced polymer composite 210
 – structure 211, 212
 Kevlar-reinforced thermosetting
 composites 270–272
 Kevlar/vinyl ester composite 427
 Kings stormwater channel bridge
 – on California State Route 86 764
 Kohlrausch–Williams–Watts (KWW)
 distribution function 721
 Kraus equation 567

l

Lagrangian velocity 72, 73
 laminate
 – Al–PC laminate 29, 32
 – ballistic composite materials 783
 – composites 4
 – Fe–Ti laminates 29, 30, 31
 – made with 32 plies of prepregs 146
 – Mo–Fe laminate 29
 – Mo–Ti laminates 29, 31
 – of unidirectional tapes 198
 – used in analytical analysis 20, 21
 – viscoelastic 18
 – wave propagation in 21
 Landau–Lifshitz equation 636
 Landau–Lifshitz–Gilbert equation 633
 Landau–Lifshitz–Looyenga equation 650
 Landau–Lifshitz–Looyenga (LLL) mixing
 rule 650
 land transportation 750
 – compartment parts 752–754
 – shell/body parts 750
 – carbon fiber-reinforced composites
 750, 751
 – glass fiber-reinforced composites 751, 752
 Lanthanum fluoride (LaF₃) 271
 Laplace transform 20, 22, 76
 latch-based spring and dashpot model 720
 layered composites
 – mixing rule conditions 700
 L/D ratio 250

- leaky mold method 729, 731
 - Leider–Woodhams equation 707
 - less-reactive filler 342
 - LFT processing 116
 - L-glass 187
 - Lichtenekker empirical equation 651
 - Lichtenekker mixture equations 650
 - life cycle analysis 15
 - LIGA process, for manufacturing high-quality microcomponents, 485
 - lignin 4, 13
 - lignocellulosic fabrics
 - thermal properties of 474
 - linear spring model 93
 - liquid composite molding (LCM)
 - processes 365, 385
 - liquid crystalline polymers (LCPs) 283, 444
 - hybrid composites 250
 - liquid/gas barrier
 - composite geotextiles 446
 - load–extension curves 152
 - localized matrix creep effects 722
 - London dispersive component 139, 148, 150, 154, 155, 160, 172, 173
 - Lorentzian dispersion curve 634
 - Lorentzian dispersion law 634
- m**
- macro/microcomposites, interfaces in
 - characterization 85–87
 - composite materials, reinforcements surface treatments 85
 - interfacial damage modeling 94–100
 - micromechanics-based analysis 87–94
 - microscale tests 85–87
 - macro/micropolymer composites
 - future trends 130–133
 - preparation and manufacturing techniques 111
 - thermoplastic polymer composites 111–122
 - thermosetting polymer composites 123–132
 - magnesium hydroxides 780
 - decomposition temperature of 780
 - magnetically soft amorphous alloy 652
 - magnetic anisotropy 636
 - magnetic composite materials 613
 - magnetic conductors 639, 652
 - magnetic coupling 644
 - magnetic crystalline anisotropy 630
 - magnetic field 629
 - magnetic fillers 615–621
 - magnetic hysteresis 631
 - magnetic inhomogeneity 663
 - magnetic moments 628, 633
 - magnetic particle-filled polymer microcomposites 613
 - bulk magnetic materials, magnetization processes in 628–641
 - electromagnetic properties with corelike structure magnetic particles 663–668
 - with high value of permeability in radiofrequency and microwave bands 651–668
 - magnetic particles preparation with corelike structure 659–661
 - with multicomponent filler 652–658
 - with multicomponent magnetic particles 659–668
 - PANI film formation mechanism 661–663
 - polymer magnetic composites
 - basic components 614–621
 - magnetization processes 641–651
 - radiofrequency and microwave bands, methods for characterization 621–628
 - magnetic particles
 - demagnetization factor 644
 - magnetic polarization 643
 - manufacturing technology 659
 - magnetic permeability 631
 - vs. magnetic field strength 632
 - magnetization mechanism 635
 - magnetization processes 628, 631, 641
 - magnetostatic processes 628–632
 - in polymer magnetic composites 641–651
 - MA-g-PP, as a compatibilizer 230
 - maleated polypropylene (MAPP) 688, 690
 - maleic anhydride-grafted isotactic polypropylene (iPP-MA) 691
 - maleic anhydride-grafted polyolefin elastomer (POE-MA) 691
 - manufacturing techniques, classification 130
 - marine applications, transportation 754, 755
 - mass transport vehicles
 - interior composite components of 753
 - master curves
 - regions 565
 - materials
 - characterization methods, comparison for 628
 - material under test (MUT) 625
 - free-space measurements, setup for 626
 - matrix compression 738, 743
 - matrix/filler interaction 688, 689
 - matrix materials 111
 - matrix polymer 347
 - matrix polystyrene 691

- MAVSTAR project 178
- maximum packing fraction 581
- Maxwell–Garnet expressions 650
- Maxwell–Garnett (MG) approximation 650
- Maxwell–Garnett mean-field model 650
- Maxwell–Garnett theory 588
- Maxwell's equations 621
- Maxwell–Voigt arrangements 719
- mean stress 67, 69, 70
- mechanical interfacial properties 155, 156
- mechanical methods 576
- melt blending 309
- melt flow index (MFI) 465
- meltmixing process 592
- melt temperature 263
- mesomodeling
 - of unit cell 383
- metal-coated particles 582
- metal-filled polymers
 - applications 575
 - composites, rule for 585
 - properties 576, 606
- metallic conductive fillers 585
- metallic particle-filled polymer microcomposites 575
 - composite transport properties theory 593–605
 - electrical conductivity 577–579
 - main factors influencing properties 585–593
 - mechanical properties 583–585
 - metallic filled polymer, achieved properties 577–585
 - metallic filler and production methods 576, 577
 - particle shape, effect 587–589
 - particle size, effect 589–591
 - physical property prediction models 593–605
 - preparation process, effect 591–593
 - thermal conductivity 579–583
 - volume fraction, effect 585–587
- metallic particles 575
 - filled composite use 606
 - production methods 576
 - suppliers for 576
 - volumetric loading 581
- metal matrix composites (MMCs) 4
- metal–polymer composite 588, 591
- methyl ethyl ketone (MEK) 143
- M-glass 187
- mica
 - black (*see* biotite)
 - heat-resistant sheets 677
 - interfacial structure morphology 691
 - powder, used as 677
 - properties 674
 - sheet 676
 - tetrahedral layer, hexagonal layout 676
 - tetrahedral, octahedral, tetrahedral (TOT) layers 674
 - types 674, 675
 - white (*see* muscovite)
- mica-filled polymers
 - melt flow index (MFI) 696
- mica-filled polypropylene (PP) 678
- mica-filled system 709
- mica/nylon6 composites 685, 687, 699
- mica/polymer composites
 - mechanical properties 679, 680
- mica/polypropylene composites 692
 - melt viscosity 697
- mica-reinforced microcomposites 709
- mica-reinforced polymer composites 673
 - applications 676, 677
 - barrier properties 698
 - chemical and physical properties 674
 - crystallization 693, 694
 - electrical properties 698–700
 - flammability 695, 696
 - interfacial adhesion 687–693
 - limitations 707–709
 - mechanical properties 677–693
 - modeling 700–709
 - processability 696, 697
 - reinforcement mechanism 678–687
 - structure 674–676
 - tensile strength 705–707
 - thermal properties 693–696
 - thermal stability 694, 695
 - Young's modulus 700–705
- mica-reinforced polypropylene 681
- microair vehicles (MAVs) 178
- microband(s) 417–420, 422
 - connecting fiber kink-bands 418
 - matrix cracks in transverse yarns 418–420
 - microscopic kink-band 418
- micro-debond test 14
- microfabrication process
 - based on 2C injection molding and electroplating, 486
- microfibrillar composites 15, 285
- microfibrillar-reinforced composite (MFC) 284
 - PET composites 283–285
- microfiller-reinforced polymer composites
 - applications of 749
 - biomedical applications 757–760

- bone replacement 759
- dental composites 759
- external fixation 758, 759
- orthopedic applications 760
- civil engineering, construction 760–767
 - composite decks 762, 763
 - pipe applications 765, 766
 - repair and retrofitting 761, 762
 - seismic rehabilitation 763
 - structural applications 764, 765
 - unique applications 764
 - wind energy applications 766
- electric and electronic applications 767–769
- features of 749, 750
- fire retardancy, high temperature applications 780–784
- internal reinforcement, for concrete 767
- mechanical engineering, tribological applications 769–772
 - bearings , 771
 - brake lining 771
 - brake pads 771
 - brakes 771
 - gear 772
 - metal forming dies 770
 - seals 770
- recreation, sport equipments 772–780
- leisure 779, 780
 - racquets, bats 777, 778
 - summersports 772, 773
 - technical sports 775–777
 - watersports 778, 779
 - wintersports 773, 774
- transportation 752–757
 - aviation 755–757
 - land transportation 752–754
 - marine applications 754, 755
 - vessel length vs. year, plot of 754
- microindentation test 14, 86
- micromechanical damage models 94, 100
- micromechanical formulation 197
- micromechanical homogenization theory 87–89
 - Eshelby's equivalent inclusion method 88, 89
 - representative volume element 87, 88
- micromechanical technique 14
- micromechanics-based analysis 84, 87–94
 - effective elastic modulus 89–92
 - interface model 92–94
 - micromechanical homogenization theory 87–89
- micron-sized fibrous materials 361
- microscale tests 85–87
 - classification 86
- microscopic fracture band. *See* microband
- microscopic kink-bands 418, 430
- microscopic techniques, for morphological changes 15
- microstructure analysis 477
- midpoint integration scheme 377
- miniband 420–423, 422
 - double-wave miniband 423
 - through-thickness miniband 423
- miniscopic fracture band. *See* miniband
- mixing rules 614, 701
- MnZn-based composites
 - particle size effect on magnetic spectrum 646
- MnZn-based polyurethane
 - complex permeability 652
- MnZn ferrite 653, 656, 662
 - composites, magnetic spectra 654
 - Lorentz microscope image 662, 663
 - particles 666
 - particle surface 665
 - powders, magnetization curve 667
- MnZn–PANI composites
 - complex permittivity 667
 - magnetic spectra 665
- MnZn–PANI interphase boundary 666
- MnZn–PANI particles
 - synthesis 664
- modulus of elasticity 584
- molded filling simulations, tapered sample
 - and calculations of maximum shear rates for, 490
 - measured surface resistances, in correlation with calculated shear rate, 493
 - simulation of maximum shear rate
 - occur when filling sample, 494
 - results of, 492
 - surface resistance of nozzle geometry, 494
 - and surface resistances measured for different stages, 493
- mold flow's fiber orientation model 259
- mold flow technique 257
 - simulation of fiber orientation 257–259
- molding 7–10, 112, 115–117, 138, 190, 298, 682, 742. *See also* compression molding; reaction injection molding; thermoplastic injection molding
- molecular jumps 721
- monolithic polymers 757
- monomer/oxidant ratio 660
- Mori–Tanaka method 90–92, 471
- multiaxis weave structures 13

- multibeam VALYN VISAR system 36–38
 - multicomponent compounds
 - properties 693
 - multicomponent magnetic particles 659
 - multidirectional reinforcing network 394
 - multifunction tribological probe
 - microscope, 502–505
 - displacement calibration, 505
 - force-deformation curve, 504
 - formulas used in calculation, 504
 - friction sensor, calibration, 505
 - measurement of functions of surface, 504
 - multifunction mapping of, 507–512
 - – cushion effect, 511
 - – indentation curves, 510
 - mappings of topography, 508, 509
 - material distributions on specimen surfaces, 511
 - percolation of carbon particles, 511, 512
 - scanning rate, 510
 - schematic diagram of, 503
 - specifications of, 505
 - specimen preparation for, 505–507
 - multilevel damage process
 - schematic presentation 98
 - multilevel modeling techniques 197
 - multiple kink-bands 419
 - multiwall carbon nanotubes (MWCNTs) 287
 - Musal (MU) mixture equations 650, 651
 - muscovite 674, 676
 - general structure 675
- n**
- nanocatalysis 302
 - nanofiller-loaded vulcanized rubber
 - 3D-TEM observation of 517, 518
 - nanolevel analysis 84
 - nanotechnology 302
 - natural aminosilane-treated silica fiber (NASF-AS)
 - TG thermograms 346
 - natural amorphous silica fiber (NASF)
 - scanning electron micrographs 341
 - TG thermograms 346
 - natural ferromagnetic resonance 637
 - frequency 633
 - natural fibers 443
 - composites 11–13
 - lower specific gravity 361
 - Mercedes-Benz E-Class components 753
 - natural fibers vs. synthetic fibers 11
 - natural fiber textile-reinforced composites
 - manufacture of 475–478
 - natural inorganic silica
 - Silexil/Biogenic silica 340
 - natural resonance 633, 634, 639
 - natural rubber (NR) 7, 283, 477, 516, 553, 697
 - composites 283
 - natural silica fiber 340
 - reinforcement effect 348
 - X-ray diffraction pattern 341
 - needle punching method 454
 - Ni-artifact made by UV-lithography, 501
 - nickel-coated phogopite 699
 - nickel electroplating, 489
 - nitrogen-based compounds 780
 - NiZn ferrite
 - composites filled with, magnetic spectra 653
 - N_{NdNd}/TV
 - dependence of number 534
 - nonbiodegradable matrix 4
 - noncrimp braided carbon fiber-reinforced plastics 13
 - noncrimp fabric (NCF) 365
 - non-E-coat polymers 9
 - nonlinear viscoelastic–viscoplastic model 281
 - nonresonant methods 624, 627
 - novolac-type phenolic composites
 - reinforced 473
 - nucleates crystallization 697
 - numerical simulations 96, 97, 99, 100, 257, 378, 382, 583
 - nylon 6 9, 294, 295, 302, 309, 348, 350, 351
 - fiber-reinforced PMMA composites 309
 - nylon fiber-reinforced polymer composites 293
 - polymer magnetic composites (PMCs) 740
 - nylon fibers 299
 - as reinforcement 301
 - used as reinforcements 294–299
 - nylon 6,6 fibers 728, 735, 742
 - monofilament, polariscope image 718
 - SEM micrographs 735
 - nylon-reinforced composites 305
 - applications 310, 311
 - basic steps to obtain microfibrils 309
 - fracture morphology 309
 - manufacturing of 305–311
 - nylon 6/silica fiber composite
 - fracture surface, scanning electron micrograph 351
 - nylon 6,6 yarn
 - recovery strain data 722
- o**
- octadecyltrimethoxy silane (ODTMS) 550
 - one-shuttle scheme 402, 403

- weaving steps, schematic drawing 404
- online monitoring of morphology of
 - composites 15
- ordinary differential equations (ODEs) 20
- organic monomers
 - *in situ* polymerization 557
- overoxidation of fibers 140
- oxidative chemicals 12, 219
- oxidized carbon surfaces 139
- oxidizing agents 85, 138
- oxyfluorinated Kevlar fibers 228
- oxyfluorination 144, 145, 163
 - effect of 163–171
 - as polymer surface modification tool 219, 220
 - reactor 145
- p**
- Padawer model 704
- PANI film 666
- PANI globule
 - internal structure, atomic force micrographs 664
- PANI thin film
 - behavior 661
 - globular structure, atomic force micrographs 662
 - islandlike structure 661
 - protonation 661
 - *in situ* growth 661
- parallel plate method
 - for permittivity measurements 625
- partially debonded damage model
 - predicted elastoplastic responses, comparisons 96
- partially oriented yarn (POY) 279
- particle–matrix bond 705
- particle–matrix fraction 707
- particle velocity 22, 37, 46, 54, 67, 72, 73
- particulate-filled composite
 - chain formation in 587
- particulate-reinforced polymer composites 673
- Payne effect 563, 564
 - role 555
- PC/LCP/Kevlar composites 250
 - dynamic mechanical analysis (DMA) 253–255
 - SEM study 256
 - thermal properties 251, 252
 - X-ray diffraction pattern 253
- pedestrian bridges 764
- pelletized long-fiber-reinforced thermoplastics (P-LFT) 113
- percolation theory 594
 - mathematical model 594
- percolation threshold 577, 586, 588, 591
- permeability 619, 698
 - dispersion region 621
 - frequency dependence 635, 657
- phase transition function 651
- phenazin-containing oligomers 661
- phenol formaldehyde 220
- phenolic resin
 - adsorption 354
 - solution 352
- picture frame test 370
 - device 378
- Piola–Kirchhoff second tensor 379
- Piola–Kirchhoff stress tensor 380
- pitch-based carbon fibers 142
- plant fibers 752
 - automotive industry 753
 - glass fibers, replacing 753
- plasma treatments 85, 138, 145, 171, 321
 - effect of 171–176
- plastic drain board (PDB) 445
- plasticization effect 251
- plate-impact experiments 19, 69
 - on GRPs 33, 49
- plate-impact shock compression experiments 36–38, 42–44
 - Hugoniot stress
 - vs. Hugoniot strain 51–54
 - vs. particle velocity 54–58
 - of S2-glass GRP 43
 - shock waves in GRP, structure of 44–49
 - state for S2-glass GRP, equation of 49–51
 - stress–velocity diagram 37
 - time vs. distance diagram 37
- plate-impact shock-wave 20
- plate-impact spall experiments 38–40, 58–66
 - spall strength, determination of 59–61
 - spall strength of GRP
 - following combined shock compression and shear loading 62–66
 - following normal shock compression 61, 62
 - stress vs. velocity diagram 38
 - time vs. distance diagram 38
- platelet-reinforced composites 682, 701
- platinum–rhodium alloy 188
- Poisson’s ratios 701
- polar effect 154
- polyacrylonitrile (PAN)
 - based carbon fibers 137, 142
 - fibers 142

- polyamide (PA) 5, 13, 116, 119, 196, 294, 295, 296, 436, 581, 673, 681, 697, 772
- polybutadiene 7, 557, 681
- polybutylene oxide (PBO) 444
- polybutylene terephthalate (PBT) 116
- polycaprolactone (PCL) 302
 - SEM micrographs 304
- polycarbonate (PC) 7, 18, 29, 196, 251, 299, 758, 768
 - composite 250
- polycondensation 277
- poly(dimethylsiloxane) (PDMS)
 - cross-linking 355
 - reinforcement 693
- polydispersed particle mixtures 708
- polyepoxides 9
- polyester fiber-reinforced polymer composite (PFRPC) 281, 282–287
- polyesters 5, 7, 9, 128, 130, 275, 282, 673
 - physical properties 280
 - properties 277, 279
 - viscoelastic response 281
- poly(ether ketone ketone) (PEKK) 5, 120, 137, 196, 210, 690, 757, 758
- polyethylene (PE) 276, 315
 - fibers
 - oxygen plasma-induced surface restructuring 321
 - reinforcement 326
- poly(ethylene 2,6-naphthalate) 282
- poly(ethylene naphthalate) (PEN) 275
 - fibers 282
- poly(ethylene terephthalate) 275, 276
 - chemical structure 278
 - fibres 275–277, 279, 281, 282, 286, 455, 695
 - for industrial fibers 278
 - market 276
 - technologies for recycling 276
 - viscoelastic properties 281
- polyethylene terephthalate (PET) 119, 299
 - fiber 276
 - nanocomposites 286, 287
- polyfluo wax (PFW) 271
- polyimide 5, 7, 120, 196, 479, 699
- polyisocyanurates 9
- polymer chain immobilization concept 685
- polymer chain movement restriction 694
- polymer composite
 - core-shelllike structure 655
- polymer composites 3, 137, 360, 678, 749, 778
 - applications of 471
 - biomedical applications of 757
 - characteristics 141, 577
 - constituents 210
 - DC conductivity, concentration dependence 654
 - dielectric spectra 657
 - electrical properties 589
 - graphite/epoxy materials 757
 - hard tissue application of 758
 - magnetic spectra 629
 - recent advances in 10–14
 - saturation magnetization 641
 - SEM photographs 655
 - transportation 752–757
- polymer–fiber adhesion 347, 355
- polymer–fiber interactions 347
- polymer fiber melt spinning production process 278
- polymer–filler adhesion 353
- polymer–filler interaction 549, 566, 567, 568
- polymeric binders 189, 704
- polymeric coupling agent 690
- polymeric fibers 716
 - types of 776
- polymeric materials
 - reinforcing filler 351
- polymeric matrix 143, 359
- polymeric/oligomeric PANI (PPy) overlayer
 - conductivity 660
- polymerization 277, 306, 307
 - filling method 592
 - of PET 278
- polymer magnetic composites (PMCs) 656, 668
 - advantage 669
 - application 613
 - ceramic systems 741
 - components 614, 649
 - electromagnetic parameters 668
 - electromagnetic properties 614, 651
 - fiber-reinforced 742
 - magnetic fillers 615–621
 - magnetization processes 641–651
 - effect of composition 641–646
 - effect of particle size, shape, and microstructure 646–651
 - morphology 644
 - permeability 613
 - polymers in 615
 - processing 614, 615
 - production 614
- polymer matrix composites 4–6, 177, 209, 342, 356, 358, 587, 613–615, 649–651, 658, 741–743, 771
 - dispersed phase inclusions, shape and orientation of 6

- fabrication of composites 7–10
- factors affecting properties 6
- interfacial adhesion 6
- for manufacturing 10
- properties of matrix 7
- polymers 189, 575, 698
 - advantages and limitations 617, 618
 - filled with metal-coated particles
 - electrical conductivity 580
 - transverse thermal conductivity 583
 - filled with metallic particles, electrical properties 578
 - for glass fiber-reinforced composites 196
 - low diffusivity in 698
 - mechanical properties 681
 - network 558
 - physical and mechanical properties 616
 - thermoplastics 615
 - thermosets 615
- polymer/silica fiber composites 349
- polymethyl methacrylate (PMMA) 299, 326
- nylon composite, optical micrograph 307
- polymorphs 322
- polyolefin fiber-reinforced thermosets
 - hybrid fiber-reinforced composites 328, 329
 - polyolefin fiber-reinforced composites 327, 328
- polyolefin fibers 319, 330
 - family 315
 - melting point of 327
 - in rubbers
 - hybrid fiber-reinforced composites 329, 330
 - polyolefin fiber-reinforced composites 329
 - and tapes 315–317
 - application of 321
 - basic characteristics of 317
 - gel drawing 318
 - hot drawing 317, 318
 - properties and applications 318–321
- polyolefin/polyolefin combinations 327
- polyolefin reinforced interface/interphase characteristics in 326
- polyolefin-reinforced thermoplastics
 - hybrid fiber-reinforced composites 327
 - polyolefin fiber-reinforced composites 324
 - coextruded tapes, consolidation of 324, 325
 - film stacking 325
 - interphase 326, 327
 - matrix, *in situ* polymerization of 326
 - powder impregnation 326
 - solution impregnation 325, 326
 - self-reinforced version 321
 - film stacking 322, 323
 - hot compaction 321, 322
 - wet impregnation 324
 - poly(phenylene ether) (PPE) 284
 - polyphenylene sulfide (PPS) 119, 652
 - polypropylene (PP)/mica 5, 7, 116, 119, 276, 310, 315, 447, 579, 678, 687, 692, 758, 777
 - composites 684, 692
 - fabric 323
 - geotextiles 461
 - heat transfer coefficient 696
 - homopolymer
 - copolymer systems 324
 - fibers 325
 - tape 324
 - tapes 318
 - polypropylene sulfide (PPS) 444
 - polystyrene (PS) domains 329
 - polysulfide rubber 7
 - polytetrafluoroethylene (PTFE) 771
 - polyureas 9
 - polyurethane (PU) composites 9, 128, 189, 196, 221, 349, 444, 616, 646, 673, 768
 - fractured surface, scanning electron micrographs 349
 - magnetic spectra 664
 - permeability 666
 - concentration dependence 656
 - polyvinylacetate 189
 - polyvinylchloride (PVC) 359
 - silica composite nanofiber 360
 - polyvinylidene fluoride (PVDF) 19, 586, 656, 657
 - filled with Co_2Z , SEM photograph 657
 - Portland cement 4
 - powder technology 576
 - power-law model 705
 - prefabricated vertical drains (PVDs) 435
 - preformed molding compounds 8
 - premix thermoplastics 769
 - prepreg lay-up 125
 - prepreg sheets 306
 - prestressed polymeric matrix composite (PPMC) materials 716
 - prestressing
 - application 715
 - properly shaped fibers 192
 - properties, determination of 197
 - pull-in of rods
 - on specimen side 428
 - pull-out load vs. displacement curves 300
 - pull-out test preparation 14

- pultruded glass fiber profiles 198
 - pultruded shapes 764
 - pultrusion process 8, 130, 138, 284
 - schematic presentation 129
 - push-out test
 - drawbacks 86
 - pyrolysis gas chromatography 552
- q**
- quality factor 627
 - frequency dependence 657
 - quartz 186
 - quasi-glass state 566
 - quasi-static resonator 627
- r**
- radioabsorbers (RA)
 - design 657
 - matching frequency 658
 - Raman spectroscopy 343
 - Ramie-cotton fabrics
 - configuration of 473
 - textile reinforced polyester composites
 - tensile strength of 472
 - Rankine–Hugoniot conservation
 - relations 49, 51, 52, 71, 72
 - ratio of modulus 562
 - Rayleigh line 69
 - rayon fibers 142
 - reaction injection molding (RIM) 7, 9, 35, 123, 127, 196, 326, 352, 472
 - recrystallization 305
 - recycled fibers 444
 - reflection coefficient 626
 - frequency dependence 658
 - refraction index 193, 194, 202
 - reinforced concrete (RC) structures 761
 - reinforced reaction injection molding (RRIM) 9
 - reinforcement fibers
 - advantages 446
 - properties 294
 - reinforcement mechanism 339, 439, 441, 558–568, 678–687
 - applications 568, 569
 - dynamic mechanical properties 564, 565
 - equilibrium swelling 566–568
 - frequency dependence of storage modulus and loss tangent 565, 566
 - mechanical properties 560–564
 - mica concentration 684, 685
 - particle size and size distribution 685–687
 - rheological properties 559, 560
 - shape and orientation 682–684
 - reinforcement of polymers 5
 - reinforcement's modulus 704
 - reinforcing agent 361
 - reinforcing fibers 750
 - impregnation of 326
 - reinforcing fillers 567
 - reinforcing phase 3, 315, 325–327
 - reinforcing polyolefin films 315
 - relaxation function 22
 - remanent magnetization 630
 - representative unit cell (RUC) 367
 - representative volume element (RVE) 87
 - definition 88
 - reshock–release loading 72
 - calculation of off-Hugoniot states for 72–74
 - stress vs. strain states 70
 - resin film infusion (RFI) 472
 - resin impregnation 393, 395
 - resin infusion techniques 199
 - resin matrix 354
 - resin solution 4
 - resin transfer molding (RTM) process 8, 9, 123, 126, 127, 326, 352, 472, 476, 477
 - applications 125
 - schematic presentation 125
 - resonance frequency 664, 665
 - resonant cavity measurements 627
 - resonant methods 624, 627
 - R-glass fibers 187, 199, 783
 - rheological characterization, of
 - compounds, 488, 489
 - rheological parameters of composites 247
 - ribbons, surface modification of 327
 - roller transfer method 516
 - rotation tensor 376
 - rubber shell model 566
 - rule-of-mixtures 409, 410
- s**
- sample-to-resonator volume ratio 627
 - saturation magnetization 629
 - sebacic acid 294
 - second-order identity tensor 93
 - seemann composites resin infusion molding process (SCRIMP)
 - NABI composite bus shell production 752
 - selective free surface velocity profiles 47, 48
 - self-assembly techniques 360
 - self-consistent dynamic shear yield strength determination method 67–71
 - self-healing polymer composites 781, 782
 - self-reinforced polymer composites (SRPCs)
 - development of 321

- self-reinforced thermoplastic polymer composites 321
- semicircular component, relaxation strength of 537
- semicrystalline polymers 693
- semicrystalline2010 polymers 307
- SEM images 228, 229
- SEM micrographs of tensile fractured surfaces 249
- separation process 437
- sequential probabilistic debonding analysis 97
- S-glass 187
- S2-glass 187
- shaped glass fibers 192
- shape-memory polymers (SMP) 782
- sharples polariscope 717
- shear angle 387
- shear curve
 - of glass plain weave 370
- shear forces 546
- shear modulus 378, 429
- shear simulation 387
- shear strain 62, 63
- shear stresses 71, 113
 - distribution 114
 - types 424
- shear–stress transfer mechanism 704
- sheet molding compound (SMC) 7, 8, 123, 127, 191
- shift factors 566
- shock–release experiments 40–42, 66–75
- shock–reshock experiments 40–42, 66–75
- shock velocity vs. particle velocity
 - data for S2-glass GRP 53
- shock waves 17, 18, 41, 43, 44, 46, 68, 76, 78
- silane coupling agents 342, 345, 346, 569
 - chemical interaction 552
- silane-treated silica fiber 355
- silane-treated silica filler
 - filler loading effect 564
- silanization
 - effect 353
 - process 343, 344, 561, 568
- silanized silica fiber-reinforced polymer composite 358
- silanol groups 342
- silica (SiO₂) 186, 340
- silica fiber (SF) 339–347
 - characteristics 340–342
 - chemical modification 342
 - chief component 340
 - content effect 351
 - effect 350
 - plausible interaction, schematic presentation 359
 - surface modification, types and methods 342, 343
 - surface-pretreated silica fiber characterization 343–347
 - surface treatment 342–347
 - types 340
- silica fiber-filled polymer composites
 - composite fabrication 347
 - composite properties, effect on 347–351
 - reinforcement mechanism 358
 - surface-modified 351–358
- silica fiber-filled rubber 355
- silica fiber/phenolics composites 353
 - ILSS, experimental data 352
- silica fiber-reinforced polymer composites 339
 - applications 358–360
 - general features 339–347
 - new developments 360
 - silica fiber-filled polymer composites 347–358
- silica-filled polymer microcomposites 545
 - as filler 545–552
 - silica-filled rubbers 552–569
 - thermoplastics and thermosets 569–571
- silica-filled rubbers 552–569
 - reinforcement mechanism 558–568
 - silica filler effect on processability of unvulcanized rubber compounds 553, 554
 - silica filler effect on vulcanizate properties of rubber compounds 554–557
 - surface-modified silica-filled rubbers 557, 558
- silica filler 515
 - characteristics 546–548
 - chemical modification 549
 - filler surface modification
 - with bifunctional coupling agents 550–552
 - with monofunctional coupling agents 550
 - physical modification 549
 - silanol groups, types 551
 - structure formation, schematic presentation 548
 - surface modification, types and methods 549–552
 - surface pretreated silica, characterization 552
 - surface treatment of silica filler 548, 549
 - TEM photographs 553
 - types 546
- silica reinforcement of polymers 571

- silica–silane filler system 568
- silica–silica interaction 554
- silicate minerals 674
- silicone/muscovite composites 686
- silicone rubber 7
 - composite, scanning electron micrographs 356
- silicon monoxide
 - oxidation 340
- silicon nitride composite materials 360
- silver-coated glass
 - thermal and electrical conductivities 590
- simulation
 - of fiber orientation by mold flow technique 257–265
 - for PC/LCP/Kevlar composites 265–270
 - technique on s-PS/Kevlar Composites 259–265
 - physical properties of material layers 29
- single-fiber composites
 - transverse tensile debonding stresses
 - schemes of 320
- single-fiber compression test 86
- single-fiber pull-out test 86
- single-walled carbon nanotubes (SWNTs) 287
- sintered polycrystalline
 - ferrites, magnetic spectra 637, 638
 - magnetic spectrum of 636
- sisal/cotton composites 473
- sisal fiber 12, 13, 248, 277, 477, 478
- sisal fiber-reinforced vinyl ester composites
 - cross-sections of 477
- sisal textile-reinforced composites
 - mechanical properties of 476
- sizing agent 189, 190, 195
- skew angles 20, 38, 58, 59, 62
- smart composite geotextiles
 - compressive stress 459, 460
 - cross-sectional areas photographs 455
 - in-plane permeability 459
 - principal transmissivity mechanism 455
 - specifications 455
 - transmissivity 460
- Snoek's law 619, 635
- Snoek's limit 619
- sodium-fluorinated synthetic mica 695
- solid Kevlar rods
 - three-axis fabrics combining 407
 - vinyl ester rods 398
- solid rods 406
 - use 405–407
- solvent species effects 354
- SpaceshipOne 757
- spall strength 59, 62
 - determination of 59
 - of E-glass GRP composite 77
 - of GRP
 - following combined shock compression and shear loading 62–66
 - following normal shock compression 61
 - of KAST-V 19
 - in relationship with normal stress and shear strain 65
- spatial orientation 410
- specific energy absorption (SEA) 741
- spectroscopic tests, for polymer surface 15
- spinel-type ferrites
 - main structural and magnetic characteristics 621
- spinning. *See* gel drawing
- split Hopkinson pressure bars (SHPBs) 19
- spray gun 124, 125
- spray-up 124, 131
- s-PS/Kevlar composites (KSO)
 - AFM study 245–246
 - differential scanning calorimetric study 239–241
 - dynamic mechanical thermal analysis 243–245
 - FTIR study 238, 239
 - mechanical properties 248
 - preparation of 238
 - properties of 238
 - SEM study 245
 - thermal properties 241, 242
 - X-ray study 242, 243
- square fabric blank
 - pure shear on 384
- steel 4
 - properties of Kevlar fiber over other fibers 213
 - properties of selected reinforcing fibers and tapes 317
- stiffness matrix 409
- Stokes/Brinkman flow simulation 387
- storage modulus 566
 - variation 357
 - vs. frequency 560
 - vs. loss modulus, log-log plot of 561
- strain-limited toughness 732
- strain–stress relationship 92
- strain-to-failure (STF) 395, 732
- stress 22
 - vs. strain states 70
- stress-free transformation strains. *see* eigenstrain
- stress increment tensors 385

- stress-strain curves 73, 74, 75, 100, 141, 560, 561, 584, 709
 – for HDPZE/zinc composites 584
 stress-strain relation 409, 411
 stress-strain responses 96
 stress tensor 380
 stress-to-yield 395
 stress transfer 322
 – efficiency 84
 Strongwell pultruded profiles 763
 structural reaction injection molding (SRIM) 9, 123, 127, 128, 131, 132
 styrene-butadiene rubber (SBR) 553, 557
 styrene/butadiene/styrene (SBS) 329
 styrene/ethylene-butylene/styrene (SEBS) structure 329
 styrene maleic anhydride (SMA) 119
 sulfonated poly(ether ether ketone)
 – thermal stability 694
 sulfur cure systems 554
 surface characteristics 153, 154, 171, 172, 219, 342, 549, 734
 surface free energy 139, 148, 154, 155, 157, 159, 160–162, 165, 167, 172, 173, 213, 218, 219, 346, 352, 600
 surface modification 256
 – of fibers 218, 219
 – of matrix polymers 219
 surface oxidation on carbon fibers 155
 surface swelling 324
 surface tension 139
 – of carbon fibers 139
 surface-to-volume ratio 686
 surface treatment 138
 – of carbon fibers 139–141, 143
 – dry methods 138
 – of reinforcements for composite materials 85
 – of silica fiber 342, 548, 549
 – wet methods 138
 swelling index 477
 SymaLite technology 751
 symmetric weaving (SW) 399
 – interlacing loops 402
 – schematic drawing 402
 syndiotactic polystyrene composites.
 See s-PS/Kevlar composites (KSO)
 synthetic fiber-reinforced composites 220–222
 synthetic fibers 4, 210, 211, 220, 276, 444
 synthetic polyisoprene 7
 synthetic polymers
 – hydrophobicity 698
 synthetic silica 340, 545
 – properties 546
- t**
- tangential tensile stress 427
 target assembly 42
 TechSIL 5000 conductive elastomer materials 769
 temperature curing cycles 728
 tensile deformation 318
 tensile force 371
 tensile fracture 413
 – fracture mechanisms, schematic drawing 414
 tensile modulus 143
 tensile properties
 – of banana fiber 13
 – effect of fiber volume fraction on 732, 733
 – factors influencing 592
 – of NR/SBR blends 557
 – of PET fibers 280
 – of PET/PP microfibrillar composites 285
 – temperature-induced degradation and 222
 tensile strain 305
 tensile strength 12, 19, 187, 192, 194, 221, 228, 229, 279, 318, 356, 358, 439, 476, 557, 584, 585, 684, 685, 692, 705–707, 738, 739, 761, 777
 – of CaCO₃ composites 684
 – of glass fibers 194
 – of mica/PP composites 685
 – predicting models 706
 – graphical representation 705
 tensile stress 39, 305, 428
 tensile stress-strain curve 142
 tensile surfaces 369
 tensile tests 396, 731
 tensile toughness 732
 terephthalic acid (PTA) 276
 testing methods, schemes of 320
 tetrahydrofuran (THF) 343
 tetrasulfide silane, bis-(3-triethoxysilylpropyl) tetrasulfide (TESPT) 550
 – silane coupling agent 557
 textile composites 4, 14, 370, 372, 388, 395, 412, 470–478
 – reinforcements 366, 367, 388
 – mechanical behavior 365
 textile fibers 329
 textile reinforcements 365, 375
 – geometry of 470
 – mechanical behavior of 470
 textile sheets
 – bending stiffness 372

- T-glass 187, 188
- thermal conductivity 220, 575, 577, 579–583, 588
 - models 595–597
 - of polyamide/Cu composites 581
- thermal decomposition 696
- thermal diffusivity 473
- thermal expansion coefficients 142, 583
- thermal properties 195, 196, 216, 220, 225, 226, 230, 245, 252, 473, 474, 693–696
- thermal protection systems 359
- thermodynamic methods 15
- thermoelastic waves 18
- thermogravimetric analysis (TGA) 346
- thermoplastic composites 209, 306, 324
 - character 111
 - manufacturing techniques
 - classification 121, 122
 - feasible series lengths 112, 123
- thermoplastic elastomers 7, 329, 557
- thermoplastic injection molding 128
- thermoplastic matrix 286
 - composites properties 115
 - prepreg tapes 117
- thermoplastic microcomposites 673
- thermoplastic polymer composites 7, 111–120, 123, 196, 299, 673, 684
 - compression molding 115–117
 - diaphragm forming 119, 120
 - extrusion 115
 - injection molding 112–115
 - mica, use 673
 - thermoplastic composite manufacturing techniques, classification 120
 - thermoplastic prepreg lay-up 117, 118
 - thermoplastic tape winding 118, 119
- thermoplastic polyurethane/mica composites 685
- thermoplastics
 - filled with metallic particles, transverse thermal conductivity 582
 - pultrusion, scheme presentation 119
- thermoplastic tape winding instruments
 - general scheme 118
- thermosets
 - filled with metallic particles, transverse thermal conductivity of 583
- thermosetting injection molding 128
- thermosetting polymer composites 123–132
 - bulk molding compound 127
 - centrifugal casting 124, 125
 - filament winding 128, 129
 - hand lamination 123, 124
 - manufacturing techniques, classification 130, 131, 132
 - prepreg lay-up 125
 - pultrusion 129, 130
 - reaction injection molding (RIM) 127, 128
 - resin transfer molding 126
 - sheet molding compound 127
 - spray-up 124
 - structural reaction injection molding (SRIM) 127
 - thermosetting injection molding 128
 - vacuum-assisted resin transfer molding 126
- thermosetting polymers 7, 9, 123, 472, 771
- thermosetting resins 767
- thermostability 209
- Thornel-25 fibers 140
- three-axis carbon/epoxy composite
 - tensile fracture 413
- three-axis orthogonal composite 398
 - tensile fracture 413
 - xy-section 399
- three-axis orthogonal fabric 397
 - schematic drawing 397
- three-component composite 655
- three dimensional transmission electron microscopy (3D-TEM) 516
- three dimensional woven fabric composites 393
 - design 429–431
 - failure behavior 412–428
 - formation 396–407
 - general characteristics 394–396
 - greater nonuniformity 394, 395
 - higher fiber crimp 395
 - interlacing loops role 428, 429
 - lower fiber volume fraction 395
 - lower stress-to-yield and higher strain-to-failure 395, 396
 - material testing, difficult in 396
 - modeling 407–412
 - more complex in damage mechanisms 396
 - multidirectional structural integrity 394
 - near-net-shape design 394
 - solid rods use 405–407
 - three-axis orthogonal weaving 396–399
 - weaving schemes design 399–403
 - yarn distortion 403–405
- three-layer structure geotextiles
 - schematic diagram 456
- three-point bending tests 415, 730
- time-dependent latch elements 720
- time–temperature superposition principles 723, 742

- Timoshenko bending theory 737
- titanium dioxide 295
- TMCS-treated silica fiber 353
- toluene
 - swelling in, Kraus plots 567
- torque 301
- torsional stiffness 774
- toughness 112, 115, 141, 150, 161, 197, 209, 218, 297, 299, 310, 678, 692, 760, 772, 776
- transcrystalline layer
 - formation of 323
- transmission/reflection method 625
- transmission tower utility pole 765
- transmissivity 455–457, 459
 - decrease ratio 452, 453
 - disadvantage 450
 - of nonwoven geotextiles with compressive stress 451, 452
 - value 454
- transverse matrix 415
 - cracking 415
- transverse shear test 424
 - damaged specimens 425
 - fixture 425
 - fracture in 3D C/C composite 426
- transverse yarns
 - matrix cracks 420
- u**
- ultrahigh modulus PE
 - structural schemes for 316
- ultrahigh molecular weight PE (UHMWPE) fibers 318, 319
 - ballistic properties of 329
 - bundles 325
 - CF-reinforced layers 329
 - coating of 326
 - coefficient of thermal expansion (CTE) of 319
 - dilute tetralin solution of 324
 - ethylene/propylene/diene rubber (EPDM) matrix 329
 - glass fiber (GF)
 - and CF 328
 - combination of 327
 - oxygen plasma treatment for 328
 - powder surface 760
 - surface modification of 320, 327
- uniaxial anisotropy 634
- unidirectional (UD) composites
 - fiber layers 319
 - reinforced composite 197
 - thermomechanical behavior of 470
 - vinyl ester composites
 - short-beam shear test 320
- unidirectional weaving (UW) 399
 - interlacing loops 400
 - schematic drawing 400
- unit-cell 407
 - schematic drawing 407, 408
- unit woven cell
 - loads on 367
- v**
- vacuum-assisted resin transfer molding (VARTM) technology 126, 766, 784
 - schematic presentation 126
- vacuum bag 125
- vacuum infusion (VI) 472
- van der Waals attraction 137
- van der Waals force 154
- variation constant 457
- veritex 782, 783
- Vestamid LR1-MHI components. See also electroplating, of injection-molded components
 - electrodeposition, deposition fail to occur in, 495
 - surface resistance distributions, and screw feed rate, 496, 497
- vinyl ester 5, 320, 328, 476, 766, 767
- vinyltrimethoxysilane (VTMS) coupling agent 343
- virtual work, principle 367–369
- viscoelastically prestressed polymeric matrix composite (VPPMC) 716
 - accelerated aging
 - impact tests 726–728
 - viscoelastic recovery 722, 723
 - applications 743, 744
 - batch of test, typical tensile stress–strain plots for 731
 - in composite materials 715, 716
 - feasibility 716
 - flexural modulus values 730
 - force–time measurements 724–726
 - with higher fiber content 729–733
 - flexural properties 729–731
 - meeting the objectives 729
 - tensile properties 731–733
 - impact toughness 739
 - improved mechanical properties mechanisms 737–739
 - background 737, 738
 - flexural stiffness 738
 - impact toughness 739
 - tensile strength 738, 739
 - long-term performance 728, 729

- polymeric deformation mechanical model 719–722
 - potential applications 740–742
 - crashworthiness 741, 742
 - enhanced crack resistance 742
 - high velocity impact protection 740, 741
 - preliminary investigations 716–719
 - initial mechanical evaluation, impact tests 718, 719
 - objectives 716, 717
 - viscoelastic recovery, creep conditions 717
 - visual evidence 717
 - principles 716
 - processing aspects 733–737
 - background 733, 734
 - fiber properties 734, 735
 - fibers in composite samples, geometrical aspects 735–737
 - representative optical micrograph sections of test 736, 737
 - tensile properties of test 732, 733
 - time–temperature aspects 719–729
 - typical appearance of test 719
 - viscoelastic bilaminates 18
 - viscoelastic deformation 720
 - viscoelastic modulus 22
 - viscoelastic recovery force 733
 - viscoelastic recovery stress 725
 - viscoelastic strain 717
 - viscosity 301
 - Voigt and Reuss average modulus 90, 701
 - volume-averaged strain tensor 91
- w**
- water-activated polyurethane 758
 - water barrier 437, 443
 - wave propagation 18, 20
 - in elastic–viscoelastic bilaminates 21–23
 - time–distance diagram 39
 - wear resistance 759
 - weaving processes 393, 396, 402, 429
 - fabrics from 403
 - weft yarns 478
 - Weibull distribution function 721
 - Weibull/KWW-based equation 724
 - Weibull’s probabilistic approach 84, 94–96, 97
 - probability distribution function 94, 99
 - Weibull’s statistical approach 94
 - Weibull statistical function 99
 - wider test 197
 - wind energy 177, 178
 - wind turbine blades 204
 - wood 4
 - tennis rockets 777
 - woven cell modeling 384–387
 - woven characteristics 475
 - woven fabrics 379, 470, 471, 474
 - composite materials 470, 471
 - reinforced composites 470
 - woven glass reinforcements 199
 - woven styles 475
 - woven unit cell
 - bending behavior 372, 373
 - biaxial tensile behavior 369, 370
 - in-plane shear behavior 370–372
 - load resultants 366, 367
 - virtual work principle 367–369
 - woven yarns 366
- x**
- X-ray photoelectron spectra (XPS) 320
- y**
- yarn distortion
 - types 403
 - yarn fracture
 - schematic illustration 424
 - yarn split 420
 - yarn swelling 405
 - yield point 430
 - Young–Laplace equations 93
 - Young’s modulus 7, 11, 142, 193, 279, 286, 287, 296, 322, 349, 356, 385, 429, 501, 504, 505, 507, 508, 509, 511, 584, 585, 590, 687, 700–705, 707, 759
 - models for prediction 702, 703
 - YRR composite
 - weaker planes 415
- z**
- Z-glass 188
 - zinc oxide 780
 - zylon 777