

Index

a

α -quinquethiophene (α -T5) 362, 363
 AA + BB approach 14, 16
 acenes 105, 108
 acoustic ink-jet printing 288–289
 active matrix backplanes 4, 220
 active matrix organic light-emitting diode (AMOLED) display 355, 356
 all-printed resistor loaded inverters 215
 ALOHA anticollision protocol 392, 393
 ambipolar LEFETs
 – blends with bulk heterojunctions 362–363
 – device characteristics 360–361
 – device modeling 375–377
 – double layers and lateral heterojunctions 363–365
 – toward electrically pumped organic lasers 377–380
 – single semiconductor FETs 365–366
 – asymmetric electrodes and 367
 – bottom contact/top gate electrodes and 368–375
 – intrinsic ambipolar transport in organic semiconductors 366–367
 – narrow bandgap semiconductors and 368
 ambipolar semiconductors 138
 analog and mixed-signal organic circuit design considerations 401–402
 – circuit design technologies for analog building blocks 403–407
 – technology challenges 402
 analog circuits 397
 anthracene, silylethynyl 121
 anthracene diimides 167, 168, 169–170
 anthradithiophenes 131
 – fluorinated 126

anticollision protocol 392, 393
 Arrhenius dependence 94
 Auger electron yield (AEY) 50

b

benzene diimides 167, 168
 bilayer lipid membrane (BLM) 222, 223
 bipolar field-effect transistors. *See* ambipolar light-emitting FETs
 bottom-contact/bottom-gate geometry 140
 bottom contact/top gate electrodes, ambipolar FETs with 368–375
 bottom-gate, top-contacts (BGTC) configuration 308, 309, 315
 bottom-gated thin-film transistor, process flow for 252
 Bragg's law 31
 bulk-heterojunction (BHJ) 41

c

capacitatively coupled RFID tags 389–390
 charge transport 67, 328–334, 340, 342
 – disordered materials
 – comparison with experiments 91–101
 – computational methods 88–91
 – dispersive and nondispersive transport 76
 – transport models 76–88
 – types of 73–75
 – organic single crystals 68
 – band and bandlike 72–73
 – band transport and experimental evidence 69–72
 – band transport general conditions 68–69
 clocked flip-flops 144
 coffee ring 248, 250
 coffee stain effect 340
 common-mode feedback (CMFB) 403, 404

- complementary circuits (CMOS) 137, 141–145, 166, 176, 178, 296
 - inverter 142, 170, 180, 188, 397
 - structure and voltage characteristics of logic gates 143
 - complementary logic 399–400
 - complementary metal-oxide semiconductor (CMOS) circuits. *See* complementary circuits
 - conducting probe atomic force microscopy (CP-AFM) 330
 - conductive inks for ink-jet printing of electrodes and interconnections 290–293
 - conjugated semiconductors. *See* complementary circuits (CMOS); field-effect transistors (FETs); organic thin-film transistors (OTFTs)
 - continuous ink-jet printing 283, 284
 - correlated disorder model (CDM) 97
 - cross-linked poly(methylmethacrylate) (C-PMMA) 313
 - crystalline phase 5, 6, 14, 15
 - crystal packing 107, 108–109, 123
 - device studies 112–114
 - electronic structure studies 110–111
 - organic light emitting diodes and photovoltaics, using silylethynyl pentacenes 116–119
 - perylene diimide derivatives 147
 - silylethynyl-substituted acenes, in organic electronics 120–121
 - silylethynyl-substituted pentacene properties 109–110
 - silylethynyl pentacene-based polymers 115–116
 - silylethynyl pentacene n-type semiconductors 119–120
 - silylethynyl pentacenes and polymer blends 114–115
 - current–voltage characteristics 357, 360–361, 362, 364, 375, 376
 - cyclohexylbenzene (CHB) 303, 304
 - Cytop. *See* poly(perfluorobutenylvinylether)
- d**
- density of states (DOS), Gaussian 76, 77, 81, 82, 84, 86, 87, 88, 92, 93, 99–100
 - depletion-load. *See* zero-vgs-load
 - deposition method 337–338
 - D flip-flop 145, 153, 177, 217
 - diagonal disorder model 74
 - N,N'*-dialkyl-naphthalenedicarboximide-dithiophene (NDIR-T2) 186
 - N,N'*-dialkylperylene-dicarboximide-dithiophene (PDIR-T2) 186
 - differential scanning calorimetry (DSC) experiments 15
 - diffraction 28, 32, 37, 40, 44
 - 2, 8-difluoro-5,11-bis (triethylsilylethynyl) anthradithiophene (F-TES ADT) 330, 334, 335, 337, 338, 339, 340, 341, 344
 - digital circuits 397
 - digital organic circuit design considerations 397–398
 - diode-load logic 398
 - diperfluorohexyl-nTs (DFH-nTs) 157, 158, 159
 - disordered materials
 - disorder effect on charge transport 75–76
 - – comparison with experiments 91–101
 - – computational methods 88–91
 - – dispersive and nondispersive transport 76
 - – transport models 76–88
 - types of 73–75
 - dispersive transport 76
 - N,N'*-ditridecylperylene-3,4,9,10-tetracarboxylic diimide (PTCDI-C₁₃H₂₇) 362, 363
 - drop-cast films 112
 - droplet ejection 245, 246, 247
 - drop on demand (DOD) ink-jet printing 283, 285–286
 - acoustic ink-jet printing 288–289
 - conductive inks for ink-jet printing of electrodes and interconnections 290–293
 - electrohydrodynamic-jet (e-jet) printing 289–290
 - piezoelectric ink-jet printing 286–288
 - thermal ink-jet printing 286
 - dual V_T logic 400–401
 - dynamic disorder 73, 74
- e**
- effective/average mobility 20
 - electrochemical gating 199
 - electrohydrodynamic-jet (e-jet) printing 289–290, 298, 300
 - electrolyte-gated organic transistors 197
 - applications
 - – active-matrix display backplanes 220
 - – organic electrochemical transistors, as chemical sensors 220–224
 - – printable low-voltage polymer transistors and circuits 213–220
 - development of 199–202
 - electrical characterization of

- – accumulated charge determination 206–209
- – charge transport at ultrahigh carrier densities 211–213
- – low-voltage operation 204–205
- – reference electrode 205–206
- – switching time 209–211
- gating mechanism in 202–204
- structure and operating mechanisms 198–199
- electronically active textiles 219
- electrophoretic displays (EPDs) 4, 5
- energy-space master equation (ESME) approach 90
- engraving, electrochemical 243, 244
- E-skin fabrication 297
- etching 243

f

- femtoliter. *See* subfemtoliter ink-jet
- field-effect enhanced LEDs 381, 383
- field-effect mobility, within OFETs 20
- field-effect transistors (FETs) 71, 72, 91, 138–141, 151, 152, 176, 189, 332, 355. *See also* light-emitting field-effect transistor (LEFET)
- film patterning, by differential microstructures 346
- finite difference time domain (FDTD) method 359
- flexographic printing 241, 242
- flip-flop 144–145, 153, 177, 217
- fullerenes 163–167, 165

g

- gate dielectrics, for downscaled organic TFTs 309–310
 - high-*k* dielectrics 310–311
 - ultra-thin dielectrics 312–313
- Gauss error function 48
- Gaussian disorder model (GDM) 94
- gold electrodes 366
- gold nanoparticle inks 292
- gravure printing 241–245
- grazing-incidence X-ray diffraction (GIXD) 38–47, 40, 44, 46, 47

h

- half-wave rectifier 395
- heteroacenes 105, 121
 - -based photovoltaics, silylethynyl 132
 - -based polymers, silylethynyl 131
 - blends of polymers and silylethyne-substituted 130–131

- crystal packing 123
- device studies 123–129
- high-performance chromophores 122
- silylethyne-substituted 122–123
- silylethynyl, for n-type applications 129–130
- hexamethyldisilazane (HMDS) 15
- highest occupied molecular orbital (HOMO) energy level 3, 7, 11, 12, 15, 68, 159
- high-*k* dielectrics 310–311
- highly oriented pyrolytic graphic (HOPG) 56, 57
- high yield printing of single-droplet nanoscale electrode arrays 304–308
- Hooge parameter 333, 335, 336
- hopping 74, 75, 81, 82, 85, 86, 92, 94, 96, 98

i

- indirect laser method 243
- inductively coupled RFID tags 390–391
 - integrated RFID transponder 393–397
 - transponder chip 391–393
- ink-jet printing 245–247
- ink-jet printing, of downscaled organic electronic devices 281
 - downscaled organic thin film transistors printing 308
 - – gate dielectrics for 309–313
 - – mask-free, all solution processed SAP TFTs 315–316
 - – organic TFTs printed with subfemtoliter printer 314–315
 - – requirements 308–309
 - – self-aligned gate contacts for fast-switching transistors 316–319
 - high-resolution printing, of highly conductive electrodes 297–298
 - – high yield printing of single-droplet nanoscale electrode arrays 304–308
 - – ink-jet printing assisted by surface-energy patterns 301
 - – ink-jet printing of narrow linewidths 298–300
 - – self-aligned printing (SAP) 302–304, 305, 306, 307
 - technologies, tools, and materials 282
 - – aerosol jet printing 285
 - – continuous ink-jet printing 284
 - – DOD ink-jet printing technologies 285–293
 - – organic electronic devices 293–297
 - – principle of operation 282–284

- ink-jet technologies 255–257
 - large-area printed electronics, discussion and future prospects of 277–278
 - organic transistors with source/drain electrodes printed using picoliter ink-jet
 - – large area pressure sensor sheet 269–270
 - – printed organic transistor active matrix 268–269
 - – transistor characteristics with changing droplet volume 264–267
 - organic transistors with source/drain electrodes printed using subfemtoliter ink-jet
 - – TFTs on polyimide gate dielectric 270, 272
 - – TFTs with self-assembled monolayer as very thin gate dielectric 272–277
 - picoliter printing 257–259, 259
 - silver nanoparticle ink 257, 258
 - subfemtoliter ink-jet 260–261
 - – droplets on organic semiconductors 261–264
 - – ejection mechanism 261
- intaglio wells 242–243
- inverted region 81
- inverter 397
- ion-sensitive field-effect transistors (ISFETs) 200, 221, 222

k

- kinetic Monte Carlo (KMC) algorithm 91

l

- Langmuir–Blodgett technique 57
- light emitting diodes (LEDs)
 - field effect enhanced 381, 383
- light-emitting field-effect transistor (LEFET) 356, 357
 - ambipolar
 - – blends with bulk heterojunctions 362–363
 - – device characteristics 360–361
 - – device modeling 375–377
 - – double layers and lateral heterojunctions 363–365
 - – single semiconductor FETs 365–375
 - – toward electrically pumped organic lasers 377–380
 - unipolar 357–360
- line formation 245
- liquid crystal displays (LCDs) 4
- lowest-unoccupied molecular orbital (LUMO) 68, 145–146, 159, 358

m

- Manchester data encoding 392–393
- Marcus theory 80–81, 91
- mask-free, all solution processed SAP TFTs 315–316
- master equation approach 89–90, 100
- master–slave D flip-flop 145
- mean medium approximation (MMA) 99
- metal-insulator-semiconductor-type organic light-emitting transistor (MIS-OLET) 381, 382
- metal-oxide-semiconductor field-effect transistor (MOSFET) 356
- microelectrochemical transistors 200–201, 202, 223, 225
- Miller–Abrahams model 79–80, 81, 86
- mobility edge 76
- molecular orientation 50, 52, 54, 56, 57
- molecular semiconductors 151
 - fullerenes 163–167, 165
 - phthalocyanine derivatives 151–157
 - rylene and diimide derivatives 167–179, 168
 - small n-channel 179–181
 - thiophene derivatives 157–163
- molecular weight, of polymers 6–7, 10, 12, 14, 16
- monothieno acenes 125
- Monte Carlo technique 88
- Mott's variable-range hopping 86
- multiple trapping and release (MTR) model 76, 78, 84, 86

n

- NAND logic gates 216–217, 397
- nanoparticle inks 292–293
- naphthalene diimides 167, 168–169, 168
- narrow bandgap semiconductors 368
- n-channel semiconductors 138
 - molecular semiconductors
 - – fullerenes 163–167, 165
 - – phthalocyanine derivatives 151–157
 - – rylene and diimide derivatives 167–179, 168
 - – small n-channel 179–181
 - – thiophene derivatives 157–163
 - polymeric semiconductors 181–189, 182, 183
- near-edge X-ray absorption fine structure (NEXAFS) spectroscopy 47, 55
 - background and general features 47–48
 - chemistry determination by 52–54
 - experimental considerations 48–52
 - horizons for 58–59

- orientation analysis in organic semiconductors 54–57
- nearest-neighbor hopping (NNH) 78, 79, 82
- N*-methyl-2-pyrrolidone (NMP) 268
- noise margin 399
- nondispersive transport 76
- nonrelief pattern lithography 128
- normal region 81
- n*-type metal-oxide semiconductor (NMOS) 141, 144
- n*-type transistors 402
- o**
- off-diagonal disorder 74
- offset printing 241–242
- ON/OFF ratio 20–21
- open-circuit voltage 118
- order and orientation characterization, in semiconducting polymers 27
- near-edge X-ray absorption fine structure (NEXAFS) spectroscopy 47, 55
 - – background and general features 47–48
 - – chemistry determination by 52–54
 - – experimental considerations 48–52
 - – horizons for 58–59
 - – orientation analysis in organic semiconductors 54–57
- X-ray diffraction (XRD) 28–29, 30
- grazing-incidence X-ray diffraction (GIXD) 38–47, 40, 44, 46, 47
- – thin-film 29–38
- organic electrochemical transistors, as chemical sensors 220–224
- organic electronic devices, ink-jet printing of 293, 297
 - OLEDs fabrication 294
 - organic photovoltaic cell fabrication 296–297
 - OTFTs fabrication 294–296
- organic field-effect transistors (OFETs) 3, 4, 5, 17, 19, 119, 139, 140, 327
 - conduction 19
 - device architecture 18
 - field-effect mobility within 20
- organic light emitting diode (OLED) displays 4, 5, 116, 281, 293, 356
 - fabrication 294
- organic photovoltaic cell fabrication 296–297
- organic RFID tags 388–389
 - capacitively coupled tags 389–390
 - inductively coupled tags 390–391
 - – integrated RFID transponder 393–397
 - – transponder chip 391–393
- organic thin-film transistors (OTFTs) 105, 197, 224–225, 281, 327, 328, 339, 387, 402
 - advanced film processing
 - – deposition under solvent vapors 342–344
 - – OTFTs patterning 344–348
 - – sensibility to processing details 340–341
 - – solvent annealing 341–342
 - downscaled printing 308
 - – gate dielectrics for 309–313
 - – mask-free, all solution processed SAP TFTs 315–316
 - – organic TFTs printed with subfemtoliter printer 314–315
 - – requirements 308–309
 - – self-aligned gate contacts for fast-switching transistors 316–319
 - electrolyte-gated
 - – applications 213–224
 - – development of 199–202
 - – electrical characterization of 204–213
 - – gating mechanism 202–204
 - – structure and operating mechanisms 198–199
 - fabrication 294–296
 - *n*-channel, material design and needs for
 - – contacts and dielectric 148–150
 - – electronic structure 145–148
 - *n*-channel semiconductors for
 - – molecular semiconductors 151–181
 - – polymeric semiconductors 181–189, 182, 183
 - printed with subfemtoliter printer 314–315
 - structure–processing–properties relationship in
 - – controlling film morphology by surface chemical modifications 334–337
 - – microstructure and mobility 331–333
 - – processing parameters affecting electrical properties 337
 - transport limits in crystalline semiconductors
 - – crystallinity and structural order role 328–329
 - – grain boundaries 329–331
 - – single crystals 331
- organic transistors, light-emitting 355–357, 378
 - ambipolar LEFETs
 - – blends with bulk heterojunctions 362–363
 - – device characteristics 360–361
 - – device modeling 375–377

- organic transistors, light-emitting (*contd.*)
 - – double layers and lateral heterojunctions 363–365
 - – toward electrically pumped organic lasers 377–380
 - – single semiconductor FETs 365–375
 - field-effect enhanced LEDs 381, 383
 - unipolar LEFETs 357–360
 - vertical light-emitting transistors 380–381
- P**
- partial electron yield (PEY) 50
- parylene 53
- p-channel semiconductors 138, 358
- pentacene 54, 180, 259, 260, 261, 262, 263, 264, 265, 267, 268, 273, 274, 275–277, 275, 341, 381
 - and derivatives 8–9
 - device studies 112–114
 - electronic structure studies 110–111
 - halogenated silylethynyl 120
 - organic light emitting diodes and photovoltaics, using silylethynyl pentacenes 116–119
 - silylethyne-substituted 106–108
 - – properties 109–110
 - silylethynyl pentacene-based polymers 115–116
 - silylethynyl pentacene n-type semiconductors 119–120
 - silylethynyl pentacenes and polymer blends 114–115
 - TIPS 109, 111, 112–113, 114, 117, 120
- perfluorobenzenethiol (PFBT) 113, 127, 334, 344–345
- percolation theory 78, 82–83
- perfluoropentacene 180
- perylene and higher rylene diimides 171, 172, 175
- [6,6]-phenyl-C61-butyric acid methyl ester (PCBM) 41, 164, 166, 296
- phonons 80
- phthalocyanine derivatives 151–157
- picoliter printing 257–259, 259
 - organic transistors with source/drain electrodes printed using ink-jet
 - – large area pressure sensor sheet 269–270
 - – printed organic transistor active matrix using ink-jet 268–269
 - – transistor characteristics with changing droplet volume 264–267
- piezoelectric ink-jet dispenser 245, 246
- piezoelectric ink-jet printing 286–288
- polaron model 80
- polishing 243–244
- poly(2,5-bis(3-alkylthiophen-2-yl)thieno[3,2-*b*]thiophene (pBTTT) 14–16, 44, 45, 295, 319
- poly(3,3''''-didodecyl quaterthiophene) (PQT) 41, 53
- poly(3,4-ethylenedioxythiophene):poly(styrenesulfonate) (PEDOT:PSS) 218, 220, 221, 222, 223, 290, 299, 301, 302–303, 304, 311, 318, 398
- poly(3-alkylthiophenes) 9–12
- poly(3-hexylthiophene) (P3HT) 9, 10, 11, 34, 41, 56, 57, 200, 203, 214, 218, 296, 297
- poly(9,9-dioctylfluorene-co-benzothiadiazole) (F8BT) 368, 370, 371, 372, 375
- poly(benzobisimidazobenzophenanthroline) (BBL) 183–184
- poly(bithiophene-cross-conjugated thiophene (pBTCT) 12–13
 - polymerization of 14
- poly(dimethylsiloxane) (PDMS) 53
- poly(methyl methacrylate) (PMMA) 370
- poly(perfluorobutenylvinylether) 313
- poly(styrene-block-ethylene oxide-block-styrene) 311
- poly(vinyl phosphonic acid-co-acrylic acid) (P(VPA-AA)) 204, 311
- polyelectrolytes 311
- polymeric aromatic semiconductors 7
- polymer light-emitting diodes (PLEDs) 220
- polymer light-emitting electrochemical cells (PLECs) 220
- polymer semiconductors 181–189, 182, 183
 - thiophene-based polymers
 - – poly(2,5-bis(3-alkylthiophen-2-yl)thieno[3,2-*b*]thiophene (pBTTT) 14–16
 - – poly(3-alkylthiophenes) 9–12
 - – thienothiophene copolymers 12–14
- Poole–Frenkel mechanism 95–97
- postedge normalization 51–52
- principle printed line behaviors 248
- printable low-voltage polymer transistors and circuits 213–220
- printed transistor 251
- printing techniques, for thin-film electronics 237
 - motivation for devices 237–238
 - pattern formation, during printing 247–250
 - printed device considerations 250–253
 - requirements, for electronic fabrication 239
 - survey, for printed electronics 239–240

- – gravure, flexographic, and offset printing 241–245
 - – ink-jet printing 245–247
 - – screen printing 240–241
 - protonated polyvinylphenol (PVP) 201
 - p-type metal-oxide semiconductor (PMOS) 141
 - p-type transistors 402, 403
 - pulse-radiolysis time-resolved microwave photoconductivity (PR-TRMC) 91
- r**
- radio frequency identification tags (RFIDs) 296
 - organic
 - – capacitively coupled tags 389–390
 - – inductively coupled tags 390–397
 - reader 388
 - regioregular (RR) poly(3-hexylthiophene) (P3HT) 9–10
 - resonant soft X-ray reflectivity (RSoXR) 59
 - resonant soft X-ray scattering (RSoXS) 59
 - ring oscillator 144
 - rocking curves 32, 34–36, 35
 - rubrene 377
 - crystal packing for 107
 - rylene and diimide derivatives 167–179, 168
- s**
- scanning Kelvin probe microscopy (SKPM) 127, 330, 333
 - scanning transmission electron microscopy (STEM) 58
 - scanning transmission X-ray microscopy (STXM) 48–49, 58
 - Scherrer equation 38
 - Schrödinger equation 74
 - screen printing 240–241
 - self-aligned gate contacts, for fast-switching transistors 316–319
 - self-aligned printing (SAP) 302–304, 305, 306, 307
 - self-assembled monolayers (SAMs) 15, 22, 289, 312, 334, 345
 - TFTs with, as very thin gate dielectric 272–277
 - self-patterning 345
 - sexithiophene 8
 - shift registers 152
 - sigma-delta analog-to-digital converter design 407
 - silver nanoparticle ink 257, 258, 292
 - silylethynyl acene synthesis 108
 - single crystals, organic 68
 - band and bandlike 72–73
 - band transport and experimental evidence 69–72
 - band transport general conditions 68–69
 - single-crystal transistors 129
 - single semiconductor ambipolar FETs 365–366
 - asymmetric electrodes and 367
 - bottom contact/top gate electrodes and 368–375
 - intrinsic ambipolar transport in organic semiconductors 366–367
 - narrow bandgap semiconductors and small molecule semiconductors 368
 - pentacene and derivatives 8–9
 - sexithiophene 8
 - solar cells
 - polythiophene-based 119
 - silylethynyl pentacene 118
 - soluble small-molecule organic semiconductors 327
 - advanced film processing
 - – deposition under solvent vapors 342–344
 - – OTFTs patterning 344–348
 - – sensibility to processing details 340–341
 - – solvent annealing 341–342
 - intrinsic defects 329, 331
 - mobility 327, 329, 330–345
 - structure–processing–properties relationship in OTFTs
 - – controlling film morphology by surface chemical modifications 334–337
 - – microstructure and mobility 331–333
 - – processing parameters affecting electrical properties 337
 - transport limits in crystalline semiconductors
 - – crystallinity and structural order role 328–329
 - – grain boundaries 329–331
 - – single crystals 331
 - solvent 338–340
 - space-charge limited current diode (SCLC) 91
 - spin casting process, solvent 342
 - static disorder 74
 - Stille coupling 13, 14, 16
 - subfemtoliter ink-jet 256–257, 260–261
 - droplets on organic semiconductors 261–264
 - ejection mechanism 261
 - organic TFTs printed with 314–315

- subfemtoliter ink-jet (*contd.*)
 - organic transistors with source/drain electrodes printed using
 - – TFTs on polyimide gate dielectric 270, 272
 - – TFTs with self-assembled monolayer as very thin gate dielectric 272–277
- surface-energy patterns, ink-jet printing assisted by 301
- switching response time 209–211

- t**
- tetracene 357–358, 357, 358
- thermal ink-jet printing 286
- thieno[3,2-*b*]thiophene monomer 16
- thienothiophene copolymers 12–14
- thin-film transistors (TFTs) 138, 146, 157, 173, 178, 179, 181, 187, 189, 256, 265, 266, 274
 - circuits, on flexible substrate 347
 - polyimide gate dielectric and 270, 272
 - self-assembled monolayer as very thin gate dielectric and 272–277
- thin-film X-ray diffraction 29–38
- thiophene 8
 - derivatives 157–163
- thiophene-based polymers
 - poly(2,5-bis(3-alkylthiophen-2-yl)thieno[3,2-*b*]thiophene (pBTTT)) 14–16
 - poly(3-alkylthiophenes) 9–12
 - thienothiophene copolymers 12–14
- time-of-flight (ToF) technique 70, 91, 94, 366
- top-contact/bottom-gate geometry 140
- top-gate, bottom-contacts (TGBC) configuration 308, 309, 311
- total electron yield (TEY) 50
- transfer matrix 74
- transistor-level design, with organic transistors 397
 - analog and mixed-signal organic circuit design considerations 401–402
 - – circuit design technologies for analog building blocks 403–407
 - – technology challenges 402
 - digital organic circuit design considerations 397–398
 - – complementary logic 399–400
 - – dual V_T logic 400–401
 - – unipolar logic 398–399
 - sigma-delta analog-to-digital converter design 407
- transistors, organic semiconductor materials for 3
 - device physics and architecture 18–22
 - material properties of organic semiconductors 5–8
 - polymer semiconductors
 - – thiophene-based polymers 9–16
 - semiconductor blends 17
 - small molecule semiconductors
 - – pentacene and derivatives 8–9
 - – sexithiophene 8
- transponder chip 391–393
- transport energy (TE) model 78, 84–85, 86, 98
- traps 75
- triethylsilylethynyl anthradithiophene (TES ADT) 330, 341, 342, 343

- u**
- ultra-thin dielectrics 312–313
- unipolar LEFETs 357–360
- unipolar logic 398–399

- v**
- variable-range hopping (VRH) 78, 79
- vertical light-emitting transistors 380–381
- viscosity 245
 - ink 242, 244

- w**
- Warren–Averbach method 38
- wide-angle x-ray scattering (WAXS) 43

- x**
- X-ray absorption near-edge structure (XANES) spectroscopy. *See* near-edge X-ray absorption fine structure (NEXAFS) spectroscopy
- X-ray diffraction (XRD) 28–29, 30, 334
 - grazing-incidence X-ray diffraction (GIXD) 38–47, 40, 44, 46, 47
 - thin-film 29–38
- X-ray photoelectron spectroscopy (XPS) 52
- xylene 303

- z**
- zero-vgs-load 398, 402, 405