#### а

A420 adhesive 277 acetone 50 acid bath etching 363-364 acrylics 13 AC-type strain amplifiers 300 adherend-adhesive interface 119 adherend bonding 16 adherend radii 48 adherends 16-17, 22-24, 52-53, 98, 111.309 - aerospace-grade aluminum 52 – asymmetric 195 - butt joint 116 - carbon-epoxy 188 – debonded 411 - deformation and rotation 29, 38 – end-notched flexure (ENF) 179 - flat 18, 29-30 - flexible 52-53, 230 - geometry of 40 - isotropic 402 - metallic 98, 103, 111 – peel 411 - quasi-static testing of thick adherend shear test specimens 126 - rigid 52 - steel 109 - symmetric 197, 199 - thickness 31 – upper 19–20 adherends/adhesive relative stiffness 186 adherend thickness ratio of ratio of four (ADCB4) 369 adherend thickness ratio of two (ADCB2) 369 adhesion failure 118 adhesive application and assembly

- bulk specimens, preparation of 6 - butt joints 39-40 - end-notched flexure (ENF) 180-182 - flexible-to-rigid peel specimens, preparation of 53-54 - lap joint with flat adherends 18-21 - thick adherend shear test (TAST) specimens 29 - T joints specimen 49 adhesive assembly conditioning 326-327 adhesive displacement, measurement of 82 - 83adhesive-free edges 35 adhesive spew fillets 15 adhesive thickness 38, 126, 129-130, 133-135, 137-140, 147-148, 180, 236, 239, 249, 277, 302, 346, 353, 360, 366, 371, 373.382 adhesive toughness 46 aerospace-grade aluminum adherends 52 air coolants 7 aluminum alloy honeycomb 256 aluminum specimen 15-16 anaerobic adhesives 155 analog-digital (AD) converters 300 anisotropic mechanisms 89 Arcan assembly design 33 Arcan fixture 420, 422 - deformation of 149 Arcan test, modified 147 - adhesive behavior under shear loads 151 - 152- deformation of the adhesive 154 - experimental results under shear monotonic loadings 149-151 - measurements 148-149

- peel stress-shear stress diagram 153

Testing Adhesive Joints: Best Practices, First Edition.

Edited by Lucas F.M. da Silva, David A. Dillard, Bamber Blackman, and Robert D. Adams. © 2012 Wiley-VCH Verlag GmbH & Co. KGaA. Published 2012 by Wiley-VCH Verlag GmbH & Co. KGaA. 427

Arcan test, modified (contd.) - strength envelope in terms of stresses 153 - 154 von Mises equivalent stress-hydrostatic stress diagram 153 - Young's modulus 153 Arcan-type device 69-70 Arcan (V-notched plate) test - comparison of bulk and joint Arcan tests 111 - 112 comparison with other shear methods 111 - 112- fixtures and specimen 104-107 - - bonding fixture 107 - - joint specimens 107 -- used at the NPL 105-106 - measurement principles 107-112 – crosshead measurement 110 - - finite element (FE) stress analyses 108 -- gauge length 110-111 – – maximum shear stress 107 – peak shear stress 108 -- shear strain 109-110 – stress concentration at ends of specimen 107 – – tensile stress 108 asymmetric adherends 195 asymmetric four-point bending (AFPB) fixture 100 atomic force microscope (AFM) 414 automatic damping measurement 399-402 AV119 epoxy adhesive 277 b

beam on elastic foundation (BOEF) 221 beam-on-elastic-foundation model 373 beam theory including bending rotations (BTBR) 185 biaxial extensometers 83 bimaterial curvature tests - analysis 408-409 - average in-plane stress in coating 404 - biaxial modulus of the coating 404 - concept of using curvature changes 403 and glass-transition temperature 403 - specimen configuration 404-406 - specimen preparation 406 - stress relaxation, measurement of 408 - test procedure 406-408 - use of noncontact displacement measurement techniques 403 bimaterial strips, characteristics of 404 bismaleimides 400

bisphenol A epoxy formulations 166 blister test 414 Boeing/SACMA setup 94 bonded joint deformation, kinematics of 148-149 bonding jigs 56-57 bondline thickness 61-62 Brownian motions 320 buckling, prevention of 94 bulk adhesive conditioning 324-326 bulk modulus measurement 87, 89 - of a bonding material 90 bulk specimens, preparation of - under hydrostatic pressure – adhesive application -- curing technique 7 – defects present 7 – failure properties 2 -- internal metallic frame 2-3 - - principle, for producing plate specimens 2 - 3-- specimen machining 7 -- standard ISO 15166 3 -- standard NFT 76-142 2-3 – – surface finish 3 -- using a metallic frame 3-4 - - using silicone rubber frame 3-5 - - void reduction 2 by injection -- centrifuging process 10 – curing process 11 - - final specimen preparation and testing 11 - 12-- metallic frame 9-10 by pouring -- centrifuge technique 14-15 – – edge effects 8 -- effect of size 14 -- mixing process 13-14 -- one-part adhesives 13 – pouring the liquid adhesive into a mold 14 – single-part adhesives 13 -- two-part adhesives 13-14 bulk tensile test 93 "butterfly" specimen 104 butt joint adherends 116 - impact test using clamped split Hopkinson bar equipment 304-305 butt joint specimen 40 - adhesive application and assembly 39 - 40- alternative manufacturing method 40 - 42

- curing technique 40 - mold for 37-38 - quasi-static testing in tension - - bondline spacer, use of 114 – – bubble removal 116 – – joint geometry 113 - - mating of adherends 116 – of minimal bond thickness secured 115 - - overriding requirements 113 - - sample preparation 116-117 - - sample testing 117-118 -- standards 113, 117 - - tensile adhesion strength 117 – tensile butt joints, geometry of 114-116 - specimen cleaning 40 - substrate preparation 38-39

# С

calibration fixture 109 carbon fiber reinforced polymer (CFRP) 59 Cauchy-Green tensor 89 centrifuging process - in injection technique 10 - pouring technique 14-15 in pouring technique 14–15 CHEM (caisson hyperbare pour etudes de matériaux) 420, 422 Chip test 347-348 Ciba AV119 111 Ciba-Geigy AV119 108 circular punch test (CPT) 417 - theoretical model 418-419 clamped Hopkinson bar – clamping system 306 - combined impact tests 304-308 - configuration of 298-300 - deformation of the specimen 302 - hydraulic actuator 299 - impact strength of adhesively bonded joints 303 - impedance matching 301 Mohr's stress circles of stress 304 - notched bolt 299 strain wave propagation in 301 - tensile impacts 300-303 -- tests 304 - tensile normal stress to the joint 307-308 - tests of tubular butt joints 304-305 torsional impacts 303 -- tests 304 - types of clamping systems 299

- velocity of stress waves in materials 298 - Young's modulus 301-302 clip-on gage 353 coefficient of friction 94 cohesive failure in adhesive 145 collision type split Hopkinson bar method 299 compact mixed mode (CMM) fracture test method - with an interface crack, analysis 205-208 - with an interlayer crack, analysis 202 - 205- fracture toughness for - - interface crack 210-212 -- interlayer crack 209-210 - stress intensity factors 201-202 - surface preparation and treatment 202 compact tension (CT) specimens 164 compliance calibration method (CCM) 185 compression chamber 90 compression piston 90 compression-shear tests 70, 151 computer numerically controlled (CNC) cutting machines 105 connector blocks 102 corrected beam theory (CBT) expression 173, 176 crack closure by COD method, measurement of 366-368 cracked lap shear (CLS) 358 - specimen 196, 198-199 crack-length-based data reduction scheme 188 crack opening displacement (COD) 366-368 cracks in adhesives 15, 21, 26, 30, 69, 184 - fracture toughness for - - interface crack 210-212 -- interlayer crack 209-210 creep 336 Crochet's equation 355 - delayed failure 352 curing technique 7 - bulk specimens, preparation of - - under hydrostatic pressure 7 - - by injection 11 - butt joints 40 - determination of actual curing time 11, 54,66 - double cantilever beam (DCB) test specimens 62 - exothermic reaction during 4

- velocity of dilatative waves 302

- lap joint with flat adherends 21

curing technique (contd.) - sealants and 54 - tapered double cantilever beam (TDCB) adhesive joint test specimens 62 thick adherend shear test (TAST) specimens 29 - T joints specimen 49-50 - use of thermocouple 7, 11, 14, 21, 40, 45, 49, 54, 57, 62 curvature changes of bimaterial or layered materials 403 curvature mismatch fracture test for subcritical debonding - data analysis 383-384 - specimen adaptations 384-386 - specimen configuration 380-381 - specimen preparation 381-382 test procedure 382–383 cyclic loading fatigue 355-358

# d

damping measurement 396-399 data acquisition system 300 DC-type strain amplifiers 300 dead loads 336 defects in bulk specimens 2 deformation kinetics - adherends 29 Arcan fixture 149 - Arcan test, modified 154 - bonded joint 148-149 - rubbery and soft materials 86 diaminodiphenyl sulfone (DDS) 166 diamond-coated saw 54 differential scanning calorimetry (DSC) 1, 390 - 391diffusion - applicability 322-323 - behavior in a joint 319 - defined 319 - mass uptake and diffusion coefficient measurement 321 - mechanisms of 320 - moisture 319 of penetrant molecules 319 – procedure 321–322 - specimens 321 diffusion coefficient of structural adhesives and sealants 323 diffusion coefficient-temperature curves 320 digital image correlation (DIC) 82, 403 dilatometry 393 DIN St37 126

direct beam theory (DBT) 185 dispensing 2 displacement transducer 103 DNV (Det Norske Veritas) certification 324 double cantilever beam (DCB) test specimens 195 - adhesive handling and application 61 bonded in a support frame or jig 56–57 - from the bonded plates 56 - bonded wood – adhesive types 66 -- aspects of 64-65 – assessment using penetration test 68 - 69-- curing technique 67-68 – procedure for fabricating 66–68 -- wood preparation 65-66 – control of bondline thickness 61–62 - curing technique 62 - determination of strain energy release rate (SERR) 55 - dimensions 58 - final specimen preparation 62-63 - - moisture and temperature conditioning 63 – standard ASTM D3433 62 - - surface pretreatment 63 - fracture of wood -- analysis of 227-229 -- bonded wood testing 226-227 -- evaluation of components 224-225 -- factors influencing 225-226 - - intrinsic variability of wood material properties 225 - initial crack 62 - standard ASTM D3433 58 - storage and substrate conditioning 59 - surface pretreatment 59-60 double strap joint 141 Drucker-Prager yield function 154 dumbbell-shaped specimens 12 durability testing using open-faced specimens - aging 330-331 - primary bonding 330 - secondary bonding 331-332 - specimen preparation and configuration 328-329 dynamic mechanical thermal analysis (DMTA) 1, 390, 392 dynamic shear modulus 276-279 - shear modulus on a bulk specimen using torsional pendulum 277 -- moment of inertia 279

– Poisson's ratio 279
– torsional rigidity 278
– thick adherend shear test (TAST) specimens
– results based on empirical relations and bulk adhesive test 278
– setup for 277
dynamic tensile modulus 273–276
dynamometer 92

#### е

EA956 adhesive 277 elastically stored energy in a plate 164 elastic-plastic bending of the peel arm 261 elastic zone behavior 150 elastomeric polymers 93 end-loaded split (ELS) test 178 - experimental setup of 188 - mode II fracture characterization of bonded joints using – – data reduction schemes 189–190 - - equivalent crack method 190-191 – gripping system 188 – load and displacement measurements 188 - 189– – R-curve 191 -- specimen geometry 187-188 - - strain energy release rate in 190 end load flexure (ENF) specimen 195 end-notched flexure (ENF) - 4-point 178 - specimen preparation - - adherends 179 – adhesive application 180–182 – final preparation of specimen 182 - 183 standards -- ASTM D3433- 99, 178 -- European (AECMA prEN 6034) 178 -- ISO/DIS 15024 178 -- Japanese (JIS 7086) 178 - testing of specimens -- data reduction schemes 185-186 – testing procedure 183–185 energy-dissipating scrim cloth 200 energy release rate 197 epoxies 13, 81, 83, 101, 399 epoxy-aluminum napkin ring 119 equilibrium moisture content (EMC) in the wood 65 Euler-Bernoulli beam theory 221 Evode TE251 111 exothermic reaction, problems of 13-14, 80,98

 overheating issue 14
 experimental compliance method (ECM) 173

extensometer 31

# f

failure envelopes 199-201 fast Fourier transformation (FFT) analysis 314 fatigue envelope 374 fatigue testing - of aged adhesive systems 334-335 dynamic fatigue - - under cyclic loading conditions 355-358 – measurement of crack closure by COD method 366-368 – measurement of the rolling force in cyclic loading 366 - - mixed-mode crack propagation data 361-363 - - mixed-mode fatigue measurements 368 -- specimen preparation 363-366 -- strain energy release rates 358-361 - static fatigue and delayed failure of adhesive joints - - creep and delayed failure 351-352 -- experimental procedure 353-354 -- result and discussion 355 – temperature-dependent delayed failure behavior 352 fiber-reinforced polymer matrix composites 55 Fickian diffusion 320 Fick's law 320, 349 fillet-free napkin ring joints 120 fixed ratio mixed mode (FRMM) test 196, 287 - specimen 197 flexible adhesives 7 flexible-to-rigid peel specimens, preparation of - adherend preparation 52-53 - adhesive application and assembly 53 - 54- curing technique 54 - final specimen and preparation 54-55 - mold for 51-52 - standards

-- ASTM C 903 51 -- ASTM D 1781 51

– – ASTM C 794 51

– – ASTM D 1876 51

flexible-to-rigid peel specimens, preparation of (contd.) – – ISO 4578 51 -- ISO 8510-1 51 -- ISO 8510-2 51 flush fillet 49 FM 300 adhesive 353 fractography 167 fracture behavior of joints, at high rates. see also impact tests - of adhesive specimens and joints by Hopkinson bar technique - - aspects concerning application of 297 -- dynamic stress-strain curve of the tested material 289 - - pulse propagation through the bar 290 – results and discussion 293–297 -- setup 289-290 - - specimen preparation and geometries 292 - 293 – split hopkinson pressure bar (SHPB) 289, 295 – – strain transducers 291 – stress–strain curves at different strain rates 296 – test specimen 289 - high-rate mixed mode I/II testing -- test experience 288-289 -- test specimen 287-288 - high-rate mode I testing – analytical considerations 286-287 -- characteristics 287 -- DCB test specimen 284-285 -- experimental conditions 285-286 -- TDCB test specimen 284-285 fracture envelope 216 fracture process zone (FPZ) 179-180, 182, 186, 190 fracture testing of aged specimens of an aluminum-/rubber-toughened adhesive system 322-323 of ODCB specimens 323 Frekote 55-NC 9 g

general-purpose triaxial testing devices 89 glass-transition temperature 12-13, 82, 84, 144, 166, 273, 275, 320-321, 325, 336, 349, 389-390, 397-398, 403 good-quality DCB specimens 64 gravimetric 321 grit blasting 50, 52, 59-60

# h

hardness of the silicone 4-5 Hexcel Composites 400 high-level hydrostatic compression 85 high-temperature cures 15 Hooke's law 90, 335 Hopkinson bar technique - aspects concerning application of 297 clamped -- combined impact tests 304-308 -- configuration of a bar 298-300 - - impact strength of adhesively bonded joints 303 -- tensile impacts 300-303 -- tensile impact tests 304 -- torsional impacts 303 -- torsional impact tests 304 - dynamic stress-strain curve of the tested material 289 - pulse propagation through the bar 290 - results and discussion 293-297 – setup 289–290 - specimen preparation and geometries 292-293 - split hopkinson pressure bar (SHPB) 289.295 - strain transducers 291 stress-strain curves at different strain rates 296 - test specimen 289 hot press 7 humidity on adhesive-bonded joints, effect of 350 Huntsman<sup>TM</sup>Araldite®420 A/B epoxy resin 147 hydraulic actuator 299 hydrostatic (bulk) compression testing, method for bulk modulus measurement 87 - compression chamber 90 - compression piston 90 - device 90-91 - load transfer 91 - mathematical expression of the stresses 89 - pressure and change in volume measurement 91-92 - results and bulk modulus determination 92-93 - rubbery and soft materials 88-89 - stiffer materials 89-90 - testing procedure 92

hydrostatic compression stress state 88

hydrostatic pressure technique, bulk specimen preparation using - adhesive application 6 - curing technique 7 - defects present 7 - failure properties 2 - internal metallic frame 2-3 principle, for producing plate specimens 2 - 3- specimen machining 7 - standard ISO 15166 3 - standard NFT 76-142 2-3 - surface finish 3 - using a metallic frame 3-4 using silicone rubber frame 3–5 void reduction 2 hydrostatic stresses, tests under - data analysis 423 - ductile-brittle transitions 419-420 - test fixture 420-421 - test procedure 422-423 hydrostatic (triaxial) compression 85

# i

ICPeel 263-265 idealized crack, stress field around 164 impact tests - ASTM Block 281 - Charpy and Izod tests 280 - combined 304 - combined peel and pull loads 312-315 - fracture behavior of joints and 284-289 - Hopkinson bar techniques 289, 298-299 - impact strength of adhesively bonded joints 303-308 - instrumented pendulum 281-283 – lap shear test 310–312 - pendulum 280-283 - tensile 300-304 - torsional 303-304 independently loaded mixed-mode specimen (ILMMS) geometries 358-363, 368-369 injection method of bulk specimen preparation - centrifuging process 10 – curing process 11 - final specimen preparation and testing 11 - 12- metallic frame 9-10 interface crack displacement field along the crack face 206 interfaces assembly machine 72 interfacial bonding 16, 29, 38, 49, 52 Iosipescu (V-notched beam) test

- horizontal separation of the points of contact 102 - joint specimens 102 - relative vertical motion 101 - standard ASTM D5379 97-101 - strain measurement principles 100-103 - test fixtures 99-100 --- alignment tools 100 - - asymmetric four-point bending (AFPB) fixture 100 -- Wyoming fixture 99-100 - test specimens 97-99 -- modifications 99 – – off-axis deflections 103 - - variations of the notch angle 99 Irwin-Kies equation 189 iso-strain diagram 339 isotropic adherends 402 isotropic peel arm 262 Izod and Charpy tests 280

- accuracy and reliability of 103-104

# j

jigs 98 J-integral solutions 167, 186, 278 joint/*in situ* joints, tests in 1 joint manufacture–alignment jig 44

#### I

lap joints, quasi-static testing of

- adherends 141-142
- - direct tensile stress acting on 142
- -- effect of thickness 142
- load corresponding to the total plastic deformation of 142
- - stress due to bending moment 142
- failure modes 145
- gripping system 142-143
- of composite materials 143
- – of high-strength materials 142–143
- load and displacement system 143-144
- -- load-displacement curve 144
- properties determination 146-147
- lap shear strength 146
- -- shear stress-shear strain curve 146
- specimen geometry 140–141
- adhesive shear stress 141
- – bending moment 141
- – double lap joint 141
- effect of boundary conditions and spacers 140
- -- peel stresses 141
- standards 139

lap joints, quasi-static testing of (contd.) testing speed and environmental conditions 144-145 - - glass-transition temperature 144-145 -- strain rate 144 lap joint with flat adherends - adhesive application and assembly 18 - 21- curing technique 21 - molds - - aluminum alloy 15-16 – – carbon steel 15 – – teflon 15 - specimen cleaning 21 substrate preparation and mounting 16 - 18lap shear joint specimens 104 latex adhesives 389 minimum film formation temperature of 393-394 Levenberg-Marguardt equation 365 lever arm extensometers 102 linear elastic fracture mechanics (LEFM) – epoxy-based structural adhesives 166 - force-displacement curves 166 - fracture mechanics 167 - load-displacement diagrams 165 - principle 163-164 procedure 164–167 -- ASTM guideline D5045-99(2007) test method 164, 166 – – ISO 13586:2000 test method 164 - for a series aromatic-amine (DDS)-cured bisphenol-A-based epoxies 167 linear elasticity theory 90 linear variable differential transformers (LVDTs) 89, 184 load-independent analysis methods 288 loading conditions, impact on adhesive and adhesive joints - ASTM Block Impact Test D950- 78, 281 - instrumented pendulum impact test 281-283 Izod and Charpy tests 280 log (decrement) 395 loss modulus 396 low-viscosity adhesives 29

# m

machining of specimens – bulk specimens, preparation of – – under hydrostatic pressure 7 – flexible adhesives, difficulties 7 - thick adherend shear test (TAST) specimens 26 -- modified 36 materials and technology support (MTS) program 125 Maxwell model creep relation 352 melting point 389 metallic adherends 111 methyl-ethyl-ketone 52 Metlbond 1113 adhesive 362, 364-365, 368 Metlbond 1113-2 adhesive 362, 364-365, 368 microcracks 7, 47, 50 minimum film formation temperature (MFFT) 389 minimum film formation temperature of latex adhesives 393-394 mixed mode adhesive fracture test specimens 195 mixed mode bending (MMB) test - data analysis 214-215 - principle of the fixture 214 - specimen geometry 212-213 - test experience 215-216 - test procedure 214 mixed-mode fatigue measurements - crack length 372-373 - fatigue loading 371-372 - with ILLM specimen 368 observations - - effect of bondline thickness 375 - - effect of mode ratio and applied G 374-375 - - effect of substrate material 375 - specimen preparation 369-371 - strain energy release rate 373 mixed mode flexure (MMF) 196, 287 mixed mode fracture testing - background 216-217 - calculation of the phase angle and strain energy release rate - - beam-on-elastic-foundation model 221-222 – – bean theory 221 - fracture energy envelopes 222 - fracture test and loading system 218 - load and crack length measurement 218 - 220- R-curve measurement 222-224 - specimen configuration and preparation 217-218 mode I fracture energy 200 mode I loading standard (BS7991:2001) 222

mode-independent fracture energy 200 mode mixity 195 modified Arcan test 70-72 modulus in vibration, measurement of - dynamic shear modulus 273-276 - dynamic tensile modulus 273-276 moisture diffusion 319 moisture on adhesives and adhesively bonded joints, influence of - adhesive assembly conditioning 326-327 - bulk adhesive conditioning 324-326 - conditioning equipment 324 - standard sampling condition 323-324 - test procedure for evaluating 327 molds - bulk specimens, preparation of -- under hydrostatic pressure 2-3 -- by injection 9-10 - - by pouring 14 - butt joints 37-38 - flexible-to-rigid peel specimens, preparation of 51-52 - lap joint with flat adherends - - aluminum alloy 15-16 – – carbon steel 15 -- teflon 15 - thick adherend shear test (TAST) specimens 28-29 - T joints specimen 47 monotonic shear loading 151 monotonic tension/compression-shear loadings 153

# n

Nadai correction technique 121, 124, 193 napkin ring specimens – adherends 42–44 - final specimen preparation 46 - inserting the adhesive 45 - joint manufacture-alignment jig 44 - in tension, shear properties 119-120 - - epoxy-aluminum napkin ring 119 - - measurement of rotation 122 -- standard ASTM E 229, 119 -- test specimen 121-122 – – torsion machine 122 neo-Hookean law 88-89 NFT 76-142, 2-3 noncontact extensometry 103, 111, 147 noncontacting laser extensometer 12 nondestructive test 273 notched torsion test, for mode III specimens – for fracture toughness 193

for rubber-toughened epoxy adhesive 193–194
test method 192
NPL extensometer 102
Nyquist–Shannon sampling theorem 300

### 0

one-dimensional theory of wave propagation in elastic rods 293 one-part adhesives 13 oscillatory index 206 outgassing of the adhesive, effect of 2

#### р

PAA core 256 Paris-Erdogan law 355, 357  $P-\delta$ data 185 peel testing 46, 50. see also T-peel test - at 180° -- data collection and analysis 246-247 - - failure mode identification 247-248 - - machine and fixtures for procedure 245-246 -- specimens 244-245 - analysis of – adhesive fracture energy 257–258 - - adhesive fracture energy using ICpeel (digitized), determination of 263 - 265- - plastic work in bending, determination of 259-261 - - root rotation using a beam on elastic foundation analysis, determination of 261-262 - climbing drum - - factors for reliable results 254-255 – – failure modes 256 -- materials 252-253 -- result analysis 256 -- test procedure 253-256 - floating roller - - finite element analysis and experimental investigation of 250-251 -- standards 249 -- test specifications 249-250 standard -- DIN EN 1465, 309-310 -- DIN EN ISO 11343 309 - wedge impact 309

- pendulum impact test for adhesives and adhesive joints
- ASTM Block impact test 281
- instrumented 281-283
- Izod and Charpy tests 280

phase angle, calculation of 221-222 phosphoric acid anodized (PAA) aluminum alloy honeycomb 256 pin and collar joint test method sample preparation -- adhesive application 157-158 -- materials 156 – preparation of adhesives 156–157 - - specimen fitting out 158 – surface treatment 156–157 testing and result analysis 158–160 "pi" tensile test 113 plastic deformation zone (PDZ) 347 4-point end-notched flexure (4ENF) test 178 Poisson's ratio 34, 73, 83-84, 89-90, 166, 205, 209, 262, 279, 403, 414 Arcan test, modified 153 "poker chip" tensile test 113 polyaromatic 81 polychloroprene 389 polyimide bond 200 polymeric adhesives 402 - viscoelastic properties of 405 polymeric phase in adhesives 389 polytetrafluoroethylene (PTFE) 42, 45, 53 - 54polyurethanes 82-83, 252, 389 adhesives 84 polyvinyl chloride (PVC) 252 pouring technique for bulk specimen preparation - bubbles, formation of 14 - centrifuge technique 14-15 – edge effects 8 effect of size 14 mixing process 13–14 - one-part adhesives 13 pouring the liquid adhesive into a mold 14 - single-part adhesives 13 two-part adhesives 13–14 pre-etch preparation 363 Pressure-Sensitive Tape Councils test method PSTC 107, 343 PSA tapes 412 pull-off forces 410 pull-off test specimen – – configuration and analysis 410–411 -- options 412-413 testing procedure and analysis 411–412 purpose-built extensometers 102 purpose-designed biaxial shear gauges 100

# q

quasi-static fracture tests - double cantilever beam (DCB) 169 – according to ASTM D3433 170–171 -- according to ISO 25217 171-174 - tapered double cantilever beam (TDCB) 169 -- according to ASTM D3433 174-175 -- according to ISO 25217 175-176 - test apparatus 170 - test methodology 176-177 - test specimen 170 quasi-static testing machines 312 quasi-static testing of bulk tensile specimens - determination of properties -- cracks, presence of 84 -- Poisson's ratio 83-84 -- tensile stress-strain curve 83-84 -- yield strength 84 -- Young's modulus 83-84 - on flat specimens -- determination of properties 96-97 - - load and displacement measurement 96 -- loading system 94-96 -- specimen geometry 93-94 - - testing speed and environmental conditions 96 - gripping system 81 - load and displacement measurement 81 - 82- specimen geometry 79-81 – dogbone-shaped specimen 79 -- elongations 79 - - round solid bar tension specimens 80 - - tensile properties 79 -- thickness 79 - testing speed and environmental conditions 82-83 -- displacement rate 82 -- strain rate 82 quasi-static testing of thick adherend shear test specimens adherends 126 - griping system 126 - manufacture of 125 - specimen geometry 126 standards – – ASTM D3983 126 -- ISO 11003-2 126

# r

*R*-curve, measurement of 187–191 rectangular gauges 100

Redux 326, 400 reinforced wedge test 348 relative mass uptake 322 residual stress and thermal expansion coefficient determination, bimaterial curvature method for - analysis 408-409 - concept of using curvature changes 403 - and glass-transition temperature 403 specimen configuration 404–406 - specimen preparation 406 - test procedure 406-408 use of noncontact displacement measurement techniques 403 residual stresses 7, 21, 40, 50, 65, 67 resin/ bulk specimens, tests on 1 Rohacell® 252 rolling force in cyclic loading, measurement of 366 room temperature vulcanizing (RTV) silicone 4 rosette gauges 100-101, 103 rubber-toughened epoxy adhesive 193

#### S

SAFT test (shear adhesion failure temperature) 343 sample preparation - butt joint specimen 116-117 pin-and-collar test method 155–158 "sandwich" tensile butt joint 114 saturation mass uptake 321 scarf joints 69 sealant peel specimens 55 sealants 41 servo-electric load frame 218 servohydraulic testing machines 312 shaft-loaded blister test (SLBT) 414-415 - circular punch test (CPT) 417 -- theoretical model 418-419 - loading configuration 414-415 - theoretical model 415-417 shear corrected beam theory (SBT) 58, 173 shear extensometers 101-102 shear strain in bulk specimens, determination 109 shear stress-shear strain curve 31, 152 - of an adhesive between metallic substrates, hydrostatic stresses 420 - Hopkinson technique 296 – clamped Hopkinson bar 302 - lap joints, quasi-static testing of 146 - napkin ring test 119 - solid butt joints in tension 121

– TAST 133 shear tests on bulk specimens 118 short peel specimen - geometry 312-313 - interpretation of test result 314-315 - manufacturing and testing of 313-314 silicone rubber frame 2-5 - release agent for 6 significance of thickness of 3 single-edge notched bending (SENB) specimens 164 - fractured 168 - span-to-width ratio 166 single lap joint (SLJ) specimens 15, 22-23. see also thick adherend shear test (TAST) specimens - preparation methods – – bonding fixture 23–26 -- traditional 23 - standards (ISO 4587 or ASTM D1002) 15 single lap joint (SLJ) test 139-140 single lap shear tests - advantages and limitations 310 - materials and specimen preparation 310-311 – adherend thickness 310 - size of the overlap 310 - and superimposed load conditions 310 - testing procedure 311-312 single leg bend (SLB) 196, 287 - specimen 198 slenderness ratio 85 solid butt joints in tension, shear properties of 120-121 - measurement of rotation 122 - polar moment of area 121 - shear stress-strain relationship 121 - test specimen 121-122 - torque-twist curve 121 - torsion machine 122 specimen cleaning - butt joints 40 - lap joint with flat adherends 21 - thick adherend shear test (TAST) specimens 29-30 specimen preparation - bimaterial curvature method 405-406 - climbing drum peel test 252-253 - curvature mismatch fracture test for subcritical debonding 381-382 - dynamic fatigue testing 363-366 - end-loaded split (ELS) test 187-188

- end-notched flexure (ENF) 179-183

specimen preparation (contd.) - mixed mode bending (MMB) test 212 - 213 mixed mode fracture testing 217–218 - peel testing at 180° 244-245 - single lap shear tests 310-311 - T-peel test 236-237 spring-loaded welding clamps 218 standards for adhesive specimens - AFNOR T 76-114 346 – ASTM 2294–1996 342 - ASTM C 794 51-52 - ASTM C 903 51 - ASTM D 570 321 – ASTM D 575 85 – ASTM D 638 79 - ASTM D 695 85-86, 93-94, 96, 133 – ASTM D 897 113 - ASTM D 903-49 249 - ASTM D 1002 15, 139, 146 - ASTM D 1151 324 - ASTM D 1183 324 - ASTM D 1780:2005 341 - ASTM D 1781 51, 249, 253-254 - ASTM D 1876 47, 51, 235, 249 – ASTM D 2293 342 – ASTM D 2293–1996 342 – ASTM D 2294–1996 342 - ASTM D 2651 373 - ASTM D 3039 79 – ASTM D 3165 141 - ASTM D 3167 249 - ASTM D 3433 56, 58-59, 62 - ASTM D 3433-99 178 - ASTMD 3762-79/83 345 – ASTM D 3762–98 351 - ASTM D 3846 93-95 - ASTM D 3983 26, 31, 126 - ASTM D 4562-90 155-158 - ASTM D 4680-1998 342-343 - ASTM D 4896 139 - ASTM D 5229 321, 325 – ASTM D 1002 353 - ASTM E 229 119 - ASTM E 647 334, 372 – ASTM E 1012 117 - BS 5350 253 - BS 7991:2001 222 - D 5045-99(2007) 164, 166 - DINISO 899 336 - EN 1943 343 - EN 15337 155-158 - EN ISO 527-2 79, 83, 96, 133 - European (AECMA prEN 6034) 178

- FINAT FTM 8, 343 - ISO 62 321 - ISO 527 336 - ISO 604 85-86 - ISO 683-9 156 - ISO 2818 7 - ISO 4578 51 - ISO 4587 15, 139, 341 - ISO 7743 85 - ISO 7743:2011 85 - ISO 8510-1 51 - ISO 10123 155 - ISO 11003-2 26, 31, 126, 133 - ISO 13586:2000 164 - ISO 14615:1997 341 - ISO 15109:2007 341 - ISO 15166 3 - ISO 25217 58-59, 62 - ISO/DIS 15024 178 - Japanese (JIS 7086) 178 - NFT 76-142 2-3, 15 - PSTC 107, 343 - SACMA SRM 1-88, 94-95 static load creep experiments 336 steel adherends 109 storage modulus 396 strain energy criterion 164 strain energy release rate (SERR) 55 - specimen 198 strain gauges 101 strain measurement principles 100-103 strain wave propagation, in clamped Hopkinson bar 301 stress-free temperature 403 stress intensity factor (SIF) 206 substrate-adhesive interfaces 31, 34-35, 69 substrate preparation - butt joint specimen 38-39 - double cantilever beam (DCB) test specimens 59 - lap joint with flat adherends 16-18 - tapered double cantilever beam (TDCB) adhesive joint test specimens 59 - thick adherend shear test (TAST) specimens 29 - T joints specimen 48-49 surface treatment on adhesive-bonded joints, effect of 350

### t

TA Instruments DMA 406 tapered double cantilever beam (TDCB) adhesive joint test specimens 55, 359

- adhesive handling and application 61 – comparison between experimental – control of bondline thickness 61–62 - curing technique 62 - dimensions 58-59 - initial crack 62 - standard ASTM D3433 58-59 - storage and substrate conditioning 59 - surface pretreatment 59-60 teflon molds 15 temperature, tests with - creep experiments at elevated temperature - - standards related to 341-343 - - static load 336 - general test procedures 336-338 glass-transition temperature 336 Hooke's law 335 - lifetime prediction 339-341 - test results 338-339 - time-dependent stress-strain relationship 339 - yield strength 336 temperature-time profile 45 tensile butt test. see butt joint specimen, quasi-static testing in tension tensile-shear loadings 69 tensile specimens 8-10 tensile stress-strain curve of a two-part epoxy adhesive 8 tensile testing 3, 11, 32, 38-39, 69-70, 72 - machine 32, 149 tension-shear loadings 72-73 tension-torsion testing machine 69 thermal conductivity of adhesives 393 thermal properties of adhesives 389 thermocouple 14 thermogravimetric analysis 392-393 thermomechanical analysis (TMA) 390, 392 thick adherend shear test (TAST) specimens 276 - adhesive application and assembly 29 - Althof specimen 26 - bending stiffness 28 - curing technique 29 - dynamic shear modulus with - - results based on empirical relations and bulk adhesive test 278 – – setup for 277 - geometry 276 - machining of specimen 26 - modified 29-30 – behavior under cyclic loadings 138-139 -- bonded specimen geometry 33-36

results TAST and 134-136 -- geometry of 31-32 - - identification of behavior of the adhesive 136 - 137 – influence of adhesive thickness 137-138 – machining of specimens with beaks 36 – – measurement 134 -- test requirements 139 - mold for 28-29 - quasi-static testing of – determination of properties 130–133 – – failure modes 130 - - load and displacement measurement 127-130 - - testing speed and environmental conditions 130 - size differences 26 - specimen cleaning 29-30 standards – – ASTM D3983 26, 31 -- ISO 11003-2 26, 31 - substrate preparation 29 time constants 300 time-dependent crack growth, measurement of - factors influencing 376-379 time-to-catastrophic failure process 355 Timoshenko beam theory 190 Tinius-Olsen Universal testing machine 353 T joints specimen 46 - adhesive application and assembly 49 - curing technique 49-50 - mold for 47 - peel testing 50 - standard ASTM D1876 47 - substrate preparation 48-49 torsional rigidity 278 torsion pendulum 395 T-peel test 312 - analysis of 265-266 - configurations and fracture mechanics interpretation 230-236 -- adherends 232 -- categories 230-236 - fracture energy of debonding 229, 232 - interpretation of results 238-241 - locus of failure 241-243 - practical adhesion 230 - specimen preparation 236-237 – standards 229

- testing procedure 238

T-peel test (*contd.*) – T-peel specimen 230–231 – T-peel strength, defined 229, 234–235 traction–shear tests 70  $\alpha$  transition 399 triaxial compression stress state 89 triaxial testing devices 89 two-component adhesives 6 two-part adhesives 13–14, 53 two-part epoxy adhesive 7 – structural 41 two-prong fork shear extensometer 102

#### и

uniaxial compression testing, method for – rubbery and soft materials 85 – – load transfer 86 – – relation between maximum compression deformation and expected 86 – – slenderness ratio 85 – – standards recommended 85 – stiffer materials 85–87 – – standards recommended 85–86 upper adherend 19–20

#### V

vacuum bonding techniques 253 vacuum release technique 2, 19 V-block-type jig 40 vibrating beam method automatic damping measurement 399-402 - manual damping measurement 396-399 video extensometers 82 viscoplastic behavior of adhesive 150 viscosity 2, 10, 13-14, 61, 64 low-viscosity adhesives 29 - low-viscosity liquids 13 - of sealants 41 - two-part epoxy structural adhesive 41 viscous form of adhesives 1-2 viscous cold-cure adhesive 9 visually determined (VIS) value 172 V-notched beam test. see Iosipescu (V-notched beam) test V-notched plate (Arcan) specimen. see Arcan (V-notched plate) test void-free flat sheets 8 void-free specimens 2

volume measurement in hydrostatic compression 91–92 – pressure/change in 92 von Mises equivalent stress 34 von Mises model 93 V-shaped grooves 44

# w

water absorbtion by adhesives 2 water jet cutting system 36 water on adhesive-bonded joints, effect of 349-350 wedge test (WT) - correlation between normal use and 350-351 - experimental details -- dimensions 345-346 - - measurements of fracture length 346 - 347- mechanics of 344-345 results -- environment, influence of 349 - - and evaluation of durability 348-34 - - relative humidity, influence of 350 - - surface treatment, influence of 350 -- temperature, influence of 349 - - value of fracture energy 348 -- water, influence of 349-350 - variations -- Chip test 347-348 -- reinforced wedge test 348 Wheatstone bridge conditioners 291 wood bonding 64-65 Wyoming fixture 99-100

#### X

X-ray photoelectron spectroscopy (XPS) 145

# γ

yield strength 336
Young's modulus 33, 73, 89–90, 221, 261–262, 294, 398. see also dynamic tensile modulus
Arcan test, modified 153
clamped Hopkinson bar 301–302
of CMM specimen with an interface crack 206
LEFM 164
of stiff adhesives 83

- of the substrate 58