

## Index

### a

- acid/base catalysis 26
- acoustic fluid shaking 157
- active micromixers
  - acoustic fluid shaking 157
  - alternating current magnetohydrodynamic (MHD) actuation 158
  - electrowetting-induced droplet shaking 156
  - elektrokinetic instability 155
  - microstirrers 157
  - pressure induced disturbances 154
  - ultrasound/piezoelectric membrane action 156
- active micromixing 144
- adiabatic temperature rise
  - multi-injection microstructured reactors 214
  - single-injection micro-structured reactors 218
- alternating current magnetohydrodynamic (MHD) actuation 158

### b

- batch reactors 1
- batch-wise operated stirred tank reactor (BSTR)
  - Damköhler number 32
  - heat balance 30
  - intermediate product yield
  - vs. Damköhler number 34
  - mass balance 30
  - reaction time 31
  - reactor performance 31
- bimolecular catalytic reactions 56
- Bodenstein number 102, 126
- BSTR *see* Batch-wise operated stirred tank reactor (BSTR) 30

- bubble columns 268
- bubbly flow 273

### c

- C-curve 93, 95
- Carberry number 64
- catalytic gas-phase reactions
  - catalytic wall micro-reactors 238
  - characteristics 238
  - randomly micro-packed bed reactors
    - advantage 233
    - backmixing 233
    - flow mal-distribution 233
    - integrated packed bed-heat exchanger 234
  - reaction slit and cooling channels 234
  - residence time distribution 233
  - shallow micro-fabricated channels 233
  - silicon cross-flow microreactor 234
  - structured catalytic micro-bed reactors
    - catalytic filaments 236
    - endothermic steam-reforming 235
    - integrated exchangeable catalytic foam plates 237
    - membrane reactor 236
    - metallic/ceramic foams 236
    - micro-structured string-reactor 235
    - parallel filaments 235
    - residence time distribution 235
    - sintered metal fibers (SMF) 238
    - slit-like channels 237
- catalytic wall micro-reactors 238
  - Damköhler number 249, 250
  - heat transfer 250
  - hydrodynamic entrance zone length 246
  - internal effectiveness factor 246
  - mass transfer characteristics 247
  - mass transfer coefficient 247

catalytic wall micro-reactors (*contd.*)

- quasi-isothermal behavior 246
- Sherwood numbers 247
- zero-order reaction 249

caterpillar micromixer 149

chaotic mixing 143, 149

characteristic mixing time 129

characteristic reaction time 3

chemical reactors

- continuum models 180
- heat balance 180
- heat management 179
- material balance 180
- temperature range selection 179

Chilton-Colburn analogy 66, 82

Churn flow 279

Coanda effect micromixer 153

complete segregation 130

complex microchannel geometries 191

constant density reactions

- CSTR 37
- PFR 40

continuous flow microstructured reactors 286

continuous stirred tank reactor (CSTR)

- constant density reactions 37
- conversion *vs.* Damköhler number 38
- degree of backmixing 35
- heat balance 38
- mass balance 36
- space time 36
- variable density reactions 37

continuous-stirred tank reactor (CSTR)

- RTD 95

continuum models 180

conversion 29

CSTR *see* Continuous stirred tank reactor (CSTR) 35

curved microchannels 189

cyclone mixer 269, 270

## d

Damköhler number 115, 132

- BSTR 32, 34
- PFR 43
- *vs.* isothermal external effectiveness factor 63

Dean number 145

deformed interface flow 282, 297

dispersed flow 283, 298

dispersion model 101, 111

dry etching 10

## e

effective heat exchange area 185

effective reaction rate 196

efficient instantaneous catalyst selectivity 76

electrowetting-induced droplet shaking 156

elektrokinetic instability micromixer 155

energetic efficiency of mixing 172

energy balance 20

Engulfment flow 144

enzymatic catalysis 27

external numbering up 8

## f

*F* curve 92, 95

falling film contactors 268

Fischer–Tropsch synthesis 261

flow separators

- conventional separators 308
- geometrical modifications 309
- gravity based separation 315
- IMM settler 315
- wettability
  - – contact angles 310
  - – flow resistance 314
  - – hydrophilic and hydrophobic material 310

– – membrane separator 311, 312

– – pressure drop 312, 313

– – Y-shaped separator 311

fluid-fluid microstructured reactors

- conventional reactors
  - – advantages and disadvantages 268, 269
  - – applications 267
  - – equipments 267
  - – gas-liquid mass transfer 267
  - – liquid-liquid reactions 267
  - – multiphase microstructured devices 268
- falling film reactor 272
- flow separation *see* Flow separators 307
- gas-liquid flow patterns
  - – annular and parallel flow 280
  - – bubbly flow 273
  - – churn flow 279
  - – classification 273
  - – slug-bubbly flow 279
  - – Taylor flow *see* Taylor flow 274
- gas-liquid reactions
  - – halogenation 317
  - – hydrogenation 319
  - – nitration 318
  - – oxidation 318
  - – sulfonation 318
- Hatta number 316
- liquid-liquid flow patterns

- annular and parallel flow 283
- classification 280
- deformed interface flow 282
- dispersed flow 283
- drop flow 281
- slug flow 281
- slug-dispersed flow 283
- slug-drop flow 282
- liquid-liquid reactions
  - benzene nitration 319
  - biodiesel production 320
  - enzymatic reactions 322
  - PTC 321
  - toluene nitration 319
  - vitamin precursor synthesis 320
- mass transfer *see* Mass transfer 284
- microchannels
  - inlet T Y and concentric contactor 271
  - mesh/sieve-like interfacial support contactors 271
  - parallel 272
  - partial two fluid contact 271
  - static mixers 272
- micromixers 269
- pressure drop *see* Pressure drop 300
- fluid-solid micro-structured reactors
  - advantages and disadvantages 232
  - catalytic dehydration 259
  - catalytic partial oxidations
    - ammonia oxidation 255
    - chip-like reactor 257
    - $H_2/O_2$  oxidation reaction 256
    - methane 256
    - quartz glass micro-reactor 256
    - silicon membrane microreactor 255
    - T-shaped microchannel 255
  - ethylene oxide synthesis 259
  - exothermic/endothermic reactions 232
  - Fischer–Tropsch synthesis 261
  - hydrodynamics
    - Ergun equation 240
    - geometric factor 242
    - Hagen–Poiseuille equation 242
    - Knudsen coefficient 240
    - mono-sized spherical particles 240
    - particle size distribution 240
    - pressure drop 239–241
    - surface area per foam volume 241, 243
  - mass transfer
    - catalytic foam micro-reactors 245
    - catalytic wall micro-reactors *see* Catalytic wall micro-reactors 246
    - Damköhler number 244
    - external and internal 244

- randomly – packed bed catalytic micro-reactor 244
- reactor selection 253
- parallel flow channels 232
- steam reforming 260
- types 231, 232
- formal kinetic equations
  - Homogeneous Catalytic Reactions 26
  - multiple homogeneous reactions 24
  - Single Homogeneous Reactions 22
- fractional surface coverage 51
- g**
  - gas-liquid-liquid systems 346
  - gas-liquid-solid systems
    - continuous phase microstructured reactors
      - mesh microcontactor 333–335
      - microstructured falling film reactor 333
    - conventional reactors 331
    - dispersed phase microstructured reactors
      - microbubble column 335
      - microstructured packed bed reactor 335
      - segmented flow gas-liquid-solid reactors 335
    - Taylor flow 334
  - mass transfer and chemical reaction
    - catalytic microstructured film reactor 337, 338
    - concentration profiles 336
    - global transformation rate 336
    - hydrodynamic characteristics 340
    - hydrogenation 341
    - interfacial area 339
    - irreversible reaction 336
    - mass transfer coefficient 338
    - mass transfer rate 337
    - mass transfer resistance 341
    - mesh microcontactor 339
    - observed reaction rate 338
    - reaction rate per unit 336
    - segmented flow gas-liquid-solid reactors 340
    - volumetric mass transfer 340
  - reaction examples
    - catalyst deactivation 345
    - catalytic hydrogenations 341
    - cyclohexene hydrogenation 346
    - heterogeneous hydrogenation 345
    - low liquid and gas velocities 346
    - micro packed beds 344
    - microfabricated structured catalyst packing 345
    - silicon/glass microreactors 346
    - types of reactions 342

**h**

- Hagen–Poiseuille equation 140
- Hatta number 45, 316
- heat balance
  - BSTR 30
  - chemical reactors 180
  - CSTR 38
  - MSR 198
  - PFR 44
- heat transfer
  - complex geometries 191
  - curved channels 189
  - multichannel micro heat exchanger
    - – axial temperature profiles 192
    - – heat exchanger efficiency 192
  - straight microchannels
    - – aspect ratio *vs.* asymptotic Nusselt number 184
    - – asymptotic Nusselt- and Sherwood-numbers 183
    - – effective heat exchange area 185
    - – laminar velocity profile 182
    - – mean Nusselt number 183
    - – overall heat transfer coefficient 182
    - – shell and tube micro heat exchanger 186
  - two phase flow system
    - – flow rate *vs.* Nusselt number 195
    - – Nusselt number 194
    - – *vs.* single phase flow 194
- helicoidal microchannel falling-film reactor 273, 293
- heterogeneous catalytic reactions
  - advantages 49
  - bimolecular catalytic reactions 56
  - concentration profiles 60
  - isothermal external effectiveness factor
    - – *vs.* Carberry number 64
    - – *vs.* Damköhler number 63
    - – yield and selectivity 64
  - isothermal internal effectiveness factor
    - – *vs.* generalized Thiele modulus 71
    - – *vs.* generalized Weisz modulus 73
    - – *vs.* Thiele modulus 69
    - – selectivity and yield 74
  - Langmuir adsorption isotherms 51
  - Langmuir–Hinshelwood model 53
  - most abundant surface intermediate (MASI) approximation 55
  - non-isothermal external effectiveness factor 67
  - physical and chemical steps 59
  - quasi-surface equilibrium approximation 54
  - rate equations 50

- rate of deactivation 58
  - transport effects estimation criteria 83
- heterogeneous reactions
- mass- and heat transfer 20
- homogeneous catalytic reactions 26
- biphasic systems
    - – catalyst recovery 45
    - – fast chemical reaction 47
    - – moderate chemical reaction 46
    - – reactor efficiency *vs.* Hatta number 48
    - – slow chemical reaction 45
  - SLP catalysts 49
- drawback 45
- formal Kinetics 26
- homogeneous reaction 4
- multiple reactions 24
  - single reaction 22
- homogeneous reactions
- definition 85
  - mass- and heat transfer 20
  - reaction mechanism 25

**i**

- ideal reactors
- BSTR *see* Batch-wise operated stirred tank reactor (BSTR) 30
  - CSTR *see* Continuous stirred tank reactor (CSTR) 35
  - performance parameters 29
  - PFR *see* plug flow reactor (PFR) 39
  - types 29
- instantaneous selectivity 30
- intensity of segregation 130, 158
- interdigital micromixers 147
- interdigital mixer 269, 270
- interexchange with mean (IEM) model 166
- international Conference on Microreaction Technology (IMRET) 11
- international Union of Pure and Applied Chemistry (IUPAC) 22
- introduction 1

**j**

- jet micromixer 151

**k**

- Knudsen coefficient 180

**l**

- Langmuir adsorption isotherms 51
- Langmuir–Hinshelwood model 53
- LIGA process 9

**m**

- macroscopic mixing 129
- mass balance
  - BSTR 30
  - CSTR 36
  - PFR 39
- mass Biot number 79
- mass transfer
  - characterization 286
  - film-penetration model 285
  - gas-liquid microstructured devices
    - – microstructured falling film reactors *see* Microstructured falling film reactors 293
    - – slug-annular and churn flow regime 292
    - – Taylor flow *see* Taylor flow, mass transfer 287
  - liquid-liquid microstructured devices
    - – annular and parallel flow 297
    - – deformed interface flow 297
    - – dispersed flow 298
    - – slug flow 296
    - – slug-dispersed flow 298
    - – slug-drop flow 297
  - liquid-side mass transfer coefficients 285
  - macro-model 285
  - micro-models 285
  - non-reactive systems 284
  - penetration model 285
  - reactive systems 284
  - vs. conventional contactors 299
- material balance 19
  - chemical reactors 180
  - MSR 197
- MBT device *see* Microfluidic baker's transformation (MBT) device 153
- mean residence time 91
- meander mixer 146
- mesh microcontactor 333, 335, 339
- Michaelis-Menten model 27, 85
- micro bubble column 317
- micro-channels
  - laminar flow mixing
    - – characteristic dimension 138
    - – characteristic mixing time 141
    - – engulfment regime 142
    - – predicted vs. experimentally determined mixing time 141, 142
    - – pressure drop 140
    - – specific power dissipation 140
    - – T-mixer 136
    - – time for diffusion 137
  - RTD
    - – axial and radial diffusion 115
    - – gas flow 117
    - – liquid flow 118
    - – multiphase flow 122
- micro-electrical discharge machining 10
- microchannels
  - inlet T Y and concentric contactor 271
  - mesh/sieve-like interfacial support contactors 271
  - parallel 272
  - partial two fluid contact 271
  - static mixers 272
- microfluidic baker's transformation (MBT) device, 153
- micromixers 269
  - active mixers *see* Active micromixers 154
  - efficiency characterization
    - – absorbance vs. Reynolds number 170
    - – chemical methods 159
    - – competitive neutralisation and acetal hydrolysis 161
    - – consecutive and parallel competitive reactions 160
    - – dependent factors 158
    - – diazo coupling reactions 161
    - – energetic efficiency of mixing 172
    - – flow rates vs. segregation index 166
    - – mixing time vs. absorbance 167
    - – mixing time vs. Reynolds number 171
    - – mixing time vs. specific power dissipation 169
    - – mixing time vs. specific power dissipation 169
    - – neutralization and ester hydrolysis reactions 160
    - – optical techniques 159
    - – physical methods 158
    - – segregation index 163
    - – Villiermaux-Dushman reaction 162
  - passive mixer *see* Passive micromixers 144
  - passive vs. active mixing 143
  - schematic representation 144
- microscopic mixing 129
- microstirrers 157
- microstructured falling film reactor 272, 317, 333, 334
  - disadvantage 293
  - mass transfer coefficient 294
  - mass transfer resistance 293
  - microchannels 293, 294
  - surface structure 296
- microstructured reactors (MSR)
  - 1-ethyle-3-methyle imidazolium ethyl sulfate synthesis 207
  - advantages

- microstructured reactors (MSR) (*contd.*)
    - – novel operating window 7
    - – numbering-up 7
    - – process safety 5
    - – transfer rates 2
    - applications 10
    - axial temperature profile 199
    - benchmarking 5
    - chemical mobile plants 12
    - chemical reactions categories of, 195
    - energy balance 198
    - fabrication techniques 9
    - fine chemical/pharmaceutical industry 12
    - fluid-fluid reactors, *see* Fluid-fluid microstructured reactors 267
    - heat evacuation 196
    - hotspot reduction strategies 196
    - laboratory tool 11
    - material balance 197
    - multi-injection *see* Multi-injection microstructured reactors 212
    - objectives 2
    - overall heat transfer coefficient 199
    - parametric sensitivity 201
    - selection steps 9
    - single-injection *see* Single-injection microstructured reactors 218
    - vs. conventional processing 13
  - miniaturized systems 2
  - mixer-settler 269
  - most abundant surface intermediate (MASI)
    - approximation 55
  - moving droplet mixers 151
  - multi-injection microstructured reactors
    - adiabatic temperature rise 214
    - Grignard reaction 224
    - heat balance 213
    - heat evacuation time 213
    - hot-spot reduction
    - – number of injection points 218
    - – unequal flow partition 219
    - mass balance 213
    - schematic representation 213
    - temperature profile 217
  - multichannel micro heat exchanger
    - axial temperature profiles 192
    - heat exchanger efficiency 192
  - multilamination mixers
    - bifurcation-type feeds 147
    - cyclone mixer 148
    - interdigital mixers 147
    - SuperFocus mixers 148
  - multiple homogeneous reactions 24
  - multiple reactions 22
- n**
- novel operating windows 7
  - nucleophilic/electrophilic catalysis 26
  - numbering-up strategy 8
  - Nusselt falling film theory 338
- o**
- organometallic complex catalysis 26, 27
  - overall volumetric heat transfer coefficient 191
- p**
- parallel microchannels 272
  - passive micromixers
    - chaotic mixing 149
    - Coanda effect mixer 153
    - integrated mixer/valve design 153
    - jet collision device 150
    - MBT 153
    - moving droplet mixers 151
    - multilamination mixers
      - – bifurcation-type feeds 147
      - – cyclone mixer 148
      - – interdigital mixers 147
      - – SuperFocus mixers 148
      - – types 147
    - SAR mixers 149
    - single channel mixers
      - – cyclone type mixers 145
      - – T-mixer 144
    - structured packing 149, 150
  - passive micromixing 143
  - PFR *see* Plug flow reactor (PFR) 39
  - phase transfer catalysis (PTC)
    - $\beta$ -keto esters 321
    - p-nitrophenyl acetate hydrolysis 321
  - plug flow reactor (PFR)
    - constant density reactions 40
    - conversion vs. Damkohler-number 43
    - heat balance 44
    - mass balance 39, 198
    - mixing
      - – Damkohler number 132
      - – fast mixing 133
      - – intermediate yield vs. conversion 134
      - – mass balances 133
      - – segregation intensity 131
      - – slow mixing 132
    - reactor volume and space time 39
    - RTD 95
    - variable density reactions 41
  - power rate law (PRL) 22, 25
  - Prater number 77, 78
  - pressure drop

- gas-liquid flow
  - – homogenous model 301
  - – separated flow model 301, 302
- liquid-liquid flow
  - – power dissipation 307
  - – with film 305
  - – without film 304
- PRL *see* Power Rate Law (PRL) 25
- process classification 1
- process safety 5
- pulse function stimulus- response method 93

## q

- quasi steady-state approximation (QSSA) 26
- quasi-surface equilibrium approximation 54

## r

- randomly-packed bed catalytic micro-reactor
  - gas-phase reactions
    - – advantage 233
    - – backmixing 233
    - – flow mal-distribution 233
    - – integrated packed bed-heat exchanger 234
    - – reaction slit and cooling channels 234
    - – residence time distribution 233
    - – shallow micro-fabricated channels 233
    - – silicon cross-flow microreactor 234
  - mass transfer 244
- rate determining step approach 25
- reaction orders 22
- reactor volume
  - CSTR 36
  - PFR 39
- residence time distribution (RTD)
  - cascade CSTR 96
  - CSTR 95
  - dispersion model 101
  - experimental determination
    - – pulse function stimulus- response method 93
    - – step function stimulus- response method 92
  - function  $E(t)$  90
  - ideal vs. real reactors 96, 97
  - micro-channel reactors
    - – axial and radial diffusion 115
    - – gas flow 117
    - – liquid flow 118
    - – multiphase flow 122
  - PFR 95
  - reactor performance
    - – dispersion model 111
    - – known formal kinetics 108

- – positive reaction order 107
- – product yield 114
- – tanks-in-series model 112
- real reactors, models for
  - – dispersion model 101
  - – tanks-in-series model 100
- tanks-in-series model 100
- tubular reactors
  - – axial dispersion estimation 105
  - – boundary conditions 102
  - – laminar flow 98
  - – pulse function stimulus-response method 94

Reynolds-number 283

RTD *see* Resident time distribution (RTD) 90

## s

- SAR mixers *see* Split-and-recombine (SAR) mixers 148
- segmented flow
  - Nusselt number 194
- segmented flow gas-liquid-solid reactors 340
- segregation 130
- selectivity 30
- shell and tube micro heat exchanger 186
- single channel mixers
  - cyclone type mixers 145
  - T-mixer 144
- single homogeneous reactions 22
- single reaction 22
- single-injection micro-structured reactors
  - 1,3-Dimethylimidazolium-triflate synthesis 221
  - adiabatic temperature rise 218
  - dialkyl-substituted thioureas nitration 222
  - methyl butyrate reduction 223
- sinusoidal corrugated-plate channels 189, 190
- skewness 91
- SLPC *see* Supported liquid phase catalysis (SLPC) 49
- slug flow, *see also* Taylor flow 274, 281, 296
- slug-bubbly flow 279
- slug-dispersed flow 298
- slug-drop flow 282, 297
- slug-flow micro-reactor 11
- space time
  - CSTR 36
  - PFR 40
- specific heat production 196
- split-and-recombine (SAR) mixers 148
- staggered herringbone mixer (SHM) 151

- stagnant film model 285
  - star lamination micromixer 148
  - step function stimulus- response method 92
  - stirred tanks 268
  - straight microchannels
    - aspect ratios. asymptotic Nusselt number 184
    - effective heat exchange area 185
    - laminar velocity profile 182
    - mean Nusselt number 183
    - overall heat transfer coefficient 182
    - shell and tube micro heat exchanger 186
  - stratified flow 144
  - streamlined fins 296
  - SuperFocus micromixer 148
  - supported liquid phase catalysis (SLPC) 49
  - system volume 19
- t**
- T-mixer
    - design 169
    - flow regimes 144
  - tanks-in-series model 100, 112
  - Taylor flow
    - applications 276
    - bubble velocity 277, 278
    - capillary number 276
    - correlations 276
    - delay tube 274
    - flow rates and fluid properties 276
    - generation 275
    - interfacial gas–liquid area 276
    - mass transfer
      - – caps and liquid film 290
      - – characteristic diffusion time 291
      - – film contact time 291
      - – film mass transfer coefficient 289
      - – gas-liquid mass transfer 287, 288
      - – Higbie penetration model 287
      - – liquid slug lengths 290
      - – superficial gas velocity 290
      - – Taylor bubbles 287
    - radial mixing 276
  - Thiele modulus 70
  - three phase systems
    - gas-liquid-liquid systems 346
    - gas-liquid-solid systems 331
    - hydrodynamics 331
  - Train flow *see* Taylor flow 274
  - trans-esterification 320
  - tubular contactors 268
  - tubular reactors
    - axial dispersion estimation 105
    - boundary conditions 102
    - laminar flow 98
    - pulse function stimulus-response method 94
- v**
- variable density reactions
    - CSTR 37
    - PFR 41
  - Villermaux-Dushman reaction 162
  - Vortex flow 144
- w**
- Weisz modulus 72
  - wet etching 10
- y**
- yield 29