

Index

a

- acetate, 116, 420–422, 471, 475
- acetic acid, 34, 116, 117, 139, 203, 421
 - decarboxylation of, 116
- acetylene, 135, 137, 141–142, 145
- achievable hydrogen prices per sector., 275
- acid gases, 499
- acidic electrolysis, 331. *see also* PEM electrolysis
- activated alumina, 557
- activated carbon, 494
 - adsorption equilibrium isotherms of CO₂ on, 500
 - adsorption of CO₂ on, 500
 - CO₂ diffusion, 500
 - efficiency for CO₂ removal, 500
 - isotherms of water on, 499
 - layer of, 500
 - loading of CO, 500
 - mechanical resistances of, 500
 - order of adsorption in, 500
 - utilization of, 499
- activated/non-activated cells, 1049
- additives, 115, 302–303, 339, 779–780
 - titanium-based, 779
- adiabatic expansion energy, 713, 730
- adiabatic reactors, 180–181, 185–185, 206
- adsorbents, 494
 - activated carbon, 494
 - capillary filling, 494
 - water isotherms, 494
 - adsorption equilibrium properties of, 496
 - alumina, 494
 - adsorption isotherms, 494
 - silica gel, 494
 - water isotherm, 494
 - selective, 499
 - zeolites, 494
 - utilization of, 494
- adsorption, 16, 316, 492
 - energies of, 492
 - equilibrium isotherms, 492
 - shape of, 492
 - type I, 492
 - of CO₂, CH₄, 493
- advanced hydrogen development turbine programme, 1023
- aeroengines, 1026
- agitated granular sludge bed reactor (AGSBR), 427
- agricultural residues, 423–424
- AIP. *see* air-independent propulsion (AIP) systems
- air condition (A/C) systems, 972
- aircraft design, planning of, 966
- air-independent propulsion (AIP) systems, 991
 - fuel cell technology in, 991
 - HDW fuel cell, 992
 - class 214, 992
 - class 212A, 992
 - overview of, 993
 - requirements for, 991
- air pollutants, 545
- alanates, 774
- alcohols, 116, 146, 179, 181, 182, 360, 427, 473
- Alder reaction, 115
- algae
 - biomass production, high, 473
 - [FeFe]-hydrogenase activation, 466
 - ferredoxin, 472
 - genetically modified, 473
 - H₂ production in, 465
 - hydrogenase, 466
 - physiology and biochemistry of, 465
- alkaline earth metal oxides, 153
- alkaline electrolysis, 27, 283, 311–312, 331
 - characteristic cell performance for, 313
 - compression, 314

- current–voltage characteristics and operating ranges for, 332
- gas separation in, 313–314
- schematic of, 314
- technology, 1040
- alkaline electrolyzer, 317, 1036, 1037, 1061
 - based risk analysis, 1039
 - cooling water system, 1038
 - design of, 1041
 - feed water treatment in, 1038
 - main components of, 1038
 - safety evaluation of compressors, 1041
 - specifications of, 1039
- alkaline water electrolysis cell
 - anode and cathode polarization, voltage of, 291
 - compositions of typical cell voltage, 292
- alkylation, 10
- alumina, 7, 499
 - mechanical properties of, 499
 - utilization of, 499
- volumetric adsorption equilibrium, higher, 499
- aluminum, 143
- aluminum plate fin heat exchangers, 758
 - advantages, 760
 - high flexibility, 760
 - high specific heat exchange surface, 760
 - low pressure losses, 760
 - low specific costs, 760
 - parameters, 758
- aluminum powder, 799
- ambient temperature, 796
- American Lung Association, 845
- amides, 775
- amines like diethanolamine (DEA), 558
- amino acids, 115
- ammonia, 5, 7, 10, 19, 491, 544, 814, 933
 - coal-based production, 26
 - global production of, 19, 32
 - Haber–Bosch process, 32
 - production, 283
 - production, based on steam reforming of natural gas, 32–33
 - schematic depiction of, 33
 - production data based on, 21
 - syngas production for, 32
 - syngas production from natural gas
 - composition of, 240
 - methane steam reforming, 240
 - steps, 239
 - water–gas shift reaction
 - Influence of temperature on equilibrium constant, 241
 - synthesis based on hydrogen
 - produced from water electrolysis, 33–34
 - synthesis reactor, 33
- anaerobic digestion technology, 398
- anaerobic filter (AF) reactor, 429
- anaerobic sequencing batch reactor (ASBR), 427
- anode–electrolyte interface, 448
- anoxygenic photosynthesis, 465
- aqueous hydrogen peroxide, 659
- argon, 134, 142
- argon–methane mixtures, 141
- Arthrospira platensis*, 470
- artificial leaf, 472
 - development of, 472
 - silicone, 472
 - technical difficulties, development of, 472
- asbestos, 41
- Asia-Pacific Economic Cooperation, 922
- Aspen Custom Modeler, 516
- asphaltene molecule, 10
- ASTERIX project, 168
- atmospheric alkaline electrolysis, 1036
- ATR. *see* autothermal reforming (ATR)
- ATR reactors, 220
- Au–CeO₂ interaction, 208
- automotive hydrogen storage, 712
- automotive pressurized fuel cell system, 793
- automotive technology, 920
- autonomous energy system, 1090
 - energy management strategies for, 1090–1092
- autonomous H₂ system, 1091
 - control strategy using battery state-of-charge for, 1091
- autonomous power supply, 1075
 - converters, 1083
 - fuel cells used in, 1086
 - schematic diagram of an, 1082
 - system configurations for, 1092–1093
 - demand side management, 1092
 - fuel for vehicles, 1093
 - oxygen use, 1093
 - seawater desalination, 1092–1093
 - system design/Configuration for, 1082–1083
- autonomous PV–H₂ system, 1092
 - hydrogen pressure level, and battery state of charge, 1092
- autothermal reformer, 204

- autothermal reforming (ATR), 25, 35, 131, 133, 134, 181, 190, 195, 197, 199, 202, 220, 221, 234
- autotrophs, 471
- auxiliary cabin heating system, 972
- auxiliary power systems, 976
- auxiliary power unit (APU), 133
 - gliding arc unit, components, 133
- Azospirillum brasilense*, 470
- Azospirillum lipoferum*, 470
- b**
- balance equations, 179
- balancing mechanism (BM), 261
- balancing power plants, 1057
- band gap, 443–448, 453, 454
 - necessary to split water, 444
 - positions, for semiconductors, 443, 444
- batteries, 265
 - and charging technology, 711
 - quick charging stations, 711
- battery electric vehicles (BEVs), 842
- battery-powered vehicles, 827
- battery type brake energy recovery, 987
- bauxite, 53
- benzene–water systems, 659
- Berlin Heidestrasse TOTAL hydrogen refueling station, 906
- BEVs. *see* battery electric vehicles (BEVs)
- biodesulfurization, 16
- biodiesel, 178, 473
- biofilm, 429
- biofuels, 65–66, 202, 393, 402, 417, 473, 476, 1058
 - environmental performance of, 403
 - production by other organisms, 473
 - – biodiesel, 473
 - – petroleum products, 473
- biogas, 224, 401, 427, 476, 543
 - fermenter tank, 1041
 - reforming, 398–399
- biohydrogen, 393, 417, 476
 - advantages of, 477
 - application of, 476
 - approaches, 395
 - – state of technology and research, and industrial players, 395–397
 - – technical characteristics, 395–397
 - economic aspects of, 477
 - production, 427
 - BOD, 427
 - by dark fermentation using bioreactor, 428
 - – from organic residues by dark fermentation, 427
 - – palm oil mill effluent (POME), 427
- bio-hydrogenation processes
 - economic analyses of, 430
 - future prospects, 431
 - to make economically viable, 431
 - reactor costs, 431
- biological H₂ production, 463
 - advantages of, 463
 - classification, 464
 - designing of, 471
 - – Calvin cycle, 471
 - – genetically modified organisms, 471
 - endergonic reaction, 469
 - factors affecting, 470
 - factors influencing, 466
 - hydrogenase for, 466
 - methods to enhance, 474
 - – dark fermentative H₂ Production, 475
 - – genetic engineering for, 476
 - – photobioreactors, 474
 - – photolytic H₂ Production by microorganisms, 474
 - – photosynthetic bacterial H₂ production, 474
 - – water electrolysis, 474
 - nitrogenase, 463, 466
 - nitrogen fixation, 463
- biological hydrogen production, 419–420
- biomass, 109, 116, 237
 - catalysts, coke produced from, 119
 - cheaper, conversion into hydrogen, 431
 - concentration of typical intermediates for degradation of phytomass glucose and, 117
 - -derived fuels, 419
 - hydrogen production from, 237
 - hydrothermal carbonization (HTC) of, 110
 - hydrothermal gasification, 111
 - influence of lignin, 118–119
 - influence of proteins, 118
 - influence of salts, 118
 - liquefaction, 110
 - methane, nickel and noble metal catalysts, 119
 - reaction scheme of hydrothermal degradation, 117
 - solubilization of, 114
 - sources, as substrate for, 423
- biomass gasification product gas
 - carbon dioxide removal from, 534, 535
 - – separation performance for, 535
- biomass production and supply, 393

- biomimetic approaches, using inorganic systems, 441
 - biomimetics, 471
 - biophotolysis, 464
 - of water, 420
 - bioreactor, 427
 - biohydrogen production, by dark fermentation using, 428
 - choice of, 427
 - prevent corrosion, 429
 - bipolar cell configuration, 1036
 - bitumen, from tar sand, 3
 - boundary conditions, 515
 - definition of, 515
 - Bradyrhizobium japonicum*, 467
 - brake resistor function, 972
 - Brandenburg, concentration of renewable energy production capacity in, 1033
 - Brandenburg Technical University
 - Cottbus-Senftenberg (BTU C-S), 1040
 - Brunauer–Emmett–Teller (BET) model, 781
 - BTU C-S. *see* Brandenburg Technical University Cottbus-Senftenberg (BTU C-S)
 - bubble management, 302–303
 - bubble phenomena, 293
 - advancing and receding angles, 294
 - bubble departure diameter
 - predictions, 293–296
 - critical diameter, stagnant model
 - approximated equation, 295
 - gas bubble on an electrode surface, schematic diagram, 294
 - model predictions with experimental observations
 - comparison of, 296–297
 - prediction of critical diameter, parameters used in, 296
 - bubble resistance, 293
 - buffer capacity, 796
 - buffer hydrogen, 796
 - buffer pressure, 797
 - bulk density, 800
 - bus applications, auxiliary power demands for, 970, 971
 - bus propulsion system, 967
 - acceleration behavior, 970
 - aerodynamic quality of, 969
 - auxiliary power demand, 970
 - heating and air condition power demand, 971
 - hill climbing capability, 969
 - internal combustion engines, 969
 - maximum acceleration, definition of, 969
 - propulsion power to drive, 967
 - bus refueling, 894
 - 350 bar tanks, 894
 - fueling nozzle, 894
 - high storage density, 894
 - pre-cooling step, 894
 - protocols, 894
 - Butler–Volmer kinetics, 596
- C**
- Ca-compounds, 101
 - CAES. *see* compressed air energy storage; compressed air energy storage (CAES)
 - Caldanaerobacter subterraneus*, 420
 - Caldicellulosiruptor owensensis*, 429
 - Caldicellulosiruptor saccharolyticus*, 420
 - California Energy Commission (CEC), 843
 - Canada
 - energy framework and relevant policies, 70
 - National Energy Board role, 70
 - hydrogen related energy policy strategies, 74
 - Canadian Hydrogen and Fuel Cell Association (CHfCa), 74
 - hydrogen research, development, demonstration, and deployment activities, 74–75
 - hydrogen and fuel cells progress, 75
 - RD&D expenditure, 74, 75
 - refueling infrastructure, 74
 - viability of hydrogen production and purification, 74
 - Canary Islands, 1080
 - Instituto Tecnológico de Canarias (ITC), 1080
 - capacity factor, 1087
 - CAPEX. *see* capital expenditure (CAPEX)
 - capital expenditure (CAPEX), 276, 406, 408, 733, 751, 843
 - carbohydrates, 475
 - carbon capture and storage (CCS)
 - process, 1022
 - carbon-containing byproducts, 138
 - carbon dioxide (CO₂), 190, 417, 517, 547, 629, 635
 - emissions, 1011
 - man-made, 283
 - platinum, 547
 - thermodynamic equilibrium calculations, 547
 - carbon fiber (CF), 713, 794
 - carbon footprint
 - of refinery operations, 4

- carbon footprints
 - of different energy sources, 418
- carbon formation, 153, 179
 - during cracking, 7
- carbon monoxide (CO), 186, 190, 206, 237, 544, 546, 635, 900
- carbon nanostructures growth, 785
- carbon number, 116
- carbon oxides, 139, 491
- carbon source, 470
- carbon suboxide, 140
- car refueling, 892
 - with compressed gaseous hydrogen (CGH), 893
 - with conventional fuels, 894
 - user-friendly, 893
- carrier induced granular sludge bed reactor (CIGSB), 427
- CASE. *see* compressed air energy storage (CAES)
- case study, 800
 - reverse engineering, 800
 - – metal hydride refueling, 802
 - – reference targets, 804
 - – sensitivity study, 805
 - – study parameters, 801
 - – system analysis model, 803
- catalyst poison, 546
 - carbon monoxide, 548
- catalysts, 119
 - choice, 201
 - -coated membrane (CCM), 300, 335, 338, 339
 - development, 200–201
 - screening, 186
- catalytic combustion, 188
- catalytic cracking, 7, 9, 11
- catalytic dehydrogenation, 819
- catalytic hydrolysis, 783
- catalytic oxidation, 41
- catalytic partial oxidation (CPOX), 193–198, 220
 - advantages, 193
- catalytic reactors, 180–181
 - catalytic combustion, 188
 - hydrogen generation, 181–184
 - preferential oxidation, 186–187
 - selective CO methanation, 187–188
 - water–gas shift reaction, 184–186
- catalytic reduction, 557–558
- cathode activation process, 1050
- caustic soda, 41, 43, 46
 - economy of, 53–55
- CcH₂. *see* cryo-compressed hydrogen (CcH₂)
- CCM. *see* catalyst, -coated membrane (CCM)
- CCS. *see* carbon capture and storage (CCS)
 - process; CO₂ capture and storage (CCS)
- CEC. *See* California Energy Commission (CEC)
- cell density, 429
- cellulose, 115
 - hydrothermal biomass degradation, reaction scheme of, 117
- centralized hydrogen production, 835
- CeO₂/Ce₂O₃ redox system, 95
- CEP. *see* Clean Energy Partnership (CEP)
- ceramic honeycomb receivers, 156
 - development, 156–157
- ceramic membranes, 510
 - molecular sieving, 511
 - separation of hydrogen, 510
- Ceria, 95
- cerium-based oxides, 96
- cerium oxide, 95
- CF. *see* carbon fiber (CF)
- CGH. *see* compressed gaseous hydrogen (CGH)
- CGH₂. *see* compressed gaseous hydrogen storage (CGH₂)
- chemical batteries, 264. *see also* batteries
- chemical energy, 441
- chemical engineering thermodynamics, 175–180
- chemical equilibrium, 175, 178–180, 199
 - limiting cases, 178
- chemical industry, 19
- chemical kinetics, 797
- chemical reactions, 178
- chemoheterotrophs, 471
- Chernobyl, 88
- Chicago Transit Association (CTA), 982
 - test and field experience, 982
- Chlamydomonas reinhardtii* mutant Stm6Glc4, 466
- chlorine, 41
 - area of research, focused on, 49
 - diaphragm electrolyzers, 45–46
 - economy of, 53–55
 - electrochemistry of production, 42
 - energy saving in chlorine industry, 55–56
 - ion exchange membrane electrolyzers, 46–49
 - liquefaction systems, 49
 - mercury electrolyzer technology, 43–45
 - parameters for chlorine production cost, 43
 - production, industrial technologies, 42
 - – based on common principles, 42
 - usage, 52–53

- data from World Chlorine Council, 52
- World chlorine production, 54
- chlorine-alkali production
 - with oxygen depolarized cathode (ODC), 49–51 (*see also* oxygen depolarized cathode (ODC))
- chlorine production, 28–29
 - daphragm cell process, 31
 - hydrogen as by-product of, 32
 - membrane cell process, 29–30
 - mercury cell process, 30–31
 - new developments, 31–32
- chloroplast, 465
 - thylakoid membrane of, 465
- chloroplasts, 441
- CH₄/O₂ ratio, 142
- CHP. *see* combined heat and power (CHP) systems
- CHP fuel cell, 1064
- Citaro FuelCELL-hybrid, 984
- city bus, acceleration requirement for, 970
- class 205 submarine, 992
- clathrate hydrates, 659
- clathrates, 597
 - structure of the cubic clathrates, 597
 - tetrahydrofuran (THF), 597
 - tetra-*n*-butylammoniumfluoride (TBAF), 597
- Clean Energy Partnership (CEP), 61, 843, 892
- Clean Power Net, 64
- clean-up technology, 230–231
- clean urban transportation, 967
- climate change, 1011
- climate protection, 417
- Clostridium thermocellum*, 420
- CMBC. *see* Costal Mountain British Columbia (CMBC)
- CO. *see* carbon monoxide (CO)
- coal, 3, 543, 1076
 - gasification of, 543
 - partial oxidation of, 32
- coal-based production
 - of ammonia, 26
- coal gasification, 242, 244, 331, 393
 - in different reactor types, conditions of, 243
- cobalt, 7, 91
- cobalt-molybdenum-alumina, 7
- cobalt-molybdenum catalysts, 7
- cobalt oxide, 7
- CO₂ capture and storage (CCS), 1011
- CoE. *See* cost of electricity (CoE)
- CO₂ emissions, 64, 109
 - from small-scale reforming, 231
- CO₂ footprint, 231
- CO/H₂ ratio, 168
- CO₂ hydrogenation, 783
- coke formation, 5
- coke-forming reactions, 5
- cold gas clean-up, 552
 - adsorption processes, 552
 - downstream synthesis, 552
 - liquid scrubbing technology, 552
- combined cycle power plant, 244
- combined heat and power (CHP) systems, 1022
- combustion technologies, 1012, 1021, 1024
 - flameless oxidation, 1024
 - lean direct injection, 1026
 - micro-mixing, 1026
 - multi-injection, 1026
- CO₂ (or dry) methane reforming (DMR), 151
- complete gas cleaning system, design of, 205–208
- complex hydrides, 591–592, 773
 - alanates, 774
 - amides, 591, 775
 - borohydrides, 779
 - hydrido alanates, 591
 - hydrido borates, 591
 - imides, 591
- compressed air energy storage (CAES), 265, 622
- compressed gas, 441
- compressed gaseous hydrogen (CGH), 893
- compressed gaseous hydrogen storage (CGH₂), 712–714, 812
 - refueling, 717–719
 - validation
 - challenges, and opportunities, 729
 - procedure, 726–729
- compressed gas storage, special forms of, 704
- compressed gas systems for vehicles, specific requirements, 699
 - common filling stations, types, 703
 - filling procedure, standardized, 701
 - filling receptacle, 701
 - legal and normative requirements, 699–700
 - refueling, 700–704
 - temperature curve, filling vehicle tank, 702
- compressed hydrogen storage, 659, 662
 - hydrogen compression, 662–663
 - hydrogen pressure vessels, 663
 - conventional small-scale bulk storage, 663–665
 - current and potential small- to medium-scale bulk storage, 665–669

- medium-scale bulk storage, new ideas for, 669
- large quantities, 659
- compressibility factor, 606
- compression, 314–316, 752
 - compressors, application ranges for, 754
 - cost optimum for, 315
 - energy demand
 - isothermal/adiabatic, 315
 - multi-step adiabatic, 315
 - of helium gas, 752
 - of hydrogen gas, 752
 - ideal isentropic compression process, 752
 - inlet temperature (T_{in}), 752
 - isentropic exponent, 752
 - impact of, 752
 - low density, 753
 - Lysholm screw rotors, 754
 - outlet temperature (T_{out}), 752
 - pressure ratio (p_{out}/p_{in}), 752
 - reciprocating compressors, 755
 - screw compressor, 753
- compressors, 643, 903
 - diaphragm, 904
 - ionic, 904
 - LH₂ pump, 904
 - piston, 903
- concentrated solar power (CSP), 151
 - technology, development and perspective, 168
- concentrated solar power (CSP) plants, 825
- concentrating receiver system (CRS), 88
- concentration polarization, 515
- condensation, 5
- conduction band (CB), 442
- conductivity, 447
- CO₂-neutral hydrogen production, 1042
- conformable containers, 705–707
- continuous stirred tank reactors (CSTRs), 427, 429
 - disadvantage with, 430
 - hydrogen production using, 429
- control strategy using battery state-of-charge, 1091
- conventional hydrogen production, 419
- conventional vehicles, 834
- coolant, 791
 - temperature, 794
- copper, 544
- CO₂-reduction strategy, 967
- corona-based plasma, 142
- corrosion, 98, 100, 429, 447, 450, 635, 888, 944, 1012, 1083
 - resistance, 859
- Costal Mountain British Columbia (CMBC), 982
 - test and field experience, 982
- cost of electricity (CoE), 1022
- coupling hydrogen production, 1059
- coupling reforming with solar energy, 154
- covalent bonding, 565–566
 - atomic orbitals, 565
 - diatomic molecules, 565
 - natural isotopes, 566
 - wave functions, 565
- covalent hydrides, 590–591
 - bond, 590
 - hydrogen bonds, 591
 - London forces, weak, 591
 - nonpolar bonds, 590
 - oxidizing agents, 591
- cracking quality, 7
- crude glycerol, 897
- crude oil, chemical nature, 3
- cryoadsorbing storage systems, 659
- cryo-compressed gas, 711
- cryo-compressed hydrogen (CCH₂), 713
 - heat receptivity, 716
 - hydrogen safety validation, 730–731
 - refueling, 718, 719, 724
 - storage density change during, 725
 - storage in a density–temperature diagram of hydrogen, operating range, 715
 - storage options, heat receptivity, 716
- storage system
 - operating principles, 722–725
 - system design, 720–722
 - prototype 2013, 720–722
 - thermodynamic opportunities, 714–717
 - validation challenges, and opportunities, 729
 - validation opportunities, 729
 - validation procedure, for storage system, 726–729
 - vehicle storage, 713
 - operating range, 726
 - validation challenges, 725–726
 - volumetric efficiency, 714
 - storage options, 714
- cryo-compressed refueling unit, 718
- cryocooler, 961
- cryogenic air separation, 237
- cryogenic fluid management (CFM) technologies, 959
- cryogenic hydrogen, 903
 - tank, 1002
- cryogenic liquid, 601

- cryogenic liquid hydrogen storage, 670
 - hydrogen liquefaction, 670–671
 - – physical and chemical properties relevant for, 670
 - liquid hydrogen storage tanks, 671–675
 - – boil-off rate of storage tanks, 675
 - – horizontal and vertical tanks, technical data of, 672
 - – spherical storage tank of NASA, 673
 - – tanks depending on their size, technical data, 673
- cryogenic liquid oxygen tanks, 1004
- cryogenic storage tanks, 864
- cryopumps, 904
- CSP. *see* concentrated solar power (CSP) plants
- CSS. *see* cyclic steady state
- CTA. *see* Chicago Transit Association (CTA)
- Cu catalysts, 201
- cumulated non-renewable energy demand, 405
- CUTE bus fleet, FC-powertrain design of, 971
- CUTE-plus program, 977
- CUTE program, 975
 - test and field experience, 984
- Cu/ZnO catalysts, 139
- cyanobacteria and microorganisms, 420
 - culture of, 471
 - genetic modification of gene in, 473
 - for H₂ production, 465
 - [NiFe]-hydrogenase, 466
 - nitrogen fixing/non-nitrogen fixing, 465
 - Nostoc species, 467
 - oxidative stress, 470
 - photosynthetic electron transport pathway, 468
 - physiology of, 465
 - uptake hydrogenase
 - – *Bradyrhizobium japonicum*, 467
 - – cyanothecae, 468
 - – *Pyrodicticum brockii*, 467
 - uptake hydrogenase (HUP), 467
- cyclic steady state (CSS), 495
- cyclohexane, 203
- d**
- Dalton's law, 316
- Danish island of Lolland, 1081
 - biogas, 1081
 - Hydrogen Community of, 1081
- dark fermentation, at thermophilic temperatures, 420
- dark fermentative H₂ production, 475
 - acetate, 475
 - butyrate, 475
 - carbohydrates, 475
 - glucose dehydrogenase, 476
 - hydrogen partial pressure, 476
 - metal ions, 476
- DBD reactor, 139, 141
- DC/AC converter, 1083
- DC/DC inverter, 1083
- DEA. *see* amines like diethanolamine
- de-carbonization, 256
 - of energy sectors and chemical industry, 275
 - strategies, 59
- dehydrating reaction, 774
- dehydrogenation, 135
- demand-side management (DSM), 262, 263
- demand–supply matching, 258
- density
 - current, 289, 291–292, 319, 348, 452, 1048, 1050, 1084, 1088
 - energy, 271, 670, 852
 - flux, 580, 583
 - gravimetric, 763
 - hydrogen and methane, 632
 - material, 800
 - power, 368, 381, 639, 994, 1025
 - storage, 694, 715, 724
- Department of Energy (DoE), 1024
- derived equilibrium hydrogen pressure for electrochemical hydrogenation, 596
- desorption, 496
 - enthalpy, 792
 - kinetics, 797
- destructive hydrogenation, 5
- desulfurization, 11, 16, 201, 218, 237
 - developments in routes to, 16
- detonation, 645
- deuterated water, 566
- deuterium, 566, 764
- Deutsche Bahn, 898
- diaphragm cell process, for production of chlorine, 31
- diaphragm compressors, 904
- diaphragm electrolyzers, 45–46
- diatomic molecules, 565, 764
- dielectric barrier discharge (DBD) plasma apparatus, 139
- dielectric heating, 140
- dielectric material (quartz), 139
- Diels–Alder reaction, 115
- diesel-electric power supply system, 991
- diesel engines, 991

diesel fuels, 3, 143, 201, 419

- fuel processor subsystem, for autothermal reforming, 196
- low sulfur, 933
- potential design, fuel processor subsystem for steam reforming, 197

diesel generator, 991

diesel oil, 16

diesel systems, 1056

diffusion in gasses, 579–580

- mass flux density, 579
- self-diffusion coefficients of pure H_2 , 581

dimerization, 115

4,6-dimethyldibenzothiophene (DMDBT), 201

di-olefins, 8

DIPPR project, 177

direct current (DC), 317

- -spark discharge plasma, 143

directly irradiated reactor/receiver, 155

directly irradiated reactors, 163

- non-structured reactors based on
 - solid particles, 167
- structured reactors based on
 - ceramic foams, 163–166
 - ceramic honeycombs, 163
 - fins, 166

directly irradiated receivers (DIRs), 156

- with stationary absorbers, 156

directly irradiated volumetric receiver–reactors (DIVRRs), 157, 168

direct methods, 611

direct tank cooling, on liquid oxygen side, 962

discharge time, 264

- electricity storage systems, 277

distillate hydrotreating, 5, 7

distillery industry waste, 425

dodecane, 176

- autothermal reforming
- heat of reaction and heat for steam supply for, 198
- mapping of hydrogen yield for, 200
- bond energies for, 178

dodecane ($C_{12}H_{26}$), 146

DOE. *see* US Department of Energy (DOE)

doping, 300

DOT. *see* US Department of Transportation (DOT)

double-barrier principle, 1006

DSM. *see* demand-side management (DSM)

Dutch energy system, 260

e

EC. *see* European Commission

EcoIsland project, 1081

eddy currents, 643

EEX. *See* European Energy Exchange (EEX)

E_F . *See* Fermi energy (E_F)

effective medium theory, 769

EFTA. *see* European Free Trade Association

EIA. *see* environmental impact assessment (EIA)

electrical and transport resistances, 292

electrical energy, 331, 629

electrical grid loads, 350

electrical grid modernization, 262

electrical power grid, 284

electrical resistances, 292–293

electric discharge systems, 141

electricity, 89

- demand, 284

electricity energy storage, installed capacities by technology, 267

electricity, from the German grid, 403

electricity grid operation

- overview of services, energy storage solutions provide relating to different aspects of, 267

electricity grid system, 258

electricity load management

- potential of DSM for, 264

electricity network, 255

electricity peak shaving, 284

electricity price, 406

electricity shedding, 261

- annual, 260

electricity shortage, 255

electricity storage, 264, 1057, 1058

- large-scale, 265

electric vehicles, 833

electrocatalysts, 448

- electrode potential, as a function of current density, 449
- and overvoltage, 448

electro-catalysts, 298–300

electrochemical devices, 543

electrochemical environment, 441

electrochemical equations, 443

electrochemical splitting, of water, 310

electrochemistry

- chlorine production, 42
- with ODC technology, 49
- of NaCl electrolysis with an ODC, 50

electrode–electrolyte interfaces, 441–442, 447, 448

electrode kinetics, 287–288

- cell overpotential, 291–292
- electrical and transport resistances, 292
- hydrogen generation overpotential, 288–290
- oxygen generation overpotential, 290–291
- electrodes, 297–298
 - hybrid, 447
 - hydrogen overpotential, 301
 - for a mass market, 441
 - metal, 297
 - Ni electrodes, 298
 - oxygen overpotential, 301
 - photoactive, 445
 - surface modifications, 298
- electrolysis, 41, 217, 226, 544, 897, 1083
 - high temperature solid oxide, 1085
 - hydrogen generation rate, 1083
 - oxygen produced in, 1093
 - water, 1093
- electrolyte, 50, 206, 289, 296, 302, 312, 362, 376, 441, 450, 544, 1041, 1065, 1088
- electrolyzers, 41, 461, 629, 814, 1083–1085
 - alkaline, 1083
 - capacity factor, 1087
 - commercial, 331
 - coupling efficiency, 1087
 - direct coupling of, 1088
 - dynamic operation of, 317–318
 - dynamic system response, 320–321
 - efficiency of an, 1084
 - electronic control for, 457
 - gas drying, 316–317
 - for hydrogen production, 331
 - intermittent operation, 1088
 - operation range of, 318–320
 - performance degradation with time, 1088
 - polymer membrane, 1084
 - power required to run, 1085
 - power supply technologies for, 317
 - proton exchange membrane (PEM), 1083
 - role in energy transition, 270–274
 - sizing of, 1088–1090
 - standby mode, 322
 - startup and shutdown process, 322
 - system design criterion, 322
 - system efficiency, 322–325
 - technology, 835
 - thyristor-based power supply, 317
 - transistor-based power supplies, 317
 - typical, 1084
 - water consumption, 1088
- electrostatic forces, 554
- electrostatic precipitators (ESPs), 554
- ENCAP. *See* ENhanced CAPture of CO₂ (ENCAP)
- energetic application, 393
- energetic efficiency, 401
 - free, 402
- energy conversion solution, 965
- energy demand, 309, 401, 402
 - for water electrolysis, 365
- energy losses
 - caused by reaction resistances, 293
- energy management, 261
- energy production, fluctuated, 309
- energy security, 1058
- energy storage, 711
 - capabilities of UK power and gas network, 276
 - evolution of demand for, 268–270
 - facilitates, 262
 - globe drive demand for, 256
- energy supply, 309
 - by renewable energy sources, 310
 - system, 811
- energy systems, features, 360
- energy transition, 255
- energy, Worldwide demand for, 417
- ENERTRAG AG, 898
- ENhanced CAPture of CO₂ (ENCAP), 1023
- enthalpy, 132, 174, 175, 177, 199
- enthalpy–entropy relationship, 794
- entrained-flow gasifier, 243
- entropy, 177, 445
- environmental friendly certificates, 967
- environmental impact assessment (EIA), 880
- environmental regulations, 3
- equation of state (EOS)
 - for gas/fluid mixtures, 631
- equilibrium constant, 179, 241, 574, 580, 595
- equilibrium pressure, 595–596, 766, 794, 796–799, 807
- Escherichia coli*, 473
 - genetic engineering of, 473
- ESPs. *see* electrostatic precipitators (ESPs)
- ethane, 6, 135, 202, 203, 545, 1016
- ethanol, 134, 135, 139, 174, 182, 422, 473, 840
 - steam reforming, 201
- ethene, 202, 203
- ethylene, 8, 201, 877
- ethylene glycol, 792
- EU27 member states
 - hydrogen production, 21
 - uniform permitting process suggested for, 926

- European Association for Storage of Energy (EASE), 266
- European chlorine production capacity, 30
- European Commission (EC), 926
 - directive proposal regulating hydrogen supply for transport, 926–927
- European Energy Exchange (EEX), 1045
- European energy policy, 891
- European Free Trade Association (EFTA), 923
- European Hydrogen Association (EHA), 81
 - Project HyER, 81
- European hydrogen production, 21
- European launchers, 954
 - Ariane 5 ECA, 954
 - coasting phase, 954–955
 - GEO/GTO orbits, 954
 - re-ignition preparation phase, 954–958
 - boiling curves, 957
 - formation of vapor bubbles, 956
 - geyser formation during re-orientation phase, 956
 - satellite, with apogee engine, 954
 - Vinci engine, 954
- European project DECARBit, 1021
- European standardization bodies, 927
- European Union, 920
 - CO₂ emission reduction target, 256
 - Commission
 - adopted communication “Energy Roadmap 2050,” 256
 - de-carbonization objective, 256
 - energy framework and relevant policies, 68–69
 - cut carbon emissions by 2050, key goals, 68
 - objectives for 2020, 68
 - hydrogen related energy policy strategies, 69
 - hydrogen research, development, demonstration, and deployment activities, 69–70
 - intermittent renewable energy sources (RES), 258–259
 - legislative acts, 920
 - directives, 920
 - regulations, 920
 - renewable electricity in, 263
 - survey of FCH JU support activities, 70
 - survey of FCH JU supported projects of call for proposals made in 2011, 70–73
 - uniform permitting process suggested for EU27, 926
- evaporators, 192
- EvoBus product, 970
- EvoBus vehicle, 975
- exhaust gas, 1012
- expanded natural graphite, 799
- expansion turbine, 755
 - gas bearing, 757
 - oil bearing, 756
- f**
 - facultative photoautotrophic microalgae, 465
 - failure mode, effect and criticality analysis (FMECA), 924
 - Faraday constant, 442
 - FC bus, 978
 - FCC. *see* fluid catalytic cracking
 - FCCJ. *see* Fuel Cell Commercialization Conference of Japan (FCCJ)
 - FCEVs. *see* fuel cell electric vehicles (FCEVs)
 - FCH JU. *see* Fuel Cells and Hydrogen Joint Undertaking (FCH JU)
 - FC-power plant, 972
 - FC-powertrain, 970
 - FCSs. *see* fuel cell systems (FCSs)
 - FCTO. *see* Fuel Cell Technology Office (FCTO)
 - FC-twin system, 979
 - Fe-compounds, 101
 - Federal Ministry of Education and Research (BMBF), 64
 - feedstock options, 223
 - feedstock purification, 238
 - Fe₃O₄/FeO, as redox material, 90
 - Fermi energy (E_F), 769
 - fermions, 566
 - ferredoxin (PetF), 465
 - ferrites, 91–93
 - cobalt and nickel ferrites, favorable thermodynamic properties, 93
 - demonstrated within the European projects, 91
 - Hydrosol pilot plant, 92
 - solar HYDROSOL reactor, 92
 - two-step thermochemical cycle, 91
 - hydrogen production via a redox cycle using, 93
 - utilization of a rotary kiln, 93
 - work on fluidized bed reactors, 93
- fiber-reinforced polymer (FRP), 859
- FICFB gasification technology, 398
- Fick’s law, 512
- filter, 553
 - types of, 553
- filter press principle, 1036
- first law of thermodynamics, 618
- Fischer-Tropsch reactions, 23, 36, 151, 225, 246, 519, 814

- fixed-bed bioreactor, 427
- fixed bed gasifier (Lurgi reactor), 242
- flameless oxidation (FLOX[®]), 1024
 - combustor characteristics, 1025
 - measured NO_x values in, 1026
- flame monitoring system, 1008
- flat sheet modules, 526
 - baffle plates, 527
 - envelope type membrane, 526
 - hydrogen selective membranes, 526
 - poly(ethylene oxide), 526
 - polysep membranes, 526
 - spiral wound membrane element, 526
- Flory–Huggins model, 512
- fluid catalytic cracking (FCC), 557
- fluidised-bed gasifier (Winkler process), 243
- fluidized-bed bioreactor, 427
- flywheels, 264, 265
- FMECA. *see* failure mode, effect and criticality analysis
- food industry waste, 425, 427
- formic acid, 814
- fossil-based CO₂ emission, 217
- fossil diesel, 403
 - in agricultural machines, 405
- fossil energy, 109, 309, 419
- fossil fuels, 22, 88, 109, 140, 151, 168, 201, 237, 283, 359, 405, 417, 419, 517, 629, 811, 891, 1075
 - catalyst development for, 201
 - combustion of, 403
 - hydrogen production from, 1076
 - for rapid industrialization and urbanization, 417
 - synthesis gas (syngas) produced from, 237
 - technologies, 256
 - used for electricity generation, 417
 - utilization of, 1075
- FRP. *see* fiber-reinforced polymer (FRP)
- fuel cell, 1086–1087
 - bus, 967
 - efficiency of, 1086
 - module, 977, 996, 1000, 1001
 - polarization curves, 1084
 - regenerative, 1083
 - supporting system, 1086
- fuel cell/battery hybrid vehicle, 1077
- Fuel Cell Commercialization Conference of Japan (FCCJ), 844
- fuel cell electric vehicles (FCEVs), 61, 64, 274, 711–712, 833
 - components, 834
 - functions, 834
- fuel cell modules, 977, 1000
 - BZM 34, 1000, 1001
 - BZM 120, 1000, 1001
- fuel cell powertrains, 973
 - automotive glycol cooling loop, 974
 - Citaro fuel cell-hybrid, 978, 979
 - CUTE program, 975
 - design solutions, 973
 - NEBUS, 973
 - hydrogen circulation in, 974
 - NEBUS, 973
 - design solution, 973
- fuel cells, 284, 543
- Fuel Cells and Hydrogen Joint Undertaking (FCH JU), 841
- fuel cell systems (FCSs), 204, 791
 - in mobile applications, 173
- fuel cell technology, 982
 - life time of, 989
 - product costs, 989
 - start–stop strategies, 987
- fuel cell technology office (FCTO), 850
- fuel choice, 173
- fuel consumption, minimization strategies, 965
- fuel gases, 543
 - potential sources of, 543
- fueling operations, 849
- fueling station, 217, 660
- fuel/pollutants, 545
 - carbonyl sulfide, 545
 - gas composition of untreated product gas, 546
 - gasification synthesis gas, 545
 - hydrogen sulfide, 545
 - main gas components, 545–547
 - carbon dioxide, 547
 - carbon monoxide, 546
 - hydrogen, 546
 - methane, 546
 - nitrogen, 547
 - steam, 547
 - mercaptans, 545
 - trace gas components, 547–550
 - alkali compounds, 549
 - halogen compounds, 550
 - nitrogen compounds, 550
 - other potential contaminants, 550
 - particulate matter, 549
 - siloxanes, 550
 - sulfur compounds, 549
 - tars, 547
- fuel power, 134

- fuel processing, 174
 - arrangement of subsystems
 - – with no connecting heat exchangers, 193
 - current challenges in, 201–203
 - subsystems of, 192–193
- fuel processor subsystem, 191
 - for autothermal reforming of diesel as a draft, 196
 - consisting of autothermal reforming of diesel and a gas cleaning unit for PEFC systems, 191
 - for steam reforming of diesel as a potential design, 197
- fuel production, 1057, 1059
- fugacity coefficients, 176, 177
- fullerenes, 145
- future energy carriers, 1033
- g**
 - gas cleaning subsystem, as a possible design for a PEFC system, 207
 - gas clean-up for fuel cell systems, 543
 - gas drying, 316–317
 - specific gas constants, 316
 - gaseous hydrogen, 812
 - safety related precautions, 939
 - gaseous hydrogen delivery, 857
 - pipeline delivery pathway, 857
 - tube-trailer delivery pathway, 860
 - gas hourly space velocity (GHSV), 181
 - gasification, 5, 26
 - of alcohols and organic acids, 116
 - glucose, 113–115
 - processes, 237
 - of solid fuels, hydrogen production by, 242–244
 - gas oils, 7
 - gasoline, 3, 5, 134, 143, 201, 419
 - -based cars, 827
 - dispenser, 711
 - reformed, effects of sulfur in, 202
 - refueling stations, 711
 - yields, 15
 - gas permeation, 190
 - gas permeation, in polymers, 580–583
 - coefficients of hydrogen for, 582
 - Fick's first law, 580
 - Henry's constant, 580
 - permeation coefficients of some selected polymer, 584
 - polymer membrane, 580
 - gas separation, 313–314, 509
 - KOH-solution level in vessels, 314
 - membrane process, 510,
 - gas–solid reactions, 101
 - gas storage system, 617
 - energy balance of, 618
 - storage temperature, 619
 - temporal change of mass, 617
 - gas transport, 642
 - gas turbine (GT), 1011
 - burning hydrogen in, 1012
 - classification of, 1020
 - combustion fundamentals of hydrogen, 1012
 - – emissions, 1018
 - – flame speed, 1016
 - – flame temperature, 1018
 - – ignition delay, 1014
 - – stability, 1018
 - combustor, 1011
 - new combustion technologies, 1022, 1024
 - – flameless oxidation, 1024
 - re-electrification of, 1055
 - research and development status, 1022
 - gas turbines, 309
 - genetically modified organisms, 471
 - genetic biomarkers, 476
 - genetic engineering, to enhance hydrogen production, 476
 - genetic biomarkers, 476
 - renewable biofuel, 476
 - *Rhodobactor sphaeroides*, 476
 - GEO (geostationary orbit), 954
 - geological hydrogen storage, 629
 - fundamental aspects, 631
 - geological storage option, general types of, 635–636
 - hydrogen and microbial inventories, interaction between, 634–635
 - hydrogen storage, in caverns, 640–642
 - hydrogen storage, in porous rocks, 636–640
 - integrated power-to-gas concept, schematic drawing of, 630
 - operational hydrogen storage projects, 649–650
 - – mixed hydrogen–natural gas, 650
 - – pure hydrogen sites, 650–651
 - – town gas storages, 651–654
 - physicochemical properties, of hydrogen and hydrogen mixtures, 631–634
 - process engineering, importance in, 642–649
 - storage options, according to storage capacity and discharge time, 630
 - geothermal power, 1080

- geothermal renewable energy, 1080
 - German Renewable Energy Law, 406
 - German wind–photovoltaics–electrolyzer system, 1034
 - Germany, 60, 601, 891
 - copper plate model, 261
 - electricity grid, 261
 - energy framework and relevant policies, 60
 - Energy Package, 60
 - master plan, 60
 - energy management, 261
 - hydrogen as road transport fuel in, 601
 - hydrogen related energy policy strategies, 60–61
 - National Hydrogen and Fuel Cell Technology Innovation Programme (NIP), 60–61
 - hydrogen research, development, demonstration, and deployment activities, 61
 - hydrogen production, 63
 - industry activity, 64–65
 - goal of, 64
 - “H2Mobility” group, 64
 - multi-energy filling station, 61–63
 - special markets, 64
 - stationary and residential applications, 63–64
 - transportation, 61, 63
 - PEM-fuel cells development at Siemens, 992
 - renewable electric energy production in, 1033
 - renewable energy, fuel capacity of, 1033
 - town gas storage project, 652–653
 - wind energy shedding, 261
 - GHGs. *see* greenhouse gases (GHGs)
 - Gibbs energy, 90, 178, 179
 - Gibb’s free energy, 145, 442, 445
 - gliding arc, 135
 - discharge plasma assisted methane reforming with CO₂, 135
 - plasma, 132–136
 - global annual hydrogen production, 393
 - global warming, 255, 417
 - glucose, 113–115
 - aldol-splitting, 113
 - conversion under hydrothermal conditions, 114
 - degradation products, 113
 - gasification, 114
 - glycerol, 471
 - glycine, 115
 - glycosidic bonds, 115
 - graphene coatings, 352
 - gravimetric energy density, 812
 - green algae, 420, 465, 469
 - green energy, 423
 - greenhouse effect, 188
 - greenhouse gases (GHG), 132, 402, 417, 629, 867
 - emissions, 59, 394, 403, 417
 - for hydrogen concepts, 405
 - mitigation potential, 404
 - green hydrogen filling station infrastructure, 1034
 - green hydrogen, production of, 1033
 - grid-related services, 266
 - grid-scale renewable energy storage, 276–277
 - grid stability, 255, 309
 - gross vehicle weight (GVW), 975
 - growth conditions, 470
 - GTO (geostationary transfer orbit), 954
 - gums, 5
 - GVW. *see* gross vehicle weight (GVW)
- ## h
- Haber–Bosch process, 32
 - hardware simulations, 1061
 - harmonization, 218
 - harvesting system, 441
 - Hawaii, 1081
 - animal fats, 1081
 - energy solutions for, 1081
 - plant oils, 1081
 - pressure swing adsorption (PSA) process, 1081
 - syngas feedstocks, 1081
 - HAZard and OPerability study (HAZOP), 924
 - HAZard Identification (HAZID), 924
 - HAZID. *see* HAZard Identification
 - HDW class 212A submarine, 992, 1004–1005
 - HDW class 214 submarine, 992, 1005
 - HDW fuel cell system, 1005
 - safety concept of, 1006
 - heat conduction, 204
 - heat exchangers, 192, 758
 - aluminum plate fin, 758
 - heat extraction, 156
 - heat generation, 349
 - heating–cooling cycles, 156
 - heat loss, 430
 - heat-of-combustion, 177
 - heat of formation, 178
 - heat of reaction, 193
 - heat of vaporization, 156
 - heat pipe receiver, 156

- heat pumps, 785
- heat receptivity, of cryo-compressed and liquid
 - hydrogen storage, 716
- heat transfer, 155, 799
 - equations, 617, 619
- heat transfer fluid, 155, 156
- heavy aromatic feedstock, 9
- heavy duty transport, 173
- heavy metal
 - impurities, 237
- heavy oils, 16, 237
 - feedstock and raw syngas composition
 - of Texaco process, 246
 - gasification of, 245
 - syngas by partial oxidation of, 244
- HEC. *see* hydrogen evolving catalyst (HEC)
- HEGSA. *see* high efficient gas turbine with syngas application (HEGSA)
- helium, 134
- Helmholtz free energy, 603
- Henry's constant, 580
- Henry's law, 512
- hercynite cycle, 93–94
- heterocyst, 465
- heterogeneous catalysis, 174
- heterotrophs, 471
- hexadecane, 140
- hexane, 202
- Heyrovski reaction, 596
- HFCEVs. *see* hydrogen fuel cell electric vehicles (HFCEVs)
- H₂–H₂ interaction, 764
- Hidráulica project, 1058
- high efficient gas turbine with syngas application (HEGSA), 1023
- high-frequency pulsed plasma (HFPP), 143
- high-temperature electrolysis, 331
- Hindenburg syndrome, 934
- hollow fiber modules, 525
 - Evonik Industries design, 525
 - high packing density, 525
 - schematic representation of, 526
- hot gas clean-up, 552
 - industrial-scale applications, 552
- HRSs. *see* hydrogen refueling stations (HRSs)
- HRU. *see* hydrogen, release unit (HRU)
- HSER. *see* hydrogen sorption-enhanced reforming (HSER)
- HUP. *see* uptake hydrogenase
- HV components, 980
 - hub wheel drive, 980
 - HV battery, 980
 - inverters, 980
 - multi converter for auxiliary power, 980
- hybrid copper chlorine cycle, 100–102
 - heat required for reaction, 101
 - idealized efficiency, 101–102
 - thermal reactions, 101
- hybrid electric passenger vehicles, 711
- hybrid electric vehicle (HEV), 712
- hybrid electrodes, 447
- hybrid power plant, operating modes of, 1042
 - base load, 1043
 - example of, 1043
 - EEX, 1045
 - forecast, 1044
 - hydrogen production, 1042
 - advantage of, 1042
 - example of, 1042
- hybrid power plant project, 1034
 - alkaline water electrolysis, 1034
 - main components of, 1035
 - at Prenzlau, 1035, 1036
 - wind turbine–electrolyzer coupling, 1034
- hybrid SMR-POX catalytic system, 147
- hybrid sulfur cycle, 89, 96–98
- hybrid thermochemical cycles, 89
- hydraulic pistons, 904
- hydraulic retarder, 972, 977
- hydraulic retention time (HRT), 429
- hydrides, 588–597
 - classification of, 588
 - complex hydrides (hydrido complexes), 591–592
 - covalent hydrides, 590–591
 - interstitial (metallic) hydrides, 592–593
 - ionic hydrides, 588–590
 - conversion with complex, 593–594
 - conversion with other, 593
 - formation of, 593–597
 - hydrolysis, 594
 - properties of, 588
 - covalent compounds, 588
- hydrido complexes. *see* complex hydrides
- hydrobromic acid, 98
- hydrocarbon cracking, 141
- hydrocarbon fuels, 140, 237, 1020
 - hydrogen production from, 237
- hydrocarbon membranes, 350
- hydrocarbons, 134, 143, 151, 237, 565
 - autothermic reforming of, 249
 - small-scale reforming, 217
- hydrochloric acid, 41
- hydrocracking, 5, 8–11, 16, 518
 - homogeneous catalysts based, 10
- hydrodesulfurization, 3, 5, 16, 238

- hydrodesulfurized products, 7
- hydrofining, 7
- hydrogen, 19, 135, 491, 546, 566, 601, 763, 891
 - absorption, 784
 - adsorption of, 493
 - alloys interactions, 764
 - applications, 891
 - and production processes in a refinery, 5
 - automotive industry, 491
 - based on biomass, 393
 - bomb, 934
 - bonds, 115, 591
 - cars, 219
 - cities, 1058
 - communities, 1058
 - compressed gaseous, 601
 - compressibility factor of, 606
 - compression work of, 614
 - containing pressure vessels, design, 715
 - conversion, main challenge for, 278
 - as coupled stream
 - in electrolytic production of chlorine, 28–29
 - data reported by Eurostat, 20–21
 - density of, 569
 - desorption, 791
 - desorption
 - from sodium alanate, 774
 - diffusion, 771
 - dissociation–recombination reaction, 771
 - distribution
 - to a filling station, 401
 - of produced hydrogen, 399–400
 - distribution costs, 410–411
 - distribution cost for a mean transport distance, 410
 - economy, 283, 1075
 - energy applications of, 784
 - energy industries, 491
 - energy relevant properties, 764
 - European production, 20
 - fractionation by gas permeation, 516–518
 - fuel cell vehicles, 217, 1034
 - as a fuel, importance and applications, 419
 - fuel properties of, 1013
 - fuel storage system, 980
 - gas, 1011
 - enthalpy of combustion, 461
 - storage, 1077
 - turbine technology, 1019
 - generation processes, indicated by educt mixture, 194
 - heat flow of, 624
 - H₂-PSA unit, 502
 - improvement of, 502
 - hydricity, 1075
 - ideal fuel, 1093
 - ignition delay time of, 1014
 - implementing agreement, 59, 81
 - inorganic solids interaction, 764
 - Islands Initiative, 1094
 - isotopes, 566, 764
 - deuterium, 764
 - tritium, 764
 - isotopes storage, 785
 - Joule–Thomson coefficient of, 608
 - laminar flame speeds of, 1016
 - lean molecules, 814
 - liberation, 791
 - liquid hydrogen storage, 601
 - management, 14–16
 - network, 16
 - metal interactions, 763
 - molecule, 565
 - network optimization, 3
 - ortho, 606
 - para, 606
 - pressures, 7, 1085
 - production
 - in nature, diverse pathway for, 464
 - route, 491
 - properties of, 461
 - purging cell, 997
 - purification, 491
 - membranes, 1008
 - purity, 221–223, 491, 495
 - upgrade, 15
 - quality, 912
 - real gas behavior of, 622
 - real isentropic exponent of, 610
 - recovery of, 492
 - in refineries, 4, 491
 - refueling stations, 217
 - refueling with compressed, 601
 - release unit (HRU), 827
 - requirements worldwide, 331
 - reversible orption of, 765
 - -rich fuels, 1011
 - as road transport fuel, 601
 - roles along chemical value chain, 19
 - safety and the elements of risk, 934–935
 - as secondary energy carrier, 891
 - selective membranes, 526
 - solubility, effect of salt on, 631
 - in space applications, 951
 - speed data of, 1016

- storage, 601, 767, 1085–1086
 - compressor, 1083
 - fuel cell, 1083
 - options, 712
 - systems, 173
 - tank, 1080
- supply infrastructure, 393, 1076
- technologies, under research, development, 59
- temperature, 614
 - change during expansion of, 616
- thermal conductivity of, 579
- in thermal processes, 4
- thermodynamic properties with methane, comparison of, 606–610
- uses and applications of, 36
- utilization, 15, 16
 - across different sectors, 20
 - technologies, commercialization of, 1076
- variation of storage tank
 - pressure of, 621
 - temperature of, 621
- vehicles, 1093
- volume required to store, 1086
- yield, 202
- hydrogen and Fuel Cells in the Economy (IPHE), 81
 - mission of the International Partnership, 81
- hydrogenases, 463, 465, 466
 - active-site structures of, 467
 - carbon monoxide, 467
 - catalytic activity of, 466
 - classes, identified, 466–467
 - for H₂ production, 466
 - hydrogen uptake, 467
- hydrogenation, 4, 7, 10, 237, 815
 - of aromatics, 11
 - selective, 11
- hydrogen/carbon monoxide separation, 517
 - methanol production, 517
 - purge gas, 517
- hydrogen combustion properties of, 1012
 - flame speed, 1012
 - flame temperature, 1012
 - ignition delay time, 1012
- hydrogen cost
 - calculation, 836
 - bottom-up approach, 836
 - top-down approach, 836
 - total cost of ownership (TCO) approach, 836
 - in Europe, 838
 - in Germany, 838
 - in Japan, 837
 - in USA, 836
- hydrogen delivery, 849, 900
 - CGH₂ delivery, 901
 - challenges, 849
 - costs, 850
 - infrastructure, 849
 - LH₂ delivery, 901
 - opportunities, 849
 - pipeline delivery, 901
- hydrogen demand, 850
 - daily, 850
 - hourly, 850
 - seasonally, 851
 - variation, 850
 - weekly, 850
- hydrogen diffusion, in metals, 583–587
 - electrochemical formation, 595–597
 - fluorite, 583
 - metallic membranes, 585
 - permeation coefficient for selected transition metal membrane, 586
 - rock salt, 583
 - Sievert's law, 583
 - wurzite, 583
- hydrogen embrittlement, 878
 - chemical hydrogen reaction, 878
 - environmental hydrogen, 878
 - metallic–physical processes, 878
- hydrogen energy project, 935
 - ALARP approach, 935
 - Do no harm approach, 935
- hydrogen energy storage, 1082
 - potential for, 1082
- hydrogen energy systems
 - NFPA 2: “Hydrogen Technologies Code,” 941
 - NFPA® 52, 941
 - regulations, codes, and standards, 940–942
 - Vehicular Gaseous Fuel Systems Code, 941
- hydrogen evolving catalyst (HEC), 448, 450
- hydrogen filling stations, 895
 - technical concepts for, 895
 - facility size, 907
 - hydrogen delivery, 900
 - hydrogen production, 895
 - hydrogen refueling stations components, 902
 - hydrogen refueling stations, integration of, 906
 - space requirements, 907
- hydrogen fuel cell electric vehicles (HFCEVs), 849

- hydrogen/hydrocarbon separation, 518
 - boiler fuel, 518
 - cold train distillation, 518
 - Huntsman Advanced Materials, 514
 - hydrocracker, 518
 - hydrotreater product gases, 518
- hydrogenics electrolyzer, 1065
- Hydrogen Implementing Agreement (HIA)
 - Task 30
 - on Global Hydrogen Resource Analysis, 59
- hydrogen in chemical industry, sources of, 22
 - electrolytic processes, 26
 - alkaline electrolysis, 27
 - high-temperature electrolysis, 27
 - PEM electrolysis, 27
 - hydrogen as coupled stream
 - in electrolytic production of chlorine, 28–29
 - hydrogen production
 - steam reforming vs. electrolysis, 28
 - process variations, 25
 - autothermal reforming, 25
 - gasification, 26
 - other waste and coupled streams, 26
 - partial oxidation, 25
 - pre-reforming, 25
 - water–gas shift conversion, 26
 - steam reforming, 23–25
 - synthesis gas-based processes, 22–23
- hydrogen infrastructure, 835, 907, 965
 - compression, 835
 - delivery cost, 835
 - dispensing cost, 835
 - incentives for promotion, 842
 - production cost, 835
 - refueling cost, 835
 - social benefits, 843
 - storage, 835
 - subsidy for, 843
 - tax credits, 842
- hydrogen interacting materials, energy
 - applications of, 784
 - chemical functions, 784
 - energy storage, 784
- hydrogen liquefaction, 733
 - conventional process, 740
 - compression, 740
 - cooling, 740
 - expansion, 741
 - economics of, 733
 - hardware components, 751
 - compression, 752
 - expansion turbine, 755
 - heat exchangers, 758
 - history of, 734
 - principles of, 739
 - final cooling, 749
 - hydrogen liquefaction processes, evolution of, 745
 - nitrogen Brayton Cycle precooling, 746
 - nitrogen precooling, Joule-Thomson process, 742
 - power requirements, 739
 - precooling part, process design of, 745
 - precooling purposes, mixed gas refrigeration for, 748
- hydrogen/nitrogen separation, 517
 - ammonia production, 517
- hydrogen peroxide (H_2O_2), 574
- hydrogen physics, 565
 - clathrates, 597
 - hydrides, 588–597
 - molecular hydrogen, 565
 - covalent bonding, 565–566
 - molecular orbitals, 565–566
 - natural isotopes, 566
 - nuclear spin-states, 566–569
 - thermodynamic properties, 569–573
 - reaction kinetics, 574–578
 - transport kinetics, 578–587
- hydrogen pipelines, 876
 - construction, 879
 - commissioning, 883
 - design parameters, adherence to, 888
 - dew point, 888
 - planning and approval, 879
 - project execution, 883
 - routes assessment, 880
 - servicing and operation, 888
 - steel material, selection of, 888
 - welding additive material, 888
 - decommissioning, 888
 - backfilling, 888
 - dismantling, 886
 - investment costs, 882
 - operations, 886
 - control center, 886
 - culvert soundings, 887
 - maintenance, 886
 - monitoring, 886
 - recurring regular tests, 887
 - regular route inspections, 887
 - repair, 886
 - troubleshooting, 886
 - reclassification, 888
 - system, 284

- hydrogen producing countries, 876
 - Belgium, 877
 - France, 877
 - Germany, 877
 - Japan, 876
 - Netherlands, 877
 - USA, 876
- hydrogen production, 12–14, 20, 88, 895, 1042
 - biological, 463, 900
 - from biomass, 896
 - biogas reforming, 897
 - biomass gasification, 897
 - glycerol reforming, 897
 - from biomass as feedstock, 422–423
 - byproduct hydrogen, 900
 - by other organisms, 473
 - by photosynthetic organisms, 461, 463
 - in the presence of sunlight, 464
 - source of renewable energy, 463
 - plant, 1042
 - power, 1042
 - processes, and impact on environment, 418
 - from solid fuels (coal, biomass), 242
 - basic principles and reactions of syngas production from solid fuels, 242
 - hydrogen production by gasification of solid fuels, 242–244
 - by steam reforming, 900
 - through electrolysis, 897
 - via methane reforming, 152
- hydrogen production costs, 406, 408–410
 - cost parameters at regional frame conditions/ time horizons, 406
 - capital expenditures, 406
 - fixed OPEX, 406
 - revenues, 406
 - variable operational expenditures, 406
 - and distribution costs, 407
 - economic assessment, assumptions for, 407
 - guideline VDI number 6025, 406
 - sensitivity analysis, 409
- hydrogen projects on islands, 1077–1082
 - fuel cell/battery hybrid vehicle, 1077
 - hydrogen compressor, 1077
 - hydrogen gas storage, 1077
 - Promoting Unst Renewable Energy (PURE), 1077
 - studied, planned, and completed projects on, 1078
- hydrogen, properties at low temperature, 735
 - ortho and para modifications, 735
 - thermodynamic properties, 735
- hydrogen refueling stations (HRSs), 892, 923
 - approval process for Germany, 928–930
 - average pressure ramp rate methodology, 894
 - basic requirements for, 892
 - bus refueling, 894
 - car refueling, 892
 - challenges, 907
 - approval processes, 910
 - costs, 909
 - gauged H₂-metering, 911
 - hydrogen quality, 912
 - refueling, technical guidelines, 911
 - reliability, 910
 - standardization, 907
 - codes of practice for, 920–921
 - construction recommendations for, 923–924
 - country/location specific issues related with, 924
 - design/construction recommendations for, 923–924
 - design of, 923
 - globally harmonized standards, need for, 923
 - Technical Barriers to Trade (TBT), 923
 - World Trade Organization's (WTO's), 923
 - maintenance of, 924
 - major components of, 902
 - compressors, 903
 - controls, 905
 - gauges, 905
 - sensors, 905
 - valves, 905
 - dispenser, 905
 - hydrogen storage, 902
 - pre-cooling, 904
 - production, 902
 - operation of, 924
 - procedures for the permission for, 924–930
 - in European Union, 924–930
 - referencing of standards, 922–923
 - regulations for, 919–920
 - decisions, 920
 - directives, 918
 - requirements for the approval of, 923–924
 - risk assessment methodologies for approval of, 924
 - technology standards for, 921–922
 - direct referencing, 922
 - indirect referencing, 922–923
 - vehicle interface requirements, 924
- hydrogen, role in wind electricity generation, 1055
 - electricity storage, 1056

- fuel production, 1058
- mini grids, 1056
- three configurations, comparison of, 1059
- hydrogen safety research, 943
- hydrogen storage systems safety research, 944
- research on physical behavior of leaked or leaking hydrogen, 943–944
- research supporting early market applications, 945
- risk mitigation measures, research on, 945–947
- simplified tools to assess and mitigate risk, 947
- hydrogen separation, 516–519
 - carbon monoxide separation, 517
 - energy generation processes, 516
 - fractionation applications in hydrogen production, 519
 - hydrocarbon separation, 518
 - from hydrocracker flash gas, 532
 - gas permeation unit for, 532
 - hydrogen content in retentate, 533
 - by membrane technology, 531
 - from hydrocracker flash gas, 532–533
 - from purge streams in ammonia production, 531–532
 - nitrogen separation, 517
 - with polymeric membranes, 509
 - from purge streams, 531
 - purge gas treatment in ammonia production, 532
- hydrogen sorption-enhanced reforming (HSER), 229
- hydrogen stations, 835
 - off-site, 835
 - on-site, 835
- hydrogen storage, 781, 791, 811, 902
 - CGH₂ storage, 902
 - in complex hydrides, 773
 - gravimetric energy density, 813
 - high open-porosity structures for, 781
 - in intermetallic compounds, 767
 - LH₂ storage, 903
 - for light-duty fuel cell vehicles, 792
 - metal hydrides based requirements, 792
 - buffer hydrogen, 796
 - containment tank, 794
 - desorption kinetics, 797
 - material compaction and heat transfer, 799
 - material thermodynamics, 794
 - operating temperatures, 792
 - sorption kinetics, 798
 - on-board efficiency, 792
 - physisorption, 781
 - solid hydrogen storage, 903
 - for submarines, 1002
 - volumetric energy density, 813
- hydrogen storage, in vehicles, 691–693
 - design of a tank system, 695–697
 - container, for compressed gas storage, 697–699
 - flow diagram, for compressed hydrogen, 696
 - pressurized storage, advantages of, 693–695
- hydrogen storage projects, 650
 - pure hydrogen storage projects, 650–651
 - town gas storages, 651–652
- hydrogen sulfide, 5, 6, 7, 10
- hydrogen sulfite, 635
 - impacts on the energy balance, 635
- hydrogen transportation, 811, 833, 875
 - dry mode, 877
 - economics, 836
 - cost, 836
 - social cost and benefits, 841
 - embrittlement, 878
 - fuel cell electric vehicles (FCEVs), 833
 - hydrogen infrastructure, 835
 - low pressure levels, 878
 - pipelines refitting, 877
 - safety related issues, 877
- hydrogen transport kinetics, 578–587
 - diffusion in gasses, 579–580
 - diffusion in metals, 583–587
 - diffusion in polymers, 580–583
 - permeation in metals, 583–587
 - permeation in polymers, 580–583
 - thermal conductivity, 578–579
- hydrogen utilization, in chemical industry, 32
 - ammonia, 32–34
 - methanol, 34–36
- hydroisomerization, 5
- hydrophilic electrode, 303
- hydroprocesses, in refinery, 4
- hydroprocessing operation, 15
- hydroprocessing parameters, 6
- hydro storage, 265
- hydrothermal biomass conversion, 109, 113
 - and saturation pressure curve of water, 110
- hydrothermal carbonization, 113
- hydrothermal degradation
 - of sodium acetate, 116
- hydrotreater product gases, 518
- hydrotreating, 7, 8, 10, 11
 - catalysts, 11

- processes, 6–8
- technology, 16
- hypothetical energy system of future, 1076
- HyWindBalance project, 1057

i

- ICE. *see* internal combustion engine (ICE)
- Iceland, 1080
 - ECTOS Hydrogen Fueling Station, 1080
 - geothermal renewable energy, 1080
- ICEVs. *see* internal combustion engine vehicles (ICEVs)
- ideal Carnot system, 91
- ideal gases, 514, 567, 601, 602–603
 - binary mixture of, 514
 - enthalpy of, 602
 - gas law, 602
 - hydrogen, 567
 - internal energy of, 602
 - isentropic relations for, 609
 - isobaric heat capacity, 602
 - isochoric heat capacity, 602
 - self diffusion coefficient of, 579
 - state equation of, 572
 - thermodynamic properties of, 601
- ideal gas law, 176
- IGCC. *see* integrated gasification combined cycle (IGCC)
- ignition delay time, 1014
 - pressure and temperature influence on, 1015
- ignition temperature, 188
- immobilization, 429
- indirectly heated reactors, 159
 - heat transfer medium, 159
 - – air, 159–160
 - – molten salts, 160–162
 - – sodium (Na) vapors, 160
 - – solid particles, 162–163
- indirectly irradiated allothermal reformer, 155
- indirectly irradiated integrated tubular reactor/receiver, 155
- indirectly irradiated reactors, 168
- indirectly irradiated receivers (IIR), 155
- indirect method, 611
- indium oxide, 447
- industrial reformers, typical
 - schematics of operation of, 153
- industrial reformer unit, components, 218
- industrial residues, 424–425
- industry standards, 921
- inner city bus application, operational environment of, 966
- InP photoelectrode, 450
- insoluble materials, 5
- in-space propulsion, 960–961
- insulation, 713
- insulation materials, 430
- integrated gasification combined cycle (IGCC), 1021
- intelligent control algorithm, 1092
- intermetallic compounds, 767
 - AB type alloy TiFe, 772
 - AB₅ type compounds, 771
 - AB₂ type hydrogen absorbing alloys, 771
 - hydrides, 773
- intermittent renewable energy sources, 261
 - integration, options for, 261
- internal combustion engine (ICE), 971
- internal combustion engine vehicles (ICEVs), 852
- internal energy, 618
 - rate of change of, 618
- International Association for Hydrogen Energy, 82
- International Association for Hydrogen Safety, 934
- international collaborations, to prioritize hydrogen safety research, 942
 - comparative risk assessment studies
 - – of hydrogen and hydrocarbon fueling stations, 2008, 943
 - Knowledge Gaps White Paper, 2008, 942–943
 - survey of hydrogen risk assessment methods, 2008, 942
- International Energy Agency (IEA), 59
- International Networks, 80–81
 - European Hydrogen Association (EHA), 81
 - – Project HyER, 81
 - Hydrogen and Fuel Cells in the Economy (IPHE)
 - – mission of the International Partnership, 81
 - Hydrogen Implementing Agreement of, 81
 - International Association for Hydrogen Energy, 82
- International Organization for Standardization (ISO), 921
- International Standard Organization (ISO), 861
- interstitial (metallic) hydrides, 592–593
 - direct reaction of the elements, 594
 - pressure isotherms for the hydrogen, 595
 - properties of ternary interstitial hydrides, 593
 - ternary Interstitial hydrides, 592

- thermally activated reaction, 594
- inverters, 1083
- investment cost, for power and gas networks, 276
- ion exchange membrane, 47
 - cross section, 47
 - electrolyzers, 46
- ionic compressor, 904
- ionic hydrides, 588–590
 - BeH_2 , 590
 - Brønsted acids, weak, 588
 - crystal structures for, 590
 - direct reaction of the elements, 593
 - nucleophiles, 588
 - overview of the (stable) binary hydrides of all elements, 589
 - thermally activated reaction, 593
- ionic liquids (ILs), 302
- ionic resistance, 293
- iridium oxide (IrO_2), 340
- iridium utilization, 351
- iron based ammonia synthesis catalyst, 238
- iron oxide (Fe_3O_4), 185, 634
- iron sulfide (FeS), 185
- isenthalpic expansion, 613
 - direct method for, 615
 - indirect method for, 615
- isentropic compression, 611–615
- isentropic expansion, 613
- isentropic exponent, 609–610
 - relations for ideal and real gases, 609
 - thermodynamic properties, definitions of, 604
- islanded systems, 1056
- ISO. *see* International Standard Organization (ISO)
- iso-butane, 10
- isobutyraldehyde, 473
- isocyanates, 52
- isomerization, 10
- isooctane, 203
- isothermal compression, 611–615
- isothermal refueling, 799
- isotope separation, 785
- ITHER project, 1058

j

- jacket cooling, 611
- Japan
 - energy framework and relevant policies, 78–79
 - energy policy, 79
 - Energy White Paper, approval for, 78

- hydrogen related energy policy strategies, 79
- goal for 2025, 79
- hydrogen research, development, demonstration, and deployment activities, 80
 - METI, subsidiary program for, 80
 - NEDO role, 80
- Japanese commercialization scenario for hydrogen and fuel cells, 79
- JHFC3 outline of a demonstration project, 80
- Japanese Atomic Energy Research Institute, 88
- jet fuels, 3, 5, 201
- Joule–Thomson coefficient, 606, 607
 - effect, 607
 - expansion, 607
- Joule–Thomson effect, 515, 572–573, 602
 - coefficient of hydrogen, 573
 - real gas, 572
- Joule–Thomson Process, 742

k

- kerosene, 5, 8, 143
 - fraction, 8
 - -range material, 10
- Koppers–Totzek process, 243
- the Kyoto Protocol, 87–88

l

- Landolt–Börnstein series, 771
- landscape conservation, environmental legislation to, 1056
- lanthanum-strontium-vanadium-oxide (LSV), 545
- large specific impulse (ISP), 951
- Laves phase alloys, 771–772
- law of mass conservation, 617
- LCA (life cycle assessment) methodology, 403
 - steps and assumptions for biohydrogen concepts, 404
- LDI. *see* lean direct injection (LDI)
- lead acid, 265
 - batteries, 991
- leading automotive companies (OEM), 919
- leaf H_2 Production, 472
 - artificial leaf, 472
 - artificial photosynthesis, 472
 - electrocatalyst, 472
 - semiconductor photoelectrochemical materials, modern, 472
- lean direct injection (LDI), 1023
- lean premixed combustion (LPC) technique, 1012, 1019, 1024

- LEL. *see* lower explosive limit (LEL)
 - Lewis number, 1017
 - LH₂. *see* liquefied hydrogen (LH₂); liquid hydrogen (LH₂)
 - LHV. *see* lower heating value (LHV)
 - light intensity, 470
 - lignin, 115
 - degradation of, 115
 - hydrothermal biomass degradation
 - – simplified reaction scheme of, 117
 - lignocelluloses, 114, 420
 - lignocellulosic feedstock, 431
 - Li-ion battery technology, 978
 - liquefaction, 764, 866
 - liquefied hydrogen (LH₂), 441, 733
 - properties, 733
 - – high energy density, 733
 - – light weight, 733
 - – low environmental impact, 733
 - pump, 904
 - liquid hydrocarbon fuels, 143
 - liquid hydrogen (LH₂), 812, 903, 951, 1085
 - advantages of compression, 717
 - based hydrogen stations with cryogenic compression, 717
 - compression, advantage of, 717
 - cryogenic compression, 717
 - heat receptivity of, 716
 - refueling, 717
 - – unit, 718
 - storage, 713, 715–716, 719, 724
 - tank insulation, 953
 - thermodynamic opportunities, 714
 - usage, constraints due to, 952–953
 - liquid hydrogen delivery pathway, 864
 - challenges, 865
 - – boil-off losses, 865
 - – liquefaction, 866
 - – underground storage, 866
 - components layout, 864
 - cost estimates, 864
 - liquid hydrogen, for access to space, 951
 - liquid hydrogen, safety related
 - precautions, 939–940
 - liquid hydrogen storage systems, 173
 - liquid hydrogen tankers, 849
 - liquid organic hydrogen carrier (LOHC) systems, 814
 - alicyclic compounds, 814
 - applications of, 822
 - – in energy transport over long distances, 824
 - – in mobile sector, 827
 - – in storage of renewable energy equivalents, 823
 - development of, 819
 - ecotoxicological properties, 815
 - heteroalicyclic compounds, 814
 - liquid aromatic or heteroaromatic compound, 814
 - toxicological properties, 815
 - Liquid oxygen, 996
 - liquid oxygen (LOX), 951–952
 - tank, 1009
 - liquid-petroleum gas (LPG), 209
 - liquid storage, 951
 - larger ISP, of liquid propellant, 951
 - mass efficiency, 951
 - lithium ion [Li-ion], 265
 - LOHC. *see* liquid organic hydrogen carrier (LOHC) systems
 - London forces, weak, 591
 - low carbon technologies, 256
 - lower explosive limit (LEL), 1041
 - lower heating value (LHV), 318, 614, 1012
 - low gravity environment, relevant tests
 - in, 958–960
 - CPST mission, illustrating technologies, 960
 - demonstration with liquid hydrogen, 959
 - source of analysis
 - – on predicted liquid hydrogen behavior, 959
 - spherical liquid hydrogen tank, 958
 - low-temperature metal hydride (LTMH) systems, 791
 - low-temperature water–gas shift reactor (LT-WGS), 176, 185
 - LOX. *see* liquid oxygen (LOX), tank
 - LPC. *see* lean premixed combustion (LPC) technique
 - LPG (liquefied pressurized gas), 24–25
 - LSV. *see* lanthanum-strontium-vanadium-oxide
 - LTMH. *see* low-temperature metal hydride (LTMH) systems
 - Lurgi-MegaMethanol Process®, 35
- m**
- magnetite, 91
 - manganese, 91
 - manganese ferrite plus activated sodium carbonate system, 93–94
 - Mark 13A cycle, 98
 - markets, energy price variation in, 1056
 - Mark 13 V2, as hybrid cycle, 98
 - mass fractions, 800
 - mass transport, 174

- material compaction, 799
- material densities, 800
- material fill factor, 800
- MATLAB Simulink software, 398
- maximum vehicle velocity, 967
- MCFC. *see* molten carbonate fuel cells
- MDEA. *see* methyl-diethanolamine
- MEA. *see* membrane electrode assembly (MEA)
- medical oxygen, 996
- medium-temperature metal hydride (MTMH) system, 791
- mega-ammonia technology, 34
- membrane bioreactor (MBR), 427
- membrane cell process, for production of chlorine, 29
- membrane classification, 519
 - free volume, quality of the, 520
 - hydrogen, properties of, 520
 - Kuhn segments, 519
 - rubbery polymers, 519
- membrane electrode assembly (MEA), 338, 995
- membrane electrolysis process, 47
- membrane gas separation, basics of, 510–516
 - chemical potential, 511
 - difference in, 510
 - coating technique, 511
 - gas separation membrane process, 510
 - isenthalpic throttling, 515
 - model for membrane modules, 516
 - permeate, 510
 - permeate pressure, applied, 516
 - permeation mechanism, 513
 - pressure ratio, definition of, 513
 - retentate, 510
 - solution diffusion mechanism, 511
 - sorption coefficient, 513
 - thermodynamic equilibrium, 512
 - transport resistances in gas permeation, 511
 - types of membranes, 510
 - carbonous membranes, 510
 - ceramic membranes, 510
 - metal alloy membranes, 510
 - polymeric membranes, 510
- membrane humidification, 974
- membrane material classification, 519–520, 528–531
 - based on glassy polymer, 528
 - chemical structure of Matrimid®, 531
 - diffusion selectivity, 529
 - industrial membrane gas separation, 530
 - permeability selectivity of polymer, 530
 - polymers of intrinsic microporosity (PIM), 530
 - Robeson plot, 530
 - scheme of polyimide conversion, 531
 - based on rubbery polymers, 527
 - chemical structure of Polyactive™, 528
 - gas transport properties of selected polymers, 529
 - poly(ethylene glycol) (PEG), 528
- membrane materials, 519
 - classification of, 519–520
 - defect curing, 524
 - Poiseuille mechanisms, 524
 - geometrical classification, 523–524
 - Loeb–Sourirajan integral asymmetric membranes, 523
 - morphological classification, 520–523
- membrane modules, 510, 519
 - classification of, 523
 - flat sheet modules, 526–528
 - hollow fiber modules, 525–526
- membrane morphological classification, 519
 - cross-section of gas separation membrane, 520
 - cross-section of polyacrylonitrile porous membrane, 522
 - gas separation membranes, 520
 - Knudsen flow, 520
 - plasticization of pores walls, 520
 - surface porosity, 522
 - TFC membrane, 521
- membrane reformer (MRF), 230
- membrane technology, 41, 46, 517
- Mercedes Benz F-cell passenger car, 979
- mercury
 - cell process, for production of chlorine, 30
 - cell room, 44
 - electrolyzer, 44
 - technology, 43–45
 - environmental and health problems, 41
- mesophiles, 429
- metal alloy membranes, 511
 - palladium, 511
- metal alloys, 448
- metal-based catalysts, 10
- metal chips, 143
- metal electrodes, 297
- metal hydrides (MH), 441, 791, 1085
 - CPI characteristics of, 1003
 - -filled pressure container, 705
 - formation, thermodynamics of, 765
 - for stationary storage, 659
 - storage

- cylinders, 1002
- devices, 704
- systems, thermal integration of, 792
- metallic membranes, 585
- metallic piping, 545
- metalloprotein, catalytic, 463
- metal membranes, 511
- palladium, 511
- metal/metal oxide thermochemical cycles, 89, 90
- $\text{CeO}_2/\text{Ce}_2\text{O}_3$, 95–96
- $\text{Fe}_3\text{O}_4/\text{FeO}$ as redox material, 90–91
- ferrites, 91–93
- hercynite cycle, 93–94
- manganese ferrite plus activated sodium carbonate, 94
- production of hydrogen based on, 90
- Zn/ZnO , as promising redox system, 94–95
- metal nitrides (M_3N_x), 775
- metal-on-metal sealing, 645
- metal–organic frameworks (MOFs), 499
- lower density of, 499
- metal oxides (MOs), 89, 90, 447
- catalyst, 7
- cycles, 89
- metal pnictides, 443
- metering, 644
- methanation, 179, 238, 867
- with CO_2 , 255
- methane, 110, 143, 544, 546, 606, 814
- as carrier gas, 140
- catalyst poison, 546
- comparison of thermodynamic properties with hydrogen, 606–610
- compressibility factor of, 606
- compression work of, 610
- conversion
- into acetylene and hydrogen, 142
- into hydrogen and C_2 hydrocarbons, 141
- main products, 134
- rate, 136
- decomposition, 153
- direct methods for, 617
- flow rate, 136
- formation, 179
- fuel properties of, 1013
- heat flow of, 624
- indirect methods for, 617
- isothermal compression of, 615
- Joule–Thomson coefficient of, 608
- nickel catalysts, 546
- oxidation, 188
- positive effect on, 134
- pyrolysis, 134
- reactivity in a microwave plasma, 137
- real gas behavior of, 622
- real isentropic exponent of, 610
- reforming process, 151
- solar thermal reforming of, 157–159
- temperature, 614
- change during expansion of, 616
- variation of the storage tank
- pressure of, 621
- temperature of, 621
- methanogenesis, 429
- methanogenic bacteria, 429
- methanol, 20, 139, 174, 177, 179, 491, 814, 933
- conversion, 139–140
- diaphragm technology, 41
- Lurgi-MegaMethanol Process®, 35
- process schematics for, 36
- production data based on, 21
- reactions of syngas to, 35
- reformer, 138
- development, 1007
- high pressure catalytic oxidation, 1008
- multi-stage catalytic oxidation device, 1008
- for submarines, 1006
- system, 1007, 1009
- methylcyclohexane, 203
- methyl–cyclohexane–toluene–hydrogen cycle, 659
- methyl-diethanolamine (MDEA), 558
- methylnaphthalene, 203
- MGT. *see* micro gas turbines (MGT)
- MH. *see* metal hydrides (MH)
- microalgae, 473
- biodiesel, 473
- microbial-based biofilms, 427
- microbial biomass, 427
- microbial immobilization, 427
- microbial inventories, 635
- microbial metabolism, 635
- micro fuel cells, 64
- micro gas turbines (MGT), 1019, 1022
- microorganisms, 634
- micro-sized gliding arc discharge reactor, 135
- microwave plasma, 136–138
- microwave plasma source, types of, 137
- microwave (2.45 GHz) “tornado”-type plasma, 138
- mixed oxides, 152
- mixed oxides ($\text{MnO}_2\text{--CuO}$), 187
- MK 904-mod stack design, 977
- mobile applications, 309

- MODBUS communication protocol, 1066
- MOFs. *see* metal-organic frameworks
- molar concentrations, 179
- molar specific enthalpy, 178
- molar specific entrop, 178
- molecular hydrogen, 19, 583
 - diffusion coefficients of, 583
- molecular orbitals, 565–566
 - antibonding MO, 565
 - bonding, antibonding molecular orbitals of H_2 molecule, 566
 - heteronuclear molecules, 566
 - nuclear spin-states, 566–569
- molten carbonate fuel cell (MCFC), 64, 544
- molybdenum, 11
 - oxides, 7
- Mo–Ni/ Al_2O_3 catalyst, 141
- monolithic ceramic structures
 - explored as volumetric receivers, 155
- monoolefins, 8
- Monte Carlo program, 782
- MOs. *see* metal oxides (MOs)
- MTMH. *see* medium-temperature metal hydride (MTMH) system
- multi-column PSA, 502
 - large flows of gas, approach to handle, 502
 - twelve-column PSA cycle, 503
- multi-fuel reforming, 174
- multivalent metals, 89
- municipal sewage, 431
- mutual solubility, of hydrogen and water, 631
- n**
- $NaAlH_4$. *see* sodium alanate ($NaAlH_4$)
- Nafion ionomer, 339
- Nafion membrane, hydrated, 1088
 - oxygen permeation rate through, 1088
- nano- and microstructured
 - photoelectrodes, 455–457
- nanosecond pulsed DBD system, 141
- nanostructures, 300
- naphthas, 7, 218, 224
 - hydrotreater, 5
- naphthenes, 8
- National Bureau of Standards (NBS), 734
- National Fire Protection Association, 941
- National Hydrogen and Fuel Cell Technology Innovation Programme (NIP), 60–61
 - defined goals for, 61
 - financial requirements for, 61
 - first/second phase of, 61
 - research, development and demonstration projects within, 61
 - total budget within, 61
- National Renewable Energy Laboratory (NERL), 836
- natural gas, 3, 201, 218, 237, 545, 601, 1076
 - autothermic reforming of, 249
 - combined cycle (NG-CC), 1021
 - composition of, 601
 - fuel properties of, 1013
 - pipeline grid, 1011
 - price projections, 227
 - syngas by steam reforming, 246–249
 - equilibrium content of methane, 247
 - evolution of methane conversion, 249
 - main reaction, 246
 - primary reformer, 248
 - secondary reformer, 250
 - temperature profile and heat fluxes, 248
 - typical process data for steam reforming/secondary reforming, 250
- natural isotopes, of H_2 , 566
 - Au-electrodes, 566
 - deuterated water, 566
 - deuterium, 566
 - mass difference, high, 566
 - neutron, 566
 - protium, 566
 - Pt-electrodes, 566
 - tritium, 566
 - water electrolysis, 566
- natural polymers, for immobilization, 429
- NBS. *see* National Bureau of Standards (NBS)
- NeBus prototype, 976
- NeBus technology, 971
 - electronic brake paddles, 987
 - fuel cell drive train data for, 983
 - test and field experience, 982
- NEC. *see* *n*-ethyl-carbazole (NEC)
- NECAR 2 fuel cell engine, 973
- NEDO. *see* New Energy and Industrial Technology Development Organization (NEDO)
- NERL. *see* National Renewable Energy Laboratory (NERL)
- Nernst equation, 1085
- n*-ethyl-carbazole (NEC), 816
- new combustion systems for gas turbines (NGT), 1023
- New Energy and Industrial Technology Development Organization (NEDO), 837
- NG-CC. *see* natural gas, combined cycle (NG-CC)
- NGOs, 81

- NGT. *see* new combustion systems for gas turbines (NGT)
- n*-hexadecane, 141, 143
- Ni alloys
- tafel slopes of, 299
- Ni/Al₂O₃ catalysts, 188
- Ni-based catalysts, 152
- inhibit carbon formation, 153
- Ni catalysts, 136, 201
- NiCGO. *see* nickel-ceria-gadolinium-oxide
- nickel, 11, 48, 91
- catalysts, 546
- nickel-ceria-gadolinium-oxide (NiCGO), 545
- nickel hydroxide cathode, 771
- nickel-metal hydride (NiMH), 265, 771
- nickel oxide-silica-alumina, 7
- Ni electrode, 299
- Ni-gadolinium doped ceria (NiGDC), 545
- Ni/γ-Al₂O₃ catalysts, 139
- NiGDC. *see* Ni-gadolinium doped ceria
- NiMH. *see* nickel-metal hydride (NiMH)
- nitric acid, 32
- nitrogen, 5, 134, 224, 403, 547, 888
- nitrogenase, 465, 466
- active site of, 469
 - endergonic reaction, 469
 - nitrogen fixation by, 469
- nitrogen-based fertilizers, 19
- nitrogen fertilizers, 32
- nitrogen monoxide (NO), 1019
- nitrogen oxide (NOx), 1013
- nitrogen source, 470
- nitrogen starvation, 471
- nitrous oxide (N₂O), 1019
- NiYSZ. *see* Ni-yttrium stabilized zirconia
- Ni-yttrium stabilized zirconia (NiYSZ), 545
- NO. *see* nitrogen monoxide (NO)
- noble metal-free catalysts, 441
- noble metal oxides, 448
- non-catalytic partial oxidation, 25, 237
- nondestructive hydrogenation, 5
- non-nuclear submarines, 991
- non-thermal plasmas, 132
- gliding-Arc plasma, 132
 - types, in hydrogen production from hydrocarbons, 133
 - used in hydrogen production, 133
- North American Free Trade Agreement, 922
- Norway
- energy framework and relevant policies, 65
 - – climate and energy fund, 65
 - – CO₂ emissions, 65–66
 - hydrogen related energy policy strategies, 65–66
 - – carbon capture and storage (CCS) program, 65
 - – zero emission vehicles, 66
 - hydrogen research, development, demonstration, and deployment activities, 66–67
 - – HyNor Project, 67
 - – Norwegian R&D institutions related to hydrogen, 66
 - – Transnova Hydrogen Projects, 68
 - – ZEG Power, 67
- n-TiO₂ layer, internal resistivity, 447
- n*-tridecane, 143
- nuclear energy, 1053
- nuclear reactors, 87, 88
- nuclear spin-states, 566–569
- antiparallel, 567
 - diatomic molecules, 568
 - equilibrium composition of (normal) n-H₂, 567
 - fermions, 566
 - molar heat capacity of p-H₂, 568
 - normal H₂, 567
 - ortho-H₂, 567
 - para-H₂, 567
 - parallel, 567
 - paramagnetic materials, 567
 - quantum number, 568
 - wave function, total, 568
- nuclear very high temperature reactors (VHTRs), 96
- nucleophiles, 588
- o**
- octane, 203
- number, 8, 218
- ODC. *see* oxygen depolarized cathode (ODC)
- OEMs. *see* leading automotive companies; Original Equipment Manufacturers (OEMs)
- ohmic resistance, 293
- oil refining, 153
- OM 908 bus diesel engine, 977
- one motor approach, 971
- one-motor-design, 978
- on-site hydrogen supply, 217
- on-site reforming, 217
- operating expenditure (OPEX), 733
- operational management and experiences, 1045
- activated electrodes, influence of, 1049
 - dynamic load, 1045
 - temperature influence on stack voltage, 1047

- voltage efficiency of electrolyzer, 1050
- OPEX. *see* operating expenditure (OPEX)
- optimization
 - of power system operation with intermittent generators, 277
- organic acids, 427, 635
- organic fertilizers, 140
- Original Equipment Manufacturers (OEMs), 852
- ortho-H₂, 566–569
- osmosis, 509
- Ostwald process, 32
- overvoltage, 448
- oxalate, 116
- oxidant, 133
- oxidation, of hydrochloric acid, 41
- oxidative desulfurization, 16
- oxinitrides, 447
- oxygen, 180, 1093
- oxygenates, 139
- oxygen depolarized cathode (ODC)
 - chlorine-alkali production with, 49–51
 - cross section of NaCl ODC based electrolysis halfshell, 51
 - electrochemistry of chlorine production with ODC technology, 49
 - – reactions, 49
 - electrochemistry of NaCl electrolysis with, 50
 - structure, 50
- oxygen sensor, 1008
- oxygen-to-carbon ratio (O/C), 200, 204

p

- PA. *see* polyamide (PA)
- PACDisplay environment, 1066
- Pacific Northwest National Laboratory (PNNL), 858
- palladium, 511
- paper industry, 53
- para-H₂, 566–569
 - heat capacity (c_v), 568
 - thermal conductivity of, 568, 569
- parallel compressed gas, 704
- parallel hydride/compressed gas storage, 704
- paramagnetic materials, 567
- partial methanol flux, 138
- partial oxidation, 25, 133, 220, 237, 331
 - of methane to syngas, 139
 - of propane to syngas, 134
- partial oxidation (POX), 5, 131, 133, 136, 142, 146, 206
- particle size, 351

- particulate matter, 552
 - electrostatic forces, 554
 - electrostatic interaction, 552
 - electrostatic precipitators (ESPs), 554
 - gravitational settling, 553
 - inertial separation, 552
 - separation efficiencies, 553
 - technologies for particulate removal, 553
- passenger car application, 966
- passenger car program, 980
- PCT. *see* pressure–composition–temperature (PCT) isotherm
- Pd/Ag membranes, 190
- PDMS. *see* polydimethylsiloxane
- Pd/ZnO catalysts, 201
- PED. *see* pressure equipment directive
- PEFC. *see* proton exchange fuel cell (PEFC) system
- PEFCs (polymer electrolyte fuel cells), 173
 - demand highest fuel quality with, 205
 - fuel processor subsystem, consisting of autothermal reforming of diesel and a gas cleaning unit for, 191
 - gas cleaning subsystem as a possible design for, 207
 - principle scheme of gas cleaning processes, for carbon monoxide and hydrogen sulfide in, 206
- PEG. *see* poly(ethylene glycol)
- PEM. *see* polymer electrolyte membrane (PEM); polymer electrolyte membrane (PEM) electrolysis; proton exchange membrane; proton exchange membrane (PEM) technology
- PEM electrolyzer, 1081
- PEM FC module, 992
- PEMFCs. *see* polymer electrolyte membrane fuel cells
- PEM fuel cells, 1086
- PEM fuel cells for submarines, 993
 - constructive feature of fuel cell module, 995
 - – cascaded fuel cell stacks, 996, 997
 - – preconditions, 995
 - – pressure cushion, 998
 - oxygen/hydrogen cell design, 994
 - – constructive features, 994
 - – fuel cell operation results, 995
 - safety features of, 1001
 - voltage–current characteristic of, 996
- PEM-fuel cell technology, 965
- permeate mole fraction, 514
- petroleum
 - fractions, 5

- products, 5
- refining, 933
- PFSA (perfluorosulfonic acid)
 - membranes, 350
- p-GaP electrode, 447
- phase 4 bus engine demonstrator, 977
- phenols, 115
 - from carbohydrates, 115
 - from lignin, 115
- PHEVs. *see* plug-in hydrogen electric vehicles (PHEVs)
- Phosphoric acid fuel cell (PAFC), 64
- photocathode, 450
- photocurrent, 441
- photodecomposition, 464
- photoelectrochemical (PEC) cells, 442, 443
 - characteristic of photovoltaic component
 - of water splitting PEC, 445
 - energy balance, 457
 - with single photoelectrode, 443–446
 - STH efficiency, 450–451
 - with a tandem photocathode immersed in acidic electrolyte, 449
 - with two photoelectrodes, 446–448
 - for water splitting device, 446
- photoelectrochemical devices, 461
 - water splitting, 442
- photoelectrochemical systems, 457
 - economic aspects, 457
- photoelectrochemical water splitting, 442
- photoelectrode preparation, 457
- photoelectrodes, 447
- photofermentation, 420
- photofermentative hydrogen production, 420
- photofermentative processes, 465
- photoheterotrophic microalgae, 465
- photoheterotrophs, 471
- photolytic H₂ production, by
 - microorganisms, 474
 - antenna system, reduction of, 475
 - biophotolysis process, 474
- photosynthesis, 441
- photosynthetic bacterial H₂ production, 475
 - metal ion, 475
 - photofermentative bacteria, 475
 - purple non-sulfur bacteria, 475
- photosynthetic microorganisms, 476
 - genetic study of, 476
- photosynthetic organisms, 461, 463
 - catalytic metalloprotein, 463
 - cyanobacteria, 463
 - green algae, 463
 - hydrogenase, 463
- photosystem II (PSII), 461
 - CaMn₄O₅ cluster in, 462
 - repair cycle, 469
 - water oxidation, 472
- photosystems, 465
 - cytochrome b6f, 470
 - electron transport chain, 465
 - LHCI, 469
 - light harvesting complexes, 465
 - multiprotein complexes, 469
 - plastoquinones, 470
 - repair cycle, 469
- photovoltages, 441, 457
- photovoltaics (PV), 59
 - efficiency, 446
 - panels, 1083
 - systems, 309
- physisorption, 781
- PID (proportional-integral-derivative)
 - controller, 232
- PIM. *see* polymers of intrinsic microporosity
- pipeline delivery pathway, 857
 - challenges, 859
 - compression, 860
 - distribution, 859
 - geologic storage, 860
 - high cost, 859
 - hydrogen and material interactions, 860
 - components layout, 857
 - cost estimates, 858
- pipeline grid, 877
- pipelines, 642
- piston compressors, 903
- plasma, 131
 - catalyst interactions, 139
 - catalytic methanol-steam reforming, 139
 - characteristics, 131
 - cracking, 141
 - decomposition of hydrocarbons co-produces carbon, 131
 - non-thermal, 131–132
 - reactor, 134, 143
 - thermal, 132
- plasmagen gas, 134
- plasmatron device, 133, 137
- plasma type, preferred
 - for hydrogen production from hydrocarbon conversion, 147
- plastoquinones, 470
- platinum, 448
- platinum-alumina, 7
- PLC. *see* programmable logic controller (PLC)

- plug-in hydrogen electric vehicles (PHEVs), 842
- PNNL. *see* Pacific Northwest National Laboratory (PNNL)
- policies promoting increased penetration of renewables
 - global view of, 257
- pollutant level requirements, 550–551
 - contaminant limits suggested, 551
 - current density, 551
- pollutants, 132
- polyamide (PA), 879
- polycyclic aromatic compounds, 10
- polycyclic aromatic content, 9
- polydimethylsiloxane (PDMS), 514
- poly(ethylene glycol) (PEG), 528
- polymer, 580
 - permeation coefficient of, 580
- polymer electrolyte membrane (PEM), 898, 992
 - electrolysis systems, 309–310, 812
- polymer electrolyte membrane (PEM) electrolysis, 27, 312
 - cell operated at temperatures range, 349
 - cell under varying flows on anode side with pin-type flow field, 347
 - challenges, 334–335
 - characteristic cell performance for, 313
 - compression, 314
 - control of temperature in, 348
 - cost reduction, 350
 - catalyst coated membranes, 350–351
 - cell design, 354
 - modular system design, 354–355
 - porous transport layer, 351–352
 - separator plates, 352–354
 - current-voltage characteristics and operating ranges for, 332
 - future trends in, 349–350
 - gas separation in, 313–314
 - general principles of, 335
 - historical perspective, 333–334
 - schematic of, 314
 - stack design, 338
 - catalyst coated membranes (CCMs), 338–340
 - flow field designs, 344
 - porous transport layer, 340–343
 - separator plate, 343–344
 - stack operation, 345
 - balanced pressure operation, 345
 - differential pressure operation, 345–346
 - thermal management, 348–349
 - water circulation, 346–348
 - stacks commercial, developers/manufacturers of, 336–337
 - state-of-the-art, 335
 - stack, specifications/components of, 335–336
 - with and without cathode water circulation, 348
- polymer electrolyte membrane fuel cells (PEMFCs), 544
- polymeric membranes, 509, 511
- polymeric membranes classification, 519
 - membrane classification, 519
 - glass transition temperature (T_g), 519
 - Kuhn segments, 519
 - morphological classification, 520–523
 - solubility exclusion mechanisms, 519
- polymerization, 5, 113
- polymer membrane, 1084
- polymers of intrinsic microporosity (PIM), 530
- polytrophic coefficients, 191
- porous material, 492
 - activated carbon, 493
 - activated zeolites, 493
- porous reservoirs, 631, 634
 - geological storage options for hydrogen in, 637
- porous support layer, 515
 - concentration gradients in, 515
- porous transport layers
 - gas flow from, 341
 - SEM micrographs, 342–343
- Porphyidium cruentum*, 473
- potassium chloride, 41
- potassium hydroxide, 41, 1036, 1037
- power plants, characteristics, 263
- power quality, and reliability, 265
- power rating, 264
- power storage technologies, 869
 - capacity, 869
 - discharge time of, 869
- power system
 - demand-side management (DSM), 263
 - flexibility resources and flexibility needs in, 262
 - IEA listing categories of flexibility sources, 262
 - operators, 1055
 - supply-side management, 263
- power technologies, 1089
- “power-to-gas” concept, 255, 1059
- power-to-gas mass energy solution, 866
 - challenges and opportunities, 869

- current applications, 867
- hydrogen methanation process, 866
- power-to-gas (PtG) plants, 274–275
- power-to-gas technology, 309
- powertrain layout, 966
 - maximum power demand, 966
 - range, 966
 - time for refueling, 966
 - torque of drive train, 966
- preferential CO oxidation, 206
- Prenzlau, hybrid power plant project in, 1035, 1036
 - alkaline electrolyzer, 1036, 1037
 - electrolyzer operation, 1034
 - overview of, 1035
- pressure–composition isotherms, 765
- pressure–composition–temperature (PCT) isotherm, 797
- pressure equalization, 497
- pressure equipment directive (PED), 928
- pressure swing adsorption (PSA), 15, 24, 221, 230, 238
- pressure–temperature phase diagram, 569–571
 - atomic plasma, 571
 - cubic closed-packed structures (fcc), 571
 - phase regions for molecular/atomic hydrogen, 570
 - supercritical fluid, 570
 - triple point, 570
- pressure–volume phase diagram, 571–572
 - critical point (p_{crit}), 572
 - p – V_m phase diagram of hydrogen, 572
- pressurized gas storage, thermodynamics of, 601
 - compression/expansion processes, analysis of, 610–617
 - isenthalpic expansion, 615–617
 - isentropic compression, 611–615
 - isentropic expansion, 615–617
 - isothermal compression, 611–615
 - expansion processes, analysis of
 - isothermal compression, 611–615
 - gas storage process, thermodynamic modeling of, 617–619
 - application examples of, 620–624
 - refueling of a vehicle storage tank, 620–622
 - salt cavern, 622–22
 - heat transfer equations, 619
 - thermodynamic properties of gases, comparison of, 606–610
 - compressibility factor, 606–607
 - isentropic exponent, 609–610
 - Joule–Thomson coefficient, 607–609
 - thermodynamic state variables, calculation of, 602–606
 - ideal gases, for, 602–603
 - real gases, for, 603–606
- probabilistic risk assessment (PRA), 935
- process control instruments, 175
- process engineering, 642
- product gas composition, for various hydrogen generation processes, 195
- product gases, 544
- production-to-demand-approach, 811
- programmable logic controller (PLC), 905, 1001
- Promoting Unst Renewable Energy (PURE), 1077
- propane, 134, 143, 203
 - conversion, 142
 - conversion depended on, 145
- propane–butane mixture (LPG), 173
- propanoic acid, 139
- propene, 203
- propulsion and auxiliary power demand, determination of, 966
- protium, 566
- proton channel, 471
 - biochemical modifications of, 471
 - genetic modifications of, 471
- proton conducting membrane, 994
- proton exchange fuel cell (PEFC) system, 792
- proton exchange membrane (PEM), 1083
 - technology, 965
- Proton OnSite hydrogen generator, 1081
- PSA cycle, improving, 501
 - adsorption processes, 501
 - large flows of gas, approach to handle, 502
 - multi-column PSA, 502
 - numerical simulation of, 502
 - purge gas, 502
 - rapid pressure swing adsorption (RPSA) units, 503
 - rotary valves, 503
 - total cycle time, 502
 - total time of, 501
 - twelve-column PSA cycle, 503
 - unit productivity, calculation of the, 501
- PSA technology, basics, 492
 - activated carbon, 493
 - activated zeolites, 493
 - adsorbent, 492
 - adsorbent productivity, 495
 - adsorption equilibrium isotherms, 492
 - adsorption processes, 492

- black-box design, 495
 - black-box scheme of, 495
 - blowdown step, 497
 - cost of the H₂ separation, 496
 - cyclic adsorption–desorption operation, 496
 - cyclic loading, 496
 - cyclic steady state, 495, 496
 - depressurization, 497
 - desorption, 496
 - energy consumption, 495
 - equilibrium state, 492
 - feed gas, 495
 - fundamental operation of, 495
 - gas mixture, 496
 - high H₂ recovery, 495
 - hydrogen recovery, 497
 - inlet stream of, 499
 - isotherms of a contaminant, 495
 - light-recycle, 497
 - multicomponent gas phase, 492
 - pressure equalization, 497
 - pressure history, in a two-column PSA process, 498
 - pressure swing adsorption, 493
 - provide purge, 498
 - Skarstrom cycle, 496
 - steam–methane reforming off gases, 493
 - tail gas, 495
 - temperature swing adsorption (TSA), 493
 - PSA technology, for H₂ separation, 491
 - basics of, 492
 - improving the PSA Cycle, 501
 - operating costs of, 492
 - PSA units, 502
 - cycle times of, 502
 - PSI, 465
 - Pt and Ru catalysts, 141
 - Pt/CeO₂ WGS catalyst, 207
 - PTFE coating, 352
 - Pt–Ru catalysts, 187
 - pulsed corona, 142
 - pulsed plasmas, 142–144
 - pumped hydro storage [PHS], 265
 - PURE. *see* Promoting Unst Renewable Energy
 - pure hydrogen storage projects, 650
 - Clemens Dome, Texas, USA, 650
 - Moss Bluff, Texas, USA, 650
 - Teesside Project, Yorkshire, UK, 651
 - pure oxygen, use of, 1004
 - purple photosynthetic bacteria, 469
 - biological nitrogen fixation in, 469
 - FeMo cofactor, 469
 - PV array, 1087
 - PV–hydrogen systems, 1087
 - economics of, 1087
 - Pyrodictium brockii*, 467
 - pyrolysis, 8, 153, 195
 - pyrolytic carbon, 143
 - pyrophoricity, 229
- q**
- QRA. *see* quantitative risk assessment
 - quantitative risk assessment (QRA), 924, 935
 - for hydrogen safety, shortcomings, 935
 - frequency probability of component failures, 936
 - human error, 935
 - ignition, 935
 - lack of uniform acceptance criteria, 937
 - probability of causing damage, 937
 - simplified engineering models, 936
 - uncertainties in QRA models, 937
 - schematic, 936
 - quantum number, 568
 - quick charging stations, 711
- r**
- rapeseed methyl ether (RME), 556
 - rapid compression machine (RCM), 1015
 - rapid pressure swing adsorption (RPSA), 503
 - rapid risk ranking (RR), 924
 - RCM. *see* rapid compression machine (RCM)
 - reactant filling station, 1004
 - reaction kinetics, 574–578
 - reaction with O₂
 - explosion limits, 577–578
 - microscopic mechanisms, 574–577
 - thermodynamics, 574
 - reaction number, defined, 178
 - reaction of H₂ with O₂
 - explosion limits, 577
 - autoignition temperature of H₂/air-mixtures, 578
 - isothermal explosion, 577
 - for mixtures of H₂ and O₂, 577
 - mechanism of, 574
 - chain reaction (unbranched), 576
 - hydrogen peroxide (H₂O₂), 574
 - hydroperoxyl radical, 575
 - hydroxyl radical, 575
 - isothermal explosion, 576
 - oxygen radical, 575
 - reaction between hydrogen and oxygen, 576
 - thermal explosion, 576
 - thermodynamics of, 574

- binary hydrides, 574
- equilibrium constant (K), 574
- free formation enthalpy of H₂O vapor, 575
- hydrogen fluoride, 574
- mass action law, 574
- reactor configurations, 427
- and scale-up challenges, 427
- reactor improvements, and design aspects, 230
- reactor operating conditions, 7
- real gases, 572, 601, 603–606
 - caloric equations of, 615
 - direct method for, 615
 - final states of, 617
 - Helmholtz free energy, 603
 - indirect method for, 615
 - isentropic relations for, 609
 - temperature of, 572
 - thermal equation of state for, 603
 - thermodynamic properties in terms Helmholtz free energy, 604
 - thermodynamic properties of, 601
- reduce boil-off (RBO) concept, 961
- reduced boil-off
 - for LH₂ by vapor venting and, 962
- refining heavy feedstocks, 11–12
- reformate gas stream, 1008
- reformer technologies
 - technology and pros/cons, 221
- reforming reaction, 491
- reforming technologies, 219, 491
- refueling, 711, 713, 717
 - and infrastructure perspectives, 717–719
(*see also cryo-compressed gases*)
- refueling station, 852
 - challenges, 854
 - analysis, 854
 - boil-off, 855
 - compression, 855
 - hydrogen quality, 855
 - land area, 855
 - metering, 855
 - refrigeration, 855
 - storage costs, 855
 - cryo-compressed, 854
 - gaseous hydrogen, 852
- Regulation on Industrial Safety and Health, 1039
- Regulations Codes and Standards (RCS), 919
- renewable-based hydrogen economy, 152
- renewable electricity, 59, 255
- renewable energy, 262, 477, 811, 1075
 - alternative sources of, 477
 - cost of, 1075
 - import, from Iceland, 826
 - aluminum production, 826
 - hydrogen-rich LOHC systems, liquid transport of, 826
 - storage of, 813
 - transport of, 813
 - utilization of, 1075
- renewable energy integration, 264
 - non-storage options for, 264
- renewable energy sources, 151, 255, 309, 417, 711, 891
 - grid integration of, 309
- renewable generators, 276
- renewable heat source, 87
- “renewable” hydrogen production route, 151
- reservoir rocks, 634
- resistance model, 509
- retentive membranes, 427
- reverse engineering, 800
 - back pressure, 805
 - bulk density, 803
 - charge kinetic rate, 803
 - discharge kinetic rate, 803
 - heat exchanger tubes, 806
 - heat transfer tubes, 806
 - refueling pressure, 803
 - refueling temperature, 803
 - state-of-charge conversion, 802
 - temperature profile, 802
 - thermal conductivity, 805
- reversible solid oxide fuel cell (RSOFC) technology, 359, 379–383
 - based sustainable energy system, 382
 - cell and stack design flexibility, 362
 - efficient and stable cyclic operation, 380–383
 - efficient production of hydrogen and chemicals in electrolysis mode, 364–366
 - electrode performance, 379–380
 - features, 361–366
 - key requirements for, 379
 - materials for, 361
 - multi-fuel capability in fuel cell mode, 364
 - operating principles, 359–360, 359–361
 - performance curve of YSZ based cell, 380
 - simplified system schematic, 382
 - stability for reversible operation, 379–380
 - ten-cell RSOFC stack and performance, 381
 - voltage–current density curves, YSZ-based cells with, 380
- Rhizobium*, uptake hydrogenase (HUP), 464
- rhodium nanoparticles, 448
- Rhodobacter sphaeroides*, 476

- light harvesting antenna complexes, deletion of, 476
 - mutation of, 476
 - risk management, 935
 - RME. *see* rapeseed methyl ether
 - RPSA. *see* rapid pressure swing adsorption
 - RR. *see* rapid risk ranking
 - RSOFC. *see* reversible solid oxide fuel cell (RSOFC) technology
 - RSOFC technology. *see* reversible solid oxide fuel cell (RSOFC) technology
 - Ru/Al₂O₃ catalysts, 188
 - RuO_x film, 446
 - ruthenium dioxide (RuO₂), 299
 - ruthenium oxide (RuO₂), 340
- S**
- Saccharomyces cerevisiae*, 473
 - safe handling, of hydrogen, 938
 - gaseous hydrogen, 939
 - handling emergencies, 940
 - liquid hydrogen, 939–940
 - safe reserve power generation systems, 1054
 - safety engineering, 1039
 - safety-related properties, of hydrogen, 937, 938
 - chemical properties, 937–938
 - corrosion and materials compatibility, 938
 - physical properties, 937
 - saline aquifers, 635
 - salt cavern, 622
 - compressed air energy storage (CAES), 622
 - diagram/input parameters of, 623
 - variation of the temperature, 623
 - salting-out effect, 632
 - Sankey diagram, 982
 - SCWG. *see* supercritical water gasification (SCWG)
 - SDOs. *see* standards drafting organizations
 - seawater, 1092
 - desalination, 1092–1093
 - secondary battery system, 834
 - selective adsorbents, 499
 - alumina, 499
 - capillary condensation, 499
 - heavy hydrocarbons, 499
 - HKUST-1 adsorbent, 499
 - linear isotherm, 501
 - mechanical properties of, 499
 - mechanical stability, 499
 - metal–organic frameworks (MOFs), 499
 - particle movement, to avoid, 499
 - pressure equalizations, 501
 - PSA unit, 499
 - silica gel, 499
 - type V isotherm, 499
 - vapor–liquid equilibrium, 499
 - water loading of a basic gamma alumina, 499
 - zeolite layer, 501
 - selective CO methanation, 206
 - self-immobilized microbes, 427
 - self-sustaining cooling, 713
 - semiconductors, 443, 447
 - band gap positions, 443, 444
 - materials, 441
 - photoelectrochemical materials, modern, 472
 - surfaces, 19
 - valence and conduction band
 - related to electrochemical redox potentials, 444
 - separation devices, 189
 - adsorption process, 189
 - balance-of-plant (BOP) components, 191
 - heat exchangers and evaporators, 192
 - pumps and compressors, 191–192
 - membrane process, 189–190
 - sewage sludge, 424
 - SHE. *see* standard hydrogen electrode
 - shock tube measurements, 1014
 - short term operating reserve (STOR), 277
 - Sievert's law, 190
 - silica gel, 499
 - water adsorbed in, 499
 - silicone, 472
 - siloxanes, 550
 - simulated grid load, 310
 - single-wall nanotubes (SWNTs), 784
 - sintering, 232
 - Skarstrom cycle, 492
 - steps of, 496
 - adsorption, 496
 - counter-current blowdown, 496
 - counter-current purge, 497
 - pressurization, 497
 - SLFs. *see* synthetic liquid fuels (SLFs)
 - slurry hydrocracking, 10
 - small-scale CO₂ capture, 231
 - small-scale reformer systems, 219
 - categorized by defining sizes, 219
 - small-scale reforming, for on-site hydrogen supply, 217
 - emerging technologies, 228–229
 - clean-up technology, 230–231
 - material development, 229–230
 - reactor improvements and design aspects, 230

- small-scale CO₂ capture, 231
- feedstock options, 223
- biodiesel, 224–225
- biomethanol and bioDME, 224
- biopropane, 225
- upgraded biogas, 223–224
- industrial reformer unit, schematics of components in, 218
- process control, 232
- reforming technologies, 219
- hydrogen purity, 221–223
- partial oxidation, 220–221
- steam methane reforming (SMR), 219–220
- small-scale reformer systems
- categorized by defining sizes, 219
- suppliers and products, 225
- cost trends, 225
 - central plant production, 225–226
 - economics, on-site vs. central plant production, 227–228
 - on-site SR, 226–227
- small scale water electrolyzers, 284
- smart grid, 1081
- SMES. *see* superconducting magnetic energy storage (SMES)
- SMRs. *see* steam-methane reformers
- SNG. *see* substitute natural gas (SNG)
- SOC. *see* state-of-charge (SOC)
- sodium alanate (NaAlH₄), 774
 - dehydrogenation of, 774
 - suspensions of, 774
- sodium alanates, 791
- sodium chloride, 41
- sodium hydroxide
 - usage, 53
- sodium hypochlorite, 53
- sodium sulfur, 265
- SOEC. *see* solid oxide electrolysis (SOEC)
- SOEC technology. *see* solid oxide electrolysis cell (SOEC) technology
- SOFCs. *see* solid oxide fuel cells
- SOFC technology. *see* solid oxide fuel cell (SOFC) technology
- solar
 - -aided chemistry, 155
 - -aided methane reforming, 154
 - chemical receiver/reactors, 157
 - concentration systems, 154
 - -driven PEC water splitting device, 457
 - energy, 87, 89, 152, 267, 461
 - import, from Northern Africa, 825
 - furnaces, 90
 - heated tubular receivers, 156
 - H₂ production, 472
 - installations, 256
 - irradiation, 155, 156
 - light, 450
 - power, 157, 260
 - plants, 266, 711
 - PV systems, 258
 - radiation, 91, 156
 - reactors, 90
 - receivers, 155
 - operational principles, 155
 - reactor concepts, 154
 - thermal power, 785
 - plants, 87
 - thermal reforming, 151
 - current development status and future prospects, 167–169
 - of methane, 157–159
 - thermal water decomposition, 87, 88
 - thermochemical cycles, 89
 - thermochemical reactor, 96
- solid fuels (coal, biomass), 242
 - basic principles and reactions of syngas production, 242
 - hydrogen production from, 242
 - gasification, 242–244
- solid–gas reactions, 91
- solid oxide electrolysis (SOEC), 309
- solid oxide electrolysis cell (SOEC)
 - technology, 372–379
 - applications, 378–379
 - Co-electrolysis of H₂O and CO₂, 378
 - current densities at thermoneutral voltage, 374
 - efficient production of hydrogen and chemicals in electrolysis mode, 364–366
 - materials for, 361
 - operation of multi-cell stacks, 373
 - performance (for hydrogen production from steam), 373
 - performance degradation and life, 375–376
 - performance degradation of 25-cell stack in terms of ASR, 377
 - performance of a ten-cell stack for electrolysis, 378
 - selected YSZ-based SOECs at thermoneutral voltage, current densities for, 374
 - ten-cell SOEC stack, 375
 - voltage as a function of time for ten-cell stack, 377
- solid oxide fuel cells (SOFCs), 544
- solid oxide fuel cell (SOFC) technology
 - applications, 371–372

- area specific resistance (ASR) breakdown, for a planar SOFC stack, 368
- catalysts for, 201
- cathode/metallic interconnect contact evolution, 370
- cell and stack design flexibility, 362
- cell-to-cell voltage variation, 367
- chromium poisoning of SOFC cathodes, potential steps in, 369
- fuel utilization, 370–371
- long-term performance of 96-cell planar stack, 371
- market sectors and applications, 372
- materials for, 361
- micrograph of Co-Mn spinel coated interconnect, 370
- multi-fuel capability in fuel cell mode, 364
- multiple fabrication options, 362
- Ni-YSZ anode, 368
- operating temperature choices, 362, 364
- performance, 366
- performance degradation and life, 368
- power systems, 373
- single cell (anode-supported) performance, 366
- single cells and microstructures, 362
- stacks and systems, operation and durability, 370
- state-of-the-art SOFC single cells, 367
- solid oxide fuel cell (SOFCs) technology, 366–371
 - market sectors and applications, 372
- solution-diffusion theory, 509
- sorbent-enhanced reforming (SER), 229
- sorption kinetics, 798
- Sotavento wind–hydrogen project, 1065
 - operation strategies tested in, 1066
 - capacity factor of wind farm, increasing of, 1070
 - deviation correction, 1069
 - load leveling enabling distributed generation, 1071
 - peaking plant, 1067
- Spain
 - electricity transport operator, 1053
 - National Renewable Energy Plan, 1053
 - RES2H2 site, 1060
 - wind power, 1053
- spark discharge, 142
- special ventilation system, 1008
- specific heat capacity, 175
- spherical liquid hydrogen tank, 958
- Spirulina maxima*, 473
- Spirulina platensis*, 470
- SSM. *see* supply-side management (SSM)
- stable compounds, 5
- stack voltage efficiency dependence, 1050
- stack voltage, temperature dependence of, 1048
- standard bus diesel engine, 971
- standard hydrogen electrode (SHE), 596
- Standards Drafting Organizations (SDOs), 921
- standards, regulations, and products, relationship between, 921
- standard systems, 1057
- Starch, 470
 - catabolism of, 470
- state-of-charge (SOC), 797, 1090
- stationary application areas, and requirements, 660
 - chemical usage, as a versatile energy carrier, 660
 - compressed gaseous tanks, 661
 - delivery infrastructure, 660–661
 - renewable energy production, 661
 - small-scale storage facilities, 661
 - storage facilities of different sizes, 661
 - underground storage facilities, 660
- stationary hydrogen storage
 - costs for bulk storage, 675
 - economic data and targets
 - of DOE, 677
 - of EC, 677
 - investment cost, based on storage size and targets of EC for, 676
 - methods for, 659
 - technical and economic data, of spherical pressure vessels, 676
 - technical assessment of bulk hydrogen storage technologies, 678–682
- steam-methane reformers (SMRs), 5, 15, 493
- steam methane reforming, 218, 231
- steam methane reforming (SMR), 131, 151, 219–220
 - steam-to-carbon ratios, 220
 - water–gas shift, 220
- steam reforming, 237, 331, 398
 - advantage of, 194
 - of natural gas, 23
- storage capacity, 630
 - electricity storage systems, 277
- storage efficiency, 660
- storage heat receptivity
 - in cold operation, 713
- storage parameters, 661–662
 - gravimetric and volumetric capacity, 661

- gross and net storage capacity, 662
 - lower heating value (LHV), 662
 - standard temperature and pressure (STP), 662
 - street system infrastructure, 966
 - “structured” catalytic systems, 155
 - Structured What-IF checklist (SWIFT), 924
 - submarine
 - hydrogen and fuel cells in, 991
 - historical perspectives, 992
 - ThyssenKrupp Marine Systems, 992
 - overview, 991
 - network system, 991
 - reformer system conceptual integration, 1008
 - snorkel operation of, 991
 - substitute natural gas (SNG), 866
 - subsystem reforming. *see also* fuel processing
 - optimization of, 193
 - catalyst development, 200–201
 - process selection and optimization, 193–200
 - technical outlook, 204–205
 - sugars, 471
 - sulfate compounds, 634
 - sulfur, 3, 5, 237
 - impurities, 237
 - sulfur components, 558
 - amines like diethanolamine (DEA), 558
 - methyl-diethanolamine (MDEA), 558
 - removal of, 558
 - sodium hydroxide (NaOH), 558
 - sulfur compounds, 152
 - sulfur-containing compounds, 19
 - sulfur-containing hydrocarbons, 190
 - sulfur cycles, 96
 - sulfuric acid, 89, 97
 - sulfur–iodine cycle, 88
 - sulfur–iodine process, 98
 - sulfur–iodine water-splitting cycle, 98–99
 - basic reactions, 98
 - efficiency, 100
 - sulfur tolerance, 201
 - superconductors, 264
 - superconducting magnetic energy storage (SMES), 264
 - superconductivity, 785
 - supercritical steam reforming, 195
 - supercritical water gasification (SCWG), 110
 - biomass used for, 109–119
 - catalysts, 119
 - limitation, 119
 - catalyst stability, 122
 - heating-up, 119
 - heat recovery, 120
 - material choice, 121–122
 - salt deposition, 121
 - yield, 120–121
 - new developments, 122–123
 - feedstock, 122–123
 - new catalysts, based on Ni-Mg-Al/Ru, 122
 - pretreatment methods, 122
 - scale-up and technical application, 122
 - plant VERENA, 122
 - super-heater device, 972
 - supply-side management (SSM), 262, 263
 - surface tension, 303
 - sustainable energy system, 1075
 - SWNTs. *see* single-wall nanotubes (SWNTs)
 - Synechococcus elongatus*, 470
 - syngas, 139, 237, 1011. *see also* synthesis gas
 - ammonia syngas production from natural gas
 - steps, 239
 - production, 153
 - based on fossil fuels and biomass, 238
 - by partial oxidation of heavy oils/gasification, 241, 244–246
 - by steam reforming of natural gas, 246–249
 - and treatment, depending on final use, 239
 - treatment steps, to remove unwanted impurities, 237
 - synthesis gas, 237, 543
 - ratio, adjustment of the, 509
 - synthetic diamond growth, 785
 - synthetic fuels, 36
 - producer of, 36
 - synthetic liquid fuels (SLFs), 151
- t**
- Tafel slope, 299
 - tail gas, 495
 - tars, 556
 - separation of, 556
 - tars/higher hydrocarbons, 555
 - catalytic reduction, 557
 - Al₂O₃, 557
 - fluid catalytic cracking (FCC), 557
 - synthetic catalysts, 557
 - catalytic reforming, 556
 - downstream processes, 556
 - hot gas tar reforming, 556
 - rapeseed methyl ether (RME), 556
 - thermal cracking, 556
 - zeolites, 557
 - TBAF. *see* tetra-*n*-butylammoniumfluoride
 - TBT. *see* Technical Barriers to Trade

- TCA. *see* temperature cycling adsorption (TCA)
- TCIs. *see* total capital investments (TCIs)
- TCO. *see* total cost of ownership (TCO)
- Technical Barriers to Trade (TBT), 923
- technical data of, 1001
 - BZM 34, 1000, 1001
 - BZM 120, 1000, 1001
- technologies, to remove pollutants, 551–558
 - alkali components, 555
 - Al_2O_3 , 555
 - getter materials, 555
 - overview of alkali removal options, 555
 - SiO_2 , 555
 - cold gas clean-up (CGC), 551, 552
 - hot gas clean-up (HGC), 551, 552
 - particulate matter, 552–555
 - sulfur components, 558–559
 - tars/higher hydrocarbons, 555–558
- technology options, for integrating variable renewables, 262
- technology readiness level (TRL), 1082
- Teflon-sealed reactor, 450
- temperature cycling adsorption (TCA), 189
- temperature swing adsorption (TSA), 493
- tetrahydrofuran (THF), 597
- tetra-*n*-butylammoniumfluoride (TBAF), 597
- TFC membrane, 522
 - discontinuous process, 523
 - resistance model of, 524
- THD. *see* total harmonic distortion (THD)
- thermal-based electricity storage, 265
- thermal conductivity, 578–579, 800
 - definition of, 578
 - fourier's law, 578
- thermal cracking, 556–557
- thermal decomposition, of water, 88
- thermal dissociation, of water, 87
- thermal efficiencies, 101, 136
- thermal plasmas
 - DC-RF plasma, 145–146
 - DC torch plasma, 144–145
 - three-phase AC plasma, 145
 - used in hydrogen production, 144
- thermal power plants, 1053
- thermal reforming, 218
- Thermoanaerobacterium*
 - thermosaccharolyticum*, 420
- thermochemical cycles, 87
 - decompose water into, 89
 - historical perspective, 88
 - *T-S* diagram of two-step cycle to split water, 90
- thermochemical hydrogen production, 87
- thermochemical processes,
 - characterization, 393
- thermochemistry, 152
- thermodynamics, 88
 - limitations, 174
 - of methane reforming, 152
 - properties of H_2 , 569–573
 - Joule–Thomson effect, 572–573
 - pressure–temperature phase diagram, 569–571
 - pressure–volume phase diagram, 571–572
 - properties relations, 175–178
 - quantities, decision tree for determination of, 176
 - state variables, calculation of, 602–606
- thermolysis reaction, 87
- thermoneutral cell voltage at STP, 1050
- thermophiles, 420, 429
- thermophilic biohydrogen production, 420
 - via dark fermentation, biochemistry, 420–421
- thermophilic dark fermentation, 429
 - costs of operation, reduction, 431
 - problem associated with, 430
- thermophilic hydrogen producing bacteria, 420
 - microbial characteristics, 421–422
- thermophilic temperature, 430
- Thermotoga elfii*, 420
- THF. *see* tetrahydrofuran
- thin film composite membranes, 511
- thylakoid membrane, 441, 465
- ThyssenKrupp Marine Systems, 992
- TiO_2 based catalyst, 141
- titanium, 352
- Tokyo motor show, 833
- toluene, 203, 205
- total capital investments (TCIs)
 - calculation, 406
 - of hydrogen production, 407–408
 - cost fractions, representation, 409
 - for similar technology devices, 406
- total cost of ownership (TCO), 836
- total European chlorine production capacity, 28
- total harmonic distortion (THD), 1062
- town gas storages, 651–652
 - Beynes, Ile de France, France, 654
 - town gas storage at ketzin, Germany, 652–653
 - town gas storage at lobodice, Czech Republic, 652

- trace gas components, 547
 - alkali compounds, 549
 - biomass gasification synthesis gas, 547
 - contaminants in biomass synthesis gas, 548
 - halogen compounds, 550
 - C_2Cl_4 , 550
 - halides of catalyst metals, 550
 - HCl, 550
 - HF, 550
 - nitrogen compounds, 550
 - HCN, 550
 - NO_x , 550
 - other potential contaminants, 550
 - metal–organic compounds, 550
 - phosphorus, 550
 - particulate matter (particles), 549
 - particle content in untreated product gas, 549
 - siloxanes, 550
 - deposition of silicon compounds, 550
 - wastewater treatment, 550
 - sulfur compounds, 549
 - tars, 547
 - content in untreated product gas, 548
 - cyclic hydrocarbons, 547
 - naphthalene, 548
 - transit bus applications, 986
 - transition metal compounds, 448
 - transition metal oxides, 443
 - transmembrane flux
 - calculation of, 515
 - transparent hydrocarbon fuels, 143
 - transport costs, 406
 - transport of molecules, 509
 - trimethylbenzene, 203
 - 2,2,4-trimethylpentane, 143
 - triple point, 570
 - tritium, 566, 764
 - TRL. *see* technology readiness level (TRL)
 - truck applications, 987
 - TSA. *see* temperature swing adsorption (TSA)
 - tube-trailer delivery pathway, 860
 - challenges, 863
 - analysis, 864
 - compression, 864
 - distribution issues, 863
 - high storage cost, 864
 - components layout, 860
 - cost estimates, 861
 - tubing, 642
 - tubular reactors, 141, 168
 - tubular reformers, 154
 - tungsten-nickel sulfide, 7
 - turbulent flame speed, 1017
 - Turkish Bozca Island, 1082
 - UNIDO-ICHET's Bozcaada Wind-Solar Hydrogen project, 1082
 - two-stage compressor system, 974
 - type3 cylinder technology, 975
 - typical time spent
 - at power demands, 968
 - at vehicle speeds, 968
- u**
- UASB reactor, 429
 - UK H2 mobility program, 217
 - ultra-low-sulfur (ULS) gasoline, 3
 - United States of America, 76
 - energy framework and relevant policies, 76
 - state and local government activities, 76
 - hydrogen related energy policy strategies, 76–77
 - Hydrogen and Fuel Cells Program, coordination, 76
 - US DOE Hydrogen and Fuel Cells Program Annual Progress Report, 76
 - zero emission vehicles, 76–77
 - hydrogen research, development, demonstration, and deployment activities, 77–78
 - Hydrogen and Fuel Cells Program, key targets/collaborations, 77–78
 - US DoE Hydrogen and Fuel Cells Program overview, 77
 - unit operations, 180
 - upflow anaerobic sludge blanket bioreactor (UASB), 427, 429
 - UPS (uninterruptable power supply), 64
 - uptake hydrogenase (HUP), 467
 - uranium–europium cycle, 100, 102
 - urea production
 - International Fertilizer Organization data, 32
 - US Department of Energy (DOE), 850
 - US Department of Transportation (DOT), 861
 - UT-3 cycle, 88, 100, 101
 - as competing process in hydrogen production, 101
 - gas–solid reactions, 101
 - research focused on, 101
 - thermal efficiency, 101
 - UV irradiation, 476
- v**
- vacuum plasma spraying (VPS), 1049
 - value-added tax (VAT), 842

- vanadium redox (VRB), 265
 - Van't Hoff plots, 765
 - VAT. *see* value-added tax (VAT)
 - Vattenfall, 898
 - vehicle batteries, 711
 - vehicle onboard storage, 711
 - vehicle storage tank, 620
 - refueling of a, 620–622
 - time of, 620
 - viscosity, 296, 340, 634, 639
 - volatile compounds, 242
 - volatile solid (VS), 429
 - voltage efficiency, 1050
 - volumetric hydrogen density, 770
 - “volumetric” receivers, 156
- W**
- waste products, 403
 - wastewater, 431
 - treatment, 1093
 - water
 - consumption rate, 347
 - dielectric constant, 112
 - hydrogen bonds, 112
 - polarity, 112
 - properties of, 111–112
 - as function of temperature, 112
 - role in different reaction pathways, 112
 - at supercritical conditions, 112
 - ionic product, 112
 - thermal decomposition, 88
 - water electrolysis, 283, 309, 457, 566
 - conceptual distributed energy system with, 284
 - gas drying, 316–317
 - hydrogen production cost, 326
 - investment costs, 325
 - lifetime of, 326
 - operating principles of different types of, 332
 - power supply, 317
 - process steps and system integration of, 310
 - system design and operation strategy, 327
 - thermodynamic consideration, 285
 - electrode kinetics, 287–292
 - theoretical cell voltages, 285–287
 - unit, 255
 - water-gas shift (WGS) reaction, 26, 118, 152, 154, 179, 181, 184–186, 231, 238
 - water oxidation, 461
 - water oxidizing photoelectrodes, 447
 - water splitting devices
 - design of, 448–455
 - water splitting mechanism, 461
 - other methods of, 462
 - electrolysis, 462
 - gasification, 463
 - photobiological splitting, 463
 - photochemical splitting, 463
 - steam electrolysis, 462
 - steam reforming, 462
 - thermal splitting of water, 463
 - water splitting membrane, 442
 - solar-to-hydrogen (STH) efficiency of, 445
 - wave speed, 646
 - Westinghouse cycle, 89
 - WGS reactor, 185
 - WI. *see* Wobbe Index (WI)
 - wind capacity, 260
 - wind constraints, 261
 - wind–electrolyzer coupling, 1045
 - wind energy, 260
 - as hydrogen, storage of, 1034
 - wind farm production, 1067
 - capacity factor of, 1070
 - H₂ storage, 1069
 - wind generator electrical power input, 1062
 - wind–hydrogen plant, 1061
 - wind–hydrogen projects, description of, 1059
 - Hidráulica project, 1061
 - ITher project, 1063
 - RES2H2 project, 1060
 - Sotavento project, 1064
 - wind–hydrogen systems, 1056, 1087
 - wind load factors, 256
 - wind penetration, 260
 - wind power, 261, 1054
 - integration on energy system, 256
 - management, 1058
 - for the Netherlands, 260
 - wind power plants, 1087
 - capacity factor, 1087
 - wind promoters, 1055
 - wind turbines, 255, 309, 317, 1083
 - Wobbe Index (WI), 1013
 - wood chip gasification, 398
 - energy demand, 405
 - World energy consumption, 359
 - World Trade Organization's (WTO's), 923
 - wurtzite, 91
- y**
- yttria-doped ceria (YDC), 367
- z**
- zeolites, 493, 557, 784
 - cost of, 501

- density of, 501
- pores in, 501
- zero boil-off (ZBO), 961
- zero emission vehicles (ZEVs), 349, 711, 845
 - air quality, 845
 - global warming reduction, 845
 - public health, 845
 - societal costs reduction, 845
- ZEVs. *See* zero emission vehicles (ZEVs)
- zinc, 13, 91, 95, 283
- zinc bromine [Zn Br], 265
- zirconium oxides, 189
- ZnO bed, 153
- ZnO/Cu₂O photocathode, 447
- ZnO, solar dissociation of, 95
- Zn/ZnO system, 94–95
- Zr-supported Rh/Pt catalyst, 201

