

Index

a

- acquisition reform 395
- active electronic components packaging
 - blends 394–395
 - adhesives 398–399
 - molding material 396–398
- aerospace adhesive applications 339–340
- aliphatic polyesters 257
- amine-terminated butadiene acrylonitrile (ATBN) 45–46, 275–276, 283
- applications 339, 343–344
 - aerospace adhesive applications 339–340
 - composites 341–342
 - epoxy resin modification 342–343
 - nanoparticle modification 343
 - rubber-modified resins 340–341
 - thermoplastic modification 343
 - thermoset-based materials for optical applications containing azobenzene chromophores 344–345
 - epoxy-based networks 345–349
 - photoaddressable networks containing alkyl compounds 354–358
 - urethane-based networks 349–354
- atomic force microscopy (AFM) 56, 153–156, 166
- autocatalytic model 113
 - model parameters determination 113–115

b

- B/D approach 110
- Bailleul model 117
- block copolymers as modifiers 16
- Bragg's law 241

c

- Cahn–Hilliard model 243
- carbon nanotubes (CNTs) 307, 309, 401, 412

- carboxyl-terminated polybutadiene (CTPB) 320–321, 331
- carboxyl-terminated
 - poly(butadiene-co-acrylonitrile (CTBN) 44–46, 210–211, 275, 299–301, 315–317, 319–320, 331–332, 340, 343, 410
- Coats–Redfern (CR) method 300
- combinatorial entropy 128
- conductivity 310–311
- confining-fluid technique 184–185
- core–shell particles 14
- core–shell rubber-modified epoxies 224, 226–227
- crack pinning 22
- crazing 19–21
- creep 413–414
- creep tests 400
- critical point 129
- cure analysis 83–84
- cured materials viscoelasticity
 - dielectric measurement 231–233
 - dynamic mechanical study 228–231
- cure reactions 1–2
- curing agents 2
 - catalytic cure 3
 - co-reactive cure 3
 - acid anhydrides 5–7
 - carboxylic acids 5
 - isocyanates 5
 - mercaptans 5
 - primary and secondary amines 3–4
- curing kinetics 84
 - activation energies 86
 - dynamic methods 86–87
 - isothermal methods 87
 - analysis 85
 - autocatalytic model 85

- curing kinetics (*contd.*)
 - dielectric spectroscopy thermal method 94–96
 - differential scanning calorimetry (DSC) 88
 - – dynamic 89–90
 - – isothermal 90–92
 - dynamic mechanical analysis (DMA) and rheological methods 97–100
 - Fourier transform infrared (FTIR) spectroscopy 92–93
 - pressure–volume–temperature (PVT) method 96–97
- curing kinetics modeling 106–107
 - mechanistic approach 107–109
 - phenomenological models describing reaction 109–117
 - rheological models 118–119
 - vitrification effect on reaction rate 119–121
- curing methods 7
 - microwave curing
 - radiation curing
 - – electron beam curing 10
 - – gamma ray irradiation 8–12
 - thermal curing 7–8
- curing process theoretical modeling 105
 - curing kinetics modeling 106–107
 - – mechanistic approach 107–109
 - – phenomenological models describing reaction 109–117
 - – rheological models 118–119
 - – vitrification effect on reaction rate 119–121
 - empirical models application 120, 122
- curometer 206
- d**
 - Debye–Bueche theory 252
 - dielectric constant 306–308, 311
 - dielectric spectroscopy thermal method 94–96
 - differential scanning calorimetry (DSC) 67, 79, 88, 106, 109–110, 113, 117, 187, 290
 - dynamic 89–90
 - isothermal 90–92
 - diffusion factor 88
 - diglycidyl ether of bisphenol-A epoxy resin (DGEBA) 316–320
 - dispersion process 17
 - dry-brush “wet-brush” model 61–63
 - dynamic (constant heating rate) methods 110
 - dynamic mechanical analysis (DMA) and rheological methods 97–100
 - dynamic scanning curing process 113–115
- e**
 - elastomeric modified epoxies dielectric properties 305–306
 - combined studies on dielectric constant volume resistivity, and conductivity, 311
 - conductivity 310
 - dielectric constant 306–308
 - volume resistivity 308–310
 - elastomer-modified epoxy resins 18
 - cavitation and rumples 22–23
 - crack pinning 22
 - crazing 20–21
 - particle deformation 18–19
 - shear yielding 19–20
 - simultaneous shear yielding and crazing 21–22
 - electrically conductive adhesives 415
 - epoxy-based networks 345–349
- f**
 - failure analysis 396, 405
 - methods 405–409
 - self-healing 416–417
 - typical failure modes and mechanisms used in micro and nanotechnologies 405
 - – ion contamination 414–416
 - – mechanical damages 409–414
 - fiber-reinforced polymer (FRP) 400
 - flash method 294
 - Flory–Huggins approximation 242
 - Flory–Huggins model 64
 - Flynn–Wall–Ozawa method 86
 - Fourier’s law 292
 - Fourier transform infrared (FTIR) spectroscopy 79, 92–93, 307, 316
 - and Raman spectroscopy 316, 320–322
 - – DGEBA epoxy/rubber blends 316–320
 - – imaging 322–323
 - Fox’s theory 204
 - fractography. *See* fracture
 - fracture 409–413
 - fracture energy 24
 - fracture toughness 65–66, 281–282
 - concentration effect 282–284
 - curing agent effect 285
 - strain rate effect 284–285
 - Furukawa scaling theory 132
- g**
 - gel permeation chromatography (GPC) 84
 - gel time model 118
 - GLARE 341–342
 - glass transition temperature 67

Gnomix apparatus 185
 guarded hot plate method 292

h

Highly Accelerated Stress Test (HAST) 396
 high-pressure liquid chromatography (HPLC) 108
 high voltage direct current (HVDC) 308
 hot disk method. *See* transient plane source
 hot wire method 293–294
 hydroxyl terminated polybutadiene (HTPB) 317, 319, 326–329, 333, 410
 hydrothermal toughening agents 14
 hyperbranched polymer blends development and properties 375–378
 – and rubbers as tougheners 383–387

i

interfacial adhesion 18
 inverse estimation method 296
 ion contamination 414–416
 isoconversional method principle 111–112
 isothermal curing methodology 113
 isothermal method 110
 isotropic polymers 255

k

Kamal and Sourour model 115–116
 Kerner equation 281
 Kissinger equation 111

l

life cycle assessment (LCA) 421–422
 – in aerospace application 429–430
 – analysis of epoxy resin containing carbon nanotubes 426
 – in automotive application 428
 – of epoxy resins produced based on propylene and glycerin 424–426
 – natural fiber-reinforced epoxy composites 430
 – of novel hybrid glass-hemp and thermoset composite 430
 – significance 422
 – – goal and scope definition 422–423
 – – impact assessment 423–424
 – – inventory analysis 423
 – – result interpretation 424
 – of wind turbine blade materials 426–428
 light scattering experiment 242–250
 liquid elastomers for toughening matrices 13–14
 liquid-filled urea-formaldehyde 416

liquid molding technologies novel toughening approaches 378–382
 liquid rubber blends manufacture 73
 – comparison of hardeners 74–77
 – cure reaction analysis 79
 – rubber-toughened epoxy resins 77–79
 liquid-rubber-modified epoxies 224
 – core–shell rubber-modified epoxies 224, 226
 – ternary systems with fillers 228
 liquid toughening rubber
 – fracture behavior of thermosets 32–35
 – natural rubbers 35–36
 – – preparation method 36–42
 – in thermoset resins 31–32, 43–49

m

Maxwell-type equation 244
 Maxwell–Wagner–Sillars polarization 94
 mechanical damages
 – creep 413–414
 – fracture 409–413
 mechanical properties 271–272
 – fracture toughness 281–282
 – – concentration effect 282–284
 – – curing agent effect 285
 – – strain rate effect 284–285
 – of rubber-modified epoxies 272–273
 – – acrylonitrile content influence 279–280
 – – curing agent influence 278–279
 – – initial cure temperature influence 276–277
 – – Kerner equation 281
 – – rubber concentration influence 273–276
 – – strain rate influence 280
 micro/nanotechnologies and reliability testing 392–394
 miscibility and phase behavior studies in polymer blends 239–240
 – light scattering experiment 242–250
 – neutron scattering
 – – small-angle neutron scattering (SANS) 261–266
 – scattering theoretical considerations 240–242
 – X-ray scattering 250–260
 modulated DSC 295
 molding compounds (MCs) 415, 416
 morphology analysis by microscopy techniques and light scattering 147
 – developments in rubber-modified epoxies 147–148
 – – atomic force microscopy (AFM) 153–156, 166

- morphology analysis by microscopy
 - techniques and light scattering (*contd.*)
 - optical microscopy (OM) 148–150
 - scanning electron microscopy (SEM) 150–153
 - small-angle light scattering (SALS) 159
 - transmission electron microscopy (TEM) 155–159
 - toughening morphology and reinforcing effects 165
 - conventional additives 165–167
 - hyperbranched polymers 167–171
 - types 160
 - homogeneous morphology 163–165
 - hybrids morphology 161–163
 - phase-separation morphology 160–161
- n**
 - nano carbon and silica nano particles toughening 213
 - nano clay toughening of epoxy resins 213
 - nanocomposites 399
 - nanoparticles 15
 - modification 343
 - nanostructured epoxy composites 53–54
 - mechanical and thermal properties
 - fracture toughness 65–66
 - glass transition temperature 67
 - microphase separation mechanism 60–61
 - reaction-induced 63–65
 - self-assembly mechanism 61–63
 - morphology 56
 - blends composition 56–58
 - curing agent choice 58–59
 - topological architecture of copolymer 59–60
 - thermoset preparation methods 54–56
 - nanostructured thermoset 374
 - National Aeronautic and Spatial Agency (NASA) 396
 - natural rubbers 35–36
 - preparation method 36
 - metathesis degradation 40–42
 - oxidation at high temperatures and high pressures 38
 - oxidation by cleavage reagent specific to double bonds 38–40
 - oxidation by photochemical method 37–38
 - oxidation in presence of redox system 36–37
 - near-infrared (NIR) spectroscopic analysis 106
 - needle probe method 293
 - neutron scattering
 - small-angle neutron scattering (SANS) 261–266
 - n*th-order model 109
 - model parameters identification 110–112
 - nucleation and growth mechanism 130
 - See also* spinodal decomposition
- o**
 - optical microscopy (OM) 148–150, 333
 - Ozawa equation 111
 - ozonolysis 38–39
- p**
 - particle deformation 18–19
 - Pascualt–Williams relation 119
 - periodic acid and transition compounds cleavage 39–40
 - periodic methods 295
 - phase-separation mechanism 127–128
 - cured blends 133–144
 - thermodynamics 128–129
 - nucleation and growth mechanism 130
 - spinodal decomposition 130–131
 - uncured epoxy resin/liquid rubber blends 131–133
 - photoaddressable networks containing alkyl compounds 354–358
 - piston-die technique 184
 - plasticization 213–214
 - polyethersulfone (PES) 211–213
 - polymerization-induced phase separation (PIPS). *See* reaction-induced phase separation (RIPS)
 - Porod–Kratky relation 252
 - premeditation 392
 - pressure–volume–temperature (PVT) analysis 96–97, 179
 - measurement techniques 184–187
 - measures, on epoxies 187–190
 - polymer behavior generalities 180–184
 - PRIFORM technology 379–382, 388
- r**
 - Rabinovitch model 120
 - reaction-induced phase separation (RIPS) 61, 127, 138, 366, 370
 - reliability testing 391–392
 - behavior in real applications and aging studies
 - blends in active electronic components packaging 394–399
 - epoxy matrix in nanocomposites 399
 - in micro/nanotechnologies 392–394
 - rheological models

- gel time model 118
- viscosity model 118–119
- Rouse theory 202–203
- rubber-modified epoxy resin 16
 - concentration effect 282–284
 - interfacial adhesion 18
 - particle size and rubber distribution 16–17
 - rubber effect 17
 - temperature effect 17
- rubber-toughened structural epoxy resin systems rheology 193
 - cure process modeling 198–201
 - cure rheological studies 206–209
 - epoxy resin chemistry 194–195
 - – basic chemical reactions 195–196
 - – cure kinetics 196–198
 - – epoxy reactivity 198
 - rheological implications of differences in reactivity 201
 - – connection between rheology and cure 203–206
 - – rheological behavior modeling 202–203
 - toughened epoxy resins 209–210
 - – carboxy-terminated butadiene acrylonitrile (CTBN) 210–211
 - – nano clay toughening of epoxy resins 213
 - – plasticization 213–214
 - – polyethersulfone (PES) 211–213
 - – toughening with nano carbon and silica nano particles 213
- Runge–Kutta algorithm 115

S

- scanning electron microscopy (SEM) 56, 150–153, 160–162, 164–167, 169–171, 210, 274, 277, 281, 316
- and TEM
 - – acid-terminated rubber/DGEBA epoxy blends 323–326
 - – hydroxyl-terminated rubber/DGEBA epoxy blends 326–329
 - – neutral rubber/DGEBA epoxy blends 329–330
- scanning probe microscopy (SPM) 153
- scanning tunneling microscopy (STM) 153–155
- Scherrer equation 254
- shear rate (SR) 308
- shear yielding 19–20
- silica nanoparticles 400–401
- simultaneous shear yielding and crazing 21–22
- size exclusion chromatography (SEC) 105

- small-angle light scattering (SALS) 159
- small-angle X-ray scattering (SAXS) 56, 61–63, 251–255, 258, 262
- specific heat 289–292
 - classical model for thermal conductivity 296–297
 - kinetic study from TGA 300–301
 - thermal conductivity 292
 - thermal steady-state methods 292–293
 - thermal transient methods 293–296
 - thermogravimetric analysis of rubber/epoxy systems 297–300
- spectroscopy analysis, of micro/nanostructured epoxy/rubber blends 315–316, 333
 - FTIR and Raman spectroscopy 316, 320–322
 - – DGEBA epoxy/rubber blends 316–320
 - – imaging 322–323
 - SEM and TEM
 - – acid-terminated rubber/DGEBA epoxy blends 323–333
 - – hydroxyl-terminated rubber/DGEBA epoxy blends 326–329
 - – neutral rubber/DGEBA epoxy blends 329–330
- spinodal curve 129
- spinodal decomposition 130–131, 136–137, 142, 144
- static bending tests 400
- strain energy release rate 66
- structure–property relationship 12–13

T

- Taylor's relationship 16–17
- thermal properties 289
 - specific heat 289–292
 - – classical model for thermal conductivity 296–297
 - – kinetic study from TGA 300–301
 - – thermal conductivity 292
 - – thermal steady-state methods 292–293
 - – thermal transient methods 293–296
 - – thermogravimetric analysis of rubber/epoxy systems 297–300
- thermoplastic blends development and properties 363–375
 - and rubbers as tougheners 383–387
- thermoplastic modification 15, 343
- thermoset-based materials for optical applications containing azobenzene chromophores 344–345
 - epoxy-based networks 345–349

- thermoset-based materials for optical applications containing azobenzene chromophores (*cont'd.*)
 - photoaddressable networks containing alkyl compounds 354–358
 - urethane-based networks 349–354
- thermoset resins. *See* liquid toughening rubber
- toughening, of epoxy resin 13
 - different agents 13
 - – block copolymers as modifiers 16
 - – core–shell particles 14
 - – hydrothermal toughening agents 14
 - – liquid elastomers for toughening matrices 13–14
 - – nanoparticles 15
 - – rigid crystalline polymers 14
 - – thermoplastic modification 15
 - toughening mechanisms quantitative assessment 23–24
 - transient line-source probe technique. *See* needle probe method
 - transient plane source 294
 - transmission electron microscopy (TEM) 20, 56–57, 63, 155–159, 258–261, 316
 - and SEM
 - – acid-terminated rubber/DGEBA epoxy blends 323–326
 - – hydroxyl-terminated rubber/DGEBA epoxy blends 326–329
 - – neutral rubber/DGEBA epoxy blends 329–330
- u**
 - ultra-small-angle X-ray scattering (USAXS) 259–261
 - upper critical solution temperature (UCST) 129–131, 134, 136
 - urethane-based networks 349–354
- v**
 - viscoelastic measurements and properties, of rubber-modified epoxies 219–220
 - below and near gel point
 - – core–shell rubber-modified epoxies 224, 226–227
 - – liquid-rubber-modified epoxies 224
 - – ternary systems with fillers 228
 - cured materials viscoelasticity 222–224
 - – dielectric measurement 231–233
 - – dynamic mechanical study 228–231
 - state transitions from liquid to solid 220–222
 - viscosity model 118–119
 - vitrification effect on reaction rate 119–121
 - vitrification of growing chain 12
 - volume resistivity 308–311
- w**
 - wide-angle X-ray scattering (WAXS) 251, 252, 254–255, 257
 - Williams–Landel–Ferry equation 222
 - wire bonds (WBs) 415–416
- x**
 - X-ray scattering 251–260