

Index

a

- abnormal degradation 237, 250, 251
- accelerated aging test 238, 239, 430
- acceptor-like defects 68
- AC electrical degradation 250
- ageing 99, 132, 235, 237–239, 242, 243, 245, 246, 249, 251–255, 268, 270, 272, 284, 288, 291, 407, 429–431
- annealing 68, 72, 74, 75, 78, 79, 83, 94, 143, 256, 261, 268, 324, 338, 356–357, 363, 377, 442
- antidegradation measures 267–272
 - heat treatment 268
 - optimization of formula 269–270
- asymmetric I–V characteristics 43–45

b

- back-to-back diode pairs 1
- bicrystal approach 143–145
- bismuth-rich phase 69, 71, 74, 76, 78, 426
- bismuth segregation 73
- breakdown 1–3, 6–8, 11, 18, 21, 43, 45, 50, 79, 85–87, 90, 93, 102, 107, 109, 126, 129, 131, 132, 134, 135, 141, 150, 153, 164, 169, 175–177, 179, 198, 207, 209, 215, 218, 237, 238, 242–244, 246, 281, 285, 286, 292, 307, 310, 311, 314, 317, 318, 321–324, 407, 410, 411, 413, 417, 441, 442, 446, 448, 453, 456
- breakdown track 198

- breakdown voltage 1–4, 6, 7, 9, 17–19, 45, 79–81, 85–87, 102, 103, 109, 110, 126, 129–132, 134, 135, 141, 153, 164, 169, 174, 175, 216, 224, 242–247, 281, 285, 286, 292, 299, 307, 310, 311, 314, 316–318, 320–325, 335, 338, 342, 354, 357, 368, 371, 373, 377, 407, 441–456
- bulk defect chemistry 78
- bypass effect model 33, 51, 156, 157

c

- capacitive current 57, 169, 170
- combustion synthesis technique 5, 309, 311
- complex donor 253, 254
- complex impedance 61, 62, 83, 283, 360, 361, 369, 374, 383, 425
- composite varistor 1, 18–22, 320
- conduction mechanism 10, 31–62, 149, 150, 152, 154–159, 165, 247, 339–341, 386
- conduction model 10, 31, 33, 46–50, 249
- controlled grain growth 321
- microwave sintering method 322–324
- spark plasma sintering (SPS) 324–327
- step-sintering approach 321
- current localization 175–179, 199–201, 206, 213–216, 220, 223, 224, 237

d

- Debye model 61
 deep bulk traps 46, 52–54, 79, 82,
 270
 deep donor 41, 60, 81, 83, 91, 253,
 254
 energy level 59–60, 414, 422
 deep level transient spectroscopy
 (DLTS) 68, 75, 93–95, 253, 300,
 422
 defect migration behavior 251
 defect reaction formula 250
 degradation 237
 asymmetrical deformation 238, 259
 drift phenomena of I – V curve 238
 of grain boundary 242–245
 degradation mechanism 11, 235–237,
 249, 257, 272
 AC 258–259
 asymmetrical variation of Schottky
 barrier 258
 DC 258
 desorption of oxygen 262
 impulse degradation factor 263–264
 microcrack 266
 nonuniform degradation 260–262
 pulse degradation 262–263
 superimposing degradation
 264–265
 δ - Bi_2O_3 71, 72, 324
 dielectric behaviors of ZnO varistor
 51
 distribution of leakage current 133,
 245
 distribution of nonlinear coefficient
 132
 dominant mobile ion 237, 252–255
 donor-like defects 68
 dopant effects
 acceptor dopants 86–87
 additives effects 79–82
 amphoteric dopants 87–92
 donor dopants 82–85
 hydrogen as a shallow donor 95
 for improving stability 93–95
 monovalent dopants 88–89

pinning action 92

rare earth oxides 92–93

trivalent dopants 89–92

double-Schottky barrier 10, 31, 100,
 101, 152, 155–158, 166, 235, 364,
 381, 441, 449, 454

dynamic resistivity 158, 159, 165, 166

e

- energy absorption capability 9, 81, 82,
 86, 92, 99, 177, 179, 193–230,
 288, 315, 429
 energy band 31, 33–40, 44–45, 47, 50,
 258, 260
 structure 31, 33, 35, 36, 39–46
 energy level 33–39, 43, 59, 60, 93, 158,
 159, 250, 251, 297
 energy state density 37, 38
 exaggerating grain growth 308–309
 seed grain method 308–309

f

- fabrication stages 75–76
 Fermi–Dirac function 37–38, 48
 first-principles calculation 95, 253,
 271
 fracture failure 197–209, 225–226

g

- grain boundaries
 classification of 134–136
 grain boundary defect model 236,
 249–251, 260, 346, 449
 grain boundary energy band diagram
 260
 grain boundary interface 78, 159, 251,
 260–262, 283, 344–346, 386,
 415, 416, 420, 422, 451
 grain boundary model 31, 166
 conduction mechanism 154–159
 I– V characteristic 151–154
 2D simulation model 159–161
 grain resistivity 49, 90, 91, 105, 159,
 180, 186, 187, 373, 428, 432,
 434
 growth-controlling mechanism 72, 96

h

high voltage gradient ZnO varistor
98–101, 229, 230

i

impulse failure mode 194–197
cracking destruction 195
puncture destruction 195, 196

impurity defect 253, 362

individual grain boundary 11, 31, 39,
40, 45, 46, 48, 50, 51, 125–127,
129, 131, 142–145, 149, 247,
251, 260

interfacial charge 31, 48, 54–58

intergranular layers 7, 17, 41, 43, 69,
70, 83, 86, 143, 153, 155–157,
183–187, 250, 251, 268, 270,
281, 285, 291, 296, 299, 339,
367

intrinsic defects 39, 83, 260, 380, 415,
420

inversion boundary 69, 81, 95–98

I–V characteristics of ZnO varistors
breakdown region 3
high electrical field region 3
low electrical field region 3
medium electrical field region 3
nonlinear region 3
pre-breakdown region 3
upturn region 3

l

line scan method 141

liquid-phase sintering 6, 9, 10, 44,
67–69, 76, 285, 286, 337, 351,
368, 370, 380, 410, 454

long-term aging simulation 253, 255

low residual voltage ZnO varistor 67,
101–110

low-voltage ZnO varistor 307–327

m

metastable polymorphs 71

microcontact method 126, 129, 244

microstructural engineering 80

microstructural nonuniformity 162,
174–175, 199, 213–216

microstructure 6

grain boundary 7

intergranular layer 7

pyrochlore phase 7

spinel 7

migration ions 237, 249–257

for degradation 257

migration of oxygen defects 257

Mott–Schottky plot 420

multiple-grain junction 69, 72, 160,
293, 426

n

nanofillers in ZnO varistor 320–321

nanosized powders 309

nonmonotonic degradation 250, 261,
262

nonohmic variable resistors 1

nonuniformity of barrier voltages
129–131

o

oxygen, role of 78–79

p

parallel path conduction 100

parameters of ZnO varistors 9
chargeability 8
discharge capacity 8
energy handling capability 9
leakage current 8
nonlinear voltage–current
characteristics 7

residual voltage 8

residual voltage ratio 8

varistor voltage 8
voltage gradient 7

point defect 38, 253, 254, 366

Polymeric line surge arrester 16, 17
series gap 16

pore 7, 39, 69, 78, 164, 183, 296,
320

distribution 77

dragging mechanism 76
effect of 76–78
and spinels 164–165, 183

- power loss characteristics of ZnO
 varistors 210
 praseodymium 281–289
 Pr-based ZnO varistor 270, 281, 282
 pulse degradation 235, 245–247,
 262–265, 268
 pulse electroacoustic (PEA) 245
 pulse-induced fracture 173
 puncture failures
 mechanisms 197–203
 simulation 204–209
- r**
 recrystallization 198, 380
 relaxation process 31, 55–57,
 358–361, 419
 relaxation time 54, 59, 61, 358
 residual voltage ratio 8, 101–110, 149,
 179, 180, 183, 184, 186–188, 416,
 432–434
- s**
 scanning probe microscopy based
 techniques 125, 137–139
 scanning transmission electron
 micrograph (STEM) 69
 shallow donor 39, 41, 46, 78, 79, 89, 95,
 253, 414, 420, 422
 SiC varistor 3, 10, 13, 14, 341
 sintering of ZnO varistors 5–6, 41, 272
 liquid-phase sintering 6
 spinel-forming dopants 86, 96
 surge protection devices 9, 12, 51, 193,
 281, 298
 synthesis of nanocrystalline ZnO
 varistor powders 309
 combustion synthesis 311
 gas-phase processing methods
 309–311
 sol-gel methods 311–315
 solution-coating method 315–319
- t**
 tank-type surge arrester 15
 thermal balance 210, 211
 thermal breakdown 194
- thermal characteristics
 heat transfer 171
 simulation model for 170–173
 thermal conduction analysis 171–173
 thermal runaway 9, 11, 154, 193–195,
 199, 209–213, 217, 223, 224, 227,
 235, 236, 288, 289, 429
 thermal stimulating current (TSC) 241
 thermal stress 149, 171, 173, 194, 201,
 202, 208, 209, 214–217, 221–225,
 230, 235, 261, 288, 430
 thermionic emission conduction model
 50
 thermograph method 197
 tin oxide varistor
 admittance spectroscopy analysis
 417–420
 atomic defect model 415–417
 capacitance–voltage analysis
 420–421
 degradation 431
 effect of thermal treatment 421–423
 electrical performance 410–414
 formation of grain boundary potential
 barrier 414–415
 mechanism 414–423
 preparation 407–410
 thermal performances 431
 topographic information for
 degradation analysis 247–248
 tungsten trioxide (WO_3) 441, 449
- v**
 valence band 36, 38, 39, 41, 48, 158,
 250, 260
 vanadium-doped ZnO varistor 290
 doping effects 290–291
 electrical characteristics 291–292
 microstructural characteristics
 292–294
 vanadium oxide 289–291, 294
 volatilization of bismuth oxide 72–74
 Voronoi network 11, 51, 150, 164–165,
 172, 174–176, 181, 206, 207,
 213
 disorder degree 162

W

WO₃-based varistor 17, 456
doping effects 452–456
electrical performance 446–448
electrical stability 448–449
mechanism model 449–451
preparation 444–446
wurtzite structure 3, 91, 162

X

X-ray computed tomography
(XCT) 77

Z

zinc interstitial 75, 237, 271
zinc interstitial defect 83, 252,
268
ZnO–BaO varistor 295–298
ZnO–glass varistor 298–300
ZnO microspherical varistors 19
ZnO microvaristor 1, 18–21
ZnO varistors 1–3
applications of 12–17
barium system 295–298
breakdown mechanism 193–230

conduction mechanism of 45–51
dielectric characteristics of 51–62
degradation mechanism of 257–265
electrical degradation 235–272
electrical properties of 137–142
energy absorption capability
193–230
energy band structure 39–45
fabrication of 3–6
failures factors 213–218
high voltage gradient 98–101
history of 9–12
impulse failure modes of 194–197
low residual voltage 101–110
microstructure 6–7, 68–71
migration ions for 249–257
nanocrystalline synthesis 309–319
nanofillers 320–321
parameters of 7–9
power loss of 210
praseodymium 281–289
tuning electrical characteristics of
67–110
vanadium system 289–294
Zn vacancy 45

