

Index

- absolute pressure sensors 300, 309 ff
- absorber layers 488
- absorption 335 ff, 352 f
- AC modulation 530
- accelerometers 140 ff, 160–184
- accuracy
 - analog frontends 526
 - digital-to-analog converters (DACs) 550
 - filters 541
 - fingerprint images 425
 - operational transconductance amplifiers (OTAs) 569
- acetic acid etching 18, 302
- acidity sensors 364
- acoustic devices 193–224
- action potentials 463
- add-on layers 43 ff
- adsorption 335 ff
- Agilent 0.5 μm process 218
- aging 150
- air damping 170
- air discharge 412 ff
- alkaline phosphatase 455
- Allen variance 570
- ALP2LV/MV 72
- aluminum
 - bulk material 97 ff
 - Seebeck coefficients 485
 - thin films 83
- aluminum bridge 233
- aluminum capacitors 247
- aluminum metallization 3 ff, 14 ff, 32 f, 43, 182
 - elastic properties 126
- aluminum-silicon alloy layers 464
- ammonium hydroxide compound etching 20
- amorphous silicon 492
- amperometric sensors 359 ff, 449
- amplifiers 196, 217 f, 227
 - chemical sensors 347, 359
 - pressure sensors 259
 - system integration 513 ff
- analog capacitors 519
- analog devices (ADI) SOI MEMS 146, 183
- analog filters 513 ff, 535 ff
- analog frontend 513, 521 ff
- analog resistors 519
- analog-to-digital converters (ADCs) 513 ff, 523, 544 ff
- analysis quality 451
- anemometers 502 f
- anisotropic etching 8 f, 18 ff, 241
- anisotropy factor 287
- annealing 34, 43
- anodically bonded glass encapsulation 309 ff
- anti-aliasing filters 542
- anti-fraud techniques 440
- antiresonant reflecting optical waveguide (ARROW) 355
- application-oriented tests 563
- architectures *see*: block diagrams
- array
 - four-cantilever 377 ff
 - phased 221
- artificial fingerprints 441
- ASIC technology 517
- Atmel's AT77C103A FingerChip 403
- atmospheric pressure vapor deposition (APCVD) 5
- atomic force microscopy (AFM) 345
- Austria Micro System (AMS) process 215 f
- authentication 397
- auto-zero techniques 522, 534
- automatic fingerprint identification system (AFIS) 395 f, 417 f
- automatic generation of test pattern 563
- Avogadro's number 75
- axisymmetric diaphragms 301
- axisymmetric plates 274
- back annotation 565
- back-end metallization 10
- bandgap voltages 555 ff
- bandpass filters 535 ff
- bandwidth
 - analog frontends 523
 - filters 541
 - inertial sensors 179
 - operational transconductance amplifiers (OTAs) 569
 - switched capacitor amplifier 513, 535
- base emitter voltage 555 ff

- basicity sensors 364
- batch fabrication, biochemical sensors 449 f
- beam test structures 115 ff
- bending stresses, thin plates 274, 277
- benzocyclobutene (BCB) switch 233
- BEOL accelerometer 169 ff
- Bessel filter 153
- bias stability 144
- BiCMOS technology 2 ff, 72, 234
 - interface circuitry 518, 521
- bifurcation 416, 422
- BioAPI 436
- biochemical sensing systems 378 ff, 447–478
- biocompatible materials 14, 464
- biological entities 338
- biometric capacitive fingerprint sensor systems 391–446
- biometric engine level error rate 426
- biosensor arrays 454 ff
- biquad filters 540 ff
- blank reticle 27
- blister test 114 f
- block diagrams
 - ADI XL150 gyroscope 158
 - ADI XL50 148
 - ADI XL76 152
 - calorimetric sensor 503 f, 570
 - chopper amplifier 535
 - constant current generator 558
 - DEP chip 461
 - dielectrophoretic cell 460
 - digital-to-analog converters 549
 - DMOS transistor 519
 - DNA hybridization 455
 - double check structure 493
 - dual slope ACD 545
 - earphone 210
 - fingerprint sensor 405
 - gas detection system 567
 - gas flow meter 505
 - hotplates 369
 - interdigitated capacitive sensor 373
 - i-Stat system 450
 - microelectrode pixel 467
 - microphone 199
 - neural probe 471
 - operational transconductance amplifiers (OTAs) 569
 - oscillator feedback circuitry 347
 - pixel recording 468
 - pressure sensors 304, 312, 316
 - RF switch 225 ff, 232
 - Sallen-Key filter 540
 - Siemens accelerometer 168
 - Sigma-Delta modulator 373, 547
 - switched capacitor amplifier 531
 - thermal RMS converter 500
 - thermocouple 484
 - transceiver 229
 - Wheatstone bridge 529
- blood gas analysis 454
- Boltzmann constant 91, 143, 198, 486
- boron etch-stop 303 ff
- borophosphosilicate glass (BPSG) 38
- boundary elements simulation (BEM) 28
- breakage test 415
- breakdown, dielectric 453
- bridge bending 100, 122 f
- brittle layers 119
- Brownian noise 143 ff, 152 ff, 170 f, 197 f
- Bubnov–Galerkin variation 273, 276
- buckling 107, 111, 115
 - acoustic devices 202 ff
- buffered oxide etching (BOE) 8
- building blocks 522, 539 ff, 559
- bulge test 100 f
- bulk material properties 83 ff, 267
- bulk micromachining 18 ff, 29, 42
 - pressure sensors 257, 300, 305 ff
- bulk silicon 368
 - accelerometer 181
 - inertial sensors 180 ff
- bus-enabled interfaces 572
- CAE (1.3 μm) 72
- cage compounds 338
- calibration
 - analog frontends 522
 - building blocks 554 ff
 - interface circuitry 521
 - pressure sensors 257, 259
- calixarenes 338
- calorimetric sensors 353, 502 f
 - gas detection system 570 f
 - switched capacitor amplifier 535
- CAN bus 554
- cantilever based sensors
- cantilevers 13, 19, 56, 90 f
 - biochemical sensors 472 ff
 - chemical sensors 345 ff, 377 ff
 - gas detection system 570 f
- capacitive acoustic devices 196
- capacitive bridges 143, 161, 171
- capacitive chemical sensors 15, 359, 568 f
- capacitive detection mode 151

- capacitive fingerprint sensor systems 391–446
- capacitive forces 73 f
- capacitive MEMS ultrasonic transducers (cMUTs) 217
- capacitive microphones 195
- capacitive pressure sensors 257, 301–314
- capacitive read-out 513
- capacitive sensors 527 f
- capacitive transducers 401 f
- capacitor inductor combination 210
- capacitor layers 80
- capacitors 142, 229 ff, 235
 - chemical sensors 372
 - interface circuitry 519
 - tunable 227
- capture conditions, fingerprint images 424
- carbon black-loaded polymers 367
- Carnegie Mellon series 169 ff, 186 f
- cartridges 450
- catalytic thermal sensors 349 ff
- cavities 300
- CBT (2 μm) 72
- cell-based assays 457 ff
- cell-electrolyte electrode interfaces 463
- cell handling 458 f, 464
- cell level ACD 545
- cell trapping, dielectrophoretic 458
- cellular activity 463
- charge carrier transport 74 f
- charge-sensitive amplifier (CSA) 538
- charge transfer 317, 340 ff
- chemical mechanical polishing (CMP) 11
- chemical mechanical rubbing test 414
- chemical reactions 340 ff
- chemical robustness 416 f
- chemical sensors 335–390, 568 f
- chemical vapor deposition (CVD) 3, 44, 202, 210, 220
- chemiluminescence 353, 457
- chemisorption 337
- chemocapacitors 372 f, 568
- chemoresistors 365
- chemotransistors 361 ff
- chopper amplifier 522, 534 f
- circuit integration 27 ff, 513–577
- circular diaphragms 293 f, 301
- circular plates 277 ff
- clamped clamped beams 115
- Clark cell 361
- Clausius–Mossotti factor 459
- clock period
 - filters 542
 - pressure sensors 319
 - switched capacitor amplifier 533
- closed couplers, acoustics 194
- closed/open loop architectures 150
- coatings 336, 401
- comb fingers 157 f, 162, 170, 237
- common biometric exchange file format (CBEFF) 437
- common mode feed back (CMFB) 317
- comparator 570
- compliance
 - acoustic devices 198
 - coefficients 73 f, 76
 - inertial sensors 147 ff
 - pressure sensors 265 ff
 - sensors 261, 266
- component-based integration 437 ff
- compressibility 262, 267
- computer-aided engineering (CAE) 6
- condensation heat 352
- condenser microphones 195
- conducting polymers 367
- conducting thermocouple materials 85
- conducting thin films 69
- conductivity
 - electrical 82 f
 - thermal 69, 73, 86 ff, 96 ff, 323
- conductometric sensors 358, 365 ff
- constant-current sources 558
- constant-flow modes 502
- contact opening reticle 27
- contact area shifts 424
- contact electrode 454
- contact oxides 12, 96
- contact resistance 80
- contamination 453
- continuous-time detection 530
- control layer, fingerprint sensors 435
- controllers, gas detection system 572 f
- conversion radio architectures 227
- converters
 - analog-to-digital (ADCs) 315
 - digital-to-analog 513 ff, 523, 549 ff
 - thermal 480, 499 ff
- cooled photon detectors 482
- coplanar waveguides (CWG) 231
- copper
 - bulk material 97 ff
 - metallization 71, 126
 - Seebeck coefficients 485
 - spiral inductor 242
 - thin films 83, 87
- core-cladding interface 355
- Coriolis acceleration 144 ff, 156 ff, 164 f

- correlated double sampling (CDS)
 - 317, 531 f
- Cottrell equation 359
- Cr–Al–Cr spacer 180
- cracking 114
- critical pressure 107
- cross sensitivity 525
- crosstalk 570
- crowding effects 240
- crown ethers 338
- cryptosmartcards 441
- current mode 151
- current references 554 ff, 558 ff
- cut-frame structures 119
- cyclodextrins 338
- CYE (0.8 μm) 72
- cytometers 458

- Daimler-Benz accelerometer 181
- damascene copper process 234
- damping 170, 182
 - acoustic devices 198
 - coefficients 140, 143
- DARPA 165, 183
- data interfaces 554 ff
- databases, fingerprint sensors 429 f, 435
- decimation filter 513, 552
- deep reactive ion etching (DRIE)
 - 21, 35, 53, 201 f
- defects 24
- defence evaluation 167
- deflection 103 ff
 - acoustic devices 211
 - diaphragms 257, 301 ff
- deformation functions 105
- delay time 570
- Delta–Sigma converters
 - 313, 319, 321 ff, 513
- demagnifying projection 399 f
- demodulation 225, 520
- demultiplexer 379
- deployment 438 ff
- deposition techniques 4 ff, 25, 301
- design guidelines
 - accelerometers 141 ff
 - biochemical sensors 464 ff
 - gas detection system 566 f
 - system integration 561 f
- design-rule-check (DRC) 26 ff, 564, 567 ff
- desorption 352
- device-under-test (DUT) 205, 527, 562
- Dialog Semiconductor accelerometer 181
- diamond shape structures 115
- diaphragms 106 f
 - acoustic devices 195
 - pressure sensors 257
- dielectric constant 73 f
 - chemical sensors 374
 - transducers 401
- dielectric layers 5, 53, 126 f, 368
 - biochemical sensors 452
 - fingerprint sensors 407
- dielectric thin films 69
- dielectrometers 372 f
- dielectrophoresis (DEP) 458 ff
- differential nonlinearity (DNL) 523
- differential circuit design 526
- differential difference amplifier (DDA) 347, 528, 570
- differential switched capacitor Sigma–Delta modulator 548
- diffraction effects 197
- diffusion barrier metallization 71
- diffusion coefficients 359
- diffusion effects 370
- diffusion layers 80, 283 ff
- diffusivity 73 f
- digital circuitry 517
- digital controllers, gas detection system 573 f
- digital filters 551 ff
- digital light processing (DLP) 46
- digital micromirror device (DMD) 22, 46
- digital output 521
- digital serial protocol controller 452
- digital signal processor (DSP) 50
- digital sound reconstruction (DSR) 193, 214 ff
- digital-to-analog converters (DACs)
 - 513 ff, 523, 549 ff
- dilatation 268
- diode array pixels 497
- diodes, varactor 249
- dirt problems, fingerprint sensors 440
- discrete time system 542
- distance transducers 401
- distortions
 - analog frontends 524
 - filters 551
 - fingerprint images 424
- DNA analysis 14
- doping 4, 24 f
 - piezoresistivity 281 ff
 - pressure sensors 303
- double polysilicon–double metal (DPDM) 184
- drain/source implantation 12, 17, 40

- drift 526
- dry etching 18 ff
- dual-band transceiver 229, 248
- dual-slope analog-to-digital converters 544
- duality principle 353
- Dulong–Petit law 75
- dynamic mode
 - chemical sensors 345
 - digital-to-analog converters (DACs) 549
- dynamic properties, analog frontend 523 f
- dynamic range, filters 551
- dynamic signature verification (DSV) 396

- earphone construction 208 ff
- ECPD10 process 72
- elastic moduli 69 ff, 73 f, 126 f
 - silicon 266
- elastic solids 261
- elastic stiffness 73 ff, 76
- elastoresistivity tensor 280
- electret microphones 195
- electrical conductivity 82 f
- electrical–electrical transduction 74 ff
- electrical material data 80 ff
- electrical resistivity 69, 73 ff, 80, 485
- electrical–thermal transduction 74 ff
- electrically programmable read-only memory (EPROM) 378 f
- electrochemical reactions 340 ff
- electrochemical read-out 454 f
- electrochemical sensors 342, 358 ff
- electrode fabrication 454, 464, 470 ff
- electrogenic cells 463 ff
- electromagnetic resonators 243 ff
- electromagnetic waves 353
- electromechanical drives 244
- electromechanical interfaces 407 f
- electron–hole pairs 353, 481
- electronic design automation (EDA) 27
- electronic noise 551
- electrophysiological assays 463
- electroplated gold lines 490
- electroplating 5 ff, 42, 47
- electrostatic deflection 100
- electrostatic/thermal actuation 117 f, 235
- electrothermomechanical material data 73 ff
- encoding 394 f, 403 ff
- endothermic reactions 348
- energy minimization method 113
- engine level error rate 426
- enrichment factor 339

- enzyme label 455
- epipolysilicon 128, 160 f
- equal error rate 427
- equivalent input noise 197
- error rates
 - analog frontends 526 f
 - filters 551
 - fingerprint sensors 426 ff, 432
 - piezoresistivity 284
- ESD air discharge 412 ff
- etch-stop techniques 20, 42, 50
 - electrochemical (ECE) 20, 51, 304 ff
 - gate polysilicon 167 f
 - microbolometers 495
 - pressure sensors 259, 300 ff
- etching 4, 18 ff, 38 ff, 241
 - chemical sensors 346, 372
 - interface circuitry 516
- ethylcellulose (EC) 380
- ethylenediamine-pyrocatechol (EDP)
 - etching 20, 53, 84, 241
 - chemical sensors 350 ff
 - pressure sensors 303
- Euler buckling 115
- evanescent waves 354
- excitation signal 570
- exothermic reactions 348
- expansion coefficients 273
 - see also*: thermal expansion coefficient
- externally polarized microphones 195

- fabrication 1–68
 - biochemical sensors 452, 464 ff
 - infrared detectors 481
 - interface circuitry 515 ff
 - microphones 197 f, 201 f
 - SOI diode microbolometer 498
 - speakers 209
 - system integration 515 ff
 - ultrasonic sensors 218 f
- Fabry–Perot devices 354 ff
- face recognition 395
- failure statistics 562
- failure-to-capture (FTC) rate 428
- failure-to-enrol (FTE) rate 428
- false acceptance rate (FAR) 397, 426
- false rejection rate (FRR) 397, 426
- faradaic currents 359
- Faraday constant 340
- feature extraction 416 ff, 424
- feedback
 - chemical sensors 345
 - fingerprint sensors 418, 439

- Fermi–Dirac integrals 281 f
- Fermi levels 282, 485
- ferromagnetic films 16
- field-effect transistors (FETs)
 - 122, 230, 361, 463
- field-oxide layers 12, 96
- field tests, fingerprint sensors 411
- figures-of-merit, thermocouples 486
- film bulk acoustic resonator (FBAR) 246
- filters 244 ff
 - building blocks 539 ff
 - digital 551 ff
 - fingerprint sensors 421
 - interface circuitry 520 ff
 - system integration 513 ff
- fingerprint sensor systems 16, 391–446
- finite element modeling (FEM) 27
 - ANSYS 567
 - gas detection system 567
 - material properties 79 f
- finite impulse response (FIR) 313, 552
- flexural plate wave devices (FPWs) 343
- flexural rigidity 103, 271
- flicker noise 163
- flow cytometric analysis 454, 458
- flow diagram, IC fabrication 4
- flow sensors, thermal 480 ff
- fluorescence 353
- fluorescence-activated cell sorting (FACS) 458
- focal plane arrays (FPA) 481 ff
- folded cascode operational transconductance amplifiers (OTAs) 568
- force balance equation 140
- force feedback 147, 150 f
- fork-type rate sensors 157 f, 164
- four-terminal transverse voltage strain gauge (X-ducer) 260, 297
- fractional resistances 294 ff
- fracture mechanical properties, silicon 123
- fracture strength/toughness
 - 69 ff, 73 f, 76, 120
- frame-stabilized structures 119
- fraud, fingerprint sensors 440
- frequency conversion 225
- frequency response 212, 216
- frequency shift 336, 343
- frequency sweep 570
- Fresnel lenses 489
- friction 73
- front-side processing, wafers 301
- fully differential analog frontend 526 f
- fused silica 452
- Gabor filter 421
- gain stability 144
- gallium arsenide 9
 - chemical sensors 353
 - RF CMOS MEMS 226
- Galvanielectrics 463
- gas detection system 379 ff, 566 ff
- gas flow meters 505
- gate capacitance 144
- gates 3, 10
 - layers 80
 - materials 6 f, 167
 - metal electrode 362
 - polysilicon 86, 167
- gauge factors
 - capacitive 300
 - polysilicon films 284 f
- gauge sections 119
- Gaussian distribution
 - piezoresistivity 283
 - system integration 559
- Gaussian plane wave filters 421
- geometric effects 109, 353
- geometric rule violations 564
- geometry–material property relations 79 f
- germanium 45, 187
- glass encapsulation 309 ff
- glucose 449
 - oxidase 454
- GmC filters 537, 543 ff
 - see also*: transconductance
- gold
 - black 488
 - electrodes 465
 - electroplating 181
 - layers 6
 - Seebeck coefficients 485
- gold–tin solder frame 307
- graph matching 425
- gravimetric mass detection 217
- Gray counter 379
- gray scale dynamics 408, 425
- Greek cross device 81 ff, 92 ff
- Gummel number 555
- gyroscopes 144 ff
- half-bridge topology 170
- Hall plates 15, 37
- hardware description language (HDL) 27
- harmonic distortion 524
- heat capacity 69, 73, 95 ff
- heat loss 85, 502
- heat transfer 75 ff

- heating elements 502
- Hermann–Schönflies notation 265
- high-g prototype 183
- high-impedance amplifiers 196
- high-temperature capacitive pressure sensors 323 ff
- high-temperature chemoresistors 367
- high-temperature polysilicon 167
- high-voltage devices 519
- Hooke's law 261–269
- hot junctions 350
- hotplates 368
 - see also*: microhotplates
- housing, acoustic devices 211
- human serum albumin (HSA) 355
- hybrid systems 454, 515
- hydrazine water etching 49
- hydrocarbons 337, 344, 352
- hydrofluoric acid (HF) etching 8, 18 f
 - pressure sensors 260, 302
- hydrogen monoxide 337
- hydrogen peroxide 360

- I2C bus interface 571
- identification 391, 416 ff, 439 ff
- identifier on card (IoC) 441
- IEEE1451.1-4 interfaces 554
- image capture, fingerprint sensors 408–419
- imaging arrays, thermopiles 489
- immobilization 464
- impedance, acoustic devices 203
- impedance spectroscopy 461
- implantation techniques 12
- impurity concentration, piezoresistors 298
- in vivo* electrophysical measurements 470 ff
- indentation 121 f
- indium phosphide 353
- indium tin oxide (ITO) 460, 465
- indiumantimonide 481
- inductors 229 ff, 238 ff, 250
- inertial sensors 137–192, 204
- infinite impulse response (IIR) 313
- information check, fingerprint sensors 420
- infrared detectors, uncooled 480, 483 ff
- inkjet printing 455
- input common mode feedback (ICMFB) amplifier 163
- input noise 197 f
- input signal domain 73
- insertion loss 225
- instrumentation amplifier 513 ff, 536

- integral nonlinearity (INL) 523
- integrated circuits (ICs) 4, 79 ff, 341
- integrated electronics 450 ff
- integrated inertial sensors 137–192
- integrated optics 354 ff
- interconnects 3, 38, 452
- interface circuitry
 - gas detection system 567 ff
 - system integration 513 ff
- interfaces
 - electrogenic cells 463 ff
 - electronics 566
 - fingerprint sensors 407 ff, 435
- interfacial cracking 114
- interferences, analog frontends 527
- interferometers 354
- intermediate CMOS integration 257
- intermetal insulators 71
- intermetal oxides 12, 96
- intermodulation filters 551
- internal reflection transducer 400
- intra CMOS micromachining 29, 37 ff
 - interface circuitry 515 f
 - pressure sensors 314 ff
- inversion layers 78, 129
- ion implantation 5
- ion-selective field-effect transistor (ISFET) 362, 378, 464
- ionic compounds 338
- iris recognition 394 f
- irradiation 353
- islands, silicon layers 368
- isolated transistors 519
- isopropyl alcohol (IPA) 303
- isotropic etching 8 f, 18 f, 21, 302
- isotropic materials, Hooke's law 269 ff
- i-Stat Portable Clinical Analyzer (PCA) 449
- ITRS road map 517

- Johnson noise 198 ff, 206 f, 486
- junctions 9 ff, 37 ff, 180 f, 234
 - chemical sensors 350
 - pressure sensors 260, 283, 322

- K band frequencies 243
- Kanda effect 281, 299
- Kelvin relation 74 f
- kernel layer, fingerprint sensors 435
- Kirchoff condition 102
- KPY60 high pressure sensor 298
- Krautkramer transducer 220

- Lamé's constants 269
- Langmuir-Blodgett films 338
- Laplacian operator 272, 278
- laser trimming 149
- lateral accelerometers 169 ff
- lattice defects 370
- layers
 - acoustic devices 196 ff
 - add-on 43 ff
 - biochemical sensors 453, 464
 - brittle 119
 - chemical sensors 336 ff, 352
 - dielectric 368
 - fabrication 3 ff, 25
 - fingerprint sensors 407
 - interface circuitry 516, 520
 - inversion 78
 - material characterization 80 ff, 89 ff, 96, 234 f
 - piezoresistivity 129, 283 ff
 - polysilicon 167
 - post CMOS micromachining 43 ff
 - pressure sensors 259 ff, 300, 305
 - system integration 565
 - thermocouples 488
 - see also*: passivation-, sacrificial-, oxide-layers
- layout-versus-schematic (LVS) verification 26, 565 ff
- lead zirconate titanate (PZT) transducers 219 f
- least significant bit (LSB) 522, 545
- lift-off technique 7, 15
- LIGA 178 f
- light-emitting diode (LED) 357
- limit-of-detection (LOD) 525
- linearity
 - analog frontends 523
 - pressure sensors 276
 - system integration 513
- lipids 338
- liquid flow 502
- lithographic structuring 27, 464
- living cells 463
- load deflection models 103 ff
- local oxidation of silicon (LOCOS) 9
- long diaphragms 109 f
- long-term stability 72
 - analog frontends 526
- long-wave infrared thermal sensors 481
- Lorentz forces 346
- loudspeaker 205
- low-doped drain (LDD) technology 3, 10
- low-noise amplifiers (LNA) 227, 536
- low-pressure CVD (LPCVD) 5, 25, 38
 - chemical sensors 350, 355
- low-pressure sensors 298
- low-temperature chemoresistors 366
- low-temperature oxide (LTO)–spin on glass–LTO sandwich (LTO–SOG–LTO) 47, 180
- lower explosive limit (LEL) 336, 349
- M test (mechanical) 118
- Mach–Zehnder interferometers 354
- magnetic actuation 346
- magnetic modes 354
- MAMOS transistors 182
- manifold air pressure (MAP) sensing 260 f
- masking 6, 18, 27
 - interface circuitry 518
 - layers 564
 - materials 18
- mass-sensitive resonant cantilever 570 f
- mass-spring damper system 140
- matcher-on-card (MoC) 441
- matching, fingerprint sensors 394 f, 419 f, 424
- material characterization 11 ff, 69–136, 338, 452
- Mauguin notation 265
- measurement techniques 69 ff, 79
- mechanical–electrical transduction 77
- mechanical energy domain 69
- mechanical material data 123 ff
- mechanical–mechanical transduction 76
- mechanical properties 100 ff, 125
- mechanical sensitivity 140
- mechanical shock resistance 414 ff
- mechanical switch 420
- medium temperature deposition 25
- membrane-based test structures 89 f
- membranes 105 f
- mercury cadmium telluride 481
- metal bulk materials 97 ff
- metal dielectric structures 172
- metal–electrolyte interface 464
- metal films 492, 296
- metal inertial sensors 176 ff
- metal layers 6 ff, 53, 169, 235
 - acoustic devices 196
 - biochemical sensors 453
 - interface circuitry 520
 - system integration 565
- metal oxide semiconductor field effect transistor (MOSFET) 3, 361

- metal oxide semiconductor implementation
 - system (MOSIS) 215 f, 218
- metal oxide–polymer diaphragms 196
- metal-plated accelerometers 177 ff
- metal silicon contacts 44
- metal thin films 83
- metallic sensor materials 338
- metallization
 - elastic properties 124 ff
 - fabrication 2–16, 32–40
 - interface circuitry 516
 - material properties 71 ff, 80 ff
- metrics, inertial sensors 140 f
- microbolometers 479–512
- microcontact printing 7, 455
- microelectrode arrays (MAs) 463
- microfabriation 1–68
- micro-g accelerometers 139 f
- microhotplates 367 ff
- micromachining
 - cantilevers 345 ff
 - pressure sensors 261 ff
 - switches 229 ff
- micromechanical structuring 79
- microphones 193 ff, 201 ff
- microsensors 335
- microspectrometers 356 ff
- microstripline filters 243
- microtensile test 100, 119 f
- mid-wave infrared thermal sensors 481
- miniaturization 195
 - biochemical sensors 448 ff
 - fingerprint sensors 394, 409
 - RF CMOS MEMS 225
- minutiae encoding 403 f, 417 f, 422
- mixed-signal processing 315 ff, 245
- mobility 144
 - data interfaces 555
 - RF CMOS MEMS 225
- Modelsim 567
- modular integrated CMOS and micro-structures (MICS) 161
- modular monolithic microelectro-mechanical systems (M²EMS) 33
- modulation, RF CMOS MEMS 225
 - see also: Delta-Sigma*
- moisture, fingerprint sensors 412
- molding 7
- molecular crystals 338
- monolithic integration
 - capacitive sensors 530
 - inertial sensors 137–192
 - pressure sensors 259, 299
 - RF CMOS MEMS 226 ff
- Monte Carlo simulations 559
- Moore's law 517
- multiband transceivers 228 ff
- multibit quantizers 547
- multichip solutions 372
- multilevel metallization 12
- multimaster interfaces 572
- multiparameter biochemical microsensor
 - systems 378 ff
- multiple component processing 194
- multiplexers
 - biochemical sensors 451, 466
 - chemical sensors 379
 - system integration 545
- multisensor systems 376 ff
- multitransducer gas sensor systems 379 ff
- n-wells 9, 12, 357
- nanoindentation 100, 121 f
- Nasicon 338
- near the edge (E) sensor 219
- Nernst equation 340, 361
- neural activity 14
- neural probe 471
- neurite guidance 464
- nickel 338
 - bulk material 97 ff
 - ring gyroscope 47
 - Seebeck coefficients 485
 - structure materials 180
 - thin films 83
- nitric acid etching 18, 302
- nitride layers 38
- noble metals 338
 - coatings 369
 - doping 372
 - electrodes 465
 - layers 6
- noise
 - acoustic devices 193 ff, 197 ff
 - analog frontends 525 ff
 - filters 551
 - inertial sensors 143 ff, 152 ff, 163 ff, 170
 - power spectrum 207
 - resonant devices 570
 - RF CMOS MEMS 225
 - switched capacitor amplifier 532, 537
 - see also: signal-to-noise ratio*
- noise-equivalent temperature difference (NETD) 479–512
- normal stresses 262, 280 f
- normalization, fingerprint images 422
- Nyquist frequency 315, 546

- offset
 - analog frontends 513, 522
 - switched capacitor amplifier 535
- ohmic conductors 291
- ohmic switches 231
- on-chip amplifier 217
- on-chip multiplexer 451
- on-chip signal processing 195, 340
- Onsager thermodynamics 75
- OpAmp-based interface circuits
 - 519 f, 530 f, 548
- operating temperatures, chemical sensors 368
- operation modes, acoustic devices 195
- operational amplifiers 359
- operational transconductance amplifiers (OTAs) 310, 543 f, 568
- optical interrogation 461
- optical path 399
- optical read-out 457 f
- optical sensors 337, 342, 353 ff
- optical transducer 399 ff
- orientation dependence, piezoresistivity 288
- oscillating mechanical surface deformation 343
- oscillators
 - circuits 164
 - frequencies 228
 - gas detection system 571 f
 - resonant cantilevers 570
- output, interface circuitry 520
- output signal domain 73
- oxide nitride layer sandwich 89
- oxide semiconductor field effect transistor (OSFET) 463, 466
- oxygen measurements 360
- oxygen precipitation 24
- oxygen vacancies 370

- p-wells 9, 12
- packaging 231
 - acoustic devices 197
 - biochemical sensors 453, 473 ff
 - inertial sensors 150
 - interface circuitry 521
 - pressure sensors 300
 - RF CMOS MEMS 226
 - system integration 560
- palladium 338, 362
 - see also*: noble metals
- parallel-plate capacitors 142, 162
- parameter deviation 559
- parameter sensitivity 513, 559 ff
- parametric adjustments, inertial sensors 149 f
- parasitic capacitance 240
 - inertial sensors 144, 152 f, 172
 - interface circuitry 517
 - pyroelectric elements 539
 - system integration 565
- parasitic resistance 80
- partition coefficient 337 ff, 343, 348
- passivation 5, 12 f
 - thermal properties 96, 99
- passivation layers 25, 44
 - biochemical sensors 453, 464
 - fingerprint sensors 407
- passive devices 516
- passive test structures 115 f
- patterning 6, 25, 455
- Pauw test structure 80, 92 f
- pellistors 349 ff
- Peltier coefficient 73 f
- pencil-drop test 415
- pendulous accelerometer 140
- performance, biometric system 425 ff
- permittivity factor 459
- person's verification 391, 416 ff, 439 ff
- personal identification number (PIN) 393, 398 f
 - diodes 230 f
- personal rights protection 396
- pH sensors 364, 454
- phantom powered microphones 196
- phased arrays 221 f
- phosphate buffered saline (PBS) 360
- phospholipids 338
- phosphorescence 353
- phosphorus implantation 38
- phosphosilicate glass (PSG) 10, 44
- photolithography 4 ff, 153
- photons 353, 482
- photopatterned silicone gasket 454
- photoresists 39, 167
 - layers 6, 234
 - plating mold 47
- photostructurable layers 7
- phototransistors 357
- phthalocyanines 338
- physical design verification 513, 564
- physical properties 69 ff
- physical vapor deposition (PVD) 5, 44
- physisorption 337, 566
- Pierce oscillator circuits 164
- piezoelectric elements 534 ff, 539
- piezoelectric materials 196

- piezoresistive accelerometers 169, 180 f
- piezoresistive coefficients 69 ff, 73 ff, 102, 122 ff, 129
- piezoresistive pressure sensors 49, 257 ff, 278 ff
- piezoresistors
 - analog frontends 527
 - diaphragms 297 ff
- Pirani pressure gauges 56, 261, 323 f
- pixel arrays, fingerprint sensors 406 f
- pixel-by-pixel compensation 457
- plane stress approximation 270 ff
- plane wave filters 421
- plasma-enhanced CVD (PECVD) 3, 71
- plastic properties 119 ff
- plating mold 47
- platinum 6, 14, 338, 349
 - bulk material 97
 - electrodes 454, 465
 - Seebeck coefficients 485
 - thin films 83
- plug-up process sequences 36
- pn-junctions 180, 234
 - fabrication 11 ff, 37 ff, 50 ff
 - pressure sensors 260, 283, 322
- pnp-transistors 556
- pointer structures 115
- Poisson ratio 69 ff, 73 ff, 101, 110, 119, 126 f
 - pressure sensors 267, 272, 284
- polarization 354
- polyether urethane (PEUT) 375 ff, 380
- polyaniline 367
- polybenzoxazole 456
- polycrystalline silicon *see*: polysilicon
- polydimethylsiloxane (PDMS) 7, 219, 352, 380
- polygermanium 45, 187
- polyimides 196, 465
- polymer coatings 336, 453
- polymer layers 6 f, 566
- polymers 338
 - conducting 367
- polypyrroles 367, 454
- polysilicon 3 ff, 10, 32, 43, 53
 - accelerometer 167
 - acoustic devices 196
 - chemical sensors 349
 - elastic properties 126
 - inertial sensors 146 ff
 - layers 85 ff, 167 ff, 305
 - material properties 83
 - piezoresistors 284 f, 305 ff
 - pressure sensors 259, 305, 312 f
 - refill 37
 - residual stress 124
 - resistors 502
 - Seebeck coefficients 485
 - system integration 559, 565
 - tensile properties 128
 - thermal properties 97
- polysilicon-germanium (polySi-Ge) materials 187, 492
- polysilicon-polysilicon interconnects 44
- polythiophene 367
- polyurethanes 338, 347, 375 ff, 380
- post-CMOS micromachining 43 ff
 - chemical sensors 344, 372
 - interface circuitry 515 f
 - passivation layers 453
 - pressure sensors 257
- potassium hydroxide (KOH) etching 5, 19 ff, 24 f, 41, 50 f
 - chemical sensors 346, 350 ff, 372
 - inductors 241
 - inertial sensors 180
 - pressure sensors 260, 303
- potentiometric sensors 358, 361 ff
- power amplifier 228
- power consumption 151
 - interface circuitry 517
 - RF CMOS MEMS 226
 - system integration 513, 559 ff
- pre-CMOS micromachining 29, 33 ff
 - pressure sensors 257
 - thermal sensors 515 f
- preamplifiers
 - biochemical sensors 466
 - interface circuitry 520
- precipitation defects 24
- precision, analog frontends 526
- preprocessing, fingerprint sensors 417 f, 421 f
- pressure sensors 49, 56, 257–334
- Privium 394
- processing 9 ff, 17 ff, 24 ff, 69
 - biochemical sensors 452
 - diaphragms 201
 - inertial sensors 145 f
 - pressure sensors 300–313
- processor smartcards 441
- proportional-integral-differential (PID) controller 369
- proportional-to-the-absolute-temperature (PTAT) 554 ff, 558 ff
- protocols, interfaces 572
- pseudo-differential amplifiers 528
- Pseudomas fluorescense* 450

- pyroelectric analog frontend 534 ff
- pyroelectric elements 539
- pyroelectric infrared detectors 492
- PZT transducers 219 f
- quadrature signals 228
- quality factor
 - biochemical sensors 451
 - chopper amplifier 536
 - fingerprint sensors 409 ff
 - resonant cantilevers 570
 - RF CMOS MEMS 225
 - spiral inductors 240
- quantization error 546
- quantization noise 162 f
- quantum efficiency 353
- quantum-well infrared photodetectors 481
- quartz microbalance (QMB) 343
- radiation resistance 198, 209
- radiation sensors 480 ff
- radio receivers 196
- raw image enhancement 421
- Rayleigh–Ritz variation 273
- Rayleigh surface acoustic waves 343 ff
- reactive ion etching (RIE) 8, 11, 169
 - chemical sensors 346, 355
 - microbolometers 495
- receiver–operator curve (ROC) 427
- receivers 227 ff
- receptors 338, 348
- recognition processes 394 ff, 411
- redox cycling 455
- reduced Fermi level 282
- reference electrodes 359, 454
- reference fingerprints 425
- reflection optical waveguides 355
- refractive index 354
- regeneration transistors 538
- reliability 72, 397
- request fingerprints 425
- residual stress 73 f, 109, 236
- residual stress/strain 101, 123
- resistive sensors 526 f
- resistivity
 - electrical 69, 73 ff, 80
 - fingerprint sensors 412 ff
- resistors 149, 502
- resolution
 - analog frontends 513, 522
 - digital-to-analog converters (DACs) 549
 - filters 551
 - fingerprint images 425
- resonance frequencies 77, 144
 - chemical sensors 336, 343
- resonant-beam oscillator 571 f
- resonant cantilever 345, 570 f
- resonators
 - inertial sensors 156 ff
 - RF CMOS MEMS 229 ff, 243 ff, 343
 - thin film bulk acoustic 246
- reticles 27
- reversibility, chemical sensors 338
- RF CMOS MEMS 225–256
- RF filtering 206
- ridges, fingerprint sensors 416, 430
- rigidity 103, 267, 271
- ring gyroscope 47, 179
- ring plates 277 ff
- Robert Bosch accelerometer 160 f
- robustness 79, 414 ff
- Root Allan deviation 160
- root mean square (RMS) voltage 479, 499 f
- rotated coordinate systems 284 f
- rotating pointer structures 115
- rotation, fingerprint images 424
- round robin test 128
- rub-off test 414
- Saccharomyces cerevisiae* 461
- sacrificial aluminum etching (SALE) 22, 55
- sacrificial layers 36 ff, 89
 - pressure sensors 259 ff, 300, 305
- sacrificial oxide etching 38
- sacrificial photoresist layer 234
- sacrificial spacer 180
- Sallen–Key filters 540
- sample handling 120, 473 ff
- sample-to-answer-path 450
- sandwich technology 3 ff, 47, 54, 89, 96
- scalability 451
- scaling 283, 451
- scanning area limits 425
- scanning probe techniques 472 ff
- scattering 353
- scenario evaluation, fingerprint sensors 429
- schematics *see*: block diagrams
- scratch resistivity 415
- security, fingerprint sensors 438 ff
- Seebeck coefficients 69 ff, 73, 84 ff, 87 ff
 - thermocouple materials 350 ff, 483 ff
- segmentation, fingerprint sensors 421
- selectivity 338, 375
- selfalignment 305

- selfheating 88, 499
- semiconducting substrates 9
- semiconducting thin films 69
- semiconductor switches 230
- sense nodes 172 f
- sensitivity
 - acoustic devices 193 ff
 - analog frontends 525
 - biochemical sensors 451
 - fingerprint sensors 407
 - inertial sensors 140 ff, 160, 177 f, 183
 - system integration 513, 559 ff
- sensor arrays 12
- sensor device integration 434 ff
- separation-by-implantation-of-oxygen (SIMOX) 40, 128, 322, 372
- serial interfaces 513, 572 f
- serpentine metal-oxide mesh pattern 201 f, 211 f, 218 f
- Severinghaus pH FET 378
- shear mode resonator 343
- shear modulus 76, 267
- shear stress 262, 280 f
- sheet resistance 73, 80, 94, 559
- shock tolerance 140
- short-term stability 570
- sidewall implantation 37
- Siemens gate polysilicon accelerometer 167
- Sigma-Delta converter
 - analog-to-digital 546 ff
 - chemical sensors 351, 373, 380
- Sigma-Delta electrostatic force 161 ff
- Sigma-Delta modulators 544, 568
- signal processing
 - biochemical sensors 452
 - fingerprint sensors 399 ff
 - pressure sensors 259, 315 ff
- signal-to-noise ratio (SNR) 152, 340, 513577
- signature recognition 396
- silicides metallization 71
- silicon 3 ff
 - acoustic devices 196
 - bulk material 97 ff
 - chemical sensors 368
 - data interfaces 555
 - diaphragms 257
 - elastic properties 126
 - material properties 74 ff, 287 ff
 - microbolometers 492
 - pressure sensors 259, 304 ff
 - RF CMOS MEMS 226
 - Seebeck coefficients 485
 - wafers 287 ff, 452
- silicon dioxide
 - layers 3 ff
 - material properties 74 ff
 - thermal properties 96 ff
- silicon germanium BiCMOS devices 234
- silicon nitride
 - chemical sensors 355
 - diaphragms 260, 305 ff
 - elastic properties 127
 - layers 3 ff, 38, 52 f, 305
 - material properties 74 ff, 78
 - residual stress 125
 - tensile properties 128
- silicon-on-glass (SOG) 47, 55, 180
 - accelerometers 184
 - coatings 71
- silicon-on-insulator (SOI) 2 ff, 35 f, 88
 - chemical sensors 372
 - inertial sensors 183 f
 - microbolometers 497
 - pressure sensors 322
- silicon oxide
 - elastic properties 127
 - residual stress 124
 - tensile properties 128
- silicon trench etching 37
- simulation results, acoustic devices 212
- sinc filters 552
- single-chip gas detection system 566 ff
- single-chip integration 250 f
- single-chip radios 225
- single-master interfaces 572
- skin effects 240
- small-size design 197 ff
- smart cart integration 440 ff
- software development kit (SDK) 434 ff, 438
- software solutions, fingerprint sensors 416 ff, 419 ff
- sol-gel process 372
- solder-bonded capacitive pressure sensors 307 ff
- sound pressure displacement 200
- sound pressure level (SPL) 205
- sound waves 195
- source drain currents 361
- source drain implantation 12, 17, 40
- space charge region 361
- spacers 180
- speaker recognition 396
- speakers 193 f, 208 ff

- specific heat 69 ff
- specifications
 - interface circuitry 520 ff
 - operational transconductance amplifiers (OTAs) 569
 - switched capacitor amplifier 535
- Spectre Synopsys 567
- spiral inductor 240
- spot noise 160, 455
- spring constant 140, 153
- springs, acoustic devices 202 f
- sputtering 6, 42, 45
 - chemical sensors 344
- square diaphragms 106 f
- squeeze film damping 182, 186, 198 f, 201 ff
- ST's TouchStrip TCS3B capacitive transducer 403
- stability 72
 - analog frontends 526
 - fingerprint sensors 432
 - resonant beam oscillator 570
- standard biometric templates 437
- standard software, fingerprint sensors 435 ff
- static mode, chemical sensors 345
- static properties, analog frontend 522 f
- static random access memory (SRAM) 46
- stepper based lithography 27
- stiction, inertial sensors 147, 149 ff
- stiffness 73 f, 76
 - tensors 261, 265 ff
- storage smartcards 441
- strain gauges
 - diaphragms 304 ff
 - pressure sensors 259
- strain tensors 261
- stress 150
 - diaphragms 257
 - relaxation 85
- stress-strain relationship 102
- SU-8 substrates 7, 465
- substrate materials 5 ff
 - biochemical sensors 452
 - interface circuitry 516 f
- substrate temperatures 88
- super-heterodyne radio architectures 227
- surface acoustic waves (SAW) 343 ff
- surface coating 464
- surface deformation 343
- surface doping 372
- surface energy, fingerprint sensors 412
- surface micromachining 22 ff, 29
 - microbolometers 491
 - pressure sensors 257, 300 ff, 344 ff
 - test structures 89 f
- surface properties 7, 78, 115
 - fingerprint sensors 399
- suspended inductors 238 ff
- suspended rings 115
- suspension 151
 - spring constant 140
- swipe sensors 403 f, 440
- switched capacitor
 - Delta-Sigma modulator 317 ff
 - filters 541 ff
 - pressure sensors 257
 - system integration 513 ff, 531 ff, 568
- switching 229 ff
 - fingerprint sensors 420 ff
- symmetry transition 113
- synthetic fingerprints 430
- system integration 513–577
 - fingerprint sensors 433 ff
- system level error rates 428
- system-on-card (SoC) 441
- system-on-chip
 - filters 551
 - interface circuitry 521
- system properties, analog frontend 525 f
- system scalability 451
- temperature coefficient of resistance (TCR) 74, 82 ff, 95 ff
 - microbolometers 492
- temperature dependence 150, 350
 - base-emitter voltage 555 ff
 - layers 491
 - piezoresistivity 281 ff
 - pressure sensors 259
 - sensitivity 207
 - transducers 402
- template-on-card (ToC) 441
- templates
 - fingerprint sensors 425, 437
 - interface circuitry 521
- tensile stress 147, 262
- tensile test 119 f
- tensor notation 261 f
- tented arches 418
- termination 416
- test structures 88 ff, 115 ff, 150, 513, 561 ff
- tetramethyl ammoniumhydroxide (TMAH) 20, 24, 53, 303, 495

- thermal accelerometer 175 f
- thermal actuation 345
- thermal conductivity 69, 73, 86 ff
 - chemical sensors 368
 - pressure sensors 323
- thermal–electrical transduction 74 ff
- thermal energy domain 69
- thermal expansion coefficient (TCE)
 - 69, 73 ff, 101, 114 ff, 126 f, 236
- thermal–mechanical transduction 77
- thermal pressure sensors 324 ff
- thermal properties 86 ff
- thermal sensors 337, 342, 348 f, 479–512
- thermal–thermal transduction 77 ff
- thermal transducers 402 ff
- thermal van der Pauw test structure
 - 80, 92 f
- thermally stabilized accelerometers 173
- thermistors 6
- thermochuck test 562
- thermocouples 350, 483 ff
- thermoelastic friction 73
- thermoelectric coolers 498
- thermoelectric analog frontend 534 ff
- thermoelectric material data 80 ff, 86 ff
- thermoelectric sensors 350 ff
- thermomechanical noise 142
 - acoustic devices 193, 197 ff

see also: Brownian noise
- thermopiles 12, 479–512
 - chemical sensors 350
 - imaging arrays 489
- thermopower 69, 82 ff
- thermovoltage 350
- thickness control, diaphragms 302 ff
- thickness-shear-mode resonator 343
- thin diaphragms 300
- thin films 69–136, 149
- thin plate deflection 271 ff
- thinned fingerprint images 423
- Thomson coefficient 73 f, 76
- three-electrode system 359
- threshold limited value (TLV) 336
- time constants
 - filters 541
 - thermal 100
- time etch-stop 303 ff
 - see also*: etch-stop
- time-of-flight flow sensors 502 f
- tin dioxide 337
- tin-lead solder frame 307
- tin oxides 338, 370
- tissue cultures 463
- titanium
 - bulk material 97
 - bolometer structures 41
 - thin films 83
- titanium–gold seed layer 47
- titanium nitride thermocouples 488
- total harmonic distortion (THD) 524
- total internal reflection transducer 400
- TouchStrip TCS3B capacitive transducer
 - 403
- toughness 69 ff, 73 f, 76, 101
- transceivers, multiband 228 ff
- transconductance 144
 - switched capacitor amplifier
 - 537, 543 ff, 548
- transducer electronic data sheet (TEDS)
 - 554
- transducers
 - acoustic 194, 214 ff, 219 ff
 - biochemical sensors 451
 - chemical sensors 336 ff, 376 f, 379 ff
 - fingerprint sensors 399 ff
 - gas detection system 567
 - pressure sensors 259 ff
 - system integration 560
- transduction effects 70 ff, 203 ff
- transfer functions
 - analog frontends 523
 - biquad filter 540
 - Delta–Sigma modulators 257, 321 ff
 - FIR filter 553
 - switched capacitor amplifier 538
- transformation tensors 263 ff, 287 ff
- transients, chemical sensors 352
- transistors 167, 182, 361
 - interface circuitry 516 f, 556
 - RF CMOS MEMS 226
 - switched capacitor amplifier 537
- transmission gates 542
- transmission lines 228, 243
- transverse modes 354
- trench isolation 35, 184
- tri-axial piezoresistive accelerometer 182
- trimming capability 149
- triple-well technologies 519
- tunable capacitors 227
- tungsten
 - bulk material 97
 - elastic properties 126
 - plug 71
 - thin films 83
- tuning fork resonant sensors 164
- tuning voltage 234

- twin-well technology 3
- two-beam interferometer 355
- ultrasonic sensors 193 f, 217 ff
- uncooled infrared detectors 480, 483 ff
- user interaction, fingerprint sensors 439 ff
- vacancies 370
- vacuum cavity 259
- vacuum operations 499
- valleys, fingerprints 416
- van der Pauw test 80, 92 f
- vanadium oxide 492
- vaporization heat 352
- varactor diodes 248
- variable gain amplifier (VGA) 227
- verification
 - fingerprint sensors 391, 416 ff, 439 ff
 - system integration 513, 564 ff
- vertical axis accelerometer 170
- vertical axis gyroscope 163
- vertical parallel-plate capacitors 235
- vertical pnp transistors 556
- vibrating metal-ring gyroscope 178 ff
- vibration rejection 193 ff, 200 f
- vibratory rate gyroscope 144 ff
- voice scan 396
- volatile organic compounds (VOCs)
 - 338, 344, 379, 566
- voltage-controlled charge source (VCQS)
 - 319
- voltage-controlled oscillator (VCO)
 - 234, 247
- voltage modes 151, 554 ff
- voltammetric sensors 337, 358 ff
- volume reduction 226
- wafer bonding 300, 310 ff
- wafer curvature 114 f
- wafer materials 9 f
- wafer technology 46 f, 452, 516 f
- water acoustics 219 ff
- wave guides 355
- weight reduction 226
- well formation 9, 12
- wet etching 18 f, 24 f, 50
 - pressure sensors 259, 302
- wet skin, fingerprint sensors 421, 439
- Wheatstone bridge 11, 50, 181
 - biochemical sensors 472
 - chemical sensors 365
 - circuit integration 513 ff, 526 ff
 - piezoresistors 261, 295 ff, 300 f
 - resonant beam oscillator 570
- whorl, fingerprint class 418
- wire bonding 16
- wireless communication 225 ff
- working electrodes 359
- working scheme
 - biometric system 318 ff
 - fingerprint sensors 431
- worst case combinations 559
- X-ducer 260, 297
- xenon difluoride etching 169, 241
- xerogels 457
- XL series inertial sensors 146, 151 ff, 155, 158 f
- yield stress 73 f, 76
- Young's modulus 69 ff, 73 ff, 101 ff, 119, 126 f
 - acoustic devices 199, 204
 - inertial sensors 146 f
 - pressure sensors 267, 272, 284
- yttrium barium copper oxide 492 ff
- zeolites 338
- zero-input signal 522
- zero-rates 427
- zinc oxide 343
- zirconium dioxide 337

