

Index

a

- accelerometers
 - description 330
 - normalized frequency response 331
 - quasi-static 331
 - resonant 334
 - single-axis 330
- acoustic streaming 437
- acoustic wave devices 381
- air damping
 - Bao's approach 57
 - cantilever-beam resonator 56
 - energy transfer 56
 - MEMS resonators 56
 - sharp dependence 58
 - shear film damping 57
 - velocities and pressures 57
 - vented resonator 58
 - viscosity 59
- AKE, *see* Akhiezer Effect (AKE)
- Akhiezer effect (AKE)
 - extensional mode 67
 - Gruneisen parameter 67
 - MEMS resonators 69
 - quality factor 68
 - silicon carbide 68
 - thermalization 67
- AlN-on-Si bulk acoustic resonator 316
- Alpha-methylacyl-CoA racemase (AMACR) 414
- AMACR, *see* Alpha-methylacyl-CoA racemase (AMACR)
- anchor damping
 - free-free mode 61
 - geometries 62
 - macroscopic perspective 61
 - MHz frequency devices 62
 - resonator motion 61

- stress waves 62
- angular resonance frequency 437
- antibody-based bio-recognition 405
- aptamers 370

b

- BAW, *see* Bulk-acoustic wave (BAW)
- Bernoulli-Euler beam theory 15
- bifurcation-based sensing 86
- bi-material hygrometric sensors 249
- bio-recognition
 - agents, definition 404
 - antibody-based 405
 - aptamers 407
 - nucleic acid-based 405
 - peptide ligands 407
 - phages 407
 - sensor response 407
- biosensors, *see also* cantilever sensors
 - bio-recognition, *see* bio-recognition
 - fabrication materials 392
 - length scales 403
 - multi-layer geometry 403
 - nucleic acid-based bio-recognition 405
 - proteins, biomarkers and toxins 414
 - single-layer geometry 402
 - virus detection 416
 - whole cells detection 409
- Boundary element methods (BEM) 436
- broadband energy harvesters
 - Duffing's type equation 459
 - generator array power spectrum 458
 - linear resonant approach 457
 - mechanical stress 457
 - multimodal/coupled oscillator structures 458
 - nonlinear harvesters 459
 - tuning magnet position 458

- broadband energy harvesters (*contd.*)
 - vibration frequency 460
- Bulk-acoustic wave (BAW)
 - angular gain 342
 - electrostatic mode matching and mode alignment 347
 - elliptical degenerate modes 342
 - ZRO, *see* Zero-rate output (ZRO)
- C**
- cantilever beams
 - arbitrary mode number model 44
 - arbitrary mode order 30
 - deflection function 38
 - dynamic response 29
 - finite beam length 50
 - finite-element fluid-structure models 38
 - flexural modes 30
 - flexural oscillation, *see* flexural oscillation
 - fluid compressibility 46
 - fluid motion 29
 - fluid-structure interaction 30
 - imaginary component $i\omega$ 42
 - inviscid fluid 29, 38
 - materials and fluids 46
 - microcantilevers 46
 - normalized mode number 39, 41
 - omega and mode number 39
 - relevant length scale 45
 - resonance peaks 49
 - Reynolds number 42
 - scaling analysis 47
 - sound waves 49
 - thermal noise 41, 49
 - torsional modes 40
 - viscosity 29
- cantilever designs and sensing systems 379
- cantilever sensors
 - active layers 403
 - array 402
 - inactive layers 403
 - length scales 403
 - multi-layer designs 403
 - piezoelectric microcantilever 403
 - silicon-based 392
 - single-layer 402, 403
 - static/dynamic mode 391
 - T-shaped piezoelectric resonators 403
- Capacitive micromachined ultrasonic (CMUT) devices 428
- capacitive resonators
 - actuation and sensing 121
 - circuit models 136, 138
 - electrical isolation 135
 - electromechanical force derivation 123
 - electroquasistatic approximation 123
 - geometry 121
 - interfaces, *see* capacitive sensing interfaces
 - microresonators 121
 - sensing and motional capacitor topologies, *see* capacitive sensing and motional capacitor topologies
 - transduction 122
 - voltage dependent force components 124
- capacitive sensing and motional capacitor topologies
 - angular moving plates 134
 - electrostatic spring softening and snap-in 132
 - parallel-moving plates 127
 - perpendicular moving plates 129
- capacitive sensing interfaces
 - high-impedance voltage detection 142
 - switched-capacitor detection 142
 - transimpedance amplifier 138
- capacitive transduction 122
- carbon-based NEMS
 - description 215
 - device geometries 217
 - electron tunneling and mechanical motion 219
 - nanotube device 215
 - position detectors 217
 - Q mechanical resonator layout 217
- Cauchy-Green deformation tensor 428
- Ceramic dual in-line packages (CERDIPs) 293
- Chemical mechanical polishing (CMP) 300
- chemically sensitive layers
 - aptamer 370
 - inorganic and organic materials 369
 - metal organic frameworks (MOFs) 370
 - polymers 368
 - SAMs 370
- chopper stabilization 140
- Complementary metal-oxide-semiconductor (CMOS) process 291
- complex-valued viscosity 430
- concave resonator geometry 307
- conductive and dielectric polymer microresonators 238
- continuous flow measurement 408
- continuous systems modeling
 - boundary value problem, vibrating microcantilever 16
- harmonically excited microcantilever, steady-state response 19

- microcantilever, free-vibration response 17
 - modeling assumptions 15
 - multiple-degree-of-freedom (MDOF) 14
 - ordinary differential equations (ODEs) 15
 - partial differential equations (PDEs) 15
 - Coriolis force 262, 265
 - Cryptosporidium parvum* 413
- d**
- damped SDOF oscillator 5
 - damping ratio 7
 - damping, resonator sensors 435
 - 3 dB bandwidth method 12
 - DDM technique, *see* Dip-dry-measure (DDM) technique
 - Deep reactive ion etching tools (DRIE) 109, 299
 - device design, polymeric micromechanical resonators
 - conductive, electrostatic actuation 235
 - dielectric polarization forces 237
 - Lorentz force actuation 239
 - magnetic actuation scheme 239
 - superparamagnetic nanoparticle composite, magnetic actuation 238
 - device level tuning 317
 - dielectric polymer, polarization force actuation 236
 - die-level vacuum-can packaging
 - CERDIPs 293
 - CMOS-only wafers 292
 - disadvantages 293
 - gyroscopes and accelerometers 291
 - individual dies 293
 - laser dicing 292
 - SOI 292
 - stealth dicing process 292
 - Dip-dry-measure (DDM) technique 408
 - direct force energy harvesters 456
 - dissipation mechanisms 55
 - doping profile engineering 307
 - double correlated sampling 143
 - Duffing's type equation 459
 - dynamic heating power 174
 - dynamic magnification factor 9
- e**
- electrical damping 63
 - electrical equivalent circuit 434, 435
 - Electroactive polymers (EAPs) 468
 - electrodynamic coupling mechanisms 427
 - electromagnetic transduction 464
 - electromechanical amplitude modulation 140
 - electromechanical force derivation 123
 - electron beam lithography 209
 - electronics
 - advantages 212
 - NEMS devices 211
 - telecommunications 212
 - electroquasistatic approximation 123
 - electrostatic spring-softening 335
 - electrostatic transduction 465
 - electrothermal actuation, MEMS
 - bending moment 182
 - bent-beam 179
 - bulk actuators 184, 188
 - cantilever 179
 - description 173
 - dog-bone structure 176
 - dynamic components 174
 - dynamic heating power 174
 - electrical circuit 175
 - heaters 183
 - lumped-element modeling 175
 - static heating component 174
 - thermal actuator 177
 - thermal domain 175
 - thermal wave 182
 - U-shape 178
 - embedded channels
 - fabrication 273
 - fluid density and flow 263, 279
 - micro- and nanoresonators 262
 - nanomechanical resonators 261
 - packaging considerations 275
 - particle mass measurements 262
 - principle 261
 - single particle measurements 271, 279
 - surface-based measurements 280
 - surface reactions 269
 - viscosity 267
 - energy harvesting devices
 - autonomous electronics system 452
 - broadband type 457
 - direct force type 456
 - frequency conversion 460
 - inertial generators 453
 - nonlinear approaches 471
 - UK's Energy Harvesting Network 471
 - Escherichia coli* O157:H7 409
 - eutectic bonding 295
 - extensional oscillation 37

f

- fabrication 273
- FEM, *see* Finite element method (FEM)
- ferroelectrets 468
- Finite element modeling (FEM)
 - commercial software packages 101
 - description 97
 - mathematical fundamentals, *see* mathematical fundamentals, FEM
 - MEMS resonator design, *see* MEMS resonator design, FEM
 - post-processing 103
 - processing (solution) 103
 - setup (pre-processing) 102
- flexural oscillation
 - Bessel functions 34
 - boundary conditions 31
 - Brownian motion 33
 - centroid 31
 - clamped-clamped beams 32
 - components 32
 - eigenvalues 32
 - flexural mode 37
 - fluid 31
 - gases and liquids 35
 - hydrodynamic load 32, 36
 - Navier-Stokes equation 34
 - parameter 32
 - quality factor 35
 - rectangular cantilever beam 30
 - thermal noise 36
 - torsional modes 36
- fluid channel 383
- fluid density and flow, embedded channels
 - Coriolis force 265
 - flow rates 265
 - internal hydrostatic pressure 264
 - measurements 279
 - microfluidic resonators 263
 - Rayleigh-Ritz method 264
 - sensitivity, vibrating tube 264
- fluid property sensors
 - Cauchy-Green deformation tensor 428
 - measuring methods 431, 432
 - miniaturized rheometers 432, 433
 - resonator 428
 - rheological properties 429–431
 - time-harmonic deformation 431
 - viscosity 427
- fluid viscosity effects, embedded channels 267
- frequency-independent properties 6
- frequency ratio 9

- Frequency response function (FRF) 12
- fusion bonding 295

g

- gas-phase chemical sensors
 - mass-sensitive sensors 374, 377
 - MEMS-based and QCM-based 378
 - MEMS-based resonant microstructures 374
 - resonant microstructures 375
 - resonator designs 377
 - silicon-based resonant cantilever 376
 - volatile organic compounds (VOC) 375
- Giardia lamblia* 413
- gravimetric methods 247
- gyroscopes
 - BAW, *see* Bulk-acoustic wave (BAW)
 - Coriolis acceleration 337
 - Coriolis effect 339
 - description 337
 - drive-loop 339
 - electrostatic sensing 338
 - Foucault pendulum 337
 - mechanical noise 347
 - mode-split vs. mode-matched 340
 - orthogonal and proportional 337
 - rotation-rate sensors 337

h

- Hepatitis B Virus (HBV) 417
- hermetic packaging, MEMS
 - characteristics 287
 - CMOS 291
 - die-level vacuum-can packaging 291
 - die separation 290
 - electrical interconnect techniques 289
 - epi-seal process 299
 - fragile structures 289
 - getters 298
 - hermetic vacuum environment 288
 - pressure-induced damping 288
 - temperature control system 288
 - temperature-induced hysteresis 289
 - thin film encapsulation 296
 - wafer bonding packaging, *see* wafer bonding packaging
- high-impedance voltage detection 142
- humidity sensor
 - linear stress-strain relation 249
 - micromechanical SU-8 string resonators 251
 - resonant glass cantilever 249
 - string resonators 248
 - thermal drift 250

- water vapor absorption 247
- hygrometric method 248
- i**
- inertial energy harvesters 453
- Inertial measurement unit (IMU)
 - description 348
 - sensor integration 352
 - single-die integration 349
 - SiP approach 348
 - vertical acceleration detection 350
- in-plane modes 314
- j**
- Joule effect 467
- l**
- liquid-phase chemical sensors
 - acoustic wave devices 381
 - cantilevers 379
 - microdisk resonators 380
 - resonant microstructures 379
- liquid trapping 427
- Listeria monocytogenes* 411, 417
- longitudinal viscosity 441
- Lorentz forces 77, 239
- Low pressure chemical vapor deposition (LPCVD) 299
- low-Q polymer micromechanical resonators 234
- m**
- magnetostriction 467
- manifold 372
- mathematical fundamentals, FEM
 - dynamic problems 100
 - problem solving steps 97
 - static problems 98
- MCLR, *see* Microcystin-leucine-arginine (MCLR)
- MEMS, *see* Micro electro mechanical systems (MEMS)
- MEMS-based artificial cochleas 253, 254
- MEMS devices, resonator sensors
 - cantilever devices 442
 - in-plane resonators devices 445
 - U-shaped cantilevers 445
- MEMS inertial sensors
 - accelerometers, *see* accelerometers
 - gyroscopes, *see* gyroscopes
- MEMS resonator design, FEM
 - anchor loss/clamping loss 110
 - capacitive and piezoelectric electrodes 106
 - categories 104
 - electrode shapes 108
 - electromechanical coupling 106
 - extensional modes 108
 - filter design 115
 - mesh and the mode shape 109
 - process-induced variation 108
 - silicon block resonator 105
 - spurious mode identification and rejection 113
 - structural features 104
 - thermoelastic damping 112
 - transduction mechanism 106
- MEMS resonators
 - compensation 306
 - control of quality factor and compensation 316
 - device level tuning 317
 - doping-profile engineering 308
 - electrostatic tuning 318
 - flexural resonators 311
 - geometry engineering 307
 - microfabrication techniques 305
 - particle polarization 312
 - performance metrics 305
 - piezoelectric tuning 319
 - polarization voltage 317
 - silicon dioxide 309
 - silicon resonators 310
 - system-level tuning 320
 - TCE 309
 - temperature tailoring 312
 - thermal effects, compensation 306
 - thermal tuning 319
 - trimming methods 321
- microacoustic sensors 440
- micro- and nanocantilevers 15
- microcantilever energy harvester 252
- Microcystin-leucine-arginine (MCLR) 415
- microdisk resonators 380
- Micro electro mechanical systems (MEMS)
 - comparison, different kinetic energy 469
 - EAP 468
 - electromagnetic transduction 464
 - electrostatic transduction 465
 - ferroelectrets 468
 - hermetic packaging, *see* hermetic packaging, MEMS
 - magnetostriction 467
 - mechanical properties 452
 - piezoelectric transduction 462
 - scaling laws 471
 - vacuum encapsulation 470
- micromechanical resonators 55
 - frequency-specific audio waves 234

micromechanical resonators (*contd.*)

- Si sensor, polymer coating 234
- Young's modulus 234

moment of inertia 16

motional resistance 137

n

Nanoelectromechanical systems (NEMS)

- amplifier boosts 207
 - bifurcation 206
 - bio-NEMS 219
 - cantilevers 208
 - carbon nanotubes 210
 - catalyst material 210
 - CMOS technology 209
 - description 203
 - design 221
 - electron beam lithography 209
 - fabrication process 209
 - frequency noise 204
 - fundamental and characteristic properties 203
 - graphene 222
 - mass-sensing experiments 204
 - mechanical properties 208
 - motional signal 206
 - nanochannels 211
 - nanopiezotronics 221
 - nanoscale-photonic circuit 207
 - nonlinear and complex dynamics 204
 - out-of-plane movement 222
 - piezomaterials 220
 - silicon 208
 - transduction efficiencies 206
- Navier-Stokes equations 437
- neo-Hookean materials 428
- Newtonian liquid 429
- nonlinear harvesters 459
- nonlinear MEMS/NEMS applications
- bistable mechanical resonator 213
 - cantilevers 213
 - detrimental noise 213
 - duffing nonlinearity 215
 - Euler buckling 215
 - geometric nonlinearity 215
 - microresonators 215
 - multi-bit logic, doubly-clamped resonator 216
 - nonlinear resonance 213
 - parametric instability 215
 - sensors and actuators 212
- non-MEMS device 470
- Normalized power density (NPD) 470
- nucleic acid-based bio-recognition 405

o

organic resonant MEMS devices

- high-Q resonator 233
- intrinsic energy loss 234
- micromechanical sensors 233
- quartz crystal microbalances (QCM) 234
- silicon-based micro gas sensors 233

p

packaging

- commercial chemical sensors 371
 - designs 373
 - manifolds 372
 - non-electrical signals 371
 - Sensirion humidity sensors 372
 - vacuum-encapsulated resonator 373
- packaging considerations, embedded channels 275

paramagnetic microcantilevers 238

parametric excitation

- amplitude-state controller 88
 - bifurcation control 88
 - device modeling 74
 - dimensional and nondimensional parameters 79
 - dynamic behavior 80
 - electrical/mechanical system 73
 - electrostatically-actuated systems 75
 - equation of motion 79
 - inertial sensing 86
 - Lorentz forces 77
 - Mathieu equation 73
 - micro- and nanosystems 74
 - microbeams 85
 - micromirror actuation 87
 - micro/nanoresonators 74
 - microresonator 76
 - microscanners 75
 - modeling and analysis techniques 77
 - nonlinear frequency response 83
 - nonlinearities 82
 - physical mechanism 78
 - Piezoelectric elements 77
 - resonant vibrations 81
 - shaped-finger comb geometry 76
 - sources 77
 - thermomechanical noise 84
 - voltage changes 75
- parametric excitation: "wedge of instability" 80
- PEMC sensors, *see* Piezoelectric-excited millimeter-sized cantilever (PEMC) sensors
- Perfectly matched layers (PML) 111

- Physical vapor deposition (PVD) techniques 147
- Piezoelectric-excited millimeter-sized cantilever (PEMC) sensors 409
- piezoelectric resonant MEMS
 - beam/plate 159
 - clamped-clamped beam 160
 - coefficients 150
 - devices 147
 - electromechanical coupling coefficient 158
 - flexural vibrations 159
 - kinetic energy 155
 - lumped circuit model 154
 - mass and stiffness 161
 - mechanical vibrations 151
 - one-port piezoelectric resonator 156
 - parameters 156
 - piezoelectric devices vs. frequency 148
 - resonator electrodes 156
 - sensing electrode 161
 - strain-charge form 149
 - stress-charge form 150
 - two-port piezoelectric resonator 157
- piezoelectric transduction 462
- piezoelectric tuning 319
- piezoresistive sensing
 - base resistance 185
 - crystalline silicon structure 190
 - electronic oscillator 189
 - feedback loop 190
 - implementations 185
 - in-plane flexural modes 187
 - out-of-plane 187
 - output signal 189
 - single-crystalline silicon 186
 - stress and strain 185
 - temperature coefficient 187
 - thermal excitation resistors 188
- polarization voltage 125
- prostate cancer biomarker
 - alpha-methylacyl-CoA racemase (AMACR) 414
 - prostate specific antigen 414
- Pyrex® wafer 295
- q**
- Q-factor 7, 437
- quality factor, polymeric micromechanical resonators
 - energy stored vs lost, oscillation 243
 - generic bending related damping mechanisms 247
 - intrinsic material damping 247
 - micro/nanomechanical string 245
 - relaxed resonators, vacuum 242
 - unrelaxed resonators, vacuum 243
 - viscous environment 242
- Quartz Crystal Microbalance (QCM) 269, 432
- quasi-static accelerometers
 - description 332
 - dissipative effect 332
 - electromechanical transduction 333
 - mechanical noise 334
 - squeeze-film air damping effect 332
 - tri-axial accelerometer 333
- quasi-static polymeric micromechanical sensors 233
- r**
- Rayleigh-Ritz method 264
- resonant accelerometers
 - acceleration sensitivity 336
 - electrostatic spring-softening 335
 - frequency oscillators 334
 - Q capacitive beam resonator 335
- resonant amplification method 11
- resonant chemical gas sensor performances 382
- resonant gate transistor 287
- resonant MEMS chemical sensors
 - advantages 355
 - chemical domain 356
 - chemical sensitivity 364
 - chemical sensor 364
 - coated microcantilevers 355
 - components 356
 - limit of detection (LOD) 366
 - long-term sensor drift 367
 - mass-sensitive 365
 - microcantilevers 357
 - quality factor 363
 - resonant frequency 362
 - resonant microcantilever chemical sensors, *see* resonant microcantilever chemical sensors
 - sensing film 364
 - signal processing 357
 - transducer effects 356
- resonant MEMS devices
 - cantilevers and doubly clamped members 23
 - continuous systems modeling, *see* continuous systems modeling
 - in-plane deformation, slender circular rings 26
 - natural frequency formulas 24
 - nomenclature 4

- resonant MEMS devices (*contd.*)
 - SDOF systems, *see* Single-degree-of-freedom (SDOF) systems
 - transverse deflection 25
 - resonant microcantilever chemical sensors
 - base layer 360
 - flexural rigidity 358
 - hydrodynamic function 359
 - microcantilever chemical sensor platform 357
 - polymer layer 361
 - time-variant neutral axis location 359
 - viscoelastic coating 358
 - resonator equivalent electrical circuit and optimization
 - actuator beam dimensions 196
 - electrical resistivity and material properties 196
 - optimization 195
 - quality factor 195
 - resonance frequency and resonator scaling 196
 - resonator sensors
 - accuracies and sensitivities 438
 - characterization process 439
 - comparison 443, 446
 - damping 435
 - doubly (or multiply) clamped 438
 - eigenmode decomposition 433, 434
 - electrical equivalent circuit 434, 435
 - excitation and readout 433
 - fluid-structure interaction 436, 437
 - membrane devices 438
 - MEMS devices, *see* MEMS devices, resonator sensors
 - microacoustic devices 440, 441
 - resonant MEMS devices 438
 - singly clamped 438
 - suspended silicon based microchannel resonator 440
 - temperature 439
 - rheometers 431, 432
 - robustness 409
- 5**
- sacrificial layer methods 273
 - SDOF systems, *see* Single-degree-of-freedom (SDOF) systems
 - Self-assembled monolayers (SAMs) 370
 - sensor chips 373
 - shear rheometer 429
 - shear-thickening effect 428
 - silanization modification 405
 - Silicon bulk acoustic resonator (SiBAR) 307
 - silicon cantilevers 380
 - Silicon-on-insulator (SOI) 109, 292, 299
 - single cell measurements 279
 - single particle measurements 271, 279
 - Single-degree-of-freedom (SDOF) systems
 - free vibration 6
 - harmonically forced vibration 8
 - quality factor contributions from multiple sources 13
 - Stanford epi-seal process
 - CMP 300
 - dies separation 301
 - DRIE 299
 - epitaxial polysilicon deposition 300
 - HF vapor release etch 300
 - LPCVD 299
 - oxide sacrificial material 299, 300
 - processing costs 302
 - SOI 299
 - Staphylococcal enterotoxin B (SEB) 415
 - static heating component 174
 - stealth dicing process 292
 - Surface acoustic wave (SAW)
 - devices 151
 - sensors 381
 - surface damping
 - gyroscopes/timing resonators 60
 - MEMS structures 59
 - surface loss mechanism 59
 - thickness 59
 - two-level energy systems 60
 - ultrathin silicon cantilever-beam resonators 60
 - Surface plasmon resonance (SPR) instruments 269
 - System-in-package (SiP) 348
 - system-level tuning 320
- t**
- TED, *see* Thermoelastic dissipation (TED)
 - Temperature-compensated crystal oscillators (TCXO) 307
 - tethers 316
 - thermally actuated resonant MEMS
 - cantilever structures 197
 - disk resonators 198
 - thermal tuning 319
 - Thermoelastic damping (TED) 110, 112, 316
 - Thermoelastic dissipation (TED)
 - cantilevers 65
 - expansion and cooling 64
 - mechanical and thermal domains 65
 - MEMS resonator 66, 67

- microfabrication processes 65
- strains 64
- thermal mode 66
- thermo-electro-mechanical modeling
 - ohmic power generation 193
 - thermal-piezoresistive resonator 193
 - transfer function 194
- Thermo-rheological complex (TRC) fluids 431
- thickness-extensional and shear vibrations 168
- thin film encapsulation-based packaging 296
- Thin-piezoelectric-on-substrate (TPoS) 314
- thiolated DNA probes 405
- time-harmonic deformation 431, 432
- tip-force-actuated cantilever beam 22
- transimpedance amplifier 138

u

- underdamped SDOF system 7
- U-shaped cantilevers 445

v

- vibrational energy harvesting
 - micromechanical cantilever 252
 - piezoelectric cantilever resonators 252
- vibrational nodes 18
- Villari effect 467
- virus detection, biosensors
 - gene signature 417
 - microRNAs (miRNAs) 416
 - silicon cantilevers 416
 - toxin-associated Genes, without DNA amplification 417
- viscosity 427

w

- wafer bonding packaging
 - anodic bonding 295
 - CMOS 294
 - definition 294
 - fusion bonding 295
 - processing costs 296
 - silicon wafer 294
 - temperature-induced errors 294
 - thermal expansion coefficient 294
 - wafer-wafer bonding 294
 - wet etching methods 294
- wafer-level packaging
 - fabrication 290
 - thin-film encapsulation 290
 - wafer bonding, *see* wafer bonding packaging
- wet etching methods 294
- whole cells detection 409
- width-extensional vibrations
 - AlN plate 164
 - description 163
 - electrode 163
 - piezoelectric plate 163
 - resonator motional resistance 166
- Williams-Landel-Ferry (WLF) model 431

y

- yield stress 428

z

- Zero-rate output (ZRO)
 - cancellation 345
 - Coriolis response 343
 - electromechanical transduction 345
 - mode-to-mode coupling 345
 - sense-mode 343
- ZRO, *see* Zero-rate output (ZRO)

