

## Index

### a

abiotic degradation 304  
 acetylated cellulose nanocrystals  
   (ACNs) 592  
 acetylated cellulose nanofibers, surface  
   degree of substitution 665  
 acetylation 667  
   NFC and BC nanopaper 666  
   porous cellulose nanofiber structures  
     665  
 advancing contact angles 735–737  
 aerogels 147. *see also* nanofibrillated  
   cellulose (NFC), aerogels  
   from cellulose solutions 659  
   description 659  
   from nanofibrillated cellulose  
     666–667  
   preparation 659  
 AKD-treated cellulose films, OTR for  
   671  
 Alberta Innovates Technology Futures  
   768  
 Alexa Fluor dyes 382  
 alkaline-acid-alkaline  
   pretreatment 28  
 alkyl ketene dimer (AKD) 344, 350,  
   744–747  
 all-cellulose nanocomposites 590  
 amorphous cellulose, preparation  
   24–25  
 amorphous nanocellulose (ANC) 13,  
   56  
 anhydrides 343  
 anhydroglucose units (AGU) 5  
 aqueous emulsion polymerization 817

arabinoglucuronoxylan (AGX) 672  
 atomic absorption spectroscopy (AAS)  
   598  
 atomic force microscopy (AFM) 69,  
   377–378  
 atomic layer deposition (ALD) 740  
 attenuated total reflectance (ATR) FTIR  
   595–596  
 Avrami model 569–570  
 Avrami plots 569, 570

### b

bacterial cellulose (BC) 8–9, 102, 525,  
   533  
   DSC thermograms of 536, 537  
   nanopaper 665  
   TGA and DTG of 531  
 bacterial cellulose nanocrystal (BCW)  
   227  
 bacterial cellulose nanofibrils (BCNF)  
   401  
 bacterial cellulose/polycaprolactone  
   (BC/PCL) nanocomposite 533  
 bacterial cellulose-polyvinyl alcohol  
   (PVA) films 587  
 bacterial nanocellulose (BNC) 88–89  
 bacterial polyester  
   poly(3-hydroxybutyrate-*co*-3  
   hydroxyvalerate) (PHBV) 534  
 batch process 769, 783, 785  
 bilayer mesoporous chiral nematic  
   polymer 811  
 bio-based films, for barrier packaging  
   653  
 biodegradation 304

- biomass-based polyester matrices
  - CNC 309–314
  - CNF 305–307
- biomedicine, cellulose nanomaterials in 821–825
- biomimetic stimuli-responsive nanocomposites 750
- bio-nanocomposites 302, 534
  - CNC
    - matrix, distribution 317–318
    - microstructure effects 325–326
    - natural polymer matrices 314–317
    - polyester matrices 309–314
    - property effects 319–325
  - CNF
    - matrix, distribution 317–318
    - microstructure effects 325–326
    - natural polymer matrices 307–309
    - polyester matrix 305–307
    - property effects 319–325
- bleaching 28
- British Standards Institute (BSI) 697
- butyl acrylate polymerization, on NFC surface 668
- C**
  - calorimetry 74–75
  - capillary viscometry 76
  - carboxymethyl xylan (CMX) films 672
  - Cassie-Baxter model 734
  - castor oil-based segmented polyurethane 592
  - cationized fibrils 782
  - $^{13}\text{C}$  cross polarization magic angle spinning nuclear magnetic resonance (CP/MAS  $^{13}\text{C}$  NMR) 587
  - cellobiose 801
  - CelluForce plant 768, 780
  - cellulose 3, 242
    - AFM 69
    - algae 8
    - applications to 611–612
    - bacterial 8–9, 57
    - biochemical methods 77
    - chemical composition 242
    - chemical methods 77
    - CP/MAS  $^{13}\text{C}$  NMR 65–67
    - crystal morphology 764
    - definition 52, 763, 801
    - dehydration reaction 526
    - electron microscopy 67–69
      - and glucose 763
    - hierarchical architecture 3
    - hierarchical structure 3
    - industrial history 762
    - infrared and Raman spectroscopy 70–71
    - LLS 69–70
    - macromolecules 53
    - moisture absorption 665
    - nanocrystallites 53
    - nitrate 753
    - noncrystalline 54
    - physicochemical methods
      - calorimetry 74–75
      - GC 75
      - HPLC 75
      - sorption 73–74
      - viscometry methods 76
      - zeta potential 76–77
    - physicomechanical properties
      - mechanical testing 72
      - physical testing 72
    - plant materials 8
    - in plants 801
      - and starch 763
    - structural characteristics 54
    - structural organization 53
    - structure and chemistry 5–7
    - superhydrophobic surfaces 732
    - supramolecular structure 54
    - thermal decomposition 526, 527
    - thermal stability of 527
    - thermoanalytical methods 71–72
    - tunicates 8
    - X-ray scattering methods 57
      - crystalline unit cell 58
      - crystallinity calculation 61–65
      - nanocrystallites 59–61
  - cellulose acetate 762
  - nanofibers 751

- cellulose aerogels 738
  - atomic layer deposition 740
  - bacterial 741
  - in carbonization 740
  - drying methods 739
  - fluorinated surfactants 740–741
  - surface topography 740
  - TiO<sub>2</sub> coating 740
- cellulose-based aerogels 659
- cellulose-based nanofibers 554
- cellulose-binding-modules (CBMs) 146–147
- cellulose–clay nanocomposite films 671
- cellulose crystallinity 764–766
- cellulose crystallites. *see* cellulose nanocrystals (CNCs)
- cellulose crystals 764–766. *see also* cellulose nanocrystals (CNCs)
- cellulose films, for gas barrier applications 671
- cellulose hydrolysis, in sulfuric acid 531
- cellulose lauroyl ester (CLE) 751–752
- cellulose microfibrils (CMF) 11
  - cryocrushing 17
  - grinding 15–17
  - high-pressure homogenization 13–14
  - HIUS 17–18
  - microfluidizer 14–15
- cellulose nanocomposites
  - glass transition temperature of 538
  - melting and glass transition temperature of 538–540
  - melting temperature of 538, 541
  - thermal expansion coefficient of 542–544
  - thermal conductivity of 545–546
  - thermal degradation of 532–534
- cellulose nanocrystals (CNCs) 11–12, 56, 525, 584, 630, 750, 764, 801–802. *see also* natural rubber/nanocellulose based green nanocomposites
  - acid recovery 778–779
  - aerogels, fabrication method 660
  - assemblies and implications 125–131
  - bionanocomposite
    - matrix, distribution 317–318
    - microstructure effects 325–326
    - natural polymer matrices 314–317
    - polyester matrices 309–314
    - property effects 319–325
  - from bleached softwood kraft pulp 802
  - characterization 78–86, 688
  - chemical modification 459
  - crystallinity 615–616
  - crystallization in 558–565
  - diafiltration 775–777
  - dynamic mechanical characterization 453, 456
    - nanocomposites 457–459
  - exposure
    - immune responses and oxidative stress 700
    - inflammatory and oxidative responses 700
  - filtration 774
  - heat requirements 777
  - high-resolution SEM images 555
  - human corneal epithelial cell viability *in vitro* 822
  - hydrolysis 766, 767
    - with metal salt catalyst 23
    - with solid acids 22
  - hydrophilic polymer matrices reinforcement 470–473
  - hydrophobic polymeric matrices reinforcement 459–470
  - influence
    - chemical modification 494–495
    - structure and morphology 490–494
  - interfacial interactions 554
    - chains entanglement 423–424
    - crosslinking 422–423
    - hydrogen bonding 418–420
    - nanocomposites reinforced 424–427
    - percolated network 420–422

- cellulose nanocrystals (CNCs) (*contd.*)
  - layer-by-layer (LbL) assembly
    - 131–134
  - mapping 618–619
  - mechanical properties 84
  - mechanical test methods 427
    - compressive testing 428
    - shear testing 428–429
  - mixing of pulp and sulfuric acid
    - 772–774
  - morphology and dimensions
    - 396–400
  - nanocellulose labeling 378–384
  - n-butanol 778
  - orientation 616–617
  - preparation 13, 801–802
    - acid hydrolysis 18–22
    - cryocrushing 17
    - grinding 15–17
    - high-pressure homogenization 13
    - HIUS 17–18
    - hydrolysis 22–23
    - microfluidizer 14–15
    - TEMPO-mediated oxidation
      - method 24
  - processing technology 401
    - electrospinning technology
      - 413–416
    - solution blending method
      - 401–409
    - thermoprocessing method
      - 409–413
  - process scale and processing basics
    - 767–772
  - product drying 777–778
  - production capability 768
  - production cost items 779
  - production facility 772
  - product purification 775–777
  - product separation using centrifuge
    - 774–775
  - PU nanocomposites 591–594
  - Raman frequencies comparison of
    - pulp 614
  - Raman spectra 612–614
  - rheology and liquid crystal phase
    - transition 486–489
  - scale up and production status 780
  - solvent exchange drying 777–778
  - surface treatment of 534
  - synthesis 247–248
  - tensile deformation 619–620
  - tetracycline hydrochloride 822
  - thermoset nanocomposites 252
    - from wood pulp 555
  - X-ray diffraction 766
- cellulose nanofibril (CNF) 11, 302
  - acid and enzyme treatments 781
  - aerogels 660
    - cyclic desorption 662–664
    - shape recovery ability 662–664
  - and AgNC films 824
  - and AgNP composites 825
  - antibacterial ability 824
  - biocompatibility 824
  - bionanocomposite
    - matrix, distribution 317–318
    - microstructure effects 325–326
    - polyester matrix 305–307
    - property effects 319–325
  - characterization 688
  - controlled drug delivery 823
  - crystallinity 615
  - crystallization in 558–565
  - description 780
  - developments 621–622
  - dynamic mechanical characterization
    - 451
    - DMA 453–454
    - nanindentation 456
    - tensile testing 455–456
  - flammability properties 251
  - flammability studies 688–689
  - flowable aqueous dispersions 88
  - high-resolution SEM images 555
  - in humid environments 744
  - hydrogels 135, 136
  - immobilization of biomolecules 825
  - influence 56, 86, 553, 554, 802, 803
    - chemical modification 494–495
    - structure and morphology
      - 490–494
  - interfacial interactions 418
    - chains entanglement 423–424

- crosslinking 422–423
- hydrogen bonding 418–420
- nanocomposites reinforced 424–427
- percolated network 420–422
- LbL 132
- mechanical properties 417
- mechanical test methods
  - compressive testing 428
  - shear testing 428–429
- methacrylic-based gel-polymer electrolytes 820
- morphology and dimensions 396–400
- nanopaper 819–820
- network-like architecture 142
- orientation 616–617
- pilot plants 781
- on polydimethylsiloxane membrane 824
- polyelectrolyte multilayer preparation 821
- preparation 246
  - enzymatic hydrolysis 24
  - steps 744
- processing technology
  - electrospinning technology 413–416
  - solution blending method 401–409
  - thermoprocessing method 409–413
- Raman frequencies comparison of pulp 614
- Raman spectra 612–614
- Rayonier Corporation 780
- rheological property 485–486
- suspensions 596
- synthesis 247
- TEMPO (*see* 2,2,6,6-tetramethyl-4-hydroxypiperidine-1-oxyl (TEMPO))
- tensile deformation 620–621
  - from wood pulp 555
  - wood pulp treatment 781
- cellulose nanofibrillated fiber 525
- cellulose nanofibrous mats (CNM) 413
- cellulose nanomaterials
  - accidental release and storage 697–698
  - in biomedicine and pharmaceuticals 821–825
  - consumer exposure and risk 701–703
  - environmental fate and mobility 717
  - environmental receptors 715
  - environmental safety 715–717
  - exposure controls and personal protective equipment 698
  - hazard data 703
  - oral and dermal exposure routes 702–703
  - physicochemical and safety aspects 688–689
  - physicochemical characteristics 717–720
  - product life-cycle, stages of 691
  - tumorigenesis 704
- cellulose nanoparticles
  - biodegradation 703–704
  - biokinetics 703–704
  - biopersistence 704
  - properties and applications 762, 763
- cellulose nanorods (CNR) 766–767
- cellulose nanowhiskers (CNW). *see* cellulose nanocrystals (CNCs)
- cellulose nanoyarn (CNY) 13, 89
- cellulose triacetate (CTA) 748–749
- cellulose whiskers films 653
- cellulosic fibres, flammability characteristics 250
- cellulosic nanostructures 178
- cellulosic reinforcement 284
  - compatibility 285–286
  - composite strength 286
  - fiber agglomeration 285
  - low density 285
- cetyltrimethylammonium bromide (CTAB) 664–665
- cetyl trimethylammonium bromide (CTAB)-coated CNC 822
- chain confinement 562
- chemical pulping process 28

- chiral mesoporous carbon films
    - 818–820
  - chiral nematic assembly 126
  - chiral nematic structure formation, in
    - nanocomposite hydrogels 812, 813
  - chiral optoelectronics, photonic
    - hydrogels for 811–815
  - chitin nanocrystals 219
  - chitosan (CS) 308, 316, 501
  - chromophore 382
  - CNC. *see* cellulose nanocrystal (CNC)
  - CNC-based nanocomposite hydrogels
    - responsive behavior from 815
    - swelling of 814
  - CNC-PANI-DBSA nanocomposite films 817
  - CNC–polymer nanocomposite hydrogels 813
  - CNF-induced inflammatory response 699
  - CNF–TiO<sub>2</sub> hybrid films 599
  - coating treatment 345–346
  - cold crystallization temperature 562
  - complex electric modulus 637
  - compression mold 412
  - cone calorimetry 260–261
  - contact angle hysteresis 735–737
  - continuous process 770, 785–786
  - controlled drug delivery (CDD) 823
  - cotton 762
  - cotton nanowhiskers 590
  - countercurrent filtrate process 776
  - coupling agents
    - affinity and adhesion 340
    - barrier properties 354–355
    - mechanical properties 350–352
    - morphological properties 355
    - physical properties 355–357
    - pretreatment
      - coating 345–346
      - graft co-polymerization 346–347
      - maleation 347
      - methacrylate graft
        - co-polymerization 347
      - unified mixing and treatment 347–350
    - reaction mechanisms 344–350
    - thermal properties 352–354
    - types and classification 340–344
  - covalent bonding 590
  - critical point drying 777
  - cross-linked rubber based
    - nanocomposites 221–222
  - cross-polarization magic angle spinning
    - <sup>13</sup>C NMR spectroscopy (CP/MAS <sup>13</sup>C NMR) 65–67
  - cryocrushing 17
  - cryofracture 384, 386
  - crystalline allomorphs 584
  - crystalline unit cell 58
  - crystallinity 615–616, 765
  - crystallites 53
  - crystallization, in polymer/CNCs (or CNFs) nanocomposites 558–565
- d**
- deflagration index 688
  - deformation behavior, of dry vs. wet aerogels 663
  - degradation 304
  - degree of surface substitution (DSS) 105
  - depolymerization 526
  - diafiltration process 769, 775
  - dielectric spectroscopy 629
  - differential scanning calorimetry (DSC) 306, 535, 566
    - evaluate thermal properties 193
    - methods of investigations 71
    - thermograms 561, 567
      - PEO/CNC films 572
      - PEO/CNF films 572
      - PEO films 572
    - and relative crystallinity 571–572
  - differential thermal analysis (DTA) 71
  - dimethylformamide (DMF) 562
  - doped CNC-PANI-DBSA nanocomposite films 818
  - doxorubicin hydrochloride (DOX) 822
  - droplet on surface, pinning behavior of 737
  - droplet-surface-gas system 736

- dust overload, in lungs 700
- dynamic mechanical analysis (DMA)
  - 321, 448–449, 562
  - of nanocomposite films 750
  - natural rubber/nanocellulose based green nanocomposites 631
- dynamic mechanical characterization
  - CNC 453, 456
  - CNF 451
    - nanoindentation 456
    - tensile testing 455–456
  - composite material 448–451
- dynamic mechanical thermal analysis (DMTA) 192, 193, 535
- e**
- ecotoxicological study, of CN exposure effects 716
- electric modulus 637
- electron microscopy 67–69, 370–377
- electron spin resonance spectroscopy (ESR) 590
- electrospinning process 25, 26, 186, 748
- electrospinning technology 413–416
- electrospun CTA mats 748
- electrospun nanofibers, crystallization of 565
- electrostatically adsorbed multilayered films 670
- elementary fibrils 801
- empty palm fruit bunch fiber (EPFBF) 15
- energy dispersive X-ray diffraction (EDS) 598
- environmental health and safety (EHS), roadmap
  - environmental and pollution prevention benefits 724–725
  - human health effects 723
  - inhalation 723
  - issues for nanomaterials 684–686
  - measurement challenges for CN 687–688
  - measurement methods 722
  - oral and dermal exposure 723–724
  - physicochemical data 722
  - priorities 720
  - product life-cycle 686–687
  - purpose 720
  - safe exposure levels 721
- enzymatic pretreatment 28–29
- evaporation-induced self-assembly (EISA), of CNC films 809
- f**
- facile two-step dip coating method 745
- feeding and mixing pulps, processes for 772
- fiber aspect ratio 188–189
- fiber, definition of 697
- fiber dispersion 187–188
- fiber-matrix adhesion 188
- fiber orientation 189–190
- fiber volume fraction 190
- fibrous nanocellulose, characterization 86–89
- fire retardancy 238–239
- flame retardant 241, 256
- flammability studies 688–689
  - characterization
    - cone calorimetry 260–261
    - LOI 258–259
    - PCFC 261
    - UL-94 test 259–260
  - impregnation 257–258
  - intumescent coatings 254–255
  - nanometric particles 256
  - surface treatment 256–257
- fluorescent labeling 378
- fluoroacrylic latex reinforced
  - superhydrophobic biopolymer-clay nanocomposite coatings 754
- Förster resonance energy transfer (FRET) 367
- Fourier transform (FT) 70
- Fourier transform infrared (FTIR) spectroscopy 583–585, 597
  - of BC/PEO composites 588
  - of chitosan /CNC nanocomposite 585, 586
  - of CNC (I) 584–586
  - of PU/ACN nanocomposites 593



- Fourier transform (FT)-Raman  
instruments 611
- Fourier transform (FT)-Raman spectra  
618
- freeze-dried CNC, TGA curves of 533
- fully green polymer matrices 302
- g**
- galactoglucomannan (GGM) 672
- gas chromatography (GC) 75
- gas permeance 654
- genotoxic potential, of cellulose  
nanomaterials 704
- glass phase transition temperature, of  
cellulose vs. water 535
- Globally Harmonized System of  
Classification and Labeling  
(GHS) 697
- graft copolymerization 346–347
- h**
- hard segments (HS) nanocellulose 592
- H-bonded carbonyl groups 591
- heat release rate (HRR) curves 262
- hemicelluloses 672, 763
- Hermans-Weidinger (HW) 61–62
- heteropolysaccharides 137
- high boiling solvents 778
- high-intensity ultrasonication (HIUS)  
17–18
- high-performance liquid  
chromatography (HPLC) 75
- high-pressure homogenization (HPH)  
13–14
- <sup>1</sup>H NMR spectroscopy 587
- H<sub>2</sub>SO<sub>4</sub>-catalyzed CNCs 822
- human health effects  
and biokinetics 703–704  
by exposure type 704–714  
genotoxicity 704
- hybrid composites  
alignment, of reinforcing fibers 288  
challenge for 275  
hierarchical structure 276  
layers 288  
matrix, cellulose 288  
practical character
- cost 289
- eco-friendly character 290
- formulation and practical design  
289–290
- safety 289
- soluble matrix materials 287–288
- summing  
evidence of synergism 291  
linkages 292–293  
load distribution 292  
nano effects 293  
rule of mixtures 290–291  
thermoplastic matrix 287  
thermoset resins 287  
woven fabric 289
- hybrid shish–kebab (HSK), formation of  
558
- hydrogels 509
- hydrogen bonding 418–420
- hydrolysis  
with gaseous acids 22–23  
with metal salt catalyst 23  
with solid acids 22  
TEMPO-mediated oxidation 24
- hydrophobic cellulose nanopaper 744
- i**
- Imerys process 781
- immobilization of biomolecules 825
- impregnation 257–258
- infrared carbonyl absorption band 592
- infrared spectra 597
- infrared spectroscopy (IR) 70–71
- inhalation  
cellulose dust 699  
OECD TG 403, 699  
physical responses 699
- inherently conducting polymer (ICP)  
816
- inorganic silicon alkoxide (TEOS) 596
- interfacial crystallization 556, 558
- intumescent coatings 254–255
- inverse complex permittivity 637
- ionic liquids (ILs) 29–30
- ionic strengths 135–136
- isocyanates 343
- isothermal crystallization 567–571



- activation energy in 570–571
  - Avrami model 569–570
  - parameters 569
  - PHBV 563
  - Izod impact test 387
- j**
- Jeziorny model 572, 574–577
- k**
- Kenaf fibers 460
- l**
- laser light scattering (LLS) 69–70
  - laser scanning confocal microscopy 367
  - latex based polymers 222
  - layer-by-layer (LbL)
    - assembly 131–134
    - deposition, of nanofibers 670–671
    - thermoplastic cellulose nanocomposites 186–187
  - Leidenfrost effect 740
  - lignin 763
  - limiting oxygen index (LOI) 258–259
  - linear thermal expansion 542
  - linen 762
  - liquid crystalline (LC) assembly 125
  - liquid crystal structures 134
  - liquid epoxidized
    - natural-rubber-toughened unsaturated polyester (LENR/UPR) 538
  - liquid natural-rubber-toughened unsaturated polyester (LNR/UPR) 534, 538
  - liquid nitrogen freeze-drying method 739
  - liquid propane freeze-drying method 739
  - liquid repellent nanocellulose coatings, on paper 745
  - low density polyethylene (LDPE) 589
    - nanocomposites 538
  - Lyocell™ filament microfiber 749
  - lysine diisocyanate (LDI) 343, 355
- m**
- magnetic glycerol drop 752
  - maleated polypropylene (MAPP) 618
  - maleation 347
  - maleic anhydride (MA) 343
  - Maxwell–Wagner–Sillars (MWS) effect 636
  - measurement challenges, for cellulose nanomaterials 687
  - mechanical pulping 772
  - melt-compounding methods 187
  - melting compounding technique 409–413
  - melting temperature 535
    - of cellulose nanocomposites 538, 541
  - melt processing technique 532–534, 556
  - membrane filtration system 776
  - mesoporous chiral nematic bilayer PF resin film synthesis 810
  - mesoporous photonic cellulose (MPC) film 803–808
    - mesoporosity 806
    - optical characterization 806
    - properties 803
    - sensing performance 807, 808
    - structural characterization 804–805
    - two-step synthesis 804
  - methacrylate graft co-polymerization 347
  - methacryloxy-propyl trimethoxysilane (MPMS) 601
  - methyated CNCs 822
  - microcrystalline cellulose (MCC) 9–10, 823
  - microfibrillated cellulose (MFC). *see* cellulose nanofibril (CNF)
  - microfibrils 178
  - microfluidizer 14–15
  - micro-Raman experiment 611
  - microscale combustion calorimetry (MCC) 261
  - microscopic techniques
    - nanocellulose labeling 378–384
    - nanocomposite fracture 384–389
    - optical microscopy 366–369, 377

- mineral-based reinforcement
  - characteristics 276–277
  - compatibility 282–283
  - elastic modulus 281–282
  - fire resistance 278–279
  - force to failure 280–281
  - gas barrier 280
  - intercalation effects 283–284
  - thermal conductivity 279–280
  - thermal stability and resistance 279
  - toughness 282
  - water-uptake reduction 277–278
- modified atmospheric packaging (MAP) 653
- moisture barrier properties 664
- moisture sorption, in nanocellulose 665
- multiwall carbon nanotubes (MWCNT) 148
- n**
- nanocelluloses 525, 583, 595, 651, 667
  - aerogels 147–151, 651
  - amorphous cellulose preparation 24–25
  - artificial 56
  - based composites characterization, spectroscopic techniques
  - nanocomposites based polymer networks 590–591
  - organic–inorganic hybrid materials 595–602
  - organic soluble polymeric matrices 589–590
  - polyurethanes 591–595
  - water-soluble polymeric matrices 583–589
- characterization 78–86
- chemical functionality 245
- classification 9
  - ANC 13
  - CMF 11
  - CNC 11–12
  - CNF 11
  - CNY 13
  - MCC 9–10
- CNC preparation 18
  - acid hydrolysis 18–22
  - hydrolysis 22–24
  - TEMPO-mediated oxidation method 24
- CNF/CMF preparation 13
  - cryocrushing 17
  - grinding 15–16
  - high-pressure homogenization 13–14
  - HIUS 17–18
  - microfluidizer 14–15
- CNF preparation, enzymatic hydrolysis 24
- crosslinking agents 110–113
- crystallinity 615–616
- esterification
  - acetylation, with acetic anhydride 103–104
  - with carboxylic acid 104–105
  - gas phase esterification 105–107
- fiber spinning 151
- gas barrier property 653
- in hemicellulose based materials 672–673
- hydrogels, drying of 738
- hydrophilicity of 657, 658
- LbL 132
- lowering water vapor sorption 664–666
- mechanical properties 133
- morphology of 655
- nanoyarn preparation 25–26
- polymerization of 668
- polymers, grafted 110
- preparation 246
- pretreatment 27
  - alkaline-acid-alkaline 28
  - bleaching 28
  - enzymatic pretreatment 28–29
  - ionic liquids 29–30
  - oxidation 30–32
  - partial esterification 34
  - pulping processes 27–28
  - steam explosion 32–33
- Raman spectroscopy 610–612, 616
- relative humidity 658

- self-assembled nanocomposites 139–147
- silylation 107–109
- structural features for absorbing water 655–656
- surface roughness and oil/water adsorption of 667
- with surface-sulfonated functionality 113–116
- swelling properties of 656–657
- the crystal and thermal conduction properties of 545–546
- thermal conductivity of 545
- thermal degradation 527–532
- thermal expansion coefficient of 543
- thermal stability 248, 249
- thermal transitions of 536–537
- tunable sorption ability, modification of 664–669
- water absorption 657–658
- water holding capacity 655
- water repellency 665
- nanocellulosic-reinforced polymeric films 651
- nanocomposite hydrogels, chiral nematic structure formation in 812, 813
- nanocomposites 584
  - applications 617–618
  - CNCs 618–620
  - CNFs 620–621
  - based polymer networks 590–591
  - biopolymers use in 628
  - cellulosic fibres for 629
  - characterization of 583
  - description 628
  - films 464
- nanocrystalline cellulose (NCC). *see* cellulose nanocrystals (CNCs)
- nanocrystallites 53
  - aggregation phenomenon 55
- nanofiber-coated microfibers 749
- nanofibers, layer-by-layer deposition of 670–671
- nanofibrillated cellulose (NFC) 302, 630. *see also* cellulose nanofibril (CNF); nanofibrillated cellulose (NFC); natural rubber/nanocellulose based green nanocomposites
- aerogels 660, 738
  - drying process 661
  - mechanical properties 660
  - shape recovery behavior of 663
  - solvent exchange 661
  - TEMPO-oxidized cellulose fibers 660
  - tert*-butanol and water mixing 661
  - tert*-butanol exchange 661
  - vacuum/rapid freeze drying 660
- microparticles 753
- with tunable oleophobicity 666–667
- nanofibrillation 555
- nanofibrils
  - of BNC 89
  - lateral size 54, 55
- nanofilms 592
- nanindentation 451
- NANO LCRA 714
  - for cellulose nanomaterial exposure assessment 691–693
  - hazard identification 691
  - risk framework 690–691
- implementation 690
- risk assessment 690
- screening-level assessment 690
- nanomaterials (NM) 446
  - defining risks 689
  - EHS issues 684–686
  - life-cycle risk assessment 690–693
  - physical and chemical characterization of 688–689
- nanometric particles 256
- nanoparticles, characterization of 583
- nanotechnology 177
- nanoyarn preparation 25–26
- natural fibers, heat diffusion in 526
- natural polymer matrices
  - CNC 314
  - CNF 307–308
- natural rubber (NR) 500
  - latex 628
  - properties 628

- natural rubber/nanocellulose based
    - green nanocomposites 630, 752
    - Cole-Cole diagram 638
    - complex impedance 639
    - conduction phenomenon 636
    - dielectric measurements 631–632
    - dielectric permittivity and loss,
      - temperature dependence of 634–642
    - dipolar relaxation 636
    - dynamic mechanical analysis 631
    - electric modulus 637
    - equivalent circuit parameters 641
    - interface thickness 642
    - interfacial adhesion 635
    - interfacial polarization 636–638
    - NFC and CNC suspensions 630
    - Nyquist diagram 638
    - Nyquist plots 639–640
    - polarization strength 639
    - polymer matrix 630
    - relaxation phenomenon 635
    - strain at break 634
    - strength 634
    - stress–strain curves 633
    - swelling properties 632–633
    - $\tan \delta$  curves 635
    - tensile properties 633–634
    - tensile tests 631
    - thermo–mechanical properties 634–635
    - water polarization 636
    - water uptake 630–631
    - Young modulus 634
  - neutralized suspensions 775
  - NIOSH recommended exposure limits (RELs) 698
  - NMR spectroscopy 600
  - noncrystalline
    - structural characteristics 54
    - structural state 54
  - non-fluorinated aerogel 743
  - nonisothermal crystallization
    - DSC thermograms and relative crystallinity 571–572
    - Jeziorny model 572–575
    - Ozawa model 575–577
  - parameters 574
  - nucleation 562
  - Nylon 6 reinforce 467
- O**
- occupational exposure and risk
    - British Standards Institute 697
    - manufacture activities 693
    - NIOSH 696–697
    - production activities 693
    - SDS gap analysis 697–698
  - occupational exposure limit (OEL) 697
  - occupational hazard/toxicity data 699–701
  - optical microscopy 366
  - optical transparency 195–196
  - organic acids 536
  - organic-inorganic hybrid materials 595–602
  - organic soluble polymeric matrices 589–590
  - organic solvents, use of 589
  - Organization for Economic Cooperation and Development (OECD) Test Guideline (TG) 699
  - organogel films 416
  - organo-mica-cellulose films 671
  - ortho*-positronium (o-Ps) 593
  - oscillatory rheometry 489–490
  - oxidation 30–32, 113
  - oxygen barrier mechanism, for packaging 669
  - oxygen permeability (OP) 653, 669
  - oxygen transmission rate (OTR) 654, 669
  - Ozawa model 575–577
- P**
- PEO-BC nanocomposites 587
    - TGA and DTG of 531
  - permeability measurement 654
  - $^1\text{H}$ ,  $^1\text{H}$ ,  $^2\text{H}$ ,  $^2\text{H}$ -perfluorodecyltrichlorosilane (PFOTS)-coated NFC 667
  - pharmaceuticals, cellulose
    - nanomaterials in 821–825
  - PHBV/CNC nanocomposites 562

- PHBV crystallization 562  
 phenol-formaldehyde (PF) resin film  
     synthesis 810  
 photonic hydrogels 811–815  
 photonic nanopaper. *see* mesoporous  
     photonic cellulose (MPC) film  
 pH sensitivity 785  
 physical storage, of dry cellulose  
     nanomaterials 688  
 plant fiber, structure and chemical  
     composition 5  
 plant protein 315  
 PLA/PBAT composites, non-isothermal  
     crystallization of 669  
 poly(hydroxyalkanoate) (PHA)  
     562–563  
 poly(L-lactide) (PLLA) 407  
 poly(lactic acid) (PLA) 404, 503  
     crystallization of 564  
 poly(methylmethacrylate) (PMMA)  
     538  
 poly(oxyethylene) (POE) 563  
 poly(vinyl alcohol) (PVA) 507, 584  
 polyacrylamide (PAM) 496–497  
 polyaniline (PANI) 816  
 polyaniline (PANI)-nanocellulose  
     particles 598  
 polycaprolactone (PCL) 311–313, 411,  
     460, 595  
     crystallization of 564  
     nanofibers 460  
 polycaprolactone-based waterborne  
     polyurethane (PCL-based WPU)  
     538  
 polyethylene (PE) nanocomposites 589  
 polymer crystallization process  
     555–556, 570  
     presence of fibers 556  
     spherulites 555  
 polymeric isocyanate 593  
 polymeric materials 543  
 polymeric methylene diisocyanate  
     (pMDI) 591  
 polymers, crystallization in 558  
 polymethylmethacrylate (PMMA) 378  
 polymethylsilsesquioxane-cellulose  
     nanofiber (PMSQ-CNF) 417  
 polyoxyethylene (PEO)  
     CNC films  
         melting characteristics 568  
         preparations of 566  
     CNF films  
         melting characteristics 568  
         preparations of 566  
     crystallization, CNCs and CNFs  
         effects on  
             isothermal crystallization  
                 567–571  
             materials and methods 565–567  
             melting 567  
             nonisothermal crystallization  
                 571–577  
     films, melting characteristics 568  
     TGA and DTG of 531  
 poly (methyl vinyl ether-co-maleic  
     acid)-poly (ethylene glycol)  
     (PMVEMA-PEG) 590  
 polysaccharide hydrogels 495–496  
 polystyrene/bacterial cellulose (PS/BC)  
     nanocomposites 533  
 polyurethanes  
     CNC/PU nanocomposites 591  
     nanocellulose/waterborne  
         polyurethanes composites 595  
 polyvinyl acetate (PVAc) 412, 461  
 porous carbon materials 818–819  
 porous cellulose nanofiber structures,  
     acetylation of 665  
 positron annihilation lifetime  
     spectroscopy (PALS) 592  
 precipitated calcium carbonate (PCC)  
     pigments 745  
 protofibrils 801  
 pulping 27–28  
 pyrolysis combustion flow calorimetry  
     (PCFC) 261–262
- q**  
 Q-NFC nanopaper 656
- r**  
 380-Raman crystallinities 612, 615  
 CNC crystallinities (CrI)  
 determination 615

- Raman effect 610
  - Raman imaging 611
  - Raman spectroscopy (RS) 71, 610, 612
    - of bleached kraft pulp fiber 616
    - CNCs and CNFs 612–617
    - crystallinity 615–616
    - orientation of nanocelluloses 616–617
    - of wood pulp CNCs and CNFs 613
  - rayon 762
  - receding contact angles 735–737
  - reinforcements
    - cellulosic 284–285
      - compatibility 285–286
      - effects 286
      - fiber agglomeration 285
      - low density 285
    - mineral-based 276–277
      - compatibility 283–284
      - gas barrier 280
      - fire resistance 278–279
      - force to failure 280–281
      - intercalation effects 284–285
      - modulus of elasticity 281–282
      - thermal stability and resistance 279
      - thermal conductivity 279–280
      - toughness 282
      - water uptake reduction 277–278
  - resorcinol-formaldehyde (RF) aerogels 659
  - responsive chiral
    - actuators 809–811
  - responsive photonic hydrogels 811–815
  - rheology
    - CNF 485
    - definition and significance 482
    - influence
      - of processing conditions 490
      - structure and morphology 490–494
    - and liquid crystal phase transition 486
    - monitoring 509
    - oscillatory rheometry 489
    - theory of polymer 483
  - robust liquid-repellent surface
    - development 751
  - rubber nanocomposites
    - applications 227–228
    - latex mixing 222–223
    - matrix polymers
      - cross-linked 221–222
      - natural 219–220
      - synthetic 220–221
    - mechanical properties 226–227
    - morphology 225
    - solution casting 223
    - solvent interaction 225–226
    - two roll mill mixing 223–224
  - rubber-toughened cellulose/organoclay nanocomposite coatings 753
  - Ruland method 765
- S**
- Safety Data Sheet (SDS) gap analysis 697–698
  - scanning electron microscope (SEM) 370
  - Segal method 766
  - Segal-WAXS 615
    - CNC crystallinities (CrI) determination 615
  - self-cleaning superhydrophobic coatings 753
  - semicrystalline polymers 556
  - shish-kebab crystalline, structure of 556
  - short CNF (SCNF) 620
  - silanes 344
  - silane-treated CNC (STCNC) 534
  - silica aerogels 738
  - silylated cellulose nanocrystals (SCNC) 407
  - silylated NFC foams 600
  - silylated NFV foams 601
  - single crystal diffraction 764
  - single wall carbon nanotubes (SWCNT) 149
  - small angle neutron scattering (SANS) 192
  - small angle X-ray scattering (SAXS) 192

- sodium hypochlorite product literature 791
  - sodium hypochlorite reaction 783
  - soft segments (SS), crystallization of 592
  - solution blending method 401–409
  - solution casting 223
  - solvent-free esterification, of CNC surface 668
  - solvent-resistant NFC films 665
  - sorption 73–74
  - spectroscopic techniques 583
    - nanocellulose-based composites characterization
    - nanocomposites based polymer networks 590–591
    - organic-inorganic hybrid materials 595–602
    - organic soluble polymeric matrices 589–590
    - polyurethanes 591–595
    - water-soluble polymeric matrices 583–589
  - spherulites 555, 556
  - spray-dried CNC powder, dustiness measurements of 696
  - steam explosion 32–33
  - styrene/ethylhexyl acrylate (ST/EHA), miniemulsion copolymerization of 601
  - substrates, for flexible electronics 819–821
  - sulfonation 113
  - sulfuric acid method 18, 767–768
  - supercritical-dried cellulose aerogels 738
  - supercritical drying 738
  - superhydrophobic films 747
  - superhydrophobic silica aerogels 738
  - superhydrophobic surfaces 732
  - superoleophobic surfaces 732
    - of NFCs 666
  - super water absorbing nanocellulose aerogels 658. *see also* cellulose nanofibril (CNF), aerogels
  - surface chemical modification techniques 532
  - surface degree of substitution, of acetylated CNF 665
  - surface treatment 256–257
  - surface wettability 737
  - sustainable electronics
    - chiral mesoporous carbon films 818–820
    - organic semi-conducting materials 816–818
    - substrates for 819–821
  - swelling, of composite hydrogels 813, 814
  - synthetic polymers 584
  - synthetic rubber based bionanocomposites 220–221
- t**
- Technological Association of the Pulp and Paper Industry (TAPPI) 725
  - TEMPO-mediated oxidized cellulose nanocrystals 594
  - TEMPO-oxidized CNC 463
  - TEMPO-oxidized nanocellulose (TOFN) 599
    - coupling reaction 589
  - tensile strength 386
  - tensile testing 449–451
    - natural rubber/nanocellulose based green nanocomposites 631
  - tension buckling 809
  - terminal cellulose synthesizing complex 763
  - terpyridines 143
  - tetracycline hydrochloride (TET) 822
  - 2,2,6,6-tetramethyl-4-hydroxypiperidine-1-oxyl (TEMPO) 30, 782
    - and chemical pretreatments 782
    - commercial plant concerns 790–791
    - disintegration 790
    - homogenizers 790
    - mass balance for recovery 788–790
    - primary alcohol oxidation 782–783
    - reaction kinetics 784–786
    - recovery and reuse 787–788
    - shear sensitivity 787



- 2,2,6,6-tetramethyl-4-hydroxypiperidine-1-oxyl (TEMPO) (*contd.*)
- thermodynamics 786–787
  - water retention measurement 787
- thermal analysis (TA) 525, 566
- thermal conductivity 544
- of cellulose nanocomposites 545–546
  - of nanocellulose 545
- thermal degradation 525
- of cellulose 526
  - of cellulose nanocomposites 532–534
  - of nanocellulose 527–532
- thermal expansion, behaviors of acrylic resin matrix and nanocomposite 544
- thermal expansion coefficient (TEC) 541
- of cellulose nanocomposites 543–544
  - of nanocellulose 543
- thermal stability 248, 249
- of cellulose 527
  - of CNF 528
  - of sulfuric acid 531
  - of wood fibers 526
- thermal transitions 534
- of cellulose nanocomposites 538
  - of nanocellulose 536
- thermoanalytical methods 71
- thermogravimetric analysis (TGA) 72, 193, 313, 526, 531–533
- thermomechanical pulp kinetic data, limitations of 784
- thermoplastic cellulose nanocomposites
- advantageous features 179
  - casting/evaporation 182
    - from aqueous medium 182–183
    - from non-aqueous liquid medium 183–186
  - characterization techniques 190
    - mechanical properties 192–193
    - morphological properties 190–192
    - optical transparency 195–196
    - thermal properties 193–194
  - electrospinning 186
  - LbL 186–187
  - melt-compounding methods 187
  - performance influencing
    - factors 187
      - fiber aspect ratio 188–189
      - fiber dispersion 187–188
      - fiber-matrix adhesion 188
      - fiber orientation 189
      - fiber volume fraction 190
    - potential applications 196–197
    - processing techniques 180–187
- thermoplastic starch (TPS) 307, 401, 497
- thermoset-cellulose nanocomposites 250
- applications 262–263
  - fire retardancy 238–239
  - flammability properties 251
  - polimers 239–242
  - structure and properties 250
- thermosetting polymers 239–242
- TiO<sub>2</sub>-coated nanocellulose aerogel 740, 742
- TiO<sub>2</sub> (anatase) nanoparticles 597
- tissue engineering scaffolds 824–825
- TOCN films 744
- transcrystallization (TC) 556, 558
- transmission electron microscope (TEM) 370
- transmittance spectra 592
- tridecafluoro-1,1,2,2-tetrahydrooctyl)-trichlorosilane 741
- tunable gas barrier nanocellulose composite fabrication 669–673
- two roll mill mixing 223–225
- U**
- underwriters' Laboratories (UL-94) test 259–260
- unplasticized xylan-NFC films 672
- unsaturated polyester (UPR) 538
- US National Institute of Occupational Safety and Health (NIOSH) 696, 697
- UV-Vis spectroscopy 600

**V**

- vacuum freeze-drying method 739
- Valonia ventricosa* 765
- vapour-driven Marangoni propulsion  
743
- viral inhibitors 822
- viscometry of dispersions 76

**W**

- water absorption capacity 652
- water absorption composites 651
- waterborne polyurethanes (WBPU)s  
404, 595
- water retention measurement 787
- water-soluble polymeric matrices  
583–589
- water vapor permeability (WVP) 653
- water vapor sorption 652–653
- water vapor transfer rate (WVTR) 653
- water vapour transmission rate (WVTR)  
324
- WBPU composites 596
- Wenzel state droplet 734
- wettability 733
- wetting
  - characterization, principles of
    - contact angle hysteresis 735–737
    - surface wettability 737
    - Young equation 733–735

- on rough surface 734
  - on solid surface 733
- wide-angle X-ray diffraction (WAXD)  
418
- wide-angle X-ray scattering (WAXS)  
57
- wood-based NFC 665

**X**

- X-ray diffractograms (XRD) 325, 583,  
584, 590, 598
  - for alginate and alginate compounds  
585
  - for CNC 585
  - silver dendritic nanostructure 599
  - silver nanoparticles 599
- X-ray photoelectron spectroscopy (XPS)  
595
- X-ray scattering methods
  - crystallinity calculation 61
  - nanocrystallites 59
- X-ray spectroscopy 587, 592
- xylans 672

**Z**

- ZnO embedded nanostructured  
cellulose acetate fibrous  
membranes 750, 751

