

Index

a

- activated ester-amine
 - azlactones 195
 - MAC2AE brushes 196
 - PGMA films 198
 - PMSSQ 195
 - poly(2-vinyl-4,4-dimethylazlactone) (PVDMA) 198
 - poly(NHS4VB) brushes 195
 - PPFMA brushes 195
 - reactive PMSSQ–PPFPA films 197
 - switchable chromophores 196
- aligned azobenzene-based films 42–43
- A3MA polymer 46, 47, 50
- amorphous fluoropolymers 187, 190
- atomic force microscopy (AFM) 145
- Au–S self-assembly 208–209
- azide–alkyne cycloadditions 201–202
- azlactones 195
- azobenzene-modified liquid crystal (Azo-LC) polymer coatings
 - azimuth angle 86–87
 - continuum-mechanics-based finite element 87
 - default input parameters 93
 - director-dependent light absorption and isomerization 92
 - dual wavelength illumination 114
 - fingerprint coatings
 - cholesteric phase 105
 - 3D topography images 109
 - experimentally 3D confocal microscopic measurement 108
 - out-of-plane deformations 110
 - polarization optical microscope image 107
 - random fingerprint films 108
 - sinusoidal-like textures 106–107
 - surface topographies 106
 - human haptic feedback technologies 114
 - light penetration 93–94
 - linearly patterned coatings 99–101
 - cholesteric pitch length 102–103
 - in-plane dimensions 101–102
 - transition area 104–105
 - material constant 112
 - photo-mechanical model
 - constitutive equations 90–92
 - light penetration model 88–90
 - polydomain coatings
 - Arithmetic Average Height 97
 - aspect ratios 97
 - average height variation 98
 - dimensionless parameters 95
 - 3D surface topographies 96
 - fluorinated acrylates 95
 - Marangoni effect 96
 - modulation depth 97
 - motivation to generate 94–95
 - predicted roughness parameters 99
 - shapes of domains 98
 - topographical features 95
 - roughness parameters, comparisons of 110–112
 - schematic overview 87–88
 - tilt angle 86–87

- azobenzene-modified liquid crystal
 - (Azo-LC) polymer coatings
 - (*contd.*)
 - variation of the average height 113
 - Wenzel roughness 110
 - Young's moduli 92
- azobenzene moiety 3, 4, 6
- azobenzene monomer (A6MA) 41–42

- b**
- bending, of hydrogels 138
 - walkers and swimmers 138
- bending process 15
- bent film 9
- biodegradable polymers 150, 151
- biomaterials 151

- c**
- cholesteric pitch length 102–103
- clamped 60- μm LCN film 39–40
- colloidal lithography technique 26
- copolymerized fluorinated monomer 127
- Copper-catalyzed azide–alkyne cycloaddition (CuAAC) reaction 201
- cross-linked liquid-crystalline polymers (CLCPs)
 - azotolane-containing CLCPs 18
 - cis*-azobenzene molecules 18
 - CW NIR-light-induced deformation 19–20
 - deformation induced by visible and NIR light 18–22
 - ferroelectric CLCP film 15–16
 - ferroelectric liquid crystals 14
 - homeotropically aligned films 13
 - macro-scaled actuators 22–25
 - micro-scaled actuators 23, 25–29
 - monodomain nematic CLCP 3
 - monodomain nematic side-on CLCPs containing azobenzenes 4, 6
 - monomer chemical structures 19
 - partially free-standing CLCP films 14
 - photoactive azobenzene moieties 18
 - photochemical phase transition 2–4
 - photochromic molecules 18
 - photodeformable CLCP/CNT nanocomposite films 10
 - photoinduced bending movements 4–12
 - bending and unbending behavior 10–11
 - diacrylate cross-linker 5
 - experimental setup 9
 - hydrogen-bond CLCP films 7–8
 - linearly polarized light 6–7
 - liquid-crystal monomer 5
 - main-chain CLCP fiber 10, 12
 - monomers 10, 12
 - one-step electron beams 8
 - photoresponsive behavior 8
 - photoresponsive molecule-containing film 4
 - plausible mechanism 4, 7
 - polydomain CLCP film 6
 - polyethylene substrates 9
 - rubbing direction 5
 - three-dimensional movement 4
 - photoinduced contraction and expansion 3–6
 - photoinduced twisting movements 10, 13–14
 - PtTPBP&BDPPA-containing polyurethane film 21
 - red-light controllable composite film 20
 - spacer groups 17
 - spontaneous polarization 15
 - surface alignment treatment 13
 - trans–*cis* isomerization of the azobenzene moieties 4–5
 - triplet–triplet annihilation 20

- d**
- 3D microstructuring 137
- DR1A polymer 46, 49, 52
- dynamic friction behavior
 - fingerprint texture, coating with 125–126
 - home-built measuring system 124–125
 - linear protrusions 128–132

- polydomain texture, coatings with 126–128
- dynamic tribology, liquid crystal coatings
 - dynamic friction behavior
 - fingerprint texture, coating with 125–126
 - home-built measuring system 124–125
 - linear protrusions 128–132
 - polydomain texture, coatings with 126–128
 - haptic applications 123
 - humidity-driven adhesive pads 124
 - responsive surface topographies 123
 - static friction coefficients 133–134

e

- electric-driven micro-actuator 44–45
- electrocapillarity 186
- electrofluidic arrays 187–188
- electrofluidic devices 190
- electrowetting effect
 - dielectric properties 175
 - effect of gravity 177–178
 - ideal and non-ideal electrowetting behavior 178–179
 - material configuration and basic electrical circuit 176
 - parallel-plate capacitor 175
 - reversible modulation 177
- electrowetting materials
 - fluoropolymer surface
 - activation/reflow cycle 183–184
 - Cytop and Hyflon reflow 186
 - physical and chemical modification 184
 - RIE treatment effect 184
 - thermal reflow effect 185
 - inorganic insulators 181–182
 - lithographic patterning 183
 - oil effect 182–183
 - Teflon 180–181

f

- fingerprint coatings
 - cholesteric phase 105

- 3D topography images 109
 - experimentally 3D confocal microscopic measurement 108
- out-of-plane deformations 110
- polarization optical microscope image 107
- random fingerprint films 108
- sinusoidal-like textures 106–107
- surface topographies 106
- fluoropolymer surface
 - activation/reflow cycle 183–184
 - Cytop and Hyflon reflow 186
 - physical and chemical modification 184
 - RIE treatment effect 184
 - thermal reflow effect 185

g

- γ -ray irradiation 211

h

- home-built friction measurement tool 124–125
- human haptic perception
 - compliance
 - discrimination 237–238
 - free sorting 237
 - hand movements 241
 - matching experiment 238
 - two-and three-dimensional search 239–241
 - experimental methods
 - auditory information 226
 - discrimination experiment 226
 - matching experiments 227
 - ordering and sorting 227–228
 - search paradigm 226–227
 - roughness
 - discrimination and identification 234–235
 - hand movements 233–234
 - ordering experiment 229–231
 - saliency 236
 - sorting experiment 228–229
 - tactile sense 236
 - three-dimensional search 232–233

- human haptic perception (*contd.*)
 - two-dimensional search 231–232
 - vibrations and pressure distribution 236
 - temperature
 - hand movements 245–246
 - heat flow discrimination 242–243
 - search experiments 247
 - thermal diffusivity discrimination 243–244
 - three-dimensional search task 244–245
- human-machine interfaces 57
- human perception upon touch 57
- hydrogel actuators
 - bending, of complex structures 141–142
 - biocompatible and biodegradable hydrogels 137
 - biomaterials 151
 - cell swelling/shrinking 137
 - complex deformation 138
 - 3D microfabrication 150–151
 - hydrogel bilayer
 - long-and short-side rolling 139
 - rectangle bilayers 140
 - volume changes 139
 - imaging devices 146
 - intrinsic anisotropy 143–145
 - microfluidic devices 147–148
 - patterned hydrogel film 141
 - photolithography and molding 137
 - sensors 145
 - smart lenses 145–146
 - stimuli-responsive surfaces 151–152
 - switchable coloration 146–147
 - walkers and swimmers 148–150
- Hydrogel polyNIPAAm films 161
- hydrogen bonding (H-bonding) 205
- 2-hydroxyethyl methacrylate (HEMA) 209
- i**
- industrialization 188–190
- inkjet printed liquid crystal cilia
 - chiral-nematic/cholesteric phases 36
 - elastic modulus 36
 - inkjet printing actuators 44–53
 - light stimulated deformation 41–44
 - MEMS applications 36
 - monolithic molecular order 36
 - polymers 35
 - principle of photopolymerization 35–36
 - processing tools 35
 - shape deformation 37
 - thermal actuation 37–41
- inkjet printing actuators
 - all-polymer micro-devices 45
 - A3MA 46
 - bimorphing structures 51
 - cis-A3MA 52
 - crossed polarizers 49
 - deformation of inkjet printed cilia 49–50
 - device design 48
 - DR1A 46
 - electric-driven micro-actuator 44–45
 - elementary actuator design 45
 - inkjet printable monomer formulations 45–46
 - large-amplitude actuators 47
 - LC elastic constants 46
 - MEMS components 44
 - micro-patterning techniques 48
 - microscope images of
 - micro-structured cilia 49–50
 - non-liquid crystal design 44–45
 - splay-bend molecular organization 47
 - strain 50
 - wavelength-controlled motion in
 - artificial cilia 51–52
- inorganic insulators 175
- in-plane dimensions 101–102
- in situ* polymerization methods 210
- ionic liquids 167

k

- kinetic friction coefficient 125, 130
- kinetic friction force 129

l

- LC glassy polymers 92
- light stimulated deformation 41–44
- linearly patterned coatings 99–101
 - cholesteric pitch length 102–103
 - in-plane dimensions 101–102
 - transition area 104–105
- linear protrusions, LC coatings 128–129
 - angular dependence of the friction force 131
 - aspect ratio 130
 - directional depended friction forces 131
 - direction-dependent kinetic friction 129
 - friction dynamics 130
 - kinetic friction coefficient 130
 - kinetic friction force 129
 - maximum kinetic friction coefficient 131
 - mutual orientation of protrusion lines 129
 - orthogonal alignment 131–132
- linear thermal expansion coefficients 38
- Lippmann regime 178
- liquid-crystalline polymer (LCP) 3
- liquid crystal network coatings
 - azobenzene-modified linear polymer films 58
 - 3D cross-linked polymers 58
 - dynamic topographic structures 57
 - formation of aliquid crystal network 59
 - mechanical properties 57
 - mechanism of surface deformation 73–79
 - microfluidic devices 57

- photo-induced surface deformation
 - (see photo-induced surface deformation, LCN)

- photo-responsive liquid crystal networks 61–62
- reactive mesogens 59
- rubbed polyimide 59
- thermal-responsiveness 60–61
- topographic textures 57
- wave-like surface deformation 58
- wettability of surfaces 57

- low critical solution temperature (LCST) 151–152, 160

m

- macro-scaled actuators 22–25
- magnetic plates 143
- Michael addition reaction 10
- Michel-Lžvy interference color chart 73
- microrobot 23–24
- micro-scaled actuators
 - azobenzene CLCP microarray 27
 - colloidal lithography technique 26
 - contact angle 25
 - light-regulated adhesion switch 23
 - microwalker 28–29
 - optical properties 27–28
 - PDMS-soft-template-based
 - secondary replication process 25–26
 - photoresponsive 2D microarray 26
 - polydimethylsiloxane-soft-template-based
 - secondary replication 25
 - superhydrophobic adhesion
 - switchable surfaces 25
 - thermal dual-responsive inverse opal films 27
 - water contact angle 26
- 60- μm -thick LCN film 39–40
- monolithically oriented (single domain)
 - and densely cross-linked polymer networks 37

n

- nanoparticles 146
- natural actuators 144
- N*-isopropylacrylamide 160

p

- patterned cholesteric LC polymer
 - coating 61
- patterned hydrogel film 141
- PDMS-soft-template-based secondary replication process 25–26
- photoactivated micropump 23, 25
- photochemical phase transition 2–4
- photochromic dyes
 - poly(acrylic acid) 162
 - spiropyran incorporation 161
- photo-induced eigenstrains 91
- photo-induced surface deformation, LCN
 - actuation principle 62–63
 - azobenzene-containing blend 65
 - azobenzene moieties 71
 - chirality 63
 - chiral-nematic alignment and isotropic orientation 66–67
 - chiral-nematic coating 64–65
 - chiral-nematic polymer network 63–64
 - continuous cholesteric LC 63
 - continuous indium tin oxide conductive layer 68
 - fingerprint analysis 71
 - fingerprint texture 69–70
 - fluorinated acrylate monomer 72
 - in situ* polymerization of LC monomers 66
 - interference microscopy 67–68, 73
 - isotropic polymer network 65
 - Marangoni effect 70
 - Michel-Lžvy interference color chart 73
 - photomask 66
 - photo-responsive effect 70
 - photo sensitivity 63
 - planar polyimide orientation layer 68
 - polarization microscope image 66–67
 - polydomain pattern 72
 - thermal-induced deformation 64
 - two-step polymerization 68
 - UV irradiation 68
- photoinduced twisting movements 10, 13–14
- photo-mechanical model
 - constitutive equations 90–92
 - light penetration model 88–90
- photopolymerization 210
- photoresponsive 2D microarray 26
- photoresponsive hydrogel films
 - cell culturing 169
 - chemical components 169
 - light induced heating 161
 - microfluidic devices
 - autonomous chemical detection systems 163
 - ionic liquids 167
 - NIPAAM 165
 - N,N*-diethylacrylamide (NDEAm) 165
 - self-cleaning surfaces 165
 - sensor platforms 163
 - sheet-like poly(Sp-NIPAAM) hydrogel films 164
 - spiropyran–NIPAAM–acrylic acid hydrogels 164
 - N*-isopropylacrylamide 160
 - photochromic dyes 161–163
 - photoresponsive cell adhesion 167–169
 - photoresponsive wettability 167
- photo-responsive liquid crystal networks 61–62
- photo-responsivity tensor 91
- physisorption 203–204
- planar uniaxial aligned LCN 39
- poly(acrylic acid) (PAA) 162
- polydimethylsiloxane-soft-template-based secondary replication 25
- polydomain coatings
 - Arithmetic Average Height 97
 - aspect ratios 97
 - average height variation 98
 - dimensionless parameters 95
 - 3D surface topographies 96
 - fluorinated acrylates 95
 - Marangoni effect 96
 - modulation depth 97
 - predicted roughness parameters 99

- shapes of domains 98
- topographical features 95
- polyelectrolytes 204
- polyfunctional LC monomers 59
- Poly(Sp-NIPAAm) hydrogel films 168
- post-polymerization modification (PPM)
 - polymer brushes
 - activated ester-amine 195–199
 - azide–alkyne cycloadditions 201–202
 - chemical and physical properties 194
 - covalent attachment 194
 - grafting from method 194
 - grafting to method 194
 - nitroxide-mediated polymerization (NMP) 194
 - physical deposition and covalent immobilization 194
 - thiol-based reactions 199–200
 - reactive polymer layers (*see* reactive polymer layers)
- PtTPBP&BDPPA-containing polyurethane film 21
- r**
 - reactive mesogens (RMs) 59
 - reactive polymer layers
 - Au–S self-assembly 208–209
 - electrochemical polymerization 206–207
 - γ -ray irradiation 211
 - in situ* polymerization methods 210
 - layer-by-layer self-assembly 204–206
 - photopolymerization 210
 - physisorption 203–204
 - plasma treatment 209–210
 - seed polymerization 210
 - self-polymerization of dopamine (PDOPA) 207–208
 - ultraviolet-ozone (UVO) and X-ray sources 210
 - reversible LC-isotropic photochemical phase transition 3–4
 - rubbed polyimide 59
- s**
 - seed polymerization 210
 - self-assembly 205
 - self-cleaning coatings 169
 - self-folding films 150–151
 - self-polymerization of dopamine (PDOPA) 207–208
 - sensors 145
 - soft actuators, CLCPs
 - macro-scaled actuators 22–25
 - micro-scaled actuators 23, 25–29
 - soft robotic fingers 126
 - spiropyran 164–166
 - stimuli-responsive hydrogels 145
 - synthetic actuators 144
- t**
 - thermal dual-responsive inverse opal films 27
 - Tinuvin 75
 - triplet–triplet annihilation (TTA) 20
 - two-photon photolithography 137
- u**
 - upconversion luminescence (UCL) 19
 - upconversion nanophosphors (UCNPs) 19
 - UV exposure 7, 168
- v**
 - 2-vinyl-4,6-diamino-1,3,5-triazine (VDT) 168
- w**
 - Wenzel-type wetting regime 167

