

## Index

### a

amorphous limit 222

### b

Boltzmann transport equation (BTE)  
63

boron-doped nanocrystalline silicon  
223

boost converter 182

buck converter 180–182

### c

capacitively-coupled (CC) etching  
systems 73

chemical vapor deposition (CVD)  
67–68

cold finger effect 102

continuity equations 130–132

cooling technologies 154–156

CuO thin film 298

### d

deposition methods

electrochemical deposition (ECD)  
216

inkjet printing 213

lithography 214

molding technique 213–214

screen-printing technique 213

vacuum depositions techniques

MBE technique 215

MOCVD 216

sputtering deposition 215

thermal evaporation 214–215

vapor–liquid–solid (VLS) growth  
216–217

dye-sensitized solar cell (DSSC)  
292–294

### e

elastic thermoelectric polymers 48

electrical contact resistance 117–121

electrical insulator plates 127

electrical power output 128

electrochemical deposition (ECD) 216

electroencephalography (EEG) system  
218

electron beam lithography (EBL) 72

*Electronic Resonance States* approach  
221

energy absorption/release processes  
133

*Energy filtering* technique 223

### f

flyback converter 184–185

focused high-energy ion beam (FIB) 72

fractional open circuit voltage  
189–191

functionally graded materials (FGM)  
concept 3

### h

half-Heusler (HH) alloys 22–23

heat equation 132

heat exchangers

cold side heat exchanger 150–154

conductive heat transport 96

constant input heat flux 136

constant power 136

in TEG systems 148–150

- heat flux sensors
  - design parameters 248
  - detectivity  $D$  242–243
  - features 249
  - ice sensor 269–274
  - integral sensitivity  $S_a$  240
  - laser power meter 274–278
  - microcalorimetry 268
  - modern sensors 235
  - noise-equivalent power (NEP) 242
  - noise level 241
  - physical properties 248
  - radiation heat flux sensors 257
  - real design, features of 255
  - self-calibration method 243–247
  - sensitivity  $S_e$  241
  - sensitivity threshold 241
  - sensors performance
    - Seebeck coefficient typical
      - temperature dependence 264
    - sensitivity temperature dependence 261–263
    - sensors sensitivity, calibration of 259
    - thermal resistance 263–264
  - thermal resistance  $R_T$  241
  - thermal time constant 243
  - thermoelectric material, properties of 251
  - thermoelectric modules
    - application 238
    - dimensions of sensor 254
    - miniaturization 237
    - pellets form-factor 251
    - pellets number 254
    - Seebeck effect 237
    - thermoelement height 252
    - units and characteristics 234–235
- high-resolution transmission
  - electron microscopy (HRTEM) image 27
- i**
  - ice sensor 269–274
  - incremental conductance (IC)
    - method 189
  - infrared thermography 207
  - inkjet printing 213
- l**
  - laser ablation 68
  - laser flash analyze/laser flash
    - method 103
  - laser power meter 274–278
  - lead chalcogenides 2
  - lithography 214
- m**
  - macroscopic composites 62
  - maximum conversion efficiency 152
  - maximum power generation 152
  - maximum power point tracking (MPPT) 301
  - metal organic chemical vapor
    - deposition (MOCVD) 216
  - microcalorimetry 268
  - microchannel heat exchangers 156
  - modulation doping 223
  - molding technique 213–214
  - molecular beam epitaxy (MBE)
    - technique 68, 215
  - Mott's formula 41
  - MPPT-methods
    - fractional open circuit voltage 189–191
    - incremental conductance (IC)
      - method 189
    - perturb and observe (P&O)
      - method 187–188
- n**
  - nanoprecipitates (NPs) 59
  - nanostructured materials
    - bulk nanostructured materials
      - $\text{Bi}_2\text{Te}_3$ -based nanocomposites 20–21
    - interfacial contact resistances 29
    - mechanical properties 29
    - PbTe-based nanostructured
      - materials 21–22
    - stability, temperature gradients 28–29
  - nanostructured oxide materials
    - n-type oxides 28

- p-type oxides 26–28
  - ZT improvement
    - band bending concept 17
    - decouple thermopower and electrical conductivity 17
    - low thermal conductivity 16
    - nanocomposite system 17
    - PbS-Ag nanocomposite 18
    - PGEC concept 17
    - phonon scattering 17
    - Seebeck coefficient 16
  - nanostructured silicon
    - electrical transport 63–66
    - nanometric defects 63
    - phonon transport 66
    - power factor 63
  - nanowire geometry 73
  - nanowires 15
  - noise-equivalent power (NEP) 242
  - n-type polybenzimidazobenzophenanthroline (BBL) 47
- O**
- 3 Omega method 105
  - organic thermoelectric materials 223–225
- P**
- parasitic resistance 127
  - Peltier effect 135
  - perturb and observe (P&O) method 187–188
  - phase separation effects, IV-VI alloys 1–6
  - photoresists 216
  - plasma enhanced vapor deposition (PECVD) 68
  - photovoltaic-thermoelectric hybrid
    - energy conversion
      - cost of TEG 286
      - dye-sensitized solar cell (DSSC) 292–294
      - energy loss 285–286
      - feasibility 289
      - fishnet meta-structure, IR band trapping 299–300
      - full-spectrum photon management 300–301
      - generated power and efficiency 285
      - geometry optimization 297–298
      - green building applications 303
      - novel hybrid solar system 303
      - overall heat conductions and light absorptions 298–299
    - photovoltaic-thermoelectric hybrid energy conversion (*contd.*)
      - PV efficiency 285
      - solar cells (SC) performance 303–306
      - solar concentrator 294–296
      - solar spectrum energy utilization 283
      - TEG efficiency 285
  - polycrystalline silicon 57–60
  - polycrystalline silicon nanowires 76
  - poly-methyl methacrylate (PMMA) 72
  - power electronic converter
    - boost converter 182
    - buck converter 180–182
    - electric isolations 180
    - flyback converter 184–185
    - inductor voltage and capacitor currents 181
    - magnetic coupling 178
    - MPPT-methods
      - fractional open circuit voltage 189–191
      - incremental conductance (IC) method 189
      - perturb and observe (P&O) method 187–188
    - requirements 193
    - specification 192–193
    - transfer functions 194–196
    - transformer 178
  - power factor (PF) 60, 62, 63, 222
  - power output 130, 137–139
- R**
- radiation heat flux sensors 257
  - radioisotope thermoelectric generators (RTGs) 77
  - reactive ion etching (RIE) 73

**S**

screen-printing technique 213  
 Seebeck coefficient 37, 60, 101–103,  
 152, 223, 235, 245  
 and charge carrier mobility 44–45  
 and electronic structure 41–43  
 Seebeck effect 37, 237  
 self-calibration method 243–247  
 semi-crystalline bipolaronic polymers  
 43  
 sensitivity threshold 241  
 SiGe alloys 77–79  
 silicon  
 bottom-up nanowires  
 catalyst deposition methods  
 70–71  
 catalyst materials 69–70  
 chemical vapor deposition  
 technique 67–68  
 laser ablation 68–69  
 material properties and  
 thermoelectric efficiency 71  
 molecular beam epitaxy (MBE)  
 68  
 solution based techniques 69  
 bulk and thin-film silicon and SiGe  
 alloys 77–79  
 degenerate and phase-segregated  
 silicon 60–63  
 nanocrystallinity and second-phase  
 formation 56  
 nanostructured silicon  
 electrical transport 63–66  
 energy harvesting 79–83  
 nanometric defects 63  
 phonon transport 66  
 power factor 63  
 nanowires and nanolayers 55  
 polycrystalline silicon 57–60  
 single-crystalline silicon (scSi)  
 57–60  
 thermoelectric generators (TEGs)  
 57–60  
 thermoelectric sensors 57  
 top-down silicon nanowires

material properties and  
 thermoelectric efficiency  
 75–76

preparation strategies 71–75

single-crystalline silicon (scSi) 57–60

single-junction device 286

skutterudites materials 24–26

solar concentrator 294–296

solar energy 286

solar power spectrum 300

soldering process 128

solution-liquid–solid (SLS)

process 69

spark plasma sintering (SPS) 23, 61,  
 115

supercritical-fluid-liquid–solid (SFSL)  
 processes 69

super-lattice systems 15

**t**

TDTR measurement 104

TEG system

channel hydraulic diameter, effect of  
 167–168

cold side heat exchanger 150–154

conversion efficiency 148

flat-plate heat exchanger vs. cross-cut  
 heat exchanger 164–167

governing equations 157

heat exchanger inlet/outlet plenums  
 158–162

heat exchanger performance 150

heat recovery 148

heat transfer coefficient 150

isothermal boundary conditions 148

micro- and nano-thermoelectric  
 materials 148

modified channel configuration  
 162–163

power-efficiency map 168

power generation 150

section design optimization 169  
 and thermoelectric power system

design 148

waste heat recovery systems 148

- tetrakis(dimethylamino)ethylene (TDAE) 45
- tetra-methyl-ammonium hydroxide (TMAH) 74
- thermal conduction 224
- thermal contacts 142
- thermal evaporation 214
- thermal resistances 242
- thermal time constant 243
- thermal transport
  - conductive heat transport 96
  - via* convection 94–96
  - via* radiation 94
- thermoelectric generators (TEGs)
  - CMOS circuit 57
  - cost of 286–287
  - deposition methods
    - electrochemical deposition (ECD) 216
    - inkjet printing 213
    - lithography 214
    - molding technique 213–214
    - screen-printing technique 213
    - vacuum depositions techniques 214
    - vapor–liquid–solid (VLS) growth 216–217
  - efficiency of 38
  - elastic thermoelectric polymers 48
  - human body heat source
    - conduction heat transfer 205
    - infrared thermography 207
    - Seebeck effect 206
    - theoretical and experimental methods 206
  - n-type organic conductors 47
  - PV devices 289
  - Seebeck effect 37
  - thermal and electrical considerations 208–212
  - thermal flow design approach 217
  - wearable devices 218–220
- thermoelectric interfaces/junctions
  - bismuth telluride based systems 115
  - conventional thermoelectric module 111
  - electrical and thermal contact resistances
    - power output 114
    - Seebeck coefficient 113
    - Seebeck voltage 113
    - ZT* reduction 113
  - electrical contact resistance 117–121
  - infrared microscope 121–123
  - soldering/brazing processes 115
  - spark plasma sintering (SPS) 115
  - thermoelectric module fabrication 111
- thermoelectric materials 5
  - bismuth chalcogenides 39
  - bulk nanostructured materials
    - Bi<sub>2</sub>Te<sub>3</sub>-based nanocomposites 20–21
    - half-Heusler (HH) alloys 22–23
  - interfacial contact resistances 29
  - mechanical properties 29
  - PbTe-based nanostructured materials 21–22
  - skutterudites materials 24–26
  - stability, temperature gradients 28–29
- CNT 40
- conducting polymers 38
- efficiency of 18
- electrochemical transistor 45
- nanostructured oxide materials
  - n-type oxides 28
  - p-type oxides 26–28
- neutral/undoped conjugated polymers 39
- n-type thermoelectric materials 18
- Onsager–Callen-relation 93
- organic and inorganic semiconductors 38
- organic conductors 38
- physical properties 221
- p-type materials 18

- radioisotope thermoelectric generators 39
  - Seebeck coefficient
    - and charge carrier mobility 44–45
    - and electronic structure 41–43
  - thermal transport 94–96
  - thermoelectric power factor 40
  - $ZT$ -value
    - electrical conductivity 98–101
    - Seebeck coefficient 101–103
    - thermal conductivity 103–107
  - thermoelectric micro-generator 79
  - thermoelectric modules 114, 191, 192, 283
    - characterization 128
    - constant heat input and constant  $\Delta T$  144–145
    - constant power 136
    - cooling technologies and design challenges 154–156
    - coupled and comprehensive simulation 157–168
    - efficiency 139–142
    - electrical and thermal contact resistance 112
    - electrode/leg junction 128
    - energy fluxes and heat equation 132
    - heat exchangers design, in TEG systems 148–150
    - microchannel heat exchangers 156
    - miniaturization 237
    - particle fluxes and continuity equation 130–132
    - power output 137–139
    - Seebeck effect 237
    - soldering process 128
    - thermal contacts 142
    - thermocouples 144
    - thermopiles 276
    - thin film solar cell 300
    - Thomson effect 135
    - transfer functions 194–196
    - transformer 178
    - transmission electron microscopy (TEM) 62
- V**
- vacuum depositions techniques
    - MBE technique 215
    - MOCVD 216
    - sputtering deposition 215
    - thermal evaporation 214
  - van- der- Pauw method 100
  - vapor–liquid–solid (VLS) growth 216–217
- Z**
- $ZT$ -value 1, 15, 38, 53, 97, 106, 112, 113, 141, 148, 208, 221, 285
    - electrical conductivity 98–101
    - Seebeck coefficient 101–103