

Index

a

AC cut-off 237–238, 240
 AC transformer 446–452
 agricultural operating areas 399, 402
 air distance 345, 437, 467, 468
 air terminal 373–377, 387–389
 ambient temperatures of light fixtures 402
 antenna systems 389
 asynchronous motor 467–489

b

back-up lighting 416
 backup protection 123, 126, 245, 309–319
 bath and shower room areas 399, 402
 battery charging capacity 422
 battery space 422, 433
 breakdown torque 469, 471
 breaking capacity 7, 23, 57, 242, 245, 248, 255–259, 264, 268, 310, 311, 315, 318, 331, 401
 Buchholzrelais 459
 Busbar Protection 138–140

c

c/k value 360, 370
 cables 269
 and lines 11, 13, 78–79, 87, 254, 264, 265, 270, 271, 274–283, 321, 328, 332, 333, 336, 400, 427, 487
 list 30
 camping vehicles, boats and yachts 403
 CE-conformity 352
 central battery systems 423–427

choking factor 363, 365
 circuit diagrams 16, 27–29, 49, 51, 72, 437, 473
 circuit group 452–454
 circuit-breakers 7, 13, 57, 66, 101, 120, 121, 123, 138, 166, 237, 238, 244–245, 247–249, 256–261, 264, 266, 304–307, 310, 312, 314–319, 348, 402, 473, 480
 classification 58, 241, 242, 244, 254, 346, 405
 coincidence factor 12–14, 16, 226, 285
 color reproduction 401, 413
 compensation 355
 for asynchronous motors 359
 central compensation 355
 for discharge lamps 359–360
 group compensation 355
 individual compensation 355
 with nonchoked capacitors 362–363
 permanent compensation 355
 for transformers 358–359
 conductor systems 32–36
 conductors 268
 down conductors 375
 earthing conductor 155, 165, 168, 169, 177–178, 189–191
 PE conductor 84, 157
 construction details 27, 29
 contactors 7–8, 244, 348, 353, 355, 473, 477, 479, 480
 continuous current carrying capacity
 of busbars 279, 296
 of overhead lines 279, 296

- correction factors
 - for deviating ambient temperatures 285
 - creepage distance 345
 - current carrying capacity 263, 270
 - of cables 276–280
 - current selectivity 309, 312, 314
 - current transformers 121, 123, 124, 133, 135, 140–141, 457
 - cut-off condition 223
 - IT system 227
 - TN system 222–223
 - TT system 224–226
 - cut-off currents of overcurrent protective equipment 229–230
 - cut-off times 228–229
- d**
- Dahlander circuit 480, 481
 - damp areas 399
 - data blocks 405–412
 - DC current installations 21–24
 - DC cut-off 237
 - decrement factors 181
 - differential protection 121, 129–133, 138, 140, 141, 459
 - differential relays 131–133
 - direct switch-on 243, 468, 473–475
 - disconnect switches 260–261
 - distance protection 121, 130, 133–137, 141, 489
 - distribution of luminous intensity 405
 - DMT 129–131
 - documentation 16, 28, 30, 122, 351
 - double earth fault 51, 161, 164–166, 188
 - down conductors 375
 - dry rooms 399, 400
 - duty classes 254
- e**
- Earth 155
 - current 170–172
 - electrode 155
 - fault current 156
 - resistance 155
 - rods 175–177
 - short-circuit current 156
 - earthing arrangement 21–22, 155
 - earthing calculation 199–217
 - earthing conductor 155, 165, 168, 169, 177–178, 189–191
 - earthing switches 7
 - earthing system 155, 156, 158, 159, 161, 163–165, 169, 170, 172, 173–175, 178, 183, 184, 186, 187, 193, 217, 347
 - economic analysis 409–412
 - efficiencies 406, 412, 459
 - electric arc 22, 235–241, 249, 251, 257, 259, 260, 315, 476
 - electrical operating areas 421, 422
 - electrical water heating 294–300, 15
 - EMC lightning protection zones 392–395
 - emergency light fixtures 417, 430
 - emergency lighting 403, 417, 425, 430
 - emergency lighting circuits 403
 - energy law 443
 - Engineering Services Manual 27
 - equivalent voltage source 68, 70–72, 488
 - errors of measuring instrument 228–229
 - exposure distance 371, 387–389
 - exterior lighting 413–415
 - exterior lightning protection 371, 374–392
- f**
- factor η 272
 - filter circuits 355, 365, 366
 - floating circuit 417, 432
 - flood law 441, 442
 - foundation earthing 157, 177, 186–187
 - frequency transformer 458–459
 - function class 251, 254
 - functional descriptions 29
 - fuse links 260, 261, 312, 348
 - fuses 13, 15, 16, 66, 101, 104, 129, 138, 166, 235, 242, 243, 245, 248, 250–257, 260, 261, 284, 309–312, 315, 316, 330, 331, 402, 473, 474, 480
- g**
- garages 400
 - generator behavior 469
 - generator node 68, 69, 143, 144, 154

- generators 3, 6, 31, 32, 36, 50, 57, 58, 61, 68, 72, 74, 75, 79, 87, 123, 131, 149, 160, 239, 240, 355, 435–440
- glare restriction 401
- ground electrode
 buried ground electrode 381–382
 concrete-footing ground electrode 383–385
 minimum length 385–386
 ring ground electrode 382–383
 surface ground electrode 380
- ground potential rise 199, 372, 373
- ground reference plane 372
- ground resistance
 buried ground electrodes 380
 of ring ground electrodes 382–383
- ground termination network 372
- grounding resistance 175, 176, 190–192, 224–228, 379, 385, 386–387, 488
- grounding system 159, 199–204, 206, 371, 372, 374, 375, 379–386, 389
- grouped battery systems 427–429
- groups of motors 76, 78
- h**
- harmonics 11, 13, 168, 355–365, 367
- hoisting gear 403
- i**
- idle voltage 448, 449
- IEEE Std. 80 157, 178–182, 190–194, 199, 203–217
- illuminance distribution curves 407
- illumination level 400, 401
- impedance corrections 58, 79–81, 111–112
- impedance phase angle 224
- induction law 31, 442
- inductor-capacitor units 363–365
- influenced short-circuit current 343
- initial short-circuit 67
- initial symmetrical short-circuit 12, 58, 59, 71, 73, 74, 76, 78, 79, 82, 89, 161, 272
- installation schedule 30
- interior lighting 399–400
- interior lightning protection 371, 392–397
- iron 10, 141, 443, 445, 446, 449, 451, 459, 460, 463, 465, 466
- iron losses 10, 449, 451, 459, 465
- Isolated earthing 162–163
- IT Systems 222, 226–228, 333, 487
- l**
- lamps 399
 discharge lamps 359–360
 low-voltage halogen lamps 415–416
- layout of overload protection equipment 265, 266
- let-through energy 249, 267, 303
- light fixtures 399, 400, 402–409, 412–414, 417, 419, 421, 424, 426, 428–430, 432
- lightning protection class 371, 373–374, 388, 390
- lightning protection system 15, 27, 199, 217, 371–397
- line length 92, 266, 294, 295, 321, 330–335, 416
- liquid-level circuit -breakers 259
- load factor 10, 275, 276, 302, 349–351, 459, 486
- load interrupter switches 260
- load node 68, 69, 143–151
- load profiles 9–10
- load switch 242
- loading 239, 241, 249, 251, 260, 263, 275, 284, 306, 355, 356, 358, 415, 454, 472
- loading capacity
 under fault conditions 271–273
 under normal operating conditions 270–271
- localized lighting 400
- location diagram 29
- loop impedance 83–85, 134, 222–226, 229, 487, 488
- loop resistance 90, 228–232, 293, 485
- low-voltage halogen lamps 415–416
- low-voltage systems 9, 10, 197, 217, 235, 324, 347, 383, 397
- luminous flux distribution 405–406

m

magnetic dispersion 443
 main earthing bar 156
 main protection equipment 248–249
 main switch 242, 244, 249, 251
 mark of origin 401, 408–409
 material lists 30
 medium voltage 1, 3, 5, 6, 8, 28, 29, 73,
 120, 138, 140, 141, 184, 197, 260,
 261, 312, 329, 441, 488
 meter mounting boards 248, 249–251,
 294, 295, 297, 299, 334, 335
 modelling 401
 motor behavior 469
 motor gear system 472–473
 motor protection 103, 105, 138, 243, 244,
 473, 482
 motor protective relay 474, 477, 479,
 480
 motor protective switches 242–244

n

negative-sequence 76, 83
 network diagram 29
 network feeders 73–74
 neutral earthing 156, 158, 160–166,
 173
 Newton–Raphson procedure 151–154
 normal lighting 400, 417
 normal workplace-oriented lighting
 400
 Numeric Protection Relays 122–123

o

open air systems 399
 operating areas subject to explosion
 hazards 400
 operating areas subject to fire hazards
 400, 403
 operating errors of measuring instrument
 228, 229
 overcurrent 263
 cut-off currents 229–230
 protection 4, 16, 22–23, 29, 81, 86, 87,
 90, 97, 122, 124–129, 130, 135, 222,
 232, 235–262, 296–298, 305, 306,
 329, 330, 339, 473
 overhung constructions 403
 overview diagram 29

overvoltage arresters 240, 393–395,
 397
 overvoltage protection 371, 395, 459

p

parallel resonant circuit 360, 362
 PE conductor 84, 157
 peak short-circuit 12, 59, 65–66, 71, 76,
 85, 88, 251, 255
 peak short-circuit current 12, 59, 65–66,
 71, 76, 85, 251, 255
 planning values for networks 14, 15
 positive-sequence 75, 76, 78, 79, 82, 83,
 331
 potential control 156
 potential grading ground electrode 372,
 373
 power
 apparent 356
 effective 356–357
 reactive 356–357
 power circuit-breaker 256–258, 264, 266,
 302, 310, 312–319
 power demand 12
 power factor 12, 148, 242, 257, 260, 324,
 355, 356, 359, 366, 368–370, 449,
 459, 480, 489
 power flow 143–154, 196
 power loss 10, 349, 350, 351–353, 355,
 412, 416, 443, 449, 488
 power station blocks 80, 81
 protection
 by cut-off 222–234
 against electric shock 219–234
 against overload 263
 against short-circuit 263
 protective circuit-breakers 244
 pull-up torque 470

r

radial system 8, 9, 11
 rated
 short-time current 264
 rated current 140, 161, 222, 231, 242,
 243, 247, 251, 253, 254, 256, 263,
 264, 271, 279, 280, 294, 296–299,
 309–312, 315, 321, 329, 331, 333,
 338, 344, 345, 349, 350, 352, 353,
 454, 477, 486

- rated current rule 264
 - rated load 281, 282, 348, 451, 471
 - rated short-time current density 263, 303
 - rated torque 29, 471, 480
 - rated voltage 28, 76, 117, 163, 221, 223–225, 227, 241, 242, 253, 257, 269, 343, 347, 358, 446, 455, 457, 460
 - RCD (residual current protective device) 245–247
 - reactive current 97, 99, 355, 357, 467, 469
 - reactive power 13, 16, 38, 39, 45–47, 61, 97–101, 143–146, 153, 355–370, 435, 439, 443
 - recognition width 417, 419
 - reflection factors 401, 403, 404, 406, 412
 - relays 119–124, 126–130, 133, 134, 141, 161, 310, 457, 480, 489
 - remuneration guidelines 27–28
 - residual earth fault current 156
 - resonant circuits 360
 - resonant earthing 163–164
 - room shielding 392
 - rooms with limited conductivity 402
 - rotor frequency 471
 - routing diagrams 29
- S**
- safety and standby lighting 416–422, 432
 - safety lighting 417–421, 423, 425–427, 429, 430, 432
 - sauna facilities 402
 - selecting light fixtures 402
 - selectivity 4, 15, 16, 101, 121, 124, 126, 130, 133, 141, 226, 248, 299, 309–319, 401
 - series resonant circuit 360, 361
 - series resonant filter circuits 365, 366
 - shielding
 - building shielding 392
 - equipment shielding 392
 - room shielding 392
 - shielding angle 373, 375
 - shock hazard protection 331
 - short-circuit
 - category 258–259
 - current 57, 263, 343, 451
 - impedance 57, 65, 66, 72–81, 82, 84, 300, 451
 - strength 87–89, 197, 253, 265, 271, 272, 275, 303–304, 348
 - short-circuit types 59
 - single-pole ground fault 59
 - three-pole short-circuit 59
 - two-pole short-circuit with contact to ground 59
 - two-pole short-circuit without contact to ground 59
 - short-line fault 240
 - single battery systems 429–432
 - single-phase 32, 38, 49, 51, 52, 68, 70, 82–83, 88, 114, 148, 329, 359, 449, 452, 454, 468, 471
 - single-pole short-circuit 58, 78, 81–84, 91–94, 99, 114, 160, 196, 224, 268, 300, 304
 - slack node 143–147, 152, 154
 - slip 31, 76, 435, 467–469, 471, 472, 479, 485
 - smart grid 1, 2, 25–26
 - soft starters 481–483
 - soil resistivity 182–184, 193, 199, 203–205, 372, 381, 382, 386, 387
 - source impedance 84, 223, 333–335
 - space allocation requirements for
 - distribution cabinets 261, 262
 - speed control 479–480
 - speed-torque characteristic 469–471
 - stand-by circuit 417
 - stand-by lighting 417
 - star connection 36–38, 41–43, 47–48, 452, 475–477, 479, 480, 484
 - star delta startup 468, 474–479
 - start-up 473–479
 - startup torque 470
 - static compensation 365
 - in series 367–368
 - thyristor-controlled 366
 - thyristor-switched 366–367
 - Static Protection Relays 122
 - steady-state short-circuit current 59, 76, 87, 88
 - step voltage 157, 159, 162, 172, 192, 200, 204, 207, 212, 371, 373

- substation 6, 119, 155–217, 368
 - substation earthing 155–217
 - superposition method 68, 69
 - swimming pools and baths 399, 402
 - switchgear combinations 343–353
 - switching angle 61
 - symmetrical breaking current 76, 85–87
 - synchronous machines 31, 32, 58, 74–75, 86, 87
 - system power 25, 405
 - systems in furniture 403
- t**
- temperature limit 266, 352
 - terminal and cross-connection diagrams 29–30
 - thermal short-circuit strength 272, 275
 - thermal strength 90, 168–169
 - thermistor protection 459, 481
 - three phase power 38–39, 369, 467
 - three-phase 49
 - system 31
 - transformer 452
 - three-pole short-circuit 59, 67–68, 70, 72, 76, 81–82, 88, 96–97, 196, 240, 245, 268, 317, 488
 - time selectivity 309, 311–312
 - time–current characteristics
 - for circuit-breakers 245
 - for DIAZED (NH) fuses 254
 - for fuse links 261
 - for gG fuses 254
 - of power circuit-breakers 258
 - of selective circuit-breakers (SLS) 249
 - TN system 21, 101, 195, 222–224, 228, 230, 394, 488
 - torque 29, 438–439, 468–480, 489
 - touch voltages 155, 157, 159, 169–173, 175, 179–180, 184, 192, 194, 207, 217, 219, 226, 228, 231–232, 242, 372, 487–488
 - transformer 119, 121, 123, 124, 133, 135, 140–141, 441–466, 489
 - transformer principle 443–444
 - transient voltage 240–241, 257
 - translation 448, 460
 - triangle circuit 37–38
 - tripping rule 264, 302, 305
 - TT systems 16, 222, 224–226, 231, 233, 247, 394, 488
- v**
- vacuum circuit-breakers 7, 259
 - VAr controller 355
 - vector group 452, 454–455, 460, 489
 - voltage drop 12, 16, 25, 44–45, 97–98, 101, 105, 107, 117, 265, 294, 298–299, 301, 307, 321–341, 358, 369, 416, 437, 443, 485–486, 488
 - voltage factor 58, 63, 72–74, 80, 82–83, 224, 332, 488
 - voltage quality 13, 68, 360–365
 - voltage ranges 221
 - voltage transformer 119, 121, 457–458, 489
- w**
- warming 350
 - weak current systems 30
 - wet areas 399
 - winding 10, 31, 66, 67, 75–76, 78, 80, 119, 124, 140, 245–246, 360, 366, 436–437, 441–443, 445–447, 449, 451–454, 457, 459–460, 463–464, 467–469, 473–475, 479–481
- x**
- XGSLab 199–200, 204
- z**
- zero-sequence 75–76, 79, 83, 85, 93–94, 159, 226, 228, 331–332