

Index

a

anisotropic magnetoresistance (AMR)
effect 177, 203, 208, 209

antiferromagnetic (AFM) 52, 55, 122,
139, 177

asymmetric multiferroics 133, 134

b

bandstop filters/attenuators 157,
164–167

BaTiO₃ (BTO) 12, 192

BiFeO₃ (BFO) 5, 8, 70, 94, 178

Bohr magneton 147

Boltzmann's constant 207

c

ceramic composites 12–16, 23
CFO–BTO composite films 20
collinear magnetism 129–130
complementary metal–oxide
semiconductor (CMOS) 185,
207, 213

composite thin films

1-3 type columnar 20–22

organic 29–32

quasi 2-2 type 27–29

two-dimensional multiferroics
32–35

2-2 type laminated 23–27

0-3 structure 22–23

conventional ferroelectricity 123

converse ME effect 5, 6, 18–19

Coulomb (Madelung) interactions 123

Curie temperature 6–8, 10, 19, 20, 33,
55, 73, 93, 130, 135, 176, 204

d

deep reactive-ion etching (DRIE) 159,
228

delay lines 157, 167–168

density-functional theory 124, 128,
130, 150

dielectric permittivity 217

dipole moments 95, 126

direct ME effect 5, 6, 18, 22, 34

domain switching 101, 134, 137, 143,
188

dynamic magnetization 101

dynamic magnetization switching 56,
58–60, 65, 184

Dzyaloshinskii–Moriya interaction 81,
127, 129

e

easy-axis rotation (EAR) 53, 54

eddy current 16, 158, 159, 213, 217,
228

elastic coupling mechanism 140, 141

electrical field (*E*-field) control of
magnetism 55

electrically tunable microwave devices
237, 238

electrical polarization 123, 124, 126,
130–132

electric double layer (EDL) 163

electric-field-dependent FM resonance
spectroscopy 93

- electric-field-induced easy-axis reorientation 53
- electric polarization 5, 23, 27, 51, 67, 98, 99, 123, 128, 129, 144, 146, 179, 193
- electrochemical reaction 29, 30, 103–105
- electrolytic cell 65
- electromechanical coupling coefficient 204
- electrostatic boundary condition 84
- electrostatic doping 29, 30, 104, 162, 163
- EM-spin wave
- coupling 55–65
 - multiferroic composites 239
- exchange bias (EB) 55, 61, 181
- AFM/FM/FE 56–60
 - correlation of 58
 - E*-field control of 59
 - in magnetic heterostructures 55
 - multiferroic composites 239
 - reverse magnetic 63
 - voltage control of 177–184
- f**
- ferrite-film-PMN-PT-substrate system 27
- ferroelectricity 5, 75, 95
- BFO 73, 75
 - conventional 123
 - electronic 125–126
 - geometric 124–125
 - induced by
 - collinear magnetism 129–130
 - noncollinear magnetism 126–129 - and magnetism 71, 123
 - of materials 95–96
 - mechanism for 123
 - in type-I multiferroics 122–123
 - in type-II multiferroics 126–130
- ferroelectric polarization 7, 10, 68, 69, 127–129, 131, 133, 135, 136, 138, 140, 146, 176, 180, 181, 185, 192–196
- ferroelectric random access memories (FeRAMs) 175
- ferroelectric switching
- in BaTiO₃/SrTiO₃ superlattice 137–139
 - in BiFeO₃ 135–137
 - properties 134, 135
- ferroelectric varactors 217, 218
- ferromagnet/ferroelectric interface 66
- ferromagnetic-antiferromagnetic interface 55
- ferromagnetic (FM) magnetization 90
- ferromagnetic resonance (FMR) 19, 107, 213
- bandstop filters/attenuators 164–167
- frequency shifts 19
- frequency tuning 238
- magnetic and magnetoelectric inductors 164, 165
- multiferroic/magnetoelectric antennas 168
- phase shifters and delay lines 167–168
- voltage control of 163, 164
- ionic liquid gating 161–163
 - strain and charge co-mediated 160
 - strain and surface spin torque co-mediated 160, 161
 - strain/stress modulation for materials with in-plane easy axis 158–159
 - strain/stress modulation for materials with out-plane easy axis 159–160
- ferromagnetic shape memory alloys (FSMAs) 183
- ferromagnetic (FM) thin films 23, 27, 55
- ferromagnetism 1, 2, 5, 8, 26, 27, 33, 56, 88, 124, 130, 131, 134, 221
- ferromagnetism/spin 88
- field-effect transistor (FET) 29, 102, 107, 220, 221, 223

- finite-difference time-domain method 168
- first-order reversal curve *I-V* (FORC-IV) 86
- frequency shifts 19, 166
- frequency tuning 219, 238
- g**
- generalized Katsura, Nagaosa, and Balatsky (gKNB) model 127, 128
- geometric ferroelectricity 124–125
- giant magnetoresistance (GMR) 177, 191, 203, 238
- giant ME (GME) 189, 204, 228
- Ginzburg–Landau equation 134
- h**
- Hall effect 203
- hexagonal-boron nitride (h-BN) 32
- i**
- interface magnetoelectric effect 144–146
- inverse magnetostrictive effect 52
- inverse piezoelectric effect 52
- ionic liquid gating 29, 161–163
- ionic-liquid-gating magnetism 30, 104
- j**
- Jahn–Teller effect 94
- k**
- Kittel equation 158
- m**
- magnetic alloy-based composites 15–16
- magnetic anisotropy 2, 18, 19, 27, 29, 51, 52, 56, 61, 64–66, 88, 100, 102, 103, 142, 144–146, 157, 163, 176, 177, 185, 186, 188, 238
- magnetic exchange interactions 129
- magnetic/ferroelectric (FE) bilayer heterostructures 102
- magnetic ferroelectric (FE) materials 2, 52, 98, 107
- magnetic field 5, 10, 78, 180
- magnetic hysteresis loops 5, 6, 9, 22, 24, 28, 56, 57, 59–64, 101, 177, 187, 190
- magnetic impulse 58, 59, 65, 184
- magnetic inductors
- magnetic materials 213–217
 - structures 211–212
- magnetic moments 5, 8, 32, 63, 92, 94, 95, 122, 123, 136, 144, 146, 149, 177, 181
- magnetic random access memories (MRAMs) 1, 29, 175
- magnetic recording 237, 238
- magnetic sensors 16, 204–206
- magnetic tunneling junction (MTJ) 191
- magnetism
- bipolar 33
 - of CFO 20
 - electric-field control of 52
 - of electrodes 27
 - in-plane/out-of-plane 32, 54, 91
 - nonvolatile control of 188–190
 - practical applications for 1–2
 - voltage control of 52, 157, 176–189, 191, 228
- magnetization
- electric field control of 84
 - reversal 55, 61, 64, 88, 101, 141, 184, 185, 191
 - switching 32, 51, 52, 56, 58–61, 63–65, 93, 94, 177, 179, 180, 183, 184, 189, 190, 193, 196, 237–239
 - tunability of 64
- magnetocrystalline anisotropy 52, 65, 66, 79, 84, 148, 150
- magnetoelectric coefficient 140, 144, 147, 149, 150, 163
- magnetoelectric (ME) coupling 1
- degrees of freedom 175
 - effect 157
 - interfacial charge-induced 65–70
 - other novel interfacial 100–109
 - strain/stress-induced 51–55

- magnetoelectric (ME) effect 2, 5–8, 12, 13, 15, 18–20, 22, 32, 34, 66, 67, 76, 77, 84, 90, 98, 124, 129, 134, 144–150, 168, 191, 203, 204
 magnetoelectric inductors 164, 165, 226
 magnetoelectric materials 7, 158, 191, 203, 221
 magnetoelectric random access memories (MeRAM) 55, 71, 176, 177, 237, 238
 magnetoelectric sensor 14, 71, 103, 203, 205–208
 magnetometry measurements 93, 183
 magnetoresistance, voltage control of 177, 191
 magnetoresistive spin value 55
 magnetostatic energy 52
 magnetron sputtering 2, 16, 56, 159, 161
 magnonics 103, 107, 239
 magnon spintronics 103
 Metglas 15–19, 164, 204, 206, 207, 226
 microelectromechanical systems (MEMS) 164, 207, 208, 219–220, 222, 223
 microwave sintering 13
 monolithic microwave integrated circuit (MMIC) 169, 220
 multiferroic devices and applications 237–238
 electrically tunable microwave devices 238
 ferroelectric switching in $\text{BaTiO}_3/\text{SrTiO}_3$ superlattice 137–138
 in BiFeO_3 135–137
 properties 134–135
 first-principles calculation 121–126
 magnetic recording 237, 238
 magnetoelectric random access memories (MeRAM) 238
 ordered perovskite cells 132–134
 phase-field simulation 134–139
 in magnetoelectric composites 140–142
 in single-phase multiferroics 142–143
 strain engineering 130, 131
 type-I conventional ferroelectricity 123
 electronic ferroelectricity 125, 126
 geometric ferroelectricity 124, 125
 ns^2 lone pair stereochemical activity 123, 124
 origins of ferroelectricity in 122, 123
 type-II ferroelectricity induced by collinear magnetism 129–130
 ferroelectricity induced by noncollinear magnetism 126–129
 multiferroic composites exchange bias (EB) 239
 spin wave 239
 multiferroic heterostructure 52 characteristics 2
 interface magnetoelectric effect 144–146
 magnetoelectric coupling 143–150
 spin-dependent screening-induced magnetoelectric effect 146–150
 ultrathin ferromagnetic films 67
 multiferroic/magnetoelectric antennas 168
 multiferroic material 82 BFO system 70–94
 bulk composites 12 ceramic composites 13–14
 converse ME effect 18–19 magnetic alloy-based composites 15–16
 polymer-based composites 16–18
 composite thin films 1–3 type columnar 20–22
 organic 29–32
 quasi 2–2 type 27–29
 two-dimensional multiferroics 32–35

- 2-2 type laminated 23–27
 0-3 structure 22–23
 EM-spin-wave coupling 55–65
 ferroelectric/ferromagnetic hysteresis loops 5
 first-principles calculations and phase field simulations 150
 interfacial charge-induced ME coupling 65–70
 magnetization and polarization in 175
 single-phase 5–11
 spiral spin order control RMnO_3 94–100
 strain/stress induced ME coupling 51–55
m
 multiferroic sensors
 AMR effect 208, 209
 highly sensitive bulk ME sensor 206, 207
 magnetic sensors 204–205
 ME coupling 203–204
 miniature NEMS sensor 207, 208
 multilayer ceramic capacitors (MLCCs) 14
 multiple magnetic resonance 213
- n**
 nanoplate resonator 205, 207–208
 nanoscale electronics 88
 noncollinear magnetism 126–129
 nonvolatile control, of magnetism 188–190
 nonvolatile switching 101, 189
- o**
 organic composite thin films 29–32
 oxygen vacancy 74, 85, 87
- p**
 $\text{Pb}(\text{ZrTi})\text{O}_3$ (PZT) 12
 perovskite cells 132–134
 perovskite-type compounds 7
 phase shifters 88, 157, 167–168, 219, 221
 phase-field modeling 88
 phase-field simulation 134
 of ferroelectric switching properties 134–135
 ferroelectric switching in BiFeO_3 135–137
 ferroelectric switching in $\text{BaTiO}_3/\text{SrTiO}_3$ superlattice 137–139
 in magnetoelectric composites 140–142
 in single-phase multiferroics 142–143
 piezoelectric coefficients 2, 53, 56, 81, 90, 158, 160, 169, 228
 piezoelectric/ferroelectric (FE) 158, 177
 piezoelectric materials 15, 16, 90, 92, 159, 168, 185
 piezoresponse force microscopy 85, 87, 137, 143
 P–N junction 84, 102
 polarization switching 10, 125, 134–136, 175, 196
 polymer-based composites 12, 16–18
 pulsed laser deposition (PLD) 8, 196
- q**
 quasi 2-2 composite thin films 27–29
- r**
 radiofrequency microelectromechanical system (RF MEMS) 219–220, 223
 rare earth manganites 7
 resonance frequency 15, 16, 26
 RF/microwave devices
 in general 163–164
 tunable 94, 157, 164–168
 voltage control of FMR 157–161
 ionic liquid gating 161–163
 Ruddlesden–Popper material 124
 Ruderman–Kittel–Kasuya–Yosida (RKKY) 32
- s**
 scanning probe microscopy (SPM) 86
 silicon-on-insulator (SOI) 159, 219

- single-phase multiferroics 2, 7–11, 95, 126, 140, 142–143
 spark plasma sintering (SPS) 13
 spin-current model 127
 spin detector 68, 192
 spin electronics 71
 spin–lattice–charge–orbit 19
 spin–lattice coupling effect 103, 107
 spin–orbit coupling 100, 101, 127, 128, 188
 spiral spin order control RMnO₃ 94–99
 SrTiO₃(STO) single crystal 8, 19
 standard microfabrication process 166
 strain engineering 19, 51, 130–132
 strain/stress
 effect 107
 FMR voltage control 158–161
 modulation
 in-plane easy axis 158–159
 out-of-plane easy axis 159–160
 strain/stress-induced ME coupling 29, 51–55
 symmetric multiferroics 133, 134
- t**
 tensile stress 56, 168
 Terfenol-D/epoxy (TDE) matrix 15, 17
 transverse piezoelectric constant 204
 tunable bandpass filter 164, 222
 tunable multiferroics 221–236
 FET switches 220–221
 RF MEMS 219–220
 RFIC and MMIC 217–222
- tunneling magnetoresistance (TMR)
 effects 177, 203, 238
 two-dimensional layered materials
 (2DLMs) 32–34
 two-dimensional multiferroics 32–35
- u**
 ultrathin ferromagnetic films 67, 84, 100, 101
- v**
 valence electron 94, 96, 124
 van der Waals heterostructures
 (vdWHs) 33, 34
 vibrating sample magnetometer (VSM) 59
 voltage control
 of domain dynamics 184–188
 of exchange bias (EB) 177–184, 239
 of FMR 157–161, 163
 ionic liquid gating 161–163
 strain/stress 158–161
 of magnetism 52, 157, 176–189, 191, 228
 of magnetoresistance 177, 191
 of perpendicular magnetic anisotropy (PMA) 159
 voltage-induced magnetic anisotropy 66
- x**
 X-ray diffraction 75, 138, 192