

## Index

### a

- agitation method 100–101
- all-solid Li–S cell, with 80Li<sub>2</sub>S–20P<sub>2</sub>S<sub>5</sub> glass 63
- amorphous silica glass, water vapor interaction with 254–257
- anisotropic magneto-resistance (AMR) 146
- annealing methods 93–94
- anodic brightening 212
- anodic leveling 212
- aqueous flow batteries 25, 26
- atmospheric nitrogen dioxide measurement 304

### b

- ball surface acoustic waves (SAW)
  - detected signal of 243
  - expended waveforms 243
  - gas sensor 249–252
    - advantages 246
    - delay time and amplitude 248
    - H<sub>2</sub> concentration 248
    - performance 248
    - principle 245
    - relative amplitude 246
  - generation of 241, 242
  - hygrometer 249
    - appearance 250
    - detection limit 251
    - output wave form of amplitude 251
    - sensitivity 250
    - sensor head and detecting circuit 249
  - propagation around sphere 241
- Barkhausen noise 134
- battery technology readiness levels (BTRL) 20–21
- bench-top batch dewatering system 166

- bis-(sodium-sulfopropyl) disulfide (SPS) 81
- Bleed and Feed operation process 120

### c

- cathodic electropolishing 224, 232, 233
- chalcogenide technologies 76
- chemical additives 206
- chemical sensors
  - atmospheric nitrogen dioxide measurement 304–306
  - networks of instruments 306–311
  - ozone measurement, low-cost instrument for 298–303
  - signal drift detection 303–304
- chemical transformation 12, 13
- clay settling areas (CSA) 160
- Co–Ni–Fe films 141, 142
- Co–Ni–Fe ternary system 140
- coercivity ( $H_c$ ) 130
- compound semiconductors, electrodeposition of
  - Cu–In–Ga co-deposition 93
  - Cu–In–Ga–O co-deposition 92
  - Cu–In–Ga–Se co-deposition 91
  - CuInSe<sub>2</sub> co-deposition 89
- conductivity response, of semiconducting oxides 264
- continuous dewatering operation *See also*
  - dewatering methods
  - final solids content 174, 175
  - power and energy consumption 175
  - schematic representation 174
- copper electroplating
  - wafer-to-wafer reproducibility 109–110
  - within-wafer uniformity 108–109

copper plating, for thin film PV applications 117

Crosscutting Science thrust 13

CuInGaSe<sub>2</sub> (CIGS) thin film solar cells

- annealing of precursor materials 93
- fabrication 95
- gallium electrodeposition 85
- indium electrodeposition 82
- paddle agitation mechanism 101
- paddle plating cell 78
- structure 78

## d

damascene process 79

Dashboard tool 31

data storage devices 129

density functional theory (DFT) 289, 290

dewatering methods 175

- electrokinetic 164
- flocculation 162–163
- lab-scale batch dewatering 165–168
- mechanical dewatering 163

diffusion tube method 251

disruptive technology 143

dual-zone continuous dewatering prototype 185–186

duplex diffusion layer 198

## e

economic assessment, for on-site electrokinetic dewatering

- capital cost 180–184
- hydrogen emission 179–180
- operation cost 181
- power and energy consumption 181
- results 184

electrochemical deburring process

- for automotive planetary gears 212–214
- with highly resistive electrolyte 212

Electrochemical Discovery Laboratory (EDL)

- redox active molecules, stability of 28
- trace water function of 27–28

electrochemical reactions, in sulfur cathode

- Li<sub>2</sub>S<sub>2</sub> reactions 48–49
- Li<sub>2</sub>S<sub>4</sub> reactions 47–48
- Li<sub>2</sub>S<sub>8</sub> reactions 46–47
- production of radical anions 49
- S<sub>8</sub> reactions 45–46

electrocrystallization 204

electrodeposited Cu<sub>2</sub>ZnSn(Se,S)<sub>4</sub> (CZTS) layers 97–99

electrodeposition-based CIGS formation

- process 116
- bath control 116–121
- commercial size 60cm x 120cm modules 116
- paddle-plating cell 101
- plating bath maintenance and reproducibility 120
- steady state operation, of plating bath 120

electrodynamic diffusion layer 200

electrokinetic dewatering methods 164

electrokinetic remediation, of contaminated soil 164

Electrolyte Genome 28–33

electron paramagnetic resonance (EPR) spectroscopy 53–54, 59

electro-osmosis 163

electrophoresis 163

electroplated Fe-P film 140

electroplated permalloy films 130

electropolishing

- cathodic 224, 232, 233
- of INCONEL<sup>®</sup> alloy 718 coupons 215
- of niobium superconducting radio frequency cavities 220, 221, 223–226
- of passive materials 214–216
- of semiconductor valves 216–220
- of strongly passive materials 220–223

Energy Storage Advisory Committee (ESAC) 16

## f

flocculation 162–163

floppy-disk drives (FDDs) 151

flux guide-type TMR heads 148

free water 162

## g

gallium electrodeposition 85

gallium electroplating

- wafer-to-wafer reproducibility 109–110
- within-wafer uniformity 108–109

gas-sensitive resistors

- conductivity response 264
- effective medium approximation model 268–270

general characteristics 263  
 microstructure model 277–284  
 multi-scale modelling 266–268  
 ozone measurement, low-cost instrument for 266  
 percolation and equivalent circuit representation 277–284  
 porous sensors 265  
 semiconducting oxides 261, 262  
 surface defect and reaction models 288–291  
 surface grafting 288  
 surface modification by poisoning 284–285  
 surface segregation 286–288  
 toxic/inflammable gas detection, sensor development for 264  
 giant magneto-resistance (GMR) head 145–147

## h

hard disk drive (HDD)  
   magnetic properties 130  
   magnetic thin films 137  
   small 143–144  
 hard magnetic materials 130  
 Hazard and Training Assessment (HATA) questionnaire 19  
 heat-assisted magnetic recording (HAMR) 138  
 high density floppy-disk drives 151

## i

indium electrodeposition 82  
 indium electroplating  
   wafer to wafer reproducibility 109  
   within wafer uniformity 108  
*in situ* spectroscopic studies, Li–S batteries  
   electron paramagnetic resonance (EPR) spectroscopy 59  
   nuclear magnetic resonance (NMR) spectroscopy 61–62  
   Raman spectroscopy 60–61  
   UV–vis spectroscopy 60  
   X-ray absorption spectroscopy 58–59  
 insoluble anode 118  
 Institutional Leadership Panel (ILP), JCESR 15, 16  
 integrated magnetic circuits 152  
 interstitial water 161

## j

Jacquet viscous salt film model 221, 233  
 Joint Center for Energy Storage Research (JCESR) 9  
   annual in-person workshop 13  
   for battery research and development 11  
   battery technology readiness levels 20–21  
   cell prototype designs 32  
   change decision process 18–19  
   chemical transformation 12–13  
   communication tools 17  
   Dashboard tool 31  
   deliverables 21–22  
   Directorate 15  
   Electrochemical Discovery Laboratory (EDL) 27  
   Electrolyte Genome 28–30  
   executive committee (ExCom) 14  
   genomic calculations 21  
   goal performance metrics 10  
   in-person collaboration forums 17  
   Intellectual Property Management Council (IPMC) 17  
   invention disclosures 21  
   legacy 33–34  
   mission support metrics 21  
   multivalent intercalation 11  
   non-aqueous redox flow 13  
   operational tools 16–17  
   organizational chart 15  
   promoting public-private partnerships 13  
   prototype development 31–33  
   publications 21  
   Rate-Capability tool 31  
   regional outreach events 22  
   research prototypes 22  
   safety 19  
   science engineering initiatives 22  
   scientific tools 22–23  
   screening of redox active molecules 29–30  
   sprint process 16  
   success metrics 21  
   team 13–16  
   techno-economic models 22–26  
   virtual collaboration tools 17

## k

Kolmogorov–Smirnov (K–S) test 309, 311

**I**

- laboratory solar cells, record efficiencies of 77
- lab-scale batch dewatering 165–168
- lithium-ion (Li-ion) batteries 8–9
- lithium polysulfide 66
  - electron paramagnetic resonance (EPR) spectroscopy 53–54
  - Raman spectroscopy 57
  - nuclear magnetic resonance (NMR) spectroscopy 57
  - UV–Vis spectroscopy 54–57
  - X-ray absorption spectroscopy 50–53
- lithium–sulfur (Li–S) batteries 41
  - advantages 43
  - basics of 41–44
  - cathode material design 62
  - charged and discharged 42
  - conventional composite lithium battery cathode 62
  - cycle-life issue 62
  - discharge profile 63
  - electrochemical reactions, in sulfur cathode 44–49
  - fingerprinting lithium polysulfide intermediates 49–57
  - fractional volume change 43
  - in situ* spectroscopic studies 58–62
  - practical considerations 62
  - reactions at electrodes 41, 42
- low-cost instrument development
  - for atmospheric nitrogen dioxide measurement 304–306
  - for ozone measurement 298–303
- low-resistance TMR head 148

**m**

- macrosmoothing 212
- magnetic domain noise 133
- magnetic random-access memories (MRAMs) 145
- magnetic recording devices 129
- magneto-optical drives (MODs) 138
- magneto-optical (MO) recording 138
- magneto-resistive (MR)
  - head 144–145
  - read sensor 131
  - technical advantage 145
  - velocity-insensitive property 144
- maskless exposure technology 249

- mechanical dewatering 163
- metal–air system 23–25
- metal-in-gap (MIG)
  - head 132–133
  - technology 143
- microsmoothing 212
- multi-scale modelling 270
- multivalent intercalation 11, 30–31

**n**

- Nafion membrane 81
- near-field optical recording 138
- networks of instruments, chemical sensors 306
- non-aqueous flow batteries 25, 26
- nuclear magnetic resonance (NMR) spectroscopy 57, 61–62

**o**

- ordered vacancy compounds (OVCs) 90
- ozone
  - dense sensor network 296
  - low-cost measurement instrument 266, 298

**p**

- paddle agitation technique 101–103
- paddle plating cell 101, 102
  - electrical contact 103
  - scaling-up to 15 cm x 15 cm 104–107
  - scaling-up to 30 cm x 60 cm 107
- paddle plating tool 104
- permalloy (Ni–Fe alloy) 130–131
- phosphate fertilizers 161
- phosphate mining 160, 161
- phosphate production 160
- phosphatic clay suspensions
  - electrokinetic dewatering 164
  - electrokinetic separation 163–164
  - flocculation 162–163
  - industrial scope 160–161
  - lab-scale batch dewatering 165–168
  - mechanical dewatering 163
  - scanning electron microscope image 162
  - water from clay difficult 161–162
- photovoltaics (PV) 75
  - annealing methods 93–94
  - electrodeposited CuInGaSe<sub>2</sub> (CIGS) 80–88
  - single Cu–In–Ga–Se–O multicomponent 88–93

plating additives 206  
 polymers of intrinsic microporosity (PIM) 26  
 porous sensors 265  
 pulse current plating process  
   current distribution effects 200  
   current efficiency effects 205  
   ductility of copper specimen 210  
   grain size effects 204  
   mass transport effects 198  
 pulse-echo-overlap method 243  
 pulse reverse current (PRC)  
   electropolishing 216  
   generalized pulse reverse current waveform 197  
   leveling 207  
   plated through-holes (PTH) diameter 206  
   plating 196–205  
 pulse reverse voltage electropolishing process 233

## q

quantum dots (QDs) 3  
 quantum yield (QY) 3

## r

Raman spectroscopy 57, 60–61  
 rapid thermal annealing process (RTP) 94  
 Rate-Capability tool 31  
 Rayleigh wave 241, 244  
   beam width 245  
   diffraction-free propagation around solid sphere 244, 245  
   propagation on spherical solid 244  
 rechargeable batteries 8  
 redox-active macromolecules 26  
 redox reactions 41

## s

scanning interference fringes (SIF) method 241  
 scientific paradigms 193  
 semiconductor/MEMS manufacturing technologies 249  
 semi-continuous dewatering operation *See also* dewatering methods  
   clear supernatant water recovery 168–170  
   continuous operation 172–175  
   power and energy consumption 175–178  
   recover solids 170–172

semi-hard magnetic materials 130  
 Shockley–Queisser (SQ) limit 3  
 signal drift detection 303  
 silicon solar cell structure 78  
 siloxane poisoning 284  
 Small Business Innovative Research (SBIR) programs 194  
 Small Business Technology Transfer (STTR) programs 194  
 soft magnetic materials 130  
 solar cells fabrication 95–97  
 sol–gel silica film, for trace moisture sensors 253–254  
 soluble anode 118  
 spectroscopy techniques, Li–S reaction  
   chemistry 50  
   electron paramagnetic resonance (EPR) spectroscopy 53–54  
   nuclear magnetic resonance (NMR) spectroscopy 57  
   Raman spectroscopy 57  
   UV–vis spectroscopy 54–57  
   X-ray absorption spectroscopy 50–53  
 spin-valve type TMR head 147  
 stress–strain data 211  
 surface finishing, of passive/oxide forming materials 216  
 surface grafting 288  
 surface oxygen vacancy 290  
 surface segregation 286–288  
 sustaining technology 143  
 Systems Analysis and Translation (SAT) thrust 13

## t

techno-economic (TE) modeling 23  
   flow batteries for grid storage applications 25–26  
   of metal–air system, for transportation applications 23–25  
 thermal asperity (TA) 151  
 thermodynamic model 254–257  
 thin-film head technology 129  
   data storage business, in Japan 137–142  
   high-moment head core material 138–141  
   high- $M_s$  write heads 141–142  
   history 132  
   magnetic domain noise 133–136  
   vs. wafer based technologies 76

toxic/inflammable gas detection, sensor  
    development for 264  
transition noise 137  
tunneling magneto resistance (TMR) head  
    Fe/MgO/Fe(001) tunneling junction 150  
    flux guide-type 148  
    vs. GMR head 147  
    infinite MR ratio 147  
    low-resistance 148–150  
    spin-valve type 147  
    thermal asperity 151  
turbidity, of supernatant liquid 169

## **U**

ultramarine pigment 41  
UV-vis spectroscopy 54–57, 60

## **V**

vicinal water 161

## **W**

Wagner number 200, 218  
water hydration 161  
web-based HATA questionnaire 19  
WO<sub>3</sub> sensor 293

## **X**

X-ray absorption spectroscopy 50–53,  
    58–59

## **Y**

yttrium aluminum garnet (YAG) laser  
    242