

Index

a

acid-stable HER catalysts 459, 480
 acoustic sensors, for FTENGs
 399–402
 activated carbon fiber tows (A-CFTs)
 41, 42
 active layer, OSCs 308–317
 acceptor materials 313–317
 donor materials 310–313
 alkali-ion rechargeable battery electrode
 113
N-allyl-*N*-methyl-*p*-nitroaniline dipoles
 223, 224
 aluminum-plastic film 189, 190, 197
 atomic layer deposition (ALD) 51,
 55–57, 61, 251, 257, 276, 361
 attached-electrode-mode TENGs 385,
 386
 Au counter electrode, in QDSSC 365

b

bacterial cellulose (BC) 137, 172
 battery array pack 184, 188, 190,
 203–206
 BDT derivatives 313
 bimodal networks 225, 227
 binder-free TiO₂ colloids 247
 biomass 118, 157, 168, 172, 174, 177
 bismuth telluride (Bi₂Te₃) 427
 bulk heterojunction (BHJ) 306

c

cable-type battery 82, 184, 188,
 199–203

carbazole-based polymer 313
 carbonaceous anodes 71
 carbon-based electrocatalysts 460,
 474, 479
 carbon based HER catalysts 479
 carbon catalysts, for HER 466
 carbon counter electrodes 365–366
 carbon fiber 39, 41, 42, 49, 74, 76, 107,
 114, 157, 164, 166, 369
 carbonized bacterial cellulose (CBC)
 137
 carbon materials 4, 7, 19, 21, 24, 39,
 41, 51–54, 74, 129, 157, 366, 459,
 463, 466
 carbon nanofibers (CNFs) 165
 buckypaper/sulfur/buckypaper
 cathode 163
 conductive porous graphene network
 164
 graphene coating 164
 and metal oxide 166
 PCNFs and Cu nanoparticles 164
 porous carbon nanofiber (PCNF)
 layers 163
 TiO₂ film 166
 carbon nanomaterials 5, 77
 carbon nanotube (CNT) 7, 129, 131,
 132, 157, 159, 161
 CNT-RGO/S 133
 elastic tubular walls of 134
 fiber and yarn supercapacitors 42
 free-standing electrode films 10
 modified PEO 140
 multi-walled CNTs

- carbon nanotube (CNT) (*contd.*)
 - chemical vapor deposition (CVD) 158
 - CNTs-rGO/S cathode 160
 - electronic conductivity and rate performance 162
 - flexible polydimethylsiloxane (PDMS) substrate 160
 - hollow graphene nanospheres 160
 - in situ polymerization and sulfur incorporation 160
 - mesoporous carbon 160
 - polypyrrole 160
 - rate performance and cyclic performance 158
 - nitrogen-doped CNTs 162–163
 - polymer composites 434
 - super-aligned CNTs (SACNT) 162
 - carbon quantum dots 113
 - carbon textiles (CT) 188, 190, 193
 - Cd-based quantum dots 347–348
 - Celgard™ separator 145–148
 - charge-discharge process 67–69, 77, 87, 90
 - charge extraction measurement, in mesoporous-planar hybrid PSCs 300
 - chemical bath deposition 356, 360
 - chemical vapor deposition (CVD) requirements 248
 - wrinkled graphene 15
 - chloropropyl-functional siloxane copolymers 224
 - coaxial wet-spinning assembly strategy 44
 - cobalt redox mediators 268
 - coin cell/Swagelok batteries, flexible lithium-air battery 188–190
 - cathode design 187
 - electrolyte/separator adaptation 188
 - lithium anode protection 188
 - structure of 186
 - cold isostatic pressing (CIP) technique 430
 - commercial P25 TiO₂ paste 245
 - composite polymer electrolytes (CPEs) 138, 143–144
 - conducting polymers (CPs) 4, 6–7, 19, 24, 251, 321, 323, 370, 430, 431, 434
 - conductive filler/elastomer composites 220–221
 - conductive plastic substrates 242
 - conductive polymer (PEDOT PSS) 317–318
 - conjugated polyelectrolytes (CPEs) 432
 - conjugated polymer-based materials 431
 - conventional capacitors 1
 - copolymer PDTP-DFBT 325
 - co-sensitization techniques, for QDs 360
 - cotton tread (CT) 54
 - counter-electrodes, in DSC 251–254
 - Cu-based quantum dots 349
 - Cu(In,Ga)Se₂ thin-film solar cells 349
 - CuInS₂ QDs 342, 349
 - Cu₂S counter electrodes 366–367
 - Cu_xS counter electrodes 367–368
 - Cu₂ZnSn(S_{1-x}Se_x)₄ (CZTS) 369
- d**
- density functional theory (DFT) calculations 114
 - dielectric elastomer actuators (DEAs) 215
 - dielectric elastomer devices 215, 231
 - dielectric elastomer generators (DEGs) 215
 - electro-mechanical conversion 216–217
 - electro-mechanical coupling equations 217–218
 - energy cycle 217
 - examples of 230–231
 - self-priming circuit 229
 - dielectric elastomer ocean wave power generator 230
 - dielectric elastomers (DEs) bimodal networks 227

- chemical modification 223–225
- efficiency 227
- elastomer blends 222
- elastomer composites 219–222
- energy density and conversion
 - efficiency 228
- increasing relative permittivity
 - 219–225
- interpenetrating polymer networks
 - 225–227
- pre-strain technique 229
- Young's modulus 225
- dielectric filler/elastomer composites
 - 221–222
- differential charge density 469
- difluorobenzothiadiazole (DFBT) 325
- disodium rhodizonate salt (DSR) 115
- dispenser-printing method 430
- doctor blading 327
- donor-acceptor (D-A) copolymers
 - 311–313
- dry-etching method 24
- dye-sensitized solar cells (DSCs)
 - characterization 240
 - metallic substrates 241
- e**
- Ecoflex silicone rubbers 387, 414
- elastomer blends 219, 222–223
- elastomer composites 219
 - conductive fillers 220–221
 - dielectric fillers 221–222
- electrical double-layer capacitor (EDLC)
 - 39
- electric field assisted CBD (EACBD)
 - 356
- electro-active polymers(EAPs)
 - classification 215
 - description 215
 - groups 215
- electrocatalysis 187, 365
- electrocatalytic hydrogen evolution
 - reaction 459
- electrochemical double-layer capacitor (EDLC) 2, 7
- electrochemical impedance
 - spectroscopy 476
- electroencephalography (EEG) system
 - 435
- electroless deposition method (ELD)
 - 55
- electrolytes 72
- electrolyte system, in FDSCs 242
- electro-mechanical harvesting scheme
 - 228
- electron-donating dithienopyran (DTP)
 - unit 325
- electronic EAPs 215
- electronic state density, of carbon 460
- electron transporting layer (ETL) 302, 308, 313, 320–321
- electrophoretic deposition (EPD) 247, 359
- electrospinning 132, 133
- electro-spinning techniques 111
- electro-spray deposition (ESD) 18, 247, 248, 359
- electro-spraying techniques 111
- energy-dispersive X-ray spectrometry (EDXS) 194
- energy harvester, FTENGs 388
 - biomechanical energy 388–390
 - water energy 392–393
 - wind energy 391
- energy harvesting mechanisms 429
- ethanol-based TiO₂ paste 246
- ethoxylated trimethylolpropane
 - triacrylate (ETPTA) 79–81
- ethylene thiourea (ETU) 141, 142
- evaporation-technique 283
- ex-situ co-sensitization process, for QDs
 - 360
- ex-situ sensitization techniques 359
- external quantum efficiency (EQE) 307
- f**
- fabricated battery 77, 197, 201, 203, 205
- fabricated sensor system 31
- fabrication methods 18, 252

- fabrication process 9, 10, 12, 19, 54, 81, 172, 177, 197, 200, 222, 226, 249, 251, 438, 443
- facial hydrothermal method 104
- fiber and yarn supercapacitors
 - active/electrode materials 39
 - activated carbon fiber tows (A-CFTs) 41
 - carbon fiber 41
 - carbon materials 41, 52
 - CNT 42
 - coaxial wet-spinning assembly
 - strategy 44
 - electroless plating 40
 - hybrid fibers/yarns 48–51
 - industrialization production 40
 - integrated electronic textile 57–61
 - metallic fiber
 - characteristics 44
 - coaxial SC (CSC) cable 47
 - CuO NWs 47
 - deformation stability 45
 - electronic conductivity and mechanical flexibility 44
 - laminating and metalizing process 44
 - MnO₂ 47
 - nickel-titanium (NiTi) wires 47
 - metallic materials 54–57
 - omni-directional flexibility 39
 - one-dimensional (1D) format 39
 - polyvinyl alcohol (PVA) solution 43
 - pseudocapacitive materials 39
 - two-dimensional (2D) planar
 - configuration 39
 - washability 39
 - weaving and knitting feasibility 39
- fiber-type FDSCs 249–251
- figure of merit 426, 427, 442
- fillers 144, 219–222
- fill factor 271, 297, 307, 346, 440
- first-generation PV cells 239
- flexible devices 10–14, 32, 99, 115, 119, 122, 241, 371, 425, 438, 440, 444, 446
- flexible dye-sensitized solar cells (FDSCs)
 - challenges 251
 - electrolyte and hole-transporting materials 270–276
 - electrolyte composition 272
 - fabrication of 249
 - fiber-type 249–251
 - nanostructured photoactive film 243–249
 - photo-electrodes, flexible substrates for 242–243
 - power conversion efficiency 244, 252
- flexible electrode, OSCs
 - conductive polymer (PEDOT PSS) 317–318
 - hybrid carbon material 319
 - metal nanowires and grids 318–319
- flexible electronics market 425
- flexible Li-S batteries
 - CBC 137
 - discharging capacity 135
 - electrochemical performance 132
 - electrochemical properties 137
 - electrolyte membranes 138–144
 - composite polymer electrolytes 143–144
 - gel polymer electrolytes 142–143
 - solid polymer electrolytes 139–142
 - electrospinning 133
 - fabrication process 130
- flexible cathode for
 - CNTs 129
 - graphene 129, 131
 - S-rGO 129
- mesoporous carbon materials 129
- MFC 134
- requirements 137
- sandwich-structured cathode 135
- separator for 144–148
- S-rGO 129, 130
- tensile strength 132
- working mechanism and challenges

- active materials, dissolution of
 - 128
 - large volume expansion 128
 - shuttle effect 128
 - sulfur, low electronic conductivity of 129
- flexible lithium-air batteries
 - battery array pack 203–206
 - cable-type battery 199–202
 - coin cell and Swagelok battery
 - buckpaper and graphene 188, 189
 - cathode design 187
 - electrolyte/separator adaptation 188
 - flexible energy storage devices 190
 - lithium anode protection 188
 - schematic cell configurations 189
 - structure of 186
 - and conversion devices 184–185
 - development 183–184
 - electrochemical performance 207
 - energy density 207
 - limitations of 207
 - planar battery 190–199
 - schematic cell configurations 186
 - woven-type battery pack 202–203
- flexible microsupercapacitor (fMSC) device 18, 19
- flexible photo-anode films 350
 - high temperature calcination 351
 - metal oxide based photo-anodes 355
 - selection and morphology 351
 - TiO₂ based photo-anodes 351–354
 - ZnO based photo-anodes 354–355
- flexible sodium ion batteries (SIBs) 97–101
- flexible solar cells 340
- flexible supercapacitors
 - conventional sandwiched structure 9
 - flexible substrate supported electrodes 14–18
 - free-standing electrode films 10–14
 - direct printing, of active materials 21–24
 - electrode materials
 - carbon nanomaterials 5–6
 - composite materials 7
 - conducting polymers (CPs) 6–7
 - in-situ synthesis, of active materials 18–21
 - integration 29–31
 - interdigitated architecture 18
 - interdigitated structure 9, 10
 - laser lithography technology 26
 - microelectrodes 9
 - microfluidic etching method 24
 - performance evaluation 28–29
 - plasma etching 24
 - sandwiched stacked and interdigitated planar structure 8
- flexible thermoelectric energy harvesters
 - energy management 439
 - thermoelectric module, architecture of 440–441
- flexible triboelectric nanogenerators (FTENGs)
 - as energy harvester 388–393
 - for hybrid energy cells 409–411
 - material used for 387–388
 - performance of 388
 - for self-charging power units 405–409
 - for self-powered sensors 393–397
 - service behavior 411–413
 - working mechanism and modes of 385–386
- free-standing electrode films
 - CNT 10
 - graphene films 12
 - graphene hydrogels 13
 - rGO thin films 13
 - 3D porous graphene network 13
 - transparent supercapacitor 10
- freestanding-mode TENGs 385, 386
- fullerene derivatives 306, 309, 313–315

g

- g-C₃N₄@x-pGr hybrid graphene 463
- gel polymer electrolytes (GPEs) 79, 115, 138, 139, 142
- glass fabric based flexible thermoelectric generator 437
- Gouy–Chapman model 3
- graphene 7, 43, 129, 132, 136
 - and buckpaper 188, 189
 - electronic and chemical properties of 131
 - films 12
 - foam 169, 171
 - gel film 13
 - hydrogels 13
 - materials 157
 - paper 168
 - porous structure of 147
 - 2D sheet structure 131
 - 3D graphene 134
 - 3D-NG 131, 132
- graphene oxide (GO) 25, 44, 45, 119, 131, 137, 146, 169, 220
- gravimetric energy densities 184
- gravure printing 22

h

- heteroatom (B, S) doped carbon based catalysts, for HER 462–463
- heteroatom-doped carbon metal-free catalysts, for HER 460
- hole transporting layer (HTL) 308, 320
- hole transporting material (HTM) free perovskite solar cells 285
- hybrid carbon material 319
- hybrid energy cells 409–411
- hybrid fibers/yarns 48–51
- hydrogen evolution reaction (HER)
 - activation 477–479
 - carbon-based electrocatalysts 460
 - carbon catalysts 466
 - carbon core shell structure 468
 - cobalt-embedded nitrogen-rich CNTs 468
 - CoNi nanoalloy 469
 - current density 475

- dual/treble doped carbons 463–464
- durability 477
- electrochemical impedance spectroscopy 476
- electrochemical surface area 475
- exchange current density 476
- heteroatom (B, S) doped carbon based catalysts 462–463
- heteroatom-doped carbon metal-free catalysts 460
- H₂ production 477
- metal doped carbon 464–466
- metal organic frameworks 471–474
- NC/Ti 471, 472
- nitrogen-doped carbon based catalysts 460–462
- nonmetal doped carbon for 460–466
- overpotential/onset potential 474–475
- Pt-based electrocatalysts 459
- single shell carbon-encapsulated iron nanoparticles 470
- Tafel plot 476
- hydrothermal assembly process 172

i

- indacenodithiophene (IDT) units 311, 317
- indium tin oxide (ITO) substrate 241
- inkjet printing 21–23, 328, 438, 439, 448
- inorganic solar cells 305
- in-situ co-sensitization process, for QDs 360
- in-situ sensitization techniques 357
- in-situ techniques, of QD sensitizers 356
 - chemical bath deposition 356
 - electrochemical deposition 357
 - spray pyrolysis deposition process 357
 - successive ionic layer adsorption and reaction 356, 357
- intensity modulated photovoltage spectroscopy (IMVS) 286

- intensity modulated voltage spectroscopy (IMVS) 291
 - interconnecting layer (ICL), tandem OSCs 322
 - interfacial engineering, in QDSSCs 360–363
 - interfacial layer, OSCs
 - ETL 320–321
 - HTL 320
 - interpenetrating polymer networks (IPN) 225
 - inverted single junction OSCs 323
 - ionic EAPs 215
 - ionic liquid (IL) 1, 8, 117, 188, 242, 257, 275
 - ITO/PEN-based FDSCs 242
 - ITO/PET-based FDSCs 242
- I**
- laser-etching 26, 32
 - laser lithography technology 26
 - laser-scribed graphene (LSG) 13
 - layer-by-layer (LBL) self-assembly method 169
 - lead chalcogenides 427
 - LiCF₃SO₃/TEGDME 192
 - light-emitting diodes (LEDs) 6, 29, 45, 74, 118, 201, 388, 425
 - Li ionic conductivity 138, 140
 - linker-assisted chemical bath deposition (LACBD) technique 360
 - liquid/gas flow sensors, for FTENGs 402–405
 - liquid-type dye-sensitized solar cells, working principle of 240
 - lithium iodide (LiI) 271
 - lithium ion battery
 - anode
 - carbonaceous anodes 71
 - metal alloy anodes 71–72
 - bendable planar lithium ion batteries
 - carbon paper and car 75
 - CNTs composites 74
 - graphene 77
 - cathode
 - LiCoO₂, layered structure 70
 - LiFePO₄ olivine structure 70
 - LiMn₂O₄ possesses spinel structure 70–71
 - materials 68
 - energy delivery and storage 69
 - fiber electrode
 - CNT fiber possessing 89
 - flexibility and wearability 89
 - MnO₂ nanoparticles 87
 - graphitic carbon 68
 - hollow and spring-like structure 82
 - polymer 79–82
 - stretchable energy-storage devices 84
 - thin copper/aluminum foils 77
- lithium phosphorus oxynitride electrolyte (LiPON) 82
- lithium-air batteries
 - anode of 207
 - battery array pack 203–206
 - cable-type battery 199–202
 - coin cell and Swagelok battery
 - buckpaper and graphene 188, 189
 - cathode design 187
 - electrolyte/separator adaptation 188
 - flexible energy storage devices 190
 - lithium anode protection 188
 - schematic cell configurations 189
 - structure of 186
 - and conversion devices 184–185
 - development 183–184
 - electrochemical performance 207
 - energy density 207
 - planar battery 190–199
 - schematic cell configurations 186
 - woven-type battery pack 202–203
- lithium-ion batteries 1, 127
- lithium-sulfur (Li-S) batteries
 - average working voltage of 127
 - battery performance and the practical applications 177
 - electrochemical performance 155
 - electrolyte membranes 138–144

- lithium-sulfur (Li-S) batteries (*contd.*)
- composite polymer electrolytes 143–144
 - gel polymer electrolytes 142–143
 - solid polymer electrolytes 139–142
- energy conversion and storage of 127
- flexible cathode for
- binder and current collector free structure 156
 - CBC 137
 - charge transfer resistance 136
 - CNF 163–166
 - CNTs 129, 132, 134, 157
 - conductive network 156
 - discharging capacity 135
 - electrical and mechanical flexibility 157
 - electrochemical performance 132, 135
 - electrochemical properties 137
 - electrospinning 132, 133
 - energy density of 132
 - fabrication process 130
 - graphene 129, 131, 132, 134
 - graphene foam 169–172
 - graphene paper 167–169
 - mechanical skeleton 156
 - mesoporous carbon materials 129
 - MFC 134
 - NPCFs 132
 - polymer fibers 166
 - rate capability and cycle stability 134
 - requirements 137
 - sandwich-structured cathode 135
 - soluble polysulfide reservoir 157
 - S-rGO 129, 131
 - tensile strength 132
 - three-dimensional materials 172–177
- separator for 144–148
- working mechanism and challenges
- active materials, dissolution of 128
 - electrochemical reaction 128
 - large volume expansion 128
 - lower discharge voltage plateau 128
 - shuttle effect 128
 - sulfur, low electronic conductivity of 129
 - upper voltage discharge plateau 128
- low bandgap polymer sub-cell, tandem OSCs 324–326
- lowest unoccupied molecular orbitals (LUMOs) 114, 240, 306
- m**
- macroporous active carbon fiber (MACF) cathode 195
- Marker Pen Lithography technique 20
- mechanical deformations 1, 82, 99, 101, 119, 121, 122
- melamine formaldehyde foam (MF) 134, 174
- mesocellular carbon foam (MMSU-F-C) 366
- mesoporous-planar hybrid perovskite solar cells
- absorption spectra 299
 - cell architecture and morphology 293–297
 - charge extraction measurement 300–302
 - external quantum efficiency (EQE) graphs 298
 - J-V characteristics 297, 298
 - meso-TiO₂ layer 292
 - photovoltaic performance 297–300
- mesoporous SiO₂ nanoparticles (MSNs) 275
- 3-methoxypropionitrile (MPN)-based electrolyte 275
- metal alloy anodes 71–72
- metal doped carbon, for HER 464–466
- metallic compound counter electrode 366–370
- metallic counter-electrodes 253
- metal nanowires and grids 318–319

- metal organic frameworks (MOFs), for
HER 471–474
- metal pyrites 369
- metal selenides counter electrodes
369–370
- metal sulfides counter electrodes 369
- MFC-based electrodes 136
- micro-extrusion printing 23, 32
- microfluidic etching method 24
- micro-patterning techniques 9, 10
- microstructure-frame-supported
organic thermoelectric
(MFSOTE) materials 433, 438
- microwave assisted CBD (MACBD)
technique 356
- Miura pattern 86
- molybdenum disulfide (MoS_2) 102
- molybdenum trioxide (MoO_3) 104
- motion sensing, FTENGs 397
of human body 397–399
of objects 399
- multiple exciton generation (MEG)
341–342
- multi-walled carbon nanotubes
(MWCNTs) 5, 113, 319
- n**
- nano-array photo-anode structures
352–354
- nanoporous NS-doped graphene 464
- nanostructured photoactive film
243–249
- Nernst equation 475
- nickel-titanium (NiTi) wires 47
- nitrogen doped carbon foam (NCF)
101
- nitrogen-doped carbon based catalysts,
for HER 460–462
- nitrogen-doped flexible carbon foam
(NCF) 174
- nitrogen doped hollow carbon
nanoparticles (N-HCNPs) 366
- nitrogen-doped mesoporous carbon
nanofibers (NPCFs) 132, 133
- noble metal counter electrodes 365
- non-fullerene acceptors 315–317
- n-type organic semiconductors 306,
309, 310, 315–317
- n-type semiconducting oxides 321
- o**
- 1D and 2D flexible carbon matrix
materials, Li-S batteries 127
- ordered multimodal porous carbons
(OMPC) CEs 366
- organic-based low-work function
modifiers 321
- organic based thermoelectric materials
429
- organic semiconductors 306
- organic solar cells (OSCs)
active layer 308–317
conventional device structure 308
fabrication technology 326–328
flexible electrode 317–320
interfacial layer 320–321
inverted device structure 308
performance characterization of
307–308
tandem OSCs 321–326
working principle 306
- organic thermoelectric materials 429,
431, 438, 447
- origami battery 84, 86
- p**
- PANI-graphene composites 434
- paper-ink cathode (PI cathode) 195,
197
- Pb-based quantum dots 348
- PC_{61}BM 315
- PCN@N-graphene film preparation
462
- peanut shell derived carbon (PSC)
cathode 119
- PEDOT/Graphene/PET electrode
fabrication 252, 253
- pentaerythritol tetra acrylate
(PETEA)-based GPE 142, 143

- perovskite based semitransparent solar cells
 - cell architecture and morphology 286–288
 - mesh-assisted assembly deposition method 286
 - recombination behavior of charges 291–292
 - structure of 286
 - transparency and photovoltaic performance 288–291
- perovskite solar cells (PSCs) 283, 285–288, 290, 297, 305, 321, 339
- perylene diimide (PDI) core unit 315
- photo-anodes
 - TiO₂ nano-array structures 352–354
 - TiO₂ nanoparticles 351–352
- photoelectric conversion efficiency 61
- photo-electrode preparation processes 250
- photo-electrodes, flexible substrates for 242
- photoresist (PR) patterning 18
- photo-thermal technique 23
- photovoltaic (PV)
 - devices 339
 - photovoltaic cells 239, 305
- planar flexible lithium-air battery 197
 - battery internal structure 192
 - CTs-Co₃O₄ NSs-Ru cathode 194
 - cycling performance 195
 - electrochemical performance 199
 - fabrication process 196
 - LiCF₃SO₃/TEGDME 192
 - MACF cathode 195
 - PI cathode 195
 - rate capability 195
 - red light-emitting diode 193, 195, 196
 - schematic cell configuration 191, 198
 - terminal discharge voltage 193
 - TiO₂ NAs/CT 190, 191, 193
- plasma etching 24
- plastic crystal electrolyte (PCE) 79
- plastic-free counter-electrodes 253
- poly (3-alkylthiophenes) (P3AT) 432
- poly(dimethylsiloxane) (PDMS) 24, 101, 189, 190, 437
- poly(3,4-ethylenedioxythiophene):
 - poly(styrene sulfonate) (PEDOT:PSS) 146
- polyethylene glycol terephthalate (PET) 189, 190
- polyethylene oxide (PEO) 139–141, 321
- polyethylene terephthalate (PET) 14, 81, 241, 351, 387, 429
- polyethylenimine ethoxylated (PEIE) 321
- poly(3-hexylthiophene) (PHT) 222, 276, 310, 433
- polymer counter electrodes 370
- polymer electrolytes 8, 13, 16, 143, 200, 207
- polymer fabric based flexible
 - thermoelectric generator 438
- polymer semiconductors, for TE devices 433
- polymer solar cell 307
- polymers polyethylenimine (PEI) 321
- poly{[N,N'-bis(2-octyl-dodecyl)-1,4,5,8-naphthalenedicarboximide-2,6-diyl]-alt-5,5'(2,2'-bithiophene)} (P(NDIOD-T2)) 432
- polyoxometalates-based (POMs) metal organic frameworks 472
- poly(phenylenevinylene) (PPV)
 - derivatives 310–311
- poly(*p*-phenylene terephthalamide) (PPTA) 56
- polypyrrole (PPy) 432
- polythiophene (PT) derivatives 310–311
- polyurethane foam (PUF) 174
- polyvinyl alcohol (PVA) solution 43
- polyvinylidene fluoride-C (PVDF-C) layer 148
- porous MoC_x nano-octahedrons 473, 474

- porous polyimide graphite film (PGF) 117
- porphyrin-based sensitizers 269
- power conversion efficiency (PCE) 306
- power electronics 29, 49, 57, 384, 406, 411, 435
- printing techniques 21, 22, 24, 318, 327, 439
- pristine carbon fiber 41
- pseudo capacitance 4, 7, 24, 39, 43, 107
- Pt-based counter-electrodes 252
- Pt counter electrode, in QDSSC 365
- p-type $\text{Sb}_2\text{Te}_3/\text{poly}$ (3, 4-ethylenedioxythiophene) thermoelectric composites 430
- PZT PDMS composites 221
- q**
- quantum dots (QDs)
- band gaps 341
 - Cd-based 347–348
 - co-sensitization techniques 360
 - ex-situ techniques 358–360
 - in-situ sensitization techniques 356–358
 - large specific surface area 343–344
 - multiple exciton generation 342
 - Pb-based 348
 - physical size of 340
 - quantum size effects 341
 - ultrafast electron transfer 342–343
- quantum dots-sensitized solar cells (QDSSCs) 339
- combined interfacial engineering methods 363
 - counter electrodes 363–365
 - fill factor 346
 - flexible conductive substrates 340
 - interfacial engineering 360
 - photo-anodes for 350
 - photo-induced electron 350
 - photovoltaic performance 345–347
 - structure and charge circulation 344–347
- quasi-solid-state sodium ion capacitor (QSS-SIC) 119, 121
- quinone-based organics 114
- r**
- radioisotope thermoelectric generators (RTG) 425
- rheological behavior, of TiO_2 pastes 245
- R-MACF cathode 195, 196
- roll-to-roll printing 21, 22, 340
- R2R printed organic thermoelectric device 439
- Ruthenium oxide (RuO_2) 4
- s**
- screen printing 21, 285, 327, 435
- Seebeck coefficient 426, 432–434, 442, 444
- self-assembly approach 284
- self-charging power unit (SCPU) 384, 405–409
- self-powered acoustic sensors, for FTENGs 399
- self-powered liquid/gas flow sensors, for FTENGs 402
- self-powered motion sensors, for FTENGs 397
- self-powered sensors 384, 393–405, 414
- self-powered touch/pressure sensors, for FTENGs 393
- self-power electronics 57
- self-priming DEG circuit 229
- semi-transparent perovskite-based solar cells 285
- semi-transparent photovoltaic devices 283
- sensitizer properties 241
- sensitizers, in FDSC
- C106 257
 - D149 257
 - D205 257
 - design considerations 254
 - indoline-based sensitizers 257
 - MK-2 257

- sensitizers, in FDSC (*contd.*)
 - N719 257
 - organic sensitizers, preconditions for 258
 - photovoltaic parameters 255
 - role of 254
 - Ru-based sensitizers 254
 - Z907 257
- sensitizers, in thin photoactive film DSC
 - C218 268
 - C257 and C258 268
 - Carbz-PAHTDIT 269
 - design rules 270
 - D21L6 268
 - photovoltaic parameters 258, 259
 - XY1-XY3 270
 - YA422 268
 - Z907 258
- service behavior, of TENG 411–413
- shape-engineerable thermoelectric painting technique 433
- shoe generators, of dielectric elastomers 230, 231
- short current (I_{sc}) 345
- short multi-walled CNTs 158
- silver nanowires (Ag NWs) 318
- single-electrode-mode TENGs 385, 386
- single shell carbon-encapsulated iron nanoparticles 470
- single-walled carbon nanotubes (SWCNTs) 5, 73, 84
- SiO₂-PDDA-GO core-shell hybrid particles 221, 222
- SiO₂-PDDA-GO/SR dielectric composites 221
- slot-die coating 328, 329
- SnO₂/ZnO based photo-anodes 355
- sodium benzene-dicarboxylate (SBDC) 116
- sodium ion batteries (SIBs)
 - electro-active materials 98
 - electrolyte 97
 - electrolytes and separators 115–117
 - flexible anode 97
 - flexible cathode 97
 - flexible micro-SIBs 122
- full cell, design of 117–121
- inorganic anode materials
 - binder-and current collector-free anode 106
 - fabricated antimony/carbon fibers electrode 107
 - facial hydrothermal method 104
 - faradic and pseudocapacitive reaction 107
 - graphite 101
 - molybdenum disulfide (MoS₂) 102
 - molybdenum trioxide (MoO₃) 104
 - Na₂Ti₆O₁₃ 110
 - phase-transformation approach 107
 - phosphorus 107
 - single microwave-assisted hydrothermal method 104
 - solvothetical method 104
 - sulfur-doped flexible graphene films (SFGs) 102
 - TiO₂ and Na–Ti–O systems 107
 - 2D layered transition metal dichalcogenides 102
- inorganic cathode materials 110–114
- mechanical deformations 122
- organic materials 114–115
- scientific issues
 - advanced active-materials 99
 - novel processing technologies 101
 - substrates and electrodes 99–101
- sodium 4,4'-stilbene-dicarboxylate (SSDC) 115
- solid polymer electrolyte (SPE) 139–142
- solid-state electrolytes
 - cell assembling process 8
 - ionic liquids 8
 - lithium ion-conducting polymer electrolytes 8
 - polymer electrolytes 7

- solid-state hole-transporting materials (HTMs) 275
- soluble polysulfide reservoir 157
- solution-processing techniques 327
- spin coating 327
- spray pyrolysis deposition (SPD) process 357
- standalone flex-SW battery electrodes 167
- stress accumulation 101
- stretchability 93–94
- stretchable TENG 387
- sub-percolation strategy 220
- successive ionic layer adsorption and reaction (SILAR) 348, 356, 357
- sucrose-PEO 140
- surface passivation
- dye molecules 362
 - large-bandgap semiconductors 361
 - metal oxides 361–362
 - molecular dipoles 362
 - molecular relays 362
- synergistic coupling effect 464
- t**
- Tafel plot 474–476
- tandem organic solar cells
- interconnecting layer 322–324
 - low bandgap polymer sub-cell 324–326
- TCO-free counter-electrodes 252, 253
- tetrachloro-1,4-benzoquinone 114
- textile supercapacitor 16
- thermoelectric (TE)
- carbon nanotubes 434
 - conversion 425, 426
 - graphene 434
- thermoelectric generators (TEGs) 435
- drawbacks 437
 - glass fabric based flexible thermoelectric generator 437
 - inorganic Bi_2Te_3 alloys 435
 - MPPT control for 440
 - polyimide (PI) films 437
 - polymer fabric based 438
 - Si based 438
- thermoelectric materials 429
- conducting polymers 431–433
 - organic based 429
 - power factors and ZT values 429
- thermoelectric sensors 446–447
- thermoplastic material 189, 190
- 3D graphene foam 77
- 3D interdigitated microbattery (3D-IMA) architectures 23
- 3D micro-extrusion printing 32
- 3D-NG-sulfur composite (3D-NGS) 130, 131
- three-dimensional nitrogen-doped graphene (3D-NG) 131, 132
- TiO_2 film construction 244
- TiO_2 film preparation, on metal substrate 243
- TiO_2 nanowire arrays (TiO_2 NAs) 190
- TiO_2 NAs/CT 191–193
- TiO_2 pastes 244
- titanium disulfide (TiS_2) 68
- touch/pressure sensing, for FTENG 393–397
- transparent metal meshes 243
- transverse thermoelectric devices
- BST/Ni tubular-type 443
 - figure of merit of 442
 - vs. longitudinal thermoelectric devices 441
 - simulations of 444–446
 - structure of 442
- transverse thermoelectric effect 441–444
- tribo-electric generators (TEGs) 31
- triboelectric nanogenerator (TENGs) 58, 383, 385–386, 393–405
- twisted PDI dimer 315
- two dimensional (2D) PT derivatives 310
- two-step in-situ co-sensitization technique, QDs 360
- u**
- ultrafast electron transfer 342–343
- ultrasonic spray deposition (USD) 242, 249

ultrathin titanium foil 78
ultraviolet photoemission spectroscopy
(UPS) 321

V

vertically oriented graphene (VG) 253
virtual reality (VR) 37
Volmer reaction 476

W

wearable technology 425, 426
world annual solar photovoltaics cell
production 240

woven-type battery pack 184, 188,
190, 202–203
wrinkled graphene 15, 16

Z

zinc-air battery 199
ZnO based photo-anodes 354–355