

Index

a

abnormal/anomalous photovoltaic (APV) effects 62, 299, 325
 AgNbO₃ 143
 Al₂O₃ 100, 104, 108, 130, 145, 189, 289, 290, 332
 γ-aminopropyl triethoxysilane (APS) 178
 anisotropic photoconductivity 66
 anisotropic porous pyroelectric materials
 freeze casting 216–218
 3D rapid prototyping 218–219
 antiferroelectric orthorhombic (AFO) phase 334
 antiferroelectrics (AFE) 89
 AgNbO₃ 143
 diagram of polarization process 132
 HfO₂ 143–144
 high energy-storage capacitors 132
 materials 244, 334
 (Na_{0.5}Bi_{0.5})TiO₃ 140
 PbZrO₃ 132–140
 antiresonance frequency 10
 anti-solvent rapid crystallization process 102
 antisolvent vapor-assisted crystallization (AVC) process 99
 aromatic polythiourea (ArPTU) 119, 175
 aromatic polyurea 119
 atomically thin single-crystalline two-dimensional hybrid

(C₄H₉NH₃)₂PbBr₄ perovskites 101
 atomic force microscopy (AFM)
 Ag nanoparticles, periodically poled
 LiNbO₃ single crystals 280
 Ag photoinduced deposition on
 LiNbO₃ 275
 Ba_{1-x}Sr_xTiO₃ samples 273, 274
 atomic layer deposition (ALD) 130, 143, 247, 249, 250
 axis of rotation 2

b

band gap engineering 79–84, 281, 294, 300
 barrier/semi-conductive capacitors 124
 BaTiO₃ (BTO) 182
 nanoparticles 182, 351
 BaTiO₃-based glass-ceramic 146–147
 BaTiO₃-based relaxor ferroelectrics 154–156
 BaTiO₃-Bi(Me)O₃ system 157
 BaTiO₃/PVDF nanocomposite 178, 181, 183, 184
 Berry phase method 312
 BFO capacitors 75, 324, 325
 biaxially-oriented polypropylene (BOPP) 169, 186, 191
 BiFeO₃ 276, 277
 based relaxor ferroelectrics 157–158
 bistable oscillators 49, 51, 52
 Bi_{1.5}Zn_{0.9}Nb_{1.5}O_{6.9} 131
 body-crystallization method 145, 146

- Born effective charges 312, 320, 327
boron nitride (BN) 191
boron nitride nanosheets (BNNs) 190, 191, 256
breakdown strength (BDS) 23, 28, 123–124, 169, 170, 172, 174, 175, 177–191, 193, 244
building integrated photovoltaics (BIPVs) 97
bulk crystal growth 99–100
bulk photovoltaic effect (BPVE) 23, 63, 65, 322
burned out plastic spheres (BURPS) 215, 216, 218
- C**
- cantilever piezoelectric energy harvesters 47
capacitance 9, 10, 19, 38, 66, 77, 86, 120, 121, 124, 125, 152, 158
center of symmetry 2, 66, 269
ceramic capacitors
 doped ferroelectric materials 124
 ferroelectric materials 124
 paraelectric materials 124
ceramic nanoparticles 177
charge-discharge measurement circuit 128
charge-discharge process 126
charge-transfer exciton (CTE) 353, 354
chlorotrifluoro ethylene (CTFE) 172
circular photovoltaic effect (CPVE) 24–25
composites, EC
 ferroelectric ceramics and polymers 256–257
 P(VDF-TRFE), coexistence of ferroelectric and relaxor 254–256
compositional engineering and bandgap tuning 98–99
core-shell structure
 0D nanofillers 181–183
 1D nanofillers 189
corona-poling method 291–293
Coulombic efficiency (CE) 352
coupled electrocaloric effects 231–235
- d**
- damping coefficient 8, 9, 33
Debye length 271
decolorization rate of RhB 281, 282
density functional perturbation theory (DFPT) 312, 322
density functional theory (DFT) 74, 207, 311, 312
dichloromethane (DCM) 100
dielectric capacitors
 breakdown strength 123–124
 capacitance 121
 charge process 121
 direct charge-discharge method 127–129
 effect of a capacitor 120
 energy efficiency 122
 energy-storage density 122
 high energy-storage performance 119
 indirect calculated method 127
 multilayer ceramic capacitor 121
 organic polymers 119
 paraelectric-like metal oxides 129
 polarization-based method 125–127
 powder density 125
 PVDF-based materials 119
 service life 125
 thermal stability 124–125
dielectric polarization 1
diisopropylammonium bromide (DIPAB) 356
direct charge-discharge method 127
direct foaming method 215, 216
direct piezoelectric effect 314
dissociation of excitons 352
domain reorientation/switching 6
domain wall photovoltaic effect (DWPVE) 26
dual-source thermal evaporation system 102, 103

- Duffing resonance (nonlinear hysteretic) resonance 50–51
- dye-sensitized solar cells (DSSCs) 96, 104, 327
- e**
- effective piezoelectric constant 48
- effect of capacitor 120
- Einstein summation convention 314
- elastic compliance matrix 9
- electrical damping coefficient 33
- electric condenser 120
- electric dipoles 1, 317, 326, 329, 331
- electric energy storage
- ferroelectric polymer-based nanocomposites 175–192
 - ferroelectric polymers 172–175
 - theory 170–171
- electric permittivity 1, 40, 42, 44, 183, 208, 219, 231, 232, 235, 249, 252, 253, 317, 358
- electric toroidal susceptibility tensor 317
- electrocaloric coefficient 12–14, 329
- electrocaloric effect (ECE) 19, 329
- composites 254–257
 - coupled 231–235
 - direct method 238, 239
- electrocaloric refrigerator prototype 242–244
- in fast ion conductors 259–260
 - ferroelectric ceramics 245
 - ferroelectric polymer materials 250
 - indirect method 238
 - L–D phenomenological theory 235–236
 - in liquid crystals 257–259
 - Maxwell relations 231
 - MLCC and MLPC EC refrigerator modules 244–245
 - positive and negative 238–242
 - statistical thermodynamics theory 236–238
- electrocaloric refrigerator prototype 242–244
- electrodes 5, 23, 25, 27, 37, 42, 48, 70, 71, 75–79, 85, 89, 103, 110, 130, 134, 137, 148, 154, 204–206, 210, 212, 245, 268, 273, 274, 291, 294, 296–298, 324, 327, 332, 345
- electromagnetic generators 37–39
- electrostatic generator 37, 38
- electrostatic term 4
- energy conversion
- electrocaloric (EC) effect 329
 - ferroelectric films 320
 - photovoltaic effect 322–327
 - piezoelectricity 313–322
 - pyroelectric effect 327–311
- energy efficiency 122, 126, 131, 133–135, 140, 141, 144–146, 148, 150, 152, 154, 156–158, 332
- energy storage 331
- energy-storage density 119, 122, 123, 125–127, 130, 131, 133–141, 143–148, 152–154, 156–159
- f**
- ferroelectric based Schottky junctions 79
- ferroelectric ceramics, EC
- in bulk ceramics and single crystals 245
 - thin films 248
- ferroelectric-ferroelectric phase transition 18, 19
- ferroelectricity 1, 2, 6, 7, 20, 80, 89, 132, 143, 281, 298, 300, 322, 337, 350–352, 354, 356
- ferroelectric oxide materials 79, 323
- ferroelectric-paraelectric phase transition 19, 256
- ferroelectric photovoltaic solar energy harvesting 23–27
- ferroelectric polymer-based nanocomposites
- 0D nanofillers 177–181
 - 1D nanofillers 184–189
 - 2D nanofillers 190–192
- Lewis's model 176

- ferroelectric polymer-based nanocomposites (*contd.*)
 nanofillers 175
 Tanaka's model 175, 176
 ferroelectric polymer materials 169–193, 250–251
 figures of merit (FOMs) 53, 212, 219–221
 fill factor (FF) 23, 61, 105
 first-principles calculations, ferroelectrics
 Berry phase method 312
 energy conversion 313–331
 energy storage 331–337
 Hamiltonian method 312–313
 quantum mechanics 312
 flexoelectric effect 89, 313–322
 foils 52–53
 formamidinium (FA) 96, 101, 326
 Frank–Condon relaxation 65
 free energy 3, 4, 12, 13, 15, 16, 22, 233, 235, 314–316
 freeze casting 216–218
 frequency up conversion 49, 51
 fused deposition technology (FDM) 218
- g**
 gel casting 215–216
 giant piezoelectric resistance (GPR) effect 317
 Gibbs free energy 12, 13, 15, 16, 22, 233, 235
 Gibbs–Shannon entropy 237
 Ginzburg–Landau theory 3
 glass-ceramic ferroelectrics
 body-crystallization method 146
 compositing method 145–146
 interface effect-related energy-storage performance 148–151
 Gouy–Chapman diffused layer 176
 graphene nanodots (GNDs) 191
 graphene nanosheets (GNs) 190, 191, 208
 graphene oxide (GO) 190, 289
- h**
 Hamiltonian method 311–313, 315, 332
 hexafluoropropylene (HFP) 172
 HfO₂ based antiferroelectric 143–144
 highest occupied molecular orbital (HOMO) 80
 high-*g*-constant piezoelectric ceramics 5
 high-quality perovskite films 95, 101, 103, 106
 high temperature phase (HTP) 356
 homogeneously aligned cells (HA-Cells) 259, 260
 hybrid halide perovskites 97, 104
 hybrid pyroelectric generators 207–210
 hysteresis loop 1, 4, 44, 47, 74, 171, 173, 332, 334, 356, 357
- i**
 indirect calculated method 127
 induced polarization 1, 39, 74
 inorganic ferroelectrics 354–357
 interdigitated electrodes (IDE) 47, 48, 76
 interface effect-related energy-storage performance 148–151
 intramolecular exchange process (IEP) 106
 inverse temperature crystallization (ITC) method 100
 iodide-chloride mixed-halide perovskite 104
 isotropic porous pyroelectric materials
 BURPS 215
 coral replication technique 214
 direct foaming method 215
 gel casting 215–216
 polymeric sponge 214–215
- k**
 kinetic energy harvesting
 kinetic vibration source in the ambient 35–36
 theory of 33–34
 transducers 36–39

$[\text{KNbO}_3]_{1-x}[\text{BaNi}_{1/2}\text{Nb}_{1/2}\text{O}_{3-\delta}]_x$
(KBNNO) 80

I

Landau–Devonshire phenomenological theory 235–236

Landau–Ginzburg–Devonshire theory 207

$\text{La}_{0.7}\text{Sr}_{0.3}\text{MnO}_3$ 75

lead-contained glass-ceramic 146

lead-free $\text{MASnBr}_{3-x}\text{I}_x$ perovskite 111

lead-free piezoelectric ceramics 7

Lewis's model 176

light entrainment effect 24, 66

linear mass-spring damper system 33, 34

linear photovoltaic effect (LPVE) 24

linear piezoelectric energy harvesters 49, 50

lithium-ion batteries (LIBs) 350, 351

lithium-ion transport, polymer electrolyte 350–351

lithium-sulfur battery (LSB) 351

lowest unoccupied molecular orbital (LUMO) 80

m

$\text{MAPbI}_{3-x}\text{Cl}_x$ films 101, 103

marker reactions 272

materials for energy harvesting
effect of stress induced by substrate 45–47

piezoelectric 43, 44

maximum transmission coefficient 41

Maxwell relations 20, 231–235, 238, 246, 251–253, 258, 260

Maxwell thermodynamical relation 329

Maxwell–Wagner–Sillars interfacial polarization 184, 189

mechanical energy harvesting 4–10, 33, 36–39, 49, 53, 349

mechanical quality factor 10

MEMS-based cantilever harvesting system 210

MEMS piezoelectric bridge Duffing oscillator 51

mesoporous TiO_2 scaffold 105

meso-superstructured solar cell (MSSC) 104

metal-organic frameworks (MOF) 289, 351

methylammonium (MA) 96

lead iodide perovskite 95

mirror planes 2

molecular dynamics (MD) method 313

Monte Carlo (MC) method 313

morphotropic phase boundary (MPB) 43, 44, 89, 157, 247, 248, 260, 315

multilayer polymer capacitors (MLPC) 244, 245

multiferroic material, BiFeO_3 87

multilayer ceramic capacitors (MLCC) 121, 156, 159, 244–245, 247, 260

multilevel structure nanocomposites

0D nanofillers 181–183

1D nanofillers 189

multi-metal oxides

$\text{Bi}_{1.5}\text{Zn}_{0.9}\text{Nb}_{1.5}\text{O}_{6.9}$ 131

SrTiO_3 131

n

$(\text{Na}_{0.5}\text{Bi}_{0.5})\text{TiO}_3$ based antiferroelectric 140–142

nanocrystal synthesis 100–101

nanogenerator 205, 206

Nb-contained glass-ceramics 147

negative electrocaloric effects 238

nonlinear bistable oscillators 51, 52

nonlinear energy harvesting 49–52

nonlinear polarization 1, 332

n-type semiconductor photoelectrode 268

o

1D nanofillers

core-shell structure 189

multilevel structure 189–190

surface modification 184–189

open-circuit coefficients 5

- optical absorption coefficient 95
 optical damage or inhomogeneity 63
 optomechanical bimorph actuator 85
 organic-inorganic hybrid perovskite solar cells
 bulk crystal growth 99–100
 charge transport properties 98
 compositional engineering and bandgap tuning 98–99
 crystal structures 96–97
 dual-source thermal evaporation system 103
 dye-sensitized solar cells 96
 efficiency roadmap 103–106
 I-V hysteresis 110–111
 long-term stability 108–110
 methylammonium lead iodide perovskite 95
 nanocrystal synthesis 100–101
 one-step solution process 101–102
 optical absorption coefficient 95
 optical properties 97–98
 optoelectronic properties 95
 organic photovoltaics (OPVs) 96
 power conversion efficiencies 95
 toxicity of raw materials 111
 two-step solution process 102–103
 vapor-phase deposition 103
 working mechanism and device architectures 106–108
 organic-inorganic hybrid PSCs 95–112
 organic photovoltaic (OPV) cells 95, 352
 organic polymers 119
 organic solar cells (OPVs) 107, 349
 organometal trihalide perovskite single crystals 98
 oxidative-reductive reactions 267
- p**
 paraelectric-like metal oxides
 Al_2O_3 130
 $\text{Bi}_{1.5}\text{Zn}_{0.9}\text{Nb}_{1.5}\text{O}_{6.9}$ 131
 SrTiO_3 131
 TiO_2 129–130
 ZrO_2 130
 paraelectric materials 124
 parallel-plate capacitor 120, 121
 $\text{Pb,La}(\text{Zr,Sn,Ti})\text{O}_3$ antiferroelectric thin films 134
 $(\text{Pb}_{0.92}\text{La}_{0.08})(\text{Zr}_{0.95}\text{Ti}_{0.05})\text{O}_3$ antiferroelectric thin films 134
 $\text{Pb}_{0.99}(\text{Zr,Sn,Ti})_{0.98}\text{Nb}_{0.02}\text{O}_3$ 133
 $\text{Pb}(\text{Zr,Sn,Ti})\text{NbO}_3$ (PNZST) 133
 $\text{Pb}(\text{Zr,Ti})\text{O}_3$ (PZT) 275
 PbTiO_3 -based relaxor ferroelectrics 157
 PbZrO_3 132
 PbZrO_3 -based AFEs 133–135
 2,3,4,5,6-pentafluorobenzyl phosphonic acid (PFBPA) 178
 perovskite 5, 95–111
 perovskite-type ferroelectric ceramics 219
 phase transitions in PbTiO_3 (PTO) 80, 315, 322, 324, 334
 photocatalysis, ferroelectrics materials degradation 280–286, 288, 289
 external screening 270
 fundamental principles 266–269
 internal screening 270
 photochemistry 271, 272, 274–280
 spontaneous polarization 269, 270
 water-splitting 289, 291–296, 298
 photocatalytic generation of hydrogen 267
 photocatalytic water-splitting 267, 268, 289, 290, 292
 photochemistry, ferroelectric materials 271, 272, 274–280
 photo-conductivity 62
 photoelectrochemical generation of hydrogen 268
 photoferroics 61, 62
 photo-mechanical coupling 84–88
 photorefraction 62
 photostriction 84–88
 photovoltaics
 abnormal/anomalous photovoltaic effect 62
 anisotropic photoconductivity 66
 band gap engineering 79–84

- band gap values 62
- bulk photovoltaic effect 63–65
- current-voltage characteristics 70
- direction of polarization 67
- effect 322
- electrodes 77–79
- electron-phonon scattering 65
- electron spin resonance
 - measurements 71
- expansion coefficients 65
- Frank Condon relaxation 65
- light entrainment effect 66
- open circuit voltage 64
- optical damage or inhomogeneity 63
- orthorhombic-rhombohedral phase transition 69
- out-of-plane (OOP) geometry 73
- perovskite structure 62
- perpendicular to the domain walls 71
- photo-conductivity 62
- photoferroics 61
- photoinduced transient spectroscopy (PITS) 70
- photo-mechanical coupling 84–88
- photorefraction 62
- pn-junction 61
- polarization 74–76
- quadratic electrical conductivity 66
- rhombohedral-rhombohedral phase transition 69
- separation of electron-hole pair 69
- shift mechanism 66
- short circuit current/photovoltaic current 61
- space charge region 61
- temperature dependence of the open circuit voltage 72
- thermally induced lattice polarization fluctuations 64
- thin film technology 62
- variation of the photocurrent 68
- piezoelectric force microscopy (PFM) 275
- piezoelectric harvester
 - linear piezoelectric energy harvesters 49–50
 - nonlinear energy harvesting 49–50
 - option of piezoelectric configuration 47
 - unimorph and bimorph structures 48–49
- piezoelectricity 2, 4, 39, 40, 313
 - catalytic effect 358
 - ceramics 6
 - coefficients 5, 86
 - constant 14
 - coupling factors 5, 9
 - damping coefficient 9
 - effect for mechanical energy harvesting 7
 - MEMS harvesting 43, 44
 - microdevices 47
 - strain coefficients 9
 - thin films on metal substrate 52
 - vibration harvesting 39, 40
 - theory 40, 41
- piezoresponse force microscopy (PFM) 26, 110, 351, 357
- piezotoroidal effect 317–320
- PLZT relaxor ferroelectrics 152–154
- polarization-based method 125–127
- polarization-electric field hysteresis (P-E) loops 110, 237, 251
- polar nanoregions (PNRs) 236
- poly(ethylene oxide) (PEO) 350
- polyaniline (PANI) 191
- polycarbonate (PC) 119
- polydimethylsiloxane (PDMS) 169, 205, 208
- polyester (PT) 119, 180
- polyimide 119, 169
- polymer-based film capacitors 169
- polymeric sponge 214–215
- poly(vinylidene fluoride-trifluoroethylene) [P(VDF-TrFE)] copolymer 20, 205, 353
- polypropylene (PP) 119, 169–171
- polysulfide trapping, Li-S batteries 351

- polyvinylidene fluoride (PVDF) 43, 119, 356
 - BaTiO₃ nanoparticles 184
 - BaTiO₃ nanowires 189
 - beta-phase of 190
 - chemical crosslinking of 174
 - copolymers 169, 170, 174
 - defect modifications of 172
 - dielectric properties of 175, 185
 - gamma-phase of 185
 - graft 174
 - hydroxylated BaTiO₃ nanoparticles 177
 - molecular defects of 172
 - schematic image of 173
 - terpolymers 169, 170, 174
 - total charged energy density 171
 - polyvinylidene fluoride (PVDF film) 169, 206, 208
 - Poole–Frenkel (PE) emission 123
 - pore-forming agent (PFA) 215
 - porous pyroelectric materials
 - anisotropic 216–219
 - FOMs 219
 - isotropic structure 214–216
 - positive electrocaloric effects 238
 - potential thermodynamic refrigeration cycle 21
 - powder density 125
 - primary and secondary pyroelectric coefficient 14–15
 - PVDF-based materials 119
 - PVDF–TrFE-based polymers 255
 - pyroelectric effect *vs.* phase transition 17
 - pyroelectric energy harvesting
 - coupling with electrochemical systems 212
 - FOMs 219
 - hybrid pyroelectric generators 207–210
 - micro-scale materials 205–207
 - nanostructure 205–207
 - oscillator systems 210–211
 - piezoelectric effect 203, 208
 - porous pyroelectric materials (*see* porous pyroelectric materials)
 - pyroelectric charge 203
 - thermoelectric devices 203
 - pyroelectricity 2
 - coefficient 12
 - effect 327
 - pyroelectric ‘nano-generators’ 205, 208, 210, 211
 - pyroelectric oscillator systems 210–211
 - pyroelectric thermal energy harvesting
 - electrocaloric coefficient 12–14
 - primary and secondary pyroelectric coefficient 14–15
 - principle of pyroelectric effect 10–12
 - pyroelectric coefficient 12–14
 - pyroelectric effect *versus* phase transition 17–19
 - tertiary pyroelectric coefficient 15–17
 - pyro-electro-catalysis 212
 - PZT coral structure 214
- q**
- quadratic electrical conductivity 66
- r**
- reactive oxygen species (ROS) 212, 358
 - redox reactions 266, 268, 271, 277, 283, 358
 - refrigerant capacity (RC) 21
 - relative dielectric constant 5, 121, 124, 125, 130, 143, 146, 148, 156, 332
 - relaxed rhombohedral phase films 83
 - relaxor ferroelectrics
 - BaTiO₃ 154–156
 - BiFeO₃ 157–158
 - PbTiO₃ 157
 - PLZT 152–154
 - relaxor ferroelectric terpolymers 253–254
 - relaxor-type ferroelectrics 89

- resonant based piezoelectric generators 49
- rhombohedrality 74
- rhombohedral perovskite ferroelectrics 40
- s**
- Sawyer–Tower circuit 127
- Schottky barriers 75, 324
- Schottky contact 324
- Schottky Emission (SE),
Fowler–Nordheim (FN)
tunneling 123
- Schrodinger equation 312
- second-order spring-mass systems 8
- semiconducting oxide materials 265
- semiconductor photocatalysis
266–269
- sequential vapour-deposited
MAPbI_{3-x}Cl_x perovskite layer
105
- short circuit current/photovoltaic
current 61
- simple metal oxides
Al₂O₃ 130
TiO₂ 129–130
ZrO₂ 130
- smart materials 358
- solar systems 209–210
- solar water-splitting 267
- solid freeform fabrication (SFF) 218
- solid hole transport material
(spiro-MeOTAD) 104
- solvent-engineering technique 102
- Space-Charge-Limited Current (SCLC)
123
- spontaneous electric polarization 269,
270
- spontaneous polarization 1
- spring stiffness 34
- SrTiO₃ 131
- stacked PbI₂/MAI bilayer structure
103
- statistical thermodynamics theory 236
- Stefan–Boltzmann law 205
- Stern layer 176
- Stirling cycle 242, 243
- strain engineering 81
- surface modification
0D nanofillers 177–181
1D nanofillers 184–189
- t**
- Tanaka’s model 175, 176
- Taylor expansion 3, 24, 313, 334
- tertiary-butyl alcohol (TBA) 216
- tertiary pyroelectric coefficient 15–17
- tetragonal-like BFO films 82, 83
- thermal annealing-induced
inter-diffusion method 103
- thermal evaporation 103
- thermal expansion coefficient (TEC)
14, 45
- thermal relaxation time 19
- thermal stability 124
- 3D rapid prototyping 218–219
- TiO₂ 129
- TMCM-MnCl₃, ferroelectricity 356,
357
- top and bottom electrodes (TBEs) 48
- top-seeded solution-growth (TSSG)
method 100
- total pyroelectric coefficient 11
- transducers 36–39
- tri-axis accelerometer 36
- trifluoroethylene (TrFE) 172
- triple-cation perovskite composition
106, 110
- 2D nanofillers 190
- u**
- 1.8- μm -(Pb_{0.97}La_{0.02})(Zr_{0.95-x}Sn_xTi_{0.05})O₃
antiferroelectric thick films 136
- unimorph and bimorph structures 48,
49
- v**
- van der Waals (vdW) interaction 326
- vapor-phase deposition 103
- virtual crystal approximation (VCA)
314
- voltage coefficient 10

W

- Wannier functions 312
- water-splitting activity, photocatalytic
290–296, 298
- Weibull distribution 123, 179
- well-crystallized MAPbI₃ perovskite
capping layer 105

X

- X-ray diffraction (XRD) analysis 351

Z

- 0D nanofillers
 - core-shell structure 181–183
 - multilevel structure 183–184
 - surface modification 177–181
- ZrO₂ 130