

Index

a

AA6061 aluminum alloy
 composites 198
 abrasion tribometer 42
 abrasive water jet cutting process 6
 abrasive wear 35, 54, 84, 97, 167
 CNT 100–101
 mechanisms 97–98
 performance
 polymer composites 167
 scar 88
 specific wear rate 186–187
 wear test 86–87
 wear volume loss 184–188
 worn surface
 morphology 188–192
 accelerated aging bones
 accelerated weathering study 9–11
 maximum load withstand 12–15
 methods
 conduct of experiment 5–8
 DOE 5
 observation and analysis 8
 planning 4
 normal/increased temperature,
 strength comparison 15–27
 temperature testing 7
 accelerated weathering study
 boiling process 9
 maceration process 11
 mass loss comparison 11
 RH 10
 acid treated carbon nanotubes (ACNT)
 effect of 107–108

surface profiles 111
 thermal images for 109–110
 adhesion wear 54, 80, 105, 109, 110
 Alicona technique surface 106
 aluminum oxide 166, 169–171, 185
 Archard's equation 148, 149
 Archard's law 36, 149, 154, 157
 Archimedes principle 39
 arthritis, adults suffered from 1–2
 ASTM 5, 41, 73, 85

b

ball-on-disk (BOD)
 configuration 155
 tribo test, wear and friction test 57
 banana peel fibers 121
 basalt fiber reinforced polymer
 composites materials 215
 basalt/PEI composites 216–218,
 220–225
 basalt/PEI/PTFE composites 217, 218,
 224
 basalt/PEI worn out composites,
 topography of 221
 basalt reinforced thermoplastic
 composite
 CoF, comparison 219–220
 friction coefficient 218
 basalt/PEI 220
 basalt/PEI/PTFE 220
 tribological test configuration 219
 basket interweave fabric 166
 bidirectional carbon fiber fabric 168
 body weight (BW) 148, 154

- bone
 - abrasive elongation of 22
 - abrasive wear elongation of 22
 - chemical properties 47
 - composition of 48
 - defects 1
 - environmental factors 2
 - fracture structure of 21
 - fracture type 33–34
 - functions 34
 - grafting 33
 - low impact fracture 38
 - 200× magnification image 45–46
 - maximum average hardness of 20
 - minimum average hardness of 19
 - nano-indentation 4
 - propagate fracture 46
 - research 38
 - species *vs.* humans 3
 - specimens 24–25
 - structure 35
 - tensile test on 3
 - uses 38
 - bovine bone
 - dimension of 8
 - EDAX analysis test 26
 - vs.* goat bone
 - bone fracture 16
 - mass loss for 11
 - maximum load withstand 14
 - porosity in 23
 - with resin and without resin 21
 - load *vs.* indentation depth graph 18
 - mechano properties of 17
 - nano-indentation temperature 19
 - normal/increased temperature,
 - strength comparison 15–27
 - temperature, RH effect 15
 - tensile strength 13
 - brake dynamometer 117, 122, 126, 127
 - brake effectiveness evaluation
 - procedure (BEEP) 122–124, 127, 128, 134
 - brake friction materials 115–118, 120–122, 126–128, 131
 - braking test procedures 117
 - fade section 118
 - green section 118
 - pressure and velocity sections 118
 - recovery section 118
 - running-in/bedding-in section 118
- C**
- carbon-epoxy composite
 - system 168–169
 - carbon fabric reinforced epoxy (C-E)
 - composites
 - carbon fabric, epoxy and micro-fillers 172
 - dry sliding wear performance
 - coefficient of friction 181–182
 - specific wear rate 179–181
 - wear volume loss 176–179
 - worn surface
 - morphology 183–184
 - friction and wear performance 176
 - carbon fabrics (T300) 169
 - carbonized (BCp) banana peels 121
 - carbon nanotubes (CNT) 100
 - abraded surface composites 101
 - abrasive wear test 100–101
 - ACNT 100
 - fabrication composites 100
 - SCNT 100
 - catalyzed resin 85
 - coconut sheath 83–85, 87–89, 93
 - coconut sheath reinforced composite 88
 - coefficient of friction (COF) 118
 - GF 58
 - variation of 43–45
 - weight loss 45
 - Colles fracture 34
 - compact bone 34, 35
 - compaction process 201, 202
 - composites
 - classification
 - behaviour, adhesion 142
 - continuous fiber 144
 - hybrid composites 145
 - short fiber/discontinuous fiber 144
 - tribological conditions 146
 - tribo-testing, basics 145–147
 - two dimensional structure 144
 - fabrication 85, 171–172

- materials, testing
 - density test 217
 - hardness test 217
 - wear test 217
 - plate 62
 - compound bone fracture 33
 - compression molding technique 85
 - conduct of experiment
 - bone processes 5
 - cutting process 6
 - gauge length 7
 - SEM/EDAX 7
 - temperature measurement 7
 - constant load (BW) 4, 5, 101, 156, 158, 179
 - constant slide-roll ratio 148, 154, 156, 157
 - copper–alumina composites 198
 - copper based composites
 - fly ash
 - AA6061 198
 - cenosphere particles 198
 - CoF 207
 - low cost and low density 198
 - material 200–201
 - microstructure 203–204
 - powder metallurgy
 - process 201–202
 - waste by-product 198
 - wear rate 205
 - wear studies 202–203
 - graphite
 - ANOVA 210
 - COF 207
 - grey relational analysis 208–209
 - microstructures 203, 204
 - response table 210
 - wear rate 205
 - MMCs 197
 - copper tin composites 198
 - corrosive wear 35, 147
 - cortical bone 4, 34, 35
 - cyclic multidirectional path of
 - motion 148
- d**
- degree of crystallinity 142
 - degree of polymerization 88
 - density testing 217
 - design of experiment (DOE),
 - accelerated aging bones 5
 - di-glycidyl ether of bisphenol-A (DGEBA) 168
 - dried polymers 57
 - dry friction 35
 - dry sand/rubber wheel abrasion tester (RWAT) 86, 174, 175
 - dry sliding wear
 - carbon-epoxy composites
 - coefficient of friction 181–182
 - specific wear rate 179–181
 - wear volume loss 176–179
 - worn surface
 - morphology 183–184
 - test 62, 172–174
- e**
- eco-friendly brake pad 124, 127, 133
 - elastic modulus 4, 16, 17, 20, 38, 47
 - energy dispersive X-ray analysis (EDAX) 7, 8, 23, 26–28, 38, 42, 46, 51
 - engineering materials 139
 - epoxy composite 103
 - erosive wear 35, 147
 - ethylene (C₂H₄) 139
 - ethylene monomers 141
- f**
- fabrication, composite
 - materials 216–217
 - fatigue wear 35, 61, 110, 111, 147
 - fiber damaged (FD) 92
 - fiber-matrix connection 142
 - fiber-matrix interface 67, 92
 - fiber reinforced polymer (FRP)
 - composites 53, 69–71, 99, 183
 - fiber reinforcement 143
 - basket interweave fabric 166
 - HPMCs 164
 - plain interweave fabric 165
 - satin interweave fabric 166
 - twill interweave fabric 166
 - wrap and weft directions 164
 - fiber surface treatment 84–85

- fillers 53–70, 99, 105, 130, 142, 164, 166, 168–172, 178, 179, 181, 183–186, 188
- fly ash
 - AA6061 198
 - cenosphere particles 198
 - CoF 207
 - low cost and low density 198
 - material 200–201
 - microstructure 203–204
 - powder metallurgy
 - process 201–202
 - waste by-product 198
 - wear rate 205
- force modelling, wear
 - equation 150–152
- fragility fracture 34
- fretting wear 35
- frictional modifiers 115
- Friction Assessment and Screening Test (FAST) machine 117
- friction force 46, 55, 115, 145, 149, 150, 159, 220–222
- friction material components
 - braking test procedures 117
 - requirements 116
- g**
- GGG composite 78
- glass composite 103–105
- glass fabric reinforced epoxy (G-E)
 - composites 66, 181
- glass fiber (GF) 58
 - friction material 120
 - reinforced composite 72
 - reinforced hybrid composites 62–67
 - wear rates 101
- glass fiber hybrid effects
 - abrasive wear test 86–87
 - composite fabrication 85
 - E-glass 83
 - fiber and matrix 84
 - fiber surface treatment 84–85
 - hardness (shore-D), composites 88
 - mechanical properties
 - of composites 86
 - fractographs, NNN-USP 87
 - mechanical testing 85
 - specific wear rate
 - fiber type and loading 88
 - MC 92
 - MP 92
 - pure and hybrid
 - composites 89–90
 - worn surface images, of
 - composites 88
 - tensile properties 85
- goat bone
 - vs. bovine bone
 - bone fracture 16
 - mass loss for 11
 - porosity in 23
 - with resin and without resin 21
 - dimension of 8
 - EDAX analysis test 27
 - mechano properties of 17
 - nano-indentation temperature 19
 - normal/increased temperature,
 - strength comparison 15–27
 - temperature, RH effect 15
 - tensile strength 13
 - Young's modulus 16
- green compact 201
- grey relational coefficient 206, 208, 210
- grey relational grade 206, 208
- h**
- hardness testing 4, 5, 28, 38, 47, 51, 217
- hemp fibers 127
- Hibiscus cannabinus* 128
- high density polyethylene (HDPE) 57–61, 179
- Hitachi S-3400N 8
- Hooke's law 37, 143
- human femur bone 19
- hybrid glass/kenaf
 - composites 103–104
 - ACNT 107–111
 - methodology
 - abraded surface composites 101
 - abrasive wear 100–101
 - fabrication of 100

- materials 99–100
 - PCNT 101–107
 - SCNT 107–111
 - hybrid metal matrix
 - composites 197–210
 - hybrid natural fiber composites
 - friction material components
 - braking test procedures 117
 - requirements 116
 - natural fibers
 - asbestos, types 119
 - BEEP 122
 - brake materials 133
 - decision matrix 130
 - moisture absorption 120
 - non-toxic 118
 - steel fibers 120
 - test materials and procedures 122
 - thermal degradation 120
 - hybrid polymer matrix composites (HPMCs)
 - fibrous reinforcement 164
 - particulate fillers 166
- i**
- injection moulding process (IMP) 58
 - Instron Universal Test Machine 41
 - interstitial bone 4, 38
- j**
- JJG composite 78, 79
 - JJJ composite 75, 77, 78
 - jute fiber 72
- k**
- kenaf composite 102–104
 - kenaf fibers 99, 100, 104, 128
- l**
- LY 556 epoxy resin 168, 171
- m**
- maleic anhydride modified polypropylene (MAgPP) 57
 - material removal rate 39
 - matrix shrinkage (MS) 92
 - maximum load withstand, bone
 - for bovine bone extension 12
 - for goat bone extension 12
 - mercantile aircraft applications 164
 - metal matrix composite (MMCs)
 - aircraft industry 197
 - applications 197
 - automobile industries 197
 - development of 197
 - matrix materials 197
 - solid lubricant 199
 - methyl ethyl ketone peroxide (MEKP) 84
 - Mettler Toledo densitometer 217
 - micro cracking (MC) 92, 97, 98, 167, 168, 192, 200
 - micro-cutting 97, 98, 103, 112, 167, 168, 192
 - micro-fatigue 97, 98, 103, 110, 111
 - micro materials nano test 7
 - micro ploughing (MP) 92, 97, 98, 112, 167, 168, 192, 222
 - moisture absorption 120, 121
 - molybdenum disulfide (MoS₂) 166, 169, 170, 179, 184–186, 190, 197
 - morphological analysis, worn-out samples
 - extreme loading conditions 221
 - SEM micrograph, basalt /PEI composite 222
 - morphological examination, of worn out surfaces
 - fabrication, composite materials 216–217
 - materials used in 216
- n**
- nano-indenter 4, 7, 18, 41, 47
 - natural fiber composite (NFC) 72, 87, 147
 - natural fibers 116
 - asbestos, types 119
 - non-toxic 118
 - steel fibers 120
 - thermal degradation 120
 - non-standard squat 151, 157
- o**
- osteonal bone 38

p

- palm kernel, fibers 124
- particulate fillers
 - aluminum oxide 170–171
 - in HPMCs 166
 - molybdenum disulfide (MoS₂) 170
- pin-on-disk (POD) *see also* ball-on-disk configuration
 - apparatus 173
 - tribometer 38
 - tribo test, wear and friction test 55–57
- pin-on-disk tribometer (PODT) 38, 39, 42
- plain interweave fabric 165
- plain woven fabric benefits 169
- plastic lactic acid (PLA) polymer 126
- plexiform bone 3
- polyamide 6 (PA6) 57–61
- polyetherimide (PEI) 163, 215, 216
- polymer composites materials (PCM) 215
- polymer journal bearing montage 68
- polymer matrix composites (PMCs)
 - friction and wear 167–168
 - matrix material 163–164, 168
 - reinforcements
 - fiber 164–166
 - HPMCs 164
 - natural fibers 164
 - particulate 166
 - synthetic fibers 164
- polymers
 - classifications 142
 - organic materials 139
 - reinforced 139
- polytetrafluoroethylene (PTFE) 59–60, 216
- pristine CNT (PCNT)
 - Alicona 3D surface 108
 - epoxy polymer 101–102
 - glass composites 101–102
 - stereomicroscope 103, 107
 - surface images of 104
 - thermal images of 105–106
 - wear rate effect 105
 - wear rates type 101–102
 - worn surface profiles 106

r

- reinforced hybrid polymer composites
 - abrasive wear 54–55
 - adhesion wear 54
 - case study 67–69
 - PA6 and HDPE 57–61
 - silicon carbide, graphite particle 62–67
 - tribo wear test methods 55–57
 - wear and friction test, BOD 57
 - wear and mechanisms 54–55
 - reinforced polymers 139
 - relative humidity (RH)
 - accelerated temperature test 4
 - at different temperature 10
 - temperature ranging 40
 - weathering condition 10
- S**
- satin interweave fabric 166
 - scanning electron microscope (SEM) 7, 8, 21, 28, 38, 42, 45, 51, 77–80, 92, 93, 178, 181, 183, 184, 188, 191, 201, 203, 222–225
 - Hitachi S-3400N 8
 - semi-crystalline polymers 141, 142
 - silane treated carbon nanotubes (SCNT)
 - effect of 107, 109
 - surface profiles 111
 - thermal images for 109–110
 - silica particle (SP) 92, 178
 - simple bone fracture 33
 - single glass/natural fiber composite (NNG) 87
 - single natural fiber/glass fiber composite (GGN) 87
 - sisal fiber 128, 130, 131
 - slide-roll modelling, wear equation
 - pure sliding 152
 - slide-roll ratios 153
 - squat simulation 154
 - wear parameters 155
 - slide-roll ratio 148
 - sliding speed, variation of 42
 - smaller precut bone 39
 - specimens
 - Archimedes principle 39

- ASTM 41
 - bone testing 5
 - dimension of 41
 - initial and final mass 39
 - weight loss for 55
 - spongy bone 34
 - squat simulation 154
 - standard squat 148, 151, 155–157
 - stereomicroscope 101, 103, 107
 - stir casting method 199
 - stress-strain curves 17, 18, 37, 46, 47
 - structural materials
 - (reinforcement) 115
 - synthetic fiber composites 147
 - synthetic fibers 53, 71, 72, 83, 120, 147, 164, 216
- t**
- Taguchi's experimental methods 42
 - tensile test 37
 - bones 3
 - UTM 7
 - thermal degradation 120
 - thermoplastics
 - matrices 163
 - structure 141
 - thermoset matrices 164
 - three-aminopropyltriethoxysilane 100
 - three-body abrasive wear (3-BAW) 54, 55, 86, 93, 103, 106, 109, 110, 112, 167, 174–176
 - tibiofemoral force, parameters 151
 - total knee replacements (TKR)
 - Archard's equation 149
 - force modelling, wear
 - equation 152–156
 - NFC 147
 - non-congruent form, knee joint 148
 - specific wear coefficient 147
 - standard and non-standard
 - squat 151–152
 - wear modelling methods 149–150
 - wear results 157–158
 - trabecular/cancellous bone 18, 34, 36, 38
 - tribological characterisation
 - FRP 71
 - glass fiber 72
 - jute fiber 73
 - materials and method 72–74
 - micrograph analysis 77–79
 - results and discussion 74–77
 - tribological test configuration 219
 - tribology 35, 53, 58, 71, 117, 145, 216
 - tribo testing machine, multi-channel
 - electronic unit 57
 - tribo wear test methods 55–57
 - tri-chlorovinyl silane 84, 85
 - twill interweave fabric 166
 - two-body (2-BAW) abrasive wear 54, 149, 167, 184
- u**
- ultra-high molecular weight
 - polyethylene (UHMWPE) 35, 59–61, 139–159
 - uncarbonized (BUNCp) banana
 - peels 121
 - universal testing machine (UTM) 7, 85, 201
 - unreinforced copper 200
 - unsaturated polyester 84, 164
- w**
- wear
 - abrasive wear 54
 - adhesion wear 54–55
 - mechanisms of 54–55
 - modelling methods 149–150
 - tribo wear test methods 55–57
 - wear and friction test
 - BOD 57
 - POD 55–57
 - wear on matrix (MW) 92
 - wear testing 217
 - abrasive wear 35
 - Archard's law 36
 - behaviour of 36
 - material removal rate 39
 - processes 35
 - sensor 39
 - three stage of 34
 - time-series 43
 - weight losses vs. 65
 - weighted decision matrix method 128

wet-dry bulb hygrometer concept 7, 8
World Health Organization
(WHO) 34, 119
World Tribology Congress (WTC) 53
worn surface morphology
 abrasive wear
 performance 188–192

C-E composite 183–184
worn surface, of N-USP 92
woven reinforcement 169

y

Young's modulus 16, 20, 37, 47, 142,
143, 215