

Index

a

acido iodidrico (HI) 221
 Advillin (Advillin-ChR2) 33
 Ag-/CdS-NW's 103
 alkylamines 241
 alkylthiols 241
 aluminum doped zinc oxide (ZnO:Al)
 224, 225, 227
 amorphous silicon based solar cells
 149–151
 anisotropic conductive film (ACF) 7
 anodic alumina membrane (AAM)
 229, 230, 232
 antireflection coating (ARC) layer 90,
 189
 aromatic thiols 241
 atomically thin 2D materials 47

b

backside reflector (BSR) 192, 201
 (2,2',2''-(1,3,5-benzinetriyl)-tris
 (1-phenyl-1-*H*-benzimidazole))
 19
 bi-color blue-green flexible LED 64
 bio-medical domain 41
 black phosphorus (BP) transistors 129
 blue and green μ -ILEDs 28
 blue-emitting μ -ILEDs 5, 6
 blue μ -ILED 28
 bolometric process 123
 bottom-up epitaxy 50–51
 bottom-up InP nanowire arrays 61
 buffer hole-injection layer (Buf-HIL)
 19

bulk ionization energy 239
 Buried oxide (BOX) 87, 89, 98

c

cadmium selenide (CdSe) QDs 8, 10,
 16, 193
 cadmium-tetradecylphosphonic acid
 (Cd-TDPA) 242
 carbon based solar cells 153–155
 CdTe thin film solar cells 224
 cetyltrimethylammonium bromide
 (CTAB) 242
 channel mode fracture 184
 channel rhodopsins 46
 chemical mechanical polishing (CMP)
 86
 chemical vapor deposition approaches
 213–214
 CH₃NH₃PbI₃ perovskite solar cells
 223
 close-spaced sublimation (CSS) 232
 clothing-integrated photovoltaics 167
 coefficient of thermal expansion (CTE)
 94
 colloidal perovskite QDs 19
 colloidal quantum dots (CQDs) 43,
 238, 239, 241–244
 color rendering index (CRI) 56, 65
 complementary
 metal-oxide-semiconductor
 (CMOS) process 52, 94, 117,
 144, 184
 compound semiconductors 98, 121,
 188

- controlled spalling technology (CST)
183, 184
- core-shell nanowire LEDs 51, 53, 54,
63
- core-shell QDs 10, 12, 13
- corning willow glass 231, 232
- crossed-nanowire LED arrays 60
- crystalline indium phosphide (InP)
179
- crystalline silicon based solar cells
HIT 146
light trapping structure 148–149
PERC 145–146
- crystalline silicon (c-Si) wafer 146,
150, 157
- curvilinear extended light sources 41
- CVD-graphene 48, 61, 67, 126, 128,
131
- d**
- direct mechanical peel-off of polymer-
embedded nanowires 43
- double-heterostructure (DH)
single-junction solar cells 180
- double junction cells 180–182
InGaP/GaAs 180–182
- dual transfer printing procedure 6
- dye-sensitized solar cells (DSSCs) 126,
127, 143
- e**
- e-beam evaporation 89, 90, 97, 227
- efficiency droop 50, 51
- electrochemical etching 86, 149
- electroluminescent (EL) QD-based
LEDs (QLEDs) 7–16, 19, 34
- electron backscatter diffraction 48
- epitaxial graphene 48
- epitaxial growth technique 86
- epitaxial lift-off (ELO) 42, 44, 46, 47,
69, 179, 183, 186–189, 191, 193,
202
- epitaxial lift-off/transfer printing 42
- 1,2-Ethanedithiol (EDT) 241, 242
- external quantum efficiency (EQE) 5,
10, 12, 13, 16, 19, 42, 50, 53, 88,
89, 93, 96, 119, 129, 131, 181, 228
- external quantum efficiency (EQE)
spectra 93, 181
- f**
- figures of merits (FOMs) 118, 120
- flexible all-graphene based devices
23
- flexible blue emitters 46
- flexible blue LED 45
- flexible CdTe/CdS solar cells
nanopillar solar cells
performance analysis 230–231
sample preparation 229–230
- polymer film
performance analysis 228–229
sample preparation 227–228
- thin glass
performance analysis 233–237
sample preparation 231–233
- flexible lateral p-i-n photodetector array
88, 89
- flexible LEDs 1, 20, 23, 25–28, 41–70
- flexible LEDs based on inorganic
bottom-up nanowires
nitride flexible LEDs on metal foils
57–59
ZnO nanowires 55–57
- flexible LEDs based on thin film transfer
conventional approaches for lift-off
and transfer of thin crystalline
films 43–46
thin film mechanical transfer using
van de Waals epitaxy 47–49
- flexible III-V LEDs 46
- flexible light sources and displays 41,
42
- flexible micro-inorganic LEDs (μ -ILEDs)
2–7, 10, 25, 28, 31, 34
- flexible nitride nanowire LEDs 62, 63,
65
- flexible nitride thin-film LEDs 45
- flexible optoelectronic systems in
neuroscience research
genetically modified recording and
stimulation 28–31
injectable neural probes 25–28
peripheral nervous system 32–33

- flexible perovskite LEDs (PeLEDs) 16–20
 - flexible perovskite solar cell
 - performance analysis 215, 221
 - sample preparation 214–215
 - flexible photodetectors
 - nanomembranes (NM) 82
 - nanowires (NW) 81
 - performance parameters
 - detectivity 83
 - I on/I off current ratio 84
 - photo conductive gain (G) 84
 - response time 84
 - responsivity 82–83
 - sensitivity (S) 84
 - flexible quantum dot LEDs (QLEDs) 7–16, 19
 - flexible red-emitting QLEDs 12
 - flexible silicon solar cells
 - bottom-up method
 - layer transfer method 156
 - SOI method 156–157
 - top-down method
 - SOM exfoliate method 157
 - wet etching method 157
 - flexible SNOP cells 233
 - flexible solar cells
 - applications 167–169
 - failure mechanism
 - fracture mechanics 166
 - Park's experimental study 162–163
 - shear lag model 163–166
 - flexible perovskite solar cells 214–221
 - performance analysis 215, 221
 - stability issues 221–222
 - flexible perovskite solar cell
 - sample preparation 214–215
 - perovskites materials
 - chemical vapor deposition
 - approaches 213–214
 - solution process deposition
 - approaches 209–211
 - vapor-assisted solution deposition
 - approaches 211–213
 - flexible substrates 214–221
 - 2D photodetectors
 - photogating detectors 135
 - photothermal effect 129
 - photovoltaic effect 125–126
 - plasma-wave-assisted THz detector 129–131
 - flexible transfer-printed blue InGaN LEDs 46
 - flexible 2D materials-based LEDs 20–23
 - flip-chip and vertical thin-film LEDs 45
 - fluorescent calcium indicators 24
 - 4 junction (4J) based cells 181, 197, 200
 - 4-junction solar cell 237
 - frame-assisted membrane transfer (FAMT) 98
 - fully-printed PeLEDs 20
 - fully transparent flexible nanowire LED 64
- g**
- GaAs/monolayer graphene/GaAs 48
 - GaAs/multilayer graphene/GaAs 48
 - GaAs photovoltaic devices 44
 - gallium arsenide (GaAs) 159, 178, 179
 - GaN core-shell micro-rod arrays 61
 - GaN-InGaN-GaN sandwich structure 45
 - genetically targeted calcium indicators (GCAMP1-7) 25, 28, 29, 31
 - genetically targeted sensor (GCAMP6) 28, 31
 - Ge NM-based flexible photodetectors 94–98
 - Ge on polyimide (GOP) 94, 109
 - germanium based solar cells 151–153
 - germanium-on-insulator (GeOI) 85
 - graphene 19, 20, 23, 43, 47, 48, 61, 65–67, 81, 118–126, 129, 131, 135, 136
 - graphene-based photodetector 129
 - green gap 50
 - green QDs/TiO₂ and red QDs/ZnO 11

h

halide anions 16, 242
 healthcare systems 177
 hetero-epitaxial nanowires 51
 heterogeneous DHNRs 12
 heterojunction with intrinsic thin layer (HIT) solar cell 144, 146
 hexagonal CVD-graphene nanodomains 67
 high-quality, monodisperse QDs 10
 high-quality nanowires 60
 hole-transport-material (HTM) 221
 hybrid passivation 242
 hydrochloric acid (HCl) 44, 188
 hydrofluoric acid (HF) 3, 186
 hydrogenated amorphous silicon (a-Si:H) 146, 149

i

iBeam materials 57
 indium gallium phosphide (InGaP) 179–180
 indium oxide flexible-PSCs 218–219
 indium tin oxide (ITO) 239
 infrared colloidal quantum dots solar cell
 PbS 239, 241
 surface passivation and air stability 239–243
 InGaN/GaN core/shell nanowires 66
 InGaN/GaN flexible visible LEDs 44
 InGaN/GaN LEDs 42, 45, 46, 52, 57, 62
 InGaN/GaN thin film LEDs 57
 InGaN LEDs 5, 45, 46, 48, 49, 63
 injectable neural probes 25
 ink-jet printing strategy 23
 inorganic flexible LEDs 43
 inorganic LEDs (ILEDs) 1, 42, 69, 196
 inorganic semiconductor 1, 41–70, 79, 81, 92
 inorganic semiconductor LEDs 42
 inorganic thin film flexible LEDs 43
 in-plane transferred nanowire LEDs 59–60
 vertically transferred nanowire LEDs 60–65
 InP NM 85, 98, 99

internal quantum efficiency (IQE) 5, 53, 119

intrinsic crystalline integrity 221

intrinsic ZnO (i-ZnO) 224, 228

k

Kapton 12

l

Langmuir-Blodgett technique 60
 laser lift-off technique 5, 45
 layer transfer method 42, 156
 lead iodide (PbI₂) 210, 215
 ligand passivation 241, 242
 light emitting diodes (LEDs) 1, 81
 light-responsive QLED 12
 light trapping structure 148–149
 low aspect ratio nanowires 43, 65
 luminescent dyes 191
 luminescent solar concentrators (LSCs) 191–193
 luminophores 191

m

MAPbBr₃ 17, 19, 20
 mass-produced n-type ZnO nanowires 59
 MBE-grown InGaN LED film 45
 mechanical spalling 184–186
 mercaptocarboxylic acids (MPA) 241
 metal-assisted chemical etching (MACE) 149, 151
 metal chalcogenide complexes (MCC) 242
 metal halide perovskites 2, 16
 metal-insulator-semiconductor (MIS) photodetectors Ge 94–98
 metallic foils 214
 metal organic chemical vapor deposition (MOCVD) 3, 45, 57, 63, 66, 67, 86, 151, 179, 182, 197, 232
 metalorganic-hydride vapor phase epitaxy 52
 metal-organic vapor deposition (MOCVD) 179
 metal-organic vapor-phase epitaxy (MOVPE) method 48, 181

- metal oxide semiconductor field effect transistor (MOSFET) 89, 90
- metal-semiconductor-metal (MSM) photodetectors Ge 97
- methylamine hydrochloride (MAcI) 210
- methyl ammonium lead bromide (MAPbBr₃) 19
- microcrystalline silicon (mc-Si:H) 151
- micro-inorganic photodetectors (μ -IPDs) 6, 7, 34
- micro-LED displays 50
- micro-pyramids 43
- micro-scale GaAs based thin-film LEDs 46
- microscale ILEDs 2
- micro-sized surgery robots 41
- micro-transfer printing 44–46
- micro-transferred InGaN/GaN LEDs 46
- miniaturized flexible LEDs 25–28
- mixed-mode fracture theory 162, 166
- molecular beam epitaxy (MBE) 45, 51–53, 65, 67, 86, 182, 197
- MOVPE AlN film 48
- MOVPE nanowire LEDs 52
- μ -ILED-based probes 25
- μ -ILEDs involved red-emitting AlInGaP epitaxial structure 2
- multijunction (MJ) 177, 178, 180, 181, 201, 202, 237, 243
- multijunction (MJ) solar cells 181, 201, 202
- multiple photolithography 3
- multi quantum wells (MQW) 4, 16, 21, 49
- n**
- nanocrystal lumophores 193
- nanomembranes (NM)
- III-V 98–100
 - donor substrates
 - epitaxial growth 86
 - Smart-Cut[®] technique 85–86
 - flexibility and bendability of 79
 - Ge 94–98
 - Si 88–93
- thickness of 79
 - transfer printing of 86–88
- nano printing process 148
- Nano scale photon detection 81
- nanostructure lift-off using van der Waals epitaxy 65–68
- nanowire(s) 43
- nanowire-based flexible LEDs 43
- nanowire LEDs 50–57, 59–66, 69
- nanowire membrane formation 61
- nanowires (NW) based flexible detectors
- critical parameters for 110
 - fabrication of
 - AgNWs/CdS 101–103
 - single crystal Si NWs 100
 - TFTs assembly of 101
 - length and diameter of 83
 - properties of 81
- National renewable energy laboratory (NREL) 179, 181, 234–236, 244
- net acceptor density (N_A) 237
- neutral mechanical plane (NMP) 3
- nickel (Ni) 184
- nitride flexible LEDs 41
- nitride flexible LEDs on metal foils 57–59
- in-plane transferred nanowire LEDs 59–60
- nitride nanowires 51, 52, 57, 61
- noise equivalent power (NEP) 83, 119
- non-indium oxide flexible-PSCs 216
- N-type crystalline silicon solar cells 144
- O**
- oleic acid (OA) 241
- I - V measurement 104, 106–108
- dark and light conditions 108
- open-circuit voltages (V_{oc}) 146, 150, 178, 179, 182, 189, 191, 201, 202, 226, 232, 240
- optimized flexible QLED device structure 11
- opto-electronic detectors 81
- optogenetics 24–26, 28, 31–33, 41, 46, 196

- organic light emitting diodes (OLEDs) 1, 7, 10, 19, 42
- organic semiconductors 42, 59, 79, 92
- p**
- Panasonic's HIT-IBC solar cells 146
- passivated emitter and rear cell (PERC) 144, 145
- PbS-based QDs 10
- perovskites 2, 16–20, 209–223
- perovskite semiconductors 16
- perovskites materials
 - chemical vapor deposition approaches 213–214
 - solution process deposition approaches 209–211
 - vapor-assisted solution deposition approaches 211–213
- phosphor-converted flexible white nanowire LED 65
- phosphor-converted white LEDs 52, 64
- phosphor-free flexible InGaN/GaN nanowire LEDs 65
- phosphors 5, 52, 63–65, 180, 191
- photo conductive gain (G) 82, 84, 135
- photocurrent, light density 103
- photodetectors 81
 - performance metrics 118–120
 - 2D materials 117–118
- photogating detectors 135
- photogating effect 124, 135
- photon recycling 178, 179, 181, 200–202
- photosensitivity of device 106
- photo thermal effect 129
- photothermoelectric effect 121–124
- photovoltaic (PV) 16, 178
- photovoltaic effect 121, 123, 125, 129, 240
- photovoltaic (PV) power conversion efficiencies 16
- piezo-phototronic effect 57, 61, 69
- plasma-assisted MBE technique 52
- plasma-wave-assisted THz detector 123, 129–131
- p-ohmic metal 188
- polydimethylsiloxane (PDMS) 3, 46, 82, 135, 162, 190, 230, 231
- poly(3,4-ethylenedioxythiophene) poly(styrenesulfonate) (PEDOT:PSS) layer 55, 161
- polyethylene naphthalate (PEN) 8, 11, 131, 135, 214
- poly(ethylene oxide) (PEO) 20
- polyethylene terephthalate (PET) 6, 55, 82, 125, 129, 189, 214
- polyimide (PI) 214
- polyimide (PI) foil 233
- polyimide or polydimethylsiloxane (PDMS) 3–5, 7, 10, 12, 46, 61, 63–65, 82, 101, 190
- polyimide (PI) substrates 7, 126, 227, 228
- polymer LEDs 42
- poly[2-methoxy-5-(2'-ethylhexyloxy-*p*-phenylenevinylene)] (MEH-PPV) 239
- poly(*p*-phenylenevinylene) (PPV) 239
- post-lift-off GaAs substrates 44
- power consumption 79, 118, 120, 121
- power-conversion efficiency (PCE) 16, 126, 155, 178, 179, 214, 220, 238
- processable perovskite solar cells (PSCs) 143, 209, 211, 214, 215, 221
- q**
- QD emission characteristics 10
- quantum-confined Stark effect 50, 51
- quantum dot LEDs 43
- quantum dots (QDs) 2, 7, 117, 191
- quantum efficiency (QE) 5, 20, 42, 50, 53, 89, 118, 119, 131, 149, 235
- r**
- reactive ion etching (RIE) 87, 98, 148, 149
- red-emitting AlGaInP epitaxial layers 7
- red-emitting, flexible vertical μ -ILEDs 7
- redox reaction 243
- reduced graphene oxide (rGO) 23, 126, 155

reflectance (R) 228
 remote epitaxy 47, 48
 remote' homoepitaxy method 188
 resonant regime of plasma-wave
 photodetection 131
 roll-to-roll (R2R) 136, 151, 211, 228

S

sapphire 6, 45, 47–49, 63
 scanning electron microscope (SEM)
 4, 53, 56, 59, 60, 67, 93, 102,
 103, 149, 162, 202, 225, 230
 self-assemble GaN nanowire LEDs
 57
 self-assembled MOCVD core-shell
 nanowire InGaN LEDs 63
 self-organized conducting polymer
 (SOCP) 19
 semiconductor NM 79, 85–88
 semiconductor-on-insulator 85, 86
 semiconductor on metal (SOM)
 exfoliate method 157
 sensitivity (S) 34, 41, 81–84, 108, 110,
 111, 118, 123
 separation by implantation of oxygen
 (SIMOX) technology 157
 series-connected amorphous silicon
 (a-Si:H) 146, 149–151
 series-connection through apertures
 formed on film (SCAF) 151
 serpentine-shaped interconnects 3
 shear lag model 162, 165
 Shockley-Queisser (SQ) theory 19, 178
 short circuit current density (J_{SC}) 126,
 146, 149, 179, 189, 228, 229, 232
 Si NM-based flexible photodetectors
 88–93
 silicon based solar cells
 amorphous 149–151
 crystalline 145–149
 PV process 144
 silicon-germanium alloys (SiGe) 152
 silicon-on-insulator (SOI) 65, 86, 117,
 156, 184
 single crystalline NMs 81, 86
 single crystal Si NWs 100
 single-crystal solar cells 211, 237

single junction solar cells
 GaAs 178–179
 InGaP 179–180
 InP 179
 Si photonics 51, 117
 smart sensor system 12
 Smart-Cut[®] technique 85–86, 94, 183
 soft lithographic techniques 46
 SOI method 156–157
 solution process deposition approaches
 210–211
 spectral response (SR) 109, 180, 228,
 241
 spectral splitting 200
 stretchable μ -ILED array 7
 substrate etching 42
 sun's power spectrum 237
 surface tension-assisted (STA) 188

T

thin crystalline films 43–46
 thin-film inorganic solar cells 193
 thin film mechanical transfer 47–49
 thin-film III–V solar cells, flexible
 substrates
 ELO 186–189
 mechanical designs 190–191
 mechanical spalling 184–186
 3D finite-difference time-domain (3D
 FDTD) technique, Si NM 90
 III–V NM-based flexible
 photodetectors 98–100
 III–V solar cells
 applications 193–196
 double junction cells
 InGaP/GaAs 180–82
 future generations
 mechanical stack 197–200
 more junctions 197
 photon recycling 200–202
 spectral splitting 200
 single junction solar cells
 GaAs 178–179
 InGaP 179–180
 InP 179
 triple junction cells
 InGaP/GaAs/Ge 182

- III–V* solar cells (*contd.*)
 InGaP/GaAs/InGaAs 182–183
 InGaP/GaAs/InGaAsNSb 183
 top-down etched Si microwire arrays
 61
 transfer 11, 32, 42, 47, 48, 61
 transfer printing 2, 3, 5–7, 10–12, 28,
 34, 42, 86–88, 191
 transition metal dichalcogenides
 (TMDs) 20, 21, 118
 transmission electron microscope
 (TEM) 152, 230, 232
 transmittance (T) 126, 214, 215, 228,
 234
 transparent conducting oxide (TCO)
 126, 227, 229, 232
 transparent conductive electrodes
 (TCE) 126
 triple junction cells
 InGaP/GaAs/Ge 182
 InGaP/GaAs/InGaAs 182–183
 InGaP/GaAs/InGaAsNSb 183
 TrpV1 promoter 33
 2D emitting materials 20
 2D FAPbBr₃ 17, 19
 2D materials-based photodetectors
 bolometric process 123
 flexible substrates
 photogating detectors 135
 photo thermal effect 129
 photovoltaic effect 125–126
 plasma-wave-assisted THz detector
 129–131
 nano-photonic techniques 136
 photogating effect 124
 photothermoelectric effect 121–123
 photovoltaic effect 121
 plasma-wave-assisted mechanism
 123
 plasma-wave-assisted Terahertz
 Detection 123
 2D nanoplatelets 16
- u**
 ultraviolet (UV) 57, 111, 118, 180, 221,
 233
 ultraviolet (UV) light 180
- unmanned aerial vehicles (UAVs) 177
 US National Renewable Energy
 Laboratory (NREL) 179
 UV absorption 109
 CdSe, P3HT and hybrid
 photodetector spectra 109
- v**
 van der Waals epitaxy 43, 47, 48,
 65–69
 van der Waals (vdW) heterojunctions
 23, 121, 136
 vapor-assisted solution deposition
 approaches 211–213
 vertically transferred nanowire flexible
 light sources 61
 vertically transferred nanowire LEDs
 60–65
 nanostructure lift-off using van der
 Waals epitaxy 65–68
 very high bond (VHB) film 135
- w**
 waterproof flexible LEDs 46
 wet etching 5, 7, 45, 85, 89, 94, 98, 157,
 161, 182, 186
 wet etching method 45, 157
 white nanowire LED 53, 54, 65
 wireless, battery-free optogenetic
 stimulation devices 32–33
 wireless, flexible optoelectronic systems
 28–31
 wurtzite crystal structure 57
- y**
 yellow nanophosphors 53, 65
- z**
 ZnO nanowire LEDs 56, 57
 ZnO nanowire/p-polymer LED array
 57
 ZnO nanowires-based flexible LEDs
 55–57
 ZnO nanowires/poly (9,
 9-dioctylfluorene) (PFO) hybrid
 structure 56
 ZnO/organic hybrid white LEDs 56