

Index

a

ab initio calculations 425
 active layer, of origami device 304
 additive process, 3D origami fabrication
 290–292
 Airy stress function 149
 ALD-synthesized ZnO nanomembranes
 223
 alginate nanomembrane 212
 AlInP semiconductor microtube resonator
 370
 alternating current (AC) 117
 alucone-coated Li-S battery 233
 amorphous Si (a-Si) nanomembranes, rate
 capability of 229
 amphiphilic polymer nanomembranes
 75
 anisotropic magnetoresistance (AMR)
 105, 112–113
 antenna on-chip (AOC) 336
 antennas, rolled-up 336
 antiferromagnetic (AFM) membranes
 107, 108, 110
 antiferromagnetic transition 120
 atomic layer deposition (ALD) 107
 axial confinement, of rolled-up WGM
 microtubes 366

b

back-thinning method 37
 ball milling (BM) 195
 band structure, of 2D transition metal
 dichalcogenides 417

BEHM model 176
 bifurcation of multi-stable structures
 179
 bilayer SiN_x based S-RuM device 325
 bimetallic catalytic Pt/Au nanorods 260
 bi-metal strip deflection 325
 biocompatibility 33
 biodegradable polymers 27
 bioimplantable electronics 95–97
 bioinspired structures, multilayer stability
 180–181
 biological and synthetic swimmers 257
 biomedical devices 17–18
 biomimetic microelectronics 211
 bistability 153
 bistable and neutral stable shells
 177–180
 bistable and reconfigurable
 nanomembrane
 experiments 153–157
 mesostructures 157–159
 bistable structures 144
 blown-bubble technique 431
 BMIMBF₄ gel electrolyte-based actuator
 69
 Boltzmann constant 31, 107
 boron carbon nitride (BCN) electrodes
 241–242
 Brownian diffusion 254
 Brownian effects 128
 bubble-based nanomembots 275
 bubble propelled nanomembots 264

- Buchwald-Hartwig coupling reactions 76
- buckling induced bending/twisting assembly
 deformation mode ratio 7
 engineered substrate strategies 10–11
 Kirigami design strategy 7–9
 multilayer design strategy 9–10
- buckling induced folding assembly
 loading path strategy 6
 non-uniform thickness strategy 3–4
 plasticity strategy 4–6
- bulk inorganic semiconductors 87
- buried oxide layer (BOX) 36
- C**
- capillary origami 301
- capillary self-folding mechanisms 291
- carbon nanotubes (CNTs) 194
- catalytic hydrogel KMnO₄ nanomembot 276
- CCW mode, of WGM 358
- cell behavior regulation
 migration and differentiation 203–206
 morphology and arrangement 200–203
 neurite signaling mediation 209
 neuron cell outgrowth 206–209
 proliferation and mitosis 203
- cell capture 209–210
- cell scaffolding nanomembranes
 cell behavior regulation 200–209
 rolled-up scaffold 197–200
 two-dimensional biocompatible nanomembranes 194–197
- chemical actuation strategy 302
- chemically-powered nanomembots 260
- chemical-responsive origami
 gas-responsive origami 303–304
 solution-responsive origami 302–303
- chemical stimuli 293
- chemical vapor deposition (CVD) 30, 61, 403
- chiral nanoarchitectures 172
- chromosome segregation errors (CSEs) 203
- circular dichroism (CD) 19
- cobalt nanomembranes 108
- CoFeSiB microwires 122
- complementary metal-oxide-semiconductor (CMOS) technology 86
- complex programmable modular microbots 267
- compressive strain, 2D TMDs 424, 425
- conducting materials 29
- conducting polymers (CPs) 194
- continuum elasticity theory 145, 150
- 2400-Co₃O₄/CC, capacitance of 236
- copolymerization of polymers 74
- Cr/VO₂ nanomembrane 153
- cryo transmission electron microscopy (cryo-TEM) 172
- crystalline MgO 117
- crystalline Si (c-Si) nanomembranes, rate capability of 229
- C/Si/C trilayer nanomembranes, for Li-ion batteries 226
- Curie point 120
- curie temperature/metamagnetism 120
- Curie–Weiss law 120
- CW mode, of WGM 358
- cyclic poly (phthalaldehyde) (cPPA) 46
- C/ZnO nanomembranes foam 223–224
- d**
- Da Vinci surgical system 125
- deep reactive ion etching (DRIE) 37
- deformations, in origami 289, 291
- degree of polarization (DoP) 427
- deionized water (DIW) 28
- density functional theory (DFT) 31
- density of states (DOS) 116
- Diamond Anvil Cells (DACs) 431–432
- dielectrics materials 33
- diethylenetriaminepentaacetic acid (DTPA) 210
- dip coating 58
- dorsal root ganglion (DRG) 18
- dynamic axial mode turning strategy 365

e

E-beam evaporation technologies 11
 elastica theory 4, 6
 electrical dissolution rate (EDR) 29
 electrical/electrochemical control, of
 nanomembots 270–272
 electrically small antenna (ESA) 14
 electrically triggered devices 46
 electrical stimuli-responsive 4D origami
 299
 electric double-layer capacitors,
 nanomembranes for 239
 electric field distributions, of WGMs 356
 electroactive hydrogels (EAH) 272
 electro-active origami microrobot 300
 electrode-nerve interface 96
 electromagnetic device 14
 electromyography (EMG) 94
 electromyography (EMG) sensor 93
 electronic-eye system 91, 92
 electro-thermal co-optimization, of
 S-RuM power inductors 343
 encoding multi-shape-morphing
 nanomembots 265
 endothelial cells (ECs) 214
 energy harvesters, 3D
 micro/nano-structures 18
 energy storage devices 222
 Li-ion batteries 223–227
 Li-S batteries 230–233
 Na-ion batteries 227–230
 supercapacitor 233–239
 Zn-ion batteries 229–230
 engineered modulus strategy 10
 engineered substrate strategies 10
 engineered thickness strategy 10
 epidermal electronics 93
 epidermal electronic system (EES) 93,
 94
 evanescent field coupling, in tubular
 WGM microcavities 361
 exchange-correlation (XC) function 32
 exchange-coupled anisotropy 110
 excitonic effects, of 2D TMDs 420–421

externally-controlled multimodal
 magneto-elastic nanomembot
 273
 external-strain-based method, axial mode
 tuning 366, 367
 extracellular matrix (ECM) 193

f

fabrication of magnetic nanomembranes
 107
 FeCo₂S₄/RGO nanomembrane multilayer
 structure 234, 235
 FeOOH QDs nanomembrane/graphene
 hybrid nanosheet electrodes 234,
 235
 Fe₃O₄-type materials 107
 ferrimagnetism 107
 ferrofluid-filled S-RuM power inductors
 343
 ferromagnetic (FM) 110
 ferromagnetic fine particles 106
 ferromagnetic layers, of MTJs 116
 ferromagnetic (FM) materials 107
 ferromagnetic particles 107
 fibronectin 198
 FIB-SID technology 338
 finite-difference time-domain (FDTD)
 method 356
 finite element analysis (FEA) 4
 finite element method (FEM) 146,
 325–327, 356
 simulation 156
 flexible electronic devices 85
 flexible electronics 95
 bioimplantable electronics 95
 bottom-up technique 89
 epidermal electronics 93
 flexible photo imaging 90–93
 mechanical designs 88
 sensing systems 90–93
 strategies 86–88
 top-down technique 89
 types of 91
 flexible optoelectronic devices 90
 flexible photo imaging 90

- flexible photonic devices 90
- flexible TMR sensor 117
- focused ion beam (FIB) triggered origami 292
- Föppl–von Kármán plate theory 145, 147–150
- 4D origami 287
 - microrobots 306
- free-standing chitosan 212
- Frenet-Serret frame 152
- FvK kinematics connect 147

- g**
- GaAs/InGaAs nanomembrane 199
- gas purification 69
- gas-responsive origami 303
- gas sensors, 2D materials nanomembrane 398–400
- Gaussian curvature 149
- Gauss Theorema Egregium 148
- genetic algorithm method (GA) 20
- GeSn rolled-up microtubes 370
- giant magnetoimpedance (GMI) 106, 118
- giant magnetoresistance (GMR) 106, 113
- Gibbs free energy 112
- 3-glycidoxypropyltrimethoxysilane (GOPS) 65
- GMR sensorics 124
- Goos-Hanchen shift (GHS) 361
- gradual bending 289, 292
- graphene-activated optoplasmonic microcavity 371, 379
- graphene-based bimorph microactuator 405
- graphene/epoxy hybrid bimorph actuator 403
- graphene gas sensors 401
- graphene nanomembrane arrays, for Na-ion batteries 227, 228
- graphene optical lens 395
- graphene oxide (GO) 195
- graphene-PDMS nanocomposite/gold bilayer-based multi-response soft actuator 406

- h**
- HeLa cells 203, 211
- helical microbot 126
- helical nanomembots 256
- helical ribbon 151
 - mechanical self-assembly 163–166
 - shape instability and transitions in 166–169
- helical stable shapes 177
- helical structures 144, 150, 172
- helices 164
- Helmholtz coil 119
- Helmholtz equation 355
- Hessian matrix 150
- high Q-factor tubular rolled-up optofluidic ring resonators 371–373
- homogeneous strain, 2D TMDs 424, 425
- Hooke's law 145
- human mesenchymal stem cells (hMSCs) 199, 205
- humidity sensing, with rolled-up polymer/oxide/polymer microcavity 378
- humidity-sensitive polypyrrole nanomembrane 299
- Husimi function 358
- hydrogel-based stimuli-responsive polymer 210
- hydrogen purification 71

- i**
- indium–gallium–zinc–oxide (IGZO) 90, 211
- inductive coupled plasma reactive ion etching (ICP-RIE) 37
- inertial layer, of origami device 304
- InGaAs/GaAs quantum dot microtubes 370
- InGaAs strained bilayer 199
- inhomogeneous strain, 2D TMDs 424, 425
- inorganic flexible electronics 90
- inorganic semiconductors 85, 86
- inorganic transient electronic device 27

- in-plane strain, 2D TMDs 424–425
 - interface anisotropy 110
 - interfacial energy 164
 - interfacial polymerization 62
 - ion-beam actuation, of Ti/Al/Cr
 - multilayer cubic assembled origami 292
 - isosceles nanoribbons 166
 - itinerant metamagnetism 120
- j**
- Janus nanomembot 261
 - Julière's model 116
- k**
- Kelvin temperature 31
 - Kirchhoff theory 145
 - kirigami 289
 - kirigami concept 87
 - Kirigami design strategy 7
 - Kirigami principle, of 2D material nanomembrane 396
 - KMnO₄/hydrogel nanomembot 276
- l**
- Langmuir-Blodgett (LB) films 60
 - large-scale transfer printing 37
 - lasing behaviors, of electrical-pumped rolled-up microtube laser 381
 - latex rubber sheets 164
 - layer by layer assembly 60
 - layered VS₂ nanomembranes 229, 230
 - lead zirconate titanate 95
 - left-handed circularly polarized light (RCP) 19
 - ligand-modified nanomembots 277
 - light-assisted water cleaning 276
 - light propagation, in tubular WGM microcavities
 - evanescent field coupling and optical characterization 361–362
 - Q factor and optical loss 359–360
 - structural asymmetry 362–368
 - light-responsive origami 296
 - light-thermal conversion actuated origami 296
 - Li-ion batteries 223
 - linear elasticity theory
 - bistable and reconfigurable nanomembrane 153–159
 - continuum elasticity theory 150–153
 - Föppl–von Kármán plate theory 147–150
 - linearized Kirchhoff theory 146–147
 - stresses and strains 145
 - linearized Kirchhoff theory 146–147
 - liquid crystal elastomers (LCEs) 406
 - liquid crystal polymer networks 169
 - liquid-phase exfoliation (LPE) 195
 - liquid-phase techniques 61
 - lithium-sulfur (Li-S) batteries 231
 - loading path strategy 6
 - Lorentz force 112
- m**
- macroscale robot 131
 - magnetic actuation 120
 - magnetic anisotropy
 - exchange-coupled anisotropy 110–111
 - interface anisotropy 110
 - magnetocrystalline anisotropy 108–109
 - shape anisotropy 109–110
 - stress-induced anisotropy 111–112
 - magnetic anisotropy constant 119
 - magnetic field (*B*), 119
 - magnetic field powered/controlled
 - motion of nanomembots 264
 - magnetic field strength detection 121
 - magnetic force 119
 - magnetic force microscopy (MFM) 112
 - magnetic materials 105
 - fabrication of 107–108
 - types 106–107
 - magnetic microbot 124
 - helical microbot 126–128
 - reconfigurable micromachines 130–133
 - tubular microbots 128–130

- magnetic microelectromechanical system (m-MEMS) 123
- magnetic nanomembranes
 - curie temperature/metamagnetism 120–121
 - functionalities 133
- magnetic microbot 124
 - helical microbot 126–128
 - reconfigurable micromachines 130–133
 - tubular microbots 128–130
- magnetic sensorics
 - magnetic field strength 121–123
 - motion and displacement 123–124
- magnetic torque and force 119–120
- magneto-electronic properties
 - AMR effect 112–113
 - GMI effect 117–119
 - GMR effect 113–116
 - Planar Hall effect 119
 - TMR effect 116–117
- overview 105106
- magnetic order 105
- magnetic responsive 4D origami 304
- magnetic-responsive origami 299
- magnetic sensorics 120
 - magnetic field strength 121–123
 - motion and displacement 123–124
- magnetic tunnel junctions (MTJs) 108, 116
- magnetocrystalline anisotropy 108
- magneto-electronic properties
 - AMR effect 112–113
 - GMI effect 117–119
 - GMR effect 113–116
 - Planar Hall effect 119
 - TMR effect 116–117
- magneto-optical Kerr effect (MOKE) 110, 112, 113
- magnetoresistance (MR) ratio 113
- magnetoresistive sensorics 121
- magnetron sputtering technologies 11
- mechanical self-assembly of rolled-up tubes 169–172
- mechanical sensors, 2D materials
 - nanomembrane 400–402
- mechanical stresses 143
- metal-coated polymer magnetic flagellum-like sperm-bots 264
- metal-insulator-metal (MIM) RF capacitor 333
- metal nanomembranes 29
- metal organic frameworks (MOF) materials 239
- metal/polymer nanomembranes 64
- metal/polyvinyl alcohol (PVA)-poly (acrylic acid) (PAA) microtube origami 303
- metamagnetism 120
- methane sulfonic acid (MSA) 43
- 2-(4-methoxystyryl)-4,6-bis (trichloromethyl)-1,3,5-triazine (MBTT) 46
- methylene blue pollutant removal 276
- microbubble-based nanomembots 275
- micro-catapult natural sporangium 155
- microelectronics based, nanomembrane technologies 1
- microengines 128, 129
- microfluidics 256
- microfluidics-based fabrication, of silica microbubbles 275
- micromotor with hollow catalytic shells 261
- micro/nano-electromechanical systems (MEMS/NEMS) 1
- micro-/nano-structures
 - chiral nanoarchitectures 172–175
 - mechanical self-assembly 169–172
 - mechanical self-assembly of helical ribbons 163–166
 - shape instability and transitions 166–169
 - wrinkling in thin flexible layers 159–163
- microscalops 132
- microsupercapacitors (MSCs) 343
- microtube helical antenna design 341
- Mindlin-Reissner shell theory 340

- miniature soft robots 132
- Miura folding mode 394
- molybdenum disulfide (MoS₂) single
 - layer, reversible conversion of 393
- monolayer WSe₂ lateral homojunction device 436
- mono-stable helical ribbons 168
- mountain fold (origami) 289
- moving morphable components method (MMC) 20
- m-phenylenediamine (MPD) 72
- multidirectional twisting 289
- multilayer design strategy 9
- multilayer stability
 - bioinspired structures 180–181
 - bistable and neutral stable shells 177–181
 - tristability of bilayer composite 175–177
- multistable shell design space 179
- MXenes 405
- n**
- Na-ion batteries 227
- nanobots 254
- nanoelectromechanical systems (NEMS) 143
- nanoelectron mechanical systems (NEMS) 150
- nano-engineered membranes 74
- nanomagnetic-encoding origami flapping
 - bird 301
- nanomembots 254, 255
 - autonomous 278
 - based on rolled-up catalytic nanomembranes 263
 - biomedical applications 273–275
 - in biosensing 273
 - chemically-powered 260–264
 - dynamic parameters and forces of 259
 - electrical and electrochemical control 270–272
 - light-powered motion of 268–270
 - magnetic field powered/controlled motion 264–268
 - man-made 278
 - principles of motion at microscale 256
 - ultrasound-modulated propulsion 272
 - water cleaning and environmental remediation 275–278
- nanomembrane-based origami response
 - to external stimuli 293
 - chemical-responsive origami 302–304
 - electric responsive origami 299
 - light-responsive origami 296–297
 - magnetic-responsive origami 299–301
 - thermal/temperature-responsive origami 293–296
 - ultrasonic responsive origami 297–299
- nanomembrane based rolled-up capacitors 344
- nanomembrane based transient electronics 28
- nanomembrane enhanced therapy
 - cell analysis platform 210–212
 - cell capture 209–210
 - tissue mimicking and enhanced therapy 212–215
- nanomembranes
 - bistable structures 144
 - in energy storage devices 222
 - helical structures 144
 - passive transient electronic device 28
 - wrinkling in thin flexible layers 159–163
- nanomembrane technology 1
- nanomembrane transient devices
 - back-thinning method 37–39
 - solution based processes 35–36
 - transfer printing technique 36–37
- nanoscale chiral twists 172
- nanostuctured PEDOT/A-CNT electrode 237, 238
- n-dodecyl pyridinium chloride 68
- near field communication (NFC) 1
- needle-shaped flexible piezoelectric microsystem 95

- neural stem cells (NSCs) 197
 Lamellipodium and filamentous 205
 neural stem/progenitor cells (NSPCs) 195
 neurite signaling mediation 209
 neuron cells 206
 neutrally stable structures 178
 neutral stable shells, bistable 177–180
 Newtonian fluids 131
 NF electrodes 237
 nickel cobaltite (NiCo_2O_4)
 nanomembranes 229
 nickel nanomembranes 107
 Ni-Fe alloy 111
 NM-based PIN diode array 43
 N,N-methylene bisacrylamide 68
 nonmagnetic (NM) layer 114
 non-Newtonian fluids 132
 non-uniform thickness strategy 3
 nuclear envelope breakdown (NBE) 203
 nucleophilic ions 31
- O**
- on-chip antennas 337, 338
 optical devices 18–19
 optical helical antenna 338
 optical loss, of WGM 360
 optically triggered designs 46
 ordinary differential equations (ODEs) 144
 organic/inorganic hybrid nanomembrane 233
 organic ReRAM 35
 organic transient electronics 35
 origami
 advantages 287
 of 2D material nanomembrane 396–398
 origami assembly methods 2, 20
 origami-inspired photo imaging 92
 out-of-plane strain, 2D TMDs 424
 oxidative chemical vapor deposition (oCVD) 238
 oxide materials, for rolled-up tubular
 optical microcavities 371
- P**
- partially bonded strip, numerical
 simulation 176–177
 passive transient electronic device 28
 pattern designing on planar structure 289
 $\text{Pb}(\text{Zr}_{0.52}\text{Ti}_{0.48})\text{O}_3$ (PZT) 12
 p-channel Si NM MOSFETs (pMOS) 15
 PCloendash PLGA tubes 214
 Pd/Cr/Ti nanomembranes 303
 Peclet number (Pe) 258
 peptide amphiphile (PA) 172
 permeability 67
 perpendicular magnetic anisotropy (PMA) 110
 phosphate-buffered saline (PBS) 31, 211
 phosphate-buffered saline solution (PBS) 14
 photo-acid generator (PAG) 46
 photonic quasi-Schrodinger equation 356
 photostriction actuated origami 297
 photothermally-driven nanomembot 269
 pH-responsive 3D printing polymer 404
 pH-responsive nanomembrane 302
 physical stimuli 293
 physical vapor deposition (PVD) 107
 piezoelectric materials 12, 17
 piezoresistive devices as strain sensors 437
 PILf_2N 77
 planar Hall effect (PHE) 106, 119
 planar micro-supercapacitor integrated
 with boron carbon nitride (BCN)
 electrodes 241, 242
 plasma-enhanced chemical vapor
 deposition (PECVD) 200
 plasticity strategy 4
 $\text{P-NiCo}_2\text{O}_{4-x}$ //Zn battery 230
 Poincaré surface of section (SOS) of
 microcavity 357
 point-of-care (PoC) diagnostics 122
 Poisson's ratio 149, 159
 polarization tuning phenomenon 368

- poly(3,4-ethylenedioxyhiophene) 76
poly (3-thiophene methyl acetate)
(P3TMA) 195
poly(acrylamide) 60
poly(acrylic acid) 60
poly(dl-lactide-co-glycolide) (PLGA)
214
poly(ϵ -caprolactone) (PCL) 43, 214
poly(ethylene oxide) (PEO) 71, 74
poly(lactic-co-glycolic acid) (PLGA) 14
poly(methacrylic acid) (PMAA) 71
poly(phthalaldehyde) 46
poly(styrene sulfonate) 60
poly(tetramethylene succinate) (PE44)
195
polyacrylic acid (PAA) 194
poly- α -methyl styrene (PAMS) 45
polydimethylsiloxane (PDMS) 3, 36,
124, 162, 194, 210, 212
poly-d-lysine(PDL) 198
polydopamine (PDA) 66
polyelectrolyte multilayer (PEM) 195
polyethene glycol diacrylate (PEGDA)
194
polyethylene glycol terephthalate (PET)
6
polyethylene terephthalate (PET) 36, 71,
76, 117
poly-l-ornithine (PLO) 194
polymer 57
polymer-based substrates 194
polymer electrolyte membrane unitized
regenerative fuel cells
(PEM-URFCs) 74
polymer electrolyte nanomembrane 74
polymeric nanomembrane 61, 63, 66
permeation control 67
polymer nanocomposites method 65
polymer nanomembranes 58
actuators and microrobots 76–78
chemical vapor deposition 61–62
fabrication and functionalization
58–64
gas purification 69–72
interfacial polymerization 62–63
Langmuir-Blodgett (LB) films 60
layer by layer assembly 60
mechanical properties 65
metal/ polymer nanomembranes 64
nanomaterials incorporation 63
permeability 67–68
polymer electrolyte nanomembrane
74–76
polymer nanomembrane 63
spin coating and dip coating 58–60
stability 67
stimuli-responsive properties 68–69
waste water treatment 72–74
polymer tubular microbot 269
Polypodium aureum 155
polypyrrole-cadmium (PPy-Cd) nanowire
hybrids 270
polystyrene (PS) 194
polystyrene-poly (4-vinyl pyridine)
(PS-P4VP) 59
polysuccinimide/polycaprolactone
(PSI/PCL) microtubes 210
poly (N-isopropyl acrylamide) (PNIPAM)
thermo-responsive hydrogel
294
polythiophene-coated porous structure,
morphology and performance of
239
polyvinylidene difluoride (PVDF)
12, 72
porous carbon/ZnO nanomembrane/
porous carbon (CZC) trilayer
nanosheets, for Li-ion batteries
225
porous polymer nanomembranes 77
postsynaptic currents (PSCs) 195, 209
potassium hydroxide (KOH) 31
power system in package (PSiP) 342
power system on chip (PSoC) 342
pressure sensors 402
principles of motion at microscale 256
printable magnetoresistive devices 115
pseudocapacitance 234
pseudocapacitors, nanomembranes for
234

- p-toluenesulfonate (PEDOT-Tos) 76
Purcell's scallop theorem 131
pyridine-linked glutamide derivative
gelator (PULG) 175
- q**
Q factor 359
- r**
reconfigurable microbot 133
reconfigurable micromachines 130
reconfigurable rolled-up electronics 347
redox-based resistive switching memory
(ReRAM) 35
reprogrammable shape morphing
nanomembot 265, 267
Reynolds number 125, 257, 258
RF capacitors, rolled-up 333
RF inductors, rolled-up 328
R6G molecules degradation 370
rGO/poly(2-acrylamide-2-
methylpropanesulfonic
acid-co-acrylamide)
nanocomposites 407
rGO@S composite film, morphology and
performance of 232
right-handed circularly polarized light
(RCP) 19
rigid folding 289, 292
robotics 16–17
rolled-up architectures 317, 318–324
rolled-up C/Si/C multilayer microtubes
227
rolled-up microtubes arrays 203
rolled-up nanotechnology 197, 253, 317
rolled-up origami
for electronics 318–324
modeling 324–328
rolled-up radio frequency electronics
antennas 336–341
RF capacitors 333–336
RF inductors 328–333
rolled-up scaffold 197
rolled-up tubes, mechanical self-assembly
of 169–172
rolled-up tubular optical microcavities
368
2D materials 370
oxide materials 371–375
semiconductor materials 369–370
rolled-up whispering gallery mode optical
microcavities
lasing applications 380–382
light propagation in tubular
microcavity 359–368
sensing applications 375–380
theoretical analysis 354
ray optics 357–359
wave equation 354–357
RPE1 cells 203
rubber polymers 70
Ruderman-Kittel-Kasuya-Yosida (RKKY)
114
- S**
scaling laws 255
scallop theorem 258
S composite nanomembrane 231
second harmonic generation (SHG)
427
self-assembly 131
self-destruction mechanisms
nanomembrane
electrically triggered devices 46–48
optically triggered devices 46
passive dissolving without triggering
40–41
thermal triggered devices 41–45
self-diffusiophoresis 260
self-electrophoresis-powered
nanomembot 269
self-electrophoretic nanomembot 264
self-propelled catalytic nanomotor 261
self-propelled microbots swimming 131
self-rolled-up electronic devices 349
semiconductor materials 11
semiconductor materials, for rolled-up
tubular optical microcavities 369,
370
semiconductor materials 31

- sensing systems 90
 - shape anisotropy 109
 - shape memory polymers (SMPs) 13
 - shape morphing nanomembots 268
 - silicon nanomembrane (SiNM) 15, 27, 31–32
 - silicon-on-insulator (SOI) 36
 - Si₃N₄ 34
 - single crystalline silicon 31, 33
 - single-layer 2D materials 393
 - single-layer graphene (SLG) 209
 - single mode WGM emission, in mesostructured diamond microcavity 368
 - SiN_x channels 208
 - SiN_x rolled-up membrane (S-RuM) nanotechnology 329
 - SiO/SiO₂ bilayer nanomembranes 371
 - SiO/SiO₂ microtubes 198, 201
 - SiO_x/SiN_x rolled-up microcavities, for solvent sensing 376
 - Si/SiO₂ bilayer nanomembranes 372
 - smart nanomembrane origami devices 288
 - 4D construction 293
 - 3D fabrication and design 290–292
 - 3D origami micro- and nanostructures 288, 289
 - 4D origami micro- and nanostructures 290
 - smooth muscle cells (SMCs) 214
 - soft hydrogel micromotor, with coated catalytic hemisphere 261
 - solution-based process 35
 - solution-responsive origami 302
 - spatial mapping method 349
 - spin-coated encapsulation method 59
 - spin coating 58
 - spindle assembly checkpoint (SAC) 203
 - S-RuM helical antenna structural design 339
 - S-RuM interdigital RF capacitors 333
 - S-RuM power inductors 341
 - S-RuM power passive electronics microsupercapacitors 343–346
 - S-RuM power inductors 341–343
 - S-RuM RF/power inductors 330, 341–343
 - stable states 177
 - state-of-the-art strategies 88
 - Stimuli-responsive microbots 128
 - strain
 - in 2D materials 422–423
 - 2D materials nanomembrane 401
 - effect on 2D TMD 425–428
 - types 424–425
 - strain field measurements 181
 - strain tuning techniques, of 2D TMDs 435
 - applications 435–438
 - atomic force microscopy 428–429
 - DACs 431–432
 - piezoelectric actuators 432–435
 - substrate deformation 429–431
 - substrate patterning 431
 - stress-induced anisotropy 111
 - subtractive process 291
 - superabsorbent polymer hydrogel (SPH) 74
 - supercapacitor, nanomembranes for 233
 - supported lipid bilayer (SLB) 195
 - swelling/shrinking actuated passive origami 293
 - swimming strategies, at low Reynolds number 259
- t**
- temperature-responsive materials actuated active origami 295
 - tensile strain, 2D TMDs 424–427
 - tetramethylammonium hydroxide (TMAH) 36
 - the electron beam (E-beam) 3
 - thermally triggered transience 45
 - thermally triggered transient devices 41
 - thermal/temperature-responsive origami 293
 - swelling/shrinking actuated passive origami 293–295

- thermal/temperature-responsive origami (*contd.*)
 - temperature-responsive materials
 - actuated active origami 295–296
- thermoelectric energy 18
- thermo-sensitive materials 41
- three-dimensional (3D) carbon nanomembranes (CNMs) 240
- three-dimensional photodetection system 92
- 3D interdigital RF capacitors 333
- 3D mesostructures 15, 158
 - applications of 19
 - 2D materials 13
 - metallic conductors 11
 - phase-change materials 13–14
 - piezoelectric materials 12–13
 - semiconductor materials 11–12
 - transfer print 14
- 3D micro/nano-structures 1
 - biomedical devices 17–18
 - electronics 14–16
 - energy harvesters 18
 - optical devices 18–19
 - robotics 16–17
 - sensors 17
- 3D piezoelectric sensors 17
- 3D pyramid-shaped hygroelectric generator 18
- 3D silicon electronic systems 15
- Ti₃C₂T_x/rGO/CNT/PANI asymmetric device 237, 238
- Ti-45Nb (TNO) membranes 199
- TiO_x/Si/TiO_x trilayer nanomembranes microtubes 226
- tissue mimicking therapy 212
- tissue non-specific alkaline phosphatase (TNAP) 205
- transfer printing method 14, 36, 37
- transient electronics 27, 97
 - conducting materials 29–31
 - dielectrics materials 33–35
 - material selection for 29–31
 - semiconductor materials 31–33
- transient nanomembrane 40
- transient quasi-static FEM modeling
 - method, for rolling process 325
- transient quasi-static FEM modeling, of rolling process 327
- transient thin-film transistor 33
- transverse-magnetic (TM)-polarized WGM 355
- trimesoyl chloride (TMC) 72
- tristability of bilayer composite 175
 - partially bonded strip 176–177
- tubular microbots 128–131
- tubular nanomembots
 - control of catalytic 265
 - fluid flow resistance 262
 - laminar fluid pumping 262
 - magnetized catalytic reaction powered 264
 - polymeric 270
 - powered by bubbles 269
 - self-propelled motion of 263
 - strain-engineered 253
- tubular polyaniline/Pt nanomembots 261
- tunable helical ribbons 163
- tunneling magnetoresistance (TMR) 116
- tunneling magneto-resistance (TMR) 106
- twist-nematic-elastomers 166
- two-dimensional biocompatible nanomembranes 194
- two-dimensional material
 - nanomembrane actuators and robots
 - fabrication 403–404
 - motion and deformation 404–407
- 2D Kirchhoff equation 146
- 2D materials 13
 - characteristics 392–394
 - development history of 391
 - gas sensors 398–400
 - Kirigami method 396
 - mechanical sensors 400–402

- origami of 396–398
 - for rolled-up tubular optical microcavities 370
 - sensors 398–400
 - suspended structure 394–395
 - 2D MoSe₂/WSe₂ heterojunction vertical device 437
 - 2D precursors 3, 5, 8
 - 2D-to-3D assembly methods 1
 - 2D transition metal dichalcogenides (TMDs)
 - applications 391–392
 - band structure 417–419
 - Brillouin zones 418
 - composition and chemical bonds 414–415
 - excitonic effects 420–421
 - optical selection rules 419–420
 - properties 391
 - strain effect 425–428
 - strain engineering 422–423
 - structural symmetry 416–417
 - valley contrasting physics 419–420
 - vibrational properties 421–422
- U**
- ultrasonic actuated rolling 299
 - ultrasonic-assisted origami 298
 - ultrasonic-heat conversion actuated origami 299
 - ultrasonic-responsive origami 297
 - ultrasound-powered nanomembots 272
 - ultrathin VO₂ nanomembrane
 - fabrication and characteristics 346
 - U-turn technique 264
- V**
- valley fold (origami) 289
 - valley Hall effect 419
 - vapor–liquid–solid method 89
 - vibrational properties, of 2D TMD 421–422
 - V₂O₅-coated carbon powders 236
 - Voigt notation 147
- W**
- waste water treatment 72
 - water desalination 72
 - water-soluble electronic devices 27
 - water-soluble supporting layer method 63
 - wax sulfonic acid 43
 - Wheatstone bridge 122
 - whispering gallery modes (WGMs) 211
- X**
- XeF₂ etching 39
 - XeF₂ vapor-based release method 342
 - Xenon difluoride (XeF₂) 37
- Y**
- Young's modulus 58, 149, 159
 - Y₂O₃/ZrO₂ bi-layer high-index-contrast nanomembranes 372, 374
 - Y₂O₃/ZrO₂ rolled-up tubular microcavities, Q factor of 360
- Z**
- Zeeman energy 112
 - ZIF-8-film-coated carbon foam 239
 - zinc oxide (ZnO) 33
 - Zn-ion batteries 229
 - ZnO/EG composite and battery assembly 224

