

## Index

### **a**

absolute temperature (T) 11, 34  
 ac 4, 5, 9, 10, 63–67, 71, 72, 74–76, 90  
 additional positive feedback (APF) 5, 61, 85, 129  
 air medium 196  
 amplitude and phase-to-frequency transfer characteristics 64, 210  
 angular velocity 10  
 applied flux 17, 18, 23, 51, 53, 55, 74, 92, 149, 150, 164, 165, 171, 174, 175, 186

### **b**

bandwidth 71–73, 79, 148–153, 208, 210, 211, 213  
 bias current feedback (BCF) 5, 87, 129  
 biomagnetism 7, 136, 153, 155, 157, 158  
 bipolar transistor 7, 143, 182, 184–186, 189, 217  
 Boltzmann's constant ( $k_B$ ) 11  
 bulk SQUID 180, 195

### **c**

capacitive coupling 178, 184, 192  
 capacitive displacement current 10  
 capacitively shunted junction (CSJ) 3, 9, 10, 12  
 capacitor tap 181–184, 188–190, 196  
 cardiogenic QRS wave 153  
 chain rule 5, 39–43, 98, 101, 117  
 charge of an electron,  $e$  9  
 choke  $L_D$  188  
 clamp potential 94, 95

coaxial cable 181–185, 188, 190, 194, 197, 209, 216  
 communication signal 47  
 complex transfer characteristics 78, 79  
 coplanar resonator 192–196, 198, 199, 204–207  
 coupling factor  $k$  173, 199  
 critical condition 5, 91–93, 97, 99, 101–104, 114, 117, 122, 125, 126  
 critical current  $I_c$  3, 9, 17, 49, 52, 54, 140, 200, 214  
 cryogenic temperature (CT) 5, 20, 25, 33, 61, 64, 85, 177  
 current bias mode 3, 18, 24, 26, 30, 33, 34, 40, 55, 62, 73, 74, 78, 85, 89–94, 98, 103, 125, 127, 129, 140, 142, 157, 172  
 current density 9  
 current noise source  $I_n$  38, 72  
 current-to-voltage ( $I$ - $V$ ) characteristics 1–3, 10–12, 15, 23, 24, 29, 49–51, 53, 74, 77, 90–92, 97, 103, 122, 125, 132, 141, 143, 144, 148, 173, 174, 187, 209

### **d**

demodulated (restored) SQUID signal 64  
 demodulator 64, 178, 185, 203  
 detector (D) 94, 177, 178, 185, 201, 215, 216  
 direct current (dc) 1, 2, 9, 12, 15, 23, 29, 45, 49, 92, 147, 172, 174, 176, 178, 180, 186, 200, 205, 214

- directional coupler (DC) 184, 185, 208, 216
- distributed point D 174
- distribution function of  $\sigma$  175
- D–L requirements 200, 201, 204, 207, 214, 217, 218
- double-pole double-throw (DPDT) switch 40
- double relaxation oscillation SQUID (D-ROS) 61
- down mixing effect 53
- dynamic inductance 100
- dynamic range 147, 150–153, 208, 210
- dynamic resistance  $R_d$  1–3, 12, 15, 18, 19, 23, 29, 37, 78, 87, 88, 94, 105, 109, 117, 121, 122, 124, 125, 127, 134, 140, 141, 143, 144, 148, 174
- e**
- effective operating temperature  $T_{e,T}$  178, 179, 183, 193, 199
- effective pickup area 181
- electromagnetic (EM) field 190, 194, 195
- electronic gradiometer 153, 212
- equivalent circuit 6, 18, 41, 89, 94, 96, 99–102, 114, 115, 125, 129, 141, 146, 147, 149, 150, 152, 174
- f**
- fetal magnetocardiogram (fMCG) 211
- field-effect transistor (FET) 114, 139, 177
- field-to-flux transfer coefficient ( $\partial B/\partial \Phi$ ) 45, 48, 132, 141, 189, 201
- field-to-flux transformer circuit (converter) 1, 4, 45–48
- first-order gradiometer 46, 162, 211
- flux amplifier 6, 158, 159, 161, 164
- flux concentrator 184, 192, 193, 197, 211
- flux noise of the readout electronics,  $\delta\Phi_e$  37
- flux quantization 1, 15, 18, 49, 171
- flux-sensitive inductor 174, 175
- focused gas field ion source 13
- Fourier-component 73, 79
- frequency response analyzer 79
- g**
- GaAs FET 179, 180, 191
- gain bandwidth 151
- gain factor 35, 147, 150
- geomagnetic exploration 153
- grain-boundary 181
- h**
- half wavelength ( $\lambda/2$ ) 48, 190, 191
- half-wavelength resonator 108
- head stage 5, 25, 26, 29, 46, 61, 62, 64, 66, 74, 85–88, 148, 150, 177, 180, 184
- helium ion microscope 13
- higher harmonic components 80, 81, 200–202, 204, 214, 217
- high-frequency disturbance 47
- high-frequency energy 56
- high-frequency protection 48
- high-impedance op-amp 62
- hysteresis 3, 4, 10, 12, 15, 49–53, 55, 93, 126, 135, 144
- hysteretic (dissipative) mode 171
- i**
- impedance matching 81, 182–184, 186, 189, 192, 193, 197, 199, 214, 218
- inductance matching 46, 48
- inductor-tap 7
- insulating layer 9
- intermediately damped 127, 154, 155
- j**
- Josephson coupling energy 11
- Josephson effect
  - ac Josephson equation 9
  - dc Josephson equation 9
- Josephson element 9, 10
- Josephson equations 9, 12
- Josephson frequency 48, 108
- Josephson junctions 1, 3, 9, 116, 157, 164, 171, 190

- Josephson radiation 214  
 Josephson tunneling 15, 18  
 junction capacitance 9, 49, 56, 140, 141  
 junction field effect transistor 37
- k**  
 kinetic energy 10  
 Kirchhoff's law 62, 129  
 Kurkijärvi's noise theory 180
- l**  
 LaAlO<sub>3</sub> substrate 189, 193, 196, 206  
 labyrinth resonator 203–208  
 λ-ring resonator 191  
 LC resonant circuit 188  
 liquid helium-cooled SQUID 46  
 lumped elements 171, 173, 181, 182, 191, 194, 196, 205, 217
- m**  
 magnetically shielded room (MSR) 17, 133, 153, 184  
 magnetic field noise  $\delta B_{\text{sys}}$  45, 148, 155  
 magnetic flux quantum  $\Phi_0$  9  
 magnetocardiography (MCG) 6, 147, 158, 180  
 magnetoencephalography (MEG) 7, 114, 139, 158, 184  
 magnetometer 1, 7, 45–48, 56, 115, 123, 124, 132, 133, 135, 141, 143, 146–148, 153, 181, 186, 188, 191, 194, 197–199, 201, 206, 207, 212, 214  
 magnitude-frequency characteristic 72, 78, 79  
 MCG-mapping 212  
 30 MHz version 176, 177, 179, 182–185, 190, 195, 200, 215, 217  
 150 MHz version 184, 186  
 microbridge 12, 181  
 microstrip version 190–192, 194  
 minimal observable noise  $(\delta\Phi_s)_{\text{min}}$  53  
 mixed bias mode 5, 61–63, 74, 75, 78, 81, 87, 129  
 mixture version 186  
 modern rf SQUID 176, 180–200, 208–211, 217, 218  
 modulation depth 4, 54, 55, 210  
 modulation flux  $\Phi_{\text{MO}}$  64, 69, 70  
 modulation frequency  $f_M$  66, 71, 73  
 modulation point 67–69, 71  
 modulation readout scheme (FMS) 56  
 multichannel first-order gradiometer 211  
 multiplier 64, 68, 69, 71, 72, 178, 184, 185, 216  
 multiturn spiral input coil  $L_{\text{in}}$  46  
 μ-metal shielding 207  
 mutual inductance  $M_{\text{rf}}$  171, 174, 177, 182, 188, 193, 199, 205
- n**  
 network analyzer 149, 215, 216  
 niobium (low  $T_c$ ) SQUID 42  
 noise cancellation (NC) 5, 87, 94, 97, 139  
 noise spectrum 36, 37, 111, 133, 198  
 noise temperature  $T_N$  178, 179, 186  
 nominal  $\beta_c$  49–51, 53, 55, 56, 143  
 nominal  $\Gamma$  52  
 nominal  $\Gamma^*$  53  
 nonhysteretic (dispersive) mode 171
- o**  
 Ohm's law 39, 76, 90  
 output voltage of the readout electronics  $V_{\text{out}}(\Phi)$  3
- p**  
 parallel feedback circuit (PFC) 5, 40, 61, 85, 89–99, 139, 157  
 pendulum 10  
 phase difference  $\delta$  9  
 phase-frequency characteristics 71, 78, 79  
 phase shifter  $\Delta\phi$  64, 71  
 pickup antennas  $L_{\text{pickup}}$  45  
 pickup area 47, 48, 181, 197, 205, 211  
 planar resonators 7, 217, 218  
 planar thin-film techniques 48  
 Planck's constant 9  
 primary field 153  
 pumping frequency 172, 175, 176, 179, 181, 188–190, 200, 203, 216, 217

**q**

QRS peak 211, 213  
 quality factor  $Q$  7, 171, 173, 174, 177,  
 178, 186, 189, 192, 216  
 quantum transition 172, 175, 180, 200  
 quasi-sinusoidal 42, 50, 80, 201

**r**

radio-frequency (rf) SQUID 171–218  
 random switching noise 52, 53  
 readout electronics 2, 6, 7, 13, 15, 18,  
 23, 33, 45, 49, 54, 63, 66, 68, 71,  
 72, 74, 75, 81, 85, 88, 92–94, 99,  
 103, 106, 108, 111, 114, 116, 118,  
 125, 139, 142, 145, 147, 152, 172,  
 176–179, 182, 184–186,  
 188–191, 194, 197, 200, 201, 207,  
 208, 215, 217, 218  
 receiving antenna 48, 194  
 reference magnetometer 212  
 reflected rf power 216  
 reflection system 216  
 relaxation oscillation SQUID (ROS)  
 12, 61  
 resistively and capacitively shunted  
 junction (RCSJ) 3, 9, 10  
 resistively shunted junction (RSJ)  
 10–12  
 resistive microstrip 48  
 resonance frequency 7, 171, 174, 177,  
 179, 181, 182, 184, 189, 193, 194,  
 196, 205, 206, 216, 217  
 rf bias current  $I_{\text{rf,bias}}$  177  
 rf radiation 48, 185, 194, 215  
 rf resonance 48, 159, 171  
 room temperature (RT) 7, 20, 33, 64,  
 88, 94, 148, 157, 177  
 rounding effect 11, 12, 52, 53, 173, 187

**s**

secondary field 153  
 second-order gradiometer 46, 162,  
 164, 168  
 sensing SQUID 6, 63, 153, 157–164,  
 167, 212  
 series feedback coil (circuit) (SFC) 85,  
 121–137

shunt resistance (resistor) 9, 10, 49, 56,  
 76, 198  
 single chip readout electronics (SCRE)  
 6, 147–154, 161  
 square wave voltage generator 64, 65  
 SQUID bootstrap circuit (SBC) 87,  
 129  
 steady-state error 152  
 step-edge junction 181, 189, 198, 204,  
 207  
 step-up transformer 4, 5, 61, 63, 66,  
 69, 71, 74, 78–80, 85  
 primary winding (PW) 74, 76, 78,  
 80, 81  
 secondary winding (SW) 66  
 Stewart–McCumber parameter  $\beta_c$  3,  
 10, 18, 49  
 strongly damped junction 43  
 substrate resonators 7, 196, 198, 201,  
 205, 207, 209, 211, 212  
 superconducting electrodes 9  
 superconducting quantum interference  
 device (SQUID) 9  
 current sensitivity 101  
 impedance  $Z_s$  5, 61, 74  
 magnetometer system 1, 4, 13, 23,  
 25, 29, 33, 45, 47, 48, 67, 85, 117,  
 123, 145, 147, 181, 183, 192, 195,  
 196  
 signal swing 54, 174, 176, 187  
 system noise power  $\delta\Phi^2_{\text{sys}}$  45  
 voltage swing  $V_{\text{swing}}$  50, 77  
 superconducting shield 47, 48  
 superconducting transmission line 48  
 superconductor-insulator-super-  
 conductor (SIS) tunnel contact  
 9  
 supercurrent 9, 10  
 symmetric SQUID 53, 186

**t**

tank circuit 2, 7, 171–186, 188–196,  
 198–200, 202, 205, 206, 208,  
 214–217  
 tank circuit noise  $\delta\Phi_T$  179, 191, 200,  
 217  
 tap voltage ratio  $\kappa$  183, 191, 193, 199

thermal energy 11  
 thermal noise limit 7, 181, 200, 204, 217  
 thermal noise parameter  $\Gamma$  11, 18, 52, 55  
 thin-film SQUID 180–182, 186, 198, 205, 206  
 three-layer construction 10  
 three-layer structure 7, 206  
 tilting parameter  $\alpha$  175  
 toroidal rf SQUID 204  
 torque 10  
 total harmonic distortion (THD) 152  
 total reflection 216  
 transfer characteristics 5, 61, 64, 78, 210, 215, 216  
 transient electromagnetic (TEM) 6, 147  
 two-stage scheme 6, 61, 63, 111–113, 117, 158–164, 168–169

## u

ultralow field magnetic resonance imaging 47, 155  
 unshielded/lightly shielded environment 47  
 un-shunted tunnel contact 10

## v

varying thickness bridge (V.T.B.) 13  
 virtual preamplifier 111  
 voltage bias mode 2, 18–21, 30, 33, 34, 40–42, 55, 61, 62, 76, 87, 94, 98, 99  
 voltage-controlled attenuator (VCA) 184  
 voltage-controlled oscillator (VCO) 184, 208  
 voltage noise source  $V_n$  85, 140  
 $V_{rf,input}$  at the tap position 182  
 $V_{rf,swing}$  ( $V_{rf,swing}$ ) 172

## w

weakly damped SQUID 6, 29, 56, 61, 63, 123–125, 139  
 white noise 35, 36, 39, 47, 52, 109, 111, 112, 137, 141, 145, 154, 194, 199, 207  
 wire-wound axial pickup antennas 45

## y

yttrium barium copper oxide (YBCO) 11, 13, 46, 176, 181, 189, 193, 196, 198, 199, 205–207, 211, 214, 218

