

Index

a

absolute temperature (T) 11, 34
 ac 4, 5, 9, 10, 63–67, 71, 72, 74–76, 90
 additional positive feedback (APF) 5, 61, 85, 129
 air medium 196
 amplitude and phase-to-frequency transfer characteristics 64, 210
 angular velocity 10
 applied flux 17, 18, 23, 51, 53, 55, 74, 92, 149, 150, 164, 165, 171, 174, 175, 186

b

bandwidth 71–73, 79, 148–153, 208, 210, 211, 213
 bias current feedback (BCF) 5, 87, 129
 biomagnetism 7, 136, 153, 155, 157, 158
 bipolar transistor 7, 143, 182, 184–186, 189, 217
 Boltzmann's constant (k_B) 11
 bulk SQUID 180, 195

c

capacitive coupling 178, 184, 192
 capacitive displacement current 10
 capacitively shunted junction (CSJ) 3, 9, 10, 12
 capacitor tap 181–184, 188–190, 196
 cardiogenic QRS wave 153
 chain rule 5, 39–43, 98, 101, 117
 charge of an electron, e 9
 choke L_D 188
 clamp potential 94, 95

coaxial cable 181–185, 188, 190, 194, 197, 209, 216
 communication signal 47
 complex transfer characteristics 78, 79
 coplanar resonator 192–196, 198, 199, 204–207
 coupling factor k 173, 199
 critical condition 5, 91–93, 97, 99, 101–104, 114, 117, 122, 125, 126
 critical current I_c 3, 9, 17, 49, 52, 54, 140, 200, 214
 cryogenic temperature (CT) 5, 20, 25, 33, 61, 64, 85, 177
 current bias mode 3, 18, 24, 26, 30, 33, 34, 40, 55, 62, 73, 74, 78, 85, 89–94, 98, 103, 125, 127, 129, 140, 142, 157, 172
 current density 9
 current noise source I_n 38, 72
 current-to-voltage (I - V) characteristics 1–3, 10–12, 15, 23, 24, 29, 49–51, 53, 74, 77, 90–92, 97, 103, 122, 125, 132, 141, 143, 144, 148, 173, 174, 187, 209

d

demodulated (restored) SQUID signal 64
 demodulator 64, 178, 185, 203
 detector (D) 94, 177, 178, 185, 201, 215, 216
 direct current (dc) 1, 2, 9, 12, 15, 23, 29, 45, 49, 92, 147, 172, 174, 176, 178, 180, 186, 200, 205, 214

- directional coupler (DC) 184, 185, 208, 216
- distributed point D 174
- distribution function of σ 175
- D–L requirements 200, 201, 204, 207, 214, 217, 218
- double-pole double-throw (DPDT) switch 40
- double relaxation oscillation SQUID (D-ROS) 61
- down mixing effect 53
- dynamic inductance 100
- dynamic range 147, 150–153, 208, 210
- dynamic resistance R_d 1–3, 12, 15, 18, 19, 23, 29, 37, 78, 87, 88, 94, 105, 109, 117, 121, 122, 124, 125, 127, 134, 140, 141, 143, 144, 148, 174
- e**
- effective operating temperature $T_{e,T}$ 178, 179, 183, 193, 199
- effective pickup area 181
- electromagnetic (EM) field 190, 194, 195
- electronic gradiometer 153, 212
- equivalent circuit 6, 18, 41, 89, 94, 96, 99–102, 114, 115, 125, 129, 141, 146, 147, 149, 150, 152, 174
- f**
- fetal magnetocardiogram (fMCG) 211
- field-effect transistor (FET) 114, 139, 177
- field-to-flux transfer coefficient ($\partial B/\partial \Phi$) 45, 48, 132, 141, 189, 201
- field-to-flux transformer circuit (converter) 1, 4, 45–48
- first-order gradiometer 46, 162, 211
- flux amplifier 6, 158, 159, 161, 164
- flux concentrator 184, 192, 193, 197, 211
- flux noise of the readout electronics, $\delta\Phi_e$ 37
- flux quantization 1, 15, 18, 49, 171
- flux-sensitive inductor 174, 175
- focused gas field ion source 13
- Fourier-component 73, 79
- frequency response analyzer 79
- g**
- GaAs FET 179, 180, 191
- gain bandwidth 151
- gain factor 35, 147, 150
- geomagnetic exploration 153
- grain-boundary 181
- h**
- half wavelength ($\lambda/2$) 48, 190, 191
- half-wavelength resonator 108
- head stage 5, 25, 26, 29, 46, 61, 62, 64, 66, 74, 85–88, 148, 150, 177, 180, 184
- helium ion microscope 13
- higher harmonic components 80, 81, 200–202, 204, 214, 217
- high-frequency disturbance 47
- high-frequency energy 56
- high-frequency protection 48
- high-impedance op-amp 62
- hysteresis 3, 4, 10, 12, 15, 49–53, 55, 93, 126, 135, 144
- hysteretic (dissipative) mode 171
- i**
- impedance matching 81, 182–184, 186, 189, 192, 193, 197, 199, 214, 218
- inductance matching 46, 48
- inductor-tap 7
- insulating layer 9
- intermediately damped 127, 154, 155
- j**
- Josephson coupling energy 11
- Josephson effect
 - ac Josephson equation 9
 - dc Josephson equation 9
- Josephson element 9, 10
- Josephson equations 9, 12
- Josephson frequency 48, 108
- Josephson junctions 1, 3, 9, 116, 157, 164, 171, 190

- Josephson radiation 214
 Josephson tunneling 15, 18
 junction capacitance 9, 49, 56, 140, 141
 junction field effect transistor 37
- k**
 kinetic energy 10
 Kirchhoff's law 62, 129
 Kurkijärvi's noise theory 180
- l**
 LaAlO₃ substrate 189, 193, 196, 206
 labyrinth resonator 203–208
 λ-ring resonator 191
 LC resonant circuit 188
 liquid helium-cooled SQUID 46
 lumped elements 171, 173, 181, 182, 191, 194, 196, 205, 217
- m**
 magnetically shielded room (MSR) 17, 133, 153, 184
 magnetic field noise δB_{sys} 45, 148, 155
 magnetic flux quantum Φ_0 9
 magnetocardiography (MCG) 6, 147, 158, 180
 magnetoencephalography (MEG) 7, 114, 139, 158, 184
 magnetometer 1, 7, 45–48, 56, 115, 123, 124, 132, 133, 135, 141, 143, 146–148, 153, 181, 186, 188, 191, 194, 197–199, 201, 206, 207, 212, 214
 magnitude-frequency characteristic 72, 78, 79
 MCG-mapping 212
 30 MHz version 176, 177, 179, 182–185, 190, 195, 200, 215, 217
 150 MHz version 184, 186
 microbridge 12, 181
 microstrip version 190–192, 194
 minimal observable noise $(\delta\Phi_s)_{\text{min}}$ 53
 mixed bias mode 5, 61–63, 74, 75, 78, 81, 87, 129
 mixture version 186
 modern rf SQUID 176, 180–200, 208–211, 217, 218
 modulation depth 4, 54, 55, 210
 modulation flux Φ_{MO} 64, 69, 70
 modulation frequency f_M 66, 71, 73
 modulation point 67–69, 71
 modulation readout scheme (FMS) 56
 multichannel first-order gradiometer 211
 multiplier 64, 68, 69, 71, 72, 178, 184, 185, 216
 multiturn spiral input coil L_{in} 46
 μ-metal shielding 207
 mutual inductance M_{rf} 171, 174, 177, 182, 188, 193, 199, 205
- n**
 network analyzer 149, 215, 216
 niobium (low T_c) SQUID 42
 noise cancellation (NC) 5, 87, 94, 97, 139
 noise spectrum 36, 37, 111, 133, 198
 noise temperature T_N 178, 179, 186
 nominal β_c 49–51, 53, 55, 56, 143
 nominal Γ 52
 nominal Γ^* 53
 nonhysteretic (dispersive) mode 171
- o**
 Ohm's law 39, 76, 90
 output voltage of the readout electronics $V_{\text{out}}(\Phi)$ 3
- p**
 parallel feedback circuit (PFC) 5, 40, 61, 85, 89–99, 139, 157
 pendulum 10
 phase difference δ 9
 phase-frequency characteristics 71, 78, 79
 phase shifter $\Delta\phi$ 64, 71
 pickup antennas L_{pickup} 45
 pickup area 47, 48, 181, 197, 205, 211
 planar resonators 7, 217, 218
 planar thin-film techniques 48
 Planck's constant 9
 primary field 153
 pumping frequency 172, 175, 176, 179, 181, 188–190, 200, 203, 216, 217

q

QRS peak 211, 213
 quality factor Q 7, 171, 173, 174, 177,
 178, 186, 189, 192, 216
 quantum transition 172, 175, 180, 200
 quasi-sinusoidal 42, 50, 80, 201

r

radio-frequency (rf) SQUID 171–218
 random switching noise 52, 53
 readout electronics 2, 6, 7, 13, 15, 18,
 23, 33, 45, 49, 54, 63, 66, 68, 71,
 72, 74, 75, 81, 85, 88, 92–94, 99,
 103, 106, 108, 111, 114, 116, 118,
 125, 139, 142, 145, 147, 152, 172,
 176–179, 182, 184–186,
 188–191, 194, 197, 200, 201, 207,
 208, 215, 217, 218
 receiving antenna 48, 194
 reference magnetometer 212
 reflected rf power 216
 reflection system 216
 relaxation oscillation SQUID (ROS)
 12, 61
 resistively and capacitively shunted
 junction (RCSJ) 3, 9, 10
 resistively shunted junction (RSJ)
 10–12
 resistive microstrip 48
 resonance frequency 7, 171, 174, 177,
 179, 181, 182, 184, 189, 193, 194,
 196, 205, 206, 216, 217
 rf bias current $I_{rf,bias}$ 177
 rf radiation 48, 185, 194, 215
 rf resonance 48, 159, 171
 room temperature (RT) 7, 20, 33, 64,
 88, 94, 148, 157, 177
 rounding effect 11, 12, 52, 53, 173, 187

s

secondary field 153
 second-order gradiometer 46, 162,
 164, 168
 sensing SQUID 6, 63, 153, 157–164,
 167, 212
 series feedback coil (circuit) (SFC) 85,
 121–137

shunt resistance (resistor) 9, 10, 49, 56,
 76, 198
 single chip readout electronics (SCRE)
 6, 147–154, 161
 square wave voltage generator 64, 65
 SQUID bootstrap circuit (SBC) 87,
 129
 steady-state error 152
 step-edge junction 181, 189, 198, 204,
 207
 step-up transformer 4, 5, 61, 63, 66,
 69, 71, 74, 78–80, 85
 primary winding (PW) 74, 76, 78,
 80, 81
 secondary winding (SW) 66
 Stewart–McCumber parameter β_c 3,
 10, 18, 49
 strongly damped junction 43
 substrate resonators 7, 196, 198, 201,
 205, 207, 209, 211, 212
 superconducting electrodes 9
 superconducting quantum interference
 device (SQUID) 9
 current sensitivity 101
 impedance Z_s 5, 61, 74
 magnetometer system 1, 4, 13, 23,
 25, 29, 33, 45, 47, 48, 67, 85, 117,
 123, 145, 147, 181, 183, 192, 195,
 196
 signal swing 54, 174, 176, 187
 system noise power $\delta\Phi^2_{sys}$ 45
 voltage swing V_{swing} 50, 77
 superconducting shield 47, 48
 superconducting transmission line 48
 superconductor-insulator-super-
 conductor (SIS) tunnel contact
 9
 supercurrent 9, 10
 symmetric SQUID 53, 186

t

tank circuit 2, 7, 171–186, 188–196,
 198–200, 202, 205, 206, 208,
 214–217
 tank circuit noise $\delta\Phi_T$ 179, 191, 200,
 217
 tap voltage ratio κ 183, 191, 193, 199

thermal energy 11
 thermal noise limit 7, 181, 200, 204, 217
 thermal noise parameter Γ 11, 18, 52, 55
 thin-film SQUID 180–182, 186, 198, 205, 206
 three-layer construction 10
 three-layer structure 7, 206
 tilting parameter α 175
 toroidal rf SQUID 204
 torque 10
 total harmonic distortion (THD) 152
 total reflection 216
 transfer characteristics 5, 61, 64, 78, 210, 215, 216
 transient electromagnetic (TEM) 6, 147
 two-stage scheme 6, 61, 63, 111–113, 117, 158–164, 168–169

u

ultralow field magnetic resonance imaging 47, 155
 unshielded/lightly shielded environment 47
 un-shunted tunnel contact 10

v

varying thickness bridge (V.T.B.) 13
 virtual preamplifier 111
 voltage bias mode 2, 18–21, 30, 33, 34, 40–42, 55, 61, 62, 76, 87, 94, 98, 99
 voltage-controlled attenuator (VCA) 184
 voltage-controlled oscillator (VCO) 184, 208
 voltage noise source V_n 85, 140
 $V_{rf,input}$ at the tap position 182
 V_{rf} swing ($V_{rf,swing}$) 172

w

weakly damped SQUID 6, 29, 56, 61, 63, 123–125, 139
 white noise 35, 36, 39, 47, 52, 109, 111, 112, 137, 141, 145, 154, 194, 199, 207
 wire-wound axial pickup antennas 45

y

yttrium barium copper oxide (YBCO) 11, 13, 46, 176, 181, 189, 193, 196, 198, 199, 205–207, 211, 214, 218

