

Index

a

acid gas removal 15, 23, 26, 28, 37–38, 313
 across-pinch rule 131, 132, 134–137, 145, 148
 autothermal reforming (ATR) 4

b

backup heat exchanger 169, 175–176, 194, 196
 Barnett shale play 2, 17, 35
 benzene 7, 163, 165
 biomass 103, 105, 107, 301–316
 biorefinery concept 302
 Biovia Materials Studio 8.0 73
 bottom-integrated configuration 126–128

c

chemical production 151
 closed-circuit configuration (CCRO) 44
 closed-loop configuration 46, 55, 56, 58–63
 coefficient of performance (COP) 143
 combined heat and mass exchange networks (CHAMENs)
 absorption and regeneration temperature optimisation 247–252
 economic objective function 236–239
 environmental objective function 238–239
 HENS model equations

driving forces, calculation of 232
 logical constraint 231–232
 overall stream heat balance 230–231
 solar panel and heat storage vessel design equation 232–233
 stage heat balance 231
 superstructure inlet temperature assignment 231
 temperature feasibility 231
 initializations and convergence 239–240
 MEN and REN model equations
 binary variable 235
 driving forces of mass exchange 235–236
 logical constraint 235
 mass balance for rich and lean streams 234
 overall mass balance for rich and lean streams 233–234
 rich and lean stream concentrations 235
 target and supply concentrations 234–235
 MOO implementation 252–254
 multi-objective function 239
 pinch technology approach 224
 regeneration 222
 sequential approach 224
 synthesis approach 227–229
 combined multi-parameter optimization diagram (CMOD) 162
 composite curves (CC) 152–155, 207, 210

- computational fluid dynamics
 - simulations 167
 - concentration polarization 45, 49
 - concentric distillation column 118
 - confinement effect 69, 71, 75
 - connection pattern 205, 209–212, 215, 217
 - continuouswell-mixed-reactor (CSTR) 157
 - conventional column 117–121, 123, 126–128
 - conventional steam stripping method 241
 - cyclohexene process
 - CMOD for benzene 165
 - flowsheet of benzene 164
- d**
- dehydration process
 - acid gas removal 26, 28
 - fractionation train 26
 - NGL recovery process 23–25
 - demethanizer 6, 31, 36
 - direct methane aromatization (DMA) 7
 - discretization approach 175
 - distillation 5–8, 26, 43, 98, 117–128, 132, 138–145
- e**
- Eco-indicator 226, 290, 293
 - electric current 274
 - electro-coagulation flocculation (ECF), for dye removal
 - aromatic compounds 99
 - carcinogenic, mutagenic and toxic 99
 - Celestine Blue dye 99
 - electro-generated coagulants 99
 - energy consumption 100
 - Fenton reagent and electro-kinetic coagulation 99
 - MECF system 102
 - membrane fouling 101
 - membrane process 99, 100
 - NaCl loading and energy input 100, 101
 - endothermic reaction 152, 155, 156, 159, 160
 - energy consumption 16, 44, 46, 50, 52, 54, 58–60, 63, 99, 100, 132, 151, 152, 155, 156, 160–163, 165, 287
 - energy integration 285, 287
 - energy requirement 43, 111, 274–276
 - ethylene 4, 6–11, 23
 - exchanger minimum approach
 - temperature (EMAT) constraint 232
 - exothermic reaction 153–156, 159–160
 - external concentration polarization (ECP) 49, 50
- f**
- forward osmosis (FO) 45, 98
 - advantages 107
 - applications 107
 - electrolysis unit 109–111
 - experimental setup 109–110
 - high energy requirement 111
 - RO system 107
 - wastewater treatment 111
 - fouling deposition 168, 169, 180, 186, 189, 192
 - fouling threshold 167, 171–172, 180, 181, 187, 194
 - fractionation train 23, 26, 37
 - furnace inlet temperature (FIT) profiles 184, 185, 193, 196
- g**
- Gauging Reaction Effectiveness for ENvironmental Sustainability of Chemistries with a multi-Objective Process Evaluator 302
 - general algebraic modelling (GAMS) environment 239, 268, 296
 - genetic algorithm-simulated annealing algorithm (GA-SA) 224
 - Gibbs free energy 45, 48, 49
 - glycol circulation rate 36
 - greenhouse emissions 5
 - GREENSCOPE

biorefinery 304
 economic indicator 306, 313, 315, 316
 efficiency indicators 312–313
 energy indicator 311
 environmental indicator 305–310
 material and energy flows 307
 process design and operation 303
 sustainability performance
 assessment 303

h

heat exchange equipment 38
 heat exchanger network (HEN)
 cold and hot streams 152–153
 coupling optimization 161–163
 decrease of pinch temperature
 140–141
 distillation 132
 economic and environmental burdens
 225
 energy-consuming units 151
 fouling mitigation in
 backup heat exchanger 175–176, 194
 cleaning schedule 168, 175
 constraints 188–189, 193
 energy recovery and operation
 stability 167
 fouling threshold concept
 171–172
 heat transfer related models
 172–173
 hydraulic behavior 168
 MINLP model 168
 mixed-integer linear programming
 (MILP) 169
 objective function 177–178
 optimization algorithm 178
 optimization constraints
 176–177
 optimizing cleaning schedule
 168
 parameter optimization 168
 pressure drop related models
 174
 regular cleaning 168
 velocity and cleaning schedule
 optimization 186–194
 velocity and temperature 167
 velocity optimization 169–171, 178–186
 velocity variation 169
 heat integration with no change in
 pinch temperature 141, 142
 with heat pump
 across-pinch rule 131, 134
 energy efficiency 131
 GCC with increased pinch
 temperature 137
 GCC with pinch interval 134, 136
 heat pocket in original pinch and
 GCC 135–137
 pinch location 133
 pinch temperature 132
 placement 142–145, 147
 vapor compression 133
 hot and cold utilities 151
 increase of pinch temperature
 138–140
 initial and average heat duty of 183
 mathematical programming methods,
 and hybrid techniques 131
 operating costs of lean, regenerating
 and utility streams 242
 pinch analysis 131
 reactor characteristic 160
 and reactor interaction 152
 systematic approaches 131
 temperatures, selectivity and
 conversion of reactor 157–160
 temperature variations 153–156
 velocity related performances of
 170
 heating value 19, 23, 31–35, 69, 90, 91, 310, 312
 heat-integrated distillation column
 (HIDiC)
 basic design of 120–122
 bottom-integrated column
 123–124
 conventional column 119
 energy savings and economic
 evaluation 126–128

- heat-integrated distillation column (HIDiC) (*contd.*)
 - geometrical analysis for heat panels 124–126
 - top integrated column 122–123
 - working principle 117, 118
- heat integration 147
 - distillation process and background process 145
 - vapor compression heat pump 145
- heat recovery pinch diagram (HRPD) 151
- heat transfer related models 172–173
- heat transfer zones 204
- high-octane gasoline (HOG) 302–304
- H₂S removal process 240–254
- hybrid process
 - concentration polarization 49
 - external concentration polarization (ECP) 49
 - Gibbs free energy of mixing 49
 - osmotic pressure 47
 - osmotic process 47
 - semi-permeable membrane 47
- hydrostatic pressure 47, 48, 104, 105

- i**
 - internal combustion engine 290
 - internal concentration polarization* (ICP) effect 45
 - internal rate of return (IRR) 88
 - interplant composite diagram 210
 - interplant heat integration (IPHI)
 - energy efficiency and environment impacts 201
 - HEN configuration 215
 - implementation result 212
 - indirect IPHI 209–212, 216
 - large-scale IPHI problem 205, 207–209
 - nimety heat sources/sinks 205, 206
 - parallel connection pattern 217
 - plant integration 201, 204–205
 - plant selection 201, 204
 - stream selection 201
 - interplant shifted composite curve 210
 - irreversible energy loss 44

- j**
 - Joule Thomson effect 82

- l**
 - large-scale IPHI problem 201, 203, 205, 207–210, 212, 217
 - life cycle assessment (LCA) 225–226, 290, 316
 - logarithmic mean concentration differences (LMCD) 236
 - logical constraints 235, 267
 - LTS inlet temperature 36

- m**
 - macroscale simulation 72
 - mass exchange networks (MENs)
 - economic and environmental burdens 225
 - lean streams 223
 - operating costs of lean, regenerating and utility streams 242
 - simultaneous synthesis of 243–244
 - synthesis of 242–243
 - mass integration 4, 285, 298
 - mass-separating agents (MSAs) 221
 - material balances 229, 264, 265, 274, 276–277
 - mathematical programming 131, 151, 167, 204
 - membrane distillation 43, 98, 108, 262
 - membrane process 70, 97–100
 - mesoscale simulation 71–72
 - methane composition 18, 19, 26
 - methanol 4–8, 11, 119, 120, 240, 244, 245, 249, 303, 304, 313
 - microalgae cultivation
 - aeration 103
 - biomass concentration 104
 - CO₂ consumption intensity 102
 - CO₂ transport and O₂ sweeping efficiency 103
 - environment sustainable approach 102

- hydrophilic coating 104
- hydrophilicity and pore size 104
- membrane aerator 105
- membrane technology 103
- surface hydrophilicity 105
- mixed-integer linear programming (MILP) 169
- mixed integer nonlinear programming (MINLP) 9, 168, 206, 227, 268
- Monte Carlo simulation 32
- multistakeholder approach 295
- n**
- nanoscale simulation 70, 71
- natural gas
 - consumers of 3
 - low natural gas prices 3
 - treatment 296
- natural gas liquids (NGLs) 3
 - methane 19
 - price 34–35
 - processing plant 15
 - recovery and separation 15
 - recovery process 23–25
- nearest and Largest Q_{rec} -based screening algorithm (NLQSA) 207
- nonlinear programming (NLP)-based approach 168
- nonlinear programming (NLP) mathematical model 224
- o**
- open-loop configuration 54–55, 58–63
- optimization constraints 176–178
- osmotic energy 45
- osmotic pressure curve 44
- p**
- permeate flowrate 279–280
- phenomena building blocks (PBBs) 8, 9
- pinch analysis 131, 145, 151, 167, 204
- pinch principles 206
- pinch technology 224
- plug-flow reactor (PFR) 157
- plus-minus principle 207
- Polley's model 167, 171, 180, 186
- pressure drop related models 174
- pressure retarded osmosis (PRO) 45, 48
 - FO 45
 - Gibbs free energy 45
 - membrane costs 46
 - process design and development 46
 - technical capability of 46
 - TFC membranes 45
 - unit model 52–54
- process integration (PI) 44, 201, 221, 261, 285–288
 - housing complex
 - environmental impact 290–292
 - fresh water consumption 289
 - greenhouse gas emissions 290
 - multistakeholder approach 295
 - process route healthiness index (PRHI) 293–294
 - sustainability return of investment 293
 - total annual cost 289
 - mass integration 285
 - targeting 285–286
 - task identification 285
- process intensification 8–11, 286
 - classification 287
 - equipment 287
 - methods 287
- process route healthiness index (PRHI) 288, 293–294
- process route index (PRI) 5, 16, 22, 30, 32
- process safety evaluation 17
- process simulation 17–20, 23–26, 35, 70, 72, 76, 117, 119, 128
 - economic calculations 21–22
 - fixed costs 21
 - revenue 21
 - variable costs 20–21
- propane 3, 6–8
- provides simultaneous phenomena building blocks (SPBBs) 8

r

- Rankine steam cycle 76
- ReCiPe method indicator values 241, 245
- regeneration network (REN) 229
 - operating costs of lean, regenerating and utility streams 242
- regeneration unit
 - electrodialysis membrane
 - regeneration unit 273–277
 - mass and contaminants balances 265
 - reverse osmosis membrane 277–280
- reverse osmosis (RO) 108
 - closed-circuit configuration (CCRO) 44
 - irreversible energy loss 44
 - single-stage RO 44
 - two-stage RO desalination 44
 - unit model 49–52
- Reynolds number 167, 171
- RO-PRO hybrid system
 - closed-loop configuration 46, 55–56
 - mathematical model 56–59
 - open-loop configuration 46, 54–55
 - optimization results and comparative analysis 59–62
 - thermodynamic analysis 46

s

- seawater desalination technologies 43
- secondary reflux and vapourization (SRV) 117
- selective hydrogenation process (SHP) 8
- sensitivity analysis 17, 32–33, 35, 107
- shale gas 15
 - methodology 18
 - natural gas price, effects on 3
 - process intensification 8–11
 - synthesis gas 4
 - technical and economic factors 2
 - treatment process 17
- shale play 2, 17

- site grand composite curve (SGCC) 203
- site source sink profiles (SSSP) 203
- Soft Confining Methodology for Ultrathin Film (SCMUF) 73
- stage heat balance 231
- synthesis gas 4

t

- task identification 285
- techno-economic analysis 15–38
- total annual costs (TAC) 9, 206, 224, 288, 289
- total capital cost (TCC) 127, 289
- total site heat integration (TSHI) 131, 201
- trans-membrane pressure 278

u

- ultrathin membrane, for
 - oxygen-enriched combustion
 - Aspen HYSYS 79–82
 - compressor power requirement 83–85
 - confinement effect 69
 - economic parameter 88–90
 - gas transport properties 69
 - macroscale simulation 72
 - mathematical model 75
 - membrane area requirement 82–83
 - mesoscale simulation 71–72
 - mixed gas transport properties 73–75, 77–79
 - nanoscale simulation 70
 - process optimization 72
 - thickness dependent physical and gas transport properties 69
 - turbine power requirements 85–88
 - unassisted heat source/sink plants (UAPC) 207, 209
 - unit model
 - PRO unit model 52–54
 - RO unit model 49–52
- v**
- van't Hoff factor 47

W

- water and energy resources
 - economic data 269
 - freshwater consumption 289
 - hydraulic fracturing process 262
 - industrial and domestic use 261
 - logical constraints 267
 - mass and contaminant balances for sinks 265
 - material balances for sources 264
 - membrane technologies 261
 - with multiple membrane regenerators 264
- objective function 267–268
- optimum design configurations of
 - blackbox model 271
- optimum water network
 - configuration 270
- process data for 268
- regeneration cost analysis 270
- source and sink approach 263
- wastewater generated and total cost of water network 269
- water balances for permeate and reject streams 265
- water-energy nexus 43

