

## Index

### a

- abrasive water jet machining (AWJM) 173, 175, 177, 179, 180
- abrasive wear 109, 116, 142
- adhesion wear 107–109
- advanced light helicopter (ALH) 9
- aircraft 21, 46, 77, 79, 82, 85, 96, 99, 165–167, 218
- Aircraft Wings 77
- ammonia 217
- animal-based fibers 215
- aramid reinforced aluminium laminates (ARALL) 147
- atomic force microscopy (AFM) 132
- autoclave curing method
  - advantages 85
  - chamber pressure 86
  - chamber temperature 85
  - composite 81
  - cooling phase 83
  - disadvantages 85
  - gas firing 82
  - heating phase 83
  - holding phase 83
  - low thermal conductivity 84
  - parameters 85
  - phenolic resin 84
  - temperature gradient 84
  - vacuum 82
- autoclave molding process 46

### b

- ball milling method 5
- banana fibers 3, 26, 31, 35, 44, 239
- barely visible damages (BVD) 147–148

- bending strength 135
- bicoherence estimation 149, 155–157, 159, 161, 162
- biocomposites 2, 3, 21, 23, 34, 124, 226–230, 238–241, 256
- biodegradability 9, 143, 209, 228, 230, 239, 249, 258
- biodegradable polymers 9, 23
- biodegradable fibers 249
- biopolymer 227, 230, 232, 238, 240–243, 255
- Brunauer–Emmett–Teller (BET) 129
- bulging of flame retardants 217–218

### c

- carbon fiber reinforced polymer (CFRP) 147, 165, 250, 252
- carbon nanotubes (CNTs) 2, 8, 41, 55, 59–61
- carbon quantum dots (CQD) 8
- characterization
  - chemical 122–126
  - definition 119
  - durability 140–144
  - fiber reinforced polymers 121
  - levels 119
  - material science tetrahedron 119
  - mechanical 132–137
  - physical 126–132
    - hardness 130–131
    - void fraction 129
  - thermal 137–140
- Charpy impact test 136
- chemical characterization 122–126
- chemical recycling methods 254

- chromatography 122–124
  - cohesive energy density 109
  - coir fibers 3, 249
  - composite materials
    - challenges 23–25
    - classification 21, 22
    - defined 147
    - development of 28
    - modeling of 48
    - nanocomposites 58
  - composite characteristics 166
  - composite fabrication 40, 46, 191
  - compounding methods 25, 26
  - compression molding 6, 11, 24, 26, 28–31, 43–45, 69, 121, 131, 166, 190, 228, 249, 256–258, 261
  - consequential approach (CLCA) 232
  - conventional machining processes 165
    - drill bit geometry 168–170
    - grinding assisted drilling 167
    - high speed drilling 168
    - milling process 171
    - turning 171–173
    - vibration assisted drilling 168
  - creep 141, 142, 209
  - crude oil 225
  - crystallinity of cellulose 210
  - curing techniques 78
    - classification of 79
    - conventional and advanced 79
    - polymer composites 79
    - radiation
      - curing 93
      - electron beam radiation 96–98
      - ultraviolet 98–99
    - resin 78
    - thermal curing
      - autoclave 81–86
      - induction 86–89
      - microwave 90–93
      - resistance 89–90
      - ultrasonic 93
- d**
- decomposition process 209
  - density 128
  - differential scanning calorimetry (DSC) 137, 139–140
  - differential thermal analysis (DTA) 137, 139–140
  - direct extrusion processes 29
  - direct intercalation 66
  - drill bit geometry 168–170, 172, 180
  - durability characterization
    - creep test 141
    - environment test 143–144
    - fatigue test 141–142
    - fire test 143
    - wear test 142–143
  - dynamic mechanical analysis (DMA) 137, 140
  - dynamic mechanical thermal analysis (DMTA) 140, 250
- e**
- electrical discharge machining (EDM) 166, 178–179
  - electrochemical discharge machining (ECDM) 166, 179–180
  - electron beam radiation (EBR) curing 96–98
  - encapsulation method 7
  - end of life (EOL) 2, 226, 230, 259
  - energy dispersive spectroscopy (EDS) 124, 197–199
  - ethylene dimethyl acrylate (EMA) 3
  - extrusion method 26
- f**
- fabrication techniques
    - autoclave molding process 46
    - compression molding process 43–45
    - filament winding 42–43
    - hand lay-up process 40–42
    - injection molding 34–35
    - nanocomposites 58
    - polymer matrix nanocomposites 59–60
      - direct mixing 68–70
      - intercalation method 64–67
      - nano-fillers 63–64, 68–70
      - sol-gel method 67–68
      - ultrasonic and dual mixing 61–63
    - pultrusion process 48–49

- resin transfer molding process
  - 46–48
- vacuum bagging process 45–46
- Fast Fourier Transform (FFT)
  - 148, 159
- fatigue wear 109, 110, 142
- Federal Motor Vehicle Safety Standard (FMVSS) 219
- fiber-metal laminates (FML) 147–162, 165
- fiber reinforced plastics
  - applications 105
  - failure mechanism 106–107
- fiber reinforced polymer composites (FRPCs) 1, 39, 70, 77
  - application of 9–11
  - architecture of 2
  - ball milling method 5
  - biodegradation of 257–258
  - carbon nanotubes 2, 8
  - chemical recycling 254–255
  - curing time 77
  - development of 2, 3
  - disadvantage 8
  - fabrication methods of 4
  - hydrolytic degradation of 255–256
  - in situ approach 5
  - landfilling method 8
  - liquid lubricant microencapsulation 7
  - matrix material 4
  - mechanical recycling 252–254
  - nanocomposites 5
  - photodegradation 256–257
  - primary and secondary processing methods 6
  - products 5
  - properties of 249
  - reprocessing/recycling methods 251–252
  - self-reinforced composites 7
  - shape memory alloy 5
  - sugarcane 250, 252
- fiber reinforced polymers (FRP)
  - characterization of 121–122
  - chemical characterization 122–126
  - composites 189
  - cost-effective 121
  - durability characterization 140–144
    - environment test 143–144
    - fatigue test 141–142
    - fire test 143
    - wear test 142–143
  - mechanical characterization 132–137
    - compression test 134
    - flexural test 135
    - impact test 136
    - shear test 136–137
    - tensile test 133–134
  - phases 121
  - physical characterization 126–132
    - density 128
    - microscopic 126–128
    - surface hardness 130–131
    - surface roughness 131–132
    - void fraction 129
  - thermal characterization 137–140
    - differential scanning calorimetry 139–140
    - differential thermal analysis 139–140
    - dynamic mechanical analysis 140
    - properties 138–139
    - thermogravimetric analysis 139
- fibers/surface, chemical treatment 3
- fiber surface modification 25, 47
- field emission scanning electron microscopy (FESEM) 61, 127, 197
- filament winding process 42, 43
- filler/polymer nanocomposites 56
- flame retardants
  - bulging 217–218
  - mineral 216–217
  - types 216
- flat bottom hole (FBH) 148, 150, 157–158
- flexural strength 9, 35, 44, 86, 93–95, 99, 135, 194–196, 200, 258
- Fourier transmission infrared spectroscopy (FTIR) 124
- friction, deformation 107

**g**

- gas chromatography (GC) 122–124
- glass fiber 2, 3, 5, 9, 10, 21, 43, 45, 48, 49, 56, 64, 83, 86, 115, 116, 142, 147, 150–152, 165, 180, 189–205, 228, 239
- glass fiber reinforced polymer (GFRP) 5, 43, 56, 147, 165, 189–206
- glass reinforced aluminum (GLARE) 147, 165
- gold bridges 9
- graphene 8, 56, 59, 69, 191, 256
- green bio-composites 226, 227, 229–230

**h**

- hand lay-up process 40–42, 81
- hardness 130–131
- Hertz equation 107
- high-density polyethylene (HDPE) 114
- high speed drilling (HSD) 168
- high speed steel (HSS) 171
- hybridization 3, 180
- hybrid polymer matrix composites (HPMCs) 189
- hydraulic pressure 112
- hydrolytic degradation 251, 255–257

**i**

- impact test 136
- induction curing
  - advantage and disadvantage 89
  - carbon fiber 86
  - coupling distance 86
  - heat generation 87
  - heating dispersion 87
  - magnetic field 88
  - polymer composites 87
  - principle 86
  - thermal energy 88
- infrared pyrometer 112
- injection molding
  - challenges
    - distribution and alignment 33
    - fiber attrition 33–34
    - residual stresses 34
  - fabrication 34

- mechanical performance 34–35
- operating parameters
  - barrel temperature 31–32
  - pressure 32
  - screw speed 32
  - speed 32
- principle 29

- in situ polymerization technique 66
- intercalation method 64–67

**j**

- Joint Committee on Powder Diffraction Standards (JCPDS) 125

**k**

- Knoop hardness (HK) 130

**l**

- laminate composites 39–41
- landfilling method 8
- laser beam machining (LBM) 173–174
- life cycle assessment (LCA)
  - bio-composites 238–241
  - biopolymer 240–241
  - natural fiber 239–240
- consequential approach 232
- definition 230–233
- goal and scope 233–234
- indirect land use change 232
- interpretation 237–238
- life cycle inventory 234–235
- life cycle impact assessment 235–237
- limitations 241–243
- methodology 226
- performance steps 232
- principle 233
- software 233
- life cycle impact assessment (LCIA) 232, 235–237
- life cycle inventory (LCI) 231, 234–235
- life cycle thinking (LCT) 238
- lignin 25, 210, 215, 219, 230, 260
- liquid column chromatography (LCC) 122, 123
- local defect resonance (LDR)

- bicoherence estimation 155–157, 159
  - concepts 149–150
  - Fast Fourier Transform 159
  - flat bottom hole modelling 157–158
  - GLARE plate model 152
  - steady state analysis 152–153, 161
  - low density polyethylene (LDPE) 111
- m**
- mass spectrometry 124
  - mathematical model 86, 138, 140, 143, 190
  - matrix material 2, 4, 7, 28, 59, 77, 79, 85, 90–92, 99, 174, 191, 209, 226, 252, 254
  - matrix phase 59, 60
  - mechanical characterization
    - compression test 134
    - flexural test 135
    - shear test 136–137
    - tensile test 133–134
  - mechanical recycling 8, 239, 250–254
  - melt compounding 68–69
  - melt mixing process 60
  - microcapsules 7
  - micro-cellulose fibrils 215
  - microcrack propagation 56
  - microscopic characterization 126–128
  - microscopic technique 113, 127
  - microwave curing method 79, 93
  - milling process 171, 173
  - mineral flame retardants 216–217
  - multiwalled carbon nanotubes (MWCNTs) 2, 7, 61
- n**
- nanocomposites
    - advantages 59
    - classification 59
    - fabrication technique 58
  - nano-fillers 56, 58, 59, 116
    - direct mixing 68–70
    - melt compounding 68–69
    - solvent method 69–70
    - three-roll mixing of 63–64
  - nanomaterials 55
    - applications 55
    - classification 58–60
  - nanoparticles 55, 56, 58–61, 63, 65–69
  - nanotechnology 55, 56
  - natural fibers 21, 209, 249
    - advantages 209
    - classification of 21
    - comparative analysis 23
    - compounding 25
    - fire performance
      - building materials 219–220
      - transportation 219–218
    - flame retardants 216–218
      - bulging 217–218
      - mineral 216–217
      - types 216
    - flammability aspects 210–215
    - life cycle assessment 239
    - mechanical performance of 209
    - preprocessing of 25–26
    - surface modification 25
    - vs. synthetic fibers 23
    - thermal behavior effects 215
    - thermal properties 210–215
  - nitrogen 129, 139, 199, 217, 236, 237, 240
  - nonconventional machining processes
    - abrasive water jet machining 175–177
    - electrical discharge machining 178–179
    - electrochemical discharge machining 179–180
    - laser beam machining 173–174
    - ultrasonic machining process 174–175
  - nondestructive evaluation (NDE) 147, 149–153
  - nondestructive techniques 190
  - non-Gaussian autoregressive model 149
  - nuclear magnetic resonance (NMR) 124
- o**
- onion peeling model 68

**p**

- paper chromatography (PC) 122, 123
  - parameter dependent bispectrum
    - technique 149
  - partially biodegradable composites 23
  - photodegradation 256–257
  - photoelectric photometer 113
  - physical characterization
    - density 128–129
    - microscopic characterization 126–128
    - surface hardness 130–131
    - surface roughness 131–132
    - void fraction 129
  - physical recycling 252
  - physicochemical characterization 124
  - pneumatic pressure 112
  - polychlorotrifluoroethylene (PCTFE) 109
  - polycrystalline diamond (PCD) 171
  - polyethylene (PE) 9, 108–110, 114, 131, 227, 256, 257, 259
  - polymer composites
    - advantages 226
    - bio-composites 226
    - reinforcing fibers 228–229
    - thermoplastic polymer 227–228
  - polymer matrix composite (PMC)
    - classification of 23
    - compounding of 25–26
    - environmental degradation 199–201
    - experimental research 60
    - fabrication techniques 34, 192–193
      - direct mixing 68–70
      - dual mixing 61–63
      - intercalation method 64–67
      - nano-fillers 63–64
      - sol–gel method 67–68
      - ultrasonic 61–63
    - fiber surface modification 25, 47
    - life assessment of 201–205
    - materials 165
    - matrix 191
    - mechanical properties 60
    - micromechanics concepts 60
    - morphology
      - energy dispersive spectroscopy 197–199
      - inspection 202–205
      - mechanical strength analysis 194–197
      - normal and hybrid 193–194
    - preprocessing 25–26
    - processing techniques
      - comparison 30
      - fabrication 29
      - injection molding 29–35
      - primary 28
      - secondary 28
      - selection 28–29
      - reinforcement 191–192
  - polymer nanocomposites 5, 56, 60, 62, 65, 66, 69
  - polytetrafluoroethylene (PTFE) 108, 110, 115
  - polyvinyl chloride (PVC) 109, 114, 189, 252, 254
  - primary processing 6, 28, 121, 166
  - pultrusion process 6, 29, 48–49
- r**
- radiation curing
    - electron beam radiation 96–98
    - ultraviolet 98–99
  - Raman spectroscopy 70, 124
  - reinforcement architectures 2
  - reprocessing/recycling methods 251–252
  - resin transfer molding (RTM) process 6, 24, 28, 30, 46–48, 189
  - resonant ultrasonic spectroscopy (RUS) 148
  - Ruland–Vonk method 125
- s**
- sandwich composites 190
  - secondary processing
    - of composites 165
    - by conventional machining processes 166
      - drill bit geometry 168–170, 172
      - drilling 166–167
      - grinding assisted drilling 167

- high speed drilling 168
  - milling process 171
  - turning 171–173
  - vibration assisted drilling 168
  - by nonconventional machining processes
    - abrasive water jet machining 175–177
    - electrical discharge machining 178–179
    - electrochemical discharge machining 179–180
    - laser beam machining 173–174
    - ultrasonic machining process 174–175
  - Segal's empirical equation 125
  - self-reinforced composites (SRCs) 7, 9, 259
  - shape memory alloy (SMA) 5
  - shear strength 2, 64, 107, 136, 137
  - shore hardness 130, 131
  - short fiber extraction 29
  - silicon carbide (SiC) particles 191–193
  - Smith master curve 107
  - sol–gel method 56, 60, 67–68
  - solution mixing 26, 31, 66, 68
  - solvent method 68–70
  - stress–strain curve 134, 135
  - structural health monitoring (SHM) 147
  - sulfuric acid ( $H_2SO_4$ ) 199
  - surface modification
    - ethylene dimethyl acrylate 3
    - fibers 3
  - synthetic fibers 2, 4, 12, 21, 23, 24, 209, 228, 249, 262
- t**
- tensile strength 1, 2, 8, 41, 70, 94, 95, 107, 108, 133–135, 191, 192, 194–196, 200–203, 205, 216–218, 220, 250, 252, 257–261
  - thermal characterization
    - differential scanning calorimetry 139–140
    - differential thermal analysis 139–140
    - dynamic mechanical analysis 140
    - thermogravimetric analysis 139
  - thermal conductivity 8, 78, 79, 84, 86, 116, 133, 137, 138, 178, 191, 192
  - thermal curing 81
  - autoclave
    - advantages 85
    - chamber pressure 86
    - chamber temperature 85–86
    - composite 81
    - cooling phase 83
    - disadvantages 85
    - gas firing 82
    - heating phase 83
    - holding phase 83
    - low thermal conductivity 84
    - parameters 85
    - phases variation 84
    - phenolic resin 84
    - pressure vessel 82
    - temperature gradient 84
    - vacuum 82
  - induction
    - advantage and disadvantage 89
    - carbon fiber 86
    - coupling distance 86
    - glass fiber 86
    - heat generation 87
    - heating dispersion 87
    - magnetic field 88
    - polymer composites 87
    - principle 86
    - thermal energy 88
  - microwave 90
  - resistance method 89
  - techniques 79
  - ultrasonic 93
  - thermal heating processes 78
  - thermocouple pyrometer 112
  - thermographic imaging 148
  - thermogravimetric analysis 137, 139
  - thermoplastic-based composites 24, 29, 32
  - thermoplastic polymer 4, 6, 77, 109, 225–244
  - thermoplastics starch (TPS) 227, 228

- thin layer chromatography (TLC) 122, 123
  - transmission electron microscopy 111, 127
  - transportation industry 1, 218
  - travel wire electrochemical spark machining (TW-ECSM) process 179
  - tribo machines 111, 112
- U**
- ultrahigh molecular weight polyethylene (UHMWPE) 9, 109, 110
  - ultrasonic curing (UV) 93, 96
  - ultrasonic machining (USM) process 6, 173–175
  - ultraviolet curing (UV) 91, 98–99
  - universal testing machine (UTM) 133, 194, 200
- V**
- vacuum-assisted resin transfer molding (VARTM) 6, 48
  - vacuum bagging process 45–46, 81
  - vibration assisted drilling (VAD) 168
- W**
- wear
    - abrasive 109
    - adhesion 107–109
    - fatigue 109–111
    - mechanism 107
    - testing method 111–114
  - wool 4, 215, 217, 218
- X**
- X-ray diffraction (XRD) 61, 124, 125