

Index

a

accelerated aging time 277
 accelerated wet aging 302
 acetophenone (AP) 34, 295, 320
 activation energy data 276, 277
 ADSS cable 381, 384
 aliphatic polyamide 41
 aluminium corrugated screens 325
 aluminium hydroxide (ATH) 171, 172, 175
 angle of refraction 354
 antimony trioxide (Sb₂O₃) 169–172
 AP1000 nuclear power plant 258
 aramids 41
 aramid yarn 366, 367, 380, 381
 armour layers 297
 Arrhenius equation 27, 274, 275
 ASEAN Smart City Network 12
 attenuation, of coaxial cables 339
 azodicarbonamide (ADCA) 28

b

balance of forces 90, 91, 95
 band dispersion unshifted single-mode optical fibre
 extended wavelength 356
 barrier zone 103
 Beer–Lambert law 212
 bending loss 357
 Bernoulli law 211
 bis-(*tert*-butyldioxyisopropyl)benzene 320
 block copolymers 61, 62

blowing agents (BA) 36, 139–141
 boiling water reactor nuclear power plant 256
 bremsstrahlung 232–233
 brominated phthalate plasticizers 170
 burner calibration 197

c

cable
 aging parameters 276
 compounds 218
 conductor material 293, 294
 extrusion lines 85–87
 history of 311
 industry 1
 insulation
 extruded 295–296
 HVDC cables 296
 lapped 294–295
 sets 165
 sheath 117, 234, 380
 tensile curve 377–378
 cable constructions
 in Asia and Australasia
 cable demand 10–11
 polymeric material demand 11–12
 demand, polymeric material 3–10
 electric 1
 in Europe
 cable demand 12–13
 polymeric materials demand 13–14

- cable constructions (*contd.*)
 - investment 2
 - in Middle East and Africa
 - cable demand 14, 15
 - polymeric materials demand 14–16
 - in North America
 - cables demand 16–17
 - polymeric material demands 17–18
 - South and Central America
 - demand cables 18–19
 - polymeric materials demand 19–20
- cabled fibre attenuation test 376
- cabled fibre PMD 376, 377
- cable lifetime aging performance
 - evaluation
 - basic principles of accelerated aging of materials 272–277
- capacitance of coaxial cable 339
- capacity
 - functional capacity 241
 - measurements 127–128
- CAP1400 nuclear power plant 260
- Cargo inspection 227
- catenary continuous vulcanization (CCV) 78
- C–C bond 223
- Cenelec HD 605 protocol 321
- ceramifiable compounds 177
- chain transfer agents (CTAs) 315–317
- characteristic impedance, coaxial cables 336
- chemical blowing agent (CBA) 139–141, 145
- chemical foaming process 29
- chemical stability 263, 267
- chlorinated paraffins 70, 169, 171
- chlorinated polyethylene (CPE) 36, 37, 224
- chlorinated polymers
 - chlorinated polyethylene 36–37
 - polyvinylchloride 35–36
- chordal length 235
- circuit integrity 165, 166
- class 1E equipment qualification
 - by analogical method 270
 - by analysis 269–270
 - by calculation 269
 - by combined method 270
 - by experience 270
 - sequence 277, 279
 - by testing 269, 270, 273
- cleanliness in material handling 321, 322
- coat hanger channels 117–119
- coax-fiber hybrid design 348
- coaxial cables 332
 - applications, history of 343–344
 - attenuation 339–341
 - automotive applications 345–347
 - capacitance 339
 - characteristic impedance 336–338
 - copper-clad steel conductors 340
 - dielectric insulator 333
 - direct current transmission 332
 - history of 331–332
 - impedance mismatch 341
 - inner conductor materials 332
 - jacket sheath materials 334
 - outer conductor 333, 334
 - principles 335
 - radio-frequency transmission 332
 - velocity of propagation 338–339
 - video, TV, broadband applications 344–345
- Coax-UTP Hybrid Design 348
- combined plot 136
- communication cable 130, 166, 263
- conductive losses 339–341
- conductor design 293, 312
- conductor screen 312–313
- cone calorimeter 167, 183, 184
- Construction Product Regulation (CPR) 178, 190
 - EN 13501-6 193
 - EN 50399 198–199
 - EN 60332-1-2 196–198
 - EN 60754-2 201–206
 - EN ISO 61 034-1 199–201
 - EN ISO 1716 196
- continuous vulcanization (CV)
 - in saturated hot water stream 78–80

- control cable 263
 - convective diffusion 108
 - cooling length
 - analytical calculation
 - for fine wires 123–124
 - for fine wires 122–123
 - finite difference calculation 123, 124
 - cooling trough 85, 86, 128, 143, 144, 149–151
 - copper corrugated screens 326
 - corrugated metal screens 325
 - Coulomb's law 89
 - CPR1000 nuclear power plant 260, 261
 - critical angle 354
 - cross-linked polyethylene (XLPE) 7, 280, 294–296, 314
 - antioxidants influence 319–320
 - cross-linking parameters and peroxide influence 320–321
 - cross-linking process 317–318
 - peroxides influence 318–319
 - cross-linking
 - building construction 216
 - electron-beam (E-beam) 217, 225
 - fishing net 216
 - high crosslink densities 216
 - intermediate/medium crosslink densities 216
 - irradiation 73
 - low crosslink densities 216
 - peroxide 217, 222–225
 - peroxide system 71–72
 - polymer chains 216, 217
 - silanes 73, 217, 218
 - sulfur system 71
 - cumylalcohol (CA) 320
 - curing 216
 - of composite materials 227
 - cut-off wavelength shifted single-mode optical fibre 356
- d**
- data transmission system (DTS) cable 264
 - diameter adaptation function
 - DDR 120–121
 - DRB 121
 - dielectric constant 28, 33, 37, 38, 134
 - dielectric losses 339–341
 - dispersion shifted fibre 356
 - dispersion unshifted single-mode optical fibre 356
 - dispersive mixing 108–110
 - distribution cable and break-out cable 380
 - distributive mixing 109–111
 - distributors
 - coat hanger channels 117–119
 - flattened distribution channel 119
 - helical channel 119
 - dot notation 154
 - draw balance (DRB) 121
 - draw down ratio (DDR) 120, 121
 - drop coaxial cable 336, 340
 - Dulmage type mixing device 111
 - duplex optical cable 380
 - dynamic submarine cable testing 303, 308
- e**
- elastomers 62
 - stabilizers 70–71
 - electrical hybrid cable 385, 386
 - electrical time division multiplexing (ETDM) 361
 - electric cables
 - constructions 1
 - fire classes for 195
 - electric optical cable 381, 382
 - electromagnetic wave 336, 354
 - electron-beam (E-beam) 217
 - advantages 244–245
 - awareness 225
 - capacity
 - dose 241–242
 - efficiency 241
 - functional capacity 241
 - compound design
 - co-agents 243
 - polymers 242–243
 - raw materials 243
 - control system 231–232
 - costs indications 243–245
 - disadvantages 245

- electron-beam (E-beam) (*contd.*)
 - high voltage 228
 - parameters
 - amperage 237
 - radiation dose 237–241
 - voltage 235–237
 - principle of 227–228
 - safety
 - access doors 234
 - Bremsstrahlung/X-rays 232–233
 - IAEA 235
 - ozone 235
 - radiation and radioactivity 232
 - shielding and radioactivity 233–234
 - scan horn and beam window 228–229
 - temperature rise 242
 - UBHS 229–231
 - electron beam cross-linking 81–82
 - electron-beam welding (EBW) 227
 - electron lithography 227
 - electron microscopes 226
 - elongation at break (EAB) 274, 280
 - EN 13 501-6 193–196
 - EN 13501-6 192–193
 - EN 50399 193, 194, 198, 199
 - EN 60332-1-2 196, 197
 - EN 60754-2 201–206
 - EN 61034-2 194
 - EN ISO 61 034-1 199–201
 - EN ISO 1716 196
 - environmental stress crack resistance (ESCR) 23
 - environment resistance 265, 267
 - EPR nuclear power plant 259
 - equipment failure 267
 - Erbium Doped Fibre Amplifier (EDFA) 356
 - ethylene chlorotrifluoroethylene (ECTFE) 40
 - ethylene copolymer 22
 - ethylene-propylene-diene terpolymer (EPDM) 223
 - ethylene propylene rubber (EPR) 21, 251, 280, 294, 295
 - ethylene tetrafluoroethylene (ETFE) 38, 39
 - ethylene vinyl acetate (EVA) 8, 21, 224
 - European Construction Product Regulation (CPR) 9
 - extruded cables 78, 312
 - extruded insulation 294, 295, 297, 299
 - extruder 87
 - size 76, 78
 - extrusion defects 130
 - extrusion head
 - function 115–117
 - pressure *vs.* average temperature 121–122
 - extrusion screw
 - friction based feeding mechanism 89–90
 - improved feeding zone 95–97
 - simple modelling 90–95
- f**
- factory acceptance (FAT) 302
 - Fast Fourier Transformation (FFT) 156
 - fast neutron breeder reactor 256, 257
 - fast reactor 256
 - feeding zone 88
 - channel depth and counter pressure 93–95
 - compression and friction 106–107
 - counter pressure on 95
 - extruder 91
 - improved 95–97
 - mass output calculation 93–95
 - volumetric output *vs.* screw flight angle 92–93
 - few-mode fibre 362, 363
 - fiber coloring 371
 - fiber crack theory 363
 - fiber length 368
 - fiber ribbon 372
 - fiber secondary coating
 - loose tube 372–374
 - tight buffer fibre 374
 - fiber unit 379, 380
 - fillers 66–68, 69
 - finite difference calculation 123, 124
 - fire growth rate (FIGRA) 178, 212, 213

- Fire Performance Index 167
 - Fire Performance of Electric Cables (FIPEC) approach
 - cable selection 185–186
 - capability study 188–189
 - correlation between real and large-scale test study 189–190
 - full-scale fire test 186–188
 - real scale fire tests 186
 - real scale scenario 184–185
 - fire testing method 181
 - 5G infrastructure 387
 - fixed analysis (FA) 377
 - flame propagation tests, wires and cables for 163–164
 - flame retardants (FR) 265, 278
 - polyolefins 174–178
 - PVC 169–174
 - wires and cables for 161, 167–169
 - flame spread (FS) 162–164, 178, 189
 - flaming droplets 193, 200
 - flexible PVC compounds 35
 - flight angle 93
 - fluoro-ethylene propylene polymer (FEP) 37, 38
 - fluoropolymers 37
 - ECTFE 40
 - ethylene tetrafluoroethylene 38–40
 - fluoro-ethylene propylene polymer 37–38
 - perfluoroalkoxy polymer 39
 - polytetrafluoroethylene polymer 38–40
 - PVDF 40
 - foam extrusion
 - blowing agents (BA) 139–141
 - coaxial cables construction 133
 - extrusion equipment
 - cooling trough 149–151
 - dosing station 145
 - extruder and screw 143
 - gas injection 145–147
 - measurement devices 151
 - melt transport 148–149
 - physical foaming process 141, 143
 - motivation 133
 - permittivity 134
 - polymer selection 136–139
 - processing
 - extrusion and die setup 152–153
 - inline analysis, FFT 156–157
 - maximum void and bubble size 154–156
 - PBA handling 154
 - process control modes 153–154
 - foam insulation 133, 144, 151, 153, 154
 - foam model factor 134
 - foam-outer skin (FS) 144
 - food processing 227
 - friction coefficients 89, 90
 - channel depth 93–95
 - constant screw 107
 - on screw characteristics 105–106
 - FRP tape 366
 - full-scale fire test 186, 187
 - full-wave fibre 356
 - Furukawa Electric Co., Ltd 5
- g**
- galvanized steel strand 366
 - gas injection 145
 - glass fibre reinforced plastic (GFRP) 366
 - glass yarn 366
 - global automotive investment growth 2, 3
 - green environmental protection products 287
- h**
- halogen free flame retardant (HFFR) 8, 12, 13, 19, 21, 36, 277
 - heat release rate (HRR) 200
 - flame spread classes 193
 - by oxygen consumption technique 213
 - FIGRA and SMOGRA 212–213
 - mass flow rate 210–211
 - methane burning 208–210
 - smoke opacity 211–212
 - Heaviside, Oliver 331
 - heavy water reactors 256, 257
 - Hengtong Group 6
 - Henry's law 149

- high carbon phosphating steel wire 366
 - high crosslink densities 216
 - high density polyethylene (HDPE) 7
 - cable jackets 31, 32
 - high-speed development stage 250
 - homopolymers 22
 - horizontal continuous vulcanization (HCV) 78
 - hot capacitance device 151
 - HPR 1000 nuclear power plant 259
 - humidity resistance 267
 - HVDC cables 296
 - hybrid coaxial cable 335
- i**
- IAEA 235, 254
 - impedance mismatch, in coaxial cables 341
 - indoor optical cable 378–380
 - in-line measurements 128–130
 - inner skin-foam (SF) 144
 - instrument cable 263
 - insulated cores 272, 295, 297
 - insulation defects measurements 126–127
 - insulation integrity 165
 - insulation screen 321–323
 - insulations, for cables 315
 - interferometry (INTY) 377
 - intermediate/medium crosslink densities 216
 - intrinsic cracking 364
 - invisible bow-type optical cable 385
 - irradiation process 81–82
 - irradiation resistance 280
- j**
- jacketing/sheathing 328
- k**
- Kevlar fibre reinforced plastic (KFRP) 366
- l**
- lapped insulation 294, 295
 - latex 57
 - law of refraction 354
 - laying costs of cables 328
 - lead-based stabilizers 35
 - lead sheath cables 324
 - Leoni AG 6
 - light attenuation 199
 - light transmission 164, 352
 - light water reactors 256
 - linear low-density polyethylene (LLDPE) 7
 - cable jackets 30
 - loose tube 372, 373
 - loss of cooling accident (LOCA) resistance 280
 - test, 264 267
 - low crosslink densities 216
 - low-density polyethylene (LDPE) 7, 314
 - production 315
 - chain transfer agents, influence of 315–317
 - cross-linked polyethylene 317–331
 - Low Smoke Zero Halogen (LS0H) 8
 - low voltage power cable 263
- m**
- magnesium hydroxide (MDH) 171, 172, 175
 - magnitude, qualitative order of 96
 - Maillefer extrusion 89, 108, 111, 112, 118, 122
 - mass flow rate 210, 211
 - mass impregnated non-draining (MIND) 294
 - cables 311
 - Maxwell's equations 354, 355
 - medium and low carbon steel wire 366
 - medium-density polyethylene (MDPE) 7
 - medium voltage power cable 263
 - melt filtration systems 113, 114
 - melt flow rate (MFR) 24, 99, 155
 - melt gear pumps 114, 115
 - melting zone 88

- metallic protections
 - corrugated metal screens 325
 - designs for high voltage cables 324
 - lead sheath cable 324–325
 - tasks 324
 - metallic screens 323
 - aluminium foil with concentric copper wires 327
 - copper and aluminium *vs.* lead 327
 - properties of 326
 - metallic sheaths 296, 297
 - metallocene technology 32
 - metal tensile 366
 - metering zone 88
 - 1D analysis 105
 - representation of 104–105
 - methane burning 208, 210
 - microduct cabling 384
 - micromodule fiber optic cables
 - polyester elastomer application 42
 - micro-structured fibre (MSF) 361
 - mixing zones 88
 - aggregates type 108, 109
 - devices selection criteria 109–111
 - dispersive mixing 108–109
 - distributive mixing 109
 - Finathene HDPE 111–113
 - homogenisation mechanism of material 108
 - slow colour concentration 108
 - molecular diffusion 108
 - Monosil[®] process 219–220
 - Mooney viscosity 66, 68, 76
 - multi-core fibre 361, 362
 - multi-mode fibre, development of 358–359
- n**
- nanocomposites 173, 176, 177
 - neper 339
 - Nexans 4–5, 14, 35
 - non-metal tensile elements 366
 - nuclear grade cables 262
 - nuclear power development stage
 - high-speed 250
 - rational 250–251
 - stagnant 250
 - verification and demonstration 249–250
 - nuclear power plants
 - AP1000 258
 - boiling water reactor 256
 - cables characteristics
 - combustion performance 265
 - environment resistance 265–267
 - low toxicity 267
 - service life 265
 - technical 258–260
 - cable standards for 267
 - CAP1400 260
 - class 1E equipment qualification in 267–269, 273
 - classification by safety level 263–264
 - classification by technical types 264
 - classification by use function 263
 - classification by use occasion 264
 - CPR1000 260, 261
 - development trend
 - in China 285–287
 - in green environmental protection products 287–288
 - in Japan 284
 - in safety 287
 - EPR 259
 - excellent flame retardancy 288
 - halogen-free 288
 - heavy water reactor 257
 - high transmittance 288
 - history 261, 262
 - HPR 1000 259
 - low toxicity 288
 - no corrosive gases 288
 - pressurized water reactor (PWR) 256
 - technical development of 257–258
 - waterproof and ultraviolet proof 288
 - nuclear safety
 - grade cables 262
 - laws and regulations 268
- o**
- 1D analysis
 - compression and friction 106–107

- 1D analysis (*contd.*)
 - friction coefficients 105–106
 - optical cable core structure 380
 - optical communication system 351, 352
 - optical fibre cables 351
 - for applications 383
 - characteristic design for 370
 - classification 355–358
 - crack 364
 - development 356, 358
 - gas pipe 383–384
 - industry 386–387
 - main features 359
 - optical transmission waveguide 353–355
 - principle of total reflection 353–355
 - sheath extrusion of 374–375
 - slotted core type 382–383
 - steel tape armored directly buried 382
 - strength 363–364
 - stress erosion coefficient 365
 - optical fibre technology
 - large effective area 359–361
 - next generation 361–363
 - photonic crystal fibre 361
 - ultra-low loss fibre 359–361
 - optical signal noise ratio (OSNR) 359, 360
 - optical transmission waveguide 353, 355
 - organoclay 8, 173, 176, 177
 - outdoor optical cable 380, 381
 - oxidation induction time (OIT)
 - measurement 28
 - oxygen depletion factor 210
- p**
- paper cables 311
 - paper insulated lead cables (PILC) 311
 - Paris Agreement (2016) 2
 - peak heat release rate (PHRR) 178
 - perfluoroalkoxy (PFA) polymer 39
 - periodicity of measurement analysis
 - in-line measurements 128–130
 - structural return loss 130
 - peroxide by-products 316
 - peroxide crosslinking process (CV-curing) 217
 - advantages 224
 - disadvantages 224–225
 - polymer selection 223–224
 - reaction 223
 - phosphate plasticizers 172
 - photonic band-gap effect 361
 - photonic crystal fibre 361
 - phthalate based plasticizers 169
 - plastic fibres 7
 - plasticizers 35, 36, 68–70
 - plastification 75, 97–104
 - Poiseuille flow 105, 114
 - polyamides (PA)
 - advantage 41
 - aliphatic 41
 - imide 282, 284
 - synthesis route 40
 - polyamide 12 41
 - polybutylphthertephtalate (PBT) 41
 - polycrystalline polymers 136
 - polyester elastomers 41
 - poly-ether-ether-ketone (PEEK) 281
 - polyetherimide (PEI) 281
 - polyethylene 312
 - for cable insulation 26–29
 - for cable jackets 29–32
 - classes 23
 - density effect 24
 - manufacturing process 25–26
 - melt index/flow rate effect 23
 - molecular weight distribution effect 24
 - repetitive units in 22
 - structure 22
 - polyimide (PI) 281
 - polymer blends 62
 - polymer-compositions 216
 - polymeric compounds 63
 - polymeric material demand
 - in Asia and Australasia 11
 - in cable insulation and jacketing 7, 8
 - in Europe 13
 - Furukawa Electric Co., Ltd 5
 - Hengtong Group 6

HFFR/LSOH 8
 Leoni AG 6
 LS Cable & System 6
 in Middle East and Africa 14–16
 Nexans 4–5
 in North America 16–18
 Prysmian 4
 South and Central America 19
 Southwire 5
 Sumitomo electric industries 5
 polyolefins 21
 flame retardants (FR) 174, 175
 polypropylene (PP) 8
 cable industry applications 33
 characteristic properties 33
 manufacturing process 33
 monomer units 32
 polypropylene-based insulation 34
 polysiloxanes 176, 177
 polytetrafluoroethylene (PTFE) polymer 39
 polyurethane 62
 polyvinylchloride (PVC) 6, 7, 35–36, 168
 polyvinylidene difluoride (PVDF)
 applications 40
 emulsion polymerization process 40
 vinylidene monomer building block for 40
 power cable production 12
 pressurized liquid continuous vulcanization (PLCV) 80
 pressurized water reactor (PWR)
 nuclear power plant 256
 primary plasticizers 68
 productivity 241
 protection of cable 324
 Prysmian 4, 5, 10, 12, 14
 Pythagoras Theorem 235

q

quality parameter
 capacity measurements 127, 128
 concentricity measurement 126
 diameter and product circularity measurement 125, 126

insulation defects measurements 126, 127
 periodicity of measurement analysis 128, 130
 sheathing wall thickness measurements 128

r

radiation resistance 29, 262, 263, 265
 random copolymer polypropylene 32
 rational development stage 250
 real scale fire tests 186
 reflection coefficient 342–343
 renewable energy 2
 return loss 342
 ring suspension cable 264
 rodent resistance 385
 rubber 8, 63
 cables 62
 coding 65
 compounds 63, 69, 73, 75, 76
 heat and oil resistance of 66
 rubber elasticity 60, 61
 rubber properties 66

s

Saxton type mixing device 111, 112
 screw characteristics, friction coefficients on 105, 106
 screw geometry 88, 89
 sea trial test 302
 secondary plasticizers 70
 security cables, functional integrity for 165–166
 self-contained fluid 294
 self contained oil filled (SCOF) 294
 self-skinning effect 152
 Shannon limit 362
 sheathing wall thickness measurement 128
 shifted single-mode optical fibre
 non-zero dispersion 356
 short-wavelength division multiplexing (SWDM) 358
 silane crosslinking 217
 advantages 221
 copolymers 220

- silane crosslinking (*contd.*)
 - disadvantages 221
 - Monosil process 219
 - reactivity of 220, 221
 - Sioplas process 218
 - simplex optical cable 379
 - single screw extruder
 - different functional screw zones
 - 87–88
 - screw geometry 88–89
 - Sioplas process 218
 - skin depth 339
 - skin-effect 332, 339
 - skin-foam-outer skin (SFS) 144
 - slotted core type optical cable 382, 383
 - SMOGRA 212, 213
 - smoke corrosivity 193
 - smoke density 278
 - test 265
 - smoke opacity 211, 212
 - smoke production rate (SPR) 193, 200, 212
 - smoke suppressants 172, 173
 - solid extruded cables 312
 - Southwire 5
 - space division multiplexing (SDM) 361
 - stagnant development stage 250
 - stainless steel
 - tape 385
 - wire and steel pipe 366
 - sterilization 227
 - Stokes parameter measurement (SPE) 377
 - stranding cable technology 374, 375
 - stress erosion coefficient 365
 - strip-able screen 322
 - structural return loss (SRL) 130, 148, 342, 343
 - styrene-butadiene-styrene-triblock copolymers 62
 - submarine power cable
 - accelerated wet aging 302
 - accessories 299–300
 - after installation or commissioning 302
 - applications 291
 - armour layers 297
 - conductor material 293, 294
 - design 292–293
 - dynamic 303–304, 308
 - factory acceptance (FAT) 302
 - installation 306–308
 - insulation 294–296
 - manufacturing plants 298, 299
 - metallic sheaths 296–297
 - other cable elements 297–298
 - power system 293
 - pre qualification 302
 - project specific and
 - development/special 302
 - protection and commissioning 306–308
 - routine 301
 - sample 301
 - sea trial test 302
 - sizing 305–306
 - testing 301–303
 - type 302
 - Sumitomo electric industries 5
 - Supersmooth screens 312
 - surface treating 227
 - system failure 267
- t**
- telecommunication wire 127, 128
 - tensile design
 - for central bundle tube optical cable 367–369
 - for layer-stranding optical cable 369–370
 - stretch calculation 366–367
 - tensile force 303–307
 - thermal resistance 280
 - thermoplastic compounds 63, 243
 - thermoplastic elastomers (TPE) 8, 60, 61
 - block copolymers 62
 - polymer blends 62
 - structural models 62
 - thermoplastic polyester elastomers (TPEE) 41, 42
 - thermoplastic polyimide 281
 - thermoplastic polymers 21
 - chlorinated polymers 35

polyolefins 21
 thermoplastic polyurethane (TPU) 42, 168
 thermoplastic vulcanizates (TPV) 62
 13th Five-year Plan 10
 thin film melting, barrier zone 103
 thin film plastification
 initiation of liquid film 98–99
 melt flow rate 99
 melting backside of flight 97–98, 100
 melting length parameters 99–103
 tight buffer fibre 374
 time domain reflectometry
 measurement (TDR) 302
 total heat released (THRR) 178
 total smoke production (TSP) 189, 212

u

ultra-high-capacity transmission 361
 under-beam handling system (UBHS) 229
 Unified National Fine thread (UNF) 143
 United Nations Organisation 2
 upside down procedure 75

v

velocity of propagation 338–339
 verification and demonstration stage 249
 vertical continuous vulcanization (VCV) 78

vinylchloride monomer (VCM) 35
 voltage source converter (VSC) 295
 voltage standing wave ratio (VSWR) 342
 vortex-induced vibrations (VIV) 303
 vulcanization technique 78
 vulcanizing 216

w

wastewater treatment 227
 water tree tests 321
 wavelength division multiplexing (WDM) 361
 WDM communication system 352
 Weibull curve 364
 wideband transport single-mode optical fibre
 non-zero dispersion 356
 wires and cables
 flame propagation tests for 163–164
 flame retardants (FR) 161–169
 flammability of 167
 polymers for flame-retardant 167–168
 smoke, corrosivity and toxicity tests for 164

y

Young's modulus 367

z

Ziegler–Natta catalysts 26, 32
 zinc borate 8, 172, 176, 177

