

Contents

| | | |
|----------|---|----------|
| 1 | Cyclic Loading/Unloading Tensile Fatigue of Ceramic-Matrix Composites | 1 |
| 1.1 | Introduction | 1 |
| 1.2 | Unidirectional Ceramic-Matrix Composites | 2 |
| 1.2.1 | Materials and Experimental Procedures | 3 |
| 1.2.1.1 | C/SiC Composite | 3 |
| 1.2.1.2 | C/Si ₃ N ₄ and SiC/Si ₃ N ₄ Composites | 3 |
| 1.2.1.3 | SiC/CAS Composite | 4 |
| 1.2.2 | Theoretical Analysis | 4 |
| 1.2.2.1 | Stress Analysis | 4 |
| 1.2.2.2 | Matrix Cracking | 6 |
| 1.2.2.3 | Interface Debonding | 7 |
| 1.2.2.4 | Fiber Failure | 8 |
| 1.2.2.5 | Hysteresis Theories | 9 |
| 1.2.3 | Results and Discussion | 13 |
| 1.2.3.1 | Effect of Fiber Volume Fraction on Fatigue Hysteresis Loops and Fatigue Hysteresis-Based Damage Parameters | 13 |
| 1.2.3.2 | Effect of Matrix Cracking Density on Fatigue Hysteresis Loops and Fatigue Hysteresis-Based Damage Parameters | 15 |
| 1.2.3.3 | Effect of Fiber/Matrix Interface Shear Stress on Fatigue Hysteresis Loops and Fatigue Hysteresis-Based Damage Parameters | 16 |
| 1.2.3.4 | Effect of Fiber/Matrix Interface Debonded Energy on Fatigue Hysteresis Loops and Fatigue Hysteresis-Based Damage Parameters | 20 |
| 1.2.3.5 | Effect of Fiber Failure on Fatigue Hysteresis Loops and Fatigue Hysteresis-Based Damage Parameters | 22 |
| 1.2.4 | Experimental Comparisons | 24 |
| 1.2.4.1 | C/SiC Composite | 24 |
| 1.2.4.2 | C/Si ₃ N ₄ Composite | 30 |
| 1.2.4.3 | SiC/Si ₃ N ₄ Composite | 33 |
| 1.2.4.4 | SiC/CAS Composite | 38 |
| 1.3 | Cross-Ply and 2D Woven Ceramic-Matrix Composites | 43 |
| 1.3.1 | Materials and Experimental Procedures | 47 |
| 1.3.1.1 | C/SiC Composite | 47 |

| | | |
|----------|--|------------|
| 1.3.1.2 | SiC/SiC Composite | 48 |
| 1.3.2 | Theoretical Analysis | 49 |
| 1.3.2.1 | Stress Analysis | 49 |
| 1.3.2.2 | Transverse and Matrix Cracking | 58 |
| 1.3.2.3 | Interface Debonding | 60 |
| 1.3.2.4 | Hysteresis Theories | 62 |
| 1.3.3 | Results and Discussions | 75 |
| 1.3.3.1 | Effect of Fiber Volume Fraction on the Interface Sliding and Fatigue Hysteresis Loops | 75 |
| 1.3.3.2 | Effect of Fatigue Peak Stress on the Interface Sliding and Fatigue Hysteresis Loops | 77 |
| 1.3.3.3 | Effect of Matrix Crack Spacing on the Interface Sliding and Fatigue Hysteresis Loops | 79 |
| 1.3.3.4 | Effect of Interface Properties on the Interface Sliding and Fatigue Hysteresis Loops | 81 |
| 1.3.3.5 | Effect of Matrix Racking Mode Proportion on Interface Sliding and Fatigue Hysteresis Loops | 85 |
| 1.3.4 | Experimental Comparisons | 87 |
| 1.3.4.1 | Cross-Ply C/SiC Composite | 87 |
| 1.3.4.2 | 2D SiC/SiC Composite | 94 |
| 1.4 | 2.5D and 3D Ceramic-Matrix Composites | 103 |
| 1.4.1 | Materials and Experimental Procedures | 104 |
| 1.4.1.1 | 2.5D C/SiC Composite | 104 |
| 1.4.1.2 | 3D Braided C/SiC Composite | 104 |
| 1.4.1.3 | 3D Needled C/SiC Composite | 105 |
| 1.4.2 | Hysteresis Theories | 105 |
| 1.4.2.1 | Interface Slip Case 1 | 105 |
| 1.4.2.2 | Interface Slip Case 2 | 106 |
| 1.4.2.3 | Interface Slip Case 3 | 107 |
| 1.4.2.4 | Hysteresis Loops | 107 |
| 1.4.3 | Experimental Comparisons | 108 |
| 1.4.3.1 | 2.5D C/SiC Composite | 108 |
| 1.4.3.2 | 3D Braided C/SiC Composite | 110 |
| 1.4.3.3 | 3D Needled C/SiC Composite | 112 |
| 1.5 | Conclusions | 112 |
| | References | 112 |
| 2 | Cyclic Fatigue Behaviors of Ceramic-Matrix Composites | 117 |
| 2.1 | Introduction | 117 |
| 2.2 | Materials and Experimental Procedures | 117 |
| 2.2.1 | Unidirectional C/SiC Composite | 117 |
| 2.2.2 | Cross-Ply C/SiC Composite | 118 |
| 2.2.3 | 2D SiC/SiC Composite at 1000 °C | 119 |
| 2.2.4 | 2D SiC/SiC Composite at 1200 °C | 120 |
| 2.2.5 | 2D SiC/SiC Composite at 1300 °C | 120 |
| 2.2.6 | 3D SiC/SiC Composite at 1300 °C | 121 |
| 2.3 | Hysteresis-Based Damage Parameters | 121 |

| | | |
|----------|--|------------|
| 2.4 | Results and Discussions | 122 |
| 2.4.1 | Effects of Fiber Volume Fraction on Fatigue Damage Evolution | 123 |
| 2.4.2 | Effects of Fatigue Peak Stress on Fatigue Damage Evolution | 125 |
| 2.4.3 | Effects of Fatigue Stress Ratio on Fatigue Damage Evolution | 127 |
| 2.4.4 | Effects of Matrix Crack Spacing on Fatigue Damage Evolution | 128 |
| 2.4.5 | Effects of Matrix Crack Mode on Fatigue Damage Evolution | 129 |
| 2.4.6 | Effects of Woven Structure on Fatigue Damage Evolution | 133 |
| 2.5 | Experimental Comparisons | 135 |
| 2.5.1 | Unidirectional CMCs | 135 |
| 2.5.1.1 | SiC/CAS Composite at Room Temperature | 135 |
| 2.5.1.2 | SiC/CAS-II Composite at Room Temperature | 137 |
| 2.5.1.3 | SiC/1723 Composite at Room Temperature | 140 |
| 2.5.1.4 | C/SiC Composite at Room Temperature | 143 |
| 2.5.1.5 | C/SiC Composite at Elevated Temperature | 147 |
| 2.5.2 | Cross-Ply CMCs | 152 |
| 2.5.2.1 | SiC/CAS Composite at Room Temperature | 152 |
| 2.5.2.2 | C/SiC Composite at Room Temperature | 155 |
| 2.5.2.3 | C/SiC Composite at 800 °C in Air Atmosphere | 156 |
| 2.5.2.4 | SiC/MAS-L Composite at 800 and 1000 °C in Inert Atmosphere | 158 |
| 2.5.3 | 2D CMCs | 158 |
| 2.5.3.1 | SiC/SiC Composite at 600, 800, and 1000 °C in Inert Atmosphere | 158 |
| 2.5.3.2 | SiC/SiC Composite at 1000 °C in Air and in Steam Atmospheres | 164 |
| 2.5.3.3 | SiC/SiC Composite at 1200 °C in Air and in Steam Atmospheres | 191 |
| 2.5.3.4 | SiC/SiC Composite at 1300 °C in Air Atmosphere | 209 |
| 2.5.4 | 3D Braided CMCs | 226 |
| 2.6 | Discussions | 229 |
| 2.6.1 | Cyclic Fatigue at Room Temperature | 229 |
| 2.6.2 | Cyclic Fatigue at Elevated Temperature | 233 |
| 2.6.3 | Comparison Analysis | 238 |
| 2.7 | Conclusions | 245 |
| | References | 246 |
| 3 | Dwell-Fatigue Behavior of Ceramic-Matrix Composites | 249 |
| 3.1 | Introduction | 249 |
| 3.2 | Theoretical Analysis | 251 |
| 3.2.1 | Dwell-Fatigue Damage Evolution Model | 253 |
| 3.2.2 | Dwell-Fatigue Lifetime Prediction Model | 256 |
| 3.3 | Results and Discussions | 258 |
| 3.3.1 | Effects of Hold Time on Dwell Fatigue Damage Evolution | 258 |
| 3.3.2 | Effects of Stress Level on Dwell Fatigue Damage Evolution | 263 |
| 3.3.3 | Effects of Matrix Crack Spacing on Dwell Fatigue Damage Evolution | 268 |
| 3.3.4 | Effects of Fiber Volume Fraction on Dwell Fatigue Damage Evolution | 272 |
| 3.3.5 | Effects of Oxidation Temperature on Dwell Fatigue Damage Evolution | 276 |
| 3.4 | Experimental Comparisons | 280 |

| | | |
|----------|--|------------|
| 3.4.1 | Cross-Ply SiC/MAS Composite | 280 |
| 3.4.1.1 | 566 °C in Air Atmosphere | 280 |
| 3.4.1.2 | 1093 °C in Air Atmosphere | 288 |
| 3.4.1.3 | Comparison Analysis | 296 |
| 3.4.2 | 2D SiC/SiC Composite | 301 |
| 3.4.3 | 2D Nextel 720/Alumina Composite | 303 |
| 3.5 | Conclusions | 304 |
| | References | 305 |
| 4 | Thermomechanical Fatigue Behaviors of Ceramic-Matrix Composites | 309 |
| 4.1 | Introduction | 309 |
| 4.2 | Theoretical Analysis | 310 |
| 4.2.1 | Thermomechanical Stress Analysis | 310 |
| 4.2.2 | Thermomechanical Damage Parameters | 312 |
| 4.3 | Thermomechanical Fatigue Hysteresis Loops | 313 |
| 4.3.1 | Results and Discussions | 313 |
| 4.3.1.1 | Effects of Fiber Volume Fraction on the Thermomechanical Fatigue Hysteresis Loops and Fiber/Matrix Interface Sliding | 313 |
| 4.3.1.2 | Effects of Fatigue Peak Stress on the Thermomechanical Fatigue Hysteresis Loops and Fiber/Matrix Interface Sliding | 317 |
| 4.3.1.3 | Effects of Matrix Crack Spacing on the Thermomechanical Fatigue Hysteresis Loops and Fiber/Matrix Interface Sliding | 321 |
| 4.3.1.4 | Effects of Fiber/Matrix Interface Frictional Coefficient on the Thermomechanical Fatigue Hysteresis Loops and Fiber/Matrix Interface Sliding | 325 |
| 4.3.1.5 | Effects of Interface Debonded Energy on the Thermomechanical Fatigue Hysteresis Loops and Fiber/Matrix Interface Sliding | 328 |
| 4.3.1.6 | Effects of Thermal Cyclic Temperature Range on the Thermomechanical Fatigue Hysteresis Loops and Fiber/Matrix Interface Sliding | 332 |
| 4.3.2 | Experimental Comparisons | 336 |
| 4.3.2.1 | Isothermal Fatigue Hysteresis Loops | 336 |
| 4.3.2.2 | In-Phase Thermomechanical Fatigue Hysteresis Loops | 341 |
| 4.3.2.3 | Out-of-phase Thermomechanical Fatigue Hysteresis Loops | 344 |
| 4.4 | In-phase Thermomechanical Fatigue Damage | 345 |
| 4.4.1 | Results and Discussions | 347 |
| 4.4.1.1 | Effects of Fiber Volume Fraction on In-phase Thermomechanical Fatigue Damage Evolution | 348 |
| 4.4.1.2 | Effects of Fatigue Peak Stress on In-phase Thermomechanical Fatigue Damage Evolution | 354 |
| 4.4.1.3 | Effects of Matrix Stochastic Cracking on In-phase Thermomechanical Fatigue Damage Evolution | 357 |
| 4.4.1.4 | Effects of Interface Properties on In-phase Thermomechanical Fatigue Damage Evolution | 361 |
| 4.4.1.5 | Effects of Thermal Cyclic Temperature Range on In-phase Thermomechanical Fatigue Damage Evolution | 365 |

| | | |
|---------|---|-----|
| 4.4.1.6 | Comparisons Between In-phase Thermomechanical and Isothermal Fatigue Loading | 368 |
| 4.4.2 | Experimental Comparisons | 370 |
| 4.4.2.1 | Thermomechanical Fatigue Loading | 371 |
| 4.4.2.2 | Isothermal Fatigue Loading | 372 |
| 4.5 | Out-of-phase Thermomechanical Fatigue | 373 |
| 4.5.1 | Results and Discussions | 374 |
| 4.5.1.1 | Effects of Fiber Volume Fraction on Out-of-phase Thermomechanical Fatigue Damage Evolution | 374 |
| 4.5.1.2 | Effects of Fatigue Peak Stress on Out-of-phase Thermomechanical Fatigue Damage Evolution | 379 |
| 4.5.1.3 | Effects of Matrix Crack Spacing on Out-of-phase Thermomechanical Fatigue Damage Evolution | 383 |
| 4.5.1.4 | Effects of Interface Frictional Coefficient on Out-of-phase Thermomechanical Fatigue Damage Evolution | 386 |
| 4.5.1.5 | Effects of Thermal Cyclic Temperature Range Out-of-phase Thermomechanical Fatigue Damage Evolution | 390 |
| 4.5.1.6 | Comparisons Between In-phase/Out-of-phase Thermomechanical Fatigue and Isothermal Fatigue Loading | 393 |
| 4.5.2 | Experimental Comparisons | 397 |
| 4.5.2.1 | Out-of-phase Thermomechanical Fatigue Loading at the Temperature Range from 566 to 1093 °C | 397 |
| 4.5.2.2 | Isothermal Fatigue Loading at 566 °C | 399 |
| 4.5.2.3 | Isothermal Fatigue Loading at 1093 °C | 401 |
| 4.6 | Thermomechanical Fatigue with Different Phase Angles | 403 |
| 4.6.1 | Results and Discussions | 403 |
| 4.6.1.1 | Effects of Fiber Volume Fraction on Thermomechanical Fatigue Damage Evolution | 408 |
| 4.6.1.2 | Effects of Fatigue Peak Stress on Thermomechanical Fatigue Damage Evolution | 416 |
| 4.6.1.3 | Effects of Matrix Crack Spacing on Thermomechanical Fatigue Damage Evolution | 426 |
| 4.6.2 | Experimental Comparisons | 432 |
| 4.6.2.1 | In-phase Thermomechanical Fatigue | 433 |
| 4.6.2.2 | Out-of-phase Thermomechanical Fatigue | 433 |
| 4.7 | Conclusions | 434 |
| | References | 434 |
| 5 | Interface Degradation of Ceramic-Matrix Composites Under Thermomechanical Fatigue Loading | 437 |
| 5.1 | Introduction | 437 |
| 5.2 | Interface Degradation Models | 438 |
| 5.2.1 | Interface Slip Case 1 | 438 |
| 5.2.2 | Interface Slip Case 2 | 439 |
| 5.2.3 | Interface Slip Case 3 | 439 |
| 5.2.4 | Interface Slip Case 4 | 440 |
| 5.2.5 | Hysteresis Loops and Hysteresis-Based Damage Parameters | 441 |

| | | |
|---------|---|-----|
| 5.3 | Experimental Comparisons | 445 |
| 5.3.1 | Unidirectional C/SiC Composite | 445 |
| 5.3.1.1 | Room Temperature | 445 |
| 5.3.1.2 | Elevated Temperature | 451 |
| 5.3.1.3 | Comparison Analysis | 456 |
| 5.3.2 | Unidirectional SiC/Si ₃ N ₄ Composite | 457 |
| 5.3.2.1 | Room Temperature | 457 |
| 5.3.2.2 | Elevated Temperature | 461 |
| 5.3.2.3 | Comparison Analysis | 467 |
| 5.3.3 | 2D SiC/SiC Composite | 468 |
| 5.3.3.1 | Room Temperature | 468 |
| 5.3.3.2 | Elevated Temperature | 470 |
| 5.3.3.3 | Comparison Analysis | 472 |
| 5.4 | Conclusions | 473 |
| | References | 474 |

Index 475