

## Index

### **a**

absolute pressure sensor 30, 49,  
54,396–397, 409, 432, 436

accelerometer ADXL50 99, 111

active matrix electron emitter array  
236, 238, 395

actuator 244

adhesive wafer bonding 352

advanced piezoresistive pressure  
sensor 49

advanced porous silicon membrane  
(APSM) 42, 49, 434

air-gap insulators 450, 455

air-gap polysilicon TSVs 464

air-gap TSVs 445, 464, 467

AlN Contour Mode Resonators  
(CMR) 117

amorphous silicon deposition 73

amperometry 226

amplitude-to-phase modulation  
(AM-PM) phase noise  
conversion 205

analog-to-digital conversion (ADC)  
183

anchor loss 201

anisotropic wet etching 17–19, 25,  
29

anodic bonding 10, 20, 392

anodic bonding (chapter 11)  
259–288

adhesion 274

charge and voltage distribution  
261

distortion 262–263

Fe-Ni-Co alloy 266

GaAs and glass surfaces 266

glass reflow process 274–276

glass-Si anodic bonding 259

influence to circuit 263–265

intermediate thin films 269–271

low temperature co-fired ceramics  
(LTCC) 269

Mallory bonding 259

variation of 271–274

atomic layer deposition (ALD) 93,  
343, 455

### **b**

back-end-of-line (BEOL) 139

ballistic electrons 231

benzocyclobutene (BCB) 224, 228,  
236, 338, 382, 455

bimorph thermal actuator 390

binary-weighted capacitor array 187

biochemical sensing 173

bis-(3-sulfopropyl) disulfide (SPS)  
458

blade test 282

bond-and etch-back 279

boron-doped diamond (BDD) 224

- Bosch process 19
  - BST varactor 241
  - bulk micromachining (chapter 2)
    - 15–48
    - active DWP (ADWP) 30, 32
    - advanced porous silicon membrane (APSM) 42, 49, 434
    - anisotropic wet etching 17–18
    - anodic bonding 20
    - bond and etched back SOI (BESOI) 22
    - cavity SOI technology 27–29
    - dissolved wafer process (DWP) 29–34
    - electrochemical etch-stop 18
    - empty-space-in silicon (ESS) 40
    - EPW (ethylenediamine pyrocatechol water) 17
    - etching techniques of Si 16
    - HF/HNO<sub>3</sub>/CH<sub>3</sub>COOH (HNA) 16
    - intermediate-layer bonding 20
    - KOH etching 18
    - micro-holes interetch and sealing (MIS) 42
    - open circuit potential (OCP) 18
    - plasma based etching 19
    - sacrificial bulk micromachining (SBM) 38
    - single-crystal reactive etching and metallization (SCREAM) process 34
    - silicon fusion bonding 20
    - silicon on glass processes 29
    - silicon on nothing (SON) 40
    - SOI MEMS 20–27
    - SOI multiuser MEMS process (SOIMUMPs) 23
    - three-degree-of-freedom (3-DOF) accelerometer 25
    - TMAH (tetramethylammonium hydroxide) 17
    - Venice process for sensors (VENSENS) 41, 437
  - bump bonding 233
  - buried channel in MEMS (chapter 19)
    - 423–442
    - application of SON 435–439
    - atomic migration 427
    - chemical etching reactions 426
    - empty space in silicon (ESS) 425
    - hydrogen annealing 427, 428
    - migration phenomena 432, 435
    - monolithic SON technology
    - pipe-and plate-shaped cavities 430
    - plate-shaped cavity 431
    - porous silicon 434
    - silicon etching phenomena 426
    - silicon on nothing (SON) 423
    - thermal treatment to silicon surface 426
  - buried oxide (BOX) 321
- C**
- cantilever piezoresistive sensor 183
  - capacitance detection circuits 7
  - capacitive accelerometers 63
  - capacitive avian influenza virus sensor 174
  - capacitive micromachined ultrasonic transducer (CMUT) 176, 468
  - capacitive pressure sensor 274
  - capacitive sensing 154
  - capacitive sensors 184
  - capacitive transduction 144
  - capacitive-type pressure sensor 436
  - capillary force based biosensor 175
  - cavity pressure 415
  - cavity SOI technology 27
  - ceramic quad flatpack (CQFP) 363
  - chemical mechanical planarization (CMP) 115, 193

- chemical mechanical polishing (CMP) 80, 275
- chemical vapor deposition (CVD) 343
- chip-in-polymer 480
- chip level transfer 236, 239
- coefficient of thermal expansion (CTE) 155, 271, 338
- combo sensors 132
- compressive stress 70
- conductive polymers 459
- copper 457
- Coriolis force 63
- creatinine detection 173
- Cu deposition rates 459
- cyclic voltammogram 225
  
- d**
- deep-etch shallow-diffusion process 32, 33
- deep reactive ion etching (DRIE) 19, 182, 233, 254, 320, 322, 451
- deposition 380, 417
- depressing thermal-mismatch stress 49
- design of experiment (DoE) 117
- diaphragm bending stress 51
- digital micromirror device (DMD) 104
- digital offset trimming 186
- direct bonded copper (DBC) substrate 370
- direct bonding (chapter 12) 279–288
  - bond and etch back SOI (BESOI) high-resolution transmission electron microscope (HRTEM) 281–284
  - hydrophilic wafer bonding 279–283
  - silicon-on-insulator (SOI) wafer 279
  - surface activated bonding (SAB) 283–285
  - wafer direct bonding 279
  - wafer fusion bonding 279
- direct current (DC) magnetron sputtering 313
- direct wafer bonding 20
- dissolved wafer process (DWP) 29, 30
- distributed tactile sensors 228
- dopamine detection 173
- doped poly Si 7
- dry-etching processes 25
- dual damascene-like processes 463
  
- e**
- elastomeric polymers 335
- electrical conductor 450
- electrochemical deposition (ECD) 321, 323
- electrochemical etch-stop 19
- electrochemical etch-stop technique (ECE) 146
- electrochemical reaction 410
- electrode module 85
- electron beam exposure system 235
- electron beam lithography 231
- electron cyclotron resonance (ECR) source 33
- electroplating 401
- electrostatic bonding 259
- electrostatic recoil detection analysis 263
- encapsulation method 381
- endoscopic optical coherence tomography (EOCT) 368
- enhance crystallization 78
- enhanced bulk micromachining based on MIS process (chapter 3) 49–60
- pressure sensor with PS<sup>3</sup> structure 50

- enhanced bulk micromachining based on MIS process (chapter 3) (*contd.*)
- advanced porous silicon in membrane (APSM) 49
  - conventional single-unit pressure sensor 53
  - cross-unit Wheatstone-bridge 50
  - depressing thermal-mismatch stress 49
  - diaphragm bending stress 51
  - dual-unit pressure sensor 51
  - dual-unit sensor 50
  - empty-space-in-silicon (ESS) 49
  - fabricated dual-unit PS3 sensor 50
  - fabricated sensor 52
  - Kovar-alloy substrate 51
  - micro-holes interetch and sealing (MIS) 49
  - silicon-on-nothing (SON) 49
  - temperature coefficient of offset (TCO) 50
- P+G integrated sensors 52
- fabrication complexity and cost 52
  - in-plane X-axis cantilever-mass accelerometer 53
  - PinG configuration 53
  - tire pressure monitoring systems (TPMS) 52
  - vertical Z-axis cantilever-mass accelerometer 53
- surface mounting technique (SMT) 58
- TUB (thin-film under bulk) 55
- epi-seal process 64, 465
- epitaxial poly Si surface micromachining (chapter 4) 61–68
- application-specific integrated circuit (ASIC) 64
  - bipolar and CMOS (BiCMOS) 62
  - capacitance detection circuit 61
  - dual thick poly Si 66
  - epi-poly Si 61
  - low-pressure chemical vapor deposition (LPCVD) 61
  - MEMS devices 61–67
- etching techniques 16
- eutectic bonding 289
- f**
- fabrication process 4, 226, 229, 274, 385, 394, 397, 417
  - femtosecond laser 391, 392
  - field assisted bonding 259
  - film bulk acoustic resonator (FBAR) 475
  - flip-chip bonding 121
  - flip-chip bump-bonding process 123
  - force feedback loop 186
  - four piezo-resistors 437
  - front-end-of-line (FEOL) 139
- g**
- gap measurement 265
  - gas sensors 180
  - germanium content 70
  - germanium sacrificial layer Ge(SA) 85
  - glass bonding process 397
  - glass frit 8
  - gold wire bonding 104
- h**
- hermetically sealed electrical feedthrough conductor 398
  - hermeticity testing 417
  - hermetic packaging 409
  - hermetic sealing 64, 397

- heterogeneously integrated
    - aluminum nitride MEMS resonators and filters (chapter 7) 113–130
    - aluminum nitride (AlN) 113
    - bandwidth (BW) 123
    - CMOS electronics 114
    - contour mode resonators (CMRs) 117
    - design of experiment (DoE) 117
    - encapsulation process 116–118
    - filter frequency responses 119–121
    - finite element analysis (FEA) 119
    - flip-chip bonding 121–123
    - free-free beam (FFB) 144
    - hybrid integration 114
    - insertion loss 123
    - out of band-rejection (OBR) 123
    - probability density function (PDF) 124
    - thin-film encapsulation (TFE) 114
    - process flow 115–116
    - redistribution layer (RDL) 114
    - self-healing filters 123
    - statistical element selection (SES) 123–12
    - thin film bulk acoustic resonator (TFBAR) 113
    - thin film encapsulation (TFE) 114
    - 3D hybrid integrated chip stack 124–126
    - universal bump metallization (UBM) 118
    - repeatable physical vapor deposition techniques 113
  - heterojunction bipolar junction transistors 70
  - high aspect ratio 19, 33, 34, 40, 147, 322, 347, 390
  - high density plasma (HDP) oxide 85
  - high-resolution transmission electron microscope (HRTEM) 281
  - hollow TSVs 445
  - hybrid polymers 335
  - hydrogen annealing 428, 435
  - hydrogen dilution 72
  - hydrophilic bonding 285
  - hydrophilic wafer bonding 279, 281
- i**
- implantable telemetry capsule 400
  - inductive coupled plasma source 19
  - inductive heating 368
  - inductive sensors 188
  - inductively coupled plasma (ICP) 19, 322
  - infrared (IR) sensors 156
  - insulated-gate bipolar transistor (IGBT) 370
  - integrated capacitive pressure sensor 378
  - integrated capacitive sensors 264
  - integrated reactive material systems (iRMS) 309
  - Interconnection methods 10
  - interdiffusion coefficient 298
  - interdigital fringing electrodes 178
  - interdigital sensing capacitors 172
  - interdigital sensing electrodes 174
  - intermediate-layer bonding 20
  - intermediate thin films 269
  - isotropic etching method 35
  - isotropic phenomenon 433
- j**
- Janus Green B (JGB) 458
- k**
- Kovar-alloy substrate 51

***l***

laser ablation 452, 388, 390  
 laser-recrystallized piezoresistive  
 micro-diaphragm pressure  
 sensor 381  
 laser soldering 362  
 liquid encapsulation 387  
 lithography/etching method 22  
 local solder assembly process 364  
 low-melting-point glass 8  
 low-pressure chemical vapor  
 deposition (LPCVD) 71, 93  
 low temperature SiO<sub>2</sub> (LTO) 93

***m***

magnetic flux 155  
 Mallory bonding 259  
 manifold absolute pressure (MAP)  
 183  
 Marangoni effect dryer 86  
 mass flow controller (MFC) 75  
 mass flow meters (MFM) 75  
 Maszara method 282  
 MEMS using CMOS wafer (chapter 8)  
 131–220  
 accelerometer 148–149  
 analog-to-digital conversion (ADC)  
 183  
 anchor loss 201  
 biochemical sensors 173–175  
 buffer oxide etch (BHF/BOE) 143  
 bulk micromachining technology  
 132  
 capacitive micromachined  
 ultrasonic transducers (CMUT)  
 176  
 coefficient of thermal expansion  
 (CTE) 155  
 creep 192  
 CTE mismatch 192  
 design rule check (DRC) 143  
 dielectric charging 203–204  
 double-ended tuning fork (DETF)  
 145  
 dry film resist (DFR) 179  
 force feedback loop 186  
 gas sensors 180–181  
 gas and humidity sensors 164  
 generic fabrication platform 136  
 Hepatitis B virus (HBV) 175  
 implementation and monolithic  
 integration 138  
 infrared (IR) sensors 156–158  
 initial deformation 192  
 interface loss 201  
 KOH & TMAH (wet anisotropic)  
 146–147  
 long-time stability 197  
 manifold absolute pressure (MAP)  
 183  
 material and interface loss  
 201–203  
 material loss 199  
 material properties 201  
 metal oxide 164–170  
 metal sacrificial 140–142  
 microelectronics and  
 micro-mechanical components  
 135  
 microfluidic structures 178–180  
 multi project wafer (MPW) 132  
 multi-sensor integration 180–183  
 nonlinearity 204–205  
 1P6M (one poly Si layer and six  
 metal layers) process 135  
 oxide sacrificial 142–143  
 phase locked loop (PLL) 191  
 phase noise 204  
 physical sensors 181–183  
 polymers 170–172  
 planar fabrication technology 131  
 poly dimethylsiloxane (PDMS)  
 178  
 poly etherurethane (PEUT) 181

- post CMOS processes 136
- pressure and acoustic sensors 175
- pressure sensor 149–150
- quality factor 199–203
- readout circuit integration
  - 183–191
- residual stresses of thin films
  - 192–199
- resonators 150–152, 158–160, 165
- RIE & DRIE 147
- sensors 165
- SF<sub>6</sub> and XeF<sub>2</sub> (dry isotropic)
  - 145–146
- single-axis and tri-axis
  - accelerometer 162
- SOI micromachining MPW
  - processes 134
- surface micromachining processes
  - 132
- tactile sensors 154–156
- TC<sub>E</sub> (temperature coefficient of elastic modulus) 144
- TC<sub>f</sub> (temperature coefficient of frequency) 144
- temperature stability 200
- thermal deformation 195
- thermal expansion coefficient
  - mismatch 195
- thermoelastic damping (TED) 201
- TiN-composite (TiN-C) 143–145
- tire pressure monitoring system (TPMS) 137
- thick epi-poly silicon layer 133
- 2P4M (two poly Si layers and four metal layers) process 135
- vertical-parallel-plate (VPP) 171, 187
- volatile organic compounds (VOC) 181
- metal bonding (chapter 13) 289–308
  - diffusion-based methods 289
  - electro-chemical deposition 291
  - eutectic bonding 301
    - Al/Ge 302–304
    - Au/Si 302
    - Au/Sn 304
  - hermetic sealing applications 301
  - microfabrication 301
  - void formation 297–298
- metal thermocompression bonding
  - 298
  - grain growth 300
  - grain reorientation 299
  - interface formation 299
- metal wafer bond technologies
  - 290
- solid liquid interdiffusion bonding (SLID) 290
  - Au/Ga and Cu/Ga 294–297
  - Au/In and Cu/In 291–294
  - Au/Sn and Cu/Sn 297
  - diffusion-based methods 289
  - electric and/or thermal conductance 289
  - Kirkendall voids 298
- 3D-integration and high precision sensors 289
- metal sacrificial 140
- metal surface micromachining (chapter 6) 99–112
- digital micromirror device (DMD) 104–110
  - amorphous TiAl<sub>3</sub>-O 108
  - anti-stick layer 110
  - creep resistance 108
  - hinge memory 105–109
  - lifetime of DMD 109
  - time-sequence control 105
- dynamic device 103
- high-temperature annealing 99
- LIGA like ultraviolet (UV) technology 99
- MEMS switch 103

- metal surface micromachining (chapter 6) (*contd.*)
    - back-end CMOS interconnect process 103
    - low resistivity metal and poly Si 103
    - single-pole four-throw
      - multiplexer configuration 104
      - working frequencies 103
    - residual stress 99
    - static device 100–101
    - static structure fixed after the single movement 101–103
    - stress-free film 99
    - X-ray lithographie, galvanoformung, abformung (LIGA) 100
  - micro cantilever 174
  - micro-electro-mechanical-systems (MEMS) 3, 15, 30
  - microencapsulation 370
  - microfabrication 3
  - microfluidic inclinometer 180
  - micro holes interetch & sealing 42, 49
  - micro-hole trenches 49
  - micromachining 3
  - micro systems 3
  - minimally invasive surgery 44, 49
  - molten solder filling 459
  - monolithically integrated switched capacitor circuit 379
  - morphotropic phase boundary (MPB) 246
- n**
- nano-imprinting resist mr-I 9000 series 352
  - nano-imprint lithography 346
  - nanosecond laser heating/bonding process 362
  - narrow-ditch trench 49
  - Ni electroplating 403, 404
  - non-cryogenic steady-state etching 452
  - non-evaporable getter (NEG) 411
- o**
- open circuit potential (OCP) 18
  - overview (chapter 1) 3–11
    - Low-temperature oxide (LTO) 7
    - LSI first approach 4
    - micro-electro-mechanical-systems (MEMS) 3
    - microstructures (MICS) 7
    - phosphosilicate glass (PSG) 7
    - system on chip (SoC) MEMS 3
    - system in package (SiP) MEMS 3
  - oxide based integrated reactive material systems (oiRMS) 313
  - oxide dry etching 162
  - oxide-rich double-ended tuning-fork (DETF) resonator 145
  - oxygen generation 410
- p**
- packaged resonator 398
  - packaging, sealing and interconnection (chapter 17) 377–407
    - conventional Al metallization 377
    - deposition sealing 380–385
    - encapsulation and electrical interconnection 377
    - interconnection by electroplating 401–404
    - lateral feedthrough interconnection 395–401
    - metal compression sealing 385–388
    - reaction sealing 378–380
    - shell packaging 380, 383



- vertical feedthrough
  - interconnection 388–395
  - through glass via interconnection 388–393
  - through Si via interconnection 393–395
- wafer level packaging (WLP) 377–378
- packaging stress suppressing
  - suspension 49
- pad module 86
- parasitic capacitance 149, 155
- parylene 176
- periodic pulse reverse (PPR) currents 458
- photolithographic techniques 3
- photolithography 3, 17
- photosensitive polymer 348
- physical sensors 181
- physical vapor deposition 313
- piezoelectric cantilevers 245
- piezoelectric material 8
- piezoelectric MEMS (chapter 10)
  - 243–256
  - cantilever and microscanner 251–254
  - composition 246
  - orientation 246
  - electrode materials and lifetime of PZT thin film 250–251
  - lead zirconate titanate (PZT) 243
  - orientation control 248–249
  - poling 254–255
  - property as an actuator 244–246
  - PZT MEMS fabrication 251–255
  - PZT thin films 249–251
  - sol-gel 249–250
  - sputtering 247–248
  - thick film deposition 249–250
  - thin film composition and orientation 246
- piezoresistive accelerometer 15
- piezoresistive sensing 21, 23, 25
- piezoresistive sensors 183
- piezoresistive Si accelerometer 396
- piezoresistive Wheatstone-bridge 55
- piezoresistors 16, 437
- piranha treatment 158
- Pirani vacuum gauge 418
- planar fabrication technology 131
- plasma based etching 19
- plasma enhanced chemical vapor deposition (PECVD) 71
- plastic deformation 103
- plastic molding 401
- plug-up process 380
- poling 254
- poly-2 as piezoresistive sensors 152
- poly-1 as thermal actuation 152
- polycrystalline Si (poly Si) 6
- polyethylene glycol (PEG) 458
- poly-ethylene2,6-naphthalate 285
- polyimide sensing film 171
- polymer bonding (chapter 15)
  - 331–360
  - dry-etch BCB 351
  - localized polymer wafer bonding 348–350
  - polymer adhesion mechanisms 332–335
  - process parameters 341–348
  - properties of polymers 335–337
  - root mean square roughness (RMS) 332
  - thermoplastic 338
  - UV curing 338
  - with thermosetting polymers 352
  - in wafer bonding 337–341
  - wafer-to-wafer alignment in 350–351
- polymer insulators 455
- polymers 170
- polypropylene glycol (PPG) 458
- polypyrrole film 171

- poly-SiGe surface micromachining (chapter 5) 69–98
    - Al-Ge bonding for microcaps 87
    - atmospheric-pressure chemical vapor deposition (APCVD) 71
    - CMEMS\* process 78
    - coefficient of thermal expansion (CTE) 79
    - cost analysis 72
    - deposition methods 70–71
    - desired SiGe properties for MEMS 70
    - electrode module 85–86
    - film thickness and Ge content 76–77
    - hydrogen peroxide release 86
    - interface challenges 79–80
    - low-temperature CVD oxide (LTO) 93
    - LPCVD polycrystalline SiGe 73
    - material properties comparison 71
    - nano-electro-mechanical (NEM) switch 92
    - pad module 86
    - particle control 75
    - plasma enhanced chemical vapor deposition (PECVD) 71
    - plug module 84
    - poly-Ge 70
    - poly-SiGe 69
    - poly-Si<sub>1-x</sub>Ge<sub>x</sub> 70
    - poly-SiGe
      - Nano-Electro-Mechanical (NEM) switches 92
    - post-CMOS integration 71
    - probability density function (PDF) 124
    - process monitoring and maintenance 75–76
    - process space mapping 77–78
    - process flow 80
    - pulsed laser deposition (PLD) 71
    - reduced-pressure chemical vapor deposition (RPCVD) 71
    - resonator for electronic timing 88–92
    - SiGe applications in IC and MEMS 70
    - slit module 85
    - spacer module 83, 85
    - structural SiGe module 85
    - structure module 85
    - top metal module 80–84
    - vertical furnace 73–75
    - X-ray fluorescence (XRF) spectrometry 76
  - polysilicon 456
  - poly-silicon deposition 55
  - polysilicon piezoresistors 174
  - poly-silicon thin-film diaphragm 57
  - pressure sensors 54, 149, 437
  - printed circuit board (PCB) 58
  - pulse method 391
  - Pyrex glass wafer 392
- q**
- quality factor 419
- r**
- radio frequency (RF) magnetron sputtering 313
  - reaction sealing 378
  - reactive bonding (chapter 14) 309–330
    - electrochemical deposition 315–319
      - dual bath technology (DBT) 316–318
      - single bath technology (SBT) 318–319
  - foil type RMS 313
  - integrated reactive material systems (iRMS) 309

- material systems 311–312
  - oxide-based integrated reactive
    - material systems (oiRMS) 313
  - physical vapor deposition
    - 313–315
  - planar multilayer stack 310
  - planar multilayer systems 310
  - reactive material systems (RMSs)
    - 309
  - self-propagating exothermic
    - reaction (SER) 309–310
  - thermite reactions 310
  - vertical multilayer stack 310
  - vertical pillar systems 310
  - vertical reactive material systems
    - 319–323
      - dimensioning 320–321
      - fabrication of 321–323
    - wafer bonding application 309
  - reactive deposition 269
  - reactive ion etching (RIE) 29, 145, 156, 282
  - redistribution layer (RDL) 114
  - release etching 424
  - resistive heating 365
  - resistive sensors 183
  - resonant sensors 190
  - resonators 150
  - resorcinol-formaldehyde (RF) aerogel
    - 172
- S**
- sacrificial etching 224
  - sacrificial layer 3
  - “scar-free” pressure sensor chip 57
  - SCREAM process 34
  - sealing and interconnection methods
    - 10
  - selective etching 417, 418
  - self-aligned metallization 22
  - self-aligned process 22
  - self-alignment effect 351
  - self-assembled beam-steering
    - micromirror 102
  - self-assembly 102
  - self-propagating exothermic reaction
    - (SER) 310, 370
  - self-propagating high-temperature
    - synthesis (SHS) 312
  - self-propagative reaction heating
    - 370
  - Semiconductor Manufacturing
    - International Corporation
      - (SMIC) 69
  - sensing films 172
  - SensorNor 132
  - sensors hub 132
  - shape memory alloy actuators 401
  - silicon beam 439
  - silicon dioxide insulators 454
  - silicon dry etching 321
  - silicon fusion bonding 20
  - silicon micromirror array 472
  - silicon-on-insulator (SOI) 20, 279
  - SOI multiuser MEMS process
    - (SOIMUMPs) 23
  - silicon on nothing (SON) 40, 49
  - silicon on sapphire (SOS) 423
  - silicon optical bench (SiOB) assembly
    - 367
  - single-crystal silicon (SCS)
    - 147, 456
  - single-wafer single-sided
    - silicon-on-nothing processes
      - 44
  - smart cut process 279
  - Smartview\* approach 350
  - SMERALDO technology 467
  - solder glass 8
  - soldering by local heating
    - (chapter 16) 361–376
      - inductive heating 368–370
      - in MEMS packaging 361
      - laser soldering 362–365

- soldering by local heating
    - (chapter 16) (*contd.*)
      - resistive heating 365–368
      - self-propagative reaction heating 370–371
      - ultrasonic frictional heating 371–373
  - solder jet bumping process 364
  - solder reflow process 364
  - sol-gel method 227
  - sol-gel orientation control 248
  - solid polysilicon TSVs 460
  - spacer layer deposition 82
  - spacer layer etch 83
  - spacer module 83, 85
  - spontaneous bonding 279
  - sputtering 247
  - state-of-the-art Bosch etchers 451
  - statistical element selection (SES)
    - technique 124
  - steady-state etching 452
  - STMicroelectronics 437
  - structure module 85
  - sub-atomspheric chemical vapor deposition (SACVD) 454
  - superconformal Cu plating 458
  - superconformal plating 458
  - super-critical rinsing and drying 233
  - surface acoustic wave filters 237
  - surface activated bonding (SAB) 283
  - surface-micromachined poly Si
    - microstructures 7
  - surface micromachining 7, 381, 400
  - surface micromachining like process 21–23
  - surface sputter etching 283
- t**
- tactile sensors 154, 229–231
  - temperature-dependent resistor 101
  - tensile stress 263
  - test evaluation group (TEG) 266
  - tetramethyl ammonium hydroxide (TMAH) 146
  - thermal annealing 7
  - thermal conduction process 372
  - thermal expansion coefficient 390, 392
  - thermal oxidation 55, 66, 378, 380
  - thermal piezoresistive resonators (TPR) 141, 152
  - thermoelastic damping (TED) 201
  - thermoplastic polymers 335, 343
  - thermosetting polymers 335, 336
  - thin film deposition 285
  - through glass via interconnection 388
  - through-substrate-vias (TSV)
    - (chapter 20) 443–492
    - conductor formation 455–460
    - conductor materials 459–460
    - copper 457–459
    - polysilicon 456
    - single crystalline silicon 456–457
    - tungsten 457
  - configuration of TSVs 444–445
    - air-gap TSVs 445
    - hollow TSVs 445
    - solid TSVs 444–445
  - deep hole etching 541–454
    - deep reactive ion etching 451–452
    - laser ablation 452–454
  - insulator formation 454–455
    - air-gaps 455
    - polymer insulators 455
    - silicon dioxide insulators 454–455
  - metal TSVs 469
    - air-gap metal TSVs 480

- hollow metal TSVs 474
  - solid metal TSVs 470
  - MIDIS technology 467
  - 1,2,3-Benzotriazole (BTA) 458
  - Periodic pulse reverse (PPR)
    - current 458
  - polysilicon TSVs 460
    - air-gap polysilicon TSVs 464
    - solid polysilicon TSVs 460
  - silicon TSVs 464–469
    - air-gap silicon TSVs 467
    - solid silicon TSVs 465
  - 3D MEMS integration and WLVP 443
  - 3-mercapto-1-propanesulfonic acid (MPS) 458
  - through glass vias (TGVs) 449
  - TSV applications in MEMS 445–450
    - CMOS-MEMS 3D integration 446–447
    - considerations for 450
    - MEMS and CMOS 2.5D integration 447–448
    - signal conduction to wafer backside 446
    - wafer-level vacuum packaging (WLVP) 448–449
  - TiN-C free-free beam (FFB) resonator 144, 145
  - TiN-composite (TiN-C) 143
  - tire pressure monitoring system (TPMS) 137
  - traditional bulk micromachining process 25
  - transversal ultrasonic bonding 372, 373
  - tri-axis accelerometer 162
  - tunable SAW filter 240, 241
  - tungsten 457
  - two multi-pore dopant injectors 75
- U**
- ultra-miniaturized wireless sensor nodes 473
  - ultrasonic Al–Al bonding 373
  - ultrasonication 372
  - ultrasonic frictional heating 371
  - ultrasonic soldering technique 372
  - UV-curable thermosetting polymers 348
  - UV nanoimprint lithography 321
- V**
- vacuum packaging (chapter 18) 409–421
    - by anodic bonding 409–414
    - cavity vacuum pressure 412
    - high vacuum cavity 411
    - non-evaporable getter (NEG) 411–414
    - optical deflection sensor 412
    - Si diaphragm vacuum gauges 413
    - soldering 410
    - vacuum encapsulation 413
    - with controlled cavity pressure 414–416
  - by deposition 417
  - by metal bonding 416–417
  - hermeticity testing 417–419
  - problems of 409
  - vacuum sealing 388
  - Venice process for sensors (VENSENS) 41, 437
  - vertical furnaces 73
  - vertical-parallel-plate (VPP) sensing capacitor 171
  - viscoelastic heating 372
- W**
- wafer direct bonding 279, 282
  - wafer level liquid compression seal 386

- wafer level packaging 377–378
- wafer-level vacuum packaging 448
- wafer transfer (chapter 9) 221–242
  - BaSeTiO<sub>3</sub> (BST) 237
  - BCB (benzocyclobutene) 224
  - boron-doped diamond (BDD) 224
  - chip level transfer 236–241
  - device transfer 226–236
    - via-first 231–236
    - via-last 226–231
  - electrochemical oxidation 232, 233
  - film bulk acoustic resonator (FBAR) 223
  - film transfer 221, 223–227
  - heterogeneous integration 221
  - low-temperature co-fired ceramics (LTCC) 221, 271, 389
  - massive parallel electron beam write (MPEBW) 232, 395
  - PZT (lead zirconate titanate) 228
  - PZT MEMS switch 228
  - tactile sensor network 228–230
  - tunable SAW filter 241
  - voltage-controlled oscillator 223
  - wafer level packaging (WLP) 222
  - wafer level transfer 223
- wet etching 62, 143
- wire-bonded through-Si vias 10
- wire bonding 401





















