

## Index

### **a**

abrasive wear 116–118  
 activation energy 137, 138, 140, 160, 311, 340  
 adhesive method 53  
 adhesive wear 115–116  
 Ag coated rGO nanocomposites 203  
 agglomerated graphene 132  
 alicyclic anhydrides 32  
 aliphatic amine 28, 187, 225, 230  
 aliphatic anhydrides 32  
 alkyl ammonium exchanged clay system 69  
 alkyl ammonium ions 65–68, 191  
 alumina 261  
 alumina nanoparticles 251  
 amines 28, 29  
 amine-terminated butadiene–acrylonitrile (ATBN) 356  
 amino-functionalization 127  
 amorphous polymers 299  
 anhydrides 32  
 aramid fibers 217, 332  
 Archimedean principle 100  
 aromatic amine 27, 28, 30, 205  
 Arrhenius equation 310  
 ATR sampling technique 218  
 automated fibre placement (AFP) 54, 55  
 average rate of heat emission 209

### **b**

ball milling 65  
 Barium titanate 312  
 barium titanate 334  
 BaTiO<sub>3</sub>/epoxy composites 311  
 benzotriazole (BTA) 364  
*N,N*-benzyl dimethyl amine (BDMA) 356  
 bio-economy 55  
 bio-epoxy composites 118  
 bisphenol-A epoxy resin 24, 34–36  
 bisphenol-F epoxy resin 34, 35  
 Boltzmann constant 319  
 broadband dielectric spectroscopy (BDS) 300  
 bubbles diffusion coefficient 246  
 buoyancy method 100

### **c**

canhydrides 32  
 carbon aerogel reinforced composites 274  
 carbon aerogels 266, 282, 284  
 carbon allotropes 137  
 carbon based nano-container 365  
 carbon-based nanofillers 263  
 carbon-based nanomaterials 266, 291  
 Carbon based nanomaterials-epoxy coating 364

- carbon black (CB) content 323
- carbon fiber composites 207
- carbon fiber reinforced composite 12, 398
- carbon fiber-reinforced epoxy systems 262
- carbon fiber-reinforced polymer (CFRP)
  - bilinear stress-strain behavior 89
  - carbon nanotubes 147–154
  - energy dissipation 89
  - fatigue 87
  - fiber-contact model 88
  - graphene-based materials 154–158
  - with hybrids 158–160
  - mechanical and interfacial properties 89
  - microstructural parameters 88
  - off-axis fiber orientations 88
  - stress-strain curves 89
  - two-point probe method 88
- carbon fibers (CF) 217, 225, 270, 276, 399
- carbon fibers-epoxy composit 374
- carbon hollow 363
- carbon nano fiber nanocomposites
  - loss factor vs. temperature of 193
  - residual weight vs. temperature curves of 195
  - SC-15 epoxy 192–194
  - storage modulus vs. temperature of 193
  - thermo gravimetric traces of 195
- carbon nanofibers 245
- carbon nanofillers 263
- carbon nanohorns 288
- carbon nanomaterials 126
- carbon nanotube fillers
  - nanocomposites
    - cellulose nanofiber nanocomposites 196, 197
    - DGEBA, OMPOSS, and APP nanocomposites 201–202
    - EPIKOTE™ resin 862 194
  - carbon nanotubes 288
    - mechanical properties 149
- carbon nanotubes (CNT) 225, 246
  - grafting CNTs 272
- carbon nanotubes (CNTs)-SME 356
- carbon-reinforced polymer composites 263
- carboxylated SWCNT (SWCNT-c) 267
- carboxylic nitrileoendash butadiene nanorubber (CNBNR) 357
- carboxyl-terminated acrylonitrile-butadiene copolymers (CTBN) 234
- cation exchange capacity (CEC) 66
- cellulose 99
- cellulose nanofibers 109, 262
- centrifugal casting 48
- CeO<sub>2</sub>/NiO hybrids 203
- ceramic fillers 260
- ceramic nanoparticles 260
- Charpy impact tests 106
- chemical recycling 409
- clay based nanomaterials-epoxy coating 365
- clay behavior 2
- clay content 72
- clay galleries 243
- clay modification 243
- clay platelets 242
- clay-reinforced nanocomposites 261
- closed-moulding process
  - centrifugal casting 48–49
    - LRTM 44–45
    - pultrusion 46–47
  - reinforced reaction injection moulding 41–42
  - vacuum bag moulding 47–48
  - vacuum infusion process (VIP) 45–46
  - VARTM 43
- combustion process 403
- combustion residue 403
- composite materials 97, 350
- cone calorimeter measurements 209

- conventional thermal curing (TMC) 138
- coupling agent 395
- covalent bonding 142
- critical phenomenon 317
- cross-linked epoxy polymers 70
- CSE-modified epoxy composites 181
- cure reaction analysis 145
- Curie temperature 312
- curing agent 67
- conventional thermal curing (TMC) 138
  - dynamic mechanical analysis 138
  - hyperbranched polyesters (HBP) 138
  - polydopamine (PDA)-MWCNT/epoxy systems 139
  - spectroscopy techniques 139
- cycloaliphatic epoxy resin 26, 34, 35
- d**
- D-clay nanocomposites DMA, 189
- DGEBA 7
- 4,4'-diaminodiphenylmethane (DDM) 140
- 4,4'-diamino diphenyl sulfone (DDS) 223, 354
- diaminodiphenyl sulphone 242
- dicyandiamide 33
- dicyclopentadiene (DCPD) 379
- dielectric permittivity 301, 304
- dielectric reinforcing function (DRF) 315
- dielectric theory 301
- Diels-Alder (DA) 372
- diethylene toluene diamine 207
- differential scanning calorimetry (DSC) 5, 111
- diglycidyl ether of bisphenol-A (DGEBA) 351, 352
- 9,10 dihydro-9-oxo-10-phosphaphenanthrene-10-oxide (DOPO) 191
- displacement method 100
- distorted structures 178
- double cantilever beam (DCB) test 374
- 3-D printing 53
- DSC 140
- dynamic mechanical analysis (DMA) 3, 113, 127, 206, 284
- dynamic mechanical thermal analysis (DMTA) 65
- e**
- e-glass fiber 84
- electrically driven heterocatalytic decomposition (EHD) 410
- electric modulus 308
- electromagnetic shielding (EMI) 13, 398
- electron-beam (E-beam) 54, 55
- embedding method 361
- energy dissipation 89
- energy-dissipative processes 290
- energy efficiency, coefficient 339, 340
- epichlorohydrin 25
- Epon 862 199
- Epon nanosuspension 199
- epoxidized natural rubbers (ENR) 373
- epoxy-amine 221
- epoxy anhydride system 223
- epoxy-based composite material (ECM) 349
- applications for 397–400
  - DSC analysis 112
  - flame retardant properties 399
  - impact properties 106–108
  - recycling options for 405–410
  - safety and environmental issues of 400–405
  - tensile properties 104–106
  - widespread use of 397
- epoxy based hybrid composites 332
- epoxy-based nanocomposites 263
- epoxy-carbon based nanomaterials composites 358

- epoxy-clay nanocomposites
  - evolution of 65–67
  - mechanical properties 61
  - mechanism of 67–72
  - micro-and nanoscale structures 62–65
  - reaction-induced phase separation 61
  - self-assembly 61
- epoxy composites 265, 290
  - carbon nanotube (CNTs) 2
  - dielectric properties 9
  - dispersion and interfacial adhesion 266–273
  - dynamic mechanical analysis 284–288
  - epoxy resins 1, 2
  - experimental techniques 3–6
  - factors 1
  - fiber-matrix interaction 218
  - fracture surface morphology 273–278
  - fracture toughness 281–282
  - futuristic processing 52–54
  - impact properties 282–284
  - lap shear properties 288–289
  - manufacturing methods, for fabrication 2–3
  - manufacturing of
    - closed-moulding process 41–49
    - open moulding 37–41
  - mechanical properties 6–9
  - morphological analysis 233
  - morphology of 11–12
  - nanoparticle filled epoxy composites 51–52
  - stress-strain properties 278–281
  - systems 259
  - thermal stability 6
  - thermosetting polymers 1
  - water/moisture absorption 9–11
  - WAXD patterns of 234
- epoxy/conductive filler
  - micro-composites 317–325
  - nano-composites 325–331
- epoxy cresol novolacs (ECN) 25
- epoxy fillers 260
- epoxy/glass fiber composites
  - bis(4-cyanato 3,5-dimethylphenyl)naphthyl methane 178–179
  - DGEBA 179–182
  - DSC cure characteristics 180
  - DSC cure curve 180
  - jute fiber content 186
  - mechanical and thermal behaviour of flax 186
  - novolac type epoxy and isocyanate modified epoxy 182
  - and sisal 186
- epoxy-hybrid reinforced system 144
- epoxy/IM-7/MWCNT buckypaper micro-nanocomposite 211
- epoxy matrix 70, 260, 265, 276
- epoxy nanocomposites 261, 273
  - cure reaction
    - DSC and DMA techniques 145
    - 3D hybrid carbon nanostructures 143
  - dynamic-mechanical analysis 130
  - EPIKOTE 828LVEL epoxy resin 136
  - hyperbranched polyamide 135
  - mechanical and thermomechanical epoxy nanocomposites 131
  - mechanical and thermomechanical performance 135
  - melamine 129
  - multi-walled carbon nanotubes 128
  - noncovalent functionalized CNTs 128
  - 1D-2D reinforcements and epoxy chains 136
  - poly(4-aminostyrene) (PAS) 128
  - polystyrene sulfonate (PSS) 128
  - pristine carbon nanotubes 130
  - thermomechanical improvements 127
  - 2D carbon nanomaterial 131

- epoxy/nature fiber composites
  - kenaf fiber composites 182–185
  - MH filled kenaf/epoxy hybrid 188
  - phormium tenax fiber composites 185–186
- epoxy/non-conductive filler
  - micro-composites 306–312
  - nano-composites 312–317
- epoxy novolac resins 35
- epoxy organoclay nanocomposite 244
- epoxy phenol novolacs (EPN) 25
- epoxy-reduced graphene oxide (RGO) 354
- epoxy resins 1, 2, 83, 91, 113, 125, 177, 284, 299
  - anhydride and etherification reaction 219
  - anionic and cationic initiators 31–32
    - alicyclic anhydrides 32
    - aliphatic anhydrides 32
    - anhydrides 32
    - canhydrides 32
    - imidazole 31
    - polymercaptan 31–32
  - bisphenol-A epoxy resin 24
  - bisphenol-F epoxy resin 24–25
  - clay nanocomposites 188–192
  - crosslinking of 83
  - cure reaction 218
  - curing condition 34
    - bisphenol-A epoxy resin 34–35
    - bisphenol-F epoxy resin 34
    - cycloaliphatic epoxy resin 34
    - glycidylamine epoxy resin 34
    - phenol novolac epoxy resin 34
  - cycloaliphatic epoxy resin 26
  - data interpretation
    - dielectric and conductivity 300–302
    - experimental techniques 300
  - D-clay nanocomposites 189–190
  - DGEBA and organomodified clay 190
  - DGEBA-DER332 DNA modified clay 191
  - DGEBA-LY556-based epoxy resin 204
  - dielectric response of 303
  - diluents 36
  - electrical properties of 302–306
  - epoxy/conductive filler
    - micro-composites 317–325
    - nano-composites 325–331
  - epoxy/non-conductive filler
    - micro-composites 306–312
    - nano-composites 312–317
  - fracture toughness 241
  - glycidylamine epoxy resin 27
  - history of 23–24
  - hybrid composites 332–342
  - latent curing agents 33, 34
    - boron trifluoride-amine complex 33
    - dicyandiamide 33, 34
    - organic-acid hydrazide 33–34
    - ultraviolet-curing agents 33
  - moisture absorption 245
  - moisture absorption behaviour
  - natural fiber 49, 90
  - organo phosphorus epoxy resins 190–191
  - phenol novolac epoxy resin 25
  - polyadditions reaction 28
  - polyamide and polyamine 28–30
  - primary amine 219
  - properties of 300
  - reaction mechanisms 34
  - resin diluents 26–27
  - safety and environmental factors 36–37
  - secondary amine 219
  - secondary and tertiary amines 30–31
  - thermal stability and electrical conductivity 260
  - worldwide production of 396

epoxy resin system 142  
 epoxy's reinforcements 264  
 epoxy surface 11  
 ethylenediamine (EDA) 126, 356,  
 369  
 5-ethylidene-2-norbornene (ENB)  
 catalyst 378  
 ethyl phenylacetate (EPA) 380  
 excess epoxy 50  
 exfoliated nanocomposites 63,  
 64  
 exfoliation process 71  
 external modifiers 259

**f**

FeO(shell) nanoparticles 198  
 fiber oendash reinforced epoxy  
 composites 217  
 fiber-epoxy interface 11  
 fiber inhalation 92  
 fiber-matrix debonding 277  
 fiber-matrix interaction 218  
 fiber-reinforced epoxy-based  
 composites 262  
 fiber-reinforced epoxy composites  
 261  
 fiber reinforced polymer composites  
 83, 98, 177  
 fiber thermal stability 111  
 Fickian behaviour 243  
 Fickian diffusion law 102  
 filament winding process 40  
 filler modification 266  
 flocculated nanocomposites 64  
 Flory-Huggins interaction parameter  
 68  
 fluorinated MWCNT (F-MWCNT)  
 225  
 Fourier transform infrared analysis  
 (FTIR) 6  
 Fourier Transform Infrared  
 Emission Spectroscopy  
 (FT-IES) 142  
 fracture toughness 249, 399  
 frontal polymerization process 66

FTIR-attenuated total reflection  
 (FTIR-ATR) 233  
 FTIR technique 144

**g**

glass aluminum reinforced epoxy  
 (GLARE) 85, 86  
 glass fibers 97, 217, 277  
 glass transition value 112  
 global warning potential (GWP) 407  
 glycidylamine epoxy resin 27, 34  
 graphene (GE) 125, 205, 263, 264  
 graphene-based materials 155  
 graphene derivatives 133  
 graphene 2D reinforcement-epoxy  
 nanocomposites 141  
 graphene nanoparticles 246  
 graphene nanoplatelets (GNPs) 7,  
 246, 253, 288, 373  
 graphene oxide (GO)-SME  
 composites 357  
 graphite fibers 226  
 graphite nano-plateletes (GNP)  
 327  
 Grubbs' catalyst 378

**h**

halloysite nanotubes (HNT) 365  
 hand lay-up process 38  
 hand lay up technique 178, 187  
 hexamethylene diisocyanate (HDI)  
 370  
 high-modulus (HM) carbon fibers  
 225  
 high-pressure mixing 65  
 high-pressure process 67  
 hollow fibers 377  
 hollow glass microspheres (HGM)  
 369  
 homo polymerization 221  
 homo-polymerization 221  
 Hoveyda-Grubbs' catalyst 378  
 hybridization 103  
 hybrid micro-nanocomposites 207  
 hydrogen bonding 65

hydroxyl-terminated polybutadiene (HTPB) 234

## *i*

Imidazole 31  
 imidazole-functionalized graphene (G-IMD) 141  
 inorganic fillers 261  
 in-situ cure monitoring 218  
 in situ intercalative polymerization 65  
 intelligent materials 349  
 interacted nanocomposites 63  
 intercalated 63, 64  
 intercalated and exfoliated nanocomposites 64  
 intercalated nanocomposites 64, 67  
 interfacial bonding 142  
 interfacial polarization (IP) 305, 333  
 interfacial shear stress (IFSS) 8, 225  
 inter laminar shear strength (ILSS) 86  
 intermediate dipolar effect (IDE) 334  
 intra-gallery polymer 69  
 intrinsic healing system 372

## *j*

Jeffamine D230 353  
 Jeffamine D400 and T403 353  
 jute fiber content 186

## *l*

labor-intensive method 217  
 lap shear joint test 289  
 layered double hydroxide (LDH) 362, 363, 367  
 life cycle assessment 397  
 light resin transfer moulding (LRTM) 44  
 long fiber reinforced epoxy composites  
 blast resistant materials 84  
 blasts and impact resistance 83  
 durability and structure 83

epoxy and long glass fiber composite 84–87  
 modified machining processes 83  
 thermal insulating materials 84  
 loss modulus 113

## *m*

matrix modification 266  
 maximum average rate of heat emission (MAHRE) 209  
 Maxwell-Garnett theory 398  
 Maxwell-Wagner-Sillars (MWS) 333  
 mechanical recycling technique 406  
 melamine 129  
 mercaptobenzothiazole (MBI) 361, 362  
 mercury intrusion porosimetry 211  
 4,4'-methylenedianiline (DDM) 354, 356  
 methylhexahydrophthalic anhydride (MHHPA) 356  
 microcapsule healing system 377  
 microcomposite 63  
 micronanocomposites 206  
 microscopic techniques 63  
 moisture absorption 243, 251  
 mono-epoxy compounds 27  
 montmorillonite (MMTs) 365  
 m-phenylenediamine (m-PDA) 354, 356  
 multi-walled carbon nanotubes (MWCNTs) 3, 128, 245, 246, 268, 269, 330, 331

## *n*

nano alumina 204, 246  
 nanoalumina filled epoxy nanocomposites 254  
 nano-carbon 289  
 nanocellulose 109  
 nanoclay concentration 67  
 nanoclay content 66  
 nanoclay dispersion technique 67  
 nanoclay layers 63  
 nanoclay modifier 67

- nanocomposites 64, 127, 130, 354  
nanofillers 247, 286, 288  
nanoparticles 336, 367  
nano-reinforcements 260  
nanotechnology 241  
natural fibers 2, 99, 217  
    advance fabrication processes 90  
    composites 7  
    hand lay-up method 90  
    kenaf fiber volume content 91  
    reinforced composites 99  
    abrasive wear 116–118  
    adhesive wear 115–116  
    erosive wear 115  
    physical behaviour 100  
    thermal behaviour 108–114  
neopentyl glycol diglycidyl ether (NGDE) 354  
non-bonding interactions 65  
nonfunctionalized porous graphene (NPG) 283  
novolac epoxy resin 25
- o**
- octadecylamine modified montmorillonite 242  
octadecyl ammonium ion-modified montmorillonite/DGEBA resin 242  
open moulding 37  
organic-acid hydrazide 33  
organic cation exchange sites 70  
organo-clay 234
- p**
- particulate filled epoxy composite 231  
peak heat release rate (PHRR) 209  
Phase separated microcomposite 62  
phenol novolac epoxy 25, 26, 34, 35  
plasticization 103  
polyacrylic acid (PAA) 361  
polyacrylonitrile (PAN) 377  
polyadditions reaction 28  
polyaniline (PANI)-stabilized silica nanoparticles nanocomposites 199, 200  
poly ethylene glycol (PEG) 366  
polyimides 177  
poly lactic acid (PLA) 377  
polymer 99  
    clay composites 62–65  
    confinement 68  
    curing process 300  
polymercaptan 31  
polymeric shell 361, 377  
polymer matrix nano-composites 312  
polymer micro/nano-container-epoxy coating 368  
polymer nanocomposites 63, 72, 263, 328, 330  
polymers 299  
polymethyl methacrylate (PMMA) 368  
polyoxyethylene octyl phenyl ether 355  
polyvinyl pyrrolidone (PVP) stabilized graphene 235  
porous graphene 264, 272  
primary energy demand (PED) 407  
printed circuit boards (PCB) 13  
pristine carbon nanotubes 130  
pristine epoxy 198  
processing techniques 66, 67  
pultrusion 46
- q**
- quaternary alkylamine modified montmorillonite (KH-MT) 242  
quaternary ammonium modified montmorillonite 242
- r**
- radial breathing modes (RBMs) 228  
Raman scattering 225  
Raman spectroscopy 139, 223, 225, 236



- Random free-energy barrier model 322
- raw sisal fibre reinforced epoxy composite 107
- reactive diluents 26
- reinforcing phase 299
- residual stresses 228
- resin casting (RC) 104
- resin diluents 26
- retro Diels-Alder (rDA) 372
- rubbers 259
  
- S**
- saline vapor exposure 233
- self-healable epoxy composites 371
- self-healing behavior 371
- self-healing epoxy composites trends 380
- intrinsic healing system 372–374
- microcapsule healing system 377–380
- self-healing behavior 371
- vascular healing system 375–377
- self-healing mechanism 399
- semiconductor encapsulation 398
- semi-crystalline polymers 65
- sepiolite 245
- shape memory alloys (SMA) 360
- shape memory effect 399
- shape memory epoxy (SME) 351
  - based composite structures 358–360
  - based nanocomposites 354–358
  - behavior epoxy 350–354
  - DGEBA 352
  - wires 360
- short strand fibre 50
- silane coupling agents 65
- silica based nanomaterials-epoxy coating 366
- silica nanoparticles 260
- single walled carbon nanotube (SWCNT) 228, 267, 268
- smart epoxy composites 349
  - carbon based nanomaterials 364–365
  - clay based nanomaterials 365–366
  - layered double hydroxide 367
  - nanoparticles-epoxy coating 367–368
  - polymer micro/nano-container 368–370
  - silica based nanomaterials 366–367
- smart materials 349
- smectite 245
- smoke production parameters 210
- solid epoxy natural fibre composite 51
- solution intercalation method 266
- spectroscopic techniques 139, 217
- spherical metal oxide nanocomposites 202
- spraying coating technique 153
- spray-up process 39
- storage modulus 113, 114
- strain calibration factor (SCF) 227
- supercapacitors 13
- supercritical fluids 409
- symmetric hopping model 322
  
- t**
- tan delta 114
- tensile analysis 280
- thermal degradation 191
- thermally reduced freeze-dried graphene oxide (TRfdGEO) 143
- thermally reduced graphene oxide (TRGO) 143, 246
- thermal processing 409
- thermogravimetry analysis (TGA) 6, 186
- thermoplastic matrices 84
- thermoplastic polymers 98, 259, 351, 374
- thermoset polymer 98
- thermosets 299

- thermosetting epoxy polymer 83
- thermosetting polymers 1, 241, 299
- 3D carbon nanomaterials 144
- 2,4-toluene diisocyanate (TDI) 354, 357
- treated sisal fibre-reinforced epoxy composite 107
- triethylenetetramine (TETA) 141, 205, 250, 376
- trimethylolpropane triglycidyl ether (TMPTE) 376
- 2D ATR-FTIR spectroscopy 233
- 2D material 263
- 2D carbon nanomaterials 131
- 2D carbon nanostructures 139
- u**
- ultrasonication 65
- ultrasonic fabrication method 54
- ultrasonic waves 269
- unsaturated polyesters 177
- urea-formaldehyde (UF) 368
- UV-initiated curing process 223
- v**
- vacuum-assisted resin infusion (VARIM) methods 104
- vacuum assisted resin transfer moulding process (VARTM) 43
- vacuum bag moulding 47
- vacuum infusion process (VIP) 45
- variable range hopping (VRH) model 319, 320
- vascular healing system 375
- vascular network healing system 376
- Vogel-Fulcher-Tammann (VFT) 311
- voids generation 100
- w**
- water absorption
  - on dielectric properties 254
  - dynamic mechanical properties 251–253
  - factors 242–247
  - on mechanical properties 247–250
  - rate 102, 103
  - test 101
  - thermomechanical properties 253–254
- water diffusion 232
- x**
- X-ray diffraction technique 232
- z**
- ZnO nanoparticles 368











