

Index

a

- acylhydrazone bonds 198
- Ag nanowires 199
- aligned carbon nanotubes (ACNTs) 32, 169
- allyl-terminated P3HT 161, 162
- allyl-terminated poly(3-hexylthiophene-2, 5-diyl) (P3HT) 79, 161
- ammonium citrate 196
- anisotropic nanofillers 7, 9

b

- ball milling 10
- barium strontium titanate (BST) nanoparticles 62
- BaTiO₃ nanoparticles 193
- bio-inspired graphite/PDMS polymer composite 139
- bio-polar behavior 230
- biodegradable polymers, in electronics biocompatibility and metabolism 53
- cellulose 62–64
- challenges and prospects 66–67
- chemical structures 54
- chitosan 64–65
- environmental protection 53
- poly(butylene succinate) 54
- poly(ϵ -caprolactone) (PCL) 54, 58–59
- poly(vinyl alcohol) (PVA) 59–61
- poly(vinyl pyrrolidone) (PVP) 61–62
- polyhydroxyalkanoates 54
- polylactide (PLA) 55–58

silk fibril (SF) 65–66

- thin film transistor (TFT) 54–55
- biodegradation 204, 207
- boron nitride (BN) 6, 10, 231
- bulk composite 192, 193

c

- capacitive pressure sensors 131, 132, 135–138
- carbon nanotubes 6, 10, 21, 24, 26, 31–32, 158–161, 169–171, 193, 200, 219, 232, 272, 275–277
- carbon rich filaments (CRF) 227, 232, 233
- cellulose 31, 35, 54, 62–64, 66–67, 204–207, 233
- cellulose-based electro-active paper (EAPap) 62, 63
- CeO₂/PANI nanocomposites 167
- chemical etching 193
- chemically-reinforced polymer nanocomposite 144
- chitosan 54, 59, 62, 64–67, 204
- complementary metal-oxide-semiconductor 77
- conducting polymers 7, 160, 162, 267, 269, 270–274
- conductive filler 21–25, 27, 29, 31, 34, 39, 40, 41, 61, 202, 247–250, 257, 258, 274
- conductive nanofillers 7, 22, 23, 31, 33–35, 37, 40, 41, 57, 267
- conductive polymer composites (CPCs) conductivity vs. filler loading 249

- conductive polymer composites (CPCs)
(*contd.*)
- electrical conductivity 21
 - fabrication methods
 - chemical modification 22
 - electrical conductivity 22, 23
 - in situ polymerization 27
 - melt blending 23–25
 - nanofillers and special processing technique 22
 - physical blending 22
 - solution blending 25–26
 - gas sensor 35–38
 - nanofillers, selective distribution of segregated structure 29, 30
 - surface coating 31–32
 - percolation threshold 248
 - piezoresistive sensor 33–35
 - polymer matrix 27–29
 - strain sensor 33
 - temperature sensor 38–40
 - conductive polymer nanocomposites 21, 59, 132, 139, 269, 278
 - conductive polymers (CPs) 21, 85, 90, 161, 164, 165, 167, 171, 269, 274
 - conventional processing equipment 57
 - covalent bonding 7, 25, 231
 - cp(S-PMAT) copolymer 161, 162
- d**
- Diels–Alder reactions 198
 - dip coating 31, 217
 - discharge–charge process 161, 162
 - dispersion-deposition process 159
 - disulfide bonds 198, 202, 204
 - 2D materials 78, 82, 83, 86, 87, 213, 218, 231–232, 234
 - double percolation effect 271, 272
 - double-screw extrusion 10
 - 3D polymer nanocomposite 196, 197
 - 3D porous ternary composites 169, 170
 - 3D printing 57, 105, 106, 206
 - 3D printing method 57
 - 3D printing technique 57, 105
- e**
- electrical conductivity 21–25, 30, 41, 56, 57, 159, 197, 202, 205, 248, 250, 256, 270, 274, 275
 - electrical double-layer capacitors (EDLCs) 164, 165
 - electro hydrodynamic (EHD) technique 62, 217, 226, 227, 228, 231
 - atomization 231
 - method 62
 - electro-hydrodynamic atomization (EDHA) technique 226
 - electro-hydrodynamic coating technique 227, 228
 - electromagnetic interference (EMI) shielding material
 - conducting polymers for 272–274
 - conductivity studies of 274–276
 - materials for 269
 - mechanisms of 277
 - polymer blend nanocomposites 271–272
 - vector network analyzer SE 277
- electrospinning 27, 57–59, 63, 194, 195, 203
- external quantum efficiency (EQE) 80–82, 88–95, 99, 101–105, 109–112, 114–115, 117–123
- f**
- fabrication techniques 27, 217–218
 - Fe_3O_4 nanosheets 6
 - fiber reinforced composites 1
 - fibre-reinforced plastics (FRPs) 261, 262
 - fingerprint pattern 35
 - fluorine doped tin oxide (FTO) 102, 221, 232
 - fossil fuel consumption 157
 - functional polymer-based nanocomposite 189
 - functionalized graphene sheets (FGSs) 159
- g**
- gas sensor 35–38, 41, 64

glass fiber-reinforced plastics 1
 gold nanoparticles 1, 57, 65
 G/PDMS polymer nanocomposite 149,
 151
 graphene nano flakes 225, 226
 graphene nanoparticles 10
 graphene nanoplatelet (GNP) 261,
 262
 graphene oxide (GO) 27, 59, 63, 152,
 159, 193, 224–227, 233, 267

h

hard-disk drive (HDD) 211
 healing process 198, 199, 200, 204
 heat distortion temperature (HDT) 23,
 58, 67
 heptane 37, 38
 high resolution transmission electron
 microscope (HRTEM) 170
 highest occupied molecular orbit
 (HOMO) 85, 123
 H-PDMS/Ag-PEDOT film 200
 human wrist pulse detection 148–149
 hydrogel 33, 63–66
 hydrogen bonding 31, 64, 172, 173, 198,
 200, 202, 224

i

imine bonds 198, 200
 in situ polymerization process 9, 22, 23,
 27, 40, 59, 160, 162, 167, 194–197,
 278
 intrinsic systems 198
 intrinsically conductive polymers (IPCs)
 274
 introduced surfactant 40

k

Kapton films 190

l

lithium batteries 158–160
 lithium-sulfur batteries 158, 161
 lowest unoccupied molecular orbit
 (LUMO) 85, 97, 98

m

melt blending 23–25, 194, 195
 melt spinning method 56
 memristor 55, 61, 62, 66, 212, 213,
 228
 microelectromechanical systems (MEMS)
 131, 154
 microneedle array (MNA) dermal
 biosensor 56
 micropillar array 35
 microstructured composite film 141
 mixed filler 254–255, 262
 montmorillonite clays (MMT) 6
 Moore’s law 211, 233
 multi-walled carbon nanotubes
 (MWCNTs) 24–26, 29, 30, 200,
 219, 255, 267, 275–278
 multifilament elastomer fiber 31

n

nanocomposites 1–11, 53–67, 77–123,
 131–154, 157–177, 189–208,
 211–234, 247–263, 267–278
 nanofiber composite 26, 31, 32, 38
 nanofiller aggregations 40
 nanofiller incorporated conducting
 polymer composites 270–271
 nanographene platelets (NGPs) 6
 nanomaterials 1–3, 5, 6, 9, 78, 132, 153,
 154, 192, 194–198, 267, 270–272
 nanostructured polyester (PET) 53, 95,
 96, 103, 139, 141, 190, 191, 205,
 214, 221, 222, 225, 226, 231,
 232
 natural biodegradable polymers 54, 204
 negative temperature coefficient (NTC)
 effect 38–40, 247, 250, 258, 262
 next generation nonvolatile memory
 (NVM) 212

o

ohmic conductance 272
 ohmic conduction 216, 219, 222–224,
 226, 229, 230
 one-dimensional nanofillers 5–6

- organosulfur electrode – cp(S-PMAT) 162, 163
- oxide based polymer nanocomposite RSM 218–222
- p**
- pattern-transfer printing process 193
- percolation threshold 5, 22, 23, 29, 30, 40, 248, 250, 253, 257, 270–272, 275, 276, 278
- phase change material 213
- [6,6]-phenyl C₆₁ butyric acid methyl ester (PCBM) 79
- photoconductor 79, 80–82, 85–88, 99, 102, 103, 115, 118, 122
- photodetectors (PD)
- complementary
 - metal-oxide-semiconductor 77
- MEH-PPV-inorganic nanocrystals
- nanocomposite 112–115
- MEH-PPV-small molecular organic
- nanocomposite 98–99
- novel semiconductors
- 2D materials 82, 83
 - CQD-based PDs 83
 - highest occupied molecular orbit (HOMO) 85
 - lowest unoccupied molecular orbit (LUMO) 85
 - P3HT and PCBM 87
 - photo-induced excitons 86
 - quantum dots (QDs) 83
- P3HT-inorganic nanocrystals
- nanocomposite 115–116
- P3HT-small molecular organic
- nanocomposite 99–100
- photoconductor 80–82
- photodiode (PDi) 80
- polymer-polymer nanocomposite 88–98
- polymer-polymer-small molecular organic nanocomposite 108–109
- polymer-small molecular
- organic-inorganic nanocrystals
 - nanocomposite 120–123
- polymer-small molecular organic-small molecular organic nanocomposite 110–111
- photodiode (PDi) 79–80, 87–99, 101–105, 109–111, 114, 115, 120
- photomultiplication 103–105, 110
- physical blending 22, 40
- piezoresistive pressure sensors 131–132, 137–143, 149, 150, 152
- piezoresistive sensor 33–35, 41, 66, 131–132
- planar polymer composite film 141
- poly(3,4-ethylenedioxothio-phene) poly(styrenesulfonate) (PEDOT:PSS) 28, 61, 111, 214, 218–221, 229–231, 234
- poly(ϵ -caprolactone) (PCL) 54, 58–59, 66–67, 203, 205, 207, 257
- poly(3,4-ethylenedioxothiophene) (PEDOT) 29, 167, 169–171, 218
- poly(3,4-ethylenedioxothiophene) (Ag-PEDOT) 199–200
- poly(3-hexylthiophene-2,5-diyl) (P3HT) 79, 85–87, 91–92, 95, 98–99, 102–107, 110–112, 115–123, 161–162, 232
- poly(*m*-aminothiophenol) (PMAT) 162
- poly(antraquinonyl sulfide) (PAQS) 158–160
- poly(L-lactide) (PLLA) 57–58
- poly(styrenesulfonate) (PSS) 26, 167, 170, 218
- poly(vinyl alcohol) (PVA) 26, 33, 54, 59–61, 64, 66, 167, 175–176, 194–195, 205, 206–207, 214, 218–219, 221, 223–226, 229–231
- poly(vinyl pyrrolidone) (PVP) 26, 60–62, 218–219, 221–222, 224–229, 231–233
- polyacrylic acid (PAA) 64, 172, 193
- polyaniline (PANI) 21, 64–65, 165, 167, 196, 274
- polybutylene terephthalate (PBT) nanocomposites 23

- polydimethylsiloxane (PDMS) 28, 31–32, 34, 59, 135–137, 140–142, 146, 153, 190, 192–194, 199–200, 205, 227
- polydimethylsiloxane-polyurethane (PDMS-PU) polymer 199
- polyimide (PI) 27, 53, 159–161, 190, 218
- polylactide (PLA) 37, 54–59, 66–67, 205–206
- polymer blend 171, 229–230, 257–259, 261–262, 271–272, 277–278
- polymer matrix 2–3, 7–8, 21–29, 31, 35, 37, 40–41, 67, 86, 91, 115, 132, 144–145, 154, 159, 176, 190, 193–196, 198, 200–201, 205, 217–218, 232, 247, 249–250, 255, 257, 261, 262, 270, 274, 278
- polymer nanocomposite (PoNa) 78–79, 86–88, 95–96, 98–99, 101
- polymer nanocomposite (PNC) 140, 141, 145, 163, 213
- advantages 3–5
 - ball milling 10
 - batteries and supercapacitors 157
 - definition 157
 - double-screw extrusion 10
 - electrode materials
 - for batteries 158
 - for supercapacitor 164
 - polymer-graphene/carbon nanotube 158–161, 165–169
 - polymer-inorganic 161–163
 - polymer-metal oxide 165
 - polymer–metal oxide-graphene/
 - carbon nanotubes 169–171
 - polymer–organic salt graphene 163, 164
- electrolytes
- for batteries 171–172
 - for supercapacitor 172–173
- flexible and wearable electronic products 159
- heat resistance and biodegradability 2
- in situ* synthesis 10–11
- materials 218
- mechanical properties 2
- one-dimensional nanofillers 5–6
- properties of 6–7
- separator
- for batteries 174–175
 - for supercapacitors 175–176
- shear mixing 9
- surface chemical and physicochemical properties of 2
- three roller milling 9–10
- three-dimensional nanofillers 6
- two-dimensional nanofillers 6
- ultrasonication-assisted solution mixing 8–9
- polymer-graphene nanocomposites 159
- polymer-graphene/carbon nanotube 158–161, 165–169
- polymer–inorganic 112, 161–163
- polymer–metal oxide 165, 169–171
- polymer–organic salt graphene 163, 164
- polymer–polymer nanocomposite 88–98
- polypyrrole (PPy) 21, 165–169, 172–173, 226, 274, 278
- polytrimethylene terephthalate/polypropylene/carbon nanotube (PTT/PP/MWCNTs) blend nanocomposites 277
- polyurethane (PU) 28, 139, 190, 203, 223, 274
- polyvinyl alcohol (PVA) 26, 33, 54, 59–61, 64, 66, 167, 176, 194, 205–207, 218–219, 221, 225, 229, 231
- polyvinyl alcohol (PVOH) 231
- polyvinylpyrrolidone 54, 196, 218
- Poole–Frenkel effect 232
- porous G/PDMS polymer composite 142–143
- positive temperature coefficient (PTC) 247
- conductive chain and thermal expansion model 249
- conductive composites 250
- contacting points 253

- positive temperature coefficient (PTC)
(*contd.*)
- effects 38, 257
 - electrical resistivity 247
 - electron tunnelling 250
 - explanation and defects 251
 - filler dispersion and distribution 253–254
 - filler size and shape 250, 253
 - in CPCs 248
 - mechanism for 249
 - mixed filler 254–255
 - polymer blend 257–258
 - polymer thermal expansion and crystallinity 255–257
 - silver coated glass spheres 250
 - temperature sensors 259
 - pressure sensing performance 35–36, 141
 - pressure sensitivity 131–132, 134, 135, 137, 140, 142–143
 - pressure sensors
 - applications of 154
 - capacitive pressure sensors 131, 135–137
 - conductive polymer nanocomposites 132
 - E-skin application 152–153
 - flexible and stretchable pressure sensors 133
 - human wrist pulse detection 148–149
 - linear relationship 134
 - LOD and response speed 134
 - microelectromechanical systems (MEMS) 131
 - piezoresistive pressure sensors 131, 137–143
 - pressure sensitivity 132, 134
 - reliability 134
 - sensitivity, LOD and response time 153
 - subtle human motion detection 149–151
 - texture roughness detection 151–152
 - triboelectric pressure sensors 143–148
- PS/graphene/toluene suspension 24
- PVA/MXene nanofibers film 195
- PVDF/rGO polymer nanocomposite 152
- q**
- quantum dots (QDs) 6, 55, 62, 83, 114, 218, 227–229, 232
- quantum dot based RSM devices 227
- r**
- radio frequency identification (RFID)
- antenna 259
- reduced graphene oxide (rGO) 27, 63, 152–154, 159, 163–164, 167, 169, 193, 227
- reliability 64, 66, 134, 189, 197, 202, 204, 208, 224
- resistive random access memory (RRAM)
- based resistive switching 60–61, 211–213, 233
- resistive switching memory (RSM)
- alkali-lignin based RSM 223
 - cations and anions migration 216
 - charge trapping/de-trapping mechanism 232
- conduction mechanisms 216–217
- conductive filaments 214–215
- crossbar arrays 212
- current-voltage (I-V) characteristics
- curve of 214
- electro-hydrodynamic coating
- technique 228
- electrons trapping and de-tapping 216
- fabrication techniques 217–218
- graphene based polymer
- nanocomposite 224–227
- logic-in-memory function 212
- metal based nanoparticles 222–224
- neuromorphic computing 212
- next generation nonvolatile memory 212
- organic polymers and inorganic nanocomposites 213
- oxide based polymer nanocomposite
- RSM 218–222

- performance comparison 243
 PNC materials 213, 214
 polymer based nanocomposites 229–231
 polymer nanocomposite materials 218
 quantum dot based RSM devices 227–229
 resistance states 212
 switching mechanisms 215
 two-dimensional (2D) materials 231–232
 universal memory 212
 working mechanism 212
 ring opening polymerization (ROP) 55, 58
 roll-to-roll lamination fabrication method 95–96
- s**
 scalable nonvolatile memory techniques 211
 scanning electron microscope (SEM) 28, 30–33, 35–36, 136–137, 141–142, 145, 151, 159–163, 165, 167, 169–172, 175–176, 195–196, 203, 206, 219–220, 225, 228, 230
 SCLC conduction mechanism 220, 224, 230–231
 sea-urchin shaped metal nanoparticles (SSNPs) 139–140
 segregated structure 27, 29, 30, 37, 41
 self-activating potentiometric sensor 65
 self-healing TENG 198–199, 201
 self-powered pressure sensors 143
 self-powered sensors 147, 190, 200
 semicrystalline polycaprolactone (PCL) 203
 shape memory polymer (SMP) 201
 shape memory PU (SMPU) 203–204
 shear mixing 9
 silica nanoparticles 10, 172
 silk fibril (SF) 65–66, 207
 silver coated glass spheres (AgS) 250, 255
 single-walled carbon nanotube (SWNT) 31–32, 160–161
 sodium alginate film 206
 sodium dodecyl benzene sulfonate 196
 solution blending 25–26, 194–195
 solution blow spinning method 56
 solution processing technique 217, 225, 229
 space charge limited current (SCLC) mechanism 216–217, 220, 223–225, 229
 S-P3HT copolymer 161
 S-P3HT sulfur composites 161–162
 spin-coating technique 194, 230
 static pressure detection 132, 140
 strain sensor 33, 41, 59, 65, 198
 structural conductive polymers (SCP) 21
 subtle human motion detection 149–151, 154
 sufficient pressure 146
 supercapacitor 157–158, 164–173, 175–176, 197
 superhydrophobicity 33
 Swagelok cells 161
 synthetic biodegradable polymers 54, 59, 205
- t**
 temperature sensor 38–41, 63, 203–204, 248, 259–260, 262
 tetrahydrofuran (THF) 37, 38, 57, 59, 230
 texture roughness detection 151–152
 texture roughness measurement 151
 thermoforming-corrosion method 196
 thin film transistor (TFT) 55, 60–62, 64, 66, 115
 three-dimensional (3D) polymer nanocomposites 196
 three roller milling 9
 time-resolved photoluminescence method 115
 toluene 24, 37–38, 59
 transfer-printing technique 95

- triboelectric nanogenerators (TENGs) 145
 applications 192
 biodegradation 204–207
 contact electrification and electrostatic induction 189, 190
 electrical output performances 192
 FT mode 192
 functional polymer nanocomposite
 Ce-doped ZnO nanoparticles 196
 conductive sponge 197
 electrospinning 194
 fabrication strategies 194
 in-suit polymerization 195
 melt blending 195
 PCP-TENG 197
 spin-coating 194
 ultrasonic dispersion 196
 grating and rotating structures 194
 grating structure 191
 ingenious structure design 194
 ITO and electrostatic charges 192
 Kapton films 190
 mechanical damage and harsh conditions 189
 monolayer MoS₂ 193
 nanostructured polyester (PET) and
 Kapton films 190
 polymer composite 192
 self-healing TENGs
 Ag nanowires and poly(3,4-ethylenedioxythiophene)
 (Ag-PEDOT) 199
 electrical performance 198
 extrinsic systems 198
 functionalized graphene nanosheets 198
 hydrogen bond-containing elastomeric substrates 198
 intrinsic systems 198
 MWCNTs 200
 non-covalent systems 198
 PDMS-PU 199
 wrinkled graphene 198
 shape memory polymer (SMP) 201–204
 surface functionalization and bulk composite 192
 2,4,6-trinitrotoluene (TNT) 57
 tristable resistive switching behavior 229
 tunneling effect 250, 272
- U**
 ultrasonic dispersion 196
 ultrasonication 25, 31, 226
 ultrasonication-assisted solution mixing 8–9
- V**
 vinyl hybrid silica nanoparticles (VSNPs) 172–173
- W**
 wet-spinning 27
 write once and read many (WORM) 213
- Z**
 ZnO nanosheets 6