

## Index

### **a**

$A_2B(I)B(III)X_6$  halide double perovskites 120–123  
 $A_2BX_6$  halide perovskite derivatives 117–118  
 $ABX_3$  halide perovskites 108–135  
 $A_3B_2X_9$  layered halide perovskites 118–120  
 active matrix array (AMA) 414  
 active matrix flat-panel imagers (AMFPIs) 418  
 additive-involved leaching method 252  
 $Ag_2BiI_5$  271, 275–278, 280  
 $AgBi_2I_7$  37, 38, 271, 275, 276, 280  
 alignment vs. passivation interfaces 157–159  
 alkali cation doping  
   in-situ photoluminescence 227–229  
   passivation effect of excess KI 225–226  
   potassium ion 226–227  
   reduction hysteresis by KI 223–225  
 alkylammonium 63  
 alkyldiammonium cations 63  
 all-inorganic tin halide perovskites  
    $Cs_2SnX_6$  269–270  
    $CsSnX_3$  267–269  
 all-perovskite tandems 41, 161, 294, 295, 437, 440, 445  
 AM1.5G spectrum 128, 131, 137, 447  
 (3-aminopropyl) triethoxysilane (APTES) 329, 418  
 5-aminovaleric acid (5AVA) 27, 358

5-aminovaleric acid iodide (AVAI) 27  
 4-(amniomethyl)piperdine (4AMP) 97  
 amorphous Si photodiodes 413  
 antibonding coupling 107, 108, 110, 116, 120, 121  
 atomic-layer-deposition (ALD) 356  
 Auger recombination 135, 161, 329, 434

### **b**

bandgap 138, 142, 249, 294  
 bandgap energy ( $E_g$ ) 14, 130  
 bathocuproine (BCP) 30, 234, 387  
 benzo-dithiophene 32  
 benzoquinone (BQ) 327  
 benzothiadiazole (BT) 32  
 bis-(2,2,4-trimethylpentyl)phosphinic acid (TMPPA) 329  
 black phase stabilization 249–282  
 blue PeLEDs 365  
 Boltzmann constant 131, 221, 385  
 broadband photodiodes 387–392  
 B-site doping 250, 253–256  
 bulk perovskite green PeLEDs 361–363  
 butanediamine iodide (BEAI<sub>2</sub>) 27  
 butyl ammonium ion (BA<sup>+</sup>) 311

### **c**

calcium titanate ( $CaTiO_3$ ) 5  
 capacitance, defect levels 186  
 carrier transport  
   diffusion coefficient and mobility 176–177

- carrier transport (*contd.*)
- galvanostatic transient method 177–179
  - impedance spectroscopy 179–181
  - luminescence, suppression 181–183
  - mixed ionic-electronic conduction 176–207
  - time constants 176–207
  - transport coefficients 176–177
- cesium lead bromide (CsPbBr<sub>3</sub>) 256–257
- cesium lead iodide (CsPbI<sub>3</sub>) 249
- additives approach 251–252
  - B-site doping 250–253
  - quantum dots (QDs) 252
  - surface treatments 253
- cesium lead mixed halide perovskites (CsPbI<sub>3-x</sub>Br<sub>x</sub>) 257–266
- chalcopyrites 437
- charge balance, PeLEDs 348–349
- charge carriers 384
- charge-discharge methods 203–206
- chemical capacitance 184
- commercialization 22, 35, 45, 447–449
- complementary metal-oxide-semiconductor (CMOS) detectors 413
- compton scattering 412
- conduction band (CB) 16, 159
- conduction band minimum (CBM) 13, 108
- contact potential difference (CPD) 97
- conventional X-ray detectors 415–416
- copper indium gallium diselenide (CIGS) 436–437
- Cs<sub>2</sub>AgBiBr<sub>6</sub> 120, 121, 140, 141, 271–275, 280
- CsPbBr<sub>3</sub> 258
- CsPbI<sub>3</sub> 250
- Cs<sub>2</sub>SnX<sub>6</sub> 269–270
- CsSnX<sub>3</sub> 267, 269
- Cs<sub>2</sub>TiBr<sub>6</sub> 38
- current density–voltage (J–V) curve 137–138
- current–voltage performance 216–218
- d**
- damp heat and humidity freeze tests 30
- dark current 386
- deep-level transient spectroscopy (DLTS) 148
- defect engineering 221–222
- defects passivation 266
- defect tolerance 14, 17, 43, 45, 233, 314, 349
- density functional theory (DFT) 13, 108, 141
- density of states (DOS) 111
- depletion capacitance 185–186
- depletion-layer capacitance 191
- detective quantum efficiency (DQE) 422–423
- diaminoethane (DAE) 35, 305, 309
- dielectric constant 225
- dielectric relaxation 184
- diffusion component 384
- digital radiography (DR) 415
- 1,8-diiodoctane (DIO) 222
- dimethylammonium iodine (DMAI) 252
- dimethyl formamide (DMF) 438
- dimethylsulfoxide (DMSO) 67
- diode ideality factor 150–152
- 4,7-diphenyl-1,10-phenanthroline 329
- 3,3-diphenylpropylamine bromide (DPPA-Br) 335
- direct perovskite X-ray detectors 416–420
- direct X-ray detectors 413, 421
- double cation perovskites 237
- drift component 384
- dye-sensitized solar cells (DSSCs) 8, 10, 81, 147, 237
- e**
- electro chemical energy 130
- electrochemical impedance spectroscopy (EIS) 146–148, 225
- electrode polarization 185
- electroluminescence 142, 346
- electron-backscatter diffraction (EBSD) 87

electron beam lithography 61  
 electron collection layer 299  
 electron-hole pair (EHP) 414  
 electron-hole pairs 434  
 electronic dimensionality 107  
 electron-injecting layer (EIL) 346  
 electron irradiation 43  
 electron transport layer (ETL)  
 136, 306  
 electron transport material (ETM)  
 15  
 electrostimulation, photon generation by  
 347–348  
 energy yield 447–448  
 equivalent circuits  
 interpretation of 194–197  
 parallel RC 175  
 erbium ytterbium silicate (EYS) 400  
 ethylammonium (EA) 23, 64  
 ethylammonium bromide (EABr) 367  
 ethylammonium ion (EA<sup>+</sup>) 311  
 ethylenediamine (EDA) 23, 252  
 ethylenediamine diiodide (EDAI)  
 305  
 ethylenediammonium diiodide (EDAI<sub>2</sub>)  
 35  
 ethylenediammonium iodide (EDAI)  
 25  
 external quantum efficiency (EQE) 37,  
 129, 346, 384

## **f**

F-doped tin oxide (FTO) 15  
 Fermi level ( $E_F$ ) 116  
 ferroelectric effect 217  
 ferroelectric photovoltaics 6  
 fluorescence resonance energy transfer  
 (FRET) 366  
 fluorine-doped tin oxide (FTO) 346  
 formamidinium (FA) 11, 215, 235, 249,  
 293  
 formamidinium (NH<sub>2</sub>CH=NH<sub>2</sub><sup>+</sup>) 63  
 formamidinium-based PSCs 191  
 formamidinium iodide (FAI) 445  
 forward scan (FS) direction 216

Frenkel defect 223, 225  
 full width at half maximum (FWHM)  
 322, 393

## **g**

galvanostatic transient method 177–179  
 GaAs 1, 13, 14, 20, 45, 107, 112, 155, 157,  
 233  
 Ge-based halide perovskites 116  
 Ge-doped Sn perovskites 307–308  
 generalized gradient approximation  
 (GGA) 109  
 ghosting 425–426  
 Goldschmidt tolerance factor 63  
 Gouy-Chapman diffuse double-layer  
 model 185  
 grain boundaries (GBs) 82, 85, 156–157  
 crystallographic texture 87–88  
 crystallographic texture effects 98–99  
 grain size and distribution 86–87  
 grain size effects 92, 95, 100  
 grain boundaries engineering 219–220  
 grain boundary passivation 309–314

## **h**

halide perovskite absorbers 18–20  
 halide perovskite photovoltaics 5–7, 11  
 halide perovskite quantum dots (HP-QDs)  
 hot electron extraction 327–328  
 hot injection method 322–324  
 ion exchange reactions 325–326  
 LED 334–338  
 ligand-assisted reprecipitation  
 322–323  
 multiple exciton generation 327  
 post-synthetic treatment 330–331  
 solar cells 337–340  
 surface coating 332–334  
 surface ligand engineering 329–331  
 surface passivation 329  
 synthesis 321  
 tunable bandgap 326–327  
 halide perovskite solar cells  
 efficiency and stability 20–21  
 external and environmental stability  
 24–33

- halide perovskite solar cells (*contd.*)
    - intrinsic stability 22–24
  - halide perovskite (HP) thin films 81
    - grain growth 89–92
    - microstructure, genesis of 88–89
  - Heyd-Scuseria-Ernzerhof (HSE) hybrid
    - functional 119
  - high dielectric constant 154
  - highest occupied molecular orbital (HOMO) level 16
  - high X-ray attenuation coefficient 414
  - hole-blocking layer (HBL) 387
  - hole-injecting layer (HIL) 346
  - hole transport layer (HTL) 306
  - hole transport materials (HTMs) 9, 15, 24, 31, 33, 43, 240
  - hole trapping system 179
  - hot electron extraction 327–328
  - hot injection method 322–324
  - hydroiodic acid 251
  - hysteretic effect 216
- i**
- ideality factor 150–152
  - ideal solar cell 129–132
  - ideal X-ray detectors 413–415
  - imaging lag 425
  - 2,2-iminodibenzoic acid (IDA) 331
  - impedance spectroscopy (IS) 175, 179, 181, 190
  - incident light power 384
  - incident photon to current efficiency (IPCE) 129, 397
  - indirect bandgap 140
  - indirect X-ray detectors 413, 414
  - indium tin oxide (ITO) 15, 346
  - indoor photovoltaic devices 41
  - inorganic metal oxides 7
  - in-phase component 147
  - intensity modulated photocurrent spectroscopy (IMPS) 200–203, 310
  - intensity-modulated photovoltage spectroscopy (IMVS) 148, 149
- interfacial engineering 220–221
  - internal quantum efficiency (IQE) 129
  - iodide/triiodide based liquid electrolyte 173
  - ion exchange reactions 325–326
  - ionic conductivity 177–179, 221
  - ionic diffusion 179–181
  - IoT applications 45, 448
  - iso-propylammonium (IPA) 367
  - isopropyl-ammonium bromide (IPABr) 367
- j**
- Johnson–Nyquist 385
  - J-V hysteresis 219
- k**
- Kelvin probe force microscopy (KPFM) 95, 187, 205
  - KI doping 223, 224
  - Kirchhoff's law of thermal radiation 133
  - Kramers–Kronig relationship 184
- l**
- Langmuir–Blodgett (LB) method 75
  - lanthanum 238
  - lateral photoconductors 397–400
  - layer-by-layer self-assembly method 74–75
  - lead-free perovskites 34–39
  - lead halide-based perovskite compounds 66–67
  - lead halide perovskites 2
  - leakage current 347
  - LED illumination 34, 35
  - levelized cost of electricity (LCOE) 433, 448
  - ligand-assisted reprecipitation (LARP) method 322, 323
  - light-emitting diode (LED) 334–337
  - light extraction 347, 358
  - light intensity 131
  - light management 369, 442
  - linear dynamic range (LDR) 385
  - long-term device stability 239

low bandgap solar cell 436  
 CIGS and CIS 437  
 silicon 436–437  
 Sn/Pb low bandgap perovskites  
 437–438  
 low-cost tandem solar cells 39, 42  
 low-frequency lattice phonons 154–155  
 low trap density 414  
 luminescence quenching 358

## **m**

magnesium-alloyed zinc oxide (MZO)  
 358  
 MAPbBr<sub>3</sub> single crystal 417  
 MAPbI<sub>3</sub> 416  
 AMFPI 418  
 FAPbI<sub>3</sub> 215  
 J-V curves for 220  
 market choice 448–449  
 MASbSI<sub>2</sub> 38  
 maximum power point (MPP) 131, 242  
 mesoporous TiO<sub>2</sub> electrodes 8  
 mesoporous titanium dioxide (mp-TiO<sub>2</sub>)  
 238  
 metal halide perovskites 6, 7, 173, 174,  
 176, 435  
 metal ion doping 360  
 metal organic chemical vapor deposition  
 (MOCVD) 61  
 metal-semiconductor-metal (MSM) 397  
 methyl acetate 337  
 methylammonium (MA) 2, 11, 18, 63,  
 84, 235, 249, 293, 295  
 methylammonium acetate (MAAc) 259  
 methylammonium cation 223  
 methylammonium free perovskites 240,  
 242  
 mitigating optical losses  
 current-matching vs. power-matching  
 447  
 parasitic absorption 442–444  
 reflection losses 443–445  
 textured substrates 445–446  
 mixed hybrid perovskites (MHP) 174  
 capacitance of 186–190

equivalent circuits, interpretation  
 194–197  
 IS model 199–200  
 Mott-Schottky analysis 191  
 negative capacitance 197–198  
 surface charging in 205  
 trap density, measurement 192–193  
 mixed ionic-electronic conduction 176,  
 207  
 mobile ions 159–160  
 modulation transfer function (MTF)  
 423, 424  
 molecular beam epitaxy (MBE) 61  
 monolithic tandem 439  
 Mott-Schottky analysis 148, 186, 191  
 Mott-Schottky plot 185  
 multidimension multicomposition  
 (MDMC) 28  
 multiple exciton generation (MEG)  
 327  
 multiple quantum wells (MQW) 357

## **n**

nanocrystal-based perovskite green  
 PeLEDs 362–364  
 nanocrystalline silicon junction 439–440  
 nanoplatelets (NPLs) 364  
 1-naphthylmethylamine cations (NMA<sup>+</sup>)  
 358  
 narrowband photodiodes 392  
 near-infrared PeLEDs 356–359  
 Nernst–Einstein relation 221  
*N*-methyl-2-pyrrolidone (NMP) 67  
*N,N*-dimethylformamide (DMF) 66  
*n*-octylamine (OAm) 322, 329  
 noise equivalent power (NEP) 385  
 non-radiative losses 349  
 non-radiative recombination 135, 137,  
 347, 359

## **o**

octadecene (ODE) 322  
 oleic acid (OA) 322  
 oleylamine 329  
 oleylammonium iodide (OAM-I) 337

- open-circuit voltage (Voc) 14, 16, 100, 108, 117, 131, 257, 295, 439
  - open circuit voltage decay (OCVD) 203
  - optical losses 442–447
  - optical outcoupling 358
  - organic-inorganic hybrid ligand (OIHL) 335
  - organic-inorganic metal halide perovskites 61–62
  - organic photovoltaics (OPVs) 81
  - organic solar cells (OSCs) 153
  - organo-lead halide perovskites 11–15
  - organo-metal halide perovskite 13
  - organometallic Grignard reagents 325
  - Ostwald ripening process 90
  - out-of-phase components 147
- P**
- parallel RC equivalent circuit 175
  - parasitic absorption losses 442–444
  - partial density of states (PDOS) 114
  - passivation effect of excess KI 225–226
  - passivation techniques 233, 237
  - Pb-based halide perovskites 108–109
    - ideal grain boundaries 111–112
    - ideal surfaces 113
    - point defects 108–112
    - surfaces and boundaries 114
  - Pb-free Sn perovskite solar cells 304, 307
    - efficiency enhancement 309–314
    - Ge-doped Sn perovskites 307–308
  - Pb-halide perovskite solar cells 293
  - PbI<sub>2</sub> passivation 299
  - PEDOT-PSS/Sn-perovskite interface 311
  - pentafluorophen-oxethylammonium iodide 306
  - PERC-type cells 436
  - perovskite crystal intrinsic properties 153
    - defect tolerance 153–154
    - fast radiative recombination 153
    - high dielectric constant 154
    - low-frequency lattice phonons 154–155
    - reduced recombination 155–156
    - relatively high absorption 153
    - shallow defects 153–154
  - perovskite-filled-membrane (PFM) 419
  - perovskite LEDs (PeLEDs)
    - blue 365
    - bulk perovskite green 361–363
    - charge balance 348–349
    - nanocrystal-based perovskite green 364
    - near-infrared 356–359
    - non-radiative losses 349
  - operation 346
  - photon generation by
    - electrostimulation 347–348
  - photon recycling 350
  - quasi 2D/3D perovskite green 363–364
  - red 359–361
  - perovskite-polymer bulk heterostructure (PPBH) 358
  - perovskites
    - 2D/3D 25, 26
    - photovoltaics 15–18
    - poly(ethylene oxide) (PEO) 361
    - silicon tandem development 443
  - perovskite solar cell (PSC) 1, 3, 62, 147
    - applications of 42–44
    - in characteristics 177
    - low-cost tandem 39–42
    - single junction solar cells 173
  - perovskite-type metal halide compounds 62, 65
  - perovskite X-ray scintillators 419, 432
  - phase shift 147
  - phenylethylamine iodide (PEAI) 25
  - phenylethylammonium iodide (PEAI) 252
  - phenylhydrazine hydrochloride 306
  - phenyltrimethylammonium bromide (PTABr) 253
  - photoconductors 394, 395
    - lateral 397–400
    - vertical 396–397

- photocurrent 384  
 photodetectors 4, 383, 386, 394  
 photodiodes 386  
   broadband 387–392  
   narrowband 392–394  
 photoelectric effect 412  
 photoemission spectroscopy 348  
 photoluminescence (PL) 4, 29, 95, 142, 144, 227–229, 303, 322  
 photoluminescence quantum efficiency (PLQE) 225, 226  
 photomultiplier tubes (PMTs) 413  
 photon recycling 350  
 photo-to-electron conversion efficiency 416  
 phototransistors 400–402  
 photovoltage, time transients of 203–204  
 photovoltaic external quantum efficiency 200  
 photovoltaic (PV) technologies 81  
 phthalocyanine (Pc) derivatives 32  
 p-i-n perovskite LEDs 346  
 pixel-to-pixel uniformity 424  
 planar inverted (p-i-n) structure 233  
 planar perovskite solar cells 187  
 point defect 223  
 poly(9-vinylcarbazole) (PVK) 364  
 poly[bis(4-phenyl)(2,4,6-trimethylphenyl)amine] (PTAA) 234  
 polycrystalline MAPbI<sub>3</sub> 84–86, 95  
 polydimethylsiloxane (PDMS) 443  
 polyelemental multicomponent engineering 235  
   double cation perovskites 237–238  
   methylammonium free perovskites 240–242  
   quadruple cation perovskites 239–240  
   single cation perovskites 236–237  
   triple cation perovskites 238  
 polyethyleneimine (PEI) 356  
 polyethylenimine ethoxylated (PEIE) 358  
 polymethyl methacrylate (PMMA) 387  
 polyvinylpyridine (PVP) 29  
 polyvinyl pyrrolidone (PVP) 252, 332  
 post-synthetic treatment 330, 331  
 potassium ion 226, 227  
 power conversion efficiency (PCE) 1, 4, 127, 129, 215, 294, 295, 337, 383  
 propylenediammonium iodide 311  
 proton irradiation 43
- q**
- quadruple cation perovskites 239  
 quantum-confinement effects 61, 64  
 quantum-dot in perovskite (QDiP) 391  
 quantum dots 252–253  
 quantum yield (QY) 322  
 quartz crystal microbalance (QCM) 298  
 quartz crystal oscillator 74  
 quasi 2D/3D perovskite green PeLEDs 363–364  
 quasi-Fermi level (QFL) 130
- r**
- radiative limit 132–135  
 Raman spectroscopy 29  
 Rayleigh scattering 412  
 RC time constant 384  
 recombination junction 438, 439  
   all-perovskite tandems 440  
   mitigating optical losses 442–447  
   nanocrystalline silicon junction 439–440  
   wide bandgap perovskite solar cell 440–442  
 recombination layer 435, 437, 440, 441  
 recombination resistance 195  
 red PeLEDs 359–360  
 reflection losses 443–445  
 resistive random access memory (ReRAM) 199  
 resonant infrared matrix assisted pulsed laser evaporation (RIR-MAPLE) 72  
 response time 384

- reverse scan (RS) direction 216
- roll-to-roll manufacturing of flexible modules 45
- roll-to-roll method 233
- Ruddlesden-Popper series 65, 69
- S**
- samarium iodide ( $\text{SmI}_2$ ) 308
- Sawyer-Tower circuit 205–206
- scanning electron microscope (SEM) 86
- Schottky barrier 185–186
- Schottky junction 416
- self-intercalation method 73
- self-organization 65, 75
- self-powered photodetector (SPPD) 389
- semiconductor impurities 156
- sequential hybrid deposition method 445
- Shockley–Queisser (SQ) limit 15, 129, 131, 132, 215, 234, 241, 293, 434
- Shockley–Read–Hall (SRH) 95, 108, 135, 347
- shunt resistance 385
- signal-to-noise ratio (SNR) 385
- silicon heterojunction (SHJ) 436
- silicon solar cells 436, 437
- silver halide 2
- single cation perovskites 236, 237
- single-junction cells 447
- single-walled carbon nanotubes (SWCNTs) 391, 399
- slot die coating 70, 233, 435
- Sn-based halide perovskites 115
- $\text{SnI}_2$  passivation 299
- Sn/Pb low bandgap perovskites 437–438
- Sn-Pb perovskite solar cells 293, 295
  - device architecture 298–303
  - efficiency enhancement 296–297
  - interfacial engineering 298–303
  - stabilization, Sn (II) ions 295–296
- Sn perovskites 17
  - conduction band minimum (CBM) 304
  - valence band maximum (VBM) of 304
- solar-cell materials 128
- solar cells, HP-QDs 337, 340
- solar irradiance 128
- solar simulator 137
- solid-state lighting 368
- space applications, PSCs 42–44
- space charge limited currents (SCLC) 152
- space irradiation 42
- spin-coating, materials 299
- spin-coating method 67, 70
- spin-orbital coupling (SOC) 109
- spiro-OMeTAD layer 31
- sputter buffer layer 443
- standard reporting conditions (STC) 131
- Stokes shift 68, 140
- subcells 435
- subgap states 133
- Sulfobetaine Zwitter ion 252
- surface coating, HP-QDs 332–334
- surface ligand engineering 329–331
- surface recombination 136
- t**
- tandem solar cells 435, 448–449
- Tauc plot 139
- thermal admittance spectroscopy (TAS) 186
- thermally stimulated currents (TSC) 299
- thin-film phototransistor (TFT) arrays 413
- time-correlated single photon counting (TCSPC) technique 144
- time dependent carrier distribution 205
- time-resolved photoluminescence (TRPL) 222–225
- time-resolved terahertz spectroscopy 327
- tolerance factor 5, 18, 20, 22, 23, 63, 236, 238, 249, 265
- total density of states (TDOS) 114
- transfer matrix formalism 449
- transient absorption (TA) spectroscopy 327
- transient photoluminescence 144, 146



- transient photovoltage decay (TPV) 148, 149
  - transition metal dichalcogenides (TMDs) 402
  - trap, bandgap 135
  - trap charge limited current (TCLC) 152
  - trap density, measurement 192
  - trap-filled limit (TFL) voltage 225
  - trifluoroethylamine (FEA) chain 25
  - trimethylaluminum (TMA) 359
  - trimethylenediammonium iodide 311
  - trioctylphosphine (TOP) 331
  - trioctylphosphine oxide (TOPO) 142, 363
  - triple-cation perovskite 18, 238
  - 2T tandems, subcells in 435
  - tunable bandgap 326–327
  - two-step deposition method 72–73
- U**
- Urbach tail 133, 141
- V**
- vacuum evaporation method 70–72
  - valence band (VB) 13, 159
  - valence band maximum (VBM) 13, 108
  - van der Waals interactions 63
  - vertical photoconductors 396–397
  - Voigt element 147
  - voltage deficit 132, 138–142
  - voltage loss 14
- W**
- wide bandgap perovskite solar cell 440–442
- X**
- XPS analysis 182
  - X-ray attenuation power 417
  - X-ray detection 411
  - X-ray detectors 425
    - conventional 415–416
    - direct perovskite 416–420
    - DQE 422–423
    - ghosting 425–426
    - ideal 413–415
    - MTF 423–424
    - perovskite scintillators 419, 432
    - pixel to pixel uniformity 424
    - sensitivity 422
    - working mechanism of 412–413
  - X-ray diffraction (XRD) 68, 88
  - x-ray exposure 425
  - X-ray imaging 412, 417
  - x-ray photoelectron spectroscopy (XPS) 239
  - X-ray scintillators 422





