

Index

a

- aero-engine core engines 29
- α -Al₂O₃ 15
- alumina matrix oxide/oxide composites 15

b

- BN interphase oxidation 8

c

- ceramic-matrix composites (CMCs)
 - aero-engine core engines 29
 - BN interphase 21
 - characteristics of 29
 - combustion chamber and high-pressure turbine components 161
 - cross-ply CMCs 122–124
 - cross-ply C/SiC composite 131–135, 144–155
 - C/SiC and SiC/SiC composites 193–195
 - cyclic loading/unloading/fatigue hysteresis behavior of 110
 - at elevated temperature in air atmosphere
 - 1000°C 172–175
 - 1200°C 175–178
 - 1300°C 178–184
 - at elevated temperature in inert atmosphere 167–172
 - at elevated temperature in steam atmosphere
 - 1000°C 185–187
 - 1200°C 187–191

- experimental investigations
 - fatigue hysteresis-based damage parameters 46–51
 - first matrix cracking stress 42–43
 - matrix cracking density 43–46
- fiber/matrix interface shear stress 30, 110, 111
- fiber-reinforced CMCs 29
- first matrix cracking stress 31
- fracture modes of monolithic ceramics 1
- high quality and high temperature properties 29
- hysteresis theories 112–118
- interface damage law
 - at room temperature 163–167
- interface effects
 - sliding resistance 19
 - thermal misfit stress 19
- interface properties, effects of
 - fatigue hysteresis-based damage parameters 32–33, 39–41
 - first matrix cracking stress 31, 33–36
 - matrix cracking density 31–32, 36–38
 - theoretical analysis 31–33
- life prediction model
 - at elevated temperature 89–100
 - at elevated temperatures in oxidative environment 77–79
 - experimental investigations 79–89
 - at room temperature 74–77, 79–89

ceramic-matrix composites (CMCs)
(*contd.*)

- theoretical analysis 73–79
- matrix cracking density 32
- monolithic ceramic and
 - fiber-reinforced 1, 2
- non-oxide CMCs 3–13
- oxide/oxide composites
 - α - Al_2O_3 15
 - Al_2O_3 and Al_2O_3 - SiO_2 ceramic fibers 14
 - environmental stability 13–17
 - fracture behavior of 15
 - fugitive coating 16
 - LaPO_4 15
 - matrix materials 15
 - PIP 8HSW Nextel 720/alumina composite 16
 - properties of 14
 - 2D Nextel 610/ Al_2O_3 - SiO_2 composite 16
 - 2D Nextel 720TM/alumina composite 17
- PyC interphase 20–21
- research and application of 29
- shape, location and area of hysteresis loops 162
- stress-strain hysteresis loop 109
- temperature, oxidation, and fiber preforms 192–193
- tensile damage and fracture process
 - experimental investigations 66–71
 - fiber failure, interface and fiber oxidation 58–59
 - fiber strength, effect of 64–65, 67
 - fiber Weibull modulus, effect of 65–66
 - interface debonding 57, 58
 - interface shear stress, effects of 62–64
 - matrix multicracking 56–57
 - pre-exposure temperature 60–61
 - pre-exposure time, effects of 61–62
 - stress analysis 54–56
 - tensile stress-strain curves 59–60

- theoretical analysis 52–60
- 2.5D C/SiC composite 135–138, 149–155
- 2D CMCs 124–127
- unidirectional CMCs 118–123
- unidirectional C/SiC composite 129–131, 138, 140–142
- unidirectional SiC/CAS and SiC/SiC composites 30
- unidirectional SiC/CAS composite 142–144
- unidirectional SiC/CAS-II composite 144, 145
- cooling methods 1
- cross-ply ceramic composite 131
- cross-ply C/SiC composite 131, 133–136
- CVI Hi-Nicalon SiC/SiC composite 11

e

- Embrittled fibers 8
- energy-dissipating mechanism 110
- Evans–Zok–McMeeking model 80, 84, 89, 93, 96, 100
- experimental fatigue hysteresis
 - dissipated energy 174, 179

f

- fatigue hysteresis behavior 129
- fatigue hysteresis dissipated energy 139, 140
 - versus* cycle number curves 168
 - of cross-ply SiC/CAS composite 167
 - of 2D SiC/SiC composite 171, 173, 175
 - of unidirectional SiC/CAS composite 165
- fatigue hysteresis loops 119, 121, 123, 125, 129, 131–134, 136, 137
- fatigue stress ratio 11, 122, 142, 149, 151
- Fatigue tests 11, 13, 16, 17, 172, 175, 178, 180, 185, 187
- fiber axial stress distribution 113–118

fiber/matrix interface shear stress
29–31, 42, 54, 110, 127, 161, 162
fiber-reinforced CMCs 1, 2, 21, 29–31,
51, 59, 71, 79, 100, 112, 155
fiber Weibull modulus 31, 59, 60, 65,
66, 68
F414 turbofan 161

g

gas turbine efficiency 1
GENx aero engine 161
Global Load Sharing criterion 58

h

Hutchinson–Jensen fiber pull-out model
110
hysteresis dissipated energy
vs. interface shear stress diagram
164

i

infrared pyrometers 118
interface shear stress 84
vs. cycle number curve 165, 167,
171–173, 175
interface slip mechanism 110
interface wear process 111, 161

l

LaPO₄ 15

m

matrix cracking density 31–32,
36–39, 43–46, 57, 100, 103
matrix Weibull modulus 57
micromechanics approach 30, 72, 100
MI Hi-Nicalon SiC/SiC composite 4,
7, 11, 12
Mullite (3Al₂O₃·2SiO₂) 15

n

Nextel 312 14
Nextel 610 14–16
Nextel 610/Al₂O₃ composite 15, 16
Nextel 550 fiber 14
Non-oxide CMCs 2–13, 21

o

oxidation embrittlement 3, 13

p

PIP 8HSW Nextel 720/alumina
composite 16
PIP SiC/SiC composite 11, 12
prepreg-MI SiC/SiC composites 4, 6
Pryce–Smith model 110
PyC interphase resion 162
PyC interphase 9–11, 19–22, 93, 96,
100, 103, 111, 162

s

sapphire/LaPO₄/alumina composite
system 15
shear-lag model 54, 56, 114
SiC/PyC/borosilicate glass composite
19
SiC/SiC composites
with BN interphase at room
temperature 6
degradation behavior of 13
with different fiber preforms 7
oxidation heat-treatment of 8
radial stress 9
stress-strain hysteresis loops 9, 100,
110, 112, 118, 120, 123, 125

t

theoretical fatigue hysteresis dissipated
energy
vs. interface shear stress curve of 2D
SiC/SiC composite 174, 179
thermal misfit stress 19
thermal residual stress (TRS) 19, 57
3D C/SiC composite 66, 67, 76, 89, 92,
100, 102, 110
3D tyranno SiC/[Si-Ti-C-O] composite
11
2D C/SiC composite 68, 80, 84, 93, 96,
109–112, 155, 162, 193, 195
2D CVI Nicalon SiC/SiC composite 9,
10

- 2D CVI SiC/SiC composite
 - oxidation of fatigue behavior of 11
 - tensile and fatigue behaviour 10
 - 2D CVI Sylramic-iBN/BN/SiC composite 12, 13
 - 2D Hi-Nicalon SiC/SiC composite 4, 7, 11, 12, 42, 49, 54
 - 2D MI Sylramic-iBN/BN/SiC composite 12, 13
 - 2D Nextel 610/ Al_2O_3 - SiO_2 composite 16
 - 2D Nextel 720-alumina composite 17
 - 2D SiC/SiC composite 167, 187
 - fatigue hysteresis loops area of 109
 - 2D Sylramic-SiC/SiC composite 46
 - 2D Tyranno-SiC/SiC composite 46, 50
 - 2.5D C/SiC composite 89, 96
 - two-parameter Weibull distribution 56, 72
 - two-parameter Weibull model 73
- u**
- unidirectional C/SiC composite 60, 70, 79–81, 129, 131, 138–142, 155
 - unidirectional SiC/CAS-II composite 118, 119, 121, 123, 144, 145, 162
- v**
- Vagaggini's hysteresis loops models 111, 162
 - Vagaggini's unidirectional hysteresis loops models 110