

Contents

Preface *ix*

Acronyms *xiii*

| | | |
|----------|---|-----------|
| 1 | Introduction to Additive Manufacturing | 1 |
| 1.1 | Evolution of Manufacturing | 1 |
| 1.2 | Concept of AM | 3 |
| 1.3 | Advantages over Conventional Manufacturing Techniques | 6 |
| 1.4 | Laser-Based AM | 7 |
| 1.4.1 | Laser-Based Directed Energy Deposition | 7 |
| 1.4.1.1 | Machine Design | 9 |
| 1.4.1.2 | Process Parameters | 9 |
| 1.4.2 | Laser Powder Bed Fusion | 10 |
| 1.4.2.1 | Process Parameters | 11 |
| 1.4.3 | Estimation of Energy Input in LAM Processes | 13 |
| 1.4.4 | Multi-Step LAM Techniques | 15 |
| | References | 16 |
| 2 | Multiscale Computational Approaches to LAM | 19 |
| 2.1 | Computational Science | 19 |
| 2.1.1 | Computational Material Science | 20 |
| 2.2 | Multiscale Modeling | 21 |
| 2.2.1 | Nano-Micro-Scale Modeling | 21 |
| 2.2.1.1 | Molecular Dynamics and Density Functional Theory | 21 |
| 2.2.1.2 | Monte Carlo Method | 22 |
| 2.2.2 | Meso-Macro Scale Modeling | 23 |
| 2.2.2.1 | Kinetic Monte Carlo Method | 24 |
| 2.2.2.2 | Cellular Automata | 25 |
| 2.2.2.3 | Phase-Field Method | 29 |
| 2.2.2.4 | Finite Element Method | 30 |
| 2.3 | Integrated Computational Materials Engineering (ICME) | 33 |
| | References | 34 |

| | | |
|----------|---|------------|
| 3 | Laser Matter Interaction in LAM | 37 |
| 3.1 | Introduction | 37 |
| 3.1.1 | Physical Phenomena in LAM | 38 |
| 3.2 | Components of Mathematical Models in Metal AM | 40 |
| 3.3 | Feedstock | 40 |
| 3.3.1 | Powder Bed Morphology in LPBF | 40 |
| 3.3.1.1 | Discrete Element Method | 41 |
| 3.3.1.2 | Powder Spreading Mechanism | 44 |
| 3.3.2 | Powder Stream Generation in LDED | 48 |
| 3.3.2.1 | Turbulent Gas Flow and Discrete Phase Model | 49 |
| 3.3.2.2 | Powder Stream Characteristics | 52 |
| 3.3.3 | Laser-Feedstock Interaction | 54 |
| 3.4 | Thermo-Fluidic Model in LAM | 60 |
| 3.4.1 | Laser Heat Source | 61 |
| 3.4.2 | Radiative and Convective Cooling | 61 |
| 3.4.3 | Recoil Pressure and Evaporative Cooling | 61 |
| 3.4.4 | Surface Tension | 62 |
| 3.4.5 | Free Surface Tracking Methods | 63 |
| 3.5 | Melt Hydrodynamics in LPBF | 65 |
| 3.5.1 | Thermo-Fluidic Anatomy of a Single Track | 65 |
| 3.5.2 | Conduction Mode LPBF | 68 |
| 3.5.3 | Keyhole Mode LPBF | 68 |
| 3.5.4 | Energy Coupling Mechanism | 71 |
| 3.6 | Melt Hydrodynamics in LDED | 74 |
| 3.7 | Multi-Layer, Multi-Track Approach | 79 |
| 3.8 | Computational Cost | 82 |
| 3.9 | Computationally Efficient Approach | 83 |
| 3.10 | Guidelines for Experimental Validation | 89 |
| | References | 89 |
| 4 | Thermokinetics, Microstructural Evolution, and Material Response | 101 |
| 4.1 | Thermokinetics in LAM | 101 |
| 4.2 | Solidification | 104 |
| 4.2.1 | Nucleation | 104 |
| 4.2.1.1 | Heterogeneous Nucleation Assisted by Inoculants | 104 |
| 4.2.1.2 | Homogeneous Nucleation | 107 |
| 4.2.1.3 | Nucleation Influenced by Acoustic Cavitation | 110 |
| 4.2.2 | Solidification Variables | 115 |
| 4.2.2.1 | Thermal Gradient | 115 |
| 4.2.2.2 | Solidification Rate | 116 |
| 4.2.3 | Growth and Orientation | 116 |
| 4.2.4 | Solidification Modes | 121 |
| 4.2.5 | Spatial Variation of Thermokinetic Parameters | 124 |
| 4.2.5.1 | Dependence on the Curvature of the Trailing Boundary | 126 |

| | | |
|----------|--|------------|
| 4.2.5.2 | Solidification Rate and Thermal Gradient | 128 |
| 4.2.5.3 | Morphology Factor and Cooling Rate Variation | 128 |
| 4.2.5.4 | Columnar-to-Equiaxed Transition | 131 |
| 4.3 | Thermal Cycles in LAM Processes | 134 |
| 4.3.1 | Thermal Cycles in LPBF | 134 |
| 4.3.1.1 | Thermal Cycles During Layer Fabrication | 137 |
| 4.3.1.2 | Thermal Cycles During Fabrication of Multiple Layers | 138 |
| 4.3.2 | Thermal Cycles in LDED | 139 |
| 4.3.2.1 | Thermal Cycles During the Deposition of a Layer | 141 |
| 4.3.2.2 | Thermal Cycles During Fabrication of Multiple Layers | 141 |
| 4.4 | Phase Transformations in LAM | 142 |
| 4.4.1 | Thermal Cycle-Driven Phase Evolution | 143 |
| 4.4.2 | Process-Driven Phase Transformations | 148 |
| 4.4.2.1 | Isothermal Effect | 148 |
| 4.4.2.2 | Process Parameters | 149 |
| 4.5 | Effect of Process Parameters | 151 |
| 4.5.1 | Laser Beam Attributes | 151 |
| 4.5.1.1 | Laser Beam Diameter | 153 |
| 4.5.1.2 | Laser Power | 154 |
| 4.5.1.3 | Laser Speed | 156 |
| 4.5.2 | Laser Process Attributes | 161 |
| 4.5.2.1 | Scanning Strategy | 161 |
| 4.5.2.2 | Preheating the Substrate | 164 |
| 4.5.2.3 | Build Orientation | 166 |
| 4.5.2.4 | Interlayer Duration | 167 |
| 4.5.2.5 | Feed Rate | 169 |
| 4.6 | Effect of Melting Modes | 170 |
| 4.7 | Laser Operation Modes | 173 |
| 4.8 | Material Response | 178 |
| 4.8.1 | Mechanical Response | 179 |
| 4.8.1.1 | Elastic Modulus | 192 |
| 4.8.1.2 | Fatigue | 193 |
| 4.8.1.3 | Creep | 194 |
| 4.8.1.4 | Wear | 195 |
| 4.8.2 | Electrochemical Response | 196 |
| | References | 200 |
| 5 | Residual Stress in LAM | 223 |
| 5.1 | Introduction | 223 |
| 5.2 | Thermo-Mechanical Model: Mathematical Framework | 225 |
| 5.2.1 | Elasto-Plastic Mechanical Model | 226 |
| 5.2.2 | Stress-Strain Behavior | 227 |
| 5.2.2.1 | Elastic Region | 227 |
| 5.2.2.2 | Yield Stress | 227 |
| 5.2.2.3 | Plastic Region | 227 |

| | | |
|----------|--|------------|
| 5.2.2.4 | Bauschinger Effect and Kinematic Hardening | 228 |
| 5.2.3 | Basic Elements of Elastic-Plastic Theory | 229 |
| 5.2.3.1 | Stress | 229 |
| 5.2.3.2 | Strain | 230 |
| 5.2.3.3 | Equation of Motion | 231 |
| 5.2.3.4 | Criterion for Initial Yielding | 231 |
| 5.2.3.5 | Flow Rule | 231 |
| 5.2.3.6 | Isotropic Strain Hardening | 232 |
| 5.2.3.7 | Viscoplasticity and Thermal Softening | 232 |
| 5.2.3.8 | Kinematic Hardening | 232 |
| 5.2.3.9 | Consistency Condition | 233 |
| 5.2.3.10 | Elastic-Plastic Stress-Strain Relation | 233 |
| 5.3 | Thermal Elastic-Plastic Formulation | 234 |
| 5.3.1 | Macro-Scale Approaches | 237 |
| 5.4 | Evolution of Residual Stress in LAM | 237 |
| 5.4.1 | Thermo-Mechanical Anatomy of a Single Track | 238 |
| 5.4.2 | Thermo-Mechanical Anatomy of a Single Layer | 241 |
| 5.4.3 | Stress Evolution at Component Scale | 241 |
| 5.4.4 | Experimental Validation of Residual Stress | 242 |
| 5.4.5 | Integrated Experimental and Numerical Approach for the Mitigation of Residual Stress | 246 |
| 5.4.5.1 | Role of the Scanning Strategy | 246 |
| 5.4.5.2 | Role of Preheating | 250 |
| 5.4.5.3 | Real-Time Control and Miscellaneous Approaches | 251 |
| | References | 253 |
| 6 | Surface Roughness in LAM | 261 |
| 6.1 | Introduction | 261 |
| 6.2 | Surface Roughness Characteristics in LAM | 262 |
| 6.3 | Surface Defects in LAM | 265 |
| 6.4 | Post-LAM Surface Finishing | 269 |
| | References | 272 |
| | Index | 277 |