

Index

a

absorbance loss 74
 absorber–metal interface 35, 108
 absorption loss 25, 55
 aerogels 14, 72, 101, 103, 132, 152–156,
 159, 165
 air–absorber interface 35, 108
 ALARA (as low as reasonably achievable)
 principle 5
 ambipolar electric field effect 69–70
 angular frequency 27, 36, 39, 41
 apertured TEM cell 60
 aramid nanofibers (ANFs) 141–142
 armchair (AC) 191
 ASTM D4935 method 57–58
 ASTM ES7-83 method 56–57
 attenuation constant 26–27, 33–34, 107,
 112, 115, 182

b

B,N-codoped reduced graphene oxide
 (B-N-MRG) 96–98
 backscattering coefficient 65
 black phosphorus (BP) 127, 177, 191,
 204
 boron-doped reduced graphene oxide
 (B-MRG) 96–97
 buckled melamine formaldehyde (BMF)
 foam 151

c

carbon black (CB) 11, 71, 89
 carbon nanofiber–graphene–carbon
 nanofiber (CNF–GN–CNF)
 heterojunction 104–107
 carbon nanotubes (CNTs) 11, 71,
 100–103, 145–147, 154, 162, 180
 Celgard membrane 137–138
 CENELEC 8–9
 cetyltrimethylammonium bromide
 (CTAB) 115, 193
 coaxial TEM cell methods 50, 55–60
 coaxial transmission line method 50
 conductive polymer nanocomposites 11
 copper monosulfide (CuS) 191
 copper sulfide (CuS) 191–194
 cut-off frequency 57–58, 60
 cutoff wavelength 36–37, 41–42

d

data security, EMI 5–6
 degrees of delamination 160
 dielectric losses 31
 dielectric relaxation loss 32
 ohmic (or conduction) loss 32
 polarization/resonance loss 32
 dielectric materials 43, 125, 159
 dielectric relaxation loss 31–32, 184
 dimethyl sulfoxide (DMSO) 93, 128, 149

- dip-coating cycles 141, 148
 - dipolar polarization mechanism 138
 - dual mode-stirred chamber 63–64
 - dual TEM cell method 59
- e**
- eddy current loss 32–33, 35, 108, 180
 - electric dipole polarization 111, 113
 - electric polarization 159–160
 - electrical conductivity 27, 71
 - EMI shielding mechanism 151
 - shielding effectiveness 30–31
 - electromagnetic compatibility (EMC)
 - European standards 9
 - FCC standards (USA) 9
 - International standards 8
 - Korean standards 9–10
 - military or defense standards 8, 10
 - electromagnetic field sources
 - artificial sources 3–4
 - human health effects 4–5
 - natural sources 3
 - electromagnetic hypersensitivity (EHS) 4
 - electromagnetic interference (EMI) 1
 - advanced 2D nanomaterials 12
 - conventional shielding materials 12
 - data security 5–6
 - electrical conductivity 151
 - shielding
 - economic aspects 6, 7
 - global market 6, 7
 - materials 6, 7, 10–14
 - mechanisms 25–26
 - electromagnetic pulses (EMPs) 62
 - electromagnetic radiation emitters 4
 - electromagnetic spectrum 2
 - frequency and wavelength ranges in 3
 - electromagnetic waves (EMWs) 1
 - absorption of 132, 203
 - shielding material 1
 - thickness 2
 - electromagnetic wave absorbers (EMWAs) 35, 108, 149
 - electrophoretic deposition (EPD) 75
 - electrospinning technique 105
 - ethylene glycol (EG) 109
 - European Standard Committee (ESC) 9–10
- f**
- FCNTs 100–101
 - ferrites 11, 35, 87, 108, 165
 - ferromagnetic materials 11
 - few-layer black phosphorus (FL-BP) 191
 - field cooling (FC) measurements 113
 - fifth generation (5G) technology 1, 14, 139
 - free space measurement method 64, 65
 - free space method 52–53, 64–66
 - free space reflection measurement method 64–66
- g**
- graphene 71, 203
 - bonding (π) and antibonding (π^*) bands of 69
 - 2D architecture of 71
 - as microwave absorber 105–116
 - graphene hybrids
 - with other carbon materials 100–105
 - graphene nanoplatelet–carbon nanotube (GCNT) 100–101
 - graphene nanosheets (GNs) 84–86, 104–105
 - graphene–polymer composites 72, 85–94
- h**
- heteroatom-doped graphene 94–100
 - hexagonal boron nitride (h-BN) 11, 177, 189–191, 204
 - high-power electromagnetics (HPEM) 61
- i**
- IEEE-STD-299 standard 61, 64, 65
 - impedance matching 34, 88, 91, 98, 107, 113, 116, 159, 163, 180, 186, 187, 191, 194, 196
 - internet of things (IoT) 1, 2, 6

- iodine-doped LG (I-LG) 98
ionizing radiation 3
- k**
- Korean EMC standards 8–9
- l**
- large graphene oxide (LGO) 81–82, 98
layer-by-layer (LbL) assembly 72, 80,
132, 146–149, 152, 189
lenthionine 96
lightweight shielding materials 29, 147
liquid-phase exfoliation (LPE) 191
- m**
- magnetic hysteresis loss 32, 33, 146
magnetic losses 32
Eddy current loss 32–33
magnetic hysteresis loss 33
magnetic nanoparticles 84, 87, 98, 163
magnetic permeability 2, 11, 27, 32–34,
46, 107, 160, 163
magnetic permittivity 27
matching frequency (f_m) 34, 108, 109
material under test (MUT) 35, 38, 42–46,
50, 55, 58, 66
Maxwell–Wagner polarization 159
medium graphene oxide (MGO) 98
metal–organic frameworks (MOFs) 177,
194–196, 204
methyl orange dyes 130
methylene blue 130
microwave absorption (MWA) 33–35,
72, 88, 92, 109, 113, 157, 158,
160–165, 177, 180, 182, 191–197
mechanisms 33–35, 164
microwave-absorbing materials
(MWAMs) 157, 158
MIL-G-83528 49, 61–63
MIL-STD-285 standard 61, 62
minimal intensive layer delamination
(MILD) method 4, 79, 127, 128,
132, 139, 156
molybdenum disulfide (MoS_2) 177–184,
187, 189, 197
- multiwalled carbon nanotubes
(MWNTs/MWCNTs) 100
MWCNT/TAGA 103
synergistic combination of 180–182
MXene-based aerogels with CNT
inclusions (MXCNTs) 154
MXenes
aerogels 153, 154
as microwave absorbers 157–165
fiber-reinforced composites of
140–144
for shielding effectiveness 131–132
hybrids with other nanomaterials
144–146
laminated films 132–140
layer-by-layer (LbL) assembly in
146–149
polymeric composites of 140–144
porous structures of 149–156
segregated structures of 156–157
synthesis of 128–129
- n**
- nanocomposite films 137, 143, 144, 148
natural rubber (NR) 156, 157
Nicolson-Ross-Weir (NRW) method
38–43
NIST iterative method 25, 40–42
nitrogen-doped graphene (NG) 109–113
nitrogen-doped reduced graphene oxide
(N-MRG) 94, 96
nonconducting polymers 141, 144
noniterative method 41–43
- o**
- ohmic (or conduction) loss 32
open field method 52–53
open-ended coaxial probe method 50–51
oxidative polymerization 162, 163
- p**
- plane-wave theory 27, 74
polarization/resonance loss 32
polyacrylonitrile (PAN) 105–106

- polyaniline (PANI) 103, 104, 142, 143, 162, 163
 polydimethylsiloxane (PDMS) 101, 102, 141, 151, 154, 156
 polyetherimide (PEI) films 75–77
 polyethylene terephthalate (PET) film 73, 77, 78, 148, 149
 polymer/graphene composite (PGC) 87, 91
 polyurethane (PU) 91, 92, 100, 101, 156, 180
 polyurethane/graphene (PUG) foam 91, 92
 polyvinyl alcohol (PVA) 117, 146, 147, 152
 polyvinylpyrrolidone (PVP) 115
 pristine graphene (PG) films 75, 79, 82–85, 87, 88, 100, 117
- r**
- rectangular split transmission line holder 59
 rectangular waveguide method 49, 60–61
 reduced graphene oxide (RGO) 75–77, 81, 82, 86, 88–90, 95–98, 100, 101, 113–117, 150–152, 159, 178
 reflection coefficient 26, 31, 33, 37, 38, 40, 42, 43, 45, 46, 50, 53, 54, 65, 107, 161, 162
 reflection loss (RL) 33, 55, 74, 107, 114, 115, 158–161, 165, 182
 reverberating chamber 60
 rotating hollow tube (RHT) 83
 Ruderman–Kittel–Kasuya–Yosida (RKKY) mechanism 113
- S**
- scanning centrifugal casting (SCC) method 82–84
 sheet resistance 31, 73, 134
 shield
 mechanical stability of 188
 shielded box method 50–52
 shielding by absorption (SE_A) 28–31, 55, 77, 80–83, 85–88, 91–93, 95, 96, 99, 102, 103–105, 133–136, 138, 140, 153, 179–181, 185, 188, 190, 191
 shielding by reflection (SE_R) 28, 30, 31, 55, 80–83, 85–88, 91–93, 95, 96, 98, 99, 102–105, 133–136, 138, 140, 153, 179, 182, 185, 188, 190, 191
 shielding effectiveness (SE) 2, 26, 29
 CVD-grown graphene films with transparency 72–79
 dielectric losses 31–32
 electrical conductivity 30–31
 graphene–polymer composites 85–94
 heteroatom-doped graphene 94–100
 incident electromagnetic field 30
 laminate films 79–85
 magnetic losses 32–33
 measurements 49
 experimental scattering parameters 53–55
 systems and standards 53–55
 test standards 62
 MXenes for 131–157
 other carbon materials, graphene hybrids with 100–105
 sheet resistance 30–31
 shield distance from source 30
 shield thickness 31
 shielding room method 51–52
 short circuit line (SCL) method 25, 43–46
 Simon’s formula 29, 134, 135
 small graphene oxide (SGO) 81, 82, 98
 sodium alginate 131
 sodium dodecyl sulfate (SDS) 145
 solution-processable functionalized graphene (SPFG) 87
 solvothermal synthesis 163
 specific absorption rate (SAR) 4
 specific shielding effectiveness (SSE) 29, 84, 94, 105, 131, 133, 134, 147, 152–155, 165, 188

split TEM cell 59–60
sulfur-doped reduced graphene oxide
(SrGO) 94–96

t

tantalum disulfide (TaS_2) 14, 177,
187–189, 197
TEM-t cell method 58
tetrabutylammonium hydroxide
(TBAOH) 128
thermally annealed graphene aerogel
(TAGA) 103, 104
TMDCs 11, 14, 72, 177, 191, 204
transmission coefficient 26, 37, 38,
41–43, 53, 54
transmission electron microscopy (TEM)
49, 50, 55, 56, 59–60, 93, 105, 106,
132, 133, 135, 140, 157, 179–181,
184, 185, 188
transmission/reflection method 35–37

tungsten disulfide (WS_2) 177, 184–187
two-dimensional (2D) nanomaterials 11

v

vacuum-assisted filtration 132, 139, 141,
143, 148, 155, 156
vector network analyzer (VNA) 25, 38,
42, 51, 53, 54, 57, 59
probe 51

w

wireless fidelity (Wi-Fi) 1
wood-derived porous carbon (WPC) 155

y

Young's modulus 70, 82, 137, 152, 178

z

zero field cooling (ZFC) 113
zigzag (ZZ) 191, 192

