

Index

a

acetylated microfibrillated cellulose 39,
41
acrylonitrile butadiene styrene (ABS)
293
additive materials 112
alkaline-acetylation treated sisal fiber
87, 88
alkaline treated fiber 88
alkali treated sisal fibers 89
aluminum hydroxide nanoparticles
(AH NPs) 210
2-amino-4,6-didodecylamino-1,3,
5-triazine (ADDT) 220
aminopropyltriethoxysilane (APS) 301
ammonium poly phosphate (APP) 178
Ananas comosus leaves 110
animal fibers 31, 32, 127
ash 7, 55, 58, 60, 63, 115

b

bacterial cellulose (BC) 206
bamboo and flax (BFBF) mat reinforced
epoxy hybrid composite 71
bamboo fiber 10, 19, 24, 44, 224,
255–267, 300
bamboo fiber based hybrid composites
flexural and tensile properties 264
Fourier transform infrared spectroscopy
259
FTIR spectra 260

impact strength and hardness
266–267
materials 257
micro-fibers 258
morphological characteristics 260
SWCNTs
amino-functionalization 258
fabrication 258–259
mechanical properties 259
tensile fracture 265–266
thermal conductivity 262–264
thermal degradation properties
260–262
thermal properties 259
bamboo nanocellulose fiber (BNF) 274,
275
banana based composite 162
banana/coir (BC) 89
banana fiber 35, 153, 300
hybridization of 154
physical and mechanical properties
154
banana fiber-based hybrid composites
applications 162
hand lay up 154–155
limiting oxygen index 155–156
thermal conductivity 160
thermal diffusivity 160–162
thermal stability 155
thermogravimetric analysis 156–158

- banana fiber-based hybrid composites (*contd.*)
 - vacuum bag assisted resin infusion technique 155
- banana fiber reinforced PP 38
- banana/flax based glass fiber hybrid composite 158
- banana leaf fiber hybrid composites 159–160
- barium titanate (BTO) 207
- basalt fabric 184
- bio-composite materials 139
- biocomposites 2, 3, 41, 135, 141, 145, 168
- biodegradable biopolymers 31
- bio-poly(trimethylene terephthalate) (Bio-PTT) based hybrid composites 36
- biosynthesized alumina nanopowder (BSANP) 89
- C**
- cane/grass fiber hybrid composites 138
 - properties of 140
 - thermal properties 140–144
- carbon fibers 54, 70, 94, 109, 110, 170, 219
- carbon fibers-based hybrid composite 54
- carbon nanotube (CNT) 116, 191, 220, 240, 256, 257
- Carpinus betulus* fiber 38
- Carpinus betulus* fiber filled PP matrix 41
- cassava bagasse reinforced cassava starch (CS) composite 66
- Catharanthus roseus* 17
- Ceiba pentandra fiber 37
- cellulose 60
- cellulose fiber 153, 246, 255, 256
- cellulose graphene plastics (CGPs) 210
- cellulose microfibers (CMF) 187
- cellulose nanocrystals (CNC) 42, 187, 202
- cellulose nanofiber composite (CNFG) 210
- cellulose nanofibers (CNF) 42, 202–203, 242
 - based composites 205–208
 - current status composites 209–212
 - functionalization of 201
 - nanocellulose 202
 - overview 202
 - preparation 203
 - surface functionalisation 203–205
 - thermal properties 208–209
- cellulosic fibers 32, 184
- cetyl trimethyl ammonium bromide (CTAB) 221, 231
- C glass 109
- char residue (CR) 35, 38, 61, 63, 242, 245
- chemical coupling agents
 - maleic anhydride 299–300
 - silanization 300–301
- chicken feather fiber (CFF) 37
- clay nanoparticles 38
- clay particles 72
- CNF based composites 205–207, 214
- CNF-PEG hybrid composite 207
- coefficient of linear thermal expansion (CLTE) 192
- coefficient of thermal expansion (CTE) 21, 176, 177, 197
- coir based composite 162
- coir fibers 231
- cold crystallisation temperature 39
- compression moulding method 139
- cone calorimeter 277, 279
- crystallinity 39
- crystallization temperature 39
- cuprous oxide (Cu_2O) particles 39
- curaua fibers (CF) 230, 232
- d**
- delaminated flax fiber reinforced composites 310
- derivative thermogravimetry (DTG) 55, 58, 157
- differential scanning calorimetry (DSC) 3, 20–21, 96, 142, 143, 221, 227
- epoxy/pineapple fiber (PALF) 124–126
- hemp fiber based hybrid composites 189–190

- kenaf fiber based hybrid composites 175–176
 - natural fiber reinforced hybrid polymer composites 38–41
 - natural fiber based hybrid composites 275
 - differential thermal analysis (DTA) 34, 169, 230, 317
 - differential thermogravimetric (DTG) 36, 95
 - diglycidyl ether of bisphenol-A (DGEBA) 221
 - dilatometric analysis (DLA) 95
 - dimensional change of material 5
 - dynamical mechanical analysis (DMA) 3, 10, 97
 - dynamic mechanical analysis(DMA)
 - epoxy/pineapple fiber (PALF) 120
 - dynamic mechanical analysis (DMA) 3, 23–24, 310
 - hemp fiber based hybrid composites 193–197
 - kenaf fiber based hybrid composites 172–174
 - natural fiber reinforced hybrid polymer composites 41–45
 - sugar palm fiber based hybrid polymer composites 63–66
 - dynamic mechanical analyzer (DMA) 23–24, 41–45, 57, 86
 - dynamic scanning calorimetry (DSC) 6, 10, 39, 246
- e**
- ecologically friendly polymeric composite 53
 - E glass 109, 193
 - empty fruit bunch (EFB) 297
 - enthalpy of crystallisation 39
 - enthalpy of melting 20, 39
 - epoxidized natural rubber (ENR) 115
 - epoxies
 - modification by filling nano-sized particulate fillers 116
 - modification by hybridization 116
 - modification by micron-sized particulate fillers 115
 - modification by reinforcing fibers 115
 - modification with other polymers or additives 114–115
 - epoxy-based natural fiber composites 36
 - epoxy composites 227
 - epoxy/Graphene nanocomposite 222
 - epoxy hybrid composites 35
 - epoxy laminates 274, 279–282, 284–286
 - epoxy/pineapple fiber (PALF)
 - differential scanning calorimetric analysis 124–126
 - dynamic mechanical analysis 120–124
 - thermal conductivity of composites 126–127
 - thermogravimetric analysis 116–120
 - epoxy resins 94, 112, 294
- f**
- fiberglass 93, 197
 - fiber-reinforced composites 20, 38, 43, 45, 89, 137, 239
 - fiber-reinforced polymer (FRP) composites 107, 309
 - flexural test 312
 - mechanical properties 313–315
 - tensile test 312
 - test of water absorption 312
 - thermal properties 316–317
 - water absorption studies 315
 - fibers 109–111
 - classification 136
 - type 1
 - fiber strengthened polymeric composites 107, 110
 - fiber strengthened polymer matrix composite (FRPC) 108
 - field emission scanning electron microscopy (FESEM) 178, 276
 - fillers 112
 - fire propagation index (FPI) 210
 - flame-retardant cellulose nanofiber-based aerogel 211
 - flammability tests 142–143, 177–178
 - flax/carbon fiber based hybrid epoxy composites 35
 - flax cultivar 97

flax fiber hybrid composites
 general properties and composition 97–98
 thermal analysis of 98–99
 flax/jute reinforced PLA hybrid composites 41
 flexible solar cells (FSC) 208
 Fourier transform infrared (FTIR) spectroscopy 276
 bamboo fiber based hybrid composites 259
 effect on 276–277
 spectra 260

g

glass and banana fiber hybrid composites 157–158
 glass/banana epoxy composites 35
 glass/carbon fiber/polymer composite 310
 glass fiber reinforced polymer composite (GFRPC) 110
 glass-fiber-reinforced polymers (GFRP) 155, 293
 glass fibers 45, 109
 glass/flax/banana epoxy composites 35
 glass/flax epoxy composites 35
 glass-reinforced polymers (GRPs) 309
 glass transition temperature (T_g) 5, 18, 39, 247, 293
 (3-glycidyloxypropyl) trimethoxysilane 222
 graphene 220
 graphene foam (GF) 221
 graphene nano platelets (GNP) 22, 116, 178, 221, 222, 227–229, 310
 graphene oxide (GO) 220, 222
 graphene oxide coated fibers (GOCF) 230, 232
 grass/cane fiber
 applications of 144–145
 differential scanning calorimetry analysis 142
 flammability test 142–143
 heat deflection temperature test 143

hybrid composite materials 137–138
 specific heat capacity measurement 143
 thermal conductivity 141–142
 thermal diffusivity 143–144
 thermogravimetric analysis 142
 green-based products 54
 GRP-mediated nanocomposites 309

h

Halloysite nanotube (HNT) 245
 hand lay-up method, banana fiber 154
 hardness 314
 heat deflection temperature (HDT) 143, 178
 heat of banana fiber hybrid composites 159
 heat transfer 108, 109, 113, 124, 153
 hemicelluloses 59, 60, 292
 hemp fiber based hybrid composites 183
 dynamic mechanical analysis 193–197
 linear coefficient of thermal expansion 192–193
 thermal conductivity 190–192
 thermogravimetric analysis 185–186
 hemp-Lyocell fiber 196
 hexabromocyclododecane 244
 high-density polyethylene (HDPE) 21, 41, 72, 154, 310
 high impact polystyrene (HIPS) 120, 293
 human-made composites 107
 hybrid composites 1, 17, 19, 24
 grass/cane fiber 137
 hemp fiber 186
 kenaf fiber based hybrid composites 168–169
 materials 138
 natural fiber 4
 thermal characterization 3
 DMA 3–5
 DSC 6
 TGA 6–10
 TMA 5–6
 thermal conductivity 141
 types of 2

- hybridization 137, 154
 hybrid natural fiber
 differential scanning calorimetry
 20–21
 dynamic mechanical analysis 23–24
 melt flow index 24–25
 thermal properties 18
 thermogravimetric analysis 18–20
 thermomechanical analysis 21–22
 hybrid polymer composites (HPC) 153
 hybrid sisal fiber/synthetic fiber
 reinforced polymeric composites
 88
 hybrid sisal/hemp bioepoxy composite
 38
 hybrid sugar palm/glass fiber/unsaturated
 polyester composites 62
 hybrid thermoplastic composites
 298–299
 hybrid thermoset composites 295–298
 hybrid TPU composites 35
 hydrogenated acrylonitrile-butadiene
 rubber (H-NBR) 207
 hydroxyperoxides 98
 hypothesis of thermal conductivity 108
- i**
- initial decomposition temperature (IDT)
 227
 injection moulding 139
 interlaminar shear strength (ILSS) 247,
 310
- j**
- jute and banana fiber hybrid composites
 156
 jute based composite 162
- k**
- kenaf fibers 24, 168–170, 174, 176–178,
 242
 kenaf fiber based hybrid composites
 168–169
 differential scanning calorimetry
 175–176
 dynamic mechanical analysis 172–174
 epoxy hybrid composites 172
 flammability tests 177–178
 heat deflection temperature 178
 hybrid composites 168–169
 PVC/TPU 170
 thermogravimetric analysis 169–172
 thermo-mechanical analysis 176–177
 kenaf woven mat 42
 Kevlar/Coconut sheath/epoxy (KCSE)
 composites 116
 Kevlar/epoxy (S1G0) polymeric structure
 310
 Kevlar fibers 112, 310, 311, 317
- l**
- lignin 60
 lignin nanoparticle (LNP) 36
 lignocellulosic fibers 86, 96, 184, 291
 ligno-cellulosic materials 95
 Li-ion batteries (LIBs) 207
 limiting oxygen index (LOI) 96,
 154–156, 210, 245
 linear coefficient of thermal expansion
 (CTE) 192–193
 linear low-density polyethylene (LLDPE)
 222
 loss modulus (E'') 4, 18, 56
 low-density polyethylene (LDPE) 126,
 302, 310, 311
 carbon fiber composite 314
 glass composite 310
 Kevlar fiber composite 314
 resin polymer composites 314
 lumen 94, 95, 97
- m**
- magnesium hydroxide (MgOH) 171,
 172, 178
 maleated polypropylene 43
 maleic anhydride 299–300
 maleic anhydride grafted polypropylene
 (MAPP) 38, 89, 154, 227, 230
 maleic-anhydride modified HDPE 41

- maleic anhydride polypropylene (MAPP) 22
 - maximal decomposition temperature (MLT) 227
 - melt flow index (MFI) 24–25
 - melt flow properties 18
 - melting temperature 39
 - methylolated indulin 88
 - microfibril formation 59
 - micron-sized particulate fillers 115
 - modified Kevlar/glass fiber 116
 - montmorillonite (MMT) 212, 240, 247
 - multi-walled carbon nanotubes (MWCNTs)-epoxy suspensions 310
- n**
- nanocellulose 201–205, 207–209
 - nanoclay 124
 - dynamic scanning calorimetry 246–247
 - glass transition temperature 247–248
 - inflammability of 244–245
 - properties 241
 - thermal stability 240–244
 - nanoelectromechanical systems (NEMS) 220
 - nano-sized particulate fillers 116
 - Napier grass fiber composites 140
 - natural bacterial cellulose (BC) 206
 - natural fiber composites (NFC) 93
 - synthetic fibers 239
 - techniques for thermal analysis 95–97
 - natural fiber-reinforced hybrid composites (NFRHC) 293
 - biodegradable thermoplastics 293
 - chemical coupling agents
 - maleic anhydride 299–300
 - silanization 300–301
 - chemical treatments
 - hybrid thermoplastic composites 298–299
 - hybrid thermoset composites 295–298
 - drawbacks 294
 - thermoplastic materials 293
 - two-step treatments 301–302
 - natural fiber reinforced hybrid polymer composites
 - differential scanning calorimetry (DSC) 38–41
 - disadvantages 32
 - dynamic mechanical analysis (DMA) 41–45
 - self-hybridization 32
 - thermogravimetric analysis 33–38
 - natural fiber-reinforced polymer composites (NFRPCs) 110
 - natural fibers 2, 6, 31, 89, 135, 291
 - polymer composite 241
 - reinforcement composites 54
 - natural fiber based hybrid composites
 - bamboo nanocellulose fiber 275
 - compression properties 283–285
 - fabrication 275
 - flame retardant properties 275
 - flammability 277–280
 - flexural properties 282–283
 - Fourier transform infra-red 276–277
 - graphene 220
 - impact strength 285
 - materials 274–275
 - mechanical properties 275–276
 - morphological properties 276
 - nanoclay
 - dynamic scanning calorimetry 246–247
 - glass transition temperature 247–248
 - inflammability of 244–245
 - nanoclay, thermal stability 240
 - polymer/graphene composites 220–223
 - polymer/natural fiber composites 223–225
 - polymer/natural fiber/graphene composites 226–232
 - tensile fracture 282
 - tensile properties 280–282
 - thermal properties 275

- natural fiber composites (NFCs) 167–168
- natural fiber reinforced polymer composites (NFRPCs) 183
- natural fibers based composite 135
- N*-methylol dimethylphosphonopropionamide (MDPA) 210
- N,N*-di-methyl formamide (DMF) 221
- non-woven hemp mat 184
- o**
- oil palm empty fruit bunch (OPEFB) fibers 224
- oil palm fibers 72
- organoclay montmorillonite (OMMT) 240
- organosolv lignins 88
- oxidation onset temperature (OOT) 176
- p**
- PALF/GF/polyester hybrid composites 126
- PALF hybrid composites 157
- PALF/kenaf fiber composites 176
- PALF reinforced epoxy composites 115
- palmyra palm leaf stalk (PPLSF) 296
- PAN-based carbon fibers 110
- Parthenium Hysterophorus* 17
- peak heat release rate (PHRR) 210
- phenolic formaldehyde (PF) 22
- piassava fiber (PF) 226
- pineapple leaf fibers (PALF) 22, 45, 110, 159, 300
- pinneapple plant 110
- plant fibers 32
- PLA-TAF 242
- poly(3-hydroxybutyrate-co-3-hydroxyvalerate) (PHBV) 32
- poly(butylsuccinate) (PBS) 100
- poly(ϵ -caprolactone) (PCL) 293
- poly(glycolic acid) (PGA) 293
- poly(hydroxybutyrate) (PHB) 100
- poly(lactic acid) (PLA) 39, 99, 101
- polyacrylonitrile (PAN) 109
- polybutylene succinate (PBS) composites 22
- polycaprolactone (PCL) 32, 301
- polycarbonate (PC) 119, 293
- poly(3-hydroxybutyrate-co-4-hydroxybutyrate) (P34HB) composites reinforced wood fiber 42
- polyether ether ketone (PEEK) 70
- polyethylene (PE) 293
- polyethylene glycol (PEG) 207
- polyhydroxy butyrate-co-valerate (PHBV) 20
- polylactic acid (PLA) 32
- polylactic acid polymer 126
- polymer-based composites 3, 6, 8
- polymer based nanocomposites 116, 255
- polymer-based nanolaminates 273
- polymer-based products 53
- polymer composites 153
- polymer/graphene composites 220–223
- polymeric composite materials 107
- polymerizable deep eutectic solvents (PDES) 206
- polymer/natural fiber composites 223–225
- polymer/natural fiber/graphene composites 226–232
- polymers
- additive materials 112
 - fibers 109–111
 - fillers 112
 - hypothesis of thermal conductivity 108–109
 - resins 111–112
 - thermal conductivity of composites 113
- polypropylene (PP) 38, 99, 101, 221, 226, 293
- polypropylene/PALF/nanoclay composites 120
- poly(hydroxybutyrate-co-valerate) resin 116

- polystyrene-block-poly(ethylene-ranbutylene)-block-poly(styrene-graft-maleic anhydride) 120
 poly-(styrene-co-maleic anhydride) 120
 polyurethane (PU) 191, 294
 pure LDPE-epoxy laminated composite 313
- R**
- raw jute 35
 recycled polypropylene (RPP) composites 40
 reduced graphene oxide (RGO) 221
 reinforced sugar palm fiber polymer composite 61
 reinforced sugar palm fiber with different polymer composites 57
 residue 9, 10
 resins 111, 139
 resin transfer moulding (RTM) 139
 rice husk biochar composites 310
 roselle fiber/sugar palm fiber composites 63
 roselle (RF)/sugar palm fiber (SPF) reinforced thermoplastic polyurethane (TPU) composites 33
- S**
- Saccharum Bengalense* 17
 sago fiber-epoxy composites 115
 Sansevieria fibers 141
 scanning electron microscope (SEM) 257
 seaweed/sugar palm fiber composites 62
 self-hybridization 32
 S3G3 310
 S4G3 310
 S glass 109
 Shimadzu DTG-60H 55
 silane treated sisal fibers 88
 silanization 300–301
 single-walled carbon nanotubes (SWCNT) 257
 amino-functionalization 258
 fabrication 258–259
 mechanical properties 259
 sisal (S) and kenaf (K) woven fabrics-based hybrid bioepoxy composites 37
 sisal/banana (SB) 89
 sisal/coir (SC) 89
 sisal fiber (SF) 230
 sisal fiber based hybrid composites 85–86
 sisal fiber/organoclay reinforced PP composites 38
 sisal fiber (mercerization and silane) reinforced epoxy composites 88
 sisal fiber reinforced PLA composites 36
 sisal fiber reinforced polymeric composites, thermal properties of 87
 sisal/glass fiber reinforced epoxy composites 35
 sisal/glyoxal-phenolic composite 88
 sisal/jute based hybrid composites 90
 sisal/nanoclay based composites 90
 sisal/other natural fiber reinforced polymeric composites 89
 sisal/propylene composites 90
 sisal woven mat 42
 smoke production rate (SPR) 245
 SPF reinforced composites 55
 storage modulus (E') 18, 86
 sugar palm/cassava bagasse 66
 sugar palm fiber (SPF) 20, 54
 glass fiber (GF)-based TPU composites 34
 hybrids 61
 natural woven structure 56
 sugar palm fiber based hybrid polymer composites
 dynamic mechanical analysis (DMA) 63–66
 potential applications 66–72
 thermogravimetric analysis (TGA) 58–60
 sugar palm/flax fibers 66
 sugar palm/glass fiber 63–66

- sugar palm short fibers 56
 sugar palm tree 56
 surface-modified grass fibers 142
 SWCNT/BF 262
 synthetic fibers 89, 239
 synthetic/natural hybrid composites 310
- t**
- TEMPO-oxidized cellulose nanofiber (TOCN) 207
 2,2,6,6-tetramethylpiperidine 1-oxyl (TEMPO), 204
 thermal characterization 3
 DMA 3–5
 DSC 6
 TGA 6–10
 TMA 5–6
 thermal conductivity 113, 141–142
 banana fiber-based hybrid composites 160
 of composites 113, 126–127
 hemp fiber based hybrid composites 190–192
 pineapple leaf and banana fiber hybrid composites 160
 testing 107
 thermal diffusivity 143–144, 160–162
 thermal expansion coefficients (TEC) 208
 thermal gravimetric analyzer (TGA) 11, 221, 262, 280
 thermal property 18
 thermal stability 8, 10, 141, 145, 155, 240–244
 thermoanalytical technique 246
 thermogravimetric analysis
 bamboo fiber based hybrid composites 259
 nanoclay 240
 thermogravimetric analysis (TGA) 3, 95, 142, 154, 230
 banana-flax based glass fiber hybrid composite 158
 epoxy/pineapple fiber (PALF) 116–120
 glass and banana fiber hybrid composites 157–158
 heat of, pineapple leaf 159–160
 hemp fiber based hybrid composites 185–186
 jute and banana fiber hybrid composites 156
 kenaf fiber based hybrid composites 169–172
 natural fiber reinforced hybrid polymer composites 33–38
 sisal fiber based hybrid composites 85–86
 sugar palm fiber based hybrid polymer composites 58–63
 thermo-mechanical analysis (TMA) 3, 5, 10, 21–22, 176–177
 thermoplastic materials 111
 thermoplastic polymers 18
 thermoplastic polysulfone (PSF) 114
 thermoplastic polyurethanes (TPU) 64
 thermoplastic starch composites 42
 thermoplastic sugar palm starch agar (TPSA) 62
 thermoset polymers 294
 thermoset resins 112
 time to ignition (TTI) 210
 time to peak heat release rate (TPHRR) 245
 total time to ignite (TTI) 245
 treated bamboo fibers (TBF) 224, 225
 treated kenaf + epoxy single fiber composite 43
 treated kenaf + glass + clay-based epoxy hybrid composites 43
Tridax procumbens 17
 Typha angustifolia grass fiber 141
- u**
- unsaturated polyester (UP) 45, 60, 112, 248
 untreated bamboo fibers (UBF) 224, 225

untreated kenaf + epoxy single fiber composite 43
untreated kenaf + glass + clay-based epoxy hybrid composites 43

V

vacuum bag assisted resin infusion technique 155
vapor grown carbon fiber (VGN) 36
vinyl ester 112
viscoelastic characteristics, polymeric composites 86

W

water glass (WG) coated sisal fibers 90
wood floor reinforced PLA composites 39

X

X-ray diffraction (XRD) 227

Y

Young's modulus 4, 22, 212

Z

zeolitic imidazolate framework-67 (ZIF-67) 207

